

Sky-Guard BG-360R Remote ID Monitoring Node

Receive-only Remote ID reception for cooperative airspace awareness



Overview

A fixed-mounted, receive-only Remote ID monitoring node. Each node listens to Remote ID broadcasts from compliant drones — serial number, type, position, speed, altitude, and pilot location — building a live cooperative traffic picture for sites, corridors, and city-scale networks. Aircraft without Remote ID stand out for spectrum-sensor confirmation.

Key Capabilities

- Receive-only operation with zero RF emissions — licence-friendly for dense urban and corridor deployments.
- Decodes Remote ID broadcasts: serial number, type, position, speed, altitude, and pilot location.
- ≤ 25 W power draw — solar-viable for standalone node deployments.
- Dual-band Remote ID receiver in a sealed sensor dome with 360° horizontal, 90° vertical coverage.

Technical Specifications

Model	BG-360R
Detection Mode	Remote ID broadcast reception (receive-only)
Coverage	0–1 km urban / 1–3 km open, per node
Concurrent Targets	50+ aircraft
Refresh Rate	1–3 s position updates
Field of View	360° horizontal; 90° vertical
Power Draw	≤ 25 W — solar-viable
RF Emissions	None (receive-only)

Hong Kong-Shenzhen Innovation and Technology Park, Hong Kong
Email: info@metabee.com.hk | Web: www.metabee.com.hk
Date Code: September 2026

The information contained in this document is provided for reference purposes only. Specifications are subject to change without prior notice.
Actual performance may vary depending on operating environment, deployment configuration, and integration conditions.