

# 14. Decorators

September 19, 2025

## 1 Decorators

Decorators modify or introduce code in methods and functions dynamically. A decorator is basically a function that receives another function as parameter, adds/modifies its functionality and returns it.

### 1.1 Functions roles and uses

In order to understand decorators, we must first remember a few things about functions.

Various names can be bound to the same function object:

```
[16]: def greet(name):  
        print(f'Hello, {name}!')  
  
greet('John')  
  
salute = greet  
salute('John')  
  
print(id(salute) == id(greet))  
print(salute is greet)
```

Hello, John!

Hello, John!

True

True

Functions can be passed as arguments to another function:

```
[17]: def add(a, b):  
        return a + b  
  
def diff(a, b):  
    return a - b  
  
def compute(a, b, operation):  
    return operation(a, b)
```

```
print(compute(10, 2, add))
print(compute(10, 2, diff))
print(compute(10, 2, pow))
print(compute(10, 2, lambda x, y: x / y))
```

```
12
8
100
5.0
```

Functions can be defined inside other functions:

```
[18]: def func():
      def inner_func():
          print('Inside!')
      inner_func()

      func()
```

```
Inside!
```

A function can return another function:

```
[19]: def func():
      def inner_func():
          print('Inside!')
      return inner_func

      func_returned = func()
      print(func_returned)
      print(type(func_returned))
```

```
<function func.<locals>.inner_func at 0x1052ee200>
<class 'function'>
```

```
[20]: func_returned()
```

```
Inside!
```

## 1.2 Simple decorators

Functions and methods are called **callable** as they can be called.

In fact, any object which implements the special method `__call__()` is a callable. So, in the most basic sense, a decorator is a callable that returns a callable.

Basically, a decorator takes in a function, adds some functionality and returns it.

```
[21]: def make_pretty(func):
      def inner():
          print("I got decorated")
          func()
      return inner
```

```

    return inner

def ordinary():
    print("I am ordinary")

pretty = make_pretty(ordinary)
pretty()

```

I got decorated  
I am ordinary

In the example shown above, `make_pretty()` is a decorator. In the assignment step:

```
pretty = make_pretty(ordinary)
```

The function `ordinary()` got decorated and the returned function was given the name `pretty`.

Generally, we decorate a function and reassign it to its initial name:

```
ordinary = make_pretty(ordinary)
```

This is a common construct and for this reason, Python has a syntax to simplify this.

We can use the `@` symbol along with the name of the decorator function and place it above the definition of the function to decorated it.

```
[22]: @make_pretty
def ordinary():
    print("I am ordinary")

```

The example above is equivalent to:

```
def ordinary():
    print("I am ordinary")

ordinary = make_pretty(ordinary)
```

The `@decorator` notation is just syntactic sugar.

Generally, decorators should be able to decorate any function. Let's see what happens when we try to decorate a function that receives an argument:

```
[23]: @make_pretty
def greet(name):
    print(f'Hello, {name}!')

try:
    greet('Anna')
except Exception as ex:
    print(f'{type(ex).__name__}: {ex}')

```

`TypeError: make_pretty.<locals>.inner() takes 0 positional arguments but 1 was given`

It looks like our decorator isn't general enough. Because `make_pretty()` returns `inner` function, we should change `inner` to accept any number of parameters and pass them along to the `func()` call inside `inner()`.

```
[24]: def make_pretty(func):
      def inner(*args, **kwargs):
          print("I got decorated")
          func(*args, **kwargs)
      return inner
```

Let's try decorating `greet` again:

```
[25]: @make_pretty
      def greet(name):
          print(f'Hello, {name}!')

      greet('Anna')
```

```
I got decorated
Hello, Anna!
```

There is still one detail we have left out. Let's try decorating a function that returns some value:

```
[26]: @make_pretty
      def increment(num, step=1):
          return num + step

      result = increment(100)
      print('Incremented value:', result)
```

```
I got decorated
Incremented value: None
```

The incremented value should be 101, but instead, it's `None`. Let's take another look at the `inner` function: it simply calls `func`, but ignores the value returned by it.

```
[27]: def make_pretty(func):
      def inner(*args, **kwargs):
          print("I got decorated")
          return func(*args, **kwargs)
      return inner

      @make_pretty
      def increment(num, step=1):
          """Increments num with step. If not provided, step=1"""
          return num + step

      result = increment(100, 2)
```

```
print('Incremented value:', result)
```

```
I got decorated  
Incremented value: 102
```

This time, our decorator seems to work properly. Let's check one last detail:

```
[28]: print(increment, increment.__doc__)
```

```
<function make_pretty.<locals>.inner at 0x1052edc60> None
```

When inspecting `increment` function, we can see it points to the `make_pretty.<locals>.inner` function object and it has lost its properties, like the docstring. In order to prevent this from happening, we can use `functools.wraps` decorator:

```
[29]: import functools  
  
def make_pretty(func):  
    @functools.wraps(func)  
    def inner(*args, **kwargs):  
        print("I got decorated")  
        return func(*args, **kwargs)  
    return inner  
  
@make_pretty  
def increment(num, step=1):  
    """Increments num with step. If not provided, step=1"""  
    return num + step  
  
result = increment(100, 2)  
print('Incremented value:', result)
```

```
I got decorated  
Incremented value: 102
```

```
[30]: print(increment, increment.__doc__)
```

```
<function increment at 0x1052ed6c0> Increments num with step. If not provided,  
step=1
```

### 1.3 Exercises

1. Write a decorator that computes (and displays) execution time for a function. Hint: `time.time()` function returns current time in seconds.
2. Write a decorator function that takes a function as an argument and prints the number of times the function has been called.