SOLUNA™

POWER DESIGNED FOR NIGHT AND DAY

SOLUNA™

POWER DESIGNED FOR NIGHT AND DAY



SOLUNA™ | www.soluna.co Email: sales@solunabattery.com Tel.: +86-21-57475835

SOLUNA™ | www.soluna.co Email: sales@solunabattery.com Tel.: +86-21-57475835

SOLUNA™
POWER DESIGNED FOR NIGHT AND DAY

Soluna 10K PACK LV is a battery solution ideal for residential and small commercial energy storage applications.

The model is adopted by the latest **LiFePO4** technology with an intelligent BMS integrated in the fault protection for energy security, offering a capacity of 10kwh which can be installed in parallel up to 12 batteries allowing 120kwh of total storage.

With a **10-year** warranty and 6000 cycle life, the Soluna 10K pack LV is a flexible, reliable and high performance battery storage solution.

Low Voltage

Scalable to 120kWh

Safest LiFePO4 battery

Long lifespan

Easy Installation

Floor,Wall mounting



SOLUNA™
POWER DESIGNED FOR NIGHT AND DAY

TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Height (mm)	760
Width (mm)	500
Depth (mm)	215
Weight (kg)	100
Installation	Indoor / Outdoor

ELECTRICAL CHARACTERISTICS

Battery type	Lithium LFP
Nominal capacity (Ah)	200
Nominal voltage (V)	51.2
Voltage range (usable) (V)	48 to 57.6
Max. charge/ discharge current(A)	100 / 200
Depth of discharge (DoD) (%)	90
Internal resistance (mΩ)	≤60
Cycle life	≥6000
Battery pack round-trip efficiency (%)	>95
DC disconnect	Contactor / fuse

BMS

Power consumption	<3W (work) <100 mW (sleep)
Monitoring parameters	System voltage System current Cell voltage Cell temperature
Communication	CAN

OPERATING CONDITIONS

Operating temperature (℃)	-10 to 50
Operating temperature(recommended) (℃)	15 to 30
Storage temperature (recommended)(℃)	15 to 30
Humidity conditions(%)	5 to 95
Altitude(m)	Max. 2,000
Cooling strategy	Natural convection

RELIABILITY AND CERTIFICATION

Certification	Cell: UL1642 Module: UN38.3 . UL1973. UL9540A IEC62619 . CE RoHS
Transportation	UN38.3
Ingress protection rating	IP 55
System configuration	1 to 12 parallel

WARRANTY

Product and performance	10-year standard warranty

SOLUNA | www.soluna.co Email: sales@solunabattery.com Tel.: +86-21-57475835

SOLUNA™
POWER DESIGNED FOR NIGHT AND DAY

TECHNICAL SPECIFICATIONS
WIFI STICK

WiFi Stick is an internal data logger in the Soluna battery monitoring series.

By connecting with the battery through CAN 1 interface and checking working status from the 3 LEDs on the WiFi Stick, it can collect information from battery and transmit data to the web server, realizing remote monitoring for users including Fault Alarm, Firmware update and parameter setting through web portal and a direct connection configuration with Soluna E-Cloud APP for user as well.





PHYSICAL CHARACTERISTICS

Model Name	WiFi Stick RSW-1
Dimension (H*W*D)	122*49*30 mm
Weight (kg)	0.1
Installation	Insert+Screw

ELECTRICAL

Input Voltage	DC 5V
Power consumption	1.5W

COMMUNICATION CONNECTING PORT

Supported device type	Soluna LV 9.6/10.24K Pack
Data collection intervals	5 minutes
Indicator	LED *3
Communication Interface	USB
Wireless communication	2.4GHz~2.48GHz/ 802.11b/g/n
Configuration	APP

ENVIRONMENT

Operating temperature	-30℃~+70℃
Storage temperature	-40℃~+90℃
Operating humidity	10%-90%
Storage humidity	<50%
Warranty	2 Years



©Soluna Shanghai Co., Ltd., All rights reserved.
* All specifications are subject to change without notice.

SOLUNA™ | Www.soluna.co Email: sales@solunabattery.com Tel.: +86-21-57475835