



UNIVERSIDAD
POLITÉCNICA
DE MADRID



UNIVERSIDAD POLITÉCNICA DE MADRID
ESCUELA TÉCNICA SUPERIOR DE INGENIERÍA Y DISEÑO
INDUSTRIAL

Grado en Ingeniería Eléctrica

TRABAJO DE FIN DE GRADO

Desarrollo de una herramienta software para la simulación de sistemas fotovoltaicos con R

Autor: Francisco Delgado López

Tutor: Oscar Perpiñán Lamigueiro

Departamento de Ingeniería Eléctrica,
Electrónica, Automática y Física aplicada

Madrid, 5 de septiembre de 2024

Agradecimientos

Agradezco a ...

Resumen

El presente proyecto se enfoca en el desarrollo de un paquete de software estadístico en R, denominado `solaR2`, diseñado para estimar la productividad de sistemas fotovoltaicos a partir de datos de irradiación solar. `solaR2` es una evolución del paquete `solaR`, con mejoras significativas en modularidad y eficiencia. A diferencia de `solaR`, que utilizaba el paquete `zoo` para la gestión de series temporales, `solaR2` se basa en `data.table`, lo que optimiza la manipulación de grandes volúmenes de datos y acelera el procesamiento. Este avance es crucial para un análisis más detallado y eficiente en el campo de la energía solar fotovoltaica.

`solaR2` ofrece herramientas avanzadas para simular el rendimiento de sistemas conectados a la red y sistemas de bombeo de agua con energía solar. Incluye clases, métodos y funciones que permiten calcular la geometría solar y la radiación solar incidente, así como estimar la productividad final de estos sistemas a partir de la irradiación global horizontal diaria e intradía.

El diseño modular basado en clases `S4` facilita el manejo de series temporales multivariantes y proporciona métodos de visualización avanzados para el análisis de rendimiento en plantas fotovoltaicas a gran escala. La implementación con `data.table` mejora la eficiencia en la manipulación de datos, permitiendo análisis más rápidos y precisos. Entre sus funcionalidades destacadas están el cálculo de radiación solar en diferentes planos, la estimación de rendimiento de sistemas fotovoltaicos y de bombeo, y la evaluación de sombras.

Además, `solaR2` ofrece herramientas avanzadas para la visualización estadística del rendimiento, compatible con otros paquetes de R para manipulación de series temporales y análisis espacial. Esto la convierte en una herramienta útil para investigadores y profesionales en el diseño y optimización de sistemas fotovoltaicos, permitiendo un análisis detallado bajo diversas condiciones. En resumen, `solaR2` representa una mejora significativa en el análisis y simulación de sistemas solares, proporcionando una herramienta flexible y reproducible para mejorar la eficiencia energética y la rentabilidad de las instalaciones solares.

Palabras clave: geometría solar, radiación solar, energía solar, fotovoltaica, métodos de visualización, series temporales, datos espacio-temporales, `S4`

Abstract

This project focuses on the development of a statistical software package in R, called `solaR2`, designed to estimate the productivity of photovoltaic systems based on solar irradiation data. `solaR2` represents an evolution of the existing `solaR` package, featuring significant improvements in modularity and efficiency. Unlike `solaR`, which relied on the `zoo` package for time series management, `solaR2` uses `data.table`, optimizing the handling of large data volumes and speeding up processing. This advancement is crucial for more detailed and efficient analysis in the field of photovoltaic solar energy.

`solaR2` provides advanced tools for simulating the performance of grid-connected systems and solar-powered water pumping systems. It includes classes, methods, and functions for calculating solar geometry and incident solar radiation, as well as estimating the final productivity of these systems from global horizontal irradiation on a daily and intraday basis.

The modular design based on S4 classes facilitates the management of multivariate time series and provides advanced visualization methods for performance analysis in large-scale photovoltaic plants. The use of `data.table` enhances data handling efficiency, allowing for faster and more precise analyses. Key functionalities include calculating solar radiation on different planes, estimating the performance of photovoltaic and pumping systems, and evaluating shading.

Additionally, `solaR2` offers advanced statistical visualization tools, compatible with other R packages for time series manipulation and spatial analysis. This makes it a valuable tool for researchers and professionals involved in the design and optimization of photovoltaic systems, enabling detailed analysis under various conditions. In summary, `solaR2` represents a significant improvement in the analysis and simulation of solar systems, providing a flexible and reproducible tool to enhance energy efficiency and the profitability of solar installations.

Keywords: solar geometry, solar radiation, solar energy, photovoltaic, visualization methods, time series, spatiotemporal data, S4

Índice general

Índice general	IX
Índice de figuras	XI
Nomenclatura	XIII
1 Introducción	1
1.1. Objetivos	1
1.2. Análisis previo de soluciones	3
1.3. Aspectos técnicos	3
2 Estado del arte	7
2.1. Situación actual de la generación fotovoltaica	7
2.2. Solución actual y sus carencias	8
3 Marco teórico	11
3.1. Naturaleza de la radiación solar	11
3.2. Radiación en superficies inclinadas	14
3.3. Cálculo de la energía producida por un generador fotovoltaico	18
3.4. Sombras y ocupación de terreno	26
4 Desarrollo del código	33
4.1. Geometría solar	33
4.2. Datos meteorológicos	39
4.3. Radiación en el plano horizontal	42
4.4. Radiación efectiva en el plano del generador	51
4.5. Producción eléctrica de un SFCR	61
4.6. Producción eléctrica de un SFB	65
4.7. Optimización de distancias	68
4.8. Métodos de visualización	72
5 Ejemplo práctico de aplicación	83
5.1. <code>solaR</code>	83
5.2. <code>PVsyst</code>	87
5.3. <code>solaR2</code>	87
5.4. Comparación y conclusiones	89
A Manual de referencia de <code>solaR2</code>	93
Bibliografía	181

Índice de figuras

3.1.	Procedimiento de cálculo	12
3.2.	Perfil de irradiancia difusa y global obtenido a partir del generador empírico de [CR79] para valores de irradiancia tomadas cada 10 minutos	15
3.3.	Ángulo de visión del cielo	16
3.4.	Pérdidas angulares de un módulo fotovoltaico para diferentes grados de suciedad en función del ángulo de incidencia.	17
3.5.	Curvas corriente-tensión(línea discontinua) y potencia-tensión(línea continua) de una célula solar ($T_a = 20^\circ C$ y $G = 800 W/m^2$)	19
3.6.	Evolución de la eficiencia de células según la tecnología (según el National Renewable Energy Laboratory [Nat24] (EEUU)).	20
3.7.	Dimensiones y distancias entre filas de un sistema estático.	27
3.8.	Sombras mutuas en un conjunto de cuatro seguidores.	28
3.9.	Dimensiones de un seguidor a doble eje y longitud de su sombra arrojada.	28
3.10.	Posibles sombras en un conjunto de seis seguidores.	28
3.11.	Ábaco para planta de seguimiento a doble eje. Recoge el ratio entre la energía anual producida por un seguidor afectado por sombras mutuas (E_{acS}) y la producida por un seguidor sin sombreado (E_{ac0}). Las curvas de color negro representan la fracción de energía no afectada por sombras. Las curvas de puntos representan el valor del ROT.	30
3.12.	Dimensiones básicas en sistemas con seguidores de eje horizontal.	30
4.1.	Proceso de cálculo de las funciones de solaR2	34
4.2.	Cálculo de la geometría solar mediante la función calcSol , la cual unifica las funciones fSolD y fSolI resultando en un objeto clase Sol el cual contiene toda la información geométrica necesaria para realizar las siguientes estimaciones.	34
4.3.	Los datos meteorologicas se pueden leer mediante las funciones readG0dm , readBD , dt2Meteo , zoo2Meteo y readSIAR las cuales procesan estos datos y los almacenan en un objeto de clase Meteo	39
4.4.	Cálculo de la radiación incidente en el plano horizontal mediante la función calcG0 , la cual procesa un objeto clase Sol y otro clase Meteo mediante las funciones fCompD y fCompI resultando en un objeto clase G0 . :	43
4.5.	Cálculo de la radiación efectiva incidente en el plano del generador mediante la función calcGef , la cual emplea la función fInclin para el computo de las componentes efectivas, la función fTheta que provee a la función anterior los ángulos necesarios para su computo y la función calcShd que reprocesa el objeto de clase Gef resultante, añadiendole el efecto de las sombras producidas entres módulos.	51
4.6.	Estimación de la producción eléctrica de un SFCR mediante la función prodGCPV , la cual emplea la función fProd para el computo de la potencia a la entrada (P_{DC}), a la salida (P_{AC}) y el rendimiento (η_{inv}) del inversor.	61
4.7.	Estimación de la producción eléctrica de un SFB mediante la función prodPVPS , la cual emplea la función fPump para el computo del rendimiento de las diferentes parte de una bomba centrífuga alimentada por un convertidor de frecuencia.	65

Nomenclatura

A_c	Área de una célula
A_G	Área de un generador fotovoltaico
α	Ángulo de orientación de un sistema fotovoltaico
AM	Masa de aire
AO	Adelanto oficial durante el horario de verano
$B_0(0)$	irradiancia extra-atmósferica o extra-terrestre en el plano horizontal
B_0	Constante solar o irradiancia solar incidente en un plano normal al vector solar en el límite superior de la atmósfera terrestre
B	Radiación directa
β	Ángulo de inclinación de un sistema fotovoltaico
D	Radiación difusa
D^C	Radiación difusa circunsolar
δ	Declinación
$\Delta\lambda$	Diferencia entre la longitud local y la longitud del huso horario
D^I	Radiación difusa isotrópica
d_n	Día del año
d_{min}	Distancia mínima entre hileras de un generador para evitar el sombreado
EoT	Ecuación del tiempo
ϵ_0	Corrección debida a la excentricidad de la elipse de la trayectoria terrestre alrededor del sol
η_{mp}	Eficiencia de una motobomba
F_D	Fracción de difusa
F_{Dd}	Fracción de difusa diaria
F_{Dm}	Fracción de difusa mensual
FT_B	Factor de pérdidas angulares para irradiancia directa
FT_R	Factor de pérdidas angulares para irradiancia de albedo

FT_D	Factor de pérdidas angulares para irradiancia difusa
g	Aceleración de la gravedad
G	Radiación global
GCR	Ground coverage ratio
G_{STC}	Irradiancia incidente en condiciones estandar de medida
H_{dt}	Nivel dinámico de un pozo
H_f	Altura asociada a las pérdidas de fricción en una tubería
H_{OT}	Diferencia de cotas entre la salida de agua y la entrada en el depósito
H_{st}	Nivel estático de un pozo
H_T	Altura total incluyendo las pérdidas de fricción de la tubería
H_{TE}	Altura total equivalente de un sistema de bombeo
H_v	Altura vertical aparente
I_{mpp}	Corriente de una célula en el punto de máxima potencia
I_{sc}	Corriente de cortocircuito de una célula
K_T	Índice de claridad
K_{Td}	Índice de claridad diario
K_{Tm}	Índice de claridad mensual
L_{eo}	Separación entre seguidores en sentido Este-Oeste
L_{ns}	Separación entre seguidores en sentido Norte-Sur
MPP	Punto de máxima potencia de un dispositivo fotovoltaico
ω	Hora solar o tiempo solar verdadero
ω_s	Ángulo del amanecer
P_{el}	Potencia eléctrica necesaria en la entrada de una motobomba
P_f	Pérdidas de fricción en la tubería de un sistema de bombeo
P_H	Potencia hidráulica necesaria en un sistema de bombeo de agua
P_H	Potencia hidráulica
ϕ	Latitud
P_{inv}	Potencia nominal de un inversor
Q	Caudal de agua
Q_{max}	caudal máximo del pozo
Q_t	Caudal de ensayo de un pozo

R	Radiación del albedo
r_D	Relación entre la irradiancia y la irradiación difusa en el plano horizontal
ρ	Densidad del agua
ρ	Coefficiente de reflexión del terreno para la irradiancia de albedo
ROT	Ratio de ocupación del terreno
STC	Condiciones estándar de medida de un dispositivo fotovoltaico
T_c^*	Temperatura de célula en condiciones estándar de medida
T_c	Temperatura de célula
θ_s	Ángulo de incidencia o ángulo entre el vector solar y el vector director de una superficie
θ_{zs}	Ángulo cenital solar
TO	Hora oficial
$TONC$	Temperatura de operación nominal de célula
V_{mpp}	Tensión de una célula en el punto de máxima potencia
V_{oc}	Tensión de circuito abierto de una célula

Introducción

1.1. Objetivos

El objetivo principal de este proyecto es el desarrollo de un paquete en R [R C23] con el cual poder realizar estimaciones y representaciones gráficas de la geometría solar, radiación solar en el plano horizontal y del generador, y el funcionamiento de sistemas fotovoltaicos de conexión a red y de bombeo de agua.

Durante el resto del documento, si fuera necesario, se hará referencia al paquete desarrollado en este proyecto con el nombre `solaR2` [CITAR SOLAR2].

El usuario puede colocar los datos que considere convenientes (desde una base de datos oficial, una base de datos propia... etc.) en cada una de las funciones que ofrece el paquete pudiendo así obtener resultados de la geometría solar, de la radiación horizontal, de la efectiva y hasta de la producción de diferentes tipos de sistemas fotovoltaicos.

El paquete también incluye una serie de funciones que permiten hacer representaciones gráficas de estos resultados con el fin de poder apreciar con más detalle las diferencias entre sistemas y contemplar cual es la mejor opción para el emplazamiento elegido.

Este proyecto toma su origen en el paquete ya existente `solaR` [Per12] el cual desarrolló el tutor de este proyecto en 2010. Esta versión, la 0.14, ha tenido una serie de actualizaciones, siendo la más reciente la 0.46 (en el 2021). Sin embargo, al ser versiones de un software antiguo se propuso la idea de renovarlo teniendo en cuenta el paquete en el que basa su funcionamiento. El paquete `solaR` basó su funcionamiento en el paquete `zoo` [ZG05] el cual proporciona una sólida base para trabajar con series temporales. Sin embargo, como base de `solaR2` se optó por el paquete `data.table` [Bar+24]. Este paquete ofrece una extensión de los clásicos `data.frame` de R en los `data.table`, los cuales pueden trabajar rápidamente con enormes cantidades de datos (por ejemplo, 100 GB de RAM).

La clave de ambos proyectos es que al estar basados en R, cualquier usuario puede acceder a ellos de forma gratuita, tan solo necesitas tener instalado R en tu dispositivo.

Para alojar este proyecto se toman dos vías:

- **Github** [Wan+23]: Donde se aloja la versión de desarrollo del paquete.

- **CRAN**: Acrónimo de Comprehensive R Archive Network, es el repositorio donde se alojan las versiones definitivas de los paquetes y desde el cual se descargan a la sesión de R.

El paquete **solar2** permite realizar las siguientes operaciones:

- Cálculo de toda la geometría que caracteriza a la radiación procedente del Sol (??).
- Tratamiento de datos meteorológicos (en especial de radiación), procedentes de datos ofrecidos del usuario y de la red de estaciones SIAR [Min23] (??).
- Una vez calculado lo anterior, se pueden hacer estimaciones de:
 - Los componentes de radiación horizontal (??).
 - Los componentes de radiación eficaz en el plano inclinado (??).
 - La producción de sistemas fotovoltaicos conectados a red (??) y sistemas fotovoltaicos de bombeo (??).

Este proyecto ha tenido a su vez una serie de objetivos secundarios:

- Uso y manejo de GNU Emacs [Sta85] en el que se realizaron todos los archivos que componen este documento (utilizando el modo Org [Dom+03]) y el paquete descrito (empleando ESS [Pro24])
- Dominio de diferentes paquetes de R:
 - **zoo** [ZG05]: Paquete que proporciona un conjunto de clases y métodos en S3 para trabajar con series temporales regulares e irregulares. Usado en el paquete **solar** como pilar central.
 - **data.table** [Bar+24]: Otorga una extensión a los datos de tipo `data.frame` que permite una alta eficiencia especialmente con conjuntos de datos muy grandes. Se ha utilizado en el paquete **solar2** en sustitución del paquete **zoo** como tipo de dato principal en el cual se construyen las clases y métodos de este paquete.
 - **microbenchmark** [Mer+23]: Proporciona infraestructura para medir y comparar con precisión el tiempo de ejecución de expresiones en R. Usado para comparar los tiempos de ejecución de ambos paquetes.
 - **profvis** [Wic+24]: Crea una interfaz gráfica donde explorar los datos de rendimiento de una expresión dada. Aplicada junto con **microbenchmark** para detectar y corregir cuellos de botella en el paquete **solar2**
 - **lattice** [Sar08]: Proporciona diversas funciones con las que representar datos. El paquete **solar2** utiliza este paquete para representar de forma visual los datos obtenidos en las estimaciones.
- Junto con el modo Org, se ha utilizado el preprocesador de textos L^AT_EX (partiendo de un archivo .org, se puede exportar a un archivo .tex para posteriormente exportar un pdf).
- Obtener conocimientos teóricos acerca de la radiación solar y de la producción de energía solar mediante sistemas fotovoltaicos y sus diversos tipos. Para ello se ha usado en mayor medida el libro “Energía Solar Fotovoltaica” [Per23].

1.2. Análisis previo de soluciones

Este proyecto, como ya se ha comentado, es el heredero del paquete **solaR** desarrollado por Oscar Perpiñán. La filosofía de ambos paquetes es la misma y los resultados que dan son muy similares. Sin embargo, lo que les diferencia (aparte de que **solaR2** es más modular, es decir, tiene muchas funciones autónomas que permiten realizar cálculos específicos, en especial de geometría y radiación) es el paquete sobre el que construyen sus datos.

Mientras que **solaR** basa sus clases y métodos en el paquete **zoo**, **solaR2** en el paquete **data.table**. Los dos paquetes pueden trabajar con series temporales, pero, mientras que **zoo** es más eficaz trabajando con series temporales, **data.table** es más eficiente a la hora de trabajar con una cantidad grande de datos, lo cual a la hora de realizar estimaciones muy precisas es beneficioso.

Por otro lado, existen otras soluciones fuera de R:

1. **PVsyst - Photovoltaic Software** [PVS24] Este software es probablemente el más conocido dentro del ámbito del estudio y la estimación de instalaciones fotovoltaicas. Permite una gran personalización de todos los componentes de la instalación.
2. **SISIFO** [Sis24] Herramienta web diseñada por el **Grupo de Sistemas Fotovoltaicos del Instituto de Energía Solar de la Universidad Politécnica de Madrid**.
3. **PVGIS** [PVG24] Aplicación web desarrollada por el **European Commission Joint Research Center** desde 2001.
4. **System Advisor Model** [SAM24] Desarrollado por el **Laboratorio Nacional de Energías Renovables**, perteneciente al Departamento de energía del gobierno de EE.UU.

En el capítulo 5 se realizará un ejemplo práctico que compare los resultados entre **PVsyst**, **solaR** y **solaR2**

1.3. Aspectos técnicos

Las fuentes de un paquete de **R** están contenidas en un directorio que contiene al menos:

- Los ficheros **DESCRIPTION** y **NAMESPACE**
- Los subdirectorios:
 - **R**: código en ficheros **.R**
 - **man**: páginas de ayuda de las funciones, métodos y clases contenidas en el paquete.

Esta estructura puede ser generada con **package.skeleton**

1.3.1. DESCRIPTION

El fichero **DESCRIPTION** contiene la información básica:

```
Package: pkgname
Version: 0.5-1
Date: 2004-01-01
Title: My First Collection of Functions
Authors@R: c(person("Joe", "Developer", role = c("aut", "cre"),
                  email = "Joe.Developer@some.domain.net"),
             person("Pat", "Developer", role = "aut"),
             person("A.", "User", role = "ctb",
                  email = "A.User@whereever.net"))
Author: Joe Developer and Pat Developer, with contributions from A. User
Maintainer: Joe Developer <Joe.Developer@some.domain.net>
Depends: R (>= 1.8.0), nlme
Suggests: MASS
Description: A short (one paragraph) description of what
             the package does and why it may be useful.
License: GPL (>= 2)
URL: http://www.r-project.org, http://www.another.url
```

- Los campos **Package**, **Version**, **License**, **Title**, **Autor** y **Maintainer** son obligatorios.
- Si usa métodos **S4** debe incluir **Depends: methods**.

1.3.2. NAMESPACE

R usa un sistema de gestión de **espacio de nombres** que permite al autor del paquete especificar:

- Las **variables** del paquete que se **exportan** (y son, por tanto, accesibles a los usuarios).
- Las **variables** que se **importan** de otros paquetes.
- Las **clases y métodos S3 y S4** que deben registrarse.

El **NAMESPACE** controla la estrategia de búsqueda de variables que utilizan las funciones del paquete:

- En primer lugar, busca entre las creadas localmente (por el código de la carpeta **R/**).
- En segundo lugar, busca entre las variables importadas explícitamente de otros paquetes.
- En tercer lugar, busca en el **NAMESPACE** del paquete **base**.
- Por último, busca siguiendo el camino habitual (usando **search()**).

1 `search()`

[1] ".GlobalEnv"	"ESSR"	"package:stats"	"package:graphics"
[5] "package:grDevices"	"package:utils"	"package:datasets"	"package:methods"
[9] "AutoLoads"	"package:base"		

Manejo de variables

- Exportar variables:

```
1 export(f, g)
```

- Importar **todas** las variables de un paquete:

```
1 import(pkgExt)
```

- Importar variables **concretas** de un paquete:

```
1 importFrom(pkgExt, var1, var2)
```

Manejo de clases y métodos

- Para registrar un **método** para una **clase** determinada:

```
1 S3method(print, myClass)
```

- Para usar clases y métodos **S4**:

```
1 import("methods")
```

- Para registrar clases **S4**:

```
1 exportClasses(class1, class2)
```

- Para registrar métodos **S4**:

```
1 exportMethods(method1, method2)
```

- Para importar métodos y clases **S4** de otro paquete:

```
1 importClassesFrom(package, ...)  
2 importMethodsFrom(package, ...)
```

1.3.3. Documentación

Las páginas de ayuda de los objetos **R** se escriben usando el formato “R documentation” (Rd), un lenguaje similar a \LaTeX .

```
\name{load}
\alias{load}
\title{Reload Saved Datasets}
\description{
  Reload the datasets written to a file with the function
  \code{save}.
}
\usage{
  load(file, envir = parent.frame())
}
\arguments{
\item{file}{a connection or a character string giving the
  name of the file to load.}
\item{envir}{the environment where the data should be
  loaded.}
}
\seealso{
  \code{\link{save}}.
}
\examples{
  ## save all data
  save(list = ls(), file= "all.RData")

  ## restore the saved values to the current environment
  load("all.RData")

  ## restore the saved values to the workspace
  load("all.RData", .GlobalEnv)
}
\keyword{file}
```

Estado del arte

2.1. Situación actual de la generación fotovoltaica

Según el informe anual de 2023 de la UNEF¹ [UNE23] en 2022 la fotovoltaica se posicionó como la tecnología con más crecimiento a nivel internacional, tanto entre las renovables como entre las no renovables. Se instalaron 240 GWp de nueva capacidad fotovoltaica a nivel mundial, suponiendo esto un incremento del 137 % con respecto a 2021.

A pesar de las diversas crisis internacionales, la energía solar fotovoltaica alcanzó a superar los 1185 GWp instalados. Como otros años, las cifras indican que China continuó siendo el primer actor mundial, superando los 106 GWp de potencia instalada en el año. La Unión Europea se situó en el segundo puesto, duplicando la potencia instalada en 2021, y alcanzando un nuevo record con 41 GWp instalados en 2022.

La producción energía fotovoltaica a nivel mundial representó el 31 % de la capacidad de generación renovable, convirtiéndose así en la segunda fuente de generación, solo por detrás de la energía hidráulica. En 2022 se añadió 3 veces más de energía solar que de energía eólica en todo el mundo.

Por otro lado, la Unión Europea superó a EE.UU. como el segundo mayor actor mundial en desarrollo fotovoltaico, instalando un 47 % más que en 2021 y alcanzando una potencia acumulada de más de 208 GWp. España lideró el mercado europeo con 8,6 GWp instalados en 2022, superando a Alemania.

El año 2022 fue significativo en términos legislativos con el lanzamiento del Plan REPowerEU² [Eur22]. Dentro de este plan, se lanzó la Estrategia de Energía Solar con el objetivo de alcanzar 400 GWp (320 GW) para 2030, incluyendo medidas para desarrollar tejados solares, impulsar la industria fotovoltaica y apoyar la formación de profesionales en el sector.

En 2022, España vivió un auge en el desarrollo fotovoltaico, instalando 5.641 MWp en plantas en suelo, un 30 % más que en 2021, y aumentando el autoconsumo en un 108 %, alcanzando 3.008 MWp. El sector industrial de autoconsumo creció notablemente, representando el 47 % del autoconsumo total.

¹UNEF: Unión Española Fotovoltaica.

²Plan REPowerEU: Proyecto por el cual la Unión Europea quiere poner fin a su dependencia de los combustibles fósiles rusos ahorrando energía, diversificando los suministros y acelerando la transición hacia una energía limpia.

España implementó varias iniciativas legislativas para enfrentar la volatilidad de precios de la energía y la dependencia del gas, destacando el RD-ley 6/2022 [BOE22b] y el RD 10/2022 [BOE22a], que han modificado mecanismos de precios y estableciendo límites al precio del gas.

El Plan SE+³ [dem22] incluye medidas fiscales y administrativas para apoyar las renovables y el autoconsumo. En 2022, se realizaron subastas de energía renovable, asignando 140 MW a solar fotovoltaica en la tercera subasta y 1.800MW en la cuarta, aunque esta última quedó desierta por precios de reserva bajos.

Se adjudicaron 1.200 MW del nudo de transición justa de Andorra a Enel Green Power España, con planes para instalar plantas de hidrógeno verde y agrovoltaica. la actividad en hidrógeno verde y almacenamiento también creció, con fondos adicionales y exenciones de cargos.

El autoconsumo, apoyado por diversas regulaciones y altos precios de la electricidad, registró un crecimiento significativo, alcanzado 2.504 MW de nueva potencia en 2022. Las comunidades energéticas también avanzaron gracias a ayudas específicas, a pesar de la falta de un marco regulatorio definido.

2022 estuvo marcado por los programas financiados por la Unión Europea, especialmente el Mecanismo de Recuperación y Resiliencia [Hac22] que canaliza los fondos NextGenerationEU [Uni20]. El PERTE⁴, aprobado en diciembre de 2021, espera crear más de 280.000 empleos, con ayudas que se ejecutarán hasta 2026. En 2023 se solicitó a Bruselas una adenda para segunda fase del PERTE, obteniendo 2.700 millones de euros adicionales.

La contribución del sector fotovoltaico a la economía española en 2022 fue significativa, aportando 7.014 millones de euros al PIB⁵, un 51 % más que el año anterior, y generando una huella económica total de 15.656 millones de euros. En términos de empleo, el sector involucró a 197.383 trabajadores, de los cuales 40.683 fueron directos, 97.600 indirectos y 59.100 inducidos.

El sector industrial fotovoltaico nacional tiene una fuerte presencia en España, con hasta un 65 % de los componentes manufacturados localmente. Empresas españolas se encuentran entre los principales fabricantes mundiales de inversores y seguidores solares. Además, España es un importante exportador de estructuras fotovoltaicas y cuenta con iniciativas prometedoras para la fabricación de módulos solares.

En definitiva, la fotovoltaica es una tecnología en auge y con perspectivas para ser el pilar de la transición ecológica. Por ello, surge la necesidad de encontrar herramientas que permitan estimar el desempeño que estos sistemas pueden tener a la hora de realizar estudios de viabilidad económica.

2.2. Solución actual y sus carencias

Como se mencionó en el capítulo 1 este proyecto toma su base en el paquete **solaR** [Per12], el cual es una herramienta robusta para el cálculo de la radiación solar y el rendimiento de sistemas fotovoltaicos. Este paquete está diseñado utilizando clases **S4** en **R**, y su núcleo se basa en series temporales multivariantes almacenadas en objetos de la clase **zoo**. El paquete permite realizar investigaciones reproducibles sobre el rendimiento de sistemas fotovoltaicos y la radiación solar, proporcionando métodos para calcular la geometría solar, la radiación incidente sobre un

³Plan + Seguridad Energética: Se trata de un plan con medidas de rápido impacto dirigidas al invierno 2022/2023, junto con medidas que contribuyen a un refuerzo estructural de esa seguridad energética.

⁴PERTE: Proyecto Estratégico para la Recuperación y Transformación Económica.

⁵PIB: Producto Interior Bruto.

generador fotovoltaico, y simular el rendimiento de sistemas fotovoltaicos tanto conectados a la red como de bombeo de agua.

Pese a ser un herramienta muy capaz, **solaR** presenta una serie de carencias relativas al paquete **zoo**:

- **Eficiencia y rendimiento:** el paquete **solaR** utiliza **zoo** para manejar series temporales, lo cual es adecuado para volúmenes de datos moderados. Sin embargo, **zoo** no está optimizado para operaciones de alta eficiencia en datasets grandes. Por otro lado, **data.table** está diseñado específicamente para manejar grandes volúmenes de datos de manera eficiente, ofreciendo un rendimiento superior en operaciones de lectura, escritura y manipulación masiva de datos.
- **Escalabilidad:** **solaR** puede experimentar problemas de escalabilidad al trabajar con datasets extensos, ya que **zoo** no es tan eficiente en operaciones que requieren manipulación compleja o paralelización. Sin embargo, **data.table** supera esta limitación al proporcionar una infraestructura altamente optimizada para operaciones en paralelo y manejo de grandes conjuntos de datos, permitiendo que las aplicaciones escalen mejor en entornos de datos intensivos.
- **Manipulación de datos:** **zoo** es adecuado para manejar series temporales básicas, pero carece de las capacidades avanzadas de manipulación de datos que ofrece **data.table**, como la indexación rápida, las uniones eficientes, y la capacidad de realizar operaciones complejas de agrupamiento y agregación. Estas características de **data.table** permiten un manejo de datos más flexible y potente, lo cual es esencial en análisis de datos complejo y en tiempo real.
- **Consumo de memoria:** **zoo** puede consumir más memoria en comparación con **data.table** cuando se trabaja con grandes conjuntos de datos. Por otro lado, **data.table** está optimizado para operaciones en memoria, lo que permite manejar datasets más grandes sin requerir un incremento proporcional en el uso de recursos, haciendo que las operaciones sean más sostenibles en términos de memoria.

Por lo tanto, al adoptar **data.table** en **solaR2**, se abordarían estas limitaciones, proporcionando un paquete más robusto y capaz de manejar los desafíos actuales en el análisis de datos de radiación solar y de producción de sistemas fotovoltaicos.

Marco teórico

El paquete **solarR2** toma como marco teórico el libro de Oscar Perpiñán, tutor de este trabajo, Energía Solar Fotovoltaica [Per23] para cada una de las operaciones de cálculo que realizan cada una de las funciones. En la figura 3.1, se muestra un diagrama que resume los pasos que se siguen a la hora de calcular la producción de sistemas fotovoltaicos. Estos pasos son:

1. Calcular la geometría que define la posición relativa del Sol desde la Tierra.
2. Obtener la irradiación global diaria en el plano horizontal
3. A partir de la irradiación global, obtener las componentes de difusa y directa.
4. Se trasladan estos valores de irradiación a valores de irradiancia.
5. Integrando estos valores se pueden obtener las estimaciones irradiación diaria difusa, directa y global
6. El generador fotovoltaico produce una potencia en corriente continua dependiente del rendimiento del mismo.
7. Se transforma en potencia en corriente alterna mediante un inversor que tiene una eficiencia asociada.
8. Integrando esta potencia se puede obtener la energía que produce el generador en un tiempo determinado.

3.1. Naturaleza de la radiación solar

Para el cálculo de la radiación solar que incide en una superficie se deben distinguir tres componentes diferenciados:

- **Radiación Directa**, B: fracción de radiación que procede en línea recta desde el Sol.
- **Radiación Difusa**, D: fracción de radiación que procede de todo el cielo, excepto del Sol. Son todos aquellos rayos que dispersa la atmósfera.
- **Radiación del albedo**, R: parte de la radiación procedente de la reflexión con el suelo.




FIGURA 3.1: Procedimiento de cálculo

La suma de las tres componentes constituye la denominada radiación global:

$$G = B + D + R \quad (3.1)$$

Tomando como base el libro antes mencionado [Per23], se describirá el proceso que se ha de seguir para obtener una estimación de las componenetes directa y difusa a partir del dato de radiación global, dado que es el que comúnmente se puede obtener de una localización determinada.

3.1.1. Radiación fuera de la atmósfera terrestre

Lo primero que se menciona en dicho proceso es la obtención de la irradiancia denominada extra-terrestre o extra-atmosférica, que es la radiación que llega a la atmósfera, directamente desde el Sol, que no sufre ninguna pérdida por interaccionar con algún medio. Como la relación entre el tamaño de nuestro planeta y la distancia entre el Sol y la Tierra es muy reducida, es posible asumir que el valor de dicha irradiancia es constante, siendo este valor $B_0 = 1367 \frac{W}{m^2}$, según varias mediciones. Como la órbita que describe la Tierra alrededor del Sol no es totalmente circular, sino que tiene forma de elipse, para calcular la irradiancia incidente en una superficie tangente a la atmosfera en ua latitud concreta, debemos aplicar un factor de corrección de la excentricidad de la elipse:

$$B_0(0) = B_0 \epsilon_0 \cos \theta_{zs} \quad (3.2)$$

Siendo cada componente:

- Constante solar: $B_0 = 1367 \frac{W}{m^2}$
- Factor de corrección por excentricidad: $\epsilon_0 = (\frac{r_0}{r})^2 = 1 + 0,033 \cdot \cos(\frac{2\pi d_n}{365})^1$
- Ángulo zenital solar: $\cos(\theta_{zs}) = \cos(\delta)\cos(\omega)\cos(\phi) + \sin(\delta)\sin(\phi)^2$ Donde:
 - Declinación: $\delta = 23,45^\circ \cdot \sin(\frac{2\pi \cdot (d_n + 284)}{365})$ donde d_n es el día del año.
 - Latitud: ϕ
 - Hora solar o tiempo solar verdadero: $\omega = 15 \cdot (TO - AO - 12) + \Delta\lambda + \frac{EoT}{4}$
 Donde:
 - Hora oficial: TO
 - Adelanto oficial durante el horario de verano: AO
 - Diferencia entre la longitud local y la longitud del huso horario: $\Delta\lambda$
 - Ecuación del tiempo: $EoT = 229,18 \cdot (-0,0334 \cdot \sin(\frac{2\pi}{365,24} \cdot dn) + 0,04184 \cdot \sin(2 \cdot \frac{2\pi}{365,24} \cdot dn + 3,5884))$

Esta irradiancia extra-terrestre solo tiene componentes geométricas. De modo que, si integramos la ecuación 3.2, se obtiene la irradiación diaria extra-terrestre:

$$B_{0d}(0) = -\frac{T}{\pi} B_0 \epsilon_0 (\omega_s \sin \phi \sin \delta + \cos \phi \cos \delta \sin \omega_s) \quad (3.3)$$

Siendo:

- Ángulo del amanecer:

$$\omega_s = \begin{cases} -\arccos(-\tan \delta \tan \phi) & \text{si } |\tan \delta \tan \phi| < 1 \\ -\pi & \text{si } -\tan \delta \tan \phi < -1 \\ 0 & \text{si } -\tan \delta \tan \phi > 1 \end{cases}$$

Es posible demostrar que el promedio mensual de esta irradiación diaria coincide numéricamente con el valor de irradiación diaria correspondiente a los denominados “días promedios”, días en los que la declinación correspondiente coincide con el promedio mensual (tabla 3.1)

TABLA 3.1: Valor d_n correspondiente a los doce días promedio.

Mes	Ene	Feb	Mar	Abr	May	Jun	Jul	Ago	Sep	Oct	Nov	Dic
d_n	17	45	74	105	135	161	199	230	261	292	322	347

¹Para las ecuaciones de este apartado se va a optar por poner la ecuación más simple posible. Sin embargo, el paquete **solar2** otorga la posibilidad de realizar los cálculos de utilizando las ecuaciones propuestas por 4 autores diferentes.

²Se van a utilizar las ecuaciones propuestas por P.I. Cooper [Coo69] por su simpleza.

3.1.2. Cálculo de componentes de radiación solar

Para caracterizar la radiación solar en un lugar, Liu y Jordan [LJ60] propusieron el índice de claridad, K_T . Este índice es la relación entre la radiación global y la radiación extra-atmosférica, ambas en el plano horizontal. El índice de claridad diario es la relación entre los valores diarios de irradiación:

$$K_{Td} = \frac{G_d(0)}{B_{0d}(0)} \quad (3.4)$$

mientras que el índice de claridad mensual es la relación entre las medias mensuales de la irradiación diaria:

$$K_{Tm} = \frac{G_{d,m}(0)}{B_{0d,m}(0)} \quad (3.5)$$

Una vez se tiene el índice de claridad, se puede calcular la fracción de radiación difusa en el plano horizontal. En el caso de medias mensuales [Pag61]:

$$F_{Dm} = 1 - 1,13 \cdot K_{Tm} \quad (3.6)$$

Donde:

- Fracción de radiación difusa: $F_D = \frac{D(0)}{G(0)}$

Al tener la fracción de radiación difusa, se pueden obtener los valores de la radiación directa y difusa en el plano horizontal:

$$D_d(0) = F_D \cdot G_d(0) \quad (3.7)$$

$$B_d(0) = G_d(0) - D_d(0) \quad (3.8)$$

3.2. Radiación en superficies inclinadas

Dados los valores de irradiación diaria difusa, directa y global en el plano horizontal se puede realizar la transformación al plano inclinado. Para ello, es necesario estimar el perfil de irradiancia correspondiente a cada valor de irradiación. dado que la variación solar durante una hora es baja, podemos suponer que el valor medio de la irradiancia durante esa hora coincide numéricamente con la irradiación horaria. Por otra parte, el análisis de valores *medios* en *largas* series temporales ha mostrado que la relación entre la irradiancia y la irradiación extra-atmosférica [CR79] (3.9):

$$r_D = \frac{D(0)}{D_d(0)} = \frac{B_0(0)}{B_{0d}(0)} \quad (3.9)$$

Este factor r_D es calculable directamente sabiendo que la relación entre irradiancia e irradiación extra-atmosférica es deducible teóricamente a partir de las ecuaciones 3.2 3.3:

$$\frac{B_0(0)}{B_{0d}(0)} = \frac{\pi}{T} \cdot \frac{\cos(\omega) - \cos(\omega_s)}{\omega_s \cdot \cos(\omega_s) - \sin(\omega_s)} = r_D \quad (3.10)$$

el mismo análisis mostró una relación entre la irradiancia e irradiación global asimilable a una función dependiente de la hora solar (3.11):

$$r_G = \frac{G(0)}{G_d(0)} = r_D \cdot (a + b \cdot \cos(w)) \quad (3.11)$$

Donde:

- $a = 0,409 - 0,5016 \cdot \sin(\omega_s + \frac{\pi}{3})$
- $b = 0,6609 + 0,4767 \cdot \sin(\omega_s + \frac{\pi}{3})$

Es importante resaltar que estos perfiles proceden de medias sobre largos períodos, y de ahí que, como es observable en la figura 3.2, las fluctuaciones propias del movimiento de nubes a lo largo del día queden atenuadas y se obtenga una curva sin alteraciones.

3.2.1. Transformación al plano del generador

Una vez obtenidos los valores de irradiancia en el plano horizontal, se traspone al plano del generador:

- **Irradiancia Directa** $B(\beta, \alpha)$: Ecuación basada en geometría solar (ángulo zenital) y del generador (ángulo de incidencia).

$$B(\beta, \alpha) = B(0) \cdot \frac{\max(0, \cos(\theta_s))}{\cos(\theta_{zs})} \quad (3.12)$$

donde:

- Ángulo de inclinación: β .
- Ángulo de orientación: α .
- **Irradiancia Difusa** $D(\beta, \alpha)$: Utilizando el modelo de cielo anisotrópico [Per23], se distinguen dos componentes de la irradiancia difusa, denominados *circumsolar* e *isotrópica*.

$$D(\beta, \alpha) = D^I(\beta, \alpha) + D^C(\beta, \alpha) \quad (3.13)$$




FIGURA 3.2: Perfil de irradiancia difusa y global obtenido a partir del generador empírico de [CR79] para valores de irradiancia tomadas cada 10 minutos

$$D^I(\beta, \alpha) = D(0)(1 - k_1) \cdot \frac{1 + \cos(\beta)}{2} \quad (3.14)$$

$$D^C(\beta, \alpha) = D(0) \cdot k_1 \cdot \frac{\max(0, \cos(\theta_s))}{\cos(\theta_{zs})} \quad (3.15)$$

Donde:

- $k_1 = \frac{B(n)}{B_0 \cdot \epsilon_0} = \frac{B(0)}{B_0(0)}$

- **Irradiancia de albedo** $R(\beta, \alpha)$: Se considera isotrópica debido a su baja contribución a la radiación global. Se calcula a partir de la irradiancia global en el plano horizontal usando un coeficiente de reflexión, ρ , que depende del terreno. En la ecuación 3.16, se utiliza el factor $\frac{1 - \cos(\beta)}{2}$, complementario al factor de visión de la difusa isotrópica (figura 3.3)

$$R(\beta, \alpha) = \rho \cdot G(0) \cdot \frac{1 - \cos(\beta)}{2} \quad (3.16)$$

3.2.2. Ángulo de incidencia y suciedad

En un módulo fotovoltaico, la radiación incidente generalmente no es perpendicular a la superficie del módulo, lo que provoca pérdidas por reflexión o pérdidas angulares, cuantificadas por el ángulo de incidencia θ_s . La suciedad acumulada en la superficie del módulo también reduce la transmitancia del vidrio (representada por $T_{limpio}(0)$), disminuyendo la irradiancia efectiva, es decir, la radiación que realmente puede ser aprovechada por el módulo. La irradiancia efectiva para radiación directa se expresa en la ecuación 3.17:

$$B_{ef}(\beta, \alpha) = B(\beta, \alpha) \cdot \left[\frac{T_{sucio}(0)}{T_{limpio}(0)} \right] \cdot (1 - FTB(\theta_s)) \quad (3.17)$$

donde $FTB(\theta_s)$ es el factor de pérdidas angulares, que se calcula con la ecuación 3.18:

$$FTB(\theta_s) = \frac{\exp(-\frac{\cos(\theta_s)}{a_r}) - \exp(-\frac{1}{a_r})}{1 - \exp(-\frac{1}{a_r})} \quad (3.18)$$




FIGURA 3.3: Ángulo de visión del cielo

Este factor depende el ángulo de incidencia θ_s y del coeficiente de pérdidas angulares a_r . Cuando la radiación es perpendicular a la superficie ($\theta_s = 0$), FTB es cero. En la figura 3.4 se puede observar que las pérdidas angulares son más significativas cuando θ_s supera los 60° , y se acentúan con mayor suciedad.

Para calcular las componente de radiación difusa isotrópica y de albedo se utilizan las ecuaciones 3.19 y 3.2.2:

$$FTD(\beta) \approx \exp\left[-\frac{1}{a_r} \cdot \left(c_1 \cdot \left(\sin\beta + \frac{\pi - \beta - \sin\beta}{1 + \cos\beta}\right) + c_2 \cdot \left(\sin\beta + \frac{\pi - \beta - \sin\beta}{1 + \cos\beta}\right)^2\right)\right] \quad (3.19)$$

$$FTR(\beta) \approx \exp\left[-\frac{1}{a_r} \cdot \left(c_1 \cdot \left(\sin\beta + \frac{\beta - \sin\beta}{1 - \cos\beta}\right) + c_2 \cdot \left(\sin\beta + \frac{\beta - \sin\beta}{1 - \cos\beta}\right)^2\right)\right] \quad (3.20)$$

Donde:

- Ángulo de inclinación del generador (en radianes): β
- Coeficiente de pérdidas angulares: a_r
- Coeficientes de ajuste: c_1 y c_2 (en la tabla 3.2 se recogen algunos valores característicos de un módulo de silicio monocristalino convencional para diferentes grados de suciedad)

Para estas componenets el cálculo de irradiancia efectiva es similar al de la irradiancia directa (ecuaciones 3.21 y 3.23). Para la componente difusa circumsolar emplearemos el factor de pérdidas angulares de la irradiancia efectiva (ecuacion 3.22):

$$D_{ef}^I(\beta, \alpha) = D^I(\beta, \alpha) \cdot \left[\frac{T_{sucio}(0)}{T_{limpio}(0)}\right] \cdot (1 - FTD(\beta)) \quad (3.21)$$




FIGURA 3.4: Pérdidas angulares de un módulo fotovoltaico para diferentes grados de suciedad en función del ángulo de incidencia.

TABLA 3.2: Valores del coeficiente de pérdidas angulares y transmitancia relativa en incidencia normal para diferentes tipos de suciedad.

Grado de suciedad	$\frac{T_{sucio}(0)}{T_{limpio}(0)}$	a_r	c_2
Limpio	1	0.17	-0.069
Bajo	0.98	0.20	-0.054
Medio	0.97	0.21	-0.049
Alto	0.92	0.27	-0.023

$$D_{ef}^C(\beta, \alpha) = D^C(\beta, \alpha) \cdot \left[\frac{T_{sucio}(0)}{T_{limpio}(0)} \right] \cdot (1 - FT_B(\theta_s)) \quad (3.22)$$

$$R_{ef}(\beta, \alpha) = R(\beta, \alpha) \cdot \left[\frac{T_{sucio}(0)}{T_{limpio}(0)} \right] \cdot (1 - FT_R(\beta)) \quad (3.23)$$

Siguiendo el esquema de la figura 3.1, a partir de estas irradiancias efectivas se puede calcular la irradiación global efectiva diaria, mensual y anual. Comparando la irradiación global incidente con la irradiación efectiva, se puede evaluar el impacto de la suciedad y el desajuste del ángulo en períodos prolongados.

3.3. Cálculo de la energía producida por un generador fotovoltaico

3.3.1. Funcionamiento de una célula solar

Para calcular la energía producida por un generador fotovoltaico, se deben tener en cuenta la influencia de factores tales como la radiación o la temperatura en una célula solar y en los valores de tensión y corriente que se alcanzan en dichas condiciones.

Para definir una célula solar, se tomar 4 variables:

- La corriente de cortocircuito: I_{sc}
- La tensión de circuito abierto: V_{oc}
- La corriente en el punto de máxima potencia: I_{mpp}
- La tensión en el punto de máxima potencia: V_{mpp}

Punto de máxima potencia

El punto de máxima potencia es aquel situado en la curva de funcionamiento del generador donde, como su propio nombre indica, los valores de tensión y corriente son tales que la potencia que entrega es máxima (figura 3.5).

Factor de forma y eficiencia

El área encerrada por el rectángulo definido por el producto $I_{mpp} \cdot V_{mpp}$ es, como es observable en la figura 3.5, inferior a la representada por el producto $I_{sc} \cdot V_{oc}$. La relación entre estas dos superficies se cuantifica con el factor de forma:

$$FF = \frac{I_{mpp} \cdot V_{mpp}}{I_{sc} \cdot V_{oc}} \quad (3.24)$$




FIGURA 3.5: Curvas corriente-tensión(línea discontinua) y potencia-tensión(línea continua) de una célula solar ($T_a = 20^\circ\text{C}$ y $G = 800\text{W}/\text{m}^2$)

Conociendo los valores de I_{sc} y V_{oc} es posible calcular la potencia en el punto de máxima potencia, dado que $P_{mpp} = FF \cdot I_{sc} \cdot V_{oc}$.

Por otra parte, la calidad de una célula se puede cuantificar con la eficiencia de conversión (ecuación 3.25).

$$\eta = \frac{I_{mpp} \cdot V_{mpp}}{P_L} \quad (3.25)$$

donde $P_L = A_c \cdot G_{ef}$ representa la potencia luminosa que incide en la célula. Como es evidente de la ecuación 3.25, este valor de eficiencia se corresponde al caso en el que el acoplamiento entre la carga y la célula permite a ésta trabajar en el punto de máxima potencia. En la figura 3.6 se muestra la evolución temporal del valor de eficiencia de célula de laboratorio para diferentes tecnologías.

Influencia de la temperatura y la radiación

La temperatura y la radiación son factores cruciales en el funcionamiento de una célula solar. El aumento de la temperatura ambiente reduce la tensión de circuito abierto según la relación dV_{oc}/dT_c , que para células de silicio cristalino es de $-2,3 \frac{\text{mV}}{^\circ\text{C}}$. Además, disminuye la eficiencia de la célula solar con $\frac{d\eta}{dT_c} = -0,4 \text{ \%}/^\circ\text{C}$.

En cuanto a la iluminación, la fotocorriente y la tensión de circuito abierto son proporcionales a la irradiancia incidente.

Tomando en cuenta estas influencias, se definen unas condiciones de funcionamiento, denominadas condiciones estándar de medida (STC), válidas para caracterizar una célula en el entorno de un laboratorio. Estas condiciones vienen determinadas por:




FIGURA 3.6: Evolución de la eficiencia de células según la tecnología (según el National Renewable Energy Laboratory [Nat24] (EEUU)).

- Irradiancia: $G_{stc} = 1000W/m^2$ con incidencia normal.
- Temperatura de célula: $T_c^* = 25^\circ C$.
- Masa de aire: $AM = 1,5$.³

Frecuentemente los fabricantes informan de los valores de las tensiones V_{oc}^* y V_{mpp}^* y las corrientes I_{sc}^* y I_{mpp}^* .⁴ A partir de estos valores es posible referir a estas condiciones:

- La potencia: $P_{mpp}^* = I_{mpp}^* \cdot V_{mpp}^*$
- El factor de forma: $FF^* = \frac{P_{mpp}^*}{I_{sc}^* \cdot V_{oc}^*}$
- La eficiencia: $\eta^* = \frac{I_{mpp}^* \cdot V_{mpp}^*}{A_c \cdot G_{stc}}$

3.3.2. Funcionamiento de un módulo fotovoltaico

Comportamiento térmico de un módulo

La mayoría de las ecuaciones que definen el comportamiento de un módulo fotovoltaico se establecen en lo que se conocen como condiciones estándar de funcionamiento. En estas condiciones, la temperatura de la célula es de $25^\circ C$. Sin embargo, la temperatura de operación de la célula es diferente y depende directamente de la radiación que recibe el módulo en cada momento.

El módulo recibe una cantidad de radiación dada, absorbiendo la fracción de ésta que no se refleja al exterior. De dicha fracción, parte de ella es transformada en energía eléctrica mientras que el resto se entrega en forma de calor al entorno.

³Relación entre el camino recorrido por los rayos directos del Sol a través de la atmósfera hasta la superficie receptora y el que recorrerían en caso de incidencia vertical ($AM = 1/\cos\theta_{zs}$).

⁴Es de uso común añadir un asterisco como superíndice para denotar aquellos parámetros medidos en estas condiciones.

Para simplificar, se puede asumir que el incremento de la temperatura de la célula respecto de la temperatura ambiente depende linealmente de la irradiancia incidente en ésta. El coeficiente de proporcionalidad depende de muchos factores, tales como el modo de instalación del módulo, la velocidad del viento, la humedad ambiente y las características constructivas del laminado.

Estos factores quedan recogidos en un valor único representado por la temperatura de operación nominal de célula (NOCT o TONC), definida como aquella que alcanza una *célula* cuando su *módulo* trabaja en las siguientes condiciones:

- Irradiancia: $G = 800 \text{ W/m}^2$.
- Masa de aire: $AM = 1,5$.
- Irradiancia normal.
- Temperatura ambiente: $T_a = 20^\circ \text{C}$.
- Velocidad de viento: $v_v = 1 \text{ m/s}$.

La ecuación 3.26 expresa una aproximación aceptable del comportamiento térmico de una célula integrada en un módulo en base a las consideraciones previas:

$$T_c = T_a + G_{ef} \cdot \frac{NOCT - 20}{800} \quad (3.26)$$

Para la simulación del funcionamiento de un módulo fotovoltaico en condiciones de operación real, es necesario contar con secuencias de valores de temperatura ambiente. Si no se dispone de información detallada, se puede asumir un valor constante de $T_a = 25^\circ \text{C}$ para simulaciones anuales. Sin embargo, si se conocen los valores máximos y mínimos diarios de la temperatura ambiente, se puede generar una secuencia intradiaria usando una combinación de funciones coseno.

Cálculo de V_{oc} y I_{sc}

Conociendo ya los valores horarios de temperatura de la célula, se puede calcular V_{oc} utilizando la ecuación 3.27. Y, por último, mediante la ecuación 3.28 se puede calcular I_{sc} .

$$V_{oc}(T_c) = V_{oc}^* + (T_c - T_c^*) \cdot \frac{dV_{oc}}{dT_c} \cdot N_{cs} \quad (3.27)$$

$$I_{sc} = G_{ef} \cdot \frac{I_{sc}^*}{G^*} \quad (3.28)$$

Factor de forma variable

Una vez obtenidos los valores de V_{oc} y I_{sc} , el siguiente paso ha de ser calcular los valores de tensión y corriente en el punto de máxima potencia, pues es donde el generador estará entregando su máxima potencia, como su propio nombre indica, y por tanto es un punto de interés para el cálculo.

Existen dos metodologías de cálculo de dicho punto, uno de ellos significativamente más sencillo que el otro. Éste consiste en suponer que el Factor de Forma, definido en la expresión 3.24 es constante.

Si suponemos que FF es constante, se podrían extraer los valores de tensión y corriente en el punto de máxima potencia ya que si

$$FF = FF^* \quad (3.29)$$

entonces

$$\frac{I_{mpp} \cdot V_{vmpp}}{I_{sc} \cdot V_{oc}} = \frac{I_{mpp}^* \cdot V_{vmpp}^*}{I_{sc}^* \cdot V_{oc}^*} \quad (3.30)$$

pudiendo así obtener los valores de I_{mpp} y V_{vmpp} .

Sin embargo, esta suposición da resultados alejados a una estimación acertada. Por ello, se tendrá en cuenta la variación del factor de forma:

- **Cálculo de la tensión termica, V_t , a temperatura de la célula:** Se calculará el valor de V_t a 25°C con la expresión:

$$V_{tn} = \frac{V_t \cdot (273 + 25)}{300} \quad (3.31)$$

- **Cálculo de R_s^* :** El segundo paso consiste en calcular el valor de resistencia en serie con los valores STC:

$$R_s^* = \frac{\frac{V_{oc}^*}{N_{cs}} - \frac{V_{mpp}^*}{N_{cs}} + m \cdot V_{tn} \cdot \ln(1 - \frac{I_{mpp}^*}{I_{sc}^*})}{\frac{I_{mpp}^*}{N_{cp}}} \quad (3.32)$$

- **Cálculo de r_s :** Utilizando los valores de R_s^* calculado en el paso anterior junto con los valores de V_{oc} y I_{sc} podemos calcular r_s que se utilizará más adelante en el proceso.

$$r_s = R_s^* \cdot \left(\frac{N_{cs}}{N_{cp}} \cdot \frac{I_{sc}}{V_{oc}} \right) \quad (3.33)$$

- **Cálculo de k_{oc} :** A continuación, utilizando los valores de temperatura ambiente obtenidos con anterioridad junto con la tensión de circuito abierto, se calcula k_{oc} mediante la expresión:

$$k_{oc} = \frac{V_{oc}/N_{cs}}{m \cdot V_t \cdot \frac{T_c + 273}{300}} \quad (3.34)$$

Con éstos cálculos previos, éste método propone localizar el punto de máxima potencia de forma aproximada mediante las ecuaciones:

$$i_{mpp} = 1 - \frac{D_M}{k_{oc}} \quad (3.35)$$

$$v_{mpp} = 1 - \frac{\ln(k_{oc}/D_M)}{k_{oc}} - r_s \cdot i_{mpp} \quad (3.36)$$

donde:

$$D_M = D_{M0} + 2 \cdot r_s \cdot D_{M0}^2 \quad (3.37)$$

$$D_{M0} = \frac{k_{oc} - 1}{k_{oc} - \ln k_{oc}} \quad (3.38)$$

Por último, multiplicando los valores de i_{mpp} y v_{mpp} por I_{sc} y V_{oc} respectivamente, se obtienen los valores de I_{mpp} y V_{mpp} que serán los que se utilicen para calcular la potencia entregada por el generador en el punto de máxima potencia.

Teniendo estos valores se puede obtener:

$$P_{mpp} = I_{mpp} \cdot V_{mpp} \quad (3.39)$$

3.3.3. Cálculo de potencias y energías de un sistema fotovoltaico conectado a la red

La potencia obtenida en el paso anterior es la de un solo módulo. Para conocer la potencia que va a ser capaz de entregar un socr, se debe tener en cuenta su configuración de módulos en serie y en paralelo.

$$P_g^* = N_s \cdot N_p \cdot P_m^* \quad (3.40)$$

Con este paso se obtiene la potencia horaria entregada por el generador fotovoltaico. El siguiente paso será pasar esa potencia a través del inversor y calcular la potencia a la salida de este.

Primero, se establecen las expresiones de las potencias normalizadas. Siendo P_{inv} la potencia nominal del inversor:

$$p_i = \frac{P_{DC}}{P_{inv}} \quad (3.41)$$

$$p_o = \frac{P_{AC}}{P_{inv}} \quad (3.42)$$

Por otro lado, el rendimiento de un inversor fotovoltaico se puede modelizar de la siguiente manera:

$$\eta_{inv} = \frac{p_o}{p_o + k_0 + k_1 p_o + k_2 p_o^2} \quad (3.43)$$

De las dos ecuaciones anteriores se puede deducir:

$$p_i = p_o + k_0 + k_1 p_o + k_2 p_o^2 \quad (3.44)$$

Desarrollando esta ecuación, se puede obtener una ecuación de segundo grado con p_o como incógnita:

$$k_2 p_o^2 + (k_1 + 1)p_o + (k_0 - p_i) = 0 \quad (3.45)$$

Por último, volviendo a las primeras expresiones se puede obtener la potencia en corriente alterna:

$$P_{AC} = p_o \cdot P_{inv} \quad (3.46)$$

Con esta potencia, integrando en función del tiempo se puede obtener la energía que genera el sistema

$$E_{AC} = \int_T P_{AC} dt \quad (3.47)$$

y la productividad:

$$Y_f = \frac{E_{ac}}{P_g^*} \quad (3.48)$$

3.3.4. Cálculo de potencias y energías de un sistema fotovoltaico de bombeo

Potencia hidráulica

La potencia hidráulica, P_H , necesaria para bombear agua es función de,

- La altura vertical aparente, H_v
- El caudal de agua, Q

$$P_H = g \cdot \rho \cdot Q \cdot H_V \quad (3.49)$$

Expresando P_H en watios, H_v en metros y Q en m^3/h la ecuación resulta en:

$$P_H = 2,725 \cdot Q \cdot H_v \quad (3.50)$$

Asumiendo que el agua bombeado sale por el co ducto a baja velocidad, la potencia de salida de la bomba necesita satisfacer P_H más las pérdidas de fricción en la tubería, P_f . Este valor se asimila a una altura equivalente H_f asociado a un caudal determinado:

$$H_T = H_v + H_f \quad (3.51)$$

La potencia eléctrica a la entrada de la motobomba, P_{el} , es:

$$P_{el} = \frac{P_H + P_f}{\eta_{mp}} \quad (3.52)$$

donde η_{mp} es la eficiencia de la motobomba. La potencia eléctrica requerida por la motobomba es entregada por un generador FV y acondicionador de potencia:

$$P_{el} = P_g^* \cdot \frac{G}{G_{stc}} \cdot \frac{\eta_g}{\eta_g^*} \cdot \eta_{inv} \quad (3.53)$$

siendo G la irradiancia en el plano del generador, η_{inv} la eficiencia del equipo de acondicionamiento de potencia y $\frac{\eta_g}{\eta_g^*}$ modela el comportamiento del generador con la temperatura.

Caudal diario

El caudal diario bombeado por este conjunto es:

$$Q_d = \int_d \frac{G}{G^*} \cdot P_g^* \cdot \eta_g \cdot \frac{\eta_{ig}}{\eta_{ig}^*} \cdot \eta_{inv} \cdot \eta_{mp} dt \quad (3.54)$$

Altura

Se puede definir una altura total equivalente, H_{TE} , con las siguientes suposiciones:

- Las pérdidas de fricción en tubería son despreciables ($H_f < 0,05 \cdot H_T$).
- El nivel del agua dentro del pozo se mantiene constante.

$$Q_d = \frac{P_g^*}{2,725 \cdot G^* \cdot H_{TE}} \int \left(\frac{G}{\eta_{ig}^* \eta_m^* \eta_{inv} \eta_{mp}} \right) dt \quad (3.55)$$

Ahora el cálculo en la integral sólo depende de la radiación, temperatura, y equipos.

Para calcular esta altura total equivalente, se debe suponer que:

- El pozo está caracterizado con tres parámetros:
 - Nivel estático, H_{st} .
 - Nivel dinámico, H_{dt} .
 - Caudal de ensayo, Q_t .

- Que se ha realizado el ensayo de bombeo para caracterizar los pozos con bomba portátil empleando el caudal máximo del pozo, Q_{max} ($Q_t = Q_{max}$).

Con estas suposiciones se puede llegar a la expresión:

$$H_{TE} = H_{ot} + H_{st} + \left(\frac{H_{dt} - H_{st}}{Q_T} \right) Q_{AP} + H_f(Q_{AP}) \quad (3.56)$$

donde:

- H_{OT} , es la altura desde la salida de agua hasta el suelo.
- Nivel estático, H_{st} .
- Nivel dinámico, H_{dt} .
- Caudal aparente, $Q_{AP} = \alpha \cdot Q_d$ ($\alpha = 1/24 = 0,0416h^{-1}$).
- $H_f(Q_{AP})$, pérdidas en la tubería al caudal aparente.

Potencia del generador

Como primera aproximación, se consideran constantes a lo largo del tiempo las eficiencias de los componentes del sistema con la elección de ciertos valores adecuados ($\frac{\eta_g}{\eta_g^*} = 0,85$, $\eta_{mp} = 0,35$, $\eta_{inv} = 0,9$). Así, es posible calcular de forma aproximada la potencia nominal del generador necesaria para bombear un caudal diario Q_d a una altura total equivalente H_{TE} a partir de la ecuación:

$$P_g^* = \frac{10 \cdot H_{TE} \cdot Q_d}{\frac{G_d}{G_{stc}}} \quad (3.57)$$

Simulación de sistemas fotovoltaicos de bombeo

Debido a la complicación del cálculo del dimensionamiento de los sistemas fotovoltaicos de bombeo, se puede recurrir a métodos de simulación asistidos por ordenaor. El algoritmo a seguir es:

1. Curva característica de la bomba que relaciona la altura, H , y el caudal, Q , a la frecuencia nominal de la bomba:

$$H = a \cdot f^2 + b \cdot f \cdot Q + c \cdot Q^2 \quad (3.58)$$

- Donde a , b , y c son coeficientes característicos de la bomba y f es la frecuencia.

2. Relaciones de semejanza para bombas centrífugas:

$$\frac{f_1}{f_2} = \frac{Q_1}{Q_2} = \left(\frac{H_1}{H_2} \right)^{1/2} = \left(\frac{P_1}{P_2} \right)^{1/3} \quad (3.59)$$

3. Cálculo de caudal y altura a frecuencia nominal (50 Hz):

$$Q_{50} = \frac{50 \cdot Q}{f} \quad (3.60)$$

$$H_{50} = H \cdot \left(\frac{50}{f} \right)^2 \quad (3.61)$$

4. Ecuación de potencia hidráulica:

$$P_{h,50} = 2,725 \cdot Q_{50} \cdot H_{50} \quad (3.62)$$

5. Potencia mecánica en el eje de la bomba a 50 Hz:

$$P_{b,50} = \frac{P_{h,50}}{\eta_b} \quad (3.63)$$

6. Potencia mecánica a frecuencia f :

$$P_b = P_{b,50} \cdot \left(\frac{f}{50}\right)^3 \quad (3.64)$$

7. Potencia eléctrica demandada por el motor:

$$P_{bc} = P_b \cdot \frac{50}{f} \quad (3.65)$$

$$P_{e,50} = \frac{P_{bc}}{\eta_m} \quad (3.66)$$

$$P_e = P_{e,50} \cdot \frac{f}{50} \quad (3.67)$$

8. Perfil de irradiancia diaria (según IEC 61725):

$$G = G_{max} \cdot \cos\left(\frac{t}{t_0} \cdot \frac{\pi}{2}\right) \cdot \left[1 + s \cdot \left(1 - \cos\left(\frac{t}{t_0} \cdot \frac{\pi}{2}\right)\right)\right] \quad (3.68)$$

donde G es la irradiancia (W/m^2) en la hora t , G_{max} es el valor máximo de irradiancia (W/m^2) durante el día en cuestión, y s es el factor de forma definido por:

$$s = \frac{d \cdot \frac{\pi}{2} - 1}{1 - \frac{\pi}{4}} \quad (3.69)$$

siendo d el factor de conjunto de datos calculado con:

$$d = \frac{G_d}{G_{max} \cdot h} \quad (3.70)$$

3.4. Sombras y ocupación de terreno

Al diseñar una central fotovoltaica se debe decidir la ubicación de las diferentes partes del generador resolviendo un compromiso entre la mejor ocupación del terreno disponible y la minimización del impacto de sombras mutuas arrojadas entre los módulos.

Este factor de sombras implica un nivel de ocupación de terreno que depende del modo de seguimiento del generador. La ocupación del terreno se puede medir con dos métricas:

- Relación de ocupación del terreno (*Ground Coverage Ratio*, GCR): es la relación entre el área del generador, A_G , y el área del terreno ocupado, A_T (por tanto, siempre será $GCR < 1$).

$$GCR = \frac{A_G}{A_T} \quad (3.71)$$

- Ratio de ocupación del terreno (ROT , o *Ground Requirement Ratio*, GRR): es el inverso del GCR , la relación entre el área de terreno ocupado, A_T , y el área del generador, A_G .

$$ROT = \frac{A_T}{A_G} \quad (3.72)$$

3.4.1. Sistemas estáticos

Las filas que componen el generador arrojan sombras unas sobre otras en determinados momentos del día y año. Como recomendación general, es de uso común respetar un mínimo de 4 horas de sol en torno al mediodía del solsticio de invierno libres de sombra. La longitud de la sombra de un obstáculo se mide con:

$$d = \frac{h}{\tan \gamma_s} \quad (3.73)$$

siendo h la altura de la fila adyacente, $h = L \cdot \sin(\beta)$ y L la longitud del generador, según se indica en la figura 3.7.

En el mediodía del solsticio de invierno la altura solar es $\gamma_s = 90^\circ - 23,45^\circ - |\phi| \simeq 67^\circ - |\phi|$. Por tanto, la distancia mínima que permite 4 horas libres de sombra alrededor del mediodía es:

$$d_{min} = \frac{h}{\tan(61^\circ - |\phi|)} \quad (3.74)$$

3.4.2. Sistemas de seguimiento a doble eje

El diseño de un sistema de seguimiento solar a doble eje busca optimizar la ubicación de los seguidores para minimizar las pérdidas de radiación por sombras, utilizando eficientemente el terreno. Para esto, se simula el sistema en diferentes configuraciones y se elige la más eficiente en términos de productividad y ROT, que se calcula con la fórmula:

$$ROT = \frac{L_{ns} \cdot L_{eo}}{L \cdot W} \quad (3.75)$$

donde (figuras 3.8 y 3.9):

- L_{ns} es la separación entre seguidores en la dirección Norte-Sur.
- L_{eo} es la separación en la dirección Este-Oeste.
- L es la longitud del seguidor.
- W es la anchura del seguidor.

El sistema se modela como un grupo de seis seguidores en una matriz de dos filas en dirección Norte-Sur (figura 3.10), representando tres situaciones de sombra: lateral (Este-Oeste), frontal




FIGURA 3.7: Dimensiones y distancias entre filas de un sistema estático.




FIGURA 3.8: Sombras mutuas en un conjunto de cuatro seguidores.




FIGURA 3.9: Dimensiones de un seguidor a doble eje y longitud de su sombra arrojada.




FIGURA 3.10: Posibles sombras en un conjunto de seis seguidores.

(Norte-Sur) y diagonal, caracterizados por los factores de sombra FS_{xx} , definidos como la relación entre el área sombreada y el área total del generador. Las ecuaciones para estos factores son, en las que se emplean los valores normalizados de las distancias, $l_{eo} = \frac{L_{eo}}{W}$ y $l_{ns} = \frac{L_{ns}}{W}$:

$$\begin{aligned} |l_{eo} \cdot \cos(\psi_s)| < 1 \\ |l_{eo} \cdot \sin(\psi_s)| < s \end{aligned} \Rightarrow FS_{eo} = \frac{(1 - |l_{eo} \cos(\psi_s)|) \cdot (s - |l_{eo} \sin(\psi_s)|)}{s} \quad (3.76)$$

$$\begin{aligned} |l_{ns} \cdot \cos(\psi_s)| < s \\ |l_{ns} \cdot \sin(\psi_s)| < 1 \end{aligned} \Rightarrow FS_{ns} = \frac{(s - |l_{ns} \cos(\psi_s)|) \cdot (1 - |l_{ns} \sin(\psi_s)|)}{s} \quad (3.77)$$

$$\begin{aligned} s &> |l_{ns} \cdot \cos(\psi_s)| + |l_{eo} \sin(\psi_s)| \\ 1 &> |l_{eo} \cdot \cos(\psi_s)| - |l_{ns} \cdot \sin(\psi_s)| \end{aligned} \Rightarrow$$

$$FS_d = \frac{[s - (|l_{eo} \cdot \sin(\psi_s)| + |l_{ns} \cos(\psi_s)|)] \cdot [1 - (|l_{eo} \cdot \cos(\psi_s)| - |l_{ns} \sin(\psi_s)|)]}{s} \quad (3.78)$$

siendo ψ_s el acimut solar y γ_s la altura solar y donde la longitud de sombra (normalizada con la anchura del seguidor) se calcula con:

$$s = s_1 + s_2 \quad (3.79)$$

$$s_1 = b \cdot \cos(\beta) \quad (3.80)$$

$$s_2 = \frac{b \cdot \sin(\beta)}{|\tan(\gamma_s)|} \quad (3.81)$$

El factor $\frac{\sin(\gamma_s)}{\sin(\gamma_s + \beta)}$ representa la proyección de sombra existente en el suelo sobre el plano del generador, y por tanto, el porcentaje de área sombreada que debe ser eliminado de la radiación directa. Desarrollando este factor se obtiene una formulación alternativa que puede facilitar el cálculo de los tres factores:

$$FS_{eo} = \frac{(1 - l_{eo} \cos(\psi_s)) \cdot (s - l_{eo} \sin(\psi_s))}{s} \quad (3.82)$$

$$FS_{ns} = \frac{(s - l_{ns} \cos(\psi_s)) \cdot (1 - l_{ns} \sin(\psi_s))}{s} \quad (3.83)$$

$$FS_d = \frac{[s - (l_{eo} \cdot \sin(\psi_s) + l_{ns} \cos(\psi_s))] \cdot [1 - (l_{eo} \cdot \cos(\psi_s) - l_{ns} \sin(\psi_s))]}{s} \quad (3.84)$$

Realizando la simulación de este sistema incluyendo el cálculo de sombras, y repitiendo la simulación para varias combinaciones (Lns, Leo) pueden elaborarse gráficos de nivel como el de la figura 3.11, donde se recoge el ratio entre la energía anual producida por un seguidor *promedio* incluyendo el efecto de por sombras mutuas⁵ y la energía anual producida por un seguidor sin sombreado.

3.4.3. Sistemas de seguimiento de eje horizontal

Se considera que los seguidores son de longitud infinita en sentido Norte-Sur (se desprecia el efecto de borde). Así, los parámetros que determinan el diseño de este tipo de sistema son (figura 3.12):

1. La inclinación del generador fotovoltaico, β , (coincidente con el ángulo ψ_{ns}).

⁵En el cálculo de la producción del seguidor afectado por sombras mutuas se considera que la reducción en potencia está exclusivamente relacionada con el área sombreada, por tanto, no se tienen en cuenta las conexiones eléctricas entre módulos.




FIGURA 3.11: Ábaco para planta de seguimiento a doble eje. Recoge el ratio entre la energía anual producida por un seguidor afectado por sombras mutuas (E_{acs}) y la producida por un seguidor sin sombreado (E_{ac0}). Las curvas de color negro representan la fracción de energía no afectada por sombras. Las curvas de puntos representan el valor del ROT.




FIGURA 3.12: Dimensiones básicas en sistemas con seguidores de eje horizontal.

2. La dimensión en sentido Este-Oeste del campo generador, L .
3. La separación entre los diferente seguidores en la dirección Este-Oeste, L_{eo} . Por tanto, $ROT = \frac{L_{eo}}{L}$.

Para caracterizar numéricamente el sombreado, se empleará el factor FS_{eo} . Mediante consideraciones geométricas, utilizando la distancia normalizada $l_{eo} = \frac{L_{eo}}{L}$, es posible escribir:

$$\begin{aligned}
 FS_{eo} &= \frac{s - l_{eo}}{s} \\
 &= 1 - l_{eo} \cdot \cos(\beta) \\
 &= 1 - l_{eo} \cdot \frac{\sin(\omega)}{\sqrt{\sin^2(\omega) + (\cos(\omega) \cos(\phi) + \tan(\delta) \sin(\phi))^2}}
 \end{aligned} \tag{3.85}$$

Limitación de ángulo y retroseguimeitno

En seguidores de eje horizontal se puede evitar la incidencia de sombras en cualquier en cualquier instante mediante algoritmos de *backtracking* o retroseguimiento [Pan+91]. Esta técnica provoca el desvío del seguidor de su posición óptima en los instantes en los que se produce la sombra entre seguidores, evitando el impacto de sombras pero con la consiguiente reducción en energía producida pro alejamiento del apuntamiento óptimo.

Para evitar la aparición de sombras, el ángulo de inclinación de los seguidores debe ser tal que la longitud de la sombra sea igual a la distancia entre seguidores. Siendo, β el ángulo de inclinación con retroseguimiento, y, β_0 el ángulo de inclinación original, de la ecuación 3.85 se deduce que sólo será necesario aplicar esta técnica cuando $l_{eo} \cdot \cos(\beta_0) \leq 1$. El triángulo definido por el rayo solar, el seguidro y la sombra debe cumplir la siguiente condición, basada en el teorema de los senos:

$$\frac{l_{eo}}{\cos(\beta_0 - \beta)} = \frac{1}{\cos \beta_0} \tag{3.86}$$

Por tanto, el ángulo de inclinación que grantiza la ausencia de sombras a costa de apartarse de la condición de seguimiento es:

$$\beta = \beta_0 - \arccos(l_{eo} \cdot \cos \beta_0) \tag{3.87}$$

ecuación que debe aplicarse sólo cuando $l_{eo} \cdot \cos(\beta_0) \leq 1$. En caso contrario $\beta = \beta_0$.

Desarrollo del código

En la figura 4.1, se muestra el proceso de cálculo que sigue el paquete a la hora de obtener la estimación de la producción del sistema fotovoltaico. A la hora de estimar la producción, el programa sigue los siguientes procesos:

4.1. Geometría solar

Para calcular la geometría que definen las posiciones de la Tierra y el Sol, **solaR2** se vale de una función constructora, **calcSol** [??], la cual mediante las funciones **fSolD** [??] y **fSolI** [??] calcula todos los ángulos y componentes que caracterizan la geometría solar.

Como se puede ver en la figura 4.2, **calcSol** funciona gracias a las siguientes funciones:

- **fSolD**: la cual, a partir de la latitud (ϕ), calcula la geometría a nivel diario, es decir, los ángulos y componentes que se pueden calcular en cada día independiente.

Estas son:

- Declinación (δ): calculada a partir de la función **declination**¹.
- Excentricidad (ϵ_o): obtenida mediante la función **eccentricity**.
- Ecuación del tiempo (EoT): obtenida mediante la función **eot**.
- Ángulo del amanecer (ω_s): calculada a partir de la función **sunrise**.
- Irradiancia diaria extra-atmosférica ($B_{0d}(0)$): obtenida a partir de la función **bo0d**.

```
1 lat <- 37.2
2 BTd <- fBTd(mode = 'prom')
3 sold <- fSolD(lat = lat, BTd = BTd)
4 show(sold)
```

Key:	<Dates>	lat	decl	eo	EoT	ws	Bo0d
	<IDat>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024-01-17	37.2	-0.36271754	1.0340422	-0.0455346238	-1.278593	4738.993
2:	2024-02-14	37.2	-0.22850166	1.0259717	-0.0614793356	-1.393341	6137.388

¹Todas las funciones mencionadas en este punto, se encuentran en el apartado ??.




FIGURA 4.1: Proceso de cálculo de las funciones de *solar2*




FIGURA 4.2: Cálculo de la geometría solar mediante la función `calcSol`, la cual unifica las funciones `fSolD` y `fSolI` resultando en un objeto clase `Sol` el cual contiene toda la información geométrica necesaria para realizar las siguientes estimaciones.

3:	2024-03-15	37.2	-0.03191616	1.0107943	-0.0368674274	-1.546560	8086.323
4:	2024-04-15	37.2	0.17531794	0.9926547	0.0017482721	-1.705659	9921.357
5:	2024-05-15	37.2	0.33246485	0.9775162	0.0143055938	-1.835976	11115.619
6:	2024-06-10	37.2	0.40257826	0.9691480	-0.0007378952	-1.899934	11573.907
7:	2024-07-18	37.2	0.36439367	0.9675489	-0.0263454380	-1.864521	11257.133
8:	2024-08-18	37.2	0.22407398	0.9758022	-0.0111761118	-1.744657	10183.208
9:	2024-09-18	37.2	0.02730595	0.9907919	0.0342189964	-1.591529	8508.642
10:	2024-10-19	37.2	-0.17900474	1.0088406	0.0689613044	-1.433019	6554.218
11:	2024-11-18	37.2	-0.33862399	1.0245012	0.0575423573	-1.300179	4951.750
12:	2024-12-13	37.2	-0.40478283	1.0328516	0.0158622941	-1.239567	4284.472

Además, **fSold** permite seleccionar el método de cálculo entre los propuestos por 4 autores diferentes (**cooper** [Coo69], **spencer** [Spe71], **strous** [Str11], **michalsky** [Mic88]) (el valor por defecto es **michalsky**):

```
1 sold_cooper <- fSold(lat = lat, BTd = BTd, method = 'cooper')
2 show(sold_cooper)
```

Key: <Dates>							
	Dates	lat	decl	eo	EoT	ws	BoOd
	<IDat>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024-01-17	37.2	-0.36506987	1.0315970	-0.0455346238	-1.276457	4702.617
2:	2024-02-14	37.2	-0.23770977	1.0235842	-0.0614793356	-1.385835	6024.833
3:	2024-03-15	37.2	-0.04219743	1.0091112	-0.0368674274	-1.538742	7968.679
4:	2024-04-15	37.2	0.17074888	0.9917107	0.0017482721	-1.702053	9870.335
5:	2024-05-15	37.2	0.33214647	0.9770196	0.0143055938	-1.835696	11107.378
6:	2024-06-10	37.2	0.40292516	0.9690335	-0.0007378952	-1.900263	11575.213
7:	2024-07-18	37.2	0.36346384	0.9684861	-0.0263454380	-1.863677	11260.684
8:	2024-08-18	37.2	0.21721704	0.9778484	-0.0111761118	-1.739110	10144.635
9:	2024-09-18	37.2	0.01056696	0.9933706	0.0342189964	-1.578817	8367.014
10:	2024-10-19	37.2	-0.19902155	1.0107363	0.0689613044	-1.417100	6356.454
11:	2024-11-18	37.2	-0.34965673	1.0247443	0.0575423573	-1.290358	4835.353
12:	2024-12-13	37.2	-0.40651987	1.0315970	0.0158622941	-1.237915	4260.830

```
1 sold_spencer <- fSold(lat = lat, BTd = BTd, method = 'spencer')
2 show(sold_spencer)
```

Key: <Dates>							
	Dates	lat	decl	eo	EoT	ws	BoOd
	<IDat>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024-01-17	37.2	-0.36483670	1.0340422	-0.0455346238	-1.276669	4716.264
2:	2024-02-14	37.2	-0.23199205	1.0259717	-0.0614793356	-1.390501	6100.057
3:	2024-03-15	37.2	-0.03563921	1.0107943	-0.0368674274	-1.543730	8048.574
4:	2024-04-15	37.2	0.17171286	0.9926547	0.0017482721	-1.702813	9888.522
5:	2024-05-15	37.2	0.33007088	0.9775162	0.0143055938	-1.833871	11096.093
6:	2024-06-10	37.2	0.40208757	0.9691480	-0.0007378952	-1.899469	11570.124
7:	2024-07-18	37.2	0.36657157	0.9675489	-0.0263454380	-1.866501	11274.319
8:	2024-08-18	37.2	0.22748717	0.9758022	-0.0111761118	-1.747427	10212.886
9:	2024-09-18	37.2	0.03143967	0.9907919	0.0342189964	-1.594670	8548.821
10:	2024-10-19	37.2	-0.17549393	1.0088406	0.0689613044	-1.435795	6590.939
11:	2024-11-18	37.2	-0.33679169	1.0245012	0.0575423573	-1.301800	4971.285
12:	2024-12-13	37.2	-0.40419949	1.0328516	0.0158622941	-1.240121	4290.674

```
1 sold_strous <- fSold(lat = lat, BTd = BTd, method = 'cooper')
2 show(sold_strous)
```

Key: <Dates>							
	Dates	lat	decl	eo	EoT	ws	BoOd
	<IDat>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024-01-17	37.2	-0.36506987	1.0315970	-0.0455346238	-1.276457	4702.617
2:	2024-02-14	37.2	-0.23770977	1.0235842	-0.0614793356	-1.385835	6024.833
3:	2024-03-15	37.2	-0.04219743	1.0091112	-0.0368674274	-1.538742	7968.679
4:	2024-04-15	37.2	0.17074888	0.9917107	0.0017482721	-1.702053	9870.335
5:	2024-05-15	37.2	0.33214647	0.9770196	0.0143055938	-1.835696	11107.378
6:	2024-06-10	37.2	0.40292516	0.9690335	-0.0007378952	-1.900263	11575.213
7:	2024-07-18	37.2	0.36346384	0.9684861	-0.0263454380	-1.863677	11260.684
8:	2024-08-18	37.2	0.21721704	0.9778484	-0.0111761118	-1.739110	10144.635
9:	2024-09-18	37.2	0.01056696	0.9933706	0.0342189964	-1.578817	8367.014
10:	2024-10-19	37.2	-0.19902155	1.0107363	0.0689613044	-1.417100	6356.454
11:	2024-11-18	37.2	-0.34965673	1.0247443	0.0575423573	-1.290358	4835.353
12:	2024-12-13	37.2	-0.40651987	1.0315970	0.0158622941	-1.237915	4260.830

- **fSolI**: toma los resultados obtenidos en **fSold** y calcula la geometría a nivel intradiario, es decir, aquella que se puede calcular en unidades de tiempo menores a los días. Estas son:

- La hora solar o tiempo solar verdadero (ω): calculada a partir de la función **sunHour**.
- Los momentos del día en los que es de noche (*night*): calculada a partir del resultado anterior y de el ángulo del amanecer (calculada en **fSold**)².
- El coseno del ángulo cenital solar ($\cos(\theta_{zs})$): obtenida a partir de la función **zenith**.
- La altura solar (γ_s): obtenida a partir del resultado anterior³.
- El ángulo acimutal solar (θ_{zs}): calculada mediante la función **azimuth**.
- La irradiancia extra-atmosférica ($B_0(0)$): calculada mediante el coseno del ángulo cenital, la constante solar (B_0) y la excentricidad (calculada en **fSold**) [ecuación 3.2].

```

1  soli <- fSolI(sold = sold[1], sample = 'hour') #Computo solo un día a fin
    mejorar la visualización
2  show(soli)

```

Index: <night>								
	Dates	lat	w	night	cosThzS	AlS	AzS	BoO
	<POSc>	<num>	<num>	<lgcl>	<num>	<num>	<num>	<num>
1:	2024-01-17 00:00:00	37.2	3.09905026	TRUE	-0.958552332	-1.281876984	3.00157749	0.00000
2:	2024-01-17 01:00:00	37.2	-2.92239722	TRUE	-0.941407376	-1.226779122	-2.49462689	0.00000
3:	2024-01-17 02:00:00	37.2	-2.66065932	TRUE	-0.874749489	-1.064918604	-2.03862388	0.00000
4:	2024-01-17 03:00:00	37.2	-2.39892132	TRUE	-0.763119126	-0.868125900	-1.77932134	0.00000
5:	2024-01-17 04:00:00	37.2	-2.13718324	TRUE	-0.614120126	-0.661270606	-1.59701536	0.00000
6:	2024-01-17 05:00:00	37.2	-1.87544507	TRUE	-0.437901763	-0.453263434	-1.44469585	0.00000
7:	2024-01-17 06:00:00	37.2	-1.61370681	TRUE	-0.246467423	-0.249033534	-1.30093496	0.00000
8:	2024-01-17 07:00:00	37.2	-1.35196846	TRUE	-0.052856976	-0.052881619	-1.15283370	0.00000
9:	2024-01-17 08:00:00	37.2	-1.09023003	FALSE	0.129741461	0.130108233	-0.99014548	183.39419
10:	2024-01-17 09:00:00	37.2	-0.82849151	FALSE	0.288889848	0.293067041	-0.80329847	408.35612
11:	2024-01-17 10:00:00	37.2	-0.56675290	FALSE	0.413747472	0.426566560	-0.58400587	584.84684
12:	2024-01-17 11:00:00	37.2	-0.30501420	FALSE	0.495809380	0.518766586	-0.32921922	700.84427
13:	2024-01-17 12:00:00	37.2	-0.04327541	FALSE	0.529485721	0.557994217	-0.04769723	748.44699
14:	2024-01-17 13:00:00	37.2	0.21846346	FALSE	0.512482515	0.538073327	0.23821864	724.41235
15:	2024-01-17 14:00:00	37.2	0.48020243	FALSE	0.445957919	0.462244212	0.50355560	630.37745
16:	2024-01-17 15:00:00	37.2	0.74194148	FALSE	0.334443348	0.341014503	0.73469016	472.74762

²Cuando la hora solar verdadera excede los ángulos en los que amanecer y anochece ($|\omega| \geq |\omega_s|$), el Sol queda por debajo de la línea del horizonte, por lo que es de noche.

³ $\gamma_s = \arcsin(\cos(\theta_s))$.

17:	2024-01-17 16:00:00	37.2	1.00368062	FALSE	0.185534810	0.186616094	0.93148844	262.26008
18:	2024-01-17 17:00:00	37.2	1.26541985	FALSE	0.009375501	0.009375638	1.10112996	13.25261
19:	2024-01-17 18:00:00	37.2	1.52715917	TRUE	-0.182035120	-0.183055757	1.25297092	0.00000
20:	2024-01-17 19:00:00	37.2	1.78889857	TRUE	-0.375658695	-0.385107424	1.39694027	0.00000
21:	2024-01-17 20:00:00	37.2	2.05063807	TRUE	-0.558306105	-0.592342658	1.54466726	0.00000
22:	2024-01-17 21:00:00	37.2	2.31237766	TRUE	-0.717535874	-0.800258081	1.71368519	0.00000
23:	2024-01-17 22:00:00	37.2	2.57411733	TRUE	-0.842501657	-1.001910427	1.93928567	0.00000
24:	2024-01-17 23:00:00	37.2	2.83585709	TRUE	-0.924691065	-1.180223341	2.30977400	0.00000
	Dates	lat	w	night	cosThzS	AlS	AzS	Bo0

Además, como los datos nocturnos aportan poco a los cálculos que atañen a este proyecto, **fSolI** presenta la posibilidad de eliminar estos datos con el argumento **keep.night**.

```
1 solI_nigth <- fSolI(sold = sold[1], sample = 'hour', keep.night = FALSE)
2 show(solI_nigth)
```

	Dates	lat	w	night	cosThzS	AlS	AzS	Bo0
	<POS>	<num>	<num>	<lgcl>	<num>	<num>	<num>	<num>
1:	2024-01-17 08:00:00	37.2	-1.09023003	FALSE	0.129741461	0.130108233	-0.99014548	183.39419
2:	2024-01-17 09:00:00	37.2	-0.82849151	FALSE	0.288889848	0.293067041	-0.80329847	408.35612
3:	2024-01-17 10:00:00	37.2	-0.56675290	FALSE	0.413747472	0.426566560	-0.58400587	584.84684
4:	2024-01-17 11:00:00	37.2	-0.30501420	FALSE	0.495809380	0.518766586	-0.32921922	700.84427
5:	2024-01-17 12:00:00	37.2	-0.04327541	FALSE	0.529485721	0.557994217	-0.04769723	748.44699
6:	2024-01-17 13:00:00	37.2	0.21846346	FALSE	0.512482515	0.538073327	0.23821864	724.41235
7:	2024-01-17 14:00:00	37.2	0.48020243	FALSE	0.445957919	0.462244212	0.50355560	630.37745
8:	2024-01-17 15:00:00	37.2	0.74194148	FALSE	0.334443348	0.341014503	0.73469016	472.74762
9:	2024-01-17 16:00:00	37.2	1.00368062	FALSE	0.185534810	0.186616094	0.93148844	262.26008
10:	2024-01-17 17:00:00	37.2	1.26541985	FALSE	0.009375501	0.009375638	1.10112996	13.25261

Aparte, en vez de identificar el intervalo intradiario (con el argumento **sample**), se puede dar directamente la base temporal intradiaria.

```
1 BTi <- fBTi(BTd, sample = 'hour')
2 solI_BTi <- fSolI(sold, BTi = BTi)
3 show(solI_BTi)
```

Index: <night>	Dates	lat	w	night	cosThzS	AlS	AzS	Bo0
	<POS>	<num>	<num>	<lgcl>	<num>	<num>	<num>	<num>
1:	2024-01-17 00:00:00	37.2	3.099050	TRUE	-0.9585523	-1.2818770	3.001577	0
2:	2024-01-17 01:00:00	37.2	-2.922397	TRUE	-0.9414074	-1.2267791	-2.494627	0
3:	2024-01-17 02:00:00	37.2	-2.660659	TRUE	-0.8747495	-1.0649186	-2.038624	0
4:	2024-01-17 03:00:00	37.2	-2.398921	TRUE	-0.7631191	-0.8681259	-1.779321	0
5:	2024-01-17 04:00:00	37.2	-2.137183	TRUE	-0.6141201	-0.6612706	-1.597015	0

284:	2024-12-13 19:00:00	37.2	1.856445	TRUE	-0.4444110	-0.4605166	1.394524	0
285:	2024-12-13 20:00:00	37.2	2.118158	TRUE	-0.6191456	-0.6676542	1.539641	0
286:	2024-12-13 21:00:00	37.2	2.379871	TRUE	-0.7679298	-0.8756029	1.709361	0
287:	2024-12-13 22:00:00	37.2	2.641583	TRUE	-0.8806309	-1.0771921	1.946876	0
288:	2024-12-13 23:00:00	37.2	2.903296	TRUE	-0.9495736	-1.2518732	2.377338	0

También, se puede indicar que no realice las correcciones de la ecuación del tiempo.

```
1 solI_EoT <- fSolI(sold = sold, BTi = BTi, EoT = FALSE)
2 show(solI_EoT)
```

```

Index: <night>
      Dates      lat      w      night      cosThzS      ALS      AzS      BoO
      <POS< <num>      <num> <lgcl>      <num>      <num>      <num> <num>
1: 2024-01-17 00:00:00 37.2 3.099050 TRUE -0.9585523 -1.2818770 3.001577 0
2: 2024-01-17 01:00:00 37.2 -2.922397 TRUE -0.9414074 -1.2267791 -2.494627 0
3: 2024-01-17 02:00:00 37.2 -2.660659 TRUE -0.8747495 -1.0649186 -2.038624 0
4: 2024-01-17 03:00:00 37.2 -2.398921 TRUE -0.7631191 -0.8681259 -1.779321 0
5: 2024-01-17 04:00:00 37.2 -2.137183 TRUE -0.6141201 -0.6612706 -1.597015 0
---
284: 2024-12-13 19:00:00 37.2 1.856445 TRUE -0.4444110 -0.4605166 1.394524 0
285: 2024-12-13 20:00:00 37.2 2.118158 TRUE -0.6191456 -0.6676542 1.539641 0
286: 2024-12-13 21:00:00 37.2 2.379871 TRUE -0.7679298 -0.8756029 1.709361 0
287: 2024-12-13 22:00:00 37.2 2.641583 TRUE -0.8806309 -1.0771921 1.946876 0
288: 2024-12-13 23:00:00 37.2 2.903296 TRUE -0.9495736 -1.2518732 2.377338 0

```

Finalmente, estas dos funciones, como se muestra en la figura 4.2, convergen en la función **calcSol**, dando como resultado un objeto de clase **Sol**. Este objeto muestra un resumen de ambos elementos junto con la latitud de los cálculos.

```

1 sol <- calcSol(lat = lat, BTd = BTd, sample = 'hour')
2 show(sol)

```

Object of class Sol

Latitude: 37.2 degrees

Daily values:

Dates	decl	eo	EoT	ws
Min. :2024-01-17	Min. : -0.404783	Min. :0.9675	Min. : -0.0614793	Min. : -1.900
1st Qu.:2024-04-07	1st Qu.: -0.256032	1st Qu.:0.9771	1st Qu.: -0.0289759	1st Qu.: -1.767
Median :2024-06-29	Median : -0.002305	Median :1.0007	Median : 0.0005052	Median : -1.569
Mean :2024-07-01	Mean : -0.001618	Mean :1.0009	Mean : 0.0008748	Mean : -1.569
3rd Qu.:2024-09-25	3rd Qu.: 0.251172	3rd Qu.:1.0249	3rd Qu.: 0.0204515	3rd Qu.: -1.370
Max. :2024-12-13	Max. : 0.402578	Max. :1.0340	Max. : 0.0689613	Max. : -1.240

BoOd

Min. : 4284
1st Qu.: 5841
Median : 8297
Mean : 8109
3rd Qu.:10416
Max. :11574

Intradaily values:

Dates	w	night	cosThzS
Min. :2024-01-17 00:00:00	Min. : -3.1393050	Mode :logical	Min. : -0.9700256
1st Qu.:2024-04-07 11:45:00	1st Qu.: -1.5692285	FALSE:145	1st Qu.: -0.5004531
Median :2024-06-29 11:30:00	Median : 0.0010871	TRUE :143	Median : 0.0062923
Mean :2024-07-01 15:30:00	Mean : 0.0009975		Mean : -0.0009523
3rd Qu.:2024-09-26 11:15:00	3rd Qu.: 1.5716412		3rd Qu.: 0.5007129
Max. :2024-12-13 23:00:00	Max. : 3.1413972		Max. : 0.9697262

ALS	AzS	BoO
Min. : -1.325336	Min. : -3.139169	Min. : 0.000
1st Qu.: -0.524130	1st Qu.: -1.570722	1st Qu.: 0.000
Median : 0.006292	Median : 0.003834	Median : 8.748
Mean : -0.001202	Mean : 0.001011	Mean : 337.752
3rd Qu.: 0.524433	3rd Qu.: 1.555342	3rd Qu.: 698.153
Max. : 1.324107	Max. : 3.141331	Max. :1284.718

4.2. Datos meteorológicos

Para el procesamiento de datos meteorológicos, **solar2** provee una serie de funciones⁴ que son capaces de leer todo tipo de datos. Estos datos se procesan y se almacenan en un objeto de tipo **Meteo** tal y como se ve en la figura 4.3. Estas funciones son:

- **readG0dm**: Esta función construye un objeto **Meteo** a partir de 12 valores de medias mensuales de irradiación.

```
1 G0dm = c(2.766,3.491,4.494,5.912,6.989,7.742,
2         7.919,7.027,5.369,3.562,2.814,2.179) * 1000;
3 Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2,
4        28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
5 BD <- readG0dm(G0dm = G0dm, Ta = Ta, lat = 37.2)
6 show(BD)
```

```
Object of class Meteo

Source of meteorological information: prom-
Latitude of source: 37.2 degrees

Meteorological Data:
  Dates      G0d      Ta
Min. :2024-01-17 Min. :2179 Min. :10.00
1st Qu.:2024-04-07 1st Qu.:3322 1st Qu.:15.50
Median :2024-06-29 Median :4932 Median :17.70
Mean   :2024-07-01 Mean   :5022 Mean   :19.22
3rd Qu.:2024-09-25 3rd Qu.:6998 3rd Qu.:21.98
Max.   :2024-12-13 Max.   :7919 Max.   :29.90
```

- **readBD**: Esta familia de funciones puede leer ficheros de datos y transformarlos en un objeto de clase **Meteo**. Se dividen en:
 - **readBDd**: Procesa datos meteorológicos de tipo diarios.

```
1 ## Se utiliza un archivo alojado en el
2 ## github del tutor de este proyecto
3 myURL <- "https://raw.githubusercontent.com/oscarperpinan/R/master/data/
   aranquez.csv"
```




FIGURA 4.3: Los datos meteorológicos se pueden leer mediante las funciones **readG0dm**, **readBD**, **dt2Meteo**, **zoo2Meteo** y **readSIAR** las cuales procesan estos datos y los almacenan en un objeto de clase **Meteo**.

⁴Las funciones comentadas en este apartado, se recogen en la sección ??

```

4 download.file(myURL, 'data/aranjuez.csv', quiet = TRUE)
5 Bdd <- readBdd(file = 'data/aranjuez.csv', lat = lat,
6               format = '%Y-%m-%d', header = TRUE,
7               fill = TRUE, dec = '.', sep = ',', dates.col = '',
8               ta.col = 'TempAvg', g0.col = 'Radiation', keep.cols = TRUE)
9 show(Bdd)

```

Object of class Meteo

Source of meteorological information: bd-data/aranjuez.csv

Latitude of source: 37.2 degrees

Meteorological Data:

Dates	G0	Ta	TempMin	TempMax	
Min. :2004-01-01	Min. : 0.277	Min. :-5.309	Min. :-12.980	Min. :-2.362	
1st Qu.:2005-12-29	1st Qu.: 9.370	1st Qu.: 7.692	1st Qu.: 1.515	1st Qu.:14.530	
Median :2008-01-09	Median :16.660	Median :13.810	Median : 7.170	Median :21.670	
Mean :2008-01-03	Mean :16.742	Mean :14.405	Mean : 6.888	Mean :22.531	
3rd Qu.:2010-01-02	3rd Qu.:24.650	3rd Qu.:21.615	3rd Qu.: 12.590	3rd Qu.:30.875	
Max. :2011-12-31	Max. :32.740	Max. :30.680	Max. : 22.710	Max. :41.910	
	NA's :13		NA's :4		
HumidAvg	HumidMax	WindAvg	WindMax	Rain	ET
Min. : 19.89	Min. : 35.88	Min. :0.251	Min. : 0.000	Min. : 0.000	Min. :0.000
1st Qu.: 47.04	1st Qu.: 81.60	1st Qu.:0.667	1st Qu.: 3.783	1st Qu.: 0.000	1st Qu.:1.168
Median : 62.58	Median : 90.90	Median :0.920	Median : 5.027	Median : 0.000	Median :2.758
Mean : 62.16	Mean : 87.22	Mean :1.174	Mean : 5.208	Mean : 1.094	Mean :3.091
3rd Qu.: 77.38	3rd Qu.: 94.90	3rd Qu.:1.431	3rd Qu.: 6.537	3rd Qu.: 0.200	3rd Qu.:4.926
Max. :100.00	Max. :100.00	Max. :8.260	Max. :10.000	Max. :49.730	Max. :8.564
	NA's :13	NA's :8	NA's :128	NA's :4	NA's :18

- **readBDi**: Procesa datos meteorológicos de tipo intradiarios.

```

1 myURL <- "https://raw.githubusercontent.com/oscarperpinan/R/master/data/
  NREL-Hawaii.csv"
2 download.file(myURL, 'data/NREL-Hawaii.csv', quiet = TRUE)
3 BDi <- readBDi(file = 'data/NREL-Hawaii.csv', lat = 19,
4               format = "%d/%m/%Y %H:%M", header = TRUE,
5               fill = TRUE, dec = '.', sep = ',',
6               dates.col = 'DATE', times.col = 'HST',
7               ta.col = 'Air Temperature [deg C]',
8               g0.col = 'Global Horizontal [W/m^2]',
9               keep.cols = TRUE)
10 show(BDi)

```

Object of class Meteo

Source of meteorological information: bdI-data/NREL-Hawaii.csv

Latitude of source: 19 degrees

Meteorological Data:

Dates	G0	Ta	Direct Normal [W/m^2]
Min. :2010-01-11 06:32:00.00	Min. : 0.4769	Min. :13.42	Min. : 0.0
1st Qu.:2010-03-11 17:37:45.00	1st Qu.: 147.4328	1st Qu.:22.76	1st Qu.: 0.0
Median :2010-06-11 17:32:30.00	Median : 300.6510	Median :24.15	Median :270.3
Mean :2010-06-26 11:55:22.63	Mean : 370.5293	Mean :23.64	Mean :356.6
3rd Qu.:2010-09-11 17:34:15.00	3rd Qu.: 585.7402	3rd Qu.:25.24	3rd Qu.:715.2
Max. :2010-12-11 17:46:00.00	Max. :1172.3000	Max. :28.12	Max. :943.0
NA's :4660			
Diffuse Horizontal [W/m^2]			
Min. : 0.4769			
1st Qu.: 78.4636			
Median :152.9320			
Mean :171.7706			


```
3rd Qu.:246.3193
Max.    :586.3600
```

- **dt2Meteo**: Transforma un **data.table** o **data.frame** en un objeto de clase **Meteo**.

```
1 data(helios)
2 names(helios) <- c('Dates', 'G0d', 'TempMax', 'TempMin')
3 helios_meteo <- dt2Meteo(file = helios, lat = 40, type = 'bd')
4 show(helios_meteo)
```

Object of class **Meteo**

Source of meteorological information: bd-data.frame

Latitude of source: 40 degrees

Meteorological Data:

Dates	G0d	TempMin	TempMax
Min. :2009-01-01 00:00:00.00	Min. : 325.6	Min. : -37.500	Min. : 1.41
1st Qu.:2009-04-08 12:00:00.00	1st Qu.: 2523.2	1st Qu.: 1.950	1st Qu.:14.41
Median :2009-07-07 00:00:00.00	Median : 4745.7	Median : 7.910	Median :23.16
Mean :2009-07-04 21:29:54.93	Mean : 4812.0	Mean : 5.323	Mean :22.59
3rd Qu.:2009-10-03 12:00:00.00	3rd Qu.: 7139.5	3rd Qu.: 15.105	3rd Qu.:31.06
Max. :2009-12-31 00:00:00.00	Max. :11253.9	Max. : 24.800	Max. :38.04

Ta

```
Min. : -23.049
1st Qu.: 7.008
Median : 12.055
Mean : 10.944
3rd Qu.: 19.472
Max. : 28.619
```

- **zoo2Meteo**: Transforma un objeto de clase **zoo**⁵ en un objeto de clase **Meteo**.

```
1 library(zoo)
2 bd_zoo <- read.csv.zoo('data/aranjuez.csv')
3 BD_zoo <- zoo2Meteo(file = bd_zoo, lat = 40)
4 show(BD_zoo)
```

Object of class **Meteo**

Source of meteorological information: bd-zoo-bd_zoo

Latitude of source: 40 degrees

Meteorological Data:

TempAvg	TempMax	TempMin	HumidAvg	HumidMax	WindAvg
Min. : -5.309	Min. : -2.362	Min. : -12.980	Min. : 19.89	Min. : 35.88	Min. : 0.251
1st Qu.: 7.692	1st Qu.:14.530	1st Qu.: 1.515	1st Qu.: 47.04	1st Qu.: 81.60	1st Qu.:0.667
Median :13.810	Median :21.670	Median : 7.170	Median : 62.58	Median : 90.90	Median :0.920
Mean :14.405	Mean :22.531	Mean : 6.888	Mean : 62.16	Mean : 87.22	Mean :1.174
3rd Qu.:21.615	3rd Qu.:30.875	3rd Qu.: 12.590	3rd Qu.: 77.38	3rd Qu.: 94.90	3rd Qu.:1.431
Max. :30.680	Max. :41.910	Max. : 22.710	Max. :100.00	Max. :100.00	Max. :8.260
		NA's :4		NA's :13	NA's :8

WindMax	Rain	Radiation	ET
Min. : 0.000	Min. : 0.000	Min. : 0.277	Min. :0.000

⁵Pese a que este proyecto trate de “desligarse” del paquete **zoo**, sigue siendo un paquete muy extendido. Por lo que es interesante tener una función así para que los usuarios tengan una mayor flexibilidad.

1st Qu.: 3.783	1st Qu.: 0.000	1st Qu.: 9.370	1st Qu.:1.168
Median : 5.027	Median : 0.000	Median :16.660	Median :2.758
Mean : 5.208	Mean : 1.094	Mean :16.742	Mean :3.091
3rd Qu.: 6.537	3rd Qu.: 0.200	3rd Qu.:24.650	3rd Qu.:4.926
Max. :10.000	Max. :49.730	Max. :32.740	Max. :8.564
NA's :128	NA's :4	NA's :13	NA's :18

- **readSIAR**: Esta función es capaz de extraer información de la red SIAR y transformarlo en un objeto de clase **Meteo**.

```

1 library(httr2)
2 library(jsonlite)
3 bd_SIAR <- readSIAR(Lat = 40.40596822621351, Lon = -3.70038308516172,
4                     ## Ubicación de la Escuela Técnica Superior
5                     ## de Ingeniería y Diseño Industrial (ETSIDI)
6                     inicio = '2023-09-01', final = '2024-08-01',
7                     tipo = 'Mensuales', n_est = 3)
8 show(bd_SIAR)
```

Object of class **Meteo**

Source of meteorological information: prom-https://servicio.mapama.gob.es
 -Estaciones: Center: Finca experimental(M01), Arganda(M02), San Martín de la Vega(M05)
 Latitude of source: 40.4 degrees

Meteorological Data:

Dates	G0d	Ta	TempMin	TempMax
Min. :2023-09-18 00:00:00	Min. :1860	Min. : 5.318	Min. : -4.6513	Min. :15.34
1st Qu.:2023-12-06 18:00:00	1st Qu.:2744	1st Qu.: 9.857	1st Qu.: -2.1466	1st Qu.:21.12
Median :2024-02-29 00:00:00	Median :4052	Median :14.890	Median : 0.3663	Median :31.01
Mean :2024-03-01 04:00:00	Mean :4502	Mean :15.307	Mean : 2.4225	Mean :29.41
3rd Qu.:2024-05-21 12:00:00	3rd Qu.:6549	3rd Qu.:20.047	3rd Qu.: 7.1506	3rd Qu.:35.47
Max. :2024-08-18 00:00:00	Max. :7608	Max. :27.069	Max. :12.6082	Max. :40.70

Esta función tiene dos argumentos importantes:

- **tipo**: La API SIAR⁶ permite tener 4 tipos de registros: **Mensuales**, **Semanales**, **Diarios** y **Horarios**.
- **n_est**: Con este argumento, la función es capaz de localizar el número seleccionado de estaciones más proximas a la ubicación dada, y obtener los datos individuales de cada una de ellas. Una vez obtenidos estos datos realiza una interpolación de distancia inversa ponderada (IDW) y entrega un solo resultado. Es importante añadir que la API SIAR tiene una limitación a la solicitud de registros que se le hace cada minuto, por lo que esta función cuenta con un comprobante para impedir que el usuario exceda este límite.

4.3. Radiación en el plano horizontal

Una vez se ha calculado la geometría solar (sección 4.1) y se han procesado los datos meteorológicos (sección 4.2), es necesario calcular la radiación en el plano horizontal. Para ello,

⁶La API (Interfaz de Programación de Aplicaciones) que se usa para la función **readSIAR** está proporcionada por la propia red SIAR [Min23].

solar2 cuenta con la función **calcG0** [??] la cual mediante las funciones **fCompD** [??] y **fCompI** [??] procesan los objetos de clase **Sol** y clase **Meteo** para dar un objeto de tipo **G0**.

Como se puede ver en la figura 4.4, **calcG0** funciona gracias a las siguientes funciones:

- **fCompD**: La cual calcula todas las componentes de la irradiación diaria en una superficie horizontal mediante regresiones entre los parámetros del índice de claridad y la fracción difusa. Para ello se pueden usar varias correlaciones dependiendo del tipo de datos:

- Mensuales:

```
1 lat <- 37.2
2 BTd <- fBTd(mode = 'prom')
3 sold <- fSold(lat, BTd)
4 G0d <- c
   (2.766,3.491,4.494,5.912,6.989,7.742,7.919,7.027,5.369,3.562,2.814,2.179)
   * 1000
5 compD_page <- fCompD(sol = sold, G0d = G0d, corr = "Page")
6 compD_page
```

Key: <Dates>						
Dates	Fd	Kt	G0d	D0d	B0d	
<POS>	<num>	<num>	<num>	<num>	<num>	<num>
1: 2024-01-17	0.3404548	0.5836683	2766	941.698	1824.302	
2: 2024-02-14	0.3572461	0.5688088	3491	1247.146	2243.854	
3: 2024-03-15	0.3719989	0.5557532	4494	1671.763	2822.237	
4: 2024-04-15	0.3266485	0.5958862	5912	1931.146	3980.854	
5: 2024-05-15	0.2895069	0.6287549	6989	2023.364	4965.636	
6: 2024-06-10	0.2441221	0.6689185	7742	1889.994	5852.006	
7: 2024-07-18	0.2050844	0.7034651	7919	1624.064	6294.936	
8: 2024-08-18	0.2202349	0.6900576	7027	1547.591	5479.409	
9: 2024-09-18	0.2869638	0.6310055	5369	1540.708	3828.292	
10: 2024-10-19	0.3858825	0.5434669	3562	1374.513	2187.487	
11: 2024-11-18	0.3578392	0.5682839	2814	1006.959	1807.041	
12: 2024-12-13	0.4253038	0.5085807	2179	926.737	1252.263	

```
1 compD_lj <- fCompD(sol = sold, G0d = G0d, corr = "LJ")
2 compD_lj
```

Key: <Dates>						
Dates	Fd	Kt	G0d	D0d	B0d	
<POS>	<num>	<num>	<num>	<num>	<num>	<num>
1: 2024-01-17	0.3058193	0.5836683	2766	845.8961	1920.104	




FIGURA 4.4: Cálculo de la radiación incidente en el plano horizontal mediante la función **calcG0**, la cual procesa un objeto clase **Sol** y otro clase **Meteo** mediante las funciones **fCompD** y **fCompI** resultando en un objeto clase **G0**.

4. DESARROLLO DEL CÓDIGO

```
2: 2024-02-14 0.3169470 0.5688088 3491 1106.4621 2384.538
3: 2024-03-15 0.3268047 0.5557532 4494 1468.6603 3025.340
4: 2024-04-15 0.2967018 0.5958862 5912 1754.1011 4157.899
5: 2024-05-15 0.2720419 0.6287549 6989 1901.3006 5087.699
6: 2024-06-10 0.2408700 0.6689185 7742 1864.8154 5877.185
7: 2024-07-18 0.2152460 0.7034651 7919 1704.5331 6214.467
8: 2024-08-18 0.2236251 0.6900576 7027 1571.4138 5455.586
9: 2024-09-18 0.2703347 0.6310055 5369 1451.4268 3917.573
10: 2024-10-19 0.3361895 0.5434669 3562 1197.5071 2364.493
11: 2024-11-18 0.3173415 0.5682839 2814 892.9990 1921.001
12: 2024-12-13 0.3637158 0.5085807 2179 792.5367 1386.463
```

- Diarios:

```
1 G0d <- readSIAR(Lat = 40.40596822621351, Lon = -3.70038308516172,
2                   inicio = '2024-07-15', final = '2024-08-01',
3                   tipo = 'Diarios', n_est = 3)
4 sol <- calcSol(lat, BTd = indexD(G0d))
5 compD_cpr <- fCompD(sol = sol, G0d = G0d, corr = "CPR")
6 compD_cpr
```

```
Key: <Dates>
      Dates      Fd      Kt      G0d      D0d      B0d
  <POS< <num> <num> <num> <num> <num>
1: 2024-07-15 0.2833125 0.6798139 7697.945 2180.924 5517.021
2: 2024-07-16 0.2597185 0.7000272 7911.858 2054.856 5857.002
3: 2024-07-17 0.2815044 0.6812283 7684.293 2163.163 5521.131
4: 2024-07-18 0.6627754 0.4674993 5262.702 3487.989 1774.713
5: 2024-07-19 0.2595844 0.7001561 7865.166 2041.675 5823.491
6: 2024-07-20 0.2594075 0.7003266 7849.961 2036.339 5813.622
7: 2024-07-21 0.2315068 0.7365959 8237.938 1907.138 6330.799
8: 2024-07-22 0.2269337 0.7493438 8361.056 1897.406 6463.650
9: 2024-07-23 0.2451723 0.7156288 7965.753 1952.982 6012.771
10: 2024-07-24 0.2620008 0.6978638 7748.845 2030.204 5718.641
11: 2024-07-25 0.2746548 0.6867564 7606.140 2089.063 5517.077
12: 2024-07-26 0.3320728 0.6462270 7138.548 2370.518 4768.030
13: 2024-07-27 0.3186769 0.6547900 7213.697 2298.839 4914.858
14: 2024-07-28 0.2767163 0.6850625 7526.355 2082.665 5443.689
15: 2024-07-29 0.6566999 0.4709412 5159.260 3388.086 1771.174
16: 2024-07-30 0.3185533 0.6548709 7153.359 2278.726 4874.633
17: 2024-07-31 0.2503814 0.7096003 7728.034 1934.956 5793.078
18: 2024-08-01 0.2428514 0.7185406 7801.435 1894.589 5906.846
```

```
1 compD_ekdd <- fCompD(sol = sol, G0d = G0d, corr = 'EKDd')
2 compD_ekdd
```

```
Key: <Dates>
      Dates      Fd      Kt      G0d      D0d      B0d
  <POS< <num> <num> <num> <num> <num>
1: 2024-07-15 1 0.6798139 7697.945 7697.945 0
2: 2024-07-16 1 0.7000272 7911.858 7911.858 0
3: 2024-07-17 1 0.6812283 7684.293 7684.293 0
4: 2024-07-18 1 0.4674993 5262.702 5262.702 0
5: 2024-07-19 1 0.7001561 7865.166 7865.166 0
6: 2024-07-20 1 0.7003266 7849.961 7849.961 0
7: 2024-07-21 1 0.7365959 8237.938 8237.938 0
8: 2024-07-22 1 0.7493438 8361.056 8361.056 0
9: 2024-07-23 1 0.7156288 7965.753 7965.753 0
10: 2024-07-24 1 0.6978638 7748.845 7748.845 0
11: 2024-07-25 1 0.6867564 7606.140 7606.140 0
12: 2024-07-26 1 0.6462270 7138.548 7138.548 0
13: 2024-07-27 1 0.6547900 7213.697 7213.697 0
14: 2024-07-28 1 0.6850625 7526.355 7526.355 0
```

```

15: 2024-07-29      1 0.4709412 5159.260 5159.260      0
16: 2024-07-30      1 0.6548709 7153.359 7153.359      0
17: 2024-07-31      1 0.7096003 7728.034 7728.034      0
18: 2024-08-01      1 0.7185406 7801.435 7801.435      0

```

```

1 compD_climeddd <- fCompD(sol = sol, G0d = G0d, corr = 'CLIMEDd')
2 compD_climeddd

```

```

Key: <Dates>
      Dates      Fd      Kt      G0d      D0d      B0d
  <POS<  <num>  <num>  <num>  <num>  <num>
1: 2024-07-15 0.2724591 0.6798139 7697.945 2097.375 5600.570
2: 2024-07-16 0.2455880 0.7000272 7911.858 1943.057 5968.801
3: 2024-07-17 0.2705287 0.6812283 7684.293 2078.822 5605.472
4: 2024-07-18 0.6086148 0.4674993 5262.702 3202.958 2059.744
5: 2024-07-19 0.2454217 0.7001561 7865.166 1930.282 5934.884
6: 2024-07-20 0.2452020 0.7003266 7849.961 1924.826 5925.135
7: 2024-07-21 0.2013208 0.7365959 8237.938 1658.468 6579.470
8: 2024-07-22 0.1873678 0.7493438 8361.056 1566.592 6794.463
9: 2024-07-23 0.2259736 0.7156288 7965.753 1800.050 6165.703
10: 2024-07-24 0.2483878 0.6978638 7748.845 1924.718 5824.126
11: 2024-07-25 0.2630540 0.6867564 7606.140 2000.826 5605.314
12: 2024-07-26 0.3202837 0.6462270 7138.548 2286.361 4852.187
13: 2024-07-27 0.3077503 0.6547900 7213.697 2220.018 4993.679
14: 2024-07-28 0.2653324 0.6850625 7526.355 1996.986 5529.369
15: 2024-07-29 0.6029930 0.4709412 5159.260 3110.998 2048.263
16: 2024-07-30 0.3076331 0.6548709 7153.359 2200.610 4952.749
17: 2024-07-31 0.2334298 0.7096003 7728.034 1803.954 5924.080
18: 2024-08-01 0.2224291 0.7185406 7801.435 1735.266 6066.168

```

También, se puede aportar una función de correlación propia.

```

1 f_corrd <- function(sol, G0d){
2   ## Función CLIMEDd
3   Kt <- Ktd(sol, G0d)
4   Fd=(Kt<=0.13)*(0.952)+
5     (Kt>0.13 & Kt<=0.8)*(0.868+1.335*Kt-5.782*Kt^2+3.721*Kt^3)+
6     (Kt>0.8)*0.141
7   return(data.table(Fd, Kt))
8 }
9 compD_user <- fCompD(sol = sol, G0d = G0d, corr = 'user', f = f_corrd)
10 compD_user

```

```

Key: <Dates>
      Dates      Fd      Kt      G0d      D0d      B0d
  <POS<  <num>  <num>  <num>  <num>  <num>
1: 2024-07-15 0.2724591 0.6798139 7697.945 2097.375 5600.570
2: 2024-07-16 0.2455880 0.7000272 7911.858 1943.057 5968.801
3: 2024-07-17 0.2705287 0.6812283 7684.293 2078.822 5605.472
4: 2024-07-18 0.6086148 0.4674993 5262.702 3202.958 2059.744
5: 2024-07-19 0.2454217 0.7001561 7865.166 1930.282 5934.884
6: 2024-07-20 0.2452020 0.7003266 7849.961 1924.826 5925.135
7: 2024-07-21 0.2013208 0.7365959 8237.938 1658.468 6579.470
8: 2024-07-22 0.1873678 0.7493438 8361.056 1566.592 6794.463
9: 2024-07-23 0.2259736 0.7156288 7965.753 1800.050 6165.703
10: 2024-07-24 0.2483878 0.6978638 7748.845 1924.718 5824.126
11: 2024-07-25 0.2630540 0.6867564 7606.140 2000.826 5605.314
12: 2024-07-26 0.3202837 0.6462270 7138.548 2286.361 4852.187
13: 2024-07-27 0.3077503 0.6547900 7213.697 2220.018 4993.679
14: 2024-07-28 0.2653324 0.6850625 7526.355 1996.986 5529.369
15: 2024-07-29 0.6029930 0.4709412 5159.260 3110.998 2048.263
16: 2024-07-30 0.3076331 0.6548709 7153.359 2200.610 4952.749
17: 2024-07-31 0.2334298 0.7096003 7728.034 1803.954 5924.080
18: 2024-08-01 0.2224291 0.7185406 7801.435 1735.266 6066.168

```

Por último, si **G0d** ya contiene todos los componentes, se puede especifica que no haga ninguna correlación.

```
1 compD_none <- fCompD(sol = sol, G0d = compD_user, corr = 'none')
2 compD_none
```

```
Key: <Dates>
      Dates      Fd      Kt      G0d      D0d      B0d
   <POS<   <num>   <num>   <num>   <num>   <num>
1: 2024-07-15 0.2724591 0.6798139 7697.945 2097.375 5600.570
2: 2024-07-16 0.2455880 0.7000272 7911.858 1943.057 5968.801
3: 2024-07-17 0.2705287 0.6812283 7684.293 2078.822 5605.472
4: 2024-07-18 0.6086148 0.4674993 5262.702 3202.958 2059.744
5: 2024-07-19 0.2454217 0.7001561 7865.166 1930.282 5934.884
6: 2024-07-20 0.2452020 0.7003266 7849.961 1924.826 5925.135
7: 2024-07-21 0.2013208 0.7365959 8237.938 1658.468 6579.470
8: 2024-07-22 0.1873678 0.7493438 8361.056 1566.592 6794.463
9: 2024-07-23 0.2259736 0.7156288 7965.753 1800.050 6165.703
10: 2024-07-24 0.2483878 0.6978638 7748.845 1924.718 5824.126
11: 2024-07-25 0.2630540 0.6867564 7606.140 2000.826 5605.314
12: 2024-07-26 0.3202837 0.6462270 7138.548 2286.361 4852.187
13: 2024-07-27 0.3077503 0.6547900 7213.697 2220.018 4993.679
14: 2024-07-28 0.2653324 0.6850625 7526.355 1996.986 5529.369
15: 2024-07-29 0.6029930 0.4709412 5159.260 3110.998 2048.263
16: 2024-07-30 0.3076331 0.6548709 7153.359 2200.610 4952.749
17: 2024-07-31 0.2334298 0.7096003 7728.034 1803.954 5924.080
18: 2024-08-01 0.2224291 0.7185406 7801.435 1735.266 6066.168
```

- **fCompI**: calcula, en base a los valores de irradiación diaria, todas las componentes de irradiancia. Se vale de dos procedimientos en base al tipo de argumentos que toma:

- **compD**: Si recibe un **data.table** resultado de **fCompD**, calcula las relaciones entre las componentes de irradiancia e irradiación de las componentes de difusa y global, obteniendo con ellas un perfil de irradiancias [3.2] (las irradiancias global y difusa salen de estas relaciones, mientras que la directa surge por diferencia entre las dos).

```
1 sol <- calcSol(lat = 37.2, BTd = fBTd(mode = 'prom'),
2               sample = 'hour', keep.night = FALSE)
3 G0d <- c(2.766,3.491,4.494,5.912,6.989,7.742,7.919,
4          7.027,5.369,3.562,2.814,2.179) * 1000
5 compD <- fCompD(sol = sol, G0d = G0d, corr = 'CPR')
6 compI <- fCompI(sol = sol, compD = compD)
7 show(compI)
```

```
Key: <Dates>
      Dates      Fd      Kt      G0      D0      B0
   <POS<   <num>   <num>   <num>   <num>   <num>
1: 2024-01-17 08:00:00 0.5656199 0.4583592  84.06042  47.54625  36.40399
2: 2024-01-17 09:00:00 0.4912826 0.5277148 215.49558 105.86922 109.51548
3: 2024-01-17 10:00:00 0.4453619 0.5821268 340.45500 151.62569 188.82159
4: 2024-01-17 11:00:00 0.4195854 0.6178887 433.04376 181.69885 251.45464
5: 2024-01-17 12:00:00 0.4098508 0.6325646 473.44106 194.04019 279.57020
---
141: 2024-12-13 12:00:00 0.5437347 0.5488870 382.71443 208.09513 174.85828
142: 2024-12-13 13:00:00 0.5556284 0.5371376 352.10710 195.64071 156.62669
143: 2024-12-13 14:00:00 0.5893861 0.5063725 276.60890 163.02945 113.57257
144: 2024-12-13 15:00:00 0.6506594 0.4586869 172.87432 112.48231  60.23704
145: 2024-12-13 16:00:00 0.7511394 0.3973283  63.15968  47.44173  15.57107
```

- **G0I**: Este argumento recibe datos de irradiancia, para después, poder aplicar las correcciones indicadas en el argumento **corr**.

```

1 GOI <- compI$GO
2 compI_ekdh <- fCompI(sol = sol, GOI = GOI, corr = 'EKDh')
3 show(compI_ekdh)

```

```

Key: <Dates>
      Dates      Fd      Kt      GO      DO      BO
      <POS<      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 0.7417600 0.4583592 84.06042 62.35265 21.70776
2: 2024-01-17 09:00:00 0.6000150 0.5277148 215.49558 129.30057 86.19500
3: 2024-01-17 10:00:00 0.4791716 0.5821268 340.45500 163.13636 177.31865
4: 2024-01-17 11:00:00 0.4004462 0.6178887 433.04376 173.41074 259.63302
5: 2024-01-17 12:00:00 0.3692679 0.6325646 473.44106 174.82659 298.61447
---
141: 2024-12-13 12:00:00 0.5533972 0.5488870 382.71443 211.79307 170.92135
142: 2024-12-13 13:00:00 0.5793829 0.5371376 352.10710 204.00484 148.10226
143: 2024-12-13 14:00:00 0.6457949 0.5063725 276.60890 178.63262 97.97628
144: 2024-12-13 15:00:00 0.7411461 0.4586869 172.87432 128.12512 44.74920
145: 2024-12-13 16:00:00 0.8439123 0.3973283 63.15968 53.30123 9.85845

```

```

1 compI_brl <- fCompI(sol = sol, GOI = GOI, corr = 'BRL')
2 show(compI_brl)

```

```

Key: <Dates>
      Dates      Fd      Kt      GO      DO      BO
      <POS<      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 0.6689300 0.4583592 84.06042 56.23053 27.82988
2: 2024-01-17 09:00:00 0.5775367 0.5277148 215.49558 124.45660 91.03897
3: 2024-01-17 10:00:00 0.4826595 0.5821268 340.45500 164.32384 176.13116
4: 2024-01-17 11:00:00 0.4204896 0.6178887 433.04376 182.09040 250.95337
5: 2024-01-17 12:00:00 0.3948666 0.6325646 473.44106 186.94604 286.49502
---
141: 2024-12-13 12:00:00 0.5872522 0.5488870 382.71443 224.74989 157.96454
142: 2024-12-13 13:00:00 0.6048894 0.5371376 352.10710 212.98583 139.12126
143: 2024-12-13 14:00:00 0.6521416 0.5063725 276.60890 180.38818 96.22073
144: 2024-12-13 15:00:00 0.7207149 0.4586869 172.87432 124.59311 48.28121
145: 2024-12-13 16:00:00 0.7818945 0.3973283 63.15968 49.38421 13.77547

```

```

1 compI_climedh <- fCompI(sol = sol, GOI = GOI, corr = 'CLIMEDh')
2 show(compI_climedh)

```

```

Key: <Dates>
      Dates      Fd      Kt      GO      DO      BO
      <POS<      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 0.7093252 0.4583592 84.06042 59.62617 24.43424
2: 2024-01-17 09:00:00 0.5818534 0.5277148 215.49558 125.38683 90.10875
3: 2024-01-17 10:00:00 0.4782729 0.5821268 340.45500 162.83039 177.62462
4: 2024-01-17 11:00:00 0.4110389 0.6178887 433.04376 177.99784 255.04592
5: 2024-01-17 12:00:00 0.3840268 0.6325646 473.44106 181.81406 291.62701
---
141: 2024-12-13 12:00:00 0.5416063 0.5488870 382.71443 207.28055 175.43387
142: 2024-12-13 13:00:00 0.5639749 0.5371376 352.10710 198.57956 153.52754
143: 2024-12-13 14:00:00 0.6220088 0.5063725 276.60890 172.05317 104.55573
144: 2024-12-13 15:00:00 0.7087489 0.4586869 172.87432 122.52448 50.34984
145: 2024-12-13 16:00:00 0.8099691 0.3973283 63.15968 51.15739 12.00229

```

Como con `fCompD`, se puede añadir una función correctora propia.

```

1 f_corri <- function(sol, GOi){
2   ## Función CLIMEDh
3   Kt <- Kti(sol, GOi)

```

```

4   Fd=(Kt<=0.21)*(0.995-0.081*Kt)+
5     (Kt>0.21 & Kt<=0.76)*(0.724+2.738*Kt-8.32*Kt^2+4.967*Kt^3)+
6     (Kt>0.76)*0.180
7   return(data.table(Fd, Kt))
8 }
9 compI_user <- fCompI(sol = sol, GOI = GOI, corr = 'user', f = f_corri)
10 show(compI_user)

```

```

Key: <Dates>
      Dates      Fd      Kt      GO      DO      BO
   <POS<   <num>   <num>   <num>   <num>   <num>
1: 2024-01-17 08:00:00 0.7093252 0.4583592 84.06042 59.62617 24.43424
2: 2024-01-17 09:00:00 0.5818534 0.5277148 215.49558 125.38683 90.10875
3: 2024-01-17 10:00:00 0.4782729 0.5821268 340.45500 162.83039 177.62462
4: 2024-01-17 11:00:00 0.4110389 0.6178887 433.04376 177.99784 255.04592
5: 2024-01-17 12:00:00 0.3840268 0.6325646 473.44106 181.81406 291.62701
---
141: 2024-12-13 12:00:00 0.5416063 0.5488870 382.71443 207.28055 175.43387
142: 2024-12-13 13:00:00 0.5639749 0.5371376 352.10710 198.57956 153.52754
143: 2024-12-13 14:00:00 0.6220088 0.5063725 276.60890 172.05317 104.55573
144: 2024-12-13 15:00:00 0.7087489 0.4586869 172.87432 122.52448 50.34984
145: 2024-12-13 16:00:00 0.8099691 0.3973283 63.15968 51.15739 12.00229

```

Y además, se puede no añadir correlación.

```

1 GOI <- compI_user
2 compI_none <- fCompI(sol = sol, GOI = GOI, corr = 'none')
3 show(compI_none)

```

```

Key: <Dates>
      Dates      Fd      Kt      GO      DO      BO
   <POS<   <num>   <num>   <num>   <num>   <num>
1: 2024-01-17 08:00:00 0.7093252 0.4583592 84.06042 59.62617 24.43424
2: 2024-01-17 09:00:00 0.5818534 0.5277148 215.49558 125.38683 90.10875
3: 2024-01-17 10:00:00 0.4782729 0.5821268 340.45500 162.83039 177.62462
4: 2024-01-17 11:00:00 0.4110389 0.6178887 433.04376 177.99784 255.04592
5: 2024-01-17 12:00:00 0.3840268 0.6325646 473.44106 181.81406 291.62701
---
141: 2024-12-13 12:00:00 0.5416063 0.5488870 382.71443 207.28055 175.43387
142: 2024-12-13 13:00:00 0.5639749 0.5371376 352.10710 198.57956 153.52754
143: 2024-12-13 14:00:00 0.6220088 0.5063725 276.60890 172.05317 104.55573
144: 2024-12-13 15:00:00 0.7087489 0.4586869 172.87432 122.52448 50.34984
145: 2024-12-13 16:00:00 0.8099691 0.3973283 63.15968 51.15739 12.00229

```

Por último, esta función incluye un argumento extra, **filterGO** que cuando su valor es **TRUE**, elimina todos aquellos valores de irradiancia que son mayores que la irradiancia extra-atmosférica (ya que es incoherente que la irradiancia terrestre sea mayor que la extra-terrestre)

Estas dos funciones, como se muestra en la figura 4.4, convergen en la función constructora **calcGO**, dando como resultado un objeto de clase **GO**. Este objeto muestra la media mensual de la irradiación diaria y la irradiación anual. Aparte, incluye los resultados de **fCompD** y **fCompI** y los objetos **Sol** y **Meteo** de los que parte.

Como argumento más importante está **modeRad**, el cual selecciona el tipo de datos que introduce el usuario en el argumento **dataRad**. Estos son:

- Medias mensuales.


```

1 G0dm <- c(2.766, 3.491, 4.494, 5.912, 6.989, 7.742, 7.919,
2           7.027, 5.369, 3.562, 2.814, 2.179) * 1000
3 Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2,
4         28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
5 prom <- data.table(G0dm, Ta)
6 g0_prom <- calcG0(lat, modeRad = 'prom', dataRad = prom)
7 show(g0_prom)

```

```

Object of class  G0

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      G0d      D0d      B0d
   <char> <num>    <num>    <num>
1: Jan. 2024 2.766 0.941698 1.824302
2: Feb. 2024 3.491 1.247146 2.243854
3: Mar. 2024 4.494 1.671763 2.822237
4: Apr. 2024 5.912 1.931146 3.980854
5: May. 2024 6.989 2.023364 4.965636
6: Jun. 2024 7.742 1.889994 5.852006
7: Jul. 2024 7.919 1.624064 6.294936
8: Aug. 2024 7.027 1.547591 5.479409
9: Sep. 2024 5.369 1.540708 3.828292
10: Oct. 2024 3.562 1.374513 2.187487
11: Nov. 2024 2.814 1.006959 1.807041
12: Dec. 2024 2.179 0.926737 1.252263

Yearly values:
      Dates      G0d      D0d      B0d
   <int>    <num>    <num>    <num>
1:  2024 1839.365 540.6331 1298.732

```

- Generación de secuencias diarias mediante matrices de transición de Markov.

```

1 g0_aguiar <- calcG0(lat, modeRad = 'aguiar', dataRad = prom)
2 show(g0_aguiar)

```

```

Object of class  G0

Source of meteorological information: bd-aguiar

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      G0d      D0d      B0d
   <char> <num>    <num>    <num>
1: Jan. 2024 2.766 1.018399 1.747601
2: Feb. 2024 3.491 1.539128 1.951872
3: Mar. 2024 4.494 2.019729 2.474271
4: Apr. 2024 5.912 2.212283 3.699717
5: May. 2024 6.989 2.443056 4.545944
6: Jun. 2024 7.742 2.469004 5.272996
7: Jul. 2024 7.919 2.202626 5.716374
8: Aug. 2024 7.027 2.245755 4.781245
9: Sep. 2024 5.369 1.714299 3.654701
10: Oct. 2024 3.562 1.791424 1.770576
11: Nov. 2024 2.814 1.148719 1.665281
12: Dec. 2024 2.179 1.161355 1.017645

Yearly values:

```

```
Key: <Dates>
  Dates      G0d      D0d      B0d
  <int>     <num>     <num>     <num>
1:  2024 1839.365 670.3165 1169.049
```

■ Diarios.

```
1 bd <- as.data.tableD(g0_aguiar)
2 g0_bd <- calcG0(lat, modeRad = 'bd', dataRad = bd)
3 show(g0_bd)
```

```
Object of class  G0

Source of meteorological information: bd-data.table

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
  Dates      G0d      D0d      B0d
  <char> <num>     <num>     <num>
1: Jan. 2024 2.766 1.018399 1.747601
2: Feb. 2024 3.491 1.539128 1.951872
3: Mar. 2024 4.494 2.019729 2.474271
4: Apr. 2024 5.912 2.212283 3.699717
5: May. 2024 6.989 2.443056 4.545944
6: Jun. 2024 7.742 2.469004 5.272996
7: Jul. 2024 7.919 2.202626 5.716374
8: Aug. 2024 7.027 2.245755 4.781245
9: Sep. 2024 5.369 1.714299 3.654701
10: Oct. 2024 3.562 1.791424 1.770576
11: Nov. 2024 2.814 1.148719 1.665281
12: Dec. 2024 2.179 1.161355 1.017645

Yearly values:
Key: <Dates>
  Dates      G0d      D0d      B0d
  <int>     <num>     <num>     <num>
1:  2024 1839.365 670.3165 1169.049
```

■ Intradiarios

```
1 bdI <- as.data.tableI(g0_aguiar)
2 g0_bdI <- calcG0(lat, modeRad = 'bdI', dataRad = bdI)
3 show(g0_bdI)
```

```
Object of class  G0

Source of meteorological information: bdI-data.table

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
  Dates      G0d      D0d      B0d
  <char> <num>     <num>     <num>
1: Jan. 2024 2.766000 0.9625472 1.8034528
2: Feb. 2024 3.491000 1.5898320 1.9011680
3: Mar. 2024 4.494000 2.0981954 2.3958046
4: Apr. 2024 5.912000 2.1497145 3.7622855
5: May. 2024 6.989000 2.3990824 4.5899176
6: Jun. 2024 7.742000 2.3030247 5.4389753
7: Jul. 2024 7.919000 1.7067936 6.2122064
8: Aug. 2024 6.483769 1.6494109 4.8343585
9: Sep. 2024 5.369000 1.6544602 3.7145398
```

```

10: Oct. 2024 3.562000 1.9052417 1.6567583
11: Nov. 2024 2.659222 0.9870476 1.6721742
12: Dec. 2024 2.179000 1.2360451 0.9429549

```

Yearly values:

Key: <Dates>

Dates	G0d	D0d	B0d
<int>	<num>	<num>	<num>
1: 2024	1817.882	629.6093	1188.272

4.4. Radiación efectiva en el plano del generador

Teniendo la radiación incidente en plano horizontal (sección 4.3), se puede calcular la radiación efectiva incidente en el plano del generador. Para ello, **solar2** cuenta con la función **calcGef** [??] la cual mediante las funciones **fInclin** y **calcShd** procesa un objeto de clase **G0** para obtener un objeto **Gef**.

Como se puede ver en la figura 4.5, **calcGef** funciona gracias a las siguientes funciones:

- **fTheta**: la cual, partiendo del ángulo de inclinación (β) y la orientación (α), calcula el ángulo de inclinación en cada instante (β), el ángulo azimutal (ψ_s) y el coseno del ángulo de incidencia de la radiación solar en la superficie ($\cos(\theta_s)$). Como principal argumento tiene **modeTrk**, el cual determina el sistema de seguimiento que tiene el sistema:

- **fixed**: para sistemas estáticos.

```

1 BTd <- fBTd(mode = 'prom')[6]
2 sol <- calcSol(lat, BTd = BTd, keep.night = FALSE)
3 beta <- lat - 10
4 alfa <- 0
5 angGen_fixed <- fTheta(sol = sol, beta = beta, alfa = alfa,
6                       modeTrk = 'fixed')
7 show(angGen_fixed)

```




FIGURA 4.5: Cálculo de la radiación efectiva incidente en el plano del generador mediante la función **calcGef**, la cual emplea la función **fInclin** para el computo de las componentes efectivas, la función **fTheta** que provee a la función anterior los ángulos necesarios para su computo y la función **calcShd** que reprocesa el objeto de clase **Gef** resultante, añadiéndole el efecto de las sombras producidas entre módulos.

4. DESARROLLO DEL CÓDIGO

	Dates	Beta	Alfa	cosTheta
	<POS>	<num>	<num>	<num>
1:	2024-06-10 05:00:00	0.4747296	0	0.00000000
2:	2024-06-10 06:00:00	0.4747296	0	0.06990810
3:	2024-06-10 07:00:00	0.4747296	0	0.30432148
4:	2024-06-10 08:00:00	0.4747296	0	0.52263672
5:	2024-06-10 09:00:00	0.4747296	0	0.70998013
6:	2024-06-10 10:00:00	0.4747296	0	0.85358815
7:	2024-06-10 11:00:00	0.4747296	0	0.94367686
8:	2024-06-10 12:00:00	0.4747296	0	0.97410861
9:	2024-06-10 13:00:00	0.4747296	0	0.94281011
10:	2024-06-10 14:00:00	0.4747296	0	0.85191372
11:	2024-06-10 15:00:00	0.4747296	0	0.70761218
12:	2024-06-10 16:00:00	0.4747296	0	0.51973665
13:	2024-06-10 17:00:00	0.4747296	0	0.30108697
14:	2024-06-10 18:00:00	0.4747296	0	0.06655958
15:	2024-06-10 19:00:00	0.4747296	0	0.00000000

- **two**: para sistemas de seguimiento de doble eje.

```
1 angGen_two <- fTheta(sol = sol, beta = beta, alfa = alfa,  
2                       modeTrk = 'two')  
3 show(angGen_two)
```

	Dates	Beta	Alfa	cosTheta
	<POS>	<num>	<num>	<num>
1:	2024-06-10 05:00:00	1.5220852	-2.043678875	1
2:	2024-06-10 06:00:00	1.3300857	-1.896688029	1
3:	2024-06-10 07:00:00	1.1285281	-1.756655282	1
4:	2024-06-10 08:00:00	0.9215732	-1.612213267	1
5:	2024-06-10 09:00:00	0.7134716	-1.445120762	1
6:	2024-06-10 10:00:00	0.5110180	-1.215351693	1
7:	2024-06-10 11:00:00	0.3328578	-0.809087856	1
8:	2024-06-10 12:00:00	0.2466893	0.006963841	1
9:	2024-06-10 13:00:00	0.3349967	0.817155564	1
10:	2024-06-10 14:00:00	0.5137803	1.219398208	1
11:	2024-06-10 15:00:00	0.7163931	1.447776194	1
12:	2024-06-10 16:00:00	0.9245147	1.614353339	1
13:	2024-06-10 17:00:00	1.1314208	1.758631827	1
14:	2024-06-10 18:00:00	1.3328735	1.898691776	1
15:	2024-06-10 19:00:00	1.5247042	2.045849315	1

- **horiz**: para sistemas de seguimiento horizontal Norte-Sur.

```
1 angGen_horiz <- fTheta(sol = sol, beta = beta, alfa = alfa,  
2                      modeTrk = 'horiz')  
3 show(angGen_horiz)
```

	Dates	Beta	Alfa	cosTheta
	<POS>	<num>	<num>	<num>
1:	2024-06-10 05:00:00	1.516091993	-1.570796	0.8905353
2:	2024-06-10 06:00:00	1.317263961	-1.570796	0.9504350
3:	2024-06-10 07:00:00	1.121771495	-1.570796	0.9859551
4:	2024-06-10 08:00:00	0.921160041	-1.570796	0.9994560
5:	2024-06-10 09:00:00	0.709555740	-1.570796	0.9966296
6:	2024-06-10 10:00:00	0.483954771	-1.570796	0.9854098
7:	2024-06-10 11:00:00	0.245151627	-1.570796	0.9742418
8:	2024-06-10 12:00:00	0.001753607	1.570796	0.9697277
9:	2024-06-10 13:00:00	0.248597042	1.570796	0.9743648
10:	2024-06-10 14:00:00	0.487239436	1.570796	0.9855868
11:	2024-06-10 15:00:00	0.712638107	1.570796	0.9967482

```

12: 2024-06-10 16:00:00 0.924058412 1.570796 0.9993956
13: 2024-06-10 17:00:00 1.124550569 1.570796 0.9856166
14: 2024-06-10 18:00:00 1.320024608 1.570796 0.9497600
15: 2024-06-10 19:00:00 1.518974473 1.570796 0.8895182

```

También, tiene un argumento **BT** que indica cuando se usa la técnica de backtracking para un sistema horizontal Norte-Sur. Para funcionar, necesita de los argumentos **struct**, el cual presenta una lista con la altura de los módulos, y **dist**, el cual presenta un **data.frame** (o **data.table**) con la distancia que separa los módulos en la dirección Este-Oeste.

```

1 struct <- list(L = 1)
2 distances <- data.table(Lew = 2)
3 angGen_BT <- fTheta(sol = sol, beta = beta, alfa = alfa,
4                     modeTrk = 'horiz', BT = TRUE,
5                     struct = struct, dist = distances)
6 show(angGen_BT)

```

	Dates <POS>	Beta <num>	Alfa <num>	cosTheta <num>
1:	2024-06-10 05:00:00	0.054868903	-1.570796	0.09738369
2:	2024-06-10 06:00:00	0.271972628	-1.570796	0.47678565
3:	2024-06-10 07:00:00	0.602487004	-1.570796	0.85598103
4:	2024-06-10 08:00:00	0.921160041	-1.570796	0.99945597
5:	2024-06-10 09:00:00	0.709555740	-1.570796	0.99662956
6:	2024-06-10 10:00:00	0.483954771	-1.570796	0.98540983
7:	2024-06-10 11:00:00	0.245151627	-1.570796	0.97424175
8:	2024-06-10 12:00:00	0.001753607	1.570796	0.96972767
9:	2024-06-10 13:00:00	0.248597042	1.570796	0.97436477
10:	2024-06-10 14:00:00	0.487239436	1.570796	0.98558683
11:	2024-06-10 15:00:00	0.712638107	1.570796	0.99674816
12:	2024-06-10 16:00:00	0.924058412	1.570796	0.99939563
13:	2024-06-10 17:00:00	0.595256963	1.570796	0.85074877
14:	2024-06-10 18:00:00	0.268563625	1.570796	0.47136897
15:	2024-06-10 19:00:00	0.051961679	1.570796	0.09215170

- **fInclin**: la cual, partiendo del resultado de **fTheta** y de un objeto de clase **GO**, calcula la irradiancia solar incidente en una superficie inclinada junto con los efectos del ángulo de incidencia y la suciedad para obtener la irradiancia efectiva. Como argumentos principales están:

- **iS**: permite seleccionar entre 4 valores del 1 al 4 correspondientes al grado de suciedad del módulo. Siendo 1 limpio y 4 alto y basandose en los valores de la tabla 3.2 calcula la irradiancia efectiva. Por defecto tiene valor 2 (grado de suciedad bajo).

```

1 compI <- calcGO(lat, dataRad = prom, keep.night = FALSE)
2 sol <- calcSol(lat, BTi = indexI(compI))
3 angGen <- fTheta(sol = sol, beta = beta, alfa = alfa)
4 inclin_limpio <- fInclin(compI = compI, angGen = angGen, iS = 1)
5 show(inclin_limpio)

```

	Dates <POS>	Bo <num>	Bn <num>	G <num>	D <num>	Di <num>	Dc <num>	B <num>	R <num>
1:	2024-01-17 08:00:00	514.5612	365.8727	186.4590	52.34286	25.82073	26.52212	133.18653	0.9295706
2:	2024-01-17 09:00:00	792.6980	464.2106	366.6704	103.96230	52.12242	51.83988	260.32510	2.3830282
3:	2024-01-17 10:00:00	1010.9063	541.3602	536.6247	145.69981	68.60264	77.09717	387.15997	3.7648749
4:	2024-01-17 11:00:00	1154.3223	592.0663	662.0048	173.72247	77.44190	96.28057	483.49354	4.7887550
5:	2024-01-17 12:00:00	1213.1770	612.8750	716.5974	185.35767	80.61172	104.74595	526.00427	5.2354830

141:	2024-12-13 12:00:00	1181.1554	470.2512	578.4583	180.82966	95.85462	84.97504	393.39650	4.2321949

4. DESARROLLO DEL CÓDIGO

```

142: 2024-12-13 13:00:00 1129.5610 453.5904 536.8668 170.08970 91.70559 78.38411 362.88341 3.8937280
143: 2024-12-13 14:00:00 994.4636 409.9651 434.0673 142.25355 79.88147 62.37208 288.75488 3.0588416
144: 2024-12-13 15:00:00 785.0640 342.3463 292.1950 99.92831 58.81096 41.11735 190.35496 1.9117069
145: 2024-12-13 16:00:00 515.6229 255.3390 140.8937 46.94651 26.80445 20.14206 93.24874 0.6984426
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 0.115032290 0.05043622 0.2503398 24.51843 23.47122 166.5523 47.98966 117.86578 0.6968621
2: 0.034235799 0.05043622 0.2503398 49.49356 50.06510 352.7578 99.55866 251.41266 1.7864615
3: 0.012139104 0.05043622 0.2503398 65.14258 76.16128 526.5864 141.30386 382.46020 2.8223770
4: 0.005426675 0.05043622 0.2503398 73.53602 95.75809 653.7538 169.29411 480.86978 3.5899392
5: 0.003640433 0.05043622 0.2503398 76.54597 104.36463 708.9248 180.91060 524.08939 3.9248333
---
141: 0.004516349 0.05043622 0.2503398 91.02007 84.59127 570.4038 175.61134 391.61978 3.1727082
142: 0.006269898 0.05043622 0.2503398 87.08031 77.89265 528.5001 164.97296 360.60816 2.9189730
143: 0.013120704 0.05043622 0.2503398 75.85255 61.55372 424.6656 137.40626 284.96622 2.2930919
144: 0.035287438 0.05043622 0.2503398 55.84476 39.66642 280.5821 95.51118 183.63782 1.4331306
145: 0.114223038 0.05043622 0.2503398 25.45254 17.84137 126.4151 43.29391 82.59758 0.5235947

```

```

1 inclin_sucio <- fInclin(compI = compI, angGen = angGen, iS = 4)
2 show(inclin_sucio)

```

```

      Dates      Bo      Bn      G      D      Di      Dc      B      R
      <POS<      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 514.5612 365.8727 186.4590 52.34286 25.82073 26.52212 133.18653 0.9295706
2: 2024-01-17 09:00:00 792.6980 464.2106 366.6704 103.96230 52.12242 51.83988 260.32510 2.3830282
3: 2024-01-17 10:00:00 1010.9063 541.3602 536.6247 145.69981 68.60264 77.09717 387.15997 3.7648749
4: 2024-01-17 11:00:00 1154.3223 592.0663 662.0048 173.72247 77.44190 96.28057 483.49354 4.7887550
5: 2024-01-17 12:00:00 1213.1770 612.8750 716.5974 185.35767 80.61172 104.74595 526.00427 5.2354830
---
141: 2024-12-13 12:00:00 1181.1554 470.2512 578.4583 180.82966 95.85462 84.97504 393.39650 4.2321949
142: 2024-12-13 13:00:00 1129.5610 453.5904 536.8668 170.08970 91.70559 78.38411 362.88341 3.8937280
143: 2024-12-13 14:00:00 994.4636 409.9651 434.0673 142.25355 79.88147 62.37208 288.75488 3.0588416
144: 2024-12-13 15:00:00 785.0640 342.3463 292.1950 99.92831 58.81096 41.11735 190.35496 1.9117069
145: 2024-12-13 16:00:00 515.6229 255.3390 140.8937 46.94651 26.80445 20.14206 93.24874 0.6984426
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 0.24100175 0.09714708 0.3918962 21.44734 18.51982 133.4885 39.96716 93.00127 0.5200533
2: 0.10321543 0.09714708 0.3918962 43.29416 42.77007 302.1765 86.06424 214.77909 1.3331982
3: 0.04727214 0.09714708 0.3918962 56.98305 67.57641 466.0152 124.55946 339.34944 2.1062799
4: 0.02455379 0.09714708 0.3918962 64.32515 86.40320 587.2996 150.72835 433.89218 2.6790952
5: 0.01743586 0.09714708 0.3918962 66.95809 94.68605 640.0594 161.64413 475.48630 2.9290196
---
141: 0.02100686 0.09714708 0.3918962 79.61921 76.53478 512.8436 156.15400 354.32187 2.3677246
142: 0.02771140 0.09714708 0.3918962 76.17293 70.11502 473.0675 146.28795 324.60121 2.1783674
143: 0.05023795 0.09714708 0.3918962 66.35152 54.49955 374.8709 120.85106 252.30856 1.7112857
144: 0.10550059 0.09714708 0.3918962 48.84983 33.83709 240.4070 82.68692 156.65061 1.0695149
145: 0.23984890 0.09714708 0.3918962 22.26444 14.08613 101.9538 36.35057 65.21248 0.3907476

```

- **alb** Correspondiente al coeficiente de reflexión del terreno para la irradiancia de albedo. Por defecto tiene un valor de 0,2 (valor aceptable para un terreno normal).

```

1 inclin_alb0 <- fInclin(compI = compI, angGen = angGen, alb = 0)
2 show(inclin_alb0)

```

```

      Dates      Bo      Bn      G      D      Di      Dc      B      R
      <POS<      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 514.5612 365.8727 185.5294 52.34286 25.82073 26.52212 133.18653 0
2: 2024-01-17 09:00:00 792.6980 464.2106 364.2874 103.96230 52.12242 51.83988 260.32510 0
3: 2024-01-17 10:00:00 1010.9063 541.3602 532.8598 145.69981 68.60264 77.09717 387.15997 0
4: 2024-01-17 11:00:00 1154.3223 592.0663 657.2160 173.72247 77.44190 96.28057 483.49354 0
5: 2024-01-17 12:00:00 1213.1770 612.8750 711.3619 185.35767 80.61172 104.74595 526.00427 0
---
141: 2024-12-13 12:00:00 1181.1554 470.2512 574.2262 180.82966 95.85462 84.97504 393.39650 0
142: 2024-12-13 13:00:00 1129.5610 453.5904 532.9731 170.08970 91.70559 78.38411 362.88341 0

```

```

143: 2024-12-13 14:00:00 994.4636 409.9651 431.0084 142.25355 79.88147 62.37208 288.75488 0
144: 2024-12-13 15:00:00 785.0640 342.3463 290.2833 99.92831 58.81096 41.11735 190.35496 0
145: 2024-12-13 16:00:00 515.6229 255.3390 140.1953 46.94651 26.80445 20.14206 93.24874 0
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 0.156321477 0.06473603 0.2994808 23.66622 21.92862 155.7141 45.59484 110.11928 0
2: 0.054197292 0.06473603 0.2994808 47.77325 48.04970 337.1148 95.82295 241.29186 0
3: 0.021399057 0.06473603 0.2994808 62.87835 73.93841 508.1144 136.81676 371.29761 0
4: 0.010185772 0.06473603 0.2994808 70.98005 93.39388 633.3713 164.37393 468.99741 0
5: 0.006996517 0.06473603 0.2994808 73.88537 101.93283 687.6958 175.81821 511.87759 0
---
141: 0.008575046 0.06473603 0.2994808 87.85638 82.56145 552.6405 170.41783 382.22264 0
142: 0.011653979 0.06473603 0.2994808 84.05356 75.92121 511.4560 159.97477 351.48128 0
143: 0.022965930 0.06473603 0.2994808 73.21605 59.72086 409.4178 132.93691 276.48089 0
144: 0.055666181 0.06473603 0.2994808 53.90370 38.05193 268.1191 91.95563 176.16345 0
145: 0.155368802 0.06473603 0.2994808 24.56786 16.67236 118.4258 41.24021 77.18558 0

```

```

1 inclin_alb1 <- fInclin(compI = compI, angGen = angGen, alb = 1)
2 show(inclin_alb1)

```

```

      Dates      Bo      Bn      G      D      Di      Dc      B      R
      <POSc>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 2024-01-17 08:00:00 514.5612 365.8727 190.1772 52.34286 25.82073 26.52212 133.18653 4.647853
2: 2024-01-17 09:00:00 792.6980 464.2106 376.2025 103.96230 52.12242 51.83988 260.32510 11.915141
3: 2024-01-17 10:00:00 1010.9063 541.3602 551.6842 145.69981 68.60264 77.09717 387.15997 18.824375
4: 2024-01-17 11:00:00 1154.3223 592.0663 681.1598 173.72247 77.44190 96.28057 483.49354 23.943775
5: 2024-01-17 12:00:00 1213.1770 612.8750 737.5394 185.35767 80.61172 104.74595 526.00427 26.177415
---
141: 2024-12-13 12:00:00 1181.1554 470.2512 595.3871 180.82966 95.85462 84.97504 393.39650 21.160975
142: 2024-12-13 13:00:00 1129.5610 453.5904 552.4417 170.08970 91.70559 78.38411 362.88341 19.468640
143: 2024-12-13 14:00:00 994.4636 409.9651 446.3026 142.25355 79.88147 62.37208 288.75488 15.294208
144: 2024-12-13 15:00:00 785.0640 342.3463 299.8418 99.92831 58.81096 41.11735 190.35496 9.558535
145: 2024-12-13 16:00:00 515.6229 255.3390 143.6875 46.94651 26.80445 20.14206 93.24874 3.492213
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: 0.156321477 0.06473603 0.2994808 23.66622 21.92862 158.9049 45.59484 110.11928 3.190792
2: 0.054197292 0.06473603 0.2994808 47.77325 48.04970 345.2947 95.82295 241.29186 8.179849
3: 0.021399057 0.06473603 0.2994808 62.87835 73.93841 521.0375 136.81676 371.29761 12.923098
4: 0.010185772 0.06473603 0.2994808 70.98005 93.39388 649.8089 164.37393 468.99741 16.437612
5: 0.006996517 0.06473603 0.2994808 73.88537 101.93283 705.6668 175.81821 511.87759 17.971025
---
141: 0.008575046 0.06473603 0.2994808 87.85638 82.56145 567.1677 170.41783 382.22264 14.527195
142: 0.011653979 0.06473603 0.2994808 84.05356 75.92121 524.8214 159.97477 351.48128 13.365392
143: 0.022965930 0.06473603 0.2994808 73.21605 59.72086 419.9174 132.93691 276.48089 10.499608
144: 0.055666181 0.06473603 0.2994808 53.90370 38.05193 274.6811 91.95563 176.16345 6.562018
145: 0.155368802 0.06473603 0.2994808 24.56786 16.67236 120.8232 41.24021 77.18558 2.397435

```

Además, cuenta con dos argumentos adicionales, **horizBright**, el cual, cuando su valor es **TRUE** (el que tiene por defecto), realiza una corrección de la radiación difusa [RBD90], y **HCPV**, es el acrónimo de **High Concentration PV system**⁷ (sistema fotovoltaico de alta concentración) que cuando su valor es **TRUE** (por defecto está puesto en **FALSE**), anula los valores de radiación difusa y de albedo.

```

1 inclin_horizBright <- fInclin(compI = compI, angGen = angGen,
2                               horizBright = FALSE)
3 show(inclin_horizBright)

```

```

      Dates      Bo      Bn      G      D      Di      Dc      B      R
      <POSc>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>

```

⁷la tecnología de concentración fotovoltaica funciona gracias a unos dispositivos ópticos que permiten concentrar la radiación solar sobre una célula fotovoltaica de tamaño reducido pero con una eficiencia muy superior a las células tradicionales. Con ello se consigue emplear menor cantidad de semiconductores reduciendo los costes.

4. DESARROLLO DEL CÓDIGO

```

1: 2024-01-17 08:00:00 514.5612 365.8727 186.2091 52.09303 25.57090 26.52212 133.18653 0.9295706
2: 2024-01-17 09:00:00 792.6980 464.2106 366.1413 103.43314 51.59325 51.83988 260.32510 2.3830282
3: 2024-01-17 10:00:00 1010.9063 541.3602 535.9087 144.98390 67.88673 77.09717 387.15997 3.7648749
4: 2024-01-17 11:00:00 1154.3223 592.0663 661.1846 172.90227 76.62170 96.28057 483.49354 4.7887550
5: 2024-01-17 12:00:00 1213.1770 612.8750 715.7390 184.49921 79.75326 104.74595 526.00427 5.2354830
---
141: 2024-12-13 12:00:00 1181.1554 470.2512 577.4973 179.86860 94.89356 84.97504 393.39650 4.2321949
142: 2024-12-13 13:00:00 1129.5610 453.5904 535.9539 169.17679 90.79268 78.38411 362.88341 3.8937280
143: 2024-12-13 14:00:00 994.4636 409.9651 433.2885 141.47476 79.10268 62.37208 288.75488 3.0588416
144: 2024-12-13 15:00:00 785.0640 342.3463 291.6442 99.37758 58.26023 41.11735 190.35496 1.9117069
145: 2024-12-13 16:00:00 515.6229 255.3390 140.6606 46.71344 26.57138 20.14206 93.24874 0.6984426
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num> <num> <num> <num> <num> <num> <num> <num> <num>
1: 0.156321477 0.06473603 0.2994808 23.43723 21.92862 156.1233 45.36586 110.11928 0.6381583
2: 0.054197292 0.06473603 0.2994808 47.28824 48.04970 338.2658 95.33794 241.29186 1.6359698
3: 0.021399057 0.06473603 0.2994808 62.22217 73.93841 510.0428 136.16059 371.29761 2.5846197
4: 0.010185772 0.06473603 0.2994808 70.22829 93.39388 635.9071 163.62217 468.99741 3.2875223
5: 0.006996517 0.06473603 0.2994808 73.09855 101.93283 690.5032 175.03138 511.87759 3.5942050
---
141: 0.008575046 0.06473603 0.2994808 86.97552 82.56145 554.6650 169.53697 382.22264 2.9054390
142: 0.011653979 0.06473603 0.2994808 83.21682 75.92121 513.2924 159.13803 351.48128 2.6730784
143: 0.022965930 0.06473603 0.2994808 72.50225 59.72086 410.8039 132.22311 276.48089 2.0999216
144: 0.055666181 0.06473603 0.2994808 53.39892 38.05193 268.9267 91.45086 176.16345 1.3124036
145: 0.155368802 0.06473603 0.2994808 24.35423 16.67236 118.6917 41.02659 77.18558 0.4794870

```

```

1 inclin_HCPV <- fInclin(compI = compI, angGen = angGen,
2                       HCPV = TRUE)
3 show(inclin_HCPV)

```

```

      Dates      Bo      Bn      G      D      Di      Dc      B      R
      <POS< <num> <num> <num> <num> <num> <num> <num> <num>
1: 2024-01-17 08:00:00 514.5612 365.8727 186.4590 52.34286 25.82073 26.52212 133.18653 0.9295706
2: 2024-01-17 09:00:00 792.6980 464.2106 366.6704 103.96230 52.12242 51.83988 260.32510 2.3830282
3: 2024-01-17 10:00:00 1010.9063 541.3602 536.6247 145.69981 68.60264 77.09717 387.15997 3.7648749
4: 2024-01-17 11:00:00 1154.3223 592.0663 662.0048 173.72247 77.44190 96.28057 483.49354 4.7887550
5: 2024-01-17 12:00:00 1213.1770 612.8750 716.5974 185.35767 80.61172 104.74595 526.00427 5.2354830
---
141: 2024-12-13 12:00:00 1181.1554 470.2512 578.4583 180.82966 95.85462 84.97504 393.39650 4.2321949
142: 2024-12-13 13:00:00 1129.5610 453.5904 536.8668 170.08970 91.70559 78.38411 362.88341 3.8937280
143: 2024-12-13 14:00:00 994.4636 409.9651 434.0673 142.25355 79.88147 62.37208 288.75488 3.0588416
144: 2024-12-13 15:00:00 785.0640 342.3463 292.1950 99.92831 58.81096 41.11735 190.35496 1.9117069
145: 2024-12-13 16:00:00 515.6229 255.3390 140.8937 46.94651 26.80445 20.14206 93.24874 0.6984426
      FTb      FTd      FTr      Dief      Dcef      Gef      Def      Bef      Ref
      <num> <num> <num> <num> <num> <num> <num> <num> <num>
1: 0.156321477 0.06473603 0.2994808 0 0 110.11928 0 110.11928 0
2: 0.054197292 0.06473603 0.2994808 0 0 241.29186 0 241.29186 0
3: 0.021399057 0.06473603 0.2994808 0 0 371.29761 0 371.29761 0
4: 0.010185772 0.06473603 0.2994808 0 0 468.99741 0 468.99741 0
5: 0.006996517 0.06473603 0.2994808 0 0 511.87759 0 511.87759 0
---
141: 0.008575046 0.06473603 0.2994808 0 0 382.22264 0 382.22264 0
142: 0.011653979 0.06473603 0.2994808 0 0 351.48128 0 351.48128 0
143: 0.022965930 0.06473603 0.2994808 0 0 276.48089 0 276.48089 0
144: 0.055666181 0.06473603 0.2994808 0 0 176.16345 0 176.16345 0
145: 0.155368802 0.06473603 0.2994808 0 0 77.18558 0 77.18558 0

```

Finalmente, esta función le otorga estos datos a la función **calcGef** para que produzca un objeto de clase **Gef** como resultado. Esta función tiene como argumentos principales los mismos que los que tiene **calcGO** 4.3, es decir, **modeRad** y **dataRad**. Y además, como es lógico, con todos los argumentos mencionados con anterioridad en **fTheta** y **fInclin**.

```

1 gef_prom <- calcGef(lat = lat, modeTrk = 'two', modeRad = 'prom',
2                   dataRad = prom,
3                   beta = lat-10, alfa = 0,

```



```

4      iS = 2, alb = 0.2,
5      horizBright = TRUE, HCPV = FALSE)
6 show(gef_prom)

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

	Dates	Bod	Bnd	Gd	Dd	Bd	Gefd	Defd	Befd
	<char>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1: Jan. 2024	14.13536	4.924221	6.522313	1.440413	4.924221	6.348801	1.384087	4.825736	
2: Feb. 2024	15.42754	5.034287	6.875052	1.672079	5.034287	6.680139	1.599929	4.933601	
3: Mar. 2024	16.58107	5.163713	7.329138	1.998110	5.163713	7.104641	1.902356	5.060439	
4: Apr. 2024	17.64047	6.408617	8.843422	2.265896	6.408617	8.578222	2.158071	6.280444	
5: May. 2024	18.70771	7.617499	10.178196	2.394606	7.617499	9.885240	2.284334	7.465149	
6: Jun. 2024	19.87238	9.102430	11.606533	2.329653	9.102430	11.293417	2.230338	8.920381	
7: Jul. 2024	18.51695	10.037233	11.801533	2.029150	9.589205	11.495648	1.948530	9.397421	
8: Aug. 2024	17.34098	8.640959	10.777404	1.947410	8.640959	10.493150	1.869393	8.468140	
9: Sep. 2024	16.25295	6.698488	8.831006	1.948075	6.698488	8.584604	1.864962	6.564518	
10: Oct. 2024	15.16994	4.546024	6.418653	1.711039	4.546024	6.226290	1.631551	4.455104	
11: Nov. 2024	14.00493	4.638289	6.247341	1.452953	4.638289	6.076159	1.393353	4.545523	
12: Dec. 2024	12.70717	3.439788	4.825181	1.254616	3.439788	4.685547	1.198824	3.370992	

Yearly values:

	Dates	Bod	Bnd	Gd	Dd	Bd	Gefd	Defd	Befd
	<int>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1: 2024	5988.455	2326.882	3058.651	684.4232	2312.993	2973.115	654.591	2266.733	

Mode of tracking: two

Inclination limit: 90

Sin embargo, como argumento importante está **modeShd**, el cual permite incluir el efecto de las sombras entre módulos al objeto **Gef** mediante el uso de la función **calcShd**. Esta opción añade las variables **Gef0**, **Def0** y **Bef0** las cuales son las componentes de radiación efectiva previas a aplicar el efecto de las sombras con el fin de poder comparar.

```

1 struct <- list(W=23.11, L=9.8, Nrow=2, Ncol=8)
2 distances <- data.table(Lew=40, Lns=30, H=0)
3 gef_shd <- calcShd(radEf = gef_prom, modeShd = 'prom',
4                   struct = struct, distances = distances)
5 show(gef_shd)

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

	Dates	Gef0d	Def0d	Bef0d	Gd	Dd	Bd	Gefd	Defd	Befd
	<char>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1: Jan. 2024	6.348801	1.384087	4.825736	6.522313	1.440413	4.924221	6.104126	1.343455	4.621693	
2: Feb. 2024	6.680139	1.599929	4.933601	6.875052	1.672079	5.034287	6.406274	1.553670	4.705996	
3: Mar. 2024	7.104641	1.902356	5.060439	7.329138	1.998110	5.163713	6.788630	1.848127	4.798657	
4: Apr. 2024	8.578222	2.158071	6.280444	8.843422	2.265896	6.408617	8.295340	2.112064	6.043569	
5: May. 2024	9.885240	2.284334	7.465149	10.178196	2.394606	7.617499	9.688308	2.253942	7.298609	
6: Jun. 2024	11.293417	2.230338	8.920381	11.606533	2.329653	9.102430	11.115054	2.205314	8.767042	

```

7: Jul. 2024 11.495648 1.948530 9.397421 11.801533 2.029150 9.589205 11.308971 1.924962 9.234312
8: Aug. 2024 10.493150 1.869393 8.468140 10.777404 1.947410 8.640959 10.196758 1.830334 8.210807
9: Sep. 2024 8.584604 1.864962 6.564518 8.831006 1.948075 6.698488 8.228309 1.810198 6.262986
10: Oct. 2024 6.226290 1.631551 4.455104 6.418653 1.711039 4.546024 6.018374 1.595528 4.283212
11: Nov. 2024 6.076159 1.393353 4.545523 6.247341 1.452953 4.638289 5.875732 1.359514 4.378935
12: Dec. 2024 4.685547 1.198824 3.370992 4.825181 1.254616 3.439788 4.575893 1.179346 3.280817

```

Yearly values:

	Dates	Gef0d	Def0d	Bef0d	Gd	Dd	Bd	Gefd	Defd	Befd
	<int>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024	2973.115	654.591	2266.733	3058.651	684.4232	2312.993	2886.328	640.9157	2193.621

```

-----
Mode of tracking: two
Inclination limit: 90

```

```

1 gef_shd2 <- calcGef(lat = lat, modeTrk = 'two', dataRad = prom,
2                               modeShd = 'prom', struct = struct, distances = distances)
3 show(gef_shd2)

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

	Dates	Gef0d	Def0d	Bef0d	Gd	Dd	Bd	Gefd	Defd	Befd
	<char>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1: Jan. 2024	6.348801	1.384087	4.825736	6.522313	1.440413	4.924221	6.104126	1.343455	4.621693	
2: Feb. 2024	6.680139	1.599929	4.933601	6.875052	1.672079	5.034287	6.406274	1.553670	4.705996	
3: Mar. 2024	7.104641	1.902356	5.060439	7.329138	1.998110	5.163713	6.788630	1.848127	4.798657	
4: Apr. 2024	8.578222	2.158071	6.280444	8.843422	2.265896	6.408617	8.295340	2.112064	6.043569	
5: May. 2024	9.885240	2.284334	7.465149	10.178196	2.394606	7.617499	9.688308	2.253942	7.298609	
6: Jun. 2024	11.293417	2.230338	8.920381	11.606533	2.329653	9.102430	11.115054	2.205314	8.767042	
7: Jul. 2024	11.495648	1.948530	9.397421	11.801533	2.029150	9.589205	11.308971	1.924962	9.234312	
8: Aug. 2024	10.493150	1.869393	8.468140	10.777404	1.947410	8.640959	10.196758	1.830334	8.210807	
9: Sep. 2024	8.584604	1.864962	6.564518	8.831006	1.948075	6.698488	8.228309	1.810198	6.262986	
10: Oct. 2024	6.226290	1.631551	4.455104	6.418653	1.711039	4.546024	6.018374	1.595528	4.283212	
11: Nov. 2024	6.076159	1.393353	4.545523	6.247341	1.452953	4.638289	5.875732	1.359514	4.378935	
12: Dec. 2024	4.685547	1.198824	3.370992	4.825181	1.254616	3.439788	4.575893	1.179346	3.280817	

Yearly values:

	Dates	Gef0d	Def0d	Bef0d	Gd	Dd	Bd	Gefd	Defd	Befd
	<int>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024	2973.115	654.591	2266.733	3058.651	684.4232	2312.993	2886.328	640.9157	2193.621

```

-----
Mode of tracking: two
Inclination limit: 90

```

El argumento **modeShd** puede ser de distintas maneras:

- **area**: el efecto de las sombras se calcula como una reducción proporcional de las irradiancias difusa circunsolar y directa.

```

1 gef_shdarea <- calcGef(lat, modeTrk = 'two', dataRad = prom,
2                               modeShd = 'area',
3                               struct = struct, distances = distances)
4 show(gef_shdarea)

```

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
  Dates      Gef0d    Def0d    Bef0d      Gd      Dd      Bd      Gefd    Defd    Befd
  <char>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>
1: Jan. 2024 6.348801 1.384087 4.825736 6.522313 1.440413 4.924221 5.877879 1.305883 4.433019
2: Feb. 2024 6.680139 1.599929 4.933601 6.875052 1.672079 5.034287 6.291348 1.534257 4.610483
3: Mar. 2024 7.104641 1.902356 5.060439 7.329138 1.998110 5.163713 6.743478 1.840379 4.761253
4: Apr. 2024 8.578222 2.158071 6.280444 8.843422 2.265896 6.408617 8.254928 2.105491 6.009730
5: May. 2024 9.885240 2.284334 7.465149 10.178196 2.394606 7.617499 9.660175 2.249601 7.274817
6: Jun. 2024 11.293417 2.230338 8.920381 11.606533 2.329653 9.102430 11.089573 2.201739 8.745137
7: Jul. 2024 11.495648 1.948530 9.397421 11.801533 2.029150 9.589205 11.282303 1.921596 9.211011
8: Aug. 2024 10.493150 1.869393 8.468140 10.777404 1.947410 8.640959 10.154416 1.824754 8.174045
9: Sep. 2024 8.584604 1.864962 6.564518 8.831006 1.948075 6.698488 8.177410 1.802375 6.219910
10: Oct. 2024 6.226290 1.631551 4.455104 6.418653 1.711039 4.546024 5.950189 1.583714 4.226840
11: Nov. 2024 6.076159 1.393353 4.545523 6.247341 1.452953 4.638289 5.705306 1.330740 4.237284
12: Dec. 2024 4.685547 1.198824 3.370992 4.825181 1.254616 3.439788 4.440179 1.155239 3.169210

Yearly values:
  Dates      Gef0d    Def0d    Bef0d      Gd      Dd      Bd      Gefd    Defd    Befd
  <int>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>
1: 2024 2973.115 654.591 2266.733 3058.651 684.4232 2312.993 2856.633 636.0199 2168.822
-----
Mode of tracking: two
Inclination limit: 90

```

- **prom**: cuando **modeTrk** es **two**, se puede calcular el efecto de las sombras de un seguidor promedio.

```

1 gef_shdprom <- calcGef(lat, modeTrk = 'two', dataRad = prom,
2                       modeShd = c('area', 'prom'),
3                       struct = struct, distances = distances)
4 show(gef_shdprom)

```

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
  Dates      Gef0d    Def0d    Bef0d      Gd      Dd      Bd      Gefd    Defd    Befd
  <char>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>
1: Jan. 2024 6.348801 1.384087 4.825736 6.522313 1.440413 4.924221 6.104126 1.343455 4.621693
2: Feb. 2024 6.680139 1.599929 4.933601 6.875052 1.672079 5.034287 6.406274 1.553670 4.705996
3: Mar. 2024 7.104641 1.902356 5.060439 7.329138 1.998110 5.163713 6.788630 1.848127 4.798657
4: Apr. 2024 8.578222 2.158071 6.280444 8.843422 2.265896 6.408617 8.295340 2.112064 6.043569
5: May. 2024 9.885240 2.284334 7.465149 10.178196 2.394606 7.617499 9.688308 2.253942 7.298609
6: Jun. 2024 11.293417 2.230338 8.920381 11.606533 2.329653 9.102430 11.115054 2.205314 8.767042
7: Jul. 2024 11.495648 1.948530 9.397421 11.801533 2.029150 9.589205 11.308971 1.924962 9.234312
8: Aug. 2024 10.493150 1.869393 8.468140 10.777404 1.947410 8.640959 10.196758 1.830334 8.210807
9: Sep. 2024 8.584604 1.864962 6.564518 8.831006 1.948075 6.698488 8.228309 1.810198 6.262986
10: Oct. 2024 6.226290 1.631551 4.455104 6.418653 1.711039 4.546024 6.018374 1.595528 4.283212
11: Nov. 2024 6.076159 1.393353 4.545523 6.247341 1.452953 4.638289 5.875732 1.359514 4.378935
12: Dec. 2024 4.685547 1.198824 3.370992 4.825181 1.254616 3.439788 4.575893 1.179346 3.280817

Yearly values:

```

```

      Dates      Gef0d      Def0d      Bef0d      Gd      Dd      Bd      Gefd      Defd      Befd
      <int>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1:  2024 2973.115 654.591 2266.733 3058.651 684.4232 2312.993 2886.328 640.9157 2193.621
-----
Mode of tracking: two
Inclination limit: 90

```

- **bt**: cuando **modeTrk** es **horiz**, se puede calcular el efecto del *backtracking* en las sombras.

```

1 gef_shdhoriz <- calcGef(lat, modeTrk = 'horiz', dataRad = prom,
2                       modeShd = 'area',
3                       struct = struct, distances = distances)
4 show(gef_shdhoriz)

```

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
      Dates      Gef0d      Def0d      Bef0d      Gd      Dd      Bd      Gefd      Defd      Befd
      <char>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1: Jan. 2024  4.274445  1.0909303  3.118987  4.528022  1.166334  3.285391  3.826940  1.0166151  2.745797
2: Feb. 2024  5.173537  1.3974587  3.699745  5.414413  1.484046  3.839622  4.709780  1.3191237  3.314324
3: Mar. 2024  6.270377  1.8008592  4.379272  6.512568  1.906181  4.498391  5.856407  1.7298195  4.036342
4: Apr. 2024  8.160354  2.1103041  5.938446  8.429640  2.222836  6.072611  7.744288  2.0426359  5.590049
5: May. 2024  9.639011  2.2544315  7.260788  9.932830  2.366831  7.416258  9.158384  2.1802588  6.854334
6: Jun. 2024 11.005388  2.1942042  8.675874 11.320680  2.294944  8.861907 10.355140  2.1029750  8.116855
7: Jul. 2024 11.220872  1.9183453  9.163290 11.527430  2.000253  9.358648 10.747413  1.8585724  8.749603
8: Aug. 2024 10.066277  1.8239013  8.112148 10.352216  1.904515  8.290847  9.601132  1.7626031  7.708301
9: Sep. 2024  7.732062  1.7621525  5.864625  7.991813  1.852070  6.013507  7.317424  1.6984219  5.513717
10: Oct. 2024 5.023316  1.4757157  3.471271  5.250215  1.568278  3.591050  4.691499  1.4182254  3.196944
11: Nov. 2024 4.211801  1.1318865  3.014748  4.452659  1.209397  3.166130  3.846165  1.0701542  2.710845
12: Dec. 2024 3.024846  0.9640813  2.008270  3.237139  1.039367  2.135901  2.849995  0.9330218  1.864479

Yearly values:
      Dates      Gef0d      Def0d      Bef0d      Gd      Dd      Bd      Gefd      Defd      Befd
      <int>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>      <num>
1:  2024 2618.414 607.6589 1975.038 2714.415 640.9193 2030.645 2463.159 583.5528 1843.889
-----
Mode of tracking: horiz
Inclination limit: 90

```

```

1 gef_shdbt <- calcGef(lat, modeTrk = 'horiz', dataRad = prom,
2                       modeShd = c('area', 'bt'),
3                       struct = struct, distances = distances)
4 show(gef_shdbt)

```

```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
      Dates      Bod      Bnd      Gd      Dd      Bd      Gefd      Defd      Befd

```

```

    <char>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>
1: Jan. 2024  8.071623  4.924221  4.069604  1.101792  2.902196  3.802336  1.0232875  2.724604
2: Feb. 2024 10.170791  5.034287  4.943127  1.417056  3.445443  4.680459  1.3258434  3.287780
3: Mar. 2024 12.816149  5.163713  6.094523  1.850253  4.148386  5.841685  1.7419635  4.020914
4: Apr. 2024 15.326568  6.408617  8.007438  2.166491  5.716983  7.711198  2.0485357  5.560571
5: May. 2024 16.624320  7.617499  9.439815  2.303156  7.000336  9.132906  2.1878882  6.833933
6: Jun. 2024 17.408383  9.102430 10.652929  2.206022  8.288629 10.286974  2.0977541  8.059004
7: Jul. 2024 16.861601 10.037233 11.038213  1.944739  8.935057 10.701158  1.8585291  8.712900
8: Aug. 2024 15.551202  8.640959  9.872463  1.850828  7.878525  9.562356  1.7662720  7.678732
9: Sep. 2024 13.422796  6.698488  7.568105  1.795358  5.655421  7.285297  1.7012821  5.487114
10: Oct. 2024 10.764846  4.546024  4.915408  1.521915  3.310678  4.666904  1.4246602  3.173452
11: Nov. 2024  8.434950  4.638289  4.079866  1.156410  2.854293  3.813241  1.0737415  2.681776
12: Dec. 2024  7.370928  3.439788  3.062505  1.023011  1.987550  2.836653  0.9441838  1.849321

Yearly values:
  Dates      Bod      Bnd      Gd      Dd      Bd      Gefd      Defd      Befd
<int>    <num>    <num>    <num>    <num>    <num>    <num>    <num>    <num>
1: 2024 4662.615 2326.882 2555.869 620.2896 1896.422 2451.499 585.4392 1833.809
-----
Mode of tracking: horiz
Inclination limit: 90

```

4.5. Producción eléctrica de un SFCR

Con la radiación efectiva, se puede estimar la producción eléctrica que va a tener un sistema fotovoltaico conectado a red. Esta estimación, se puede calcular mediante la función **prodGCPV** [??] la cual mediante la función **fProd** [??] procesa un objeto de clase **Gef** y obtiene un objeto **ProdGCPV**.

Como se puede ver en la figura 4.6, **prodGCPV** funciona gracias a la siguiente función:

- **fProd**: simula el comportamiento de un sistema fotovoltaico conectado a red bajo diferentes condiciones de temperatura e irradiancia. Tiene los siguientes argumentos:
 - **inclin**: puede ser tanto un objeto de clase **Gef** como un **data.frame** (o **data.table**). Sin embargo, si es un **data.frame**, debe contener como mínimo una columna para **Gef** y otra para **Ta**
 - **module**: una lista de valores numéricos con la información sobre el módulo fotovoltaico:
 - **Vocn**: tensión de circuito abierto en STC (V_{oc}^*)(condiciones estandar de medida). Por defecto, tiene un valor de 57,2V.




FIGURA 4.6: Estimación de la producción eléctrica de un SFCR mediante la función **prodGCPV**, la cual emplea la función **fProd** para el computo de la potencia a la entrada (P_{DC}), a la salida (P_{AC}) y el rendimiento (η_{inv}) del inversor.

- **Iscn**: corriente de cortocircuito en STC (I_{sc}^*). Por defecto, tiene un valor de 4,7A.
- **Vmn**: tensión en el punto de máxima potencia en STC (I_{MPP}^*). Por defecto, tiene un valor de 46,08V.
- **Imn**: corriente de cortocircuito en STC (I_{MPP}^*). Por defecto, tiene un valor de 4,35A).
- **Ncs**: número de células en serie dentro del módulo. Por defecto, tiene un valor de 96.
- **Ncp**: número de células en paralelo dentro del módulo. Por defecto, tiene un valor de 1.
- **CoefVT**: coeficiente de disminución de la tensión de cada célula con la temperatura (dV_{oc}/dT_c). Por defecto, tiene un valor de $-0,0023V/^{\circ}C$.
- **TONC**: temperatura de operación nominal de célula ($TONC$). Por defecto, tiene un valor de $47^{\circ}C$.
- **generator**: lista de valores numéricos con la información sobre el generador:
 - **Nms**: número de módulos en serie. Por defecto, tiene un valor de 12.
 - **Nmp**: número de módulos en paralelo. Por defecto, tiene un valor de 11.
- **inverter**: lista de valores numéricos con la información del inversor DC/AC.
 - **Ki**: coeficientes de la curva de eficiencia del inversor. Se puede presentar en un vector de 3 valores (por defecto, **c(0.01, 0.025, 0.05)**) o una matriz de 9 valores (si tiene dependencia del voltage).
 - **Pinv**: potencia nominal del inversor. Por defecto, tiene un valor de 25000W.
 - **Vmin**: mínima tensión del rango MPP del inversor. Por defecto, tiene un valor de 420V.
 - **Vmax**: máxima tensión del rango MPP del inversor. Por defecto, tiene un valor de 750V.
 - **Gumb**: irradiancia umbral de funcionamiento del inversor. Por defecto, tiene un valor de $20W/m^2$.
- **effSys**: una lista de valores numéricos con la información sobre las pérdidas del sistema.
 - **ModQual**: tolerancia media del set de módulos (%). Por defecto, tiene un valor de 3.
 - **ModDisp**: pérdidas por dispersión en los módulos (%). Por defecto, tiene un valor de 2.
 - **OhmDC**: pérdidas por efecto Joule en el cableado de DC (%). Por defecto, tiene un valor de 1.5.
 - **OhmAC**: pérdidas por efecto Joule en el cableado de AC (%). Por defecto, tiene un valor de 1.5.
 - **MPP**: error promedio del algoritmo de búsqueda del MPP del inversor (%). Por defecto, tiene un valor de 1.
 - **TrafoMT**: pérdidas por el transformador MT (%). Por defecto, tiene un valor de 1.
 - **Disp**: pérdidas por las paradas del sistema (%). Por defecto, tiene un valor de 0.5.

```
1 inclin <- calcGef(lat, dataRad = prom, keep.night = FALSE)
2 module <- list(Vocn=57.6, Iscn=4.7, Vmn=46.08, Imn=4.35,
3               Ncs=96, Ncp=1, CoefVT=0.0023, TONC=47)
```

```

4 generator <- list(Nms=12, Nmp=11)
5 inverter <- list(Ki=c(0.01, 0.025, 0.05), Pinv=25000,
6               Vmin=420, Vmax=750, Gumb=20)
7 effSys <- list(ModQual=3, ModDisp=2, OhmDC=1.5, OhmAC=1.5,
8               MPP=1, TrafoMT=1, Disp=0.5)
9 prod <- fProd(inclin = inclin, module = module,
10             generator = generator, inverter = inverter,
11             effSys = effSys)
12 show(prod)

```

	Dates <POS<	Tc <num>	Voc <num>	Isc <num>	Vmpp <num>	Imp <num>	Vdc <num>	Idc <num>	Pac <num>
1:	2024-01-17 08:00:00	15.27689	716.9624	8.083413	607.4640	7.620135	607.4640	7.620135	3796.209
2:	2024-01-17 09:00:00	21.43284	700.6516	17.513415	583.9663	16.433741	583.9663	16.433741	8053.912
3:	2024-01-17 10:00:00	27.23609	685.2753	26.403138	562.0190	24.658263	562.0190	24.658263	11650.920
4:	2024-01-17 11:00:00	31.48724	674.0114	32.915263	546.0746	30.625265	546.0746	30.625265	14041.629
5:	2024-01-17 12:00:00	33.33104	669.1261	35.739693	539.1958	33.196772	539.1958	33.196772	15016.481

141:	2024-12-13 12:00:00	33.94967	667.4869	28.721724	542.4718	26.706186	542.4718	26.706186	12177.570
142:	2024-12-13 13:00:00	32.55186	671.1906	26.580476	547.6944	24.746716	547.6944	24.746716	11395.331
143:	2024-12-13 14:00:00	29.08872	680.3665	21.275466	560.6878	19.868077	560.6878	19.868077	9362.088
144:	2024-12-13 15:00:00	24.29331	693.0724	13.929608	578.8034	13.059814	578.8034	13.059814	6316.091
145:	2024-12-13 16:00:00	19.21305	706.5331	6.147403	598.1441	5.786102	598.1441	5.786102	2784.663

	Pdc <num>	EffI <num>							
1:	4290.940	0.9118076							
2:	8895.974	0.9330800							
3:	12846.437	0.9347232							
4:	15502.477	0.9335163							
5:	16592.492	0.9327431							

141:	13429.451	0.9345615							
142:	12563.918	0.9347755							
143:	10326.335	0.9343983							
144:	7007.083	0.9290019							
145:	3208.198	0.8945754							

Esta función brinda estos datos a la función **prodGCPV** para que produzca un objeto de clase **ProdGCPV** como resultado. Esta función tiene como argumentos principales los mismo que **calcGef**, ya que parte de un objeto tipo **Gef**, y los argumentos de la función **fProd**.

```

1 prodFixed <- prodGCPV(lat, modeTrk = 'fixed', dataRad = prom)
2 show(prodFixed)

```

```

Object of class  ProdGCPV

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
  Dates      Eac      Edc      Yf
  <char>    <num>    <num>    <num>
1: Jan. 2024  95.36291 105.62767 3.604158
2: Feb. 2024 101.50809 112.56166 3.836410
3: Mar. 2024 110.26945 122.11835 4.167538
4: Apr. 2024 124.53728 138.29836 4.706778
5: May. 2024 131.48629 145.91065 4.969410
6: Jun. 2024 135.89421 150.78725 5.136003
7: Jul. 2024 134.98501 149.81246 5.101641
8: Aug. 2024 130.25804 144.39951 4.922989

```

4. DESARROLLO DEL CÓDIGO

```
9: Sep. 2024 119.91911 132.77648 4.532238
10: Oct. 2024 96.49455 106.99182 3.646928
11: Nov. 2024 90.17737 99.88152 3.408175
12: Dec. 2024 73.89289 81.80967 2.792718
```

Yearly values:

	Dates	Eac	Edc	Yf
	<int>	<num>	<num>	<num>
1:	2024	41014.8	45473.37	1550.119

Mode of tracking: fixed

Inclination: 27.2

Orientation: 0

Generator:

Modules in series: 12

Modules in parallel: 11

Nominal power (kWp): 26.5

```
1 prod2x <- prodGCPV(lat, modeTrk = 'two', dataRad = prom)
2 show(prod2x)
```

Object of class ProdGCPV

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

	Dates	Eac	Edc	Yf
	<char>	<num>	<num>	<num>
1:	Jan. 2024	138.6806	153.2566	5.241314
2:	Feb. 2024	143.4987	158.5247	5.423408
3:	Mar. 2024	151.8477	167.7311	5.738952
4:	Apr. 2024	178.6717	197.4274	6.752741
5:	May. 2024	200.8888	222.0523	7.592419
6:	Jun. 2024	223.9959	247.6903	8.465728
7:	Jul. 2024	214.2749	236.9628	8.098332
8:	Aug. 2024	194.6043	215.1439	7.354902
9:	Sep. 2024	168.9824	186.7349	6.386542
10:	Oct. 2024	132.2995	146.0747	5.000145
11:	Nov. 2024	128.5783	141.9871	4.859507
12:	Dec. 2024	102.9116	113.5613	3.889454

Yearly values:

	Dates	Eac	Edc	Yf
	<int>	<num>	<num>	<num>
1:	2024	60369.04	66710.67	2281.595

Mode of tracking: two

Inclination limit: 90

Generator:

Modules in series: 12

Modules in parallel: 11

Nominal power (kWp): 26.5

```
1 prodHoriz <- prodGCPV(lat, modeTrk = 'horiz', dataRad = prom)
2 show(prodHoriz)
```

Object of class ProdGCPV

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

	Dates	Eac	Edc	Yf
	<char>	<num>	<num>	<num>
1:	Jan. 2024	99.43006	109.66074	3.757873
2:	Feb. 2024	116.24796	128.22238	4.393490
3:	Mar. 2024	137.39485	151.61074	5.192719
4:	Apr. 2024	172.03044	189.97488	6.501741
5:	May. 2024	196.91337	217.61396	7.442169
6:	Jun. 2024	219.15566	242.31468	8.282797
7:	Jul. 2024	210.33644	232.56087	7.949482
8:	Aug. 2024	189.03576	208.87993	7.144442
9:	Sep. 2024	156.22909	172.44519	5.904542
10:	Oct. 2024	110.69482	122.11859	4.183614
11:	Nov. 2024	94.40734	104.14723	3.568043
12:	Dec. 2024	69.94550	77.30532	2.643529

Yearly values:

	Dates	Eac	Edc	Yf
	<int>	<num>	<num>	<num>
1:	2024	54052.14	59697.16	2042.854

Mode of tracking: horiz
Inclination limit: 90

Generator:

Modules in series: 12
Modules in parallel: 11
Nominal power (kWp): 26.5

4.6. Producción eléctrica de un SFB

De igual forma que en el apartado anterior, se puede estimar la producción eléctrica de un sistema fotovoltaico de bombeo.

Como se puede ver en la figura 4.7, **prodPVPS** funciona gracias a la siguiente función:

- **fPump**: calcula el rendimiento de las diferentes partes de una bomba centrífuga alimentada por un convertidor de frecuencia siguiendo las leyes de afinidad. Tiene solo dos argumentos:
 - **pump**: lista que contiene los parametros de la bomba que va a ser simulada. Puede ser una fila de **pumpCoef**:




FIGURA 4.7: Estimación de la producción eléctrica de un SFB mediante la función **prodPVPS**, la cual emplea la función **fPump** para el computo del rendimiento de las diferentes parte de una bomba centrífuga alimentada por un convertidor de frecuencia.

```
1 CoefSP8A44 <- pumpCoef[Qn == 8 & stages == 44]
2 show(CoefSP8A44)
```

	Qn	stages	Qmax	Pmn	a	b	c	g	h	i	j	k	l
	<int>	<int>	<num>	<int>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1:	8	44	12	7500	0.1043011	-0.101288	-0.726	-0.24	0.42	0.64	-0.0058	0.095	0.2013

- **H**: el salto manometrico total.

```
1 fSP8A44 <- fPump(pump = CoefSP8A44, H = 40)
```

Obtiene como resultado los siguientes valores y funciones:

- **lim**: rango de valores de la potencia eléctrica de salida.

```
1 show(fSP8A44$lim)
```

```
[1] 190.100 4084.218
```

- **fQ**: función que relaciona el caudal con la potencia eléctrica.

```
1 show(fSP8A44$fQ)
```

```
function (x, deriv = 0L)
{
  deriv <- as.integer(deriv)
  if (deriv < 0L || deriv > 3L)
    stop("'deriv' must be between 0 and 3")
  if (deriv > 0L) {
    z0 <- double(z$n)
    z[c("y", "b", "c")] <- switch(deriv, list(y = z$b, b = 2 *
      z$c, c = 3 * z$d), list(y = 2 * z$c, b = 6 * z$d,
      c = z0), list(y = 6 * z$d, b = z0, c = z0))
    z[["d"]] <- z0
  }
  res <- .splinefun(x, z)
  if (deriv > 0 && z$method == 2 && any(ind <- x <= z$x[1L]))
    res[ind] <- ifelse(deriv == 1, z$y[1L], 0)
  res
}
<bytecode: 0x00000241cd298748>
<environment: 0x00000241cd29cda0>
```

- **fPb**: función que relaciona la potencia del eje de la bomba con la potencia eléctrica del motor.

```
1 show(fSP8A44$fPb)
```

```
function (x, deriv = 0L)
{
  deriv <- as.integer(deriv)
  if (deriv < 0L || deriv > 3L)
    stop("'deriv' must be between 0 and 3")
  if (deriv > 0L) {
    z0 <- double(z$n)
    z[c("y", "b", "c")] <- switch(deriv, list(y = z$b, b = 2 *
      z$c, c = 3 * z$d), list(y = 2 * z$c, b = 6 * z$d,
      c = z0), list(y = 6 * z$d, b = z0, c = z0))
    z[["d"]] <- z0
  }
  res <- .splinefun(x, z)
  if (deriv > 0 && z$method == 2 && any(ind <- x <= z$x[1L]))
```

```

      res[ind] <- ifelse(deriv == 1, z$y[1L], 0)
    res
  }
  <bytecode: 0x00000241cd298748>
  <environment: 0x00000241cd311e08>

```

- **fPh**: función que relaciona la potencia hidráulica con la potencia eléctrica del motor.

```
1 show(fSP8A44$fPh)
```

```

function (x, deriv = 0L)
{
  deriv <- as.integer(deriv)
  if (deriv < 0L || deriv > 3L)
    stop("'deriv' must be between 0 and 3")
  if (deriv > 0L) {
    z0 <- double(z$n)
    z[c("y", "b", "c")] <- switch(deriv, list(y = z$b, b = 2 *
      z$c, c = 3 * z$d), list(y = 2 * z$c, b = 6 * z$d,
      c = z0), list(y = 6 * z$d, b = z0, c = z0))
    z[["d"]] <- z0
  }
  res <- .splinefun(x, z)
  if (deriv > 0 && z$method == 2 && any(ind <- x <= z$x[1L]))
    res[ind] <- ifelse(deriv == 1, z$y[1L], 0)
  res
}
<bytecode: 0x00000241cd298748>
<environment: 0x00000241cd32cd30>

```

- **fFreq**: función que relaciona la frecuencia con la potencia eléctrica del motor.

```
1 show(fSP8A44$fFreq)
```

```

function (x, deriv = 0L)
{
  deriv <- as.integer(deriv)
  if (deriv < 0L || deriv > 3L)
    stop("'deriv' must be between 0 and 3")
  if (deriv > 0L) {
    z0 <- double(z$n)
    z[c("y", "b", "c")] <- switch(deriv, list(y = z$b, b = 2 *
      z$c, c = 3 * z$d), list(y = 2 * z$c, b = 6 * z$d,
      c = z0), list(y = 6 * z$d, b = z0, c = z0))
    z[["d"]] <- z0
  }
  res <- .splinefun(x, z)
  if (deriv > 0 && z$method == 2 && any(ind <- x <= z$x[1L]))
    res[ind] <- ifelse(deriv == 1, z$y[1L], 0)
  res
}
<bytecode: 0x00000241cd298748>
<environment: 0x00000241cd2be128>

```

Se pueden realizar operaciones con este objeto:

```

1 SP8A44 = with(fSP8A44,{
2   Pac = seq(lim[1],lim[2],l=10)
3   Pb = fPb(Pac)
4   etam = Pb/Pac
5   Ph = fPh(Pac)
6   etab = Ph/Pb
7   f = fFreq(Pac)
8   Q = fQ(Pac)
9   result = data.table(Q,Pac,Pb,Ph,etam,etab,f)})
10 show(SP8A44)

```

	Q <num>	Pac <num>	Pb <num>	Ph <num>	etam <num>	etab <num>	f <num>
1:	0.3133325	190.1000	124.8346	34.15325	0.6566786	0.2735880	20.47033
2:	2.0718468	622.7798	429.6728	225.83130	0.6899274	0.5255890	22.33036
3:	4.0764128	1055.4595	752.8970	444.32900	0.7133358	0.5901591	25.51459
4:	5.6406747	1488.1393	1087.3665	614.83354	0.7306887	0.5654336	28.73213
5:	6.9474993	1920.8190	1429.7984	757.27743	0.7443692	0.5296393	31.78514
6:	8.1028841	2353.4988	1778.0156	883.21437	0.7554776	0.4967416	34.69527
7:	9.1607296	2786.1786	2130.4683	998.51953	0.7646560	0.4686855	37.49608
8:	10.1514390	3218.8583	2486.0213	1106.50685	0.7723301	0.4450915	40.21428
9:	11.0937480	3651.5381	2843.8295	1209.21854	0.7788032	0.4252078	42.86977
10:	12.0000000	4084.2179	3203.2578	1308.00000	0.7843014	0.4083343	45.47737

Esta función entrega todos estos resultados a **prodPVPS** la cual calcula los resultados en base a la potencia del generador a simular, y devuelve un objeto de clase **ProdPVPS**.

```

1 prodsfb <- prodPVPS(lat, modeTrk = 'fixed', dataRad = prom,
2                       pump = CoefSP8A44, H = 40, Pg = SP8A44$Pac[10])
3 show(prodsfb)

```

```

Object of class  ProdPVPS

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      Eac      Qd      Yf
      <char>    <num>    <num>    <num>
1: Jan. 2024  14.07129  50.46621  3.445284
2: Feb. 2024  15.43701  54.71213  3.779675
3: Mar. 2024  17.00102  59.68995  4.162613
4: Apr. 2024  19.39135  67.24260  4.747874
5: May. 2024  20.65046  71.34195  5.056160
6: Jun. 2024  21.63947  74.27359  5.298315
7: Jul. 2024  22.62915  76.77927  5.540633
8: Aug. 2024  22.17136  75.07166  5.428546
9: Sep. 2024  19.61622  67.34348  4.802932
10: Oct. 2024  14.92078  53.24853  3.653277
11: Nov. 2024  13.75298  49.50040  3.367348
12: Dec. 2024  11.21349  40.90244  2.745567

Yearly values:
      Dates      Eac      Qd      Yf
      <int>    <num>    <num>    <num>
1: 2024  6482.059  22589.95  1587.099
-----
Mode of tracking:  fixed
  Inclination:    27.2
  Orientation:    0
-----
Pump:
  Qn: 8
  Stages: 44
Height (m): 40
Generator (Wp): 4084.218

```

4.7. Optimización de distancias

Por último, el paquete **solar2** contiene una función que permite calcular un conjunto de combinaciones de distancias entre los elementos de un sistema fotovoltaico conectado a red, con

el fin de que el usuario posteriormente pueda optar cual es la opción mas rentable en base a los precios del cableado y de la ocupación del terreno.

Esta función es **optimShd**, la cual en base a una resolución (determinada por el argumento **res**, el cual, indica el incremento de la secuencia de distancias) obtiene la producción de cada combinación y la plasma en un objeto de clase **Shade**.

```

1 struct2x <- list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 3)
2 dist2x <- list(Lew = c(30, 45), Lns = c(20, 40))
3 ShdM2x <- optimShd(lat, dataRad = prom, modeTrk = 'two',
4                   modeShd = c('area', 'prom'),
5                   distances = dist2x, struct = struct2x,
6                   res = 5,
7                   prog = FALSE) #Se quita la barra de progreso
8 show(ShdM2x)

```

```

Object of class  Shade

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
Dimensions of structure:
$W
[1] 23.11

$L
[1] 9.8

$Nrow
[1] 2

$Ncol
[1] 3

Shade calculation mode:
[1] "area" "prom"
Productivity without shadows:
Object of class  ProdGCPV

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
  Dates      Eac      Edc      Yf
  <char>    <num>    <num>    <num>
1: Jan. 2024 138.6806 153.2566 5.241314
2: Feb. 2024 143.4987 158.5247 5.423408
3: Mar. 2024 151.8477 167.7311 5.738952
4: Apr. 2024 178.6717 197.4274 6.752741
5: May. 2024 200.8888 222.0523 7.592419
6: Jun. 2024 223.9959 247.6903 8.465728
7: Jul. 2024 214.2749 236.9628 8.098332
8: Aug. 2024 194.6043 215.1439 7.354902
9: Sep. 2024 168.9824 186.7349 6.386542
10: Oct. 2024 132.2995 146.0747 5.000145
11: Nov. 2024 128.5783 141.9871 4.859507
12: Dec. 2024 102.9116 113.5613 3.889454

Yearly values:
  Dates      Eac      Edc      Yf
  <int>    <num>    <num>    <num>
1: 2024 60369.04 66710.67 2281.595

```

```

-----
Mode of tracking: two
Inclination limit: 90
-----
Generator:
  Modules in series: 12
  Modules in parallel: 11
  Nominal power (kWp): 26.5

Summary of results:

```

Lew		Lns		H		FS		GRR		Yf	
Min.	:30.00	Min.	:20	Min.	:0	Min.	:0.01509	Min.	:2.649	Min.	:2104
1st Qu.	:33.75	1st Qu.	:25	1st Qu.	:0	1st Qu.	:0.02223	1st Qu.	:3.946	1st Qu.	:2192
Median	:37.50	Median	:30	Median	:0	Median	:0.02870	Median	:4.802	Median	:2216
Mean	:37.50	Mean	:30	Mean	:0	Mean	:0.03463	Mean	:4.967	Mean	:2203
3rd Qu.	:41.25	3rd Qu.	:35	3rd Qu.	:0	3rd Qu.	:0.03945	3rd Qu.	:6.016	3rd Qu.	:2231
Max.	:45.00	Max.	:40	Max.	:0	Max.	:0.07769	Max.	:7.948	Max.	:2247

```

1 structHoriz = list(L = 4.83)
2 distHoriz = list(Lew = structHoriz$L * c(2,5))
3 Shd12HorizBT <- optimShd(lat = lat, dataRad = prom,
4                           modeTrk = 'horiz',
5                           betaLim = 60,
6                           distances = distHoriz, res = 2,
7                           struct = structHoriz,
8                           modeShd = 'bt',
9                           prog = FALSE) #Se quita la barra de progreso
10 show(Shd12HorizBT)

```

```

Object of class Shade

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
Dimensions of structure:
$L
[1] 4.83

Shade calculation mode:
[1] "bt"
Productivity without shadows:
Object of class ProdGCPV

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:

```

	Dates	Eac	Edc	Yf
	<char>	<num>	<num>	<num>
1: Jan. 2024	97.48365	107.53823	3.684309	
2: Feb. 2024	114.31569	126.11751	4.320462	
3: Mar. 2024	135.67629	149.74056	5.127767	
4: Apr. 2024	170.28530	188.06424	6.435785	
5: May. 2024	194.83600	215.33865	7.363657	
6: Jun. 2024	216.37522	239.26256	8.177713	
7: Jul. 2024	208.20413	230.21074	7.868894	
8: Aug. 2024	187.19428	206.84745	7.074845	
9: Sep. 2024	154.37402	170.41035	5.834432	
10: Oct. 2024	109.27362	120.57435	4.129901	
11: Nov. 2024	92.82584	102.42576	3.508272	
12: Dec. 2024	69.13228	76.42401	2.612794	

```

Yearly values:
  Dates      Eac      Edc      Yf
  <int>      <num>      <num>      <num>
1:  2024 53386.77 58969.19 2017.707
-----
Mode of tracking:  horiz
Inclination limit: 60
-----
Generator:
  Modules in series: 12
  Modules in parallel: 11
  Nominal power (kWp): 26.5

Summary of results:
      Lew      H      FS      GRR      Yf
Min.   : 9.66  Min.   :0  Min.   :0.04804  Min.   :2.000  Min.   :1736
1st Qu.:13.16  1st Qu.:0  1st Qu.:0.05727  1st Qu.:2.725  1st Qu.:1824
Median :16.66  Median :0  Median :0.07295  Median :3.449  Median :1871
Mean   :16.66  Mean   :0  Mean   :0.08078  Mean   :3.449  Mean   :1855
3rd Qu.:20.16  3rd Qu.:0  3rd Qu.:0.09598  3rd Qu.:4.174  3rd Qu.:1902
Max.   :23.66  Max.   :0  Max.   :0.13968  Max.   :4.899  Max.   :1921

```

```

1 structFixed = list(L = 5)
2 distFixed = list(D = structFixed$L*c(1,3))
3 Shd12Fixed <- optimShd(lat = lat, dataRad = prom,
4                       modeTrk = 'fixed',
5                       distances = distFixed, res = 2,
6                       struct = structFixed,
7                       modeShd = 'area',
8                       prog = FALSE) #Se quita la barra de progreso
9 show(Shd12Fixed)

```

```

Object of class  Shade

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
Dimensions of structure:
$L
[1] 5

Shade calculation mode:
[1] "area"
Productivity without shadows:
Object of class  ProdGCPV

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:
      Dates      Eac      Edc      Yf
      <char>      <num>      <num>      <num>
1: Jan. 2024  95.36291 105.62767 3.604158
2: Feb. 2024 101.50809 112.56166 3.836410
3: Mar. 2024 110.26945 122.11835 4.167538
4: Apr. 2024 124.53728 138.29836 4.706778
5: May. 2024 131.48629 145.91065 4.969410
6: Jun. 2024 135.89421 150.78725 5.136003
7: Jul. 2024 134.98501 149.81246 5.101641
8: Aug. 2024 130.25804 144.39951 4.922989

```

```
9: Sep. 2024 119.91911 132.77648 4.532238
10: Oct. 2024 96.49455 106.99182 3.646928
11: Nov. 2024 90.17737 99.88152 3.408175
12: Dec. 2024 73.89289 81.80967 2.792718

Yearly values:
  Dates      Eac      Edc      Yf
  <int>    <num>    <num>    <num>
1: 2024 41014.8 45473.37 1550.119
-----
Mode of tracking: fixed
Inclination: 27.2
Orientation: 0
-----
Generator:
  Modules in series: 12
  Modules in parallel: 11
  Nominal power (kWp): 26.5

Summary of results:
      D      H      FS      GRR      Yf
Min.   : 5.0  Min.   :0  Min.   :0.0008477  Min.   :1.0  Min.   :1364
1st Qu.: 7.5  1st Qu.:0  1st Qu.:0.0015710  1st Qu.:1.5  1st Qu.:1511
Median :10.0  Median :0  Median :0.0038992  Median :2.0  Median :1544
Mean   :10.0  Mean   :0  Mean   :0.0269608  Mean   :2.0  Mean   :1508
3rd Qu.:12.5  3rd Qu.:0  3rd Qu.:0.0252790  3rd Qu.:2.5  3rd Qu.:1548
Max.   :15.0  Max.   :0  Max.   :0.1199180  Max.   :3.0  Max.   :1549
```

4.8. Métodos de visualización

Una vez creados todos los objetos, para mejorar la visualización de los mismos, `solar2` cuenta con una serie de métodos que ayudan a la compresión de los datos obtenidos.

4.8.1. Datos meteorológicos

La clase `Meteo` cuenta con un método para `xyplot`.


```
1 lat <- 37.2
2 G0dm = c(2.766,3.491,4.494,5.912,6.989,7.742,
3         7.919,7.027,5.369,3.562,2.814,2.179) * 1000;
4 Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2,
5        28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
6 BD <- readG0dm(G0dm = G0dm, Ta = Ta, lat = lat)
7 show(BD)
```

```
Object of class  Meteo

Source of meteorological information: prom-
Latitude of source: 37.2 degrees

Meteorological Data:
  Dates      G0d      Ta
Min.   :2024-01-17  Min.   :2179  Min.   :10.00
1st Qu.:2024-04-07  1st Qu.:3322  1st Qu.:15.50
Median :2024-06-29  Median :4932  Median :17.70
Mean   :2024-07-01  Mean   :5022  Mean   :19.22
3rd Qu.:2024-09-25  3rd Qu.:6998  3rd Qu.:21.98
Max.   :2024-12-13  Max.   :7919  Max.   :29.90
```

```
1 xyplot(BD)
```

4.8.2. Radiación en el plano horizontal

La clase **G0** cuenta con un método para **xyplot**.

```
1 g0 <- calcG0(lat, dataRad = BD)
2 show(g0)
```

```
Object of class  G0


Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      G0d      D0d      B0d
  <char> <num>    <num>    <num>
1: Jan. 2024  2.766  0.941698  1.824302
2: Feb. 2024  3.491  1.247146  2.243854
3: Mar. 2024  4.494  1.671763  2.822237
4: Apr. 2024  5.912  1.931146  3.980854
5: May. 2024  6.989  2.023364  4.965636
6: Jun. 2024  7.742  1.889994  5.852006
7: Jul. 2024  7.919  1.624064  6.294936
8: Aug. 2024  7.027  1.547591  5.479409
9: Sep. 2024  5.369  1.540708  3.828292
10: Oct. 2024  3.562  1.374513  2.187487
11: Nov. 2024  2.814  1.006959  1.807041
12: Dec. 2024  2.179  0.926737  1.252263


Yearly values:
      Dates      G0d      D0d      B0d
  <int>    <num>    <num>    <num>
1: 2024 1839.365  540.6331 1298.732
```

```
1 xyplot(g0)
```



Y con un método para **compare**.

```
1 g02 <- calcG0(lat, dataRad = list(G0dm = G0dm*0.95, Ta = Ta))
2 compare(g0, g02)
```



4.8.3. Radiación efectiva en el plano del generador

La clase **Gef** cuenta con un método para **xyplot**.

```
1 gef <- calcGef(lat, dataRad = BD)
2 show(gef)
```

Object of class Gef

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees

Monthly avarages:


	Dates	Bod	Bnd	Gd	Dd	Bd	Gefd	Defd	Befd
	<char>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1:	Jan. 2024	8.724907	4.924221	4.489744	1.200992	3.258164	4.220907	1.119517	3.080392
2:	Feb. 2024	9.592013	5.034287	4.919206	1.451954	3.428647	4.628492	1.352529	3.249460
3:	Mar. 2024	10.281308	5.163713	5.413543	1.779951	3.583896	5.101556	1.657369	3.410070
4:	Apr. 2024	10.527227	6.408617	6.282631	1.936897	4.280357	5.918787	1.803811	4.070094
5:	May. 2024	10.431853	7.617499	6.784202	1.937331	4.769584	6.371295	1.802060	4.516177
6:	Jun. 2024	10.291163	9.102430	7.173475	1.762326	5.325535	6.725684	1.639192	5.027718
7:	Jul. 2024	10.305302	10.037233	7.511733	1.533887	5.890275	7.058263	1.430322	5.567823
8:	Aug. 2024	10.394682	8.640959	7.295543	1.545089	5.672747	6.879777	1.443952	5.382478
9:	Sep. 2024	10.233884	6.698488	6.335591	1.647975	4.628244	5.982520	1.539552	4.402209
10:	Oct. 2024	9.659077	4.546024	4.746760	1.538325	3.169044	4.470026	1.432213	3.010771
11:	Nov. 2024	8.798687	4.638289	4.393712	1.244217	3.118376	4.134590	1.159756	2.953471
12:	Dec. 2024	8.176298	3.439788	3.478125	1.128381	2.325648	3.274677	1.050626	2.207509

Yearly values:

	Dates	Bod	Bnd	Gd	Dd	Bd	Gefd	Defd	Befd
	<int>	<num>	<num>	<num>	<num>	<num>	<num>	<num>	<num>
1:	2024	3580.873	2326.882	2099.528	570.4317	1508.756	1975.745	531.5105	1430.271


Mode of tracking: fixed
Inclination: 27.2
Orientation: 0

```
1 xyplot(gef)
```



Y con un método para **compare**.

```
1 gef2x <- calcGef(lat, modeTrk = 'two', dataRad = BD)
2 gefhoriz <- calcGef(lat, modeTrk = 'horiz', dataRad = BD)
3 compare(gef, gef2x, gefhoriz)
```



4.8.4. Producción eléctrica de un SFCR

La clase **ProdGCPV** cuenta con un método para **xyplot**.

```
1 prodFixed <- prodGCPV(lat, modeTrk = 'fixed', dataRad = BD)
2 show(prodFixed)
```

```
Object of class ProdGCPV

Source of meteorological information: prom-

Latitude of source: 37.2 degrees
Latitude for calculations: 37.2 degrees


Monthly avarages:
  Dates      Eac      Edc      Yf
  <char>    <num>    <num>    <num>
1: Jan. 2024 95.36291 105.62767 3.604158
2: Feb. 2024 101.50809 112.56166 3.836410
3: Mar. 2024 110.26945 122.11835 4.167538
4: Apr. 2024 124.53728 138.29836 4.706778
5: May. 2024 131.48629 145.91065 4.969410
6: Jun. 2024 135.89421 150.78725 5.136003
7: Jul. 2024 134.98501 149.81246 5.101641
8: Aug. 2024 130.25804 144.39951 4.922989
9: Sep. 2024 119.91911 132.77648 4.532238
10: Oct. 2024 96.49455 106.99182 3.646928
11: Nov. 2024 90.17737 99.88152 3.408175
12: Dec. 2024 73.89289 81.80967 2.792718
```

```

Yearly values:
  Dates      Eac      Edc      Yf
<int> <num> <num> <num>
1: 2024 41014.8 45473.37 1550.119
-----
Mode of tracking: fixed
  Inclination: 27.2
  Orientation: 0
-----
Generator:
  Modules in series: 12
  Modules in parallel: 11
  Nominal power (kWp): 26.5

```

```
1 xyplot(prodFixed)
```




Un método para **compare**.

```


1 prod2x <- prodGCPV(lat, modeTrk = 'two', dataRad = BD)
2 prodHoriz <- prodGCPV(lat, modeTrk = 'horiz', dataRad = BD)
3 compare(prodFixed, prod2x, prodHoriz)

```



Y un método para `compareLosses`.

```
1 compareLosses(prodFixed, prod2x, prodHoriz)
```



4.8.5. Producción electrica de un SFB

La clase `ProdPVPS` cuenta con un método para `xyplot`.

```

1 pump <- prodPVPS(lat, dataRad = BD, pump = CoefSP8A44, H = 40, Pg = 5000)
2 show(pump)

```

```

Object of class  ProdPVPS

Source of meteorological information: prom-

Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      Eac      Qd      Yf
      <char>    <num>    <num>    <num>
1: Jan. 2024 17.22642 59.71506 3.445284
2: Feb. 2024 18.89837 64.60949 3.779675
3: Mar. 2024 20.81307 70.36542 4.162613
4: Apr. 2024 23.73937 79.08382 4.747874
5: May. 2024 25.28080 83.74003 5.056160
6: Jun. 2024 26.49158 87.02474 5.298315
7: Jul. 2024 27.70317 89.81648 5.540633
8: Aug. 2024 27.14273 87.89528 5.428546
9: Sep. 2024 24.01466 79.04010 4.802932
10: Oct. 2024 18.26638 63.00860 3.653277
11: Nov. 2024 17.06794 59.03182 3.413588
12: Dec. 2024 13.72784 48.99686 2.745567


Yearly values:
      Dates      Eac      Qd      Yf
      <int>    <num>    <num>    <num>
1:  2024 7942.432 26608.76 1588.486
-----
Mode of tracking:  fixed
  Inclination:  27.2
  Orientation:   0
-----
Pump:
  Qn:  8
  Stages:  44
Height (m):  40
Generator (Wp): 5000

```

```

1 xyplot(pump)

```



4.8.6. Optimización de distancias

La clase **Shade** cuenta con un método para **shadeplot**.

```
1 struct2x = list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 3)
2 dist2x = list(Lew = c(30, 45),Lns = c(20, 40))
3 ShdM2x <- optimShd(lat = lat, dataRad = prom, modeTrk = 'two',
4                   modeShd = c('area','prom'),
5                   distances = dist2x, struct = struct2x,
6                   res = 5, prog = FALSE)
7 show(ShdM2x)
```

Object of class Shade

Source of meteorological information: prom-

Latitude of source: 37.2 degrees

Latitude for calculations: 37.2 degrees

Monthly avarages:

Dimensions of structure:

\$W

[1] 23.11

\$L

[1] 9.8

\$Nrow

[1] 2

\$Ncol

[1] 3

Shade calculation mode:

[1] "area" "prom"


```
Productivity without shadows:
Object of class  ProdGCPV

Source of meteorological information: prom-


Latitude of source:  37.2 degrees
Latitude for calculations:  37.2 degrees

Monthly avarages:
      Dates      Eac      Edc      Yf
    <char>    <num>    <num>    <num>
1: Jan. 2024 138.6806 153.2566 5.241314
2: Feb. 2024 143.4987 158.5247 5.423408
3: Mar. 2024 151.8477 167.7311 5.738952
4: Apr. 2024 178.6717 197.4274 6.752741
5: May. 2024 200.8888 222.0523 7.592419
6: Jun. 2024 223.9959 247.6903 8.465728
7: Jul. 2024 214.2749 236.9628 8.098332
8: Aug. 2024 194.6043 215.1439 7.354902
9: Sep. 2024 168.9824 186.7349 6.386542
10: Oct. 2024 132.2995 146.0747 5.000145
11: Nov. 2024 128.5783 141.9871 4.859507
12: Dec. 2024 102.9116 113.5613 3.889454

Yearly values:
      Dates      Eac      Edc      Yf
    <int>    <num>    <num>    <num>
1:  2024 60369.04 66710.67 2281.595
-----
Mode of tracking: two
Inclination limit: 90
-----
Generator:
  Modules in series: 12
  Modules in parallel: 11
  Nominal power (kWp): 26.5

Summary of results:
      Lew      Lns      H      FS      GRR      Yf
Min.   :30.00  Min.   :20  Min.   :0  Min.   :0.01509  Min.   :2.649  Min.   :2104
1st Qu.:33.75  1st Qu.:25  1st Qu.:0  1st Qu.:0.02223  1st Qu.:3.946  1st Qu.:2192
Median :37.50  Median :30  Median :0  Median :0.02870  Median :4.802  Median :2216
Mean   :37.50  Mean   :30  Mean   :0  Mean   :0.03463  Mean   :4.967  Mean   :2203
3rd Qu.:41.25  3rd Qu.:35  3rd Qu.:0  3rd Qu.:0.03945  3rd Qu.:6.016  3rd Qu.:2231
Max.   :45.00  Max.   :40  Max.   :0  Max.   :0.07769  Max.   :7.948  Max.   :2247
```

```
1 shadeplot(ShdM2x)
```



Ejemplo práctico de aplicación

Una vez explicado como funciona el paquete, se puede realizar una demostración práctica tomando como ejemplo los módulos fotovoltaicos que tiene en su azotea la Escuela Técnica Superior de Ingeniería y Diseño Industrial (en adelante la ETSIDI).

Se tomará de base un estudio realizado por profesores de la escuela [Adr+17], en el cual, comparan la producción energética de seis tipos de tecnologías fotovoltaicas.

En este ejemplo se realizará el mismo análisis tomando tres herramientas distintas: **solaR**, para poder tomar como referencia el paquete del que sale para poder apreciar las mejoras del programa, **PVSyst**, ya que es uno de los softwares más usados en el ámbito de la fotovoltaica y puede servir como punto de referencia, y por último **solaR2**.

5.1. solaR

Se empieza inicilizando el paquete:

```
1 library(solaR)
```

```
Cargando paquete requerido: zoo
Adjuntando el paquete: 'zoo'
The following objects are masked from 'package:base':
  as.Date, as.Date.numeric
Cargando paquete requerido: lattice
Cargando paquete requerido: latticeExtra
Time Zone set to UTC.
```

En el estudio anterior, se recopilaron datos intradiarios de irradiación los cuales fueron almacenados en archivos.

```
1 enemar13 <- readBDi(file = 'TFG/data/ETSIDI/etsidi/EneMar2013_1.csv',
2                       lat = 40.4, time.col = 'Fecha')
3 show(enemar13)
```

```

Object of class  Meteo

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv
Latitude of source: 40.4 degrees

Meteorological Data:
      Index              GO              Ta
Min.   :2013-01-24 00:15:00.00  Min.   : 0.0  Min.   : -33.80
1st Qu.:2013-02-09 18:00:00.00  1st Qu.: 13.0  1st Qu.:  9.50
Median :2013-02-26 11:15:00.00  Median : 13.0  Median : 12.20
Mean   :2013-02-26 11:19:20.84  Mean   :113.2  Mean   : 11.97
3rd Qu.:2013-03-15 04:30:00.00  3rd Qu.:135.0  3rd Qu.: 14.40
Max.   :2013-03-31 23:45:00.00  Max.   :755.0  Max.   : 64.50

```

Una vez se tienen estos datos, se puede calcular la producción que van a tener los diferentes sistemas fotovoltaicos.

Para ello, se necesitan los parámetros de los diferentes sistemas. En la tabla 5.1 se pueden ver los distintos parámetros de los módulos fotovoltaicos.

Se almacena esta información en listas con la información de cada módulo.

```

1  ## mc-Si
2  module1 <- list(Vocn = 37.1,
3                  Iscn = 8.76,
4                  Vmn = 29.9,
5                  Imn = 8.37,
6                  Ncs = 60,
7                  Ncp = 1,
8                  CoefVT = 0.00338,
9                  TONC = 43.7)
10 ## pc-Si
11 module2 <- list(Vocn = 36.5,
12                 Iscn = 8.15,
13                 Vmn = 29,
14                 Imn = 7.59,
15                 Ncs = 60,

```

TABLA 5.1: *Parámetros técnicos de diferentes tipos de células solares.*

Parámetros Técnicos	mc-Si	pc-Si
Potencia se salida (Wp)	250	220
Voltaje en P_{max} (Vmp)	29.9	29.0
Corriente en P_{max} (Imp)	8.37	7.59
Voltaje en circuito abierto (Voc)	37.1	36.5
Corriente en cortocircuito (Isc)	8.76	8.15
Eficiencia del módulo (%)	15.5	14.4
α_{Isc} (%/K)	0.0043	0.06
β_{Voc} (%/K)	-0.338	-0.37
γ_{Pmpp} (%/K)	-0.469	-0.45
Temperatura NOC (°C)	43.7	46

```

16     Ncp = 1,
17     CoefVT = 0.0037,
18     TONC = 46)

```

Una vez se tiene la información de cada tipo de módulo, en la tabla 5.2 se pueden ver la información de la agrupación de cada sistema.

De la misma manera, se almacenará esta información en listas.

```

1 ## mc-Si
2 generator1 <- list(Nms = 5, Nmp = 1)
3 ## pc-Si
4 generator2 <- list(Nms = 5, Nmp = 1)

```

Una vez se tienen todos los parámetros del sistema fotovoltaico, se requieren los parámetros del inversor que tienen estos sistemas. Para facilitar el estudio, en el artículo explican que se usa el mismo inversor para todos los sistemas. Los parámetros de este se pueden ver en la tabla 5.3.

Se almacena esta información en otra lista:

```

1 inverter <- list(Pinv = 1200,
2                 Vmin = 100,

```

TABLA 5.2: *Sistemas fotovoltaicos.*

Sistema	Tecnología	Año de Fabricación	Módulos en Serie	Módulos en Paralelo	Potencia del Sistema STC (W_{pSTC})	Tamaño (m^2)
1	mc-Si	2012	5	1	1250	8
2	pc-Si	2009	5	1	1100	8.2

TABLA 5.3: *Características del inversor.*

Inversor	SMA Sunny Boy-1200
Potencia máxima DC	1320 W
Corriente máxima DC	12.6 A
Tensión máxima DC	400 V
Rango de tensión fotovoltaica (mpp)	100-320 V
Potencia máxima DC	1320 W
Potencia nominal de salida	1200 W
Maxima potencia aparente	1200 VA
Corriente máxima AC	6.1 A
Eficiencia	92.1 %

```
3      Vmax = 320)
```

Una vez recopilada toda la información (la información que falta se deja sin añadir para que el propio paquete añada sus valores por defecto), se puede calcular la producción que tuvieron los sistemas:

```
1 prod1 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
2                   dataRad = enemar13,
3                   beta = 30, alfa = -19, iS = 1,
4                   module = module1, generator = generator1,
5                   inverter = inverter)
6 show(prod1)
```

```
Object of class  ProdGCPV

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv

Latitude of source:  40.4 degrees
Latitude for calculations:  40.4 degrees

Monthly averages:
      Eac      Edc      Yf
ene. 2013 2.288657 2.544214 1.829001
feb. 2013 2.912867 3.246235 2.327844
mar. 2013 2.642931 2.958194 2.112123

Yearly values:
      Eac      Edc      Yf
2013 181.8004 202.9523 145.2875
-----
Mode of tracking:  fixed
  Inclination:    30
  Orientation:   -19
-----
Generator:
  Modules in series:  5
  Modules in parallel: 1
  Nominal power (kWp): 1.3
```

```
1 prod2 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
2                   dataRad = enemar13,
3                   beta = 30, alfa = -19, iS = 1,
4                   module = module2, generator = generator2,
5                   inverter = inverter)
6 show(prod2)
```

```
Object of class  ProdGCPV

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv

Latitude of source:  40.4 degrees
Latitude for calculations:  40.4 degrees

Monthly averages:
      Eac      Edc      Yf
ene. 2013 1.995563 2.219924 1.813242
feb. 2013 2.546910 2.840829 2.314216
mar. 2013 2.324995 2.608686 2.112576

Yearly values:
```

```

      Eac      Edc      Yf
2013 159.3528 178.1718 144.7938
-----
Mode of tracking: fixed
Inclination: 30
Orientation: -19
-----
Generator:
Modules in series: 5
Modules in parallel: 1
Nominal power (kWp): 1.1

```

5.2. PVsyst

Con la herramienta **PVsyst**, se ha generado un año promedio de datos de irradiación en la localización y con estos datos se han obtenido dos informes (uno por cada sistema).

Por comodidad, en este documento se van a extraer solo unas tablas con los resultados principales, sin embargo los informes completos están disponibles en el [github](#) del documento.

En las tablas 5.4 y 5.5 se tienen los resultados de la simulación de los sistemas.

5.3. solar2

Con los datos obtenidos en la sección 5.1, hacemos la misma operación pero con el paquete **solar2**.

```
1 library(solar2)
```

```

Cargando paquete requerido: data.table
data.table 1.15.4 using 6 threads (see ?getDTthreads). Latest news: r-datatable.com
Cargando paquete requerido: lattice
Cargando paquete requerido: latticeExtra
Time Zone set to UTC.

```

TABLA 5.4: *Energía media mensual estimada por PVsyst en KWh del sistema 1.*

Ene	Feb	Mar	Abr	May	Jun	Jul	Ago	Sep	Oct	Nov	Dic	Total
3,7	4,0	5,6	5,3	6,7	6,7	7,9	7,2	6,4	4,8	3,5	3,6	1941,1

TABLA 5.5: *Energía media mensual estimada por PVsyst en KWh del sistema 2.*

Ene	Feb	Mar	Abr	May	Jun	Jul	Ago	Sep	Oct	Nov	Dic	Total
4,3	4,6	6,4	6,1	7,3	7,3	8,3	7,7	6,9	5,4	4,1	4,4	2213,7

Para ello importamos de la misma manera los datos de radiación.

```
1 enemar13 <- readBDi(file = 'TFG/data/ETSIDI/etsidi/EneMar2013_1.csv',
2                       lat = 40.4, dates.col = 'Fecha')
3 show(enemar13)
```

Object of class Meteo

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv

Latitude of source: 40.4 degrees

Meteorological Data:

Dates	GO	Ta
Min. :2013-01-24 00:15:00.00	Min. : 0.0	Min. : -33.80
1st Qu.:2013-02-09 18:00:00.00	1st Qu.: 13.0	1st Qu.: 9.50
Median :2013-02-26 11:15:00.00	Median : 13.0	Median : 12.20
Mean :2013-02-26 11:19:20.84	Mean :113.2	Mean : 11.97
3rd Qu.:2013-03-15 04:30:00.00	3rd Qu.:135.0	3rd Qu.: 14.40
Max. :2013-03-31 23:45:00.00	Max. :755.0	Max. : 64.50

Con estos datos se procede al cálculo de la producción (los datos de los componentes del sistema son los mismos que los realizados en la sección 5.1).

```
1 prod1 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
2                  dataRad = enemar13,
3                  beta = 30, alfa = -19, iS = 1,
4                  module = module1, generator = generator1,
5                  inverter = inverter)
6 show(prod1)
```

Object of class ProdGCPV

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv

Latitude of source: 40.4 degrees

Latitude for calculations: 40.4 degrees

Monthly avarages:

Dates	Eac	Edc	Yf
<char>	<num>	<num>	<num>
1: Jan. 2013	2.288657	2.544214	1.829001
2: Feb. 2013	2.912867	3.246235	2.327844
3: Mar. 2013	2.642931	2.958194	2.112123

Yearly values:

Dates	Eac	Edc	Yf
<int>	<num>	<num>	<num>
1: 2013	181.8004	202.9523	145.2875

Mode of tracking: fixed

Inclination: 30

Orientation: -19

Generator:

Modules in series: 5

Modules in parallel: 1

Nominal power (kWp): 1.3

```
1 prod2 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
2                  dataRad = enemar13,
```



```

3      beta = 30, alfa = -19, iS = 1,
4      module = module2, generator = generator2,
5      inverter = inverter)
6 show(prod2)

```

```

Object of class ProdGCPV

Source of meteorological information: bdI-TFG/data/ETSIDI/etsidi/EneMar2013_1.csv

Latitude of source: 40.4 degrees
Latitude for calculations: 40.4 degrees

Monthly avarages:
      Dates      Eac      Edc      Yf
    <char>    <num>    <num>    <num>
1: Jan. 2013 1.995563 2.219924 1.813242
2: Feb. 2013 2.546910 2.840829 2.314216
3: Mar. 2013 2.324995 2.608686 2.112576

Yearly values:
      Dates      Eac      Edc      Yf
    <int>    <num>    <num>    <num>
1: 2013 159.3528 178.1718 144.7938
-----
Mode of tracking: fixed
  Inclination: 30
  Orientation: -19
-----
Generator:
  Modules in series: 5
  Modules in parallel: 1
  Nominal power (kWp): 1.1

```

5.4. Comparación y conclusiones

Como se puede observar en las secciones anteriores, tanto el paquete **solar** como el paquete **solar2** ofrecen los mismos resultados ya que toman las mismas referencias y estudios para realizar los cálculos. Sin embargo, el paquete **solar2**, a parte de la corrección de algunos errores, presenta unas claras ventajas frente a su antecesor. Estas son:

- **Eficiencia:** al estar basado en **data.table**, el paquete gana eficiencia en operaciones complejas. Para mostrar esto vamos a utilizar el paquete **microbenchmark**.

```

1 ## Con el paquete solar
2 library(microbenchmark)
3 prodGCPVcustom <- function(){
4   prod1 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
5                     dataRad = enemar13, beta = 30, alfa = -19,
6                     iS = 1, module = module1,
7                     generator = generator1, inverter = inverter)
8 }
9 microbenchmark(prodGCPVcustom(), times = 50)

```

```

Unit: milliseconds
      expr      min      lq     mean   median      uq     max neval
prodGCPVcustom() 529.5188 543.3399 554.9077 548.5941 558.3901 626.5719     50

```

```

1 ## Con el paquete solaR2
2 library(microbenchmark)
3 prodGCPVcustom <- function(){
4   prod1 <- prodGCPV(lat = 40.4, modeTrk = 'fixed', modeRad = 'bdI',
5                     dataRad = enemar13, beta = 30, alfa = -19,
6                     iS = 1, module = module1,
7                     generator = generator1, inverter = inverter)
8 }
9 microbenchmark(prodGCPVcustom(), times = 50)

```

Unit: milliseconds							
expr	min	lq	mean	median	uq	max	neval
prodGCPVcustom()	333.9282	338.6178	345.8622	341.9009	345.6647	402.8548	50

Aquí se puede ver que la eficiencia mejora. Sin embargo, suponiendo que en vez de un sistema fijo, tuvieramos un sistema de seguimiento de doble eje y quisieramos obtener la mejor combinación de distancias, se podría utilizar la función **optimShd**, la cual al ser una tarea muy exigente se aprecia con más detalle las virtudes del paquete **solaR2** gracias al uso de **data.table**.

```

1 ## Con el paquete solaR
2 struct2x <- list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 3)
3 dist2x <- list(Lew = c(30, 45), Lns = c(20, 40))
4 optimShdcustom <- function(){
5   optim <- optimShd(lat = 40.4, modeTrk = 'two', modeRad = 'bdI',
6                     dataRad = enemar13, beta = 30, alfa = -19,
7                     iS = 1, module = module1,
8                     generator = generator1, inverter = inverter,
9                     modeShd = c('area', 'prom'),
10                     distances = dist2x, struct = struct2x,
11                     res = 5, prog = FALSE)
12 }
13 microbenchmark(optimShdcustom(), times = 20)

```

Unit: seconds							
expr	min	lq	mean	median	uq	max	neval
optimShdcustom()	6.30659	6.387046	6.447254	6.453184	6.48896	6.610802	20

```

1 ## Con el paquete solaR2
2 struct2x <- list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 3)
3 dist2x <- list(Lew = c(30, 45), Lns = c(20, 40))
4 optimShdcustom <- function(){
5   optim <- optimShd(lat = 40.4, modeTrk = 'two', modeRad = 'bdI',
6                     dataRad = enemar13, beta = 30, alfa = -19,
7                     iS = 1, module = module1,
8                     generator = generator1, inverter = inverter,
9                     modeShd = c('area', 'prom'),
10                     distances = dist2x, struct = struct2x,
11                     res = 5, prog = FALSE)
12 }
13 microbenchmark(optimShdcustom(), times = 20)

```

Unit: seconds							
expr	min	lq	mean	median	uq	max	neval
optimShdcustom()	5.121113	5.154294	5.175936	5.171816	5.182229	5.249169	20

Manual de referencia de solaR2

En este apéndice se incluye el manual de referencia del paquete solaR2. Este manual se genera en base a los archivos de documentación (`.Rd`) propios de un paquete de R, y en el cual se recoge la información de todas las funciones, objetos y set de datos que contiene el paquete.

Se distribuye siguiendo la siguiente nomenclatura:

- **Constructores:** se trata de funciones que devuelven un objeto de una clase propia del paquete. Como identificador, se añade la letra **A** antes del nombre.
- **Clases:** la definición de las clases de los objetos definidos por este paquete. Como identificador, se añade la letra **B** antes del nombre.
- **Utilidades:** funciones que sirven de apoyo a los cálculos de las funciones constructoras. Como identificador, se añade la letra **C** antes del nombre.
- **Métodos:** métodos para los objetos definidos en el paquete. Como identificador, se añade la letra **D** antes del nombre.

Package ‘solaR2’

September 5, 2024

Type Package
Title Radiation and Photovoltaic Systems
Version 0.10
Encoding UTF-8
Description Calculation methods of solar radiation and performance of photovoltaic systems from daily and intradaily irradiation data sources.
URL <https://solarization.github.io/solaR2/>
BugReports <https://github.com/solarization/solaR2/issues>
License GPL-3
LazyData yes
Depends R (>= 4.0.0), data.table, lattice, latticeExtra
Imports RColorBrewer, graphics, grDevices, stats, methods, utils
Suggests zoo, sp, raster, rasterVis, tdr, meteoForecast, httr2, jsonlite, testthat (>= 3.0.0)
Config/testthat/edition 3
NeedsCompilation no
Author Oscar Perpiñán-Lamigueiro [cre, aut]
([<https://orcid.org/0000-0002-4134-7196>](https://orcid.org/0000-0002-4134-7196)),
Francisco Delgado-López [aut]
Maintainer Oscar Perpiñán-Lamigueiro <oscar.perpinan@upm.es>

Contents

solaR2-package	3
A1_calcSol	5
A2_calcG0	6
A3_calcGef	9
A4_prodGCPV	11
A5_prodPVPS	15
A6_calcShd	17
A7_optimShd	18
A8_Meteo2Meteo	22
A8_readBD	23
A8_readG0dm	25

A8_readSIAR	26
B1_Meteo-class	27
B2_Sol-class	28
B3_G0-class	29
B4_Gef-class	30
B5_ProdGCPV-class	32
B6_ProdPVPS-class	33
B7_Shade-class	34
C_corrFdKt	36
C_fBTd	38
C_fBTi	39
C_fCompD	40
C_fCompI	41
C_fInclin	43
C_fProd	45
C_fPump	47
C_fSolD	48
C_fSolI	50
C_fSombra	52
C_fTemp	54
C_fTheta	55
C_HQCurve	57
C_local2Solar	58
C_NmgPVPS	59
C_sample2Diff	61
C_solarAngles	62
C_utils-angle	64
C_utils-time	64
D_as.data.tableD-methods	65
D_as.data.tableI-methods	66
D_as.data.tableM-methods	68
D_as.data.tableY-methods	69
D_compare-methods	70
D_getData-methods	71
D_getG0-methods	71
D_getLat-methods	71
D_indexD-methods	72
D_indexI-methods	72
D_levelplot-methods	73
D_Losses-methods	73
D_mergesolaR-methods	74
D_shadeplot-methods	75
D_window-methods	75
D_writeSolar-methods	76
D_xyplot-methods	78
E_aguiar	79
E_helios	79
E_prodEx	80
E_pumpCoef	80
E_SIAR	81
E_solaR.theme	81

Description

The *solaR2* package allows for reproducible research both for photovoltaics (PV) systems performance and solar radiation. It includes a set of classes, methods and functions to calculate the sun geometry and the solar radiation incident on a photovoltaic generator and to simulate the performance of several applications of the photovoltaic energy. This package performs the whole calculation procedure from both daily and intradaily global horizontal irradiation to the final productivity of grid-connected PV systems and water pumping PV systems.

Details

solaRd is designed using a set of S4 classes whose core is a group of slots with multivariate time series. The classes share a variety of methods to access the information and several visualization methods. In addition, the package provides a tool for the visual statistical analysis of the performance of a large PV plant composed of several systems.

Although *solaRd* is primarily designed for time series associated to a location defined by its latitude/longitude values and the temperature and irradiation conditions, it can be easily combined with spatial packages for space-time analysis.

Please note that this package needs to set the timezone to UTC. Every ‘data.table’ object created by the package will have an index with this time zone as a synonym of mean solar time..

You can check it after loading *solaR2* with:

```
Sys.getenv('TZ')
```

If you need to change it, use:

```
Sys.setenv(TZ = 'YourTimeZone')
```

Index of functions and classes:

G0-class	Class "G0": irradiation and irradiance on the horizontal plane.
Gef-class	Class "Gef": irradiation and irradiance on the generator plane.
HQCurve	H-Q curves of a centrifugal pump
Meteo-class	Class "Meteo"
NmgPVPS	Nomogram of a photovoltaic pumping system
ProdGCPV-class	Class "ProdGCPV": performance of a grid connected PV system.
ProdPVPS-class	Class "ProdPVPS": performance of a PV pumping system.
Shade-class	Class "Shade": shadows in a PV system.
Sol-class	Class "Sol": Apparent movement of the Sun from the Earth
aguiar	Markov Transition Matrices for the Aguiar et al. procedure
as.data.tableD	Methods for Function <code>as.data.frameD</code>
as.data.tableI	Methods for Function <code>as.data.frameI</code>
as.data.tableM	Methods for Function <code>as.data.frameM</code>
as.data.tableY	Methods for Function <code>as.data.frameY</code>

calcG0	Irradiation and irradiance on the horizontal plane.
calcGef	Irradiation and irradiance on the generator plane.
calcShd	Shadows on PV systems.
calcSol	Apparent movement of the Sun from the Earth
compare	Compare G0, Gef and ProdGCPV objects
compareLosses	Losses of a GCPV system
corrFdKt	Correlations between the fraction of diffuse irradiation and the clearness index.
d2r	Conversion between angle units.
diff2Hours	Small utilities for difftime objects.
fBTd	Daily time base
fCompD	Components of daily global solar irradiation on a horizontal surface
fCompI	Calculation of solar irradiance on a horizontal surface
fInclin	Solar irradiance on an inclined surface
fProd	Performance of a PV system
fPump	Performance of a centrifugal pump
fSolD	Daily apparent movement of the Sun from the Earth
fSolI	Instantaneous apparent movement of the Sun from the Earth
fSombra	Shadows on PV systems
fTemp	Intradaily evolution of ambient temperature
fTheta	Angle of incidence of solar irradiation on a inclined surface
getData	Methods for function getData
getG0	Methods for function getG0
getLat	Methods for Function getLat
helios	Daily irradiation and ambient temperature from the Helios-IES database
hour	Utilities for time indexes.
indexD	Methods for Function indexD
indexI	Methods for Function indexI
levelplot-methods	Methods for function levelplot.
local2Solar	Local time, mean solar time and UTC time zone.
mergesolaR	Merge solaR objects
optimShd	Shadows calculation for a set of distances between elements of a PV grid connected plant.
prodEx	Productivity of a set of PV systems of a PV plant.
prodGCPV	Performance of a grid connected PV system.
prodPVPS	Performance of a PV pumping system
pumpCoef	Coefficients of centrifugal pumps.
readBD	Daily or intradaily values of global horizontal irradiation and ambient temperature from a local file or a data.frame.
readG0dm	Monthly mean values of global horizontal irradiation.
readSIAR	Meteorological data exported from the SIAR network

A1_calcSol

5

shadeplot	Methods for Function shadeplot
solaR.theme	solaR theme
window	Methods for extracting a time window
writeSolar	Exporter of solaR results
xyplot-methods	Methods for function xyplot in Package 'solaR'

Author(s)

Oscar Perpiñán Lamigueiro and Francisco Delgado López

*A1_calcSol**Apparent movement of the Sun from the Earth*

Description

Compute the apparent movement of the Sun from the Earth with the functions [fSold](#) and [fSolI](#).

Usage

```
calcSol(lat, BTd, sample = 'hour', BTi,  
        EoT = TRUE, keep.night = TRUE,  
        method = 'michalsky')
```

Arguments

lat	Latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
BTd	Daily time base, a POSIXct object which may be the result of fBTd . It is not considered if BTi is provided.
sample	Increment of the intradaily sequence. It is a character string, containing one of "sec", "min", "hour". This can optionally be preceded by a (positive or negative) integer and a space, or followed by "s". It is used by seq.POSIXt . It is not considered if BTi is provided.
BTi	Intradaily time base, a POSIXct object to be used by fSolI . It may be the result of fBTi .
EoT	logical, if TRUE the Equation of Time is used. Default is TRUE.
keep.night	logical, if TRUE (default) the night is included in the time series.
method	character, method for the sun geometry calculations to be chosen from 'cooper', 'spencer', 'michalsky' and 'strous'. See references for details.

Value

A [Sol-class](#) object.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Cooper, P.I., Solar Energy, 12, 3 (1969). "The Absorption of Solar Radiation in Solar Stills"
- Spencer, Search 2 (5), 172, <https://www.mail-archive.com/sundial@uni-koeln.de/msg01050.html>
- Strous: <https://www.aa.quae.nl/en/reken/zonpositie.html>
- Michalsky, J., 1988: The Astronomical Almanac's algorithm for approximate solar position (1950-2050), Solar Energy 40, 227-235
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

Examples

```
BTd = fBTd(mode = 'serie')

lat = 37.2
sol = calcSol(lat, BTd[100])
print(as.data.tableD(sol))

library(lattice)
xyplot(as.data.tableI(sol))

solStrous = calcSol(lat, BTd[100], method = 'strous')
print(as.data.tableD(solStrous))

solSpencer = calcSol(lat, BTd[100], method = 'spencer')
print(as.data.tableD(solSpencer))

solCooper = calcSol(lat, BTd[100], method = 'cooper')
print(as.data.tableD(solCooper))
```

A2_calcG0

Irradiation and irradiance on the horizontal plane.

Description

This function obtains the global, diffuse and direct irradiation and irradiance on the horizontal plane from the values of *daily* and *intradaily* global irradiation on the horizontal plane. It makes use of the functions [calcSol](#), [fCompD](#), [fCompI](#), [fBTd](#) and [readBDd](#) (or equivalent).

Besides, if information about maximum and minimum temperatures values are available it obtains a series of temperature values with [fTemp](#).

Usage

```
calcG0(lat, modeRad = 'prom', dataRad,
       sample = 'hour', keep.night = TRUE,
       sunGeometry = 'michalsky',
       corr, f, ...)
```

A2_calcG0

7

Arguments

lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
modeRad	<p>A character string, describes the kind of source data of the global irradiation and ambient temperature.</p> <p>It can be modeRad = 'prom' for monthly mean calculations. With this option, a set of 12 values inside dataRad must be provided, as defined in readG0dm.</p> <p>modeRad = 'aguiar' uses a set of 12 monthly average values (provided with dataRad) and produces a synthetic daily irradiation time series following the procedure by Aguiar et al. (see reference below).</p> <p>If modeRad = 'bd' the information of <i>daily</i> irradiation is read from a file, a data.table defined by dataRad, a zoo or a Meteo object. (See readBDd, dt2Meteo and zoo2Meteo for details).</p> <p>If modeRad = 'bdI' the information of <i>intradaily</i> irradiation is read from a file, a data.table defined by dataRad, a zoo or a Meteo object. (See readBDi, dt2Meteo and zoo2Meteo for details).</p>
dataRad	<ul style="list-style-type: none">• If modeRad = 'prom' or modeRad = 'aguiar', a numeric with 12 values or a named list whose components will be processed with readG0dm.• If modeRad = 'bd' a character (name of the file to be read with readBDd), a data.table (to be processed with dt2Meteo), a zoo (to be processed with zoo2Meteo), a Meteo object, or a list as defined by readBDd, dt2Meteo or zoo2Meteo. The resulting object will include a column named Ta, with information about ambient temperature.• If modeRad = 'bdI' a character (name of the file to be read with readBDi), a data.table (to be processed with dt2Meteo), a zoo (to be processed with zoo2Meteo), a Meteo object, or a list as defined by readBDi, dt2Meteo or zoo2Meteo. The resulting object will include a column named Ta, with information about ambient temperature.
sample	character, containing one of "sec", "min", "hour". This can optionally be preceded by a (positive or negative) integer and a space, or followed by "s" (used by seq.POSIXt). It is not used when modeRad = "bdI".
keep.night	logical. When it is TRUE (default) the time series includes the night.
sunGeometry	character, method for the sun geometry calculations. See calcSol , fSolD and fSolI .
corr	<p>A character, the correlation between the fraction of diffuse irradiation and the clearness index to be used.</p> <p>With this version several options are available, as described in corrFdKt. For example, the FdKtPage is selected with corr = 'Page' while the FdKtCPR with corr = 'CPR'.</p> <p>If corr = 'user' the use of a correlation defined by a function f is possible.</p> <p>If corr = 'none' the object defined by dataRad should include information about global, diffuse and direct daily irradiation with columns named G0d, D0d and B0d, respectively (or G0, D0 and B0 if modeRad = 'bdI'). If corr is missing, then it is internally set to CPR when modeRad = 'bd', to Page when modeRad = 'prom' and to BRL when modeRad = 'bdI'.</p>
f	A function defining a correlation between the fraction of diffuse irradiation and the clearness index. It is only necessary when corr = 'user'
...	Additional arguments for fCompD or fCompI

Value

A G0 object.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09
- Aguiar, Collares-Pereira and Conde, "Simple procedure for generating sequences of daily radiation values using a library of Markov transition matrices", Solar Energy, Volume 40, Issue 3, 1988, Pages 269–279

See Also

[calcSol](#), [fCompD](#), [fCompI](#), [readG0dm](#), [readBDd](#), [readBDi](#), [dt2Meteo](#), [corrFdKt](#).

Examples

```
G0dm = c(2.766, 3.491, 4.494, 5.912, 6.989, 7.742, 7.919, 7.027, 5.369, 3.562, 2.814, 2.179)*1000;
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2,
      15.2)

g0 <- calcG0(lat = 37.2, modeRad = 'prom', dataRad = list(G0dm = G0dm, Ta = Ta))
print(g0)
xyplot(g0)

## Aguiar et al.

g0 <- calcG0(lat = 37.2, modeRad = 'aguiar', dataRad = G0dm)
print(g0)
xyplot(g0)

##Now the G0I component of g0 is used as
##the bdi argument to calcG0 in order to
##test the intradaily correlations of fd-kt

BDi = as.data.tableI(g0)
BDi$Ta = 25 ##Information about temperature must be contained in BDi

g02 <- calcG0(lat = 37.2,
              modeRad = 'bdi',
              dataRad = list(lat = 37.2, file = BDi),
              corr = 'none')

print(g02)

g03 <- calcG0(lat = 37.2,
              modeRad = 'bdi',
              dataRad = list(lat = 37.2, file = BDi),
              corr = 'BRL')

print(g03)
```

A3_calcGef

9

```
xyplot(Fd ~ Kt, data = g03, pch = 19, alpha = 0.3)
```

*A3_calcGef**Irradiation and irradiance on the generator plane.*

Description

This function obtains the global, diffuse and direct irradiation and irradiance on the generator plane from the values of *daily* or *intradaily* global irradiation on the horizontal plane. It makes use of the functions [calcG0](#), [fTheta](#), [fInclin](#). Besides, it can calculate the shadows effect with the [calcShd](#) function.

Usage

```
calcGef(lat,  
        modeTrk = 'fixed',  
        modeRad = 'prom',  
        dataRad,  
        sample = 'hour',  
        keep.night = TRUE,  
        sunGeometry = 'michalsky',  
        corr, f,  
        betaLim = 90, beta = abs(lat)-10, alpha = 0,  
        iS = 2, alb = 0.2, horizBright = TRUE, HCPV = FALSE,  
        modeShd = '',  
        struct = list(),  
        distances = data.table(),  
        ...)
```

Arguments

lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
modeTrk	character, to be chosen from 'fixed', 'two' or 'horiz'. When modeTrk = 'fixed' the surface is fixed (inclination and azimuth angles are constant). The performance of a two-axis tracker is calculated with modeTrk = 'two', and modeTrk = 'horiz' is the option for an horizontal N-S tracker. Its default value is modeTrk = 'fixed'
modeRad, dataRad	Information about the source data of the global irradiation. See calcG0 for details.
sample, keep.night	See calcSol for details.
sunGeometry	character, method for the sun geometry calculations. See calcSol , fSolD and fSolI .
corr, f	See calcG0 for details.
beta	numeric, inclination angle of the surface (degrees). It is only needed when modeTrk = 'fixed'.

betaLim	numeric, maximum value of the inclination angle for a tracking surface. Its default value is 90 (no limitation))
alpha	numeric, azimuth angle of the surface (degrees). It is measured from the south ($\alpha = 0$), and it is negative to the east and positive to the west. It is only needed when modeTrk = 'fixed'. Its default value is $\alpha = 0$
iS	integer, degree of dirtiness. Its value must be included in the set (1,2,3,4). iS = 1 corresponds to a clean surface while iS = 4 is the selection for a dirty surface. Its default value is 2.
alb	numeric, albedo reflection coefficient. Its default value is 0.2
modeShd, struct, distances	See calcShd for details.
horizBright	logical, if TRUE, the horizon brightness correction proposed by Reind et al. is used.
HCPV	logical, if TRUE the diffuse and albedo components of the <i>effective</i> irradiance are set to zero. HCPV is the acronym of High Concentration PV system.
...	Additional arguments for calcSol and calcG0

Value

A Gef object.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Hay, J. E. and McKay, D. C.: Estimating Solar Irradiance on Inclined Surfaces: A Review and Assessment of Methodologies. Int. J. Solar Energy, (3):pp. 203, 1985.
- Martin, N. and Ruiz, J.M.: Calculation of the PV modules angular losses under field conditions by means of an analytical model. Solar Energy Materials & Solar Cells, 70:25–38, 2001.
- D. T. Reindl and W. A. Beckman and J. A. Duffie: Evaluation of hourly tilted surface radiation models, Solar Energy, 45:9-17, 1990.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[calcG0](#), [fTheta](#), [fInclin](#), [calcShd](#).

Examples

```
lat <- 37.2

###12 Average days.

G0dm = c(2.766, 3.491, 4.494, 5.912, 6.989, 7.742, 7.919, 7.027, 5.369,
         3.562, 2.814, 2.179)*1000;
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2,
       15.2)
```

```
##Fixed surface, default values of inclination and azimuth.

gef <- calcGef(lat = lat, modeRad = 'prom', dataRad = list(G0dm = G0dm, Ta = Ta))
print(gef)
xyplot(gef)

##Two-axis surface, no limitation angle.

gef2 <- calcGef(lat = lat, modeRad = 'prom',
               dataRad = list(G0dm = G0dm, Ta = Ta),
               modeTrk = 'two')
print(gef2)
xyplot(gef2)

struct = list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 8)
distances = data.table(Lew = 40, Lns = 30, H = 0)

gefShd <- calcGef(lat = lat, modeRad = 'prom',
                 dataRad = list(G0dm = G0dm, Ta = Ta),
                 modeTrk = 'two',
                 modeShd = c('area', 'prom'),
                 struct = struct, distances = distances)
print(gefShd)
```

A4_prodGCPV*Performance of a grid connected PV system.*

Description

Compute every step from solar angles to effective irradiance to calculate the performance of a grid connected PV system.

Usage

```
prodGCPV(lat,
         modeTrk = 'fixed',
         modeRad = 'prom',
         dataRad,
         sample = 'hour',
         keep.night = TRUE,
         sunGeometry = 'michalsky',
         corr, f,
         betaLim = 90, beta = abs(lat)-10, alpha = 0,
         iS = 2, alb = 0.2, horizBright = TRUE, HCPV = FALSE,
         module = list(),
         generator = list(),
         inverter = list(),
         effSys = list(),
         modeShd = '',
         struct = list(),
         distances = data.table(),
         ...)
```


Arguments

lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
modeTrk	A character string, describing the tracking method of the generator. See calcGef for details.
modeRad, dataRad	Information about the source data of the global irradiation. See calcG0 for details.
sample, keep.night	See calcSol for details.
sunGeometry	character, method for the sun geometry calculations. See calcSol , fSolD and fSolI .
corr, f	See calcG0 for details.
betaLim, beta, alpha, iS, alb, horizBright, HCPV	See calcGef for details.
module	list of numeric values with information about the PV module, Vocn open-circuit voltage of the module at Standard Test Conditions (default value 57.6 volts.) Iscn short circuit current of the module at Standard Test Conditions (default value 4.7 amperes.) Vmn maximum power point voltage of the module at Standard Test Conditions (default value 46.08 amperes.) Imn Maximum power current of the module at Standard Test Conditions (default value 4.35 amperes.) Ncs number of cells in series inside the module (default value 96) Ncp number of cells in parallel inside the module (default value 1) CoefVT coefficient of decrement of voltage of each cell with the temperature (default value 0.0023 volts per celsius degree) TONC nominal operational cell temperature, celsius degree (default value 47).
generator	list of numeric values with information about the generator, Nms number of modules in series (default value 12) Nmp number of modules in parallel (default value 11)
inverter	list of numeric values with information about the DC/AC inverter, Ki vector of three values, coefficients of the efficiency curve of the inverter (default c(0.01, 0.025, 0.05)), or a matrix of nine values (3x3) if there is dependence with the voltage (see references). Pinv nominal inverter power (W) (default value 25000 watts.) Vmin, Vmax minimum and maximum voltages of the MPP range of the inverter (default values 420 and 750 volts) Gumb minimum irradiance for the inverter to start (W/m ²) (default value 20 W/m ²)
effSys	list of numeric values with information about the system losses, ModQual average tolerance of the set of modules (%), default value is 3 ModDisp module parameter dispersion losses (%), default value is 2 OhmDC Joule losses due to the DC wiring (%), default value is 1.5 OhmAC Joule losses due to the AC wiring (%), default value is 1.5

A4_prodGCPV

13

MPP average error of the MPP algorithm of the inverter (%), default value is 1
TrafoMT losses due to the MT transformer (%), default value is 1
Disp losses due to stops of the system (%), default value is 0.5
modeShd, struct, distances
See [calcShd](#) for details.
... Additional arguments for [calcG0](#) or [calcGef](#)

Details

The calculation of the irradiance on the horizontal plane is carried out with the function [calcG0](#). The transformation to the inclined surface makes use of the [fTheta](#) and [fInclin](#) functions inside the [calcGef](#) function. The shadows are computed with [calcShd](#) while the performance of the PV system is simulated with [fProd](#).

Value

A ProdGCPV object.

Author(s)

Oscar Perpiñán Lamigueiro

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, [doi:10.18637/jss.v050.i09](https://doi.org/10.18637/jss.v050.i09)

See Also

[fProd](#), [calcGef](#), [calcShd](#), [calcG0](#), [compare](#), [compareLosses](#), [mergesolaR](#)

Examples

```
library(lattice)
library(latticeExtra)

lat <- 37.2;

G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562,
         2814, 2179)

Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2,
       17.2, 15.2)

prom <- list(G0dm = G0dm, Ta = Ta)

###Comparison of different tracker methods
prodFixed <- prodGCPV(lat = lat, dataRad = prom,
                     keep.night = FALSE)

prod2x <- prodGCPV(lat = lat, dataRad = prom,
                  modeTrk = 'two',
                  keep.night = FALSE)
```

```

prodHoriz <- prodGCPV(lat = lat, dataRad = prom,
                     modeTrk = 'horiz',
                     keep.night = FALSE)

##Comparison of yearly productivities
compare(prodFixed, prod2x, prodHoriz)
compareLosses(prodFixed, prod2x, prodHoriz)

##Comparison of power time series
ComparePac <- data.table(Dates = indexI(prod2x),
                        two = as.data.tableI(prod2x)$Pac,
                        horiz = as.data.tableI(prodHoriz)$Pac,
                        fixed = as.data.tableI(prodFixed)$Pac)

AngSol <- as.data.tableI(as(prodFixed, 'Sol'))

ComparePac <- merge(AngSol, ComparePac, by = 'Dates')

ComparePac[, Month := as.factor(month(Dates))]]

xyplot(two + horiz + fixed ~ AzS|Month, data = ComparePac,
       type = 'l',
       auto.key = list(space = 'right',
                       lines = TRUE,
                       points = FALSE),
       ylab = 'Pac')

###Shadows
#Two-axis trackers
struct2x <- list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 8)
dist2x <- data.table(Lew = 40, Lns = 30, H = 0)
prod2xShd <- prodGCPV(lat = lat, dataRad = prom,
                     modeTrk = 'two',
                     modeShd = 'area',
                     struct = struct2x,
                     distances = dist2x)

print(prod2xShd)

#Horizontal N-S tracker
structHoriz <- list(L = 4.83);
distHoriz <- data.table(Lew = structHoriz$L*4);

#Without Backtracking
prodHorizShd <- prodGCPV(lat = lat, dataRad = prom,
                        sample = '10 min',
                        modeTrk = 'horiz',
                        modeShd = 'area', betaLim = 60,
                        distances = distHoriz,
                        struct = structHoriz)

print(prodHorizShd)

xyplot(r2d(Beta)~r2d(w),
       data = prodHorizShd,
       type = 'l',

```

```
main = 'Inclination angle of a horizontal axis tracker',
xlab = expression(omega (degrees)),
ylab = expression(beta (degrees)))

#With Backtracking
prodHorizBT <- prodGCPV(lat = lat, dataRad = prom,
                      sample = '10 min',
                      modeTrk = 'horiz',
                      modeShd = 'bt', betaLim = 60,
                      distances = distHoriz,
                      struct = structHoriz)

print(prodHorizBT)

xyplot(r2d(Beta)~r2d(w),
      data = prodHorizBT,
      type = 'l',
      main = 'Inclination angle of a horizontal axis tracker\n with backtracking',
      xlab = expression(omega (degrees)),
      ylab = expression(beta (degrees)))

compare(prodFixed, prod2x, prodHoriz, prod2xShd,
        prodHorizShd, prodHorizBT)

compareLosses(prodFixed, prod2x, prodHoriz, prod2xShd,
              prodHorizShd, prodHorizBT)

compareYf2 <- mergesolaR(prodFixed, prod2x, prodHoriz, prod2xShd,
                        prodHorizShd, prodHorizBT)

xyplot(prodFixed + prod2x +prodHoriz + prod2xShd + prodHorizShd + prodHorizBT ~ Dates,
      data = compareYf2, type = 'l', ylab = 'kWh/kWp',
      main = 'Daily productivity',
      auto.key = list(space = 'right'))
```

A5_prodPVPS*Performance of a PV pumping system*

Description

Compute every step from solar angles to effective irradiance to calculate the performance of a PV pumping system.

Usage

```
prodPVPS(lat,
        modeTrk = 'fixed',
        modeRad = 'prom',
        dataRad,
        sample = 'hour',
        keep.night = TRUE,
        sunGeometry = 'michalsky',
        corr, f,
```

```

betaLim = 90, beta = abs(lat)-10, alpha = 0,
iS = 2, alb = 0.2, horizBright = TRUE, HCPV = FALSE,
pump , H,
Pg, converter= list(),
effSys = list(),
...)

```

Arguments

lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
modeTrk	A character string, describing the tracking method of the generator. See calcGef for details.
modeRad, dataRad	Information about the source data of the global irradiation. See calcG0 for details.
sample, keep.night	See calcSol for details.
sunGeometry	character, method for the sun geometry calculations. See calcSol , fSolD and fSolI .
corr, f	See calcG0 for details.
betaLim, beta, alpha, iS, alb, horizBright, HCPV	See calcGef for details.
pump	A list extracted from pumpCoef
H	Total manometric head (m)
Pg	Nominal power of the PV generator (Wp)
converter	list containing the nominal power of the frequency converter, Pnom, and Ki, vector of three values, coefficients of the efficiency curve.
effSys	list of numeric values with information about the system losses, ModQual average tolerance of the set of modules (%), default value is 3 ModDisp module parameter dispersion losses (%), default value is 2 OhmDC Joule losses due to the DC wiring (%), default value is 1.5 OhmAC Joule losses due to the AC wiring (%), default value is 1.5
...	Additional arguments for calcSol , calcG0 and calcGef .

Details

The calculation of the irradiance on the generator is carried out with the function [calcGef](#). The performance of the PV system is simulated with [fPump](#).

Value

A [ProdPVPS](#) object.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Abella, M. A., Lorenzo, E. y Chenlo, F.: PV water pumping systems based on standard frequency converters. *Progress in Photovoltaics: Research and Applications*, 11(3):179–191, 2003, ISSN 1099-159X.
- Perpiñán, O, *Energía Solar Fotovoltaica*, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", *Journal of Statistical Software*, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[NmgPVPS](#), [fPump](#), [pumpCoef](#)

A6_calcShd

Shadows on PV systems.

Description

Compute the irradiance and irradiation including shadows for two-axis and horizontal N-S axis trackers and fixed surfaces. It makes use of the function [fSombra](#) for the shadows factor calculation. It is used by the function [calcGef](#).

Usage

```
calcShd(radEf,
        modeShd = '',
        struct = list(),
        distances = data.table())
```

Arguments

radEf	A Gef object. It may be the result of the calcGef function.
modeShd	character, defines the type of shadow calculation. In this version of the package the effect of the shadow is calculated as a proportional reduction of the circumsolar diffuse and direct irradiances. This type of approach is selected with modeShd = 'area'. In future versions other approaches which relate the geometric shadow and the electrical connections of the PV generator will be available. If radEf@modeTrk = 'horiz' it is possible to calculate the effect of backtracking with modeShd = 'bt'. If modeShd = c('area', 'bt') the backtracking method will be carried out and therefore no shadows will appear. Finally, for two-axis trackers it is possible to select modeShd = 'prom' in order to calculate the effect of shadows on an average tracker (see fSombra6). The result will include three variables (Gef0, Def0 and Bef0) with the irradiance/irradiation without shadows as a reference.
struct	list. When radEf@modeTrk = 'fixed' or modeTrk = 'horiz' only a component named L, which is the height (meters) of the tracker, is needed. For two-axis trackers (radEf@modeTrk = 'two'), an additional component named W, the width of the tracker, is required. Moreover, only when radEf@modeTrk = 'two' two components named Nrow and Ncol are included under this list. These components define, respectively, the number of rows and columns of the whole set of two-axis trackers in the PV plant.

distances data.frame.

When `radEf@modeTrk = 'fixed'` it includes a component named `D` for the distance between fixed surfaces. An additional component named `H` can be included with the relative height between surfaces.

When `radEf@modeTrk = 'horiz'` it only includes a component named `Lew`, being the distance between horizontal NS trackers along the East-West direction.

When `radEf@modeTrk = 'two'` it includes a component named `Lns` being the distance between trackers along the North-South direction, a component named `Lew`, being the distance between trackers along the East-West direction and a (optional) component named `H` with the relative height between surfaces.

The distances, in meters, are defined between axis of the trackers.

Value

A `Gef` object including three additional variables (`Gef0`, `Def0` and `Bef0`) in the slots `GefI`, `GefD`, `Gefdm` and `Gefy` with the irradiance/irradiation without shadows as a reference.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[calcG0](#), [fTheta](#), [fInclin](#), [calcShd](#).

A7_optimShd

Shadows calculation for a set of distances between elements of a PV grid connected plant.

Description

The optimum distance between trackers or static structures of a PV grid connected plant depends on two main factors: the ground requirement ratio (defined as the ratio of the total ground area to the generator PV array area), and the productivity of the system including shadow losses. Therefore, the optimum separation may be the one which achieves the highest productivity with the lowest ground requirement ratio.

However, this definition is not complete since the terrain characteristics and the costs of wiring or civil works could alter the decision. This function is a help for choosing this distance: it computes the productivity for a set of combinations of distances between the elements of the plant.

Usage

```
optimShd(lat,  
         modeTrk = 'fixed',  
         modeRad = 'prom',  
         dataRad,  
         sample = 'hour',  
         keep.night = TRUE,  
         sunGeometry = 'michalsky',  
         betaLim = 90, beta = abs(lat)-10, alpha = 0,  
         iS = 2, alb = 0.2, HCPV = FALSE,  
         module = list(),  
         generator = list(),  
         inverter = list(),  
         effSys = list(),  
         modeShd = '',  
         struct = list(),  
         distances = data.table(),  
         res = 2,  
         prog = TRUE)
```

Arguments

lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
modeTrk	character, to be chosen from 'fixed', 'two' or 'horiz'. When modeTrk = 'fixed' the surface is fixed (inclination and azimuth angles are constant). The performance of a two-axis tracker is calculated with modeTrk = 'two', and modeTrk = 'horiz' is the option for an horizontal N-S tracker. Its default value is modeTrk = 'fixed'
modeRad, dataRad	Information about the source data of the global irradiation. See calcG0 for details. For this function the option modeRad = 'bdI' is not supported.
sample	character, containing one of "sec", "min", "hour". This can optionally be preceded by a (positive or negative) integer and a space, or followed by "s" (used by seq.POSIXt)
keep.night	logical When it is TRUE (default) the time series includes the night.
sunGeometry	character, method for the sun geometry calculations. See calcSol , fSolD and fSolI .
betaLim, beta, alpha, iS, alb, HCPV	See calcGef for details.
module	list of numeric values with information about the PV module, Vocn open-circuit voltage of the module at Standard Test Conditions (default value 57.6 volts.) Iscn short circuit current of the module at Standard Test Conditions (default value 4.7 amperes.) Vmn maximum power point voltage of the module at Standard Test Conditions (default value 46.08 amperes.) Imn Maximum power current of the module at Standard Test Conditions (default value 4.35 amperes.)

	Ncs number of cells in series inside the module (default value 96)
	Ncp number of cells in parallel inside the module (default value 1)
	CoefVT coefficient of decrement of voltage of each cell with the temperature (default value 0.0023 volts per celsius degree)
	TONC nominal operational cell temperature, celsius degree (default value 47).
generator	list of numeric values with information about the generator,
	Nms number of modules in series (default value 12)
	Nmp number of modules in parallel (default value 11)
inverter	list of numeric values with information about the DC/AC inverter,
	Ki vector of three values, coefficients of the efficiency curve of the inverter (default c(0.01, 0.025, 0.05)), or a matrix of nine values (3x3) if there is dependence with the voltage (see references).
	Pinv nominal inverter power (W) (default value 25000 watts.)
	Vmin, Vmax minimum and maximum voltages of the MPP range of the inverter (default values 420 and 750 volts)
	Gumb minimum irradiance for the inverter to start (W/m ²) (default value 20 W/m ²)
effSys	list of numeric values with information about the system losses,
	ModQual average tolerance of the set of modules (%), default value is 3
	ModDisp module parameter dispersion losses (%), default value is 2
	OhmDC Joule losses due to the DC wiring (%), default value is 1.5
	OhmAC Joule losses due to the AC wiring (%), default value is 1.5
	MPP average error of the MPP algorithm of the inverter (%), default value is 1
	TrafoMT losses due to the MT transformer (%), default value is 1
	Disp losses due to stops of the system (%), default value is 0.5
modeShd	character, defines the type of shadow calculation. In this version of the package the effect of the shadow is calculated as a proportional reduction of the circum-solar diffuse and direct irradiances. This type of approach is selected with modeShd = 'area'. In future versions other approaches which relate the geometric shadow and the electrical connections of the PV generator will be available. If modeTrk = 'horiz' it is possible to calculate the effect of backtracking with modeShd = 'bt'. If modeShd = c('area', 'bt') the backtracking method will be carried out and therefore no shadows will appear. Finally, for two-axis trackers it is possible to select modeShd = 'prom' in order to calculate the effect of shadows on an average tracker (see fSombra6). The result will include three variables (Gef0, Def0 and Bef0) with the irradiance/irradiation without shadows as a reference.
struct	list. When modeTrk = 'fixed' or modeTrk = 'horiz' only a component named L, which is the height (meters) of the tracker, is needed. For two-axis trackers (modeTrk = 'two'), an additional component named W, the width of the tracker, is required. Moreover, two components named Nrow and Ncol are included under this list. These components define, respectively, the number of rows and columns of the whole set of trackers in the PV plant.
distances	list, whose three components are vectors of length 2: Lew (only when modeTrk = 'horiz' or modeTrk = 'two'), minimum and maximum distance (meters) between horizontal NS and two-axis trackers along the East-West direction.

A7_optimShd

21

	Lns (only when modeTrk = 'two'), minimum and maximum distance (meters) between two-axis trackers along the North-South direction.
	D (only when modeTrk = 'fixed'), minimum and maximum distance (meters) between fixed surfaces.
	These distances, in meters, are defined between the axis of the trackers.
res	numeric; optimShd constructs a sequence from the minimum to the maximum value of distances, with res as the increment, in meters, of the sequence.
prog	logical, show a progress bar; default value is TRUE

Details

optimShd calculates the energy produced for every combination of distances as defined by distances and res. The result of this function is a [Shade-class](#) object. A method of shadeplot for this class is defined ([shadeplot-methods](#)), and it shows the graphical relation between the productivity and the distance between trackers or fixed surfaces.

Value

A [Shade](#) object.

Author(s)

Oscar Perpiñán Lamigueiro

References

- Perpiñán, O.: Grandes Centrales Fotovoltaicas: producción, seguimiento y ciclo de vida. PhD Thesis, UNED, 2008. https://www.researchgate.net/publication/39419806_Grandes_Centrales_Fotovoltaicas_Produccion_Seguimiento_y_Ciclo_de_Vida.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[prodGCPV](#), [calcShd](#)

Examples

```
library(lattice)
library(latticeExtra)

lat = 37.2;
G0dm = c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562, 2814,
2179)
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom = list(G0dm = G0dm, Ta = Ta)

###Two-axis trackers
struct2x = list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 3)
dist2x = list(Lew = c(30, 45), Lns = c(20, 40))

ShdM2x <- optimShd(lat = lat, dataRad = prom, modeTrk = 'two',
```

```

modeShd = c('area','prom'),
distances = dist2x, struct = struct2x,
res = 5)

shadeplot(ShdM2x)

pLew = xyplot(Yf~GRR,data = ShdM2x,groups = factor(Lew),type = c('l','g'),
  main = 'Productivity for each Lew value')
pLew+glayer(panel.text(x[1], y[1], group.value))

pLns = xyplot(Yf~GRR,data = ShdM2x,groups = factor(Lns),type = c('l','g'),
  main = 'Productivity for each Lns value')
pLns+glayer(panel.text(x[1], y[1], group.value))

## 1-axis tracker with Backtracking
structHoriz = list(L = 4.83);
distHoriz = list(Lew = structHoriz$L * c(2,5));

Shd12HorizBT <- optimShd(lat = lat, dataRad = prom,
  modeTrk = 'horiz',
  betaLim = 60,
  distances = distHoriz, res = 2,
  struct = structHoriz,
  modeShd = 'bt')

shadeplot(Shd12HorizBT)

xyplot(diff(Yf)~GRR[-1],data = Shd12HorizBT,type = c('l','g'))

###Fixed system
structFixed = list(L = 5);
distFixed = list(D = structFixed$L*c(1,3));
Shd12Fixed <- optimShd(lat = lat, dataRad = prom,
  modeTrk = 'fixed',
  distances = distFixed, res = 2,
  struct = structFixed,
  modeShd = 'area')
shadeplot(Shd12Fixed)

```

A8_Meteo2Meteo

Transformation of intradaily meteorological data into daily and daily into monthly data.

Description

Functions for the class Meteo that transforms an intradaily Meteo object into a daily and a daily into a monthly.

Usage

```
Meteoi2Meteod(G0i)
```

```
Meteod2Meteom(G0d)
```

Arguments

- G0i

A Meteo object with intradaily data
- G0d

A Meteo object with daily data

Value

A Meteo object

See Also

[readBDd](#), [readG0dm](#), [readSIAR](#)

Examples

```
G0dm = c(2.766,3.491,4.494,5.912,6.989,7.742,7.919,
        7.027,5.369,3.562,2.814,2.179) * 1000;
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2,
      28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom = list(G0dm = G0dm, Ta = Ta)

g0 = calcG0(lat = 37.2, dataRad = prom, modeRad = 'aguiar')
G0i = as.data.tableI(g0)
G0i = dt2Meteo(G0i, lat = 37.2)
G0i

G0d = MeteoI2Meteod(G0i)
G0d

G0m = Meteod2Meteom(G0d)
G0m
```

A8_readBD	Daily or intradaily values of global horizontal irradiation and ambient temperature from a local file or a data.frame.
-----------	--

Description

Constructor for the class Meteo with values of *daily* or *intradaily* values of global horizontal irradiation and ambient temperature from a local file or a data.frame.

Usage

```
readBDd(file, lat,
        format = '%d/%m/%Y',
        header = TRUE, fill = TRUE, dec = '.', sep = ';',
        dates.col = 'Dates', ta.col = 'Ta',
        g0.col = 'G0', keep.cols = FALSE, ...)

readBDi(file, lat,
        format = '%d/%m/%Y %H:%M:%S',
        header = TRUE, fill = TRUE, dec = '.',
```

```

sep = ';', dates.col = 'Dates', times.col,
ta.col = 'Ta', g0.col = 'G0', keep.cols = FALSE, ...)

dt2Meteo(file, lat, source = '', type)

zoo2Meteo(file, lat, source = '')

```

Arguments

file	<p>The name of the file (readBDd and readBDi), data.frame (or data.table) (dt2Meteo) or zoo (zoo2Meteo) which the data are to be read from. It should contain a column G0d with <i>daily</i> (readBDd) or G0 with <i>intradaily</i> (readBDi) values of global horizontal irradiation (Wh/m²). It should also include a column named Ta with values of ambient temperature. However, if the object is only a vector with irradiation values, it will be converted to a data.table with two columns named G0 and Ta (filled with constant values)</p> <p>If the Meteo object is to be used with calcG0 (or fCompD, fCompI) and the option corr = 'none', the file/data.frame must include three columns named G0, B0 and D0 with values of global, direct and diffuse irradiation on the horizontal plane.</p> <p>Only for daily data: if the ambient temperature is not available, the file should include two columns named TempMax and TempMin with daily values of maximum and minimum ambient temperature, respectively (see fTemp for details).</p>
header, fill, dec, sep	See fread
format	character string with the format of the dates or time index. (Default for daily time bases: %d/%m/%Y). (Default for intradaily time bases: %d/%m/%Y %H:%M:%S)
lat	numeric, latitude (degrees) of the location.
dates.col	character string with the name of the column which contains the dates of the time series.
times.col	character string with the name of the column which contains the time index of the series in case it is in a different column than the dates.
source	character string with information about the source of the values. (Default: the name of the file).
ta.col, g0.col	character, the name of the columns with the information of ambient temperature and radiation in the provided file
keep.cols	If keep.cols=FALSE (default value), the Meteo object does not include the columns that are not important for the rest of operations
...	Arguments for fread
type	character, type of the data in dt2Meteo. To choose between 'prom', 'bd' and 'bdI'. If it is not provided, the function dt2Meteo calculates the type.

Value

A Meteo object.

Author(s)

Oscar Perpiñán Lamigueiro.

A8_readG0dm

25

See Also[fread](#), [readG0dm](#).**Examples**

```
data(helios)
names(helios) = c('Dates', 'G0d', 'TempMax', 'TempMin')

bd = dt2Meteo(helios, lat = 41, source = 'helios-IES', type = 'bd')

getData(bd)

xyplot(bd)
```

*A8_readG0dm**Monthly mean values of global horizontal irradiation.*

Description

Constructor for the class `Meteo` with 12 values of monthly means of irradiation.

Usage

```
readG0dm(G0dm, Ta = 25, lat = 0,
  year= as.POSIXlt(Sys.Date())$year+1900,
  promDays = c(17,14,15,15,15,10,18,18,18,19,18,13),
  source = '')
```

Arguments

<code>G0dm</code>	numeric, 12 values of monthly means of daily global horizontal irradiation (Wh/m ²).
<code>Ta</code>	numeric, 12 values of monthly means of ambient temperature (degrees Celsius).
<code>lat</code>	numeric, latitude (degrees) of the location.
<code>year</code>	numeric (Default: current year).
<code>promDays</code>	numeric, set of the average days for each month.
<code>source</code>	character string with information about the source of the values.

Value

`Meteo` object

Author(s)

Oscar Perpiñán Lamigueiro.

See Also[readBDd](#)

Examples

```
G0dm =
  c(2.766,3.491,4.494,5.912,6.989,7.742,7.919,7.027,5.369,3.562,2.814,2.179) * 1000;
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
BD <- readG0dm(G0dm = G0dm, Ta = Ta, lat = 37.2)
print(BD)
getData(BD)
xyplot(BD)
```

A8_readSIAR

Meteorological data from the SIAR network.

Description

Download, interpolate and transform meteorological data fromm the SIAR network.

Usage

```
readSIAR(Lon = 0, Lat = 0,
  inicio = paste(year(Sys.Date())-1, '01-01', sep = '-'),
  final = paste(year(Sys.Date())-1, '12-31', sep = '-'),
  tipo = 'Mensuales', n_est = 3)
```

Arguments

Lon	numeric, longitude (degrees) of the location.
Lat	numeric, latitude (degrees) of the location.
inicio	character or Date, first day of the records.
final	character or Date, last day of the records.
tipo	character, tipe of the records. To choose between Mensuales, Semanales, Diarios, Horarios.
n_est	integer, select that number of stations closest to the given point and then perform an IDW (Inverse Distance Weighting) interpolation with these data.

Value

A Meteo object

Author(s)

Francisco Delgado López

See Also

[readG0dm](#), [readBDd](#)

Examples

```
library(httr2)
library(jsonlite)

SIAR = readSIAR(Lon = -3.603, Lat = 40.033,
## Aranjuez, Community of Madrid, Spain
              inicio = '2023-01-01',
              final = '2023-05-01',
              tipo = 'Mensuales', n_est = 3)

SIAR
```

B1_Meteo-class*Class "Meteo"*

Description

A class for meteorological data.

Objects from the Class

Objects can be created by the family of [readBDd](#) functions.

Slots

latm: Latitude (degrees) of the meteorological station or source of the data.

data: A `data.table` object with the time series of daily irradiation (G_0 , Wh/m²), the ambient temperature (T_a) or the maximum and minimum ambient temperature (`TempMax` and `TempMin`).

source: A character with a short description of the source of the data.

type: A character, `prom`, `bd` or `bdI` depending on the constructor.

Methods

getData signature(object = "Meteo"): extracts the data slot as a `data.table` object.

getG0 signature(object = "Meteo"): extracts the irradiation as vector.

getLat signature(object = "Meteo"): extracts the latitude value.

indexD signature(object = "Meteo"): extracts the index of the data slot.

xyplot signature(x = "formula", data = "Meteo"): plot the content of the object according to the formula argument.

xyplot signature(x = "Meteo", data = "missing"): plot the data slot using the `xyplot` method for zoo objects.

Author(s)

Oscar Perpiñán Lamigueiro.

See Also

[readBDd](#), [readBDi](#), [zoo2Meteo](#), [dt2Meteo](#), [readG0dm](#),

B2_Sol-class

*Class "Sol": Apparent movement of the Sun from the Earth***Description**

A class which describe the apparent movement of the Sun from the Earth.

Objects from the Class

Objects can be created by `calcSol`.

Slots

`lat`: numeric, latitude (degrees) as defined in the call to `calcSol`.

`sold`: Object of class "data.table" created by `fSold`.

`solI`: Object of class "data.table" created by `fSolI`.

`method`: character, method for the sun geometry calculations.

`sample`: difftime, increment of the intradaily sequence.

Methods

as.data.tableD signature(object = "Sol"): conversion to a data.table with daily values.

as.data.tableI signature(object = "Sol"): conversion to a data.table with intradaily values.

getLat signature(object = "Sol"): latitude (degrees) as defined in the call to `calcSol`.

indexD signature(object = "Sol"): index of the sold slot.

indexI signature(object = "Sol"): index of the solI object.

xyplot signature(x = "formula", data = "Sol"): displays the contents of a Sol object with the xyplot method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

`G0`, `Gef`.

B3_G0-class

*Class "G0": irradiation and irradiance on the horizontal plane.***Description**

This class contains the global, diffuse and direct irradiation and irradiance on the horizontal plane, and ambient temperature.

Objects from the Class

Objects can be created by the function `calcG0`.

Slots

G0D: Object of class `data.table` created by `fCompD`. It includes daily values of:

Fd: numeric, the diffuse fraction

Ktd: numeric, the clearness index

G0d: numeric, the global irradiation on a horizontal surface (Wh/m²)

D0d: numeric, the diffuse irradiation on a horizontal surface (Wh/m²)

B0d: numeric, the direct irradiation on a horizontal surface (Wh/m²)

G0I: Object of class `data.table` created by `fCompI`. It includes values of:

kt: numeric, clearness index

G0: numeric, global irradiance on a horizontal surface, (W/m²)

D0: numeric, diffuse irradiance on a horizontal surface, (W/m²)

B0: numeric, direct irradiance on a horizontal surface, (W/m²)

G0dm: Object of class `data.table` with monthly mean values of daily irradiation.

G0y: Object of class `data.table` with yearly sums of irradiation.

Ta: Object of class `data.table` with intradaily ambient temperature values.

Besides, this class contains the slots from the `Sol` and `Meteo` classes.

Extends

Class "`Meteo`", directly. Class "`Sol`", directly.

Methods

as.data.tableD signature(object = "G0"): conversion to a `data.table` with daily values.

as.data.tableI signature(object = "G0"): conversion to a `data.table` with intradaily values.

as.data.tableM signature(object = "G0"): conversion to a `data.table` with monthly values.

as.data.tableY signature(object = "G0"): conversion to a `data.frame` with yearly values.

indexD signature(object = "G0"): index of the `solD` slot.

indexI signature(object = "G0"): index of the `solI` slot.

getLat signature(object = "G0"): latitude of the inherited `Sol` object.

xyplot signature(x = "G0", data = "missing"): display the time series of daily values of irradiation.

xyplot signature(x = "formula", data = "G0"): displays the contents of a `G0` object with the `xyplot` method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[Sol](#), [Gef](#).

B4_Gef-class

Class "Gef": irradiation and irradiance on the generator plane.

Description

This class contains the global, diffuse and direct irradiation and irradiance on the horizontal plane, and ambient temperature.

Objects from the Class

Objects can be created by the function [calcGef](#).

Slots

`GefI`: Object of class `data.table` created by [fInclin](#). It contains these components:

Bo: Extra-atmospheric irradiance on the inclined surface (W/m^2)

Bn: Direct normal irradiance (W/m^2)

G, B, D, Di, Dc, R: Global, direct, diffuse (total, isotropic and anisotropic) and albedo irradiance incident on an inclined surface (W/m^2)

Gef, Bef, Def, Dief, Dcef, Ref: Effective global, direct, diffuse (total, isotropic and anisotropic) and albedo irradiance incident on an inclined surface (W/m^2)

FTb, FTd, FTr: Factor of angular losses for the direct, diffuse and albedo components

`GefD`: Object of class `data.table` with daily values of global, diffuse and direct irradiation.

`Gefdm`: Object of class `data.table` with monthly means of daily global, diffuse and direct irradiation.

`Gefy`: Object of class `data.table` with yearly sums of global, diffuse and direct irradiation.

`Theta`: Object of class `data.table` created by [fTheta](#). It contains these components:

Beta: numeric, inclination angle of the surface (radians). When `modeTrk='fixed'` it is the value of the argument `beta` converted from degrees to radians.

Alpha: numeric, azimuth angle of the surface (radians). When `modeTrk='fixed'` it is the value of the argument `alpha` converted from degrees to radians.

cosTheta: numeric, cosine of the incidence angle of the solar irradiance on the surface

iS: numeric, degree of dirtiness.

alb: numeric, albedo reflection coefficient.

B4_Gef-class

31

modeTrk: character, mode of tracking.

modeShd: character, mode of shadows.

angGen: A list with the values of alpha, beta and betaLim.

struct: A list with the dimensions of the structure.

distances: A data.frame with the distances between structures.

Extends

Class "**G0**", directly. Class "**Meteo**", by class "G0", distance 2. Class "**Sol**", by class "G0", distance 2.

Methods

as.data.tableD signature(object = "Gef"): conversion to a data.table with daily values.

as.data.tableI signature(object = "Gef"): conversion to a data.table with intradaily values.

as.data.tableM signature(object = "Gef"): conversion to a data.table with monthly values.

as.data.tableY signature(object = "Gef"): conversion to a data.table with yearly values.

indexD signature(object = "Gef"): index of the solD slot.

indexI signature(object = "Gef"): index of the solI slot.

getLat signature(object = "Gef"): latitude of the inherited **Sol** object.

xyplot signature(x = "Gef", data = "missing"): display the time series of daily values of irradiation.

xyplot signature(x = "formula", data = "Gef"): displays the contents of a Gef object with the xyplot method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:[10.18637/jss.v050.i09](https://doi.org/10.18637/jss.v050.i09)

See Also

Sol, **G0**.

B5_ProdGCPV-class	Class "ProdGCPV": performance of a grid connected PV system.
-------------------	--

Description

A class containing values of the performance of a grid connected PV system.

Objects from the Class

Objects can be created by `prodGCPV`.

Slots

`prodI`: Object of class `data.table` created by `fProd`. It includes these components:

Tc: cell temperature, °C.

Voc, Isc, Vmpp, Impp: open circuit voltage, short circuit current, MPP voltage and current, respectively.

Vdc, Idc: voltage and current at the input of the inverter.

Pdc: power at the input of the inverter, W

Pac: power at the output of the inverter, W

EffI: efficiency of the inverter

`prodD`: A `data.table` object with daily values of AC (Eac) and DC (Edc) energy (Wh), and productivity (Yf, Wh/Wp) of the system.

`prodDm`: A `data.table` object with monthly means of daily values of AC and DC energy (kWh), and productivity of the system.

`prody`: A `data.table` object with yearly sums of AC and DC energy (kWh), and productivity of the system.

`module`: A list with the characteristics of the module.

`generator`: A list with the characteristics of the PV generator.

`inverter`: A list with the characteristics of the inverter.

`effSys`: A list with the efficiency values of the system.

Besides, this class contains the slots from the "`Meteo`", "`Sol`", "`G0`" and "`Gef`" classes.

Extends

Class "`Gef`", directly. Class "`G0`", by class "`Gef`", distance 2. Class "`Meteo`", by class "`Gef`", distance 3. Class "`Sol`", by class "`Gef`", distance 3.

Methods

as.data.tableD signature(object = "ProdGCPV"): conversion to a `data.table` with daily values.

as.data.tableI signature(object = "ProdGCPV"): conversion to a `data.table` with intradaily values.

as.data.tableM signature(object = "ProdGCPV"): conversion to a `data.table` with monthly values.

as.data.tableY signature(object = "ProdGCPV"): conversion to a `data.table` with yearly values.

indexD signature(object = "ProdGCPV"): index of the sold slot.

indexI signature(object = "ProdGCPV"): index of the solI object.
getLat signature(object = "ProdGCPV"): latitude of the inherited **Sol** object.
xyplot signature(x = "ProdGCPV", data = "missing"): display the time series of daily values.
xyplot signature(x = "formula", data = "ProdGCPV"): displays the contents of a ProdGCPV object with the xyplot method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

Sol, **G0**, **Gef**, **Shade**.

B6_ProdPVPS-class	<i>Class "ProdPVPS": performance of a PV pumping system.</i>
-------------------	--

Description

Performance of a PV pumping system with a centrifugal pump and a variable frequency converter.

Objects from the Class

Objects can be created by **prodPVPS**.

Slots

prodI: Object of class `data.table` with these components:

Q: Flow rate, (m³/h)

Pb, Ph: Pump shaft power and hydraulical power (W), respectively.

etam, etab: Motor and pump efficiency, respectively.

f: Frequency (Hz)

prodD: A `data.table` object with daily values of AC energy (Wh), flow (m³) and productivity of the system.

prodDm: A `data.table` object with monthly means of daily values of AC energy (kWh), flow (m³) and productivity of the system.

prody: A `data.table` object with yearly sums of AC energy (kWh), flow (m³) and productivity of the system.

pump A list extracted from **pumpCoef**

H Total manometric head (m)

Pg Nominal power of the PV generator (Wp)

converter list containing the nominal power of the frequency converter, Pnom, and Ki, vector of three values, coefficients of the efficiency curve.

effSys list of numeric values with information about the system losses

Besides, this class contains the slots from the **Gef** class.

Extends

Class "**Gef**", directly. Class "**G0**", by class "Gef", distance 2. Class "**Meteo**", by class "Gef", distance 3. Class "**Sol**", by class "Gef", distance 3.

Methods

as.data.tableD signature(object = "ProdPVPS"): conversion to a data.table with daily values.
as.data.tableI signature(object = "ProdPVPS"): conversion to a data.table with intradaily values.
as.data.tableM signature(object = "ProdPVPS"): conversion to a data.table with monthly values.
as.data.tableY signature(object = "ProdPVPS"): conversion to a data.table with yearly values.
indexD signature(object = "ProdPVPS"): index of the sold slot.
indexI signature(object = "ProdPVPS"): index of the solI object.
getLat signature(object = "ProdPVPS"): latitude of the inherited **Sol** object.
xyplot signature(x = "ProdPVPS", data = "missing"): display the time series of daily values.
xyplot signature(x = "formula", data = "ProdPVPS"): displays the contents of a ProdPVPS object with the xyplot method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Abella, M. A., Lorenzo, E. y Chenlo, F.: PV water pumping systems based on standard frequency converters. Progress in Photovoltaics: Research and Applications, 11(3):179–191, 2003, ISSN 1099-159X.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

prodPVPS, **fPump**.

B7_Shade-class

Class "*Shade*": shadows in a PV system.

Description

A class for the optimization of shadows in a PV system.

Objects from the Class

Objects can be created by **optimShd**.

Slots

FS: numeric, shadows factor values for each combination of distances.

GRR: numeric, Ground Requirement Ratio for each combination.

Yf: numeric, final productivity for each combination.

FS.loess: A local fitting of FS with loess.

Yf.loess: A local fitting of Yf with loess.

modeShd: character, mode of shadows.

struct: A list with the dimensions of the structure.

distances: A data.frame with the distances between structures.

res numeric, difference (meters) between the different steps of the calculation.

Besides, as a reference, this class includes a [ProdGCPV](#) object with the performance of a PV systems without shadows.

Extends

Class "[ProdGCPV](#)", directly. Class "[Gef](#)", by class "ProdGCPV", distance 2. Class "[G0](#)", by class "ProdGCPV", distance 3. Class "[Meteo](#)", by class "ProdGCPV", distance 4. Class "[Sol](#)", by class "ProdGCPV", distance 4.

Methods

as.data.frame signature(x = "Shade"): conversion to a data.frame including columns for distances (Lew, Lns, and D) and results (FS, GRR and Yf).

shadeplot signature(x = "Shade"): display the results of the iteration with a level plot for the two-axis tracking, or with conventional plot for horizontal tracking and fixed systems.

xyplot signature(x = "formula", data = "Shade"): display the content of the Shade object with the xyplot method for formulas.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O.: Grandes Centrales Fotovoltaicas: producción, seguimiento y ciclo de vida. PhD Thesis, UNED, 2008. https://www.researchgate.net/publication/39419806_Grandes_Centrales_Fotovoltaicas_Produccion_Seguimiento_y_Ciclo_de_Vida.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[Gef](#), [ProdGCPV](#).

C_corrFdKt	<i>Correlations between the fraction of diffuse irradiation and the clearness index.</i>
------------	--

Description

A set of correlations between the fraction of diffuse irradiation and the clearness index used by [fCompD](#) and [fCompI](#).

Usage

```
## Monthly means of daily values
Ktm(sol, G0dm)
FdKtPage(sol, G0dm)
FdKtLJ(sol, G0dm)

## Daily values
Ktd(sol, G0d)
FdKtCPR(sol, G0d)
FdKtEKDd(sol, G0d)
FdKtCLIMEDd(sol, G0d)

## Intradaily values
Kti(sol, G0i)
FdKtEKDh(sol, G0i)
FdKtCLIMEDh(sol, G0i)
FdKtBRL(sol, G0i)
```

Arguments

sol	A Sol object, it may be the result of the calcSol function.
G0dm	A Meteo object with monthly means of radiation. It may be the result of the readG0dm function.
G0d	A Meteo object with daily values of radiation. It may be the result of the readBDd (or equivalent) function.
G0i	A Meteo object with intradaily values of radiation. It may be the result of the readBDi (or equivalent) function.

Value

A data.table, with two columns:

Fd	A numeric, the diffuse fraction.
Kt	A numeric, the clearness index(provided by the Kt functions).

Author(s)

Oscar Perpiñán Lamigueiro; The BRL model was suggested by Kevin Ummel.

References

- Page, J. K., The calculation of monthly mean solar radiation for horizontal and inclined surfaces from sunshine records for latitudes 40N-40S. En U.N. Conference on New Sources of Energy, vol. 4, págs. 378–390, 1961.
- Collares-Pereira, M. y Rabl, A., The average distribution of solar radiation: correlations between diffuse and hemispherical and between daily and hourly insolation values. Solar Energy, 22:155–164, 1979.
- Erbs, D.G, Klein, S.A. and Duffie, J.A., Estimation of the diffuse radiation fraction for hourly, daily and monthly-average global radiation. Solar Energy, 28:293:302, 1982.
- De Miguel, A. et al., Diffuse solar irradiation model evaluation in the north mediterranean belt area, Solar Energy, 70:143-153, 2001.
- Ridley, B., Boland, J. and Lauret, P., Modelling of diffuse solar fraction with multiple predictors, Renewable Energy, 35:478-482, 2010.

See Also

[fCompD](#), [fCompI](#)

Examples

```
lat = 37.2
BTd = fBTd(mode = 'prom')
G0dm = c(2.766, 3.491, 4.494, 5.912, 6.989, 7.742, 7.919, 7.027, 5.369,
         3.562, 2.814, 2.179)*1000;
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2,
       15.2)

prom = readG0dm(G0dm = G0dm, Ta = Ta, lat = lat)
sol = calcSol(lat = lat, BTd = BTd)

Kt = Ktm(sol = sol, G0dm = prom)
Kt

Page = FdKtPage(sol = sol, G0dm = prom)
LJ = FdKtLJ(sol = sol, G0dm = prom)
Monthly = merge(Page, LJ, by = 'Kt',
                suffixes = c('.Page', '.LJ'))
Monthly

xyplot(Fd.Page+Fd.LJ~Kt, data = Monthly,
       type = c('l', 'g'), auto.key = list(space = 'right'))

Kt = Ktd(sol = sol, G0d = prom)
Kt

CPR = FdKtCPR(sol = sol, G0d = prom)
CLIMEDd = FdKtCLIMEDd(sol = sol, G0d = prom)
Daily = merge(CPR, CLIMEDd, by = 'Kt',
              suffixes = c('.CPR', '.CLIMEDd'))
Daily

xyplot(Fd.CPR + Fd.CLIMEDd ~ Kt, data = Daily,
       type = c('l', 'g'), auto.key = list(space = 'right'))
```

C_fBTd

*Daily time base***Description**

Construction of a daily time base for solar irradiation calculation

Usage

```
fBTd(mode = "prom",
      year = as.POSIXlt(Sys.Date())$year+1900,
      start = paste('01-01-',year,sep = ''),
      end = paste('31-12-',year,sep = ''),
      format = '%d-%m-%Y')
```

Arguments

mode	character, controls the type of time base to be created. With mode = 'serie' the result is a daily time series from start to end. With mode = 'prom' only twelve days, one for each month, are included. During these 'average days' the declination angle is equal to the monthly mean of this angle.
year	which year is to be used for the time base when mode = 'prom'. Its default value is the current year.
start	first day of the time base for mode = 'serie'. Its default value is the first of January of the current year.
end	last day of the time base for mode = 'serie'. Its default value is the last day of December of the current year.
format	format of start and end.

Details

This function is commonly used inside fSolD.

Value

This function returns a POSIXct object.

Author(s)

Oscar Perpiñán Lamigueiro

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

fSolD, as.POSIXct, seq.POSIXt.

Examples

```
#Average days
fBTd(mode = 'prom')

#The day #100 of the year 2008
BTd = fBTd(mode = 'serie', year = 2008)
BTd[100]
```

C_fBTi	<i>Intra-daily time base</i>
--------	------------------------------

Description

Construction of an intra-daily time base for solar irradiation calculation

Usage

```
fBTi(BTd, sample = 'hour')
```

Arguments

- BTd
- vector, it may be a result for fBTd or indexD
- sample
- character, identify the sample of the time set. Its default value is 'hour'.

Details

This function is commonly used inside fSolI.

Value

This function returns a POSIXct object.

Author(s)

Oscar Perpiñán Lamigueiro

Examples

```
#Average days
BTd <- fBTd(mode = 'prom')

#Intradaily base time for the first day
BTi <- fBTi(BTd = BTd[1], sample = 'hour')
BTi
```

C_fCompD

*Components of daily global solar irradiation on a horizontal surface***Description**

Extract the diffuse and direct components from the daily global irradiation on a horizontal surface by means of regressions between the clearness index and the diffuse fraction parameters.

Usage

```
fCompD(sol, G0d, corr = "CPR", f)
```

Arguments

sol	A Sol object from calcSol or a data.table object from fSolD . Both of them include a component named Bo0d, which stands for the extra-atmospheric daily irradiation incident on a horizontal surface
G0d	A Meteo object from readG0dm , readBDd , or a data.table object containing daily global irradiation (Wh/m ²) on a horizontal surface. See below for corr = 'none'.
corr	A character, the correlation between the fraction of diffuse irradiation and the clearness index to be used. With this version several options are available, as described in corrFdKt . For example, the FdKtPage is selected with corr = 'Page' and the FdKtCPR with corr = 'CPR'. If corr = 'user' the use of a correlation defined by a function f is possible. If corr = 'none' the G0d object should include information about global, diffuse and direct daily irradiation with columns named G0d, D0d and B0d, respectively.
f	A function defining a correlation between the fraction of diffuse irradiation and the clearness index. It is only necessary when corr = 'user'

Value

A data.table object which includes:

Fd	numeric, the diffuse fraction
Ktd	numeric, the clearness index
G0d	numeric, the global irradiation on a horizontal surface (Wh/m ²)
D0d	numeric, the diffuse irradiation on a horizontal surface (Wh/m ²)
B0d	numeric, the direct irradiation on a horizontal surface (Wh/m ²)

Author(s)

Oscar Perpiñán Lamigueiro

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

C_fCompI

41

See Also[fCompI](#)**Examples**

```
lat = 37.2;
BTd = fBTd(mode = 'serie')

SolD <- fSolD(lat, BTd[100])

G0d = 5000
fCompD(SolD, G0d, corr = "Page")
fCompD(SolD, G0d, corr = "CPR")

#define a function fKtd with the correlation of CPR
fKtd = function(sol, G0d){
  Kt = Ktm(sol, G0d)
  Fd = (0.99*(Kt <= 0.17))+ (Kt>0.17)*(1.188 -2.272 * Kt + 9.473 * Kt^2 -
  21.856 * Kt^3 + 14.648 * Kt^4)
  return(data.table(Fd, Kt))}
#The same as with corr = "CPR"
fCompD(SolD, G0d, corr = "user", f = fKtd)

lat = -37.2;
SolDs <- fSolD(lat, BTd[283])
G0d = data.table(Dates = SolDs$Dates, G0d = 5000)
fCompD(SolDs, G0d, corr = "CPR")

lat = 37.2;
G0dm = c(2.766,3.491,4.494,5.912,6.989,7.742,7.919,7.027,5.369,3.562,2.814,2.179)*1000;
Rad = readG0dm(G0dm, lat = lat)
solD <- fSolD(lat, fBTd(mode = 'prom'))
fCompD(solD, Rad, corr = 'Page')
```

C_fCompI*Calculation of solar irradiance on a horizontal surface*

Description

From the daily global, diffuse and direct irradiation values supplied by `fCompD`, the profile of the global, diffuse and direct irradiance is calculated with the `rd` and `rg` components of `fSolI`.

Usage

```
fCompI(sol, compD, G0I, corr = 'none', f, filterG0 = TRUE)
```

Arguments

<code>sol</code>	A <code>Sol</code> object as provided by calcSol or a <code>data.table</code> object as provided by fSolI .
<code>compD</code>	A <code>data.table</code> object as provided by <code>fCompD</code> . It is not considered if <code>G0I</code> is provided.

G0I	A Meteo object from readBDi , dt2Meteo or zoo2Meteo , or a <code>data.table</code> object containing <i>intradaily</i> global irradiance (W/m ²) on a horizontal surface. See below for <code>corr = 'none'</code> .
corr	A character, the correlation between the the fraction of intradaily diffuse irradiation and the clearness index to be used. It is ignored if G0I is not provided. With this version several correlations are available, as described in corrFdKt . You should choose one of <i>intradaily</i> proposals. For example, the FdKtCLIMEDh is selected with <code>corr = 'CLIMEDh'</code> . If <code>corr = 'user'</code> the use of a correlation defined by a function <code>f</code> is possible. If <code>corr = 'none'</code> the G0I object must include information about global, diffuse and direct intradaily irradiation with columns named G0, D0 and B0, respectively.
f	A function defining a correlation between the fraction of diffuse irradiation and the clearness index. It is only necessary when <code>corr = 'user'</code>
filterG0	A logical. If TRUE (default) this function sets the global irradiation values to NA when they are higher than the extra-atmospheric irradiation values.

Value

A `data.table` with these components:

kt	numeric, clearness index.
fd	numeric, diffuse fraction.
G0	numeric, global irradiance on a horizontal surface, (W/m ²)
D0	numeric, diffuse irradiance on a horizontal surface, (W/m ²)
B0	numeric, direct irradiance on a horizontal surface, (W/m ²)

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Collares-Pereira, M. y Rabl, A., The average distribution of solar radiation: correlations between diffuse and hemispherical and between daily and hourly insolation values. *Solar Energy*, 22:155–164, 1979.
- Perpiñán, O, *Energía Solar Fotovoltaica*, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", *Journal of Statistical Software*, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fCompD](#), [fSolI](#), [calcSol](#), [corrFdKt](#).

Examples

```
lat <- 37.2

BTd <- fBTd(mode = 'serie')
solD <- fSolD(lat, BTd[100])
solI <- fSolI(solD, sample = 'hour')
G0d <- data.table(Dates = solD$Dates, G0d = 5000)
```

```
compD <- fCompD(solD, G0d, corr = "Page")
fCompI(solI, compD)

sol <- calcSol(lat, fBTd(mode = 'prom'), sample = 'hour', keep.night = FALSE)

G0dm <- c(2.766, 3.491, 4.494, 5.912, 6.989, 7.742,
          7.919, 7.027, 5.369, 3.562, 2.814, 2.179)*1000

Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9,
        24.3, 18.2, 17.2, 15.2)

BD <- readG0dm(G0dm = G0dm, Ta = Ta, lat = lat)
compD <- fCompD(sol, BD, corr = 'Page')
compI <- fCompI(sol, compD)
head(compI)

## Use of 'corr'. The help page of calcG0 includes additional examples
## with intradaily data xyplot(fd ~ kt, data = compI)

climed <- fCompI(sol, G0I = compI, corr = 'CLIMEDh')
xyplot(Fd ~ Kt, data = climed)

ekdh <- fCompI(sol, G0I = compI, corr = 'EKDh')
xyplot(Fd ~ Kt, data = ekdh)

brl <- fCompI(sol, G0I = compI, corr = 'BRL')
xyplot(Fd ~ Kt, data = brl)
```

C_fInclin	<i>Solar irradiance on an inclined surface</i>
-----------	--

Description

The solar irradiance incident on an inclined surface is calculated from the direct and diffuse irradiance on a horizontal surface, and from the evolution of the angles of the Sun and the surface. Moreover, the effect of the angle of incidence and dust on the PV module is included to obtain the effective irradiance.

This function is used by the [calcGef](#) function.

Usage

```
fInclin(compI, angGen, iS = 2, alb = 0.2, horizBright = TRUE, HCPV = FALSE)
```

Arguments

compI	A G0 object. It may be the result of calcG0 .
angGen	A data.table object, including at least three variables named Beta, Alpha and cosTheta. It may be the result of fTheta .
iS	integer, degree of dirtiness. Its value must be included in the set (1,2,3,4). iS = 1 corresponds to a clean surface while iS = 4 is the choice for a dirty surface. Its default value is 2
alb	numeric, albedo reflection coefficient. Its default value is 0.2

horizBright	logical, if TRUE, the horizon brightness correction proposed by Reind et al. is used.
HCPV	logical, if TRUE the diffuse and albedo components of the <i>effective</i> irradiance are set to zero. HCPV is the acronym of High Concentration PV system.

Details

The solar irradiance incident on an inclined surface can be calculated from the direct and diffuse irradiance on a horizontal surface, and from the evolution of the angles of the Sun and the surface. The transformation of the direct radiation is straightforward since only geometric considerations are needed. However, the treatment of the diffuse irradiance is more complex since it involves the modelling of the atmosphere. There are several models for the estimation of diffuse irradiance on an inclined surface. The one which combines simplicity and acceptable results is the proposal of Hay and McKay. This model divides the diffuse component in isotropic and anisotropic whose values depends on a anisotropy index. On the other hand, the effective irradiance, the fraction of the incident irradiance that reaches the cells inside a PV module, is calculated with the losses due to the angle of incidence and dirtiness. This behaviour can be simulated with a model proposed by Martin and Ruiz requiring information about the angles of the surface and the level of dirtiness (iS).

Value

A data.table object with these components:

Bo	Extra-atmospheric irradiance on the inclined surface (W/m ²)
Bn	Direct normal irradiance (W/m ²)
G, B, D, Di, Dc, R	Global, direct, diffuse (total, isotropic and anisotropic) and albedo irradiance incident on an inclined surface (W/m ²)
Gef, Bef, Def, Dief, Dcef, Ref	Effective global, direct, diffuse (total, isotropic and anisotropic) and albedo irradiance incident on an inclined surface (W/m ²)
FTb, FTd, FTr	Factor of angular losses for the direct, diffuse and albedo components

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Hay, J. E. and McKay, D. C.: Estimating Solar Irradiance on Inclined Surfaces: A Review and Assessment of Methodologies. Int. J. Solar Energy, (3):pp. 203, 1985.
- Martin, N. and Ruiz, J.M.: Calculation of the PV modules angular losses under field conditions by means of an analytical model. Solar Energy Materials & Solar Cells, 70:25–38, 2001.
- D. T. Reindl and W. A. Beckman and J. A. Duffie: Evaluation of hourly tilted surface radiation models, Solar Energy, 45:9-17, 1990.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fTheta](#), [fCompI](#), [calcGef](#).

C_fProd

45

*C_fProd**Performance of a PV system***Description**

Simulate the behaviour of a grid connected PV system under different conditions of irradiance and temperature. This function is used by the [prodGCPV](#) function.

Usage

```
fProd(inclin, module, generator, inverter, effSys)
```

Arguments

<i>inclin</i>	A Gef object, a <code>data.table</code> object. In case of being <code>data.table</code> it must include a component named <code>Gef</code> (effective irradiance, W/m ²) and another named <code>Ta</code> (ambient temperature, °C).
<i>module</i>	list of numeric values with information about the PV module, <i>Vocn</i> open-circuit voltage of the module at Standard Test Conditions (default value 57.6 volts.) <i>Iscn</i> short circuit current of the module at Standard Test Conditions (default value 4.7 amperes.) <i>Vmn</i> maximum power point voltage of the module at Standard Test Conditions (default value 46.08 volts.) <i>Imn</i> Maximum power current of the module at Standard Test Conditions (default value 4.35 amperes.) <i>Ncs</i> number of cells in series inside the module (default value 96) <i>Ncp</i> number of cells in parallel inside the module (default value 1) <i>CoefVT</i> coefficient of decrement of voltage of each cell with the temperature (default value 0.0023 volts per celsius degree) <i>TONC</i> nominal operational cell temperature, celsius degree (default value 47).
<i>generator</i>	list of numeric values with information about the generator, <i>Nms</i> number of modules in series (default value 12) <i>Nmp</i> number of modules in parallel (default value 11)
<i>inverter</i>	list of numeric values with information about the DC/AC inverter, <i>Ki</i> vector of three values, coefficients of the efficiency curve of the inverter (default <code>c(0.01, 0.025, 0.05)</code>), or a matrix of nine values (3x3) if there is dependence with the voltage (see references). <i>Pinv</i> nominal inverter power (W) (default value 25000 watts.) <i>Vmin</i> , <i>Vmax</i> minimum and maximum voltages of the MPP range of the inverter (default values 420 and 750 volts) <i>Gumb</i> minimum irradiance for the inverter to start (W/m ²) (default value 20 W/m ²)
<i>effSys</i>	list of numeric values with information about the system losses, <i>ModQual</i> average tolerance of the set of modules (%), default value is 3 <i>ModDisp</i> module parameter dispersion losses (%), default value is 2

OhmDC Joule losses due to the DC wiring (%), default value is 1.5
 OhmAC Joule losses due to the AC wiring (%), default value is 1.5
 MPP average error of the MPP algorithm of the inverter (%), default value is 1
 TrafoMT losses due to the MT transformer (%), default value is 1
 Disp losses due to stops of the system (%), default value is 0.5

Value

If `inclin` is `data.table` or `Gef` object, the result is a `data.table` object with these components:

Tc	cell temperature, °C.
Voc, Isc, Vmpp, Impp	open circuit voltage, short circuit current, MPP voltage and current, respectively, in the conditions of irradiance and temperature provided by <code>Inclin</code>
Vdc, Idc	voltage and current at the input of the inverter. If no voltage limitation occurs (according to the values of <code>inverter\$Vmax</code> and <code>inverter\$Vmin</code>), their values are identical to <code>Vmpp</code> and <code>Impp</code> . If the limit values are reached a warning is produced
Pdc	power at the input of the inverter, W
Pac	power at the output of the inverter, W
EffI	efficiency of the inverter

Author(s)

Oscar Perpiñán Lamigueiro

References

- Jantsch, M., Schmidt, H. y Schmid, J.: Results on the concerted action on power conditioning and control. 11th European photovoltaic Solar Energy Conference, 1992.
- Baumgartner, F. P., Schmidt, H., Burger, B., Bründlinger, R., Haeberlin, H. and Zehner, M.: Status and Relevance of the DC Voltage Dependency of the Inverter Efficiency. 22nd European Photovoltaic Solar Energy Conference, 2007.
- Alonso Garcia, M. C.: Caracterización y modelado de asociaciones de dispositivos fotovoltaicos. PhD Thesis, CIEMAT, 2005.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fInclin](#), [prodGCPV](#), [fTemp](#).

Examples

```
inclin = data.table(Gef = c(200,400,600,800,1000),Ta = 25)

#using default values
fProd(inclin)

#Using a matrix for Ki (voltage dependence)
```

C_fPump

47

```
inv1 <- list(Ki = rbind(c(-0.00019917, 7.513e-06, -5.4183e-09),
c(0.00806, -4.161e-06, 2.859e-08),
c(0.02118, 3.4002e-05, -4.8967e-08)))

fProd(inclin, inverter = inv1)

#Voltage limits of the inverter
inclin = data.table(Gef = 800,Ta = 30)
gen1 = list(Nms = 10, Nmp = 11)

prod = fProd(inclin,generator = gen1)
print(prod)

with(prod, Vdc * Idc / (Vmpp * Impp))
```

C_fPump	<i>Performance of a centrifugal pump</i>
---------	--

Description

Compute the performance of the different parts of a centrifugal pump fed by a frequency converter following the affinity laws.

Usage

```
fPump(pump, H)
```

Arguments

pump	list containing the parameters of the pump to be simulated. It may be a row of pumpCoef .
H	Total manometric head (m).

Value

lim	Range of values of electrical power input
fQ	Function constructed with <code>splinefun</code> relating flow and electrical power
fPb	Function constructed with <code>splinefun</code> relating pump shaft power and electrical power of the motor
fPh	Function constructed with <code>splinefun</code> relating hydraulical power and electrical power of the motor
fFreq	Function constructed with <code>splinefun</code> relating frequency and electrical power of the motor

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Abella, M. A., Lorenzo, E. y Chenlo, F.: PV water pumping systems based on standard frequency converters. *Progress in Photovoltaics: Research and Applications*, 11(3):179–191, 2003, ISSN 1099-159X.
- Perpiñán, O, *Energía Solar Fotovoltaica*, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", *Journal of Statistical Software*, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[NmgPVPS](#), [prodPVPS](#), [pumpCoef](#), [splinefun](#).

Examples

```
library(latticeExtra)

data(pumpCoef)
CoefSP8A44 <- subset(pumpCoef, Qn == 8 & stages == 44)

fSP8A44 <- fPump(pump = CoefSP8A44, H = 40)
SP8A44 = with(fSP8A44, {
  Pac = seq(lim[1], lim[2], by = 100)
  Pb = fPb(Pac)
  etam = Pb/Pac
  Ph = fPh(Pac)
  etab = Ph/Pb
  f = fFreq(Pac)
  Q = fQ(Pac)
  result = data.frame(Q, Pac, Pb, Ph, etam, etab, f)})

#Efficiency of the motor, pump and the motor-pump
SP8A44$etamb = with(SP8A44, etab*etam)
lab = c(expression(eta[motor]), expression(eta[pump]), expression(eta[mp]))
p <- xyplot(etam + etab + etamb ~ Pac, data = SP8A44, type = 'l', ylab = 'Efficiency')
p+glayer(panel.text(x[1], y[1], lab[group.number], pos = 3))

#Mechanical, hydraulic and electrical power
lab = c(expression(P[pump]), expression(P[hyd]))
p <- xyplot(Pb + Ph ~ Pac, data = SP8A44, type = 'l', ylab = 'Power (W)', xlab = 'AC Power (W)')
p+glayer(panel.text(x[length(x)], y[length(x)], lab[group.number], pos = 3))

#Flow and electrical power
xyplot(Q ~ Pac, data = SP8A44, type = 'l')
```

Description

Compute the daily apparent movement of the Sun from the Earth. This movement is mainly described (for the simulation of photovoltaic systems) by the declination angle, the sunrise angle and the daily extra-atmospheric irradiation.

C_fSolD

49

Usage

```
fSolD(lat, BTd, method = 'michalsky')
```

Arguments

lat	Latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
BTd	Daily temporal base, a POSIXct object which may be the result of fBTd .
method	character, method for the sun geometry calculations to be chosen from 'cooper', 'spencer', 'michalsky' and 'strous'. See references for details.

Value

A data.table object with these components:

lat	Latitude (degrees)
decl	Declination angle (radians) for each day of year in dn or BTd
eo	Factor of correction due the eccentricity of orbit of the Earth around the Sun.
ws	Sunrise angle (in radians) for each day of year. Due to the convention which considers that the solar hour angle is negative before midday, this angle is negative.
Bo0d	Extra-atmospheric daily irradiation (watt-hour per squared meter) incident on a horizontal surface
EoT	Equation of Time.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Cooper, P.I., Solar Energy, 12, 3 (1969). "The Absorption of Solar Radiation in Solar Stills"
- Spencer, Search 2 (5), 172, <https://www.mail-archive.com/sundial@uni-koeln.de/msg01050.html>
- Strous: <https://www.aa.quae.nl/en/reken/zonpositie.html>
- Michalsky, J., 1988: The Astronomical Almanac's algorithm for approximate solar position (1950-2050), Solar Energy 40, 227-235
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

Examples

```
BTd <- fBTd(mode = 'serie')

lat <- 37.2
fSolD(lat, BTd[100])
fSolD(lat, BTd[100], method = 'strous')
fSolD(lat, BTd[100], method = 'spencer')
fSolD(lat, BTd[100], method = 'cooper')
```

```

lat <- -37.2
fSold(lat, BTd[283])

#Solar angles along the year
Sold <- fSold(lat, BTd = fBTd())

library(lattice)
xyplot(Sold)

#Calculation of the daylength for several latitudes
library(latticeExtra)

Lats <- c(-60, -40, -20, 0, 20, 40, 60)
NomLats <- ifelse(Lats > 0, paste(Lats,'N', sep = ''),
                  paste(abs(Lats), 'S', sep = ''))
NomLats[Lats == 0] <- '0'

BTd <- fBTd(mode = 'serie')
mat <- matrix(nrow = length(BTd), ncol = length(Lats))
colnames(mat) <- NomLats
WsZ <- data.table(Dates = BTd, mat)

for (i in seq_along(Lats)){
  SolDaux <- fSold(lat = Lats[i], BTd = fBTd(mode = 'serie'));
  WsZ[,i+1] <- r2h(2*abs(SolDaux$ws))}

p = xyplot(`60S` + `40S` + `20S` + `0` + `20N` + `40N` + `60N` ~ Dates, data = WsZ, type = "l",
           ylab = expression(omega[s] * (h)))
plab = p+glayer(panel.text(x[1], y[1], NomLats[group.number], pos = 2))
print(plab)

```

C_fSolI

*Instantaneous apparent movement of the Sun from the Earth***Description**

Compute the angles which describe the intradaily apparent movement of the Sun from the Earth.

Usage

```
fSolI(sold, sample = 'hour', BTi, EoT = TRUE, keep.night = TRUE, method = 'michalsky')
```

Arguments

sold	A data.table object with the result of fSold
sample	Increment of the intradaily sequence. It is a character string, containing one of "sec", "min", "hour". This can optionally be preceded by a (positive or negative) integer and a space, or followed by "s". It is used by seq.POSIXt . It is not considered when BTi is provided.
BTi	Intradaily time base, a POSIXct object. It could be the index of the G0I argument to calcG0 . fSolI will produce results only for those days contained both in sold and in BTi.

C_fSolI

51

EoT	logical, if TRUE (default) the Equation of Time is used.
keep.night	logical, if TRUE (default) the night is included in the time series.
method	character, method for the sun geometry calculations to be chosen from 'cooper', 'spencer', 'michalsky' and 'strous'. See references for details.

Value

A data.table object is returned with these components:

lat	numeric, latitude (degrees)
w	numeric, solar hour angle (radians)
aman	logical, TRUE when Sun is above the horizon
cosThzS	numeric, cosine of the solar zenith angle
AzS	numeric, solar acimuth angle (radians)
AlS	numeric, solar elevation angle (radians)
Bo0	numeric, extra-atmospheric irradiance (W/m2)

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Cooper, P.I., Solar Energy, 12, 3 (1969). "The Absorption of Solar Radiation in Solar Stills"
- Spencer, Search 2 (5), 172, <https://www.mail-archive.com/sundial@uni-koeln.de/msg01050.html>
- Strous: <https://www.aa.quae.nl/en/reken/zonpositie.html>
- Michalsky, J., 1988: The Astronomical Almanac's algorithm for approximate solar position (1950-2050), Solar Energy 40, 227-235
- Collares-Pereira, M. y Rabl, A., The average distribution of solar radiation: correlations between diffuse and hemispherical and between daily and hourly insolation values. Solar Energy, 22:155–164, 1979.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fSold](#)

Examples

```
###Angles for one day
BTd = fBTd(mode = 'serie')

#North hemisphere
lat = 37.2
sold <- fSold(lat,BTd[100])
solI <- fSolI(sold, sample = 'hour')
print(solI)
```



```

#South hemisphere
lat = -37.2;
solDs <- fSolD(lat,BTd[283])
solIs <- fSolI(solDs, sample = 'hour')
print(solIs)

###Angles for the 12 average days
lat = 37.2;
solD <- fSolD(lat,BTd = fBTd(mode = 'prom'))
solI <- fSolI(solD, sample = '10 min', keep.night = FALSE)

library(lattice)
library(latticeExtra)

###Solar elevation angle vs. azimuth.
#This kind of graphics is useful for shadows calculations
mon = month.abb
p <- xyplot(r2d(AlS)~r2d(AzS),
  groups = month(Dates),
  data = solI, type = 'l', col = 'black',
  xlab = expression(psi[s]),ylab = expression(gamma[s]))

plab <- p + glayer({
  idx <- round(length(x)/2+1)
  panel.text(x[idx], y[idx], mon[group.value], pos = 3, offset = 0.2, cex = 0.8)})

print(plab)

```

C_fSombra

*Shadows on PV systems***Description**

Compute the shadows factor for two-axis and horizontal N-S axis trackers and fixed surfaces.

Usage

```
fSombra(angGen, distances, struct, modeTrk = 'fixed',prom = TRUE)
```

```
fSombra6(angGen,distances,struct,prom = TRUE)
```

```
fSombra2X(angGen,distances,struct)
```

```
fSombraHoriz(angGen, distances,struct)
```

```
fSombraEst(angGen, distances,struct)
```

Arguments

angGen A data.table object, including at least variables named Beta, Alpha, AzS, AlS and cosTheta.

distances	data.frame, with a component named Lew , being the distance (meters) between horizontal NS and two-axis trackers along the East-West direction, a component named Lns for two-axis trackers or a component named D for static surfaces. An additional component named H can be included with the relative height (meters) between surfaces. When modeTrk = 'two' (or when fSombra6 is used) this data.frame may have five rows. Each of these rows defines the distances of a tracker in a set of six ones.
struct	list. When modeTrk = 'fixed' or modeTrk = 'horiz' only a component named L , which is the height (meters) of the tracker, is needed. For two-axis trackers (modeTrk = 'two'), an additional component named W , the width of the tracker, is required. Moreover, two components named Nrow and Ncol are included under this list. These components define, respectively, the number of rows and columns of the whole set of trackers in the PV plant.
modeTrk	character, to be chosen from 'fixed' , 'two' or 'horiz' . When modeTrk = 'fixed' the surface is fixed (inclination and azimuth angles are constant). The performance of a two-axis tracker is calculated with modeTrk = 'two' , and modeTrk = 'horiz' is the option for an horizontal N-S tracker. Its default value is modeTrk = 'fixed'
prom	logical, only needed for two-axis tracker mode. If TRUE the shadows are averaged between the set of trackers defined by struct\$Nrow and struct\$Ncol

Details

fSombra is only a wrapper for **fSombra6** (two-axis trackers), **fSombraEst** (fixed systems) and **fSombraHoriz** (horizontal N-S axis trackers). Depending on the value of **modeTrk** the corresponding function is selected. **fSombra6** calculates the shadows factor in a set of six two-axis trackers. If **distances** has only one row, this function constructs a symmetric grid around a tracker located at (0,0,0). These five trackers are located at (-Lew, Lns, H), (0, Lns, H), (Lew, Lns, H), (-Lew, 0, H) and (Lns, 0, H). It is possible to define a irregular grid around (0,0,0) including five rows in **distances**. When **prom = TRUE** the shadows factor for each of the six trackers is calculated. Then, according to the distribution of trackers in the plant defined by **struct\$Nrow** and **struct\$Ncol**, a weighted average of the shadows factors is the result. It is important to note that the distances are defined between axis for trackers and between similar points of the structure for fixed surfaces.

Value

data.table including **angGen** and a variable named **FS**, which is the shadows factor. This factor is the ratio between the area of the generator affected by shadows and the total area. Therefore its value is 1 when the PV generator is completely shadowed.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O.: Grandes Centrales Fotovoltaicas: producción, seguimiento y ciclo de vida. PhD Thesis, UNED, 2008. https://www.researchgate.net/publication/39419806_Grandes_Centrales_Fotovoltaicas_Produccion_Seguimiento_y_Ciclo_de_Vida.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[calcShd](#), [optimShd](#), [fTheta](#), [calcSol](#)

Examples

```
lat = 37.2;
sol <- calcSol(lat, fBTd(mode = 'prom'), sample = '10 min', keep.night = FALSE)
angGen <- fTheta(sol, beta = 35);
Angles <- merge(as.data.tableI(sol), angGen)

###Two-axis tracker
#Symmetric grid
distances = data.table(Lew = 40,Lns = 30,H = 0)
struct = list(W = 23.11, L = 9.8, Nrow = 2, Ncol = 8)

ShdFactor <- fSombra6(Angles, distances, struct, prom = FALSE)

Angles$FS = ShdFactor
xyplot(FS ~ w, groups = month(Dates), data = Angles,
       type = 'l',
       auto.key = list(space = 'right',
                       lines = TRUE,
                       points = FALSE))

#Symmetric grid defined with a five rows data.frame
distances = data.table(Lew = c(-40,0,40,-40,40),
                      Lns = c(30,30,30,0,0),
                      H = 0)
ShdFactor2 <- fSombra6(Angles, distances, struct,prom = FALSE)

#of course, with the same result
identical(ShdFactor, ShdFactor2)
```

C_fTemp

Intradaily evolution of ambient temperature

Description

From the maximum and minimum daily values of ambient temperature, its evolution its calculated through a combination of cosine functions (ESRA method)

Usage

```
fTemp(sol, BD)
```

Arguments

sol	A Sol object. It may be the result of the calcSol function.
BD	A Meteo object, as provided by the readBDd function. It must include information about TempMax and TempMin.

`C_fTheta`

55

Details

The ESRA method estimates the dependence of the temperature on the time of the day (given as the local solar time) from only two inputs: minimum and maximum daily temperatures. It assumes that the temperature daily profile can be described using three piecewise cosine functions, dividing the day into three periods: from midnight to sunrise, from sunrise to the time of peak temperature (3 hours after midday), and to midnight.

Value

A `data.table` object with the profile of the ambient temperature.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Huld, T. , Suri, M., Dunlop, E. D., and Micale F., Estimating average daytime and daily temperature profiles within Europe, *Environmental Modelling & Software* 21 (2006) 1650-1661.
- Perpiñán, O, *Energía Solar Fotovoltaica*, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", *Journal of Statistical Software*, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[calcSol](#), [readBDd](#).

`C_fTheta`*Angle of incidence of solar irradiation on a inclined surface*

Description

The orientation, azimuth and incidence angle are calculated from the results of `fSolI` or `calcSol` and from the information supplied by the arguments `beta` and `alpha` when the surface is fixed (`modeTrk = 'fixed'`) or the movement equations when a tracking surface is chosen (`modeTrk = 'horiz'` or `modeTrk = 'two'`). Besides, the modified movement of a horizontal NS tracker due to the back-tracking strategy is calculated if `BT = TRUE` with information about the tracker and the distance between the trackers included in the system.

This function is used by the [calcGef](#) function.

Usage

```
fTheta(sol, beta, alpha = 0, modeTrk = "fixed", betaLim = 90,
      BT = FALSE, struct, dist)
```

Arguments

sol	Sol object as provided by calcSol .
beta	numeric, inclination angle of the surface (degrees). It is only needed when modeTrk = 'fixed'.
alpha	numeric, azimuth angle of the surface (degrees). It is measured from the south (alpha = 0), and it is negative to the east and positive to the west. It is only needed when modeTrk = 'fixed'. Its default value is alpha = 0 (surface facing to the south).
modeTrk	character, to be chosen from 'fixed', 'two' or 'horiz'. When modeTrk = 'fixed' the surface is fixed (inclination and azimuth angles are constant). The performance of a two-axis tracker is calculated with modeTrk = 'two', and modeTrk = 'horiz' is the option for an horizontal N-S tracker. Its default value is modeTrk = 'fixed'
betaLim	numeric, maximum value of the inclination angle for a tracking surface. Its default value is 90 (no limitation))
BT	logical, TRUE when the backtracking technique is to be used with a horizontal NS tracker, as described by Panico et al. (see References). The default value is FALSE. In future versions of this package this technique will be available for two-axis trackers.
struct	Only needed when BT = TRUE. A list, with a component named L, which is the height (meters) of the tracker. In future versions the backtracking technique will be used in conjunction with two-axis trackers, and a additional component named W will be needed.
dist	Only needed when BT = TRUE. A data.frame, with a component named Lew, being the distance between the horizontal NS trackers along the East-West direction. In future versions an additional component named Lns will be needed for two-axis trackers with backtracking.

Value

A data.table object with these components:

Beta	numeric, inclination angle of the surface (radians). When modeTrk = 'fixed' it is the value of the argument beta converted from degrees to radians.
Alpha	numeric, azimuth angle of the surface (radians). When modeTrk = 'fixed' it is the value of the argument alpha converted from degrees to radians.
cosTheta	numeric, cosine of the incidence angle of the solar irradiance on the surface

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Panico, D., Garvison, P., Wenger, H. J., Shugar, D., Backtracking: a novel strategy for tracking PV systems, Photovoltaic Specialists Conference, 668-673, 1991
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

C_HQCurve

57

See Also[fInclin](#), [fSombra](#), [calcGef](#).

*C_HQCurve**H-Q curves of a centrifugal pump*

Description

Compute and display the H-Q curves of a centrifugal pump fed working at several frequencies, and the iso-efficiency curve as a reference.

Usage`HQCurve(pump)`**Arguments**

<code>pump</code>	list containing the parameters of the pump to be simulated. It may be a row of pumpCoef .
-------------------	---

Value

<code>result</code>	A <code>data.frame</code> with the result of the simulation. It contains several columns with values of manometric height (H), frequency (fe and fb), mechanical power (Pb), AC electrical power (Pm), DC electrical power (Pdc) and efficiency of the pump (etab) and motor (etam).
<code>plot</code>	The plot with several curves labelled with the correspondent frequencies, and the isoefficiency curve (named "ISO").

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Abella, M. A., Lorenzo, E. y Chenlo, F.: PV water pumping systems based on standard frequency converters. *Progress in Photovoltaics: Research and Applications*, 11(3):179–191, 2003, ISSN 1099-159X.
- Perpiñán, O, *Energía Solar Fotovoltaica*, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", *Journal of Statistical Software*, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also[NmgPVPS](#), [prodPVPS](#), [pumpCoef](#).

Examples

```
library(lattice)
library(latticeExtra)

data(pumpCoef)

CoefSP8A44 <- subset(pumpCoef, Qn == 8&stages == 44)
CurvaSP8A44 <- HQCurve(pump = CoefSP8A44)
```

C_local2Solar

*Local time, mean solar time and UTC time zone.***Description**

The function `local2Solar` converts the time zone of a `POSIXct` object to the mean solar time and set its time zone to UTC as a synonym of mean solar time. It includes two corrections: the difference of longitudes between the location and the time zone, and the daylight saving time.

The function `lonHH` calculates the longitude (radians) of a time zone.

Usage

```
local2Solar(x, lon = NULL)
lonHH(tz)
```

Arguments

<code>x</code>	a <code>POSIXct</code> object
<code>lon</code>	A numeric value of the longitude (degrees) of the location. If <code>lon = NULL</code> (default), this value is assumed to be equal to the longitude of the time zone of <code>x</code> , so only the daylight saving time correction (if needed) is included.
<code>tz</code>	A character, a time zone as documented in https://en.wikipedia.org/wiki/List_of_tz_database_time_zones .

Details

Since the result of `local2Solar` is the mean solar time, the Equation of Time correction is not calculated with this function. The `eot` function includes this correction if desired.

Value

The function `local2Solar` produces a `POSIXct` object with its time zone set to UTC.

The function `lonHH` gives a numeric value.

Note

It is important to note that the `solar2` package sets the system time zone to UTC with `Sys.setenv(TZ = 'UTC')`.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

Examples

```
t.local <- as.POSIXct("2006-01-08 10:07:52", tz = 'Europe/Madrid')

##The local time zone and the location have the same longitude (15 degrees)
local2Solar(t.local)
##But Madrid is at lon = -3
local2Solar(t.local, lon = -3)

##Daylight saving time
t.local.dst <- as.POSIXct("2006-07-08 10:07:52", tz = 'Europe/Madrid')

local2Solar(t.local.dst)
local2Solar(t.local.dst, lon = -3)
```

C_NmgPVPS*Nomogram of a photovoltaic pumping system*

Description

This function simulate the performance of a water pump fed by a frequency converter with several PV generators of different size during a day. The result is plotted as a nomogram which relates the nominal power of the PV generator, the total water flow and the total manometric head.

Usage

```
NmgPVPS(pump, Pg, H, Gd, Ta = 30,
         lambda = 0.0045, TONC = 47, eta = 0.95,
         Gmax = 1200, t0 = 6, Nm = 6,
         title = '', theme = custom.theme.2())
```

Arguments

pump	A list extracted from pumpCoef
Pg	Sequence of values of the nominal power of the PV generator (Wp))
H	Sequence of values of the total manometric head (m)
Gd	Global irradiation incident on the generator (Wh/m ²)
Ta	Ambient temperature (°C).
lambda	Power losses factor due to temperature
TONC	Nominal operational cell temperature (°C).
eta	Average efficiency of the frequency converter
Gmax	Maximum value of irradiance (parameter of the IEC 61725)
t0	Hours from midday to sunset (parameter of the IEC 61725)

Nm	Number of samples per hour
title	Main title of the plot.
theme	Theme of the lattice plot.

Details

This function computes the irradiance profile according to the IEC 61725 "Analytical Expression for Daily Solar Profiles", which is a common reference in the official documents regarding PV pumping systems. At this version only pumps from the manufacturer Grundfos are included in [pumpCoef](#).

Value

I	list with the results of irradiance, power and flow of the system.
D	list with the results of total irradiation, electrical energy and flow for every nominal power of the generator.
param	list with the arguments used in the call to the function.
plot	trellis object containing the nomogram.

Author(s)

Oscar Perpiñán Lamigueiro.

References

- Abella, M. A., Lorenzo, E. y Chenlo, F.: PV water pumping systems based on standard frequency converters. Progress in Photovoltaics: Research and Applications, 11(3):179–191, 2003, ISSN 1099-159X.
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fPump](#), [prodPVPS](#), [pumpCoef](#)

Examples

```
Pg = seq(4000, 8000, by = 100);
H = seq(120, 150, by = 5);

data(pumpCoef)

CoefSP8A44 <- subset(pumpCoef, Qn == 8 & stages == 44)

NmgSP8A44 <- NmgPVPS(pump = CoefSP8A44, Pg = Pg, H = H, Gd = 5000,
  title = 'Choice of Pump', theme = custom.theme())
```

C_sample2Diff

61

*C_sample2Diff**Small utilities for difftime objects.*

Description

`diff2Hours` converts a `difftime` object into its numeric value with `units = 'hours'`.

`char2diff` converts a character description into a `difftime` object, following the code of [seq.POSIXt](#).

`sample2Hours` calculates the sampling time in hours described by a character or a `difftime`.

`P2E` (power to energy) sums a series of power values (for example, irradiance) to obtain energy aggregation (for example, irradiation) using `sample2Hours` for the units conversion.

Usage

```
diff2Hours(by)
char2diff(by)
sample2Hours(by)
P2E(x, by)
```

Arguments

<code>by</code>	A character for <code>char2diff</code> , <code>sample2Hours</code> and <code>P2E</code> , or a <code>difftime</code> for <code>diff2Hours</code> , <code>sample2Hours</code> and <code>P2E</code> .
<code>x</code>	A numeric vector.

Value

A numeric value or a `difftime` object.

Author(s)

Oscar Perpiñán Lamigueiro

See Also

[Sol](#)

Examples

```
char2diff('min')
char2diff('2 s')

sample2Hours('s')
sample2Hours('30 m')

by1 <- char2diff('10 min')
sample2Hours(by1)
```

C_solarAngles	<i>Solar angles</i>
---------------	---------------------

Description

A set of functions that compute the apparent movement of the Sun from the Earth.

Usage

```
## Declination
declination(d, method = 'michalsky')

## Eccentricity
eccentricity(d, method = 'michalsky')

## Equation of time
eot(d)

## Solar time
sunrise(d, lat, method = 'michalsky',
        decl = declination(d, method = method))

## Extraterrestrial irradiation
bo0d(d, lat, method = 'michalsky',
    decl = declination(d, method = method),
    eo = eccentricity(d, method = method),
    ws = sunrise(d, lat, method = method))

## Sun hour angle
sunHour(d, BTi, sample = 'hour', EoT = TRUE,
        method = 'michalsky',
        eqtime = eot(d))

## Cosine of the zenith angle
zenith(d, lat, BTi, sample = 'hour', method = 'michalsky',
    decl = declination(d, method = method),
    w = sunHour(d, BTi, sample, method = method))

## Azimuth angle
azimuth(d, lat, BTi, sample = 'hour', method = 'michalsky',
    decl = declination(d, method = method),
    w = sunHour(d, BTi, sample, method = method),
    cosThzS = zenith(d, lat, BTi, sample,
        method = method,
        decl = decl,
        w = w))
```

Arguments

d Date, a daily time base, it may be the result of [fBTd](#)

C_solarAngles

63

method	character, method for the sun geometry calculations, to be chosen from 'cooper', 'spencer', 'michalsky' and 'strous'. See references for details.
lat	numeric, latitude (degrees) of the point of the Earth where calculations are needed. It is positive for locations above the Equator.
sample	Character, increment of the intradaily sequence.
BTi	POSIXct, intradaily time base, it may the result of fBTi .
EoT	logical, if EoT=TRUE (default value), the function sunHour use the Equation of time
decl, eo, ws, eqtime, w, cosThzS	Arguments that compute the variables they reference (default value). It can be replaced with previously calculated values to avoid calculating the same variable twice.

References

- Cooper, P.I., Solar Energy, 12, 3 (1969). "The Absorption of Solar Radiation in Solar Stills"
- Spencer, Search 2 (5), 172, <https://www.mail-archive.com/sundial@uni-koeln.de/msg01050.html>
- Strous: <https://www.aa.quae.nl/en/reken/zonpositie.html>
- Michalsky, J., 1988: The Astronomical Almanac's algorithm for approximate solar position (1950-2050), Solar Energy 40, 227-235
- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, [doi:10.18637/jss.v050.i09](https://doi.org/10.18637/jss.v050.i09)

See Also[fSold](#), [fSolI](#), [calcSol](#)**Examples**

```
d = fBTd(mode = 'serie')[100]

decl = declination(d, method = 'michalsky')
decl

w = sunHour(d, sample = 'hour', method = 'michalsky')
w

cosThzS = zenith(d, lat = 37.2, sample = 'hour',
                 method = 'michalsky',
                 decl = decl,
                 w = w)
cosThzS
```

C_utils-angle	<i>Conversion between angle units.</i>
---------------	--

Description

Several small functions to convert angle units.

Usage

```
d2r(x)
r2d(x)
h2r(x)
h2d(x)
r2h(x)
d2h(x)
r2sec(x)
```

Arguments

x	A numeric value.
---	------------------

Value

A numeric value:

d2r: Degrees to radians.

r2d: Radians to degrees.

h2r: Hours to radians.

r2h: Radians to hours.

h2d: Hours to degrees.

d2h: Degrees to hours.

r2sec: Radians to seconds.

Author(s)

Oscar Perpiñán Lamigueiro.

C_utils-time	<i>Utilities for time indexes.</i>
--------------	------------------------------------

Description

Several small functions to extract information from POSIXct indexes.

Usage

```
hms(x)
doy(x)
dom(x)
dst(x)
truncDay(x)
```

Arguments

x A POSIXct vector.

Value

doy and dom provide the (numeric) day of year and day of month, respectively.

hms gives the numeric value

hour(x)+minute(x)/60+second(x)/3600

dst is +1 if the Daylight Savings Time flag is in force, zero if not, -1 if unknown ([DateTimeClasses](#)).

truncDay truncates the POSIXct object towards the day.

Author(s)

Oscar Perpiñán Lamigueiro.

See Also

as.POSIXct

*D_as.data.tableD-methods**Methods for Function as.data.tableD*

Description

Convert a Sol, G0, Gef, ProdGCPV or ProdPVPS object into a data.table object with daily values.

Usage

```
## S4 method for signature 'Sol'
as.data.tableD(object, complete=FALSE, day=FALSE)
```

Arguments

object	A Sol object (or extended.)
complete	A logical.
day	A logical.

Methods

`signature(object = "Sol")` Conversion to a `data.table` object with the content of the `sold` slot. If `day=TRUE` (default is `FALSE`), the result includes three columns named `month`, `day` (day of the year) and `year`.

`signature(object = "G0")` If `complete=FALSE` (default) the result includes only the columns of `G0d`, `D0d` and `B0d` from the `G0D` slot. If `complete=TRUE` it returns the contents of the slots `sold` and `G0D`.

`signature(object = "Gef")` If `complete=FALSE` (default) the result includes only the columns of `Gefd`, `Defd` and `Befd` from the `GefD` slot. If `complete=TRUE` it returns the contents of the slots `sold`, `G0D` and `GefD`.

`signature(object = "ProdGCPV")` If `complete=FALSE` (default) the result includes only the columns of `Eac`, `Edc` and `Yf` from the `prodD` slot. If `complete=TRUE` it returns the contents of the slots `sold`, `G0D`, `GefD` and `prodD`.

`signature(object = "ProdPVPS")` If `complete=FALSE` (default) the result includes only the columns of `Eac`, `Qd` and `Yf` from the `prodD` slot. If `complete=TRUE` it returns the contents of the slots `sold`, `G0D`, `GefD` and `prodD`.

Author(s)

Oscar Perpiñán Lamigueiro

Examples

```
lat = 37.2
BTd = fBTd(mode = 'prom')
sol = calcSol(lat, BTd)
sold = as.data.tableD(sol)
sold

sold2 = as.data.tableD(sol, day = TRUE)
sold2

G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562,
          2814, 2179)
Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2,
        17.2, 15.2)
prom <- list(G0dm = G0dm, Ta = Ta)
prodfixed = prodGCPV(lat, dataRad = prom)
prodD = as.data.tableD(prodfixed, complete = TRUE, day = TRUE)
prodD
```

D_as.data.tableI-methods

Methods for Function as.data.tableI

Description

Convert a `Sol`, `G0`, `Gef`, `ProdGCPV` or `ProdPVPS` object into a `data.table` object with daily values.

Usage

```
## S4 method for signature 'Sol'  
as.data.tableI(object, complete=FALSE, day=FALSE)
```

Arguments

object	A Sol object (or extended.)
complete	A logical.
day	A logical.

Methods

signature(object = "Sol") If complete=FALSE and day=FALSE (default) the result includes only the content of the solI slot. If complete=TRUE the contents of the sold slots are included.

signature(object = "G0") If complete=FALSE and day=FALSE (default) the result includes only the columns of G0, D0 and B0 of the G0I slot. If complete=TRUE it returns the contents of the slots G0I and solI. If day=TRUE the daily values (slots G0D and sold) are also included.)

signature(object = "Gef") If complete=FALSE and day=FALSE (default) the result includes only the columns of Gef, Def and Bef of the GefI slot. If complete=TRUE it returns the contents of the slots GefI, G0I and solI. If day=TRUE the daily values (slots GefD, G0D and sold) are also included.)

signature(object = "ProdGCPV") If complete=FALSE and day=FALSE (default) the result includes only the columns of Pac and Pdc of the prodI slot. If complete=TRUE it returns the contents of the slots prodI, GefI, G0I and solI. If day=TRUE the daily values (slots prodD, GefD, G0D and sold) are also included.)

signature(object = "ProdPVPS") If complete=FALSE and day=FALSE (default) the result includes only the columns of Pac and Q of the prodI slot. If complete=TRUE it returns the contents of the slots prodI, GefI, G0I and solI. If day=TRUE the daily values (slots prodD, GefD, G0D and sold) are also included.)

Author(s)

Oscar Perpiñán Lamigueiro

Examples

```
lat = 37.2  
BTd = fBTd(mode = 'prom')[1]  
sol = calcSol(lat, BTd, keep.night = FALSE)  
solI = as.data.tableI(sol)  
solI  
  
solI2 = as.data.tableI(sol, day = TRUE)  
solI2  
  
G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562,  
         2814, 2179)  
Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2,  
       17.2, 15.2)  
prom <- list(G0dm = G0dm, Ta = Ta)  
prodfixed = prodGCPV(lat, dataRad = prom)  
prodI = as.data.tableI(prodfixed, complete = TRUE, day = TRUE)  
prodI
```

D_as.data.tableM-methods

Methods for Function as.data.tableM

Description

Convert a G0, Gef, ProdGCPV or ProdPVPS object into a as.data.table object with monthly average of daily values.

Usage

```
## S4 method for signature 'G0'
as.data.tableM(object, complete=FALSE, day=FALSE)
```

Arguments

object	A G0 object (or extended.)
complete	A logical.
day	A logical

Methods

signature(object = "G0") The result is the G0dm slot. If day=TRUE (default is FALSE), the result includes two columns names month and year.

signature(object = "Gef") If complete=FALSE (default) the result is the slot Gefdm. If complete=TRUE it returns the slot G0dm.

signature(object = "ProdGCPV") If complete=FALSE (default) the result is the prodDm slot. If complete=TRUE the result includes the slots G0dm and Gefdm.

signature(object = "ProdPVPS") If complete=FALSE (default) the result is the prodDm slot. If complete=TRUE the result includes the slots G0dm and Gefdm.

Author(s)

Oscar Perpiñán Lamigueiro

Examples

```
lat = 37.2
G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562,
         2814, 2179)
Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2,
       17.2, 15.2)
prom <- list(G0dm = G0dm, Ta = Ta)
prodfixed = prodGCPV(lat, dataRad = prom)
prodM = as.data.tableM(prodfixed, complete = TRUE, day = TRUE)
prodM
```

*D_as.data.tableY-methods**Methods for Function as.data.tableY*

Description

Convert a `G0`, `Gef`, `ProdGCPV` or `ProdPVPS` object into a `data.table` object with yearly values.

Usage

```
## S4 method for signature 'G0'  
as.data.tableY(object, complete=FALSE, day=FALSE)
```

Arguments

<code>object</code>	A <code>G0</code> object (or extended.)
<code>complete</code>	A logical.
<code>day</code>	A logical.

Methods

`signature(object = "G0")` The result is the `G0y` slot. If `day = TRUE` (default is `FALSE`), the result includes a column named `year`.

`signature(object = "Gef")` If `complete=FALSE` (default) the result is the slot `Gefy`. If `complete=TRUE` it returns the slot `G0y`.

`signature(object = "ProdGCPV")` If `complete=FALSE` (default) the result is the `prody` slot. If `complete=TRUE` the result includes the slots `G0y` and `Gefy`.

`signature(object = "ProdPVPS")` If `complete=FALSE` (default) the result is the `prody` slot. If `complete=TRUE` the result includes the slots `G0y` and `Gefy`.

Author(s)

Oscar Perpiñán Lamigueiro

Examples

```
lat = 37.2  
G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562,  
         2814, 2179)  
Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2,  
       17.2, 15.2)  
prom <- list(G0dm = G0dm, Ta = Ta)  
prodfixed = prodGCPV(lat, dataRad = prom)  
prodY = as.data.tableY(prodfixed, complete = TRUE, day = TRUE)  
prodY
```

D_compare-methods *Compare G0, Gef and ProdGCPV objects*

Description

Compare and plot the yearly values of several objects.

Usage

```
## S4 method for signature 'G0'
compare(...)
```

Arguments

... A list of objects to be compared.

Methods

The class of the first element of ... is used to determine the suitable method. The result is plotted with [dotplot](#):

```
signature(... = "G0") yearly values of G0d, B0d and D0d.
signature(... = "Gef") yearly values of Gefd, Befd and Defd.
signature(... = "ProdGCPV") yearly values of Yf, Gefd and G0d.
```

Author(s)

Oscar Perpiñán Lamigueiro

See Also

[dotplot](#)

Examples

```
lat = 37.2;
G0dm = c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562, 2814,
2179)
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom = list(G0dm = G0dm, Ta = Ta)

###Comparison of different tracker methods
ProdFixed <- prodGCPV(lat = lat, dataRad = prom, keep.night = FALSE)
Prod2x <- prodGCPV(lat = lat, dataRad = prom, modeTrk = 'two', keep.night = FALSE)
ProdHoriz <- prodGCPV(lat = lat, dataRad = prom, modeTrk = 'horiz', keep.night = FALSE)

compare(ProdFixed, Prod2x, ProdHoriz)

##The first element rules the method
GefFixed = as(ProdFixed, 'Gef')
compare(GefFixed, Prod2x, ProdHoriz)
```

D_getData-methods	<i>Methods for function getData</i>
-------------------	-------------------------------------

Description

Meteorological source data of a Meteo (or extended) object.

Methods

signature(object = "Meteo") returns the meteorological source data of the slot data of the object.

Author(s)

Oscar Perpiñán Lamigueiro

D_getG0-methods	<i>Methods for function getG0</i>
-----------------	-----------------------------------

Description

Global irradiation source data of a Meteo (or extended) object.

Methods

signature(object = "Meteo") returns the global irradiation values stored in a Meteo object.

Author(s)

Oscar Perpiñán Lamigueiro

D_getLat-methods	<i>Methods for Function getLat</i>
------------------	------------------------------------

Description

Latitude angle of solaR objects.

Usage

getLat(object, units='rad')

Arguments

- | | |
|--------|--------------------------------------|
| object | A Sol or Meteo object (or extended.) |
| units | A character, 'rad' or 'deg'. |

Methods

This function returns the latitude angle in radians (`units='rad'`, default) or degrees (`units='deg'`).

`signature(object = "Meteo")` Value of the `latData` slot, which is defined by the argument `lat` of the `readG0dm` and `readBDd` functions, or by the `lat` component of the `dataRad` object passed to `calcG0` (or equivalent). It is the latitude of the meteorological station (or equivalent) which provided the irradiation source data. It may be different from the value used for the calculation procedure.

`signature(object = "Sol")` Value of the `lat` slot, which is defined by the argument `lat` of the `calcSol` function. It is the value used through the calculation procedure.

`signature(object = "G0")` same as for the `Sol` class.

Author(s)

Oscar Perpiñán Lamigueiro

D_indexD-methods

Methods for Function indexD

Description

Daily time index of `solaR` objects.

Methods

`signature(object = "Meteo")` returns the index of the data slot (a `data.table` object.)

`signature(object = "Sol")` returns the index of the `solD` slot (a `data.table` object.)

`signature(object = "G0")` same as for `object='Sol'`

Author(s)

Oscar Perpiñán Lamigueiro

D_indexI-methods

Methods for Function indexI

Description

Intra-daily time index of `solaR` objects.

Methods

`signature(object = "Sol")` returns the index of the slot `solI` (a `data.table` object).

Author(s)

Oscar Perpiñán Lamigueiro

D_levelplot-methods	<i>Methods for function levelplot.</i>
---------------------	--

Description

Methods for function levelplot and zoo and solaR objects.

Methods

signature(x = "formula", data = "Meteo"): The Meteo object is converted into a data.table object, and the previous method is used.
signature(x = "formula", data = "Sol"): idem
signature(x = "formula", data = "G0"): idem

Author(s)

Oscar Perpiñán Lamigueiro

D_Losses-methods	<i>Losses of a GCPV system</i>
------------------	--------------------------------

Description

The function losses calculates the yearly losses from a Gef or a ProdGCPV object. The function compareLosses compares the losses from several ProdGCPV objects and plots the result with dotplot.

Usage

compareLosses(...)
losses(object)

Arguments

... A list of ProdGCPV objects to be compared.
object An object of Gef or ProdGCPV class..

Methods

signature(... = "Gef") shadows and angle of incidence (AoI) losses.
signature(... = "ProdGCPV") shadows, AoI, generator (mainly temperature), DC and AC system (as detailed in effSys of fProd) and inverter losses.

Author(s)

Oscar Perpiñán Lamigueiro

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

See Also

[fInclin](#), [fProd](#)

Examples

```
lat = 37.2;
G0dm = c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562, 2814,
2179)
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom = list(G0dm = G0dm, Ta = Ta)

###Comparison of different tracker methods
ProdFixed <- prodGCPV(lat = lat,dataRad = prom, keep.night = FALSE)
Prod2x <- prodGCPV(lat = lat, dataRad = prom, modeTrk = 'two', keep.night = FALSE)
ProdHoriz <- prodGCPV(lat = lat,dataRad = prom, modeTrk = 'horiz', keep.night = FALSE)

losses(ProdFixed)
losses(as(ProdFixed, 'Gef'))

compareLosses(ProdFixed, Prod2x, ProdHoriz)
```

D_mergesolaR-methods *Merge solaR objects*

Description

Merge the daily time series of solaR objects

Usage

```
## S4 method for signature 'G0'
mergesolaR(...)
```

Arguments

... A list of objects to be merged.

Methods

The class of the first element of ... is used to determine the suitable method. Only the most important daily variable is merged, depending on the class of the objects:

```
signature(... = "Meteo") G0
signature(... = "G0") G0d
signature(... = "Gef") Gefd
signature(... = "ProdGCPV") Yf
signature(... = "ProdPVPS") Yf
```

Examples

```
lat = 37.2;
G0dm = c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562, 2814,
2179)
Ta = c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom = list(G0dm = G0dm, Ta = Ta)

###Different tracker methods
ProdFixed <- prodGCPV(lat = lat,dataRad = prom, keep.night = FALSE)
Prod2x <- prodGCPV(lat = lat, dataRad = prom, modeTrk = 'two', keep.night = FALSE)
ProdHoriz <- prodGCPV(lat = lat,dataRad = prom, modeTrk = 'horiz', keep.night = FALSE)

prod <- mergesolaR(ProdFixed, Prod2x, ProdHoriz)
head(prod)
```

<i>D_shadeplot-methods</i>	<i>Methods for Function shadeplot</i>
----------------------------	---------------------------------------

Description

Visualization of the content of a [Shade](#) object.

Methods

`signature(x = "Shade")` display the results of the iteration with a level plot for the two-axis tracking, or with conventional plot for horizontal tracking and fixed systems.

Author(s)

Oscar Perpiñán Lamigueiro

<i>D_window-methods</i>	<i>Methods for extracting a time window</i>
-------------------------	---

Description

Method for extracting the subset of a `solaR` object whose daily time index ([indexD](#)) is comprised between the times `i` and `j`.

Usage

```
## S4 method for signature 'Meteo'
x[i, j, ..., drop = TRUE]
## S4 method for signature 'Sol'
x[i, j, ..., drop = TRUE]
## S4 method for signature 'G0'
x[i, j, ..., drop = TRUE]
## S4 method for signature 'Gef'
x[i, j, ..., drop = TRUE]
## S4 method for signature 'ProdGCPV'
x[i, j, ..., drop = TRUE]
## S4 method for signature 'ProdPVPS'
x[i, j, ..., drop = TRUE]
```


Arguments

x	A Meteo, Sol, etc. object.
i	an index/time value (Date or POSIXct classes) defining the start of the time window.
j	an index/time value (Date or POSIXct classes) defining the end of the time window.
..., drop	Additional arguments for window.zoo

Author(s)

Oscar Perpiñán Lamigueiro

See Also

[indexD](#)

Examples

```
lat = 37.2
sol = calcSol(lat, BTd = fBTd(mode = 'serie'))
range(indexD(sol))

start <- as.Date(indexD(sol)[1])
end <- start + 30

solWindow <- sol[start, end]
range(indexD(solWindow))
```

D_writeSolar-methods *Exporter of solaR results*

Description

Exports the results of the solaR functions as text files using [write.table](#)

Usage

```
## S4 method for signature 'Sol'
writeSolar(object, file, complete = FALSE,
           day = FALSE, timeScales = c('i', 'd', 'm', 'y'), sep = ',', ...)
```

Arguments

object	A Sol object (or extended.)
file	A character with the name of the file.
complete	A logical. Should all the variables be exported?
day	A logical. Should be daily values included in the intradaily file?
timeScales	A character. Use 'i' to export intradaily values, 'd' for daily values, 'm' for monthly values and 'y' for yearly values. A different file will be created for each choice.
sep	The field separator character.
...	Additional arguments for write.table

Methods

`signature(object = "Sol")` This function exports the slots with results using `write.table`. If `complete = FALSE` and `day = FALSE` (default) the result includes only the content of the `solI` slot. If `day = TRUE` the contents of the `solD` slot are included.

`signature(object = "G0")` If `complete = FALSE` and `day = FALSE` (default) the result includes only the columns of `G0`, `D0` and `B0` of the `G0I` slot. If `complete = TRUE` it returns the contents of the slots `G0I` and `solI`. If `day = TRUE` the daily values (slots `G0D` and `solD`) are also included.

`signature(object = "Gef")` If `complete = FALSE` and `day = FALSE` (default) the result includes only the columns of `Gef`, `Def` and `Bef` of the `GefI` slot. If `complete = TRUE` it returns the contents of the slots `GefI`, `G0I` and `solI`. If `day = TRUE` the daily values (slots `GefD`, `G0D` and `solD`) are also included.

`signature(object = "ProdGCPV")` If `complete = FALSE` and `day = FALSE` (default) the result includes only the columns of `Pac` and `Pdc` of the `prodI` slot. If `complete = TRUE` it returns the contents of the slots `prodI`, `GefI`, `G0I` and `solI`. If `day = TRUE` the daily values (slots `prodD`, `GefD`, `G0D` and `solD`) are also included.

`signature(object = "ProdPVPS")` If `complete = FALSE` and `day = FALSE` (default) the result includes only the columns of `Pac` and `Q` of the `prodI` slot. If `complete = TRUE` it returns the contents of the slots `prodI`, `GefI`, `G0I` and `solI`. If `day = TRUE` the daily values (slots `prodD`, `GefD`, `G0D` and `solD`) are also included.

Author(s)

Oscar Perpiñán Lamigueiro

See Also

`write.table`, `fread`, `as.data.tableI`, `as.data.tableD`, `as.data.tableM`, `as.data.tableY`

Examples

```
lat <- 37.2;
G0dm <- c(2766, 3491, 4494, 5912, 6989, 7742, 7919, 7027, 5369, 3562, 2814, 2179)
Ta <- c(10, 14.1, 15.6, 17.2, 19.3, 21.2, 28.4, 29.9, 24.3, 18.2, 17.2, 15.2)
prom <- list(G0dm = G0dm, Ta = Ta)

prodFixed <- prodGCPV(lat = lat, dataRad = prom, modeRad = 'aguair', keep.night = FALSE)

old <- setwd(tempdir())

writeSolar(prodFixed, 'prodFixed.csv')

dir()

zI <- fread("prodFixed.csv",
            header = TRUE, sep = ",")
zI

zD <- fread("prodFixed.D.csv",
            header = TRUE, sep = ",")
zD

zM <- fread("prodFixed.M.csv",
            header = TRUE, sep = ",")
```

```

zM
zY <- fread("prodFixed.Y.csv",
            header = TRUE, sep = ",")
zY
setwd(old)

```

D_xyplot-methods

Methods for function xyplot in Package 'solaR'

Description

Methods for function xyplot in Package 'solaR'

Methods

`signature(x = "data.table", data = "missing")`: This method creates an XY plot for objects of class `data.table` without specifying a data argument. It must contain a column named `Dates` with the time information.

`signature(x = "formula", data = "Meteo")`: The `Meteo` object is converted into a `data.table` object with `getData(x)` and displayed with the method for `data.table`.

`signature(x = "formula", data = "Sol")`: The `Sol` object is converted into a `data.table` object with `as.data.tableI(x, complete = TRUE, day = TRUE)` and displayed with the method for `data.table`.

`signature(x = "formula", data = "G0")`: Idem.

`signature(x = "Meteo", data = "missing")`: The `Meteo` object is converted into a `data.table` object with `getData(data)`. This `data.table` is the `x` argument for a call to `xyplot`, using the S4 method for `signature(x = "data.table", data = "missing")`.

`signature(x = "G0", data = "missing")`: The `G0` object is converted into a `data.table` object with `indexD(data)`. This `data.table` is the `x` argument for a call to `xyplot`, using the S4 method for `signature(x = 'data.table', data = 'missing')`.

`signature(x = "ProdGCPV", data = "missing")`: Idem, but the variables are not superposed.

`signature(x = "ProdPVPS", data = "missing")`: Idem.

`signature(x = "formula", data = "Shade")`: Idem.

Author(s)

Oscar Perpiñán Lamigueiro

E_aguiar

79

*E_aguiar**Markov Transition Matrices for the Aguiar etal. procedure*

Description

Markov Transition Matrices and auxiliary data for generating sequences of daily radiation values.

Usage

`data(MTM)`

Format

MTM is a `data.frame` with the collection of Markov Transition Matrices defined in the paper "Simple procedure for generating sequences of daily radiation values using a library of Markov transition matrices", Aguiar et al., Solar Energy, 1998. `Ktlim` (matrix) and `Ktmtm` (vector) are auxiliary data to choose the correspondent matrix of the collection.

*E_helios**Daily irradiation and ambient temperature from the Helios-IES database*

Description

A year of irradiation, maximum and minimum ambient temperature from the HELIOS-IES database.

Usage

`data(helios)`

Format

A data frame with 355 observations on the following 4 variables:

`yyyy.mm.dd` a factor: year, month and day.

`G.0.` a numeric vector, daily global horizontal irradiation.

`TambMax` a numeric vector, maximum ambient temperature.

`TambMin` a numeric vector, minimum ambient temperature.

Source

<http://helios.ies-def.upm.es/consulta.aspx>

E_prodEx

*Productivity of a set of PV systems of a PV plant.***Description**

A data.table object with the time evolution of the final productivity of a set of 22 systems of a large PV plant.

Usage

```
data(prodEx)
```

References

O. Perpiñán, Statistical analysis of the performance and simulation of a two-axis tracking PV system, Solar Energy, 83:11(2074–2085), 2009.https://oa.upm.es/1843/1/PERPINAN_ART2009_01.pdf

E_pumpCoef

*Coefficients of centrifugal pumps.***Description**

Coefficients of centrifugal pumps

Usage

```
data(pumpCoef)
```

Format

A data.table with 13 columns:

Qn rated flux

stages number of stages

Qmax maximum flux

Pmn rated motor power

a, b, c Coefficients of the equation $H = a \cdot f^2 + b \cdot f \cdot Q + c \cdot Q^2$.

g, h, i Coefficients of the efficiency curve of the motor (50 Hz): $\eta_m = g \cdot (\%P_{mn})^2 + h \cdot (\%P_{mn}) + i$.

j, k, l Coefficients of the efficiency curve of the pump (50 Hz): $\eta_b = j \cdot Q^2 + k \cdot Q + l$.

Details

With this version only pumps from the manufacturer Grundfos are included.

Source

<https://product-selection.grundfos.com/>

E_SIAR

81

References

- Perpiñán, O, Energía Solar Fotovoltaica, 2015. (<https://oscarperpinan.github.io/esf/>)
- Perpiñán, O. (2012), "solaR: Solar Radiation and Photovoltaic Systems with R", Journal of Statistical Software, 50(9), 1-32, doi:10.18637/jss.v050.i09

*E_SIAR**Data on the stations that make up the SIAR network*

Description

Information about the location and operational status of the stations that make up the SIAR network

Usage

```
data(SIAR)
```

Format

`est_SIAR` is a `data.table` with 625 estations containing the following information:

`Estacion` character, name of the station.

`Codigo` character, code of the station.

`Longitud` numeric, longitude of the station in degrees (negative is for locations in the west).

`Latitud` numeric, latitud of the station in degrees.

`Altitud` integer, altitude of the station in meters.

`Fecha_Instalacion` Date, day the station was installed, and therefore, the start of its records.

`Fecha_Baja` Date, day the station was decommisioned, and therefore, the end of its records (if its value is NA, it means it is still operational).

Source

<https://servicio.mapa.gob.es/websiar/>

*E_solaR.theme**solaR theme*

Description

A customized theme for lattice. It is based on the `custom.theme.2` function of the `latticeExtra` package with the next values:

- `pch = 19`
- `cex = 0.7`
- `region = rev(brewer.pal(9, 'YlOrRd'))`
- `strip.background$col = 'lightgray'`
- `strip.shingle$col = 'transparent'`

Index

* classes

B1_Meteo-class, [27](#)
B2_Sol-class, [28](#)
B3_G0-class, [29](#)
B4_Gef-class, [30](#)
B5_ProdGCPV-class, [32](#)
B6_ProdPVPS-class, [33](#)
B7_Shade-class, [34](#)

* constructors

A1_calcSol, [5](#)
A2_calcG0, [6](#)
A3_calcGef, [9](#)
A4_prodGCPV, [11](#)
A5_prodPVPS, [15](#)
A6_calcShd, [17](#)
A7_optimShd, [18](#)
A8_readBD, [23](#)
A8_readG0dm, [25](#)
A8_readSIAR, [26](#)

* datasets

E_aguiar, [79](#)
E_helios, [79](#)
E_prodEx, [80](#)
E_pumpCoef, [80](#)
E_SIAR, [81](#)
E_solar.theme, [81](#)

* methods

D_as.data.tableD-methods, [65](#)
D_as.data.tableI-methods, [66](#)
D_as.data.tableM-methods, [68](#)
D_as.data.tableY-methods, [69](#)
D_compare-methods, [70](#)
D_getData-methods, [71](#)
D_getG0-methods, [71](#)
D_getLat-methods, [71](#)
D_indexD-methods, [72](#)
D_indexI-methods, [72](#)
D_levelplot-methods, [73](#)
D_Losses-methods, [73](#)
D_mergesolar-methods, [74](#)
D_shadeplot-methods, [75](#)
D_window-methods, [75](#)
D_writeSolar-methods, [76](#)

D_xyplot-methods, [78](#)

* utilities

C_corrFdKt, [36](#)
C_fBTd, [38](#)
C_fBTi, [39](#)
C_fCompD, [40](#)
C_fCompI, [41](#)
C_fInclin, [43](#)
C_fProd, [45](#)
C_fPump, [47](#)
C_fSolD, [48](#)
C_fSolI, [50](#)
C_fSombra, [52](#)
C_fTemp, [54](#)
C_fTheta, [55](#)
C_HQCurve, [57](#)
C_local2Solar, [58](#)
C_NmgPVPS, [59](#)
C_sample2Diff, [61](#)
C_solarAngles, [62](#)
C_utils-angle, [64](#)
C_utils-time, [64](#)

[,G0,ANY,ANY-method (D_window-methods),
[75](#)

[,G0-method (D_window-methods), [75](#)

[,Gef,ANY,ANY-method
(D_window-methods), [75](#)

[,Gef-method (D_window-methods), [75](#)

[,Meteo,ANY,ANY-method
(D_window-methods), [75](#)

[,Meteo-method (D_window-methods), [75](#)

[,ProdGCPV,ANY,ANY-method
(D_window-methods), [75](#)

[,ProdGCPV-method (D_window-methods), [75](#)

[,ProdPVPS,ANY,ANY-method
(D_window-methods), [75](#)

[,ProdPVPS-method (D_window-methods), [75](#)

[,Sol,ANY,ANY-method
(D_window-methods), [75](#)

[,Sol-method (D_window-methods), [75](#)

A1_calcSol, [5](#)

A2_calcG0, [6](#)

A3_calcGef, [9](#)

- A4_prodGCPV, [11](#)
- A5_prodPVPS, [15](#)
- A6_calcShd, [17](#)
- A7_optimShd, [18](#)
- A8_Meteo2Meteo, [22](#)
- A8_readBD, [23](#)
- A8_readG0dm, [25](#)
- A8_readSIAR, [26](#)
- aguiar (E_aguiar), [79](#)
- as.data.frame, Shade-method
(B7_Shade-class), [34](#)
- as.data.tableD, [77](#)
- as.data.tableD
(D_as.data.tableD-methods), [65](#)
- as.data.tableD,G0-method
(D_as.data.tableD-methods), [65](#)
- as.data.tableD,Gef-method
(D_as.data.tableD-methods), [65](#)
- as.data.tableD,ProdGCPV-method
(D_as.data.tableD-methods), [65](#)
- as.data.tableD,ProdPVPS-method
(D_as.data.tableD-methods), [65](#)
- as.data.tableD,Sol-method
(D_as.data.tableD-methods), [65](#)
- as.data.tableD-methods
(D_as.data.tableD-methods), [65](#)
- as.data.tableI, [77](#)
- as.data.tableI
(D_as.data.tableI-methods), [66](#)
- as.data.tableI,G0-method
(D_as.data.tableI-methods), [66](#)
- as.data.tableI,Gef-method
(D_as.data.tableI-methods), [66](#)
- as.data.tableI,ProdGCPV-method
(D_as.data.tableI-methods), [66](#)
- as.data.tableI,ProdPVPS-method
(D_as.data.tableI-methods), [66](#)
- as.data.tableI,Sol-method
(D_as.data.tableI-methods), [66](#)
- as.data.tableI-methods
(D_as.data.tableI-methods), [66](#)
- as.data.tableM, [77](#)
- as.data.tableM
(D_as.data.tableM-methods), [68](#)
- as.data.tableM,G0-method
(D_as.data.tableM-methods), [68](#)
- as.data.tableM,Gef-method
(D_as.data.tableM-methods), [68](#)
- as.data.tableM,ProdGCPV-method
(D_as.data.tableM-methods), [68](#)
- as.data.tableM,ProdPVPS-method
(D_as.data.tableM-methods), [68](#)
- as.data.tableM-methods
(D_as.data.tableM-methods), [68](#)
- as.data.tableY, [77](#)
- as.data.tableY
(D_as.data.tableY-methods), [69](#)
- as.data.tableY,G0-method
(D_as.data.tableY-methods), [69](#)
- as.data.tableY,Gef-method
(D_as.data.tableY-methods), [69](#)
- as.data.tableY,ProdGCPV-method
(D_as.data.tableY-methods), [69](#)
- as.data.tableY,ProdPVPS-method
(D_as.data.tableY-methods), [69](#)
- as.data.tableY-methods
(D_as.data.tableY-methods), [69](#)
- as.POSIXct, [38](#)
- azimuth (C_solarAngles), [62](#)
- B1_Meteo-class, [27](#)
- B2_Sol-class, [28](#)
- B3_G0-class, [29](#)
- B4_Gef-class, [30](#)
- B5_ProdGCPV-class, [32](#)
- B6_ProdPVPS-class, [33](#)
- B7_Shade-class, [34](#)
- bo0d (C_solarAngles), [62](#)
- C_corrFdKt, [36](#)
- C_fBTd, [38](#)
- C_fBTi, [39](#)
- C_fCompD, [40](#)
- C_fCompI, [41](#)
- C_fInclin, [43](#)
- C_fProd, [45](#)
- C_fPump, [47](#)
- C_fSolD, [48](#)
- C_fSolI, [50](#)
- C_fSombra, [52](#)
- C_fTemp, [54](#)
- C_fTheta, [55](#)
- C_HQCurve, [57](#)
- C_local2Solar, [58](#)
- C_NmgPVPS, [59](#)
- C_sample2Diff, [61](#)
- C_solarAngles, [62](#)
- C_utils-angle, [64](#)
- C_utils-time, [64](#)
- calcG0, [9](#), [10](#), [12](#), [13](#), [16](#), [18](#), [19](#), [24](#), [29](#), [43](#), [50](#)
- calcG0 (A2_calcG0), [6](#)
- calcGef, [12](#), [13](#), [16](#), [17](#), [19](#), [30](#), [43](#), [44](#), [55](#), [57](#)
- calcGef (A3_calcGef), [9](#)
- calcShd, [9](#), [10](#), [13](#), [18](#), [21](#), [54](#)
- calcShd (A6_calcShd), [17](#)

- calcSol, [6–10](#), [12](#), [16](#), [19](#), [28](#), [36](#), [40–42](#), [54–56](#), [63](#)
- calcSol (A1_calcSol), [5](#)
- char2diff (C_sample2Diff), [61](#)
- compare, [13](#)
- compare (D_compare-methods), [70](#)
- compare,G0-method (D_compare-methods), [70](#)
- compare,Gef-method (D_compare-methods), [70](#)
- compare,ProdGCPV-method (D_compare-methods), [70](#)
- compare-methods (D_compare-methods), [70](#)
- compareLosses, [13](#)
- compareLosses (D_Losses-methods), [73](#)
- compareLosses,ProdGCPV-method (D_Losses-methods), [73](#)
- compareLosses-methods (D_Losses-methods), [73](#)
- corrFdKt, [7](#), [8](#), [40](#), [42](#)
- corrFdKt (C_corrFdKt), [36](#)
- d2h (C_utils-angle), [64](#)
- d2r (C_utils-angle), [64](#)
- D_as.data.tableD-methods, [65](#)
- D_as.data.tableI-methods, [66](#)
- D_as.data.tableM-methods, [68](#)
- D_as.data.tableY-methods, [69](#)
- D_compare-methods, [70](#)
- D_getData-methods, [71](#)
- D_getG0-methods, [71](#)
- D_getLat-methods, [71](#)
- D_indexD-methods, [72](#)
- D_indexI-methods, [72](#)
- D_levelplot-methods, [73](#)
- D_Losses-methods, [73](#)
- D_mergesolar-methods, [74](#)
- D_shadeplot-methods, [75](#)
- D_window-methods, [75](#)
- D_writeSolar-methods, [76](#)
- D_xyplot-methods, [78](#)
- DateTimeClasses, [65](#)
- declination (C_solarAngles), [62](#)
- diff2Hours (C_sample2Diff), [61](#)
- dom (C_utils-time), [64](#)
- dotplot, [70](#), [73](#)
- doy (C_utils-time), [64](#)
- dst (C_utils-time), [64](#)
- dt2Meteo, [7](#), [8](#), [27](#), [42](#)
- dt2Meteo (A8_readBD), [23](#)
- E_aguiar, [79](#)
- E_helios, [79](#)
- E_prodEx, [80](#)
- E_pumpCoef, [80](#)
- E_SIAR, [81](#)
- E_solar.theme, [81](#)
- eccentricity (C_solarAngles), [62](#)
- eot, [58](#)
- eot (C_solarAngles), [62](#)
- est_SIAR (E_SIAR), [81](#)
- fBTd, [5](#), [6](#), [49](#), [62](#)
- fBTd (C_fBTd), [38](#)
- fBTi, [5](#), [63](#)
- fBTi (C_fBTi), [39](#)
- fCompD, [6–8](#), [29](#), [36](#), [37](#), [42](#)
- fCompD (C_fCompD), [40](#)
- fCompI, [6–8](#), [29](#), [36](#), [37](#), [41](#), [44](#)
- fCompI (C_fCompI), [41](#)
- FdKtBRL (C_corrFdKt), [36](#)
- FdKtCLIMEDd (C_corrFdKt), [36](#)
- FdKtCLIMEDh, [42](#)
- FdKtCLIMEDh (C_corrFdKt), [36](#)
- FdKtCPR, [7](#), [40](#)
- FdKtCPR (C_corrFdKt), [36](#)
- FdKtEKDd (C_corrFdKt), [36](#)
- FdKtEKDh (C_corrFdKt), [36](#)
- FdKtLJ (C_corrFdKt), [36](#)
- FdKtPage, [7](#), [40](#)
- FdKtPage (C_corrFdKt), [36](#)
- fInclin, [9](#), [10](#), [13](#), [18](#), [30](#), [46](#), [57](#), [74](#)
- fInclin (C_fInclin), [43](#)
- fProd, [13](#), [32](#), [73](#), [74](#)
- fProd (C_fProd), [45](#)
- fPump, [16](#), [17](#), [34](#), [60](#)
- fPump (C_fPump), [47](#)
- fread, [24](#), [25](#), [77](#)
- fSolD, [5](#), [7](#), [9](#), [12](#), [16](#), [19](#), [28](#), [38](#), [40](#), [51](#), [63](#)
- fSolD (C_fSolD), [48](#)
- fSolI, [5](#), [7](#), [9](#), [12](#), [16](#), [19](#), [28](#), [41](#), [42](#), [63](#)
- fSolI (C_fSolI), [50](#)
- fSombra, [17](#), [53](#), [57](#)
- fSombra (C_fSombra), [52](#)
- fSombra2X (C_fSombra), [52](#)
- fSombra6, [17](#), [20](#), [53](#)
- fSombra6 (C_fSombra), [52](#)
- fSombraEst, [53](#)
- fSombraEst (C_fSombra), [52](#)
- fSombraHoriz, [53](#)
- fSombraHoriz (C_fSombra), [52](#)
- fTemp, [6](#), [24](#), [46](#)
- fTemp (C_fTemp), [54](#)
- fTheta, [9](#), [10](#), [13](#), [18](#), [30](#), [43](#), [44](#), [54](#)
- fTheta (C_fTheta), [55](#)

- G0, [28, 31–35](#)
- G0-class (B3_G0-class), [29](#)
- Gef, [17, 28, 30, 32–35, 45](#)
- Gef-class (B4_Gef-class), [30](#)
- getData (D_getData-methods), [71](#)
- getData, Meteo-method (D_getData-methods), [71](#)
- getData-methods (D_getData-methods), [71](#)
- getG0 (D_getG0-methods), [71](#)
- getG0, Meteo-method (D_getG0-methods), [71](#)
- getG0-methods (D_getG0-methods), [71](#)
- getLat (D_getLat-methods), [71](#)
- getLat, G0-method (D_getLat-methods), [71](#)
- getLat, Meteo-method (D_getLat-methods), [71](#)
- getLat, Sol-method (D_getLat-methods), [71](#)
- getLat-methods (D_getLat-methods), [71](#)
- h2d (C_utils-angle), [64](#)
- h2r (C_utils-angle), [64](#)
- helios (E_helios), [79](#)
- hms (C_utils-time), [64](#)
- HQCurve (C_HQCurve), [57](#)
- indexD, [75, 76](#)
- indexD (D_indexD-methods), [72](#)
- indexD, G0-method (D_indexD-methods), [72](#)
- indexD, Meteo-method (D_indexD-methods), [72](#)
- indexD, Sol-method (D_indexD-methods), [72](#)
- indexD-methods (D_indexD-methods), [72](#)
- indexI (D_indexI-methods), [72](#)
- indexI, Sol-method (D_indexI-methods), [72](#)
- indexI-methods (D_indexI-methods), [72](#)
- Ktd (C_corrFdKt), [36](#)
- Kti (C_corrFdKt), [36](#)
- Ktlim (E_aguiar), [79](#)
- Ktm (C_corrFdKt), [36](#)
- Ktmtm (E_aguiar), [79](#)
- levelplot, formula, G0-method (D_levelplot-methods), [73](#)
- levelplot, formula, Meteo-method (D_levelplot-methods), [73](#)
- levelplot, formula, Sol-method (D_levelplot-methods), [73](#)
- levelplot, formula, zoo-method (D_levelplot-methods), [73](#)
- levelplot-methods (D_levelplot-methods), [73](#)
- local2Solar (C_local2Solar), [58](#)
- lonHH (C_local2Solar), [58](#)
- losses (D_Losses-methods), [73](#)
- losses, Gef-method (D_Losses-methods), [73](#)
- losses, ProdGCPV-method (D_Losses-methods), [73](#)
- losses-methods (D_Losses-methods), [73](#)
- mergesolaR, [13](#)
- mergesolaR (D_mergesolaR-methods), [74](#)
- mergesolaR, G0-method (D_mergesolaR-methods), [74](#)
- mergesolaR, Gef-method (D_mergesolaR-methods), [74](#)
- mergesolaR, Meteo-method (D_mergesolaR-methods), [74](#)
- mergesolaR, ProdGCPV-method (D_mergesolaR-methods), [74](#)
- mergesolaR, ProdPVPS-method (D_mergesolaR-methods), [74](#)
- mergesolaR-methods (D_mergesolaR-methods), [74](#)
- Meteo, [29, 31, 32, 34–36, 54](#)
- Meteo-class (B1_Meteo-class), [27](#)
- Meteod2Meteom (A8_Meteo2Meteo), [22](#)
- Meteoi2Meteod (A8_Meteo2Meteo), [22](#)
- MTM (E_aguiar), [79](#)
- NmgPVPS, [17, 48, 57](#)
- NmgPVPS (C_NmgPVPS), [59](#)
- optimShd, [34, 54](#)
- optimShd (A7_optimShd), [18](#)
- P2E (C_sample2Diff), [61](#)
- prodEx (E_prodEx), [80](#)
- ProdGCPV, [35](#)
- prodGCPV, [21, 32, 45, 46](#)
- prodGCPV (A4_prodGCPV), [11](#)
- ProdGCPV-class (B5_ProdGCPV-class), [32](#)
- ProdPVPS, [16](#)
- prodPVPS, [33, 34, 48, 57, 60](#)
- prodPVPS (A5_prodPVPS), [15](#)
- ProdPVPS-class (B6_ProdPVPS-class), [33](#)
- pumpCoef, [16, 17, 33, 47, 48, 57, 59, 60](#)
- pumpCoef (E_pumpCoef), [80](#)
- r2d (C_utils-angle), [64](#)
- r2h (C_utils-angle), [64](#)
- r2sec (C_utils-angle), [64](#)
- readBDd, [6–8, 23, 25–27, 36, 40, 54, 55, 72](#)
- readBDd (A8_readBD), [23](#)
- readBDi, [7, 8, 27, 36, 42](#)
- readBDi (A8_readBD), [23](#)
- readG0dm, [7, 8, 23, 25–27, 36, 40, 72](#)

- readG0dm (A8_readG0dm), 25
- readSIAR, 23
- readSIAR (A8_readSIAR), 26
- sample2Hours (C_sample2Diff), 61
- seq.POSIXt, 5, 7, 19, 38, 50, 61
- Shade, 21, 33, 75
- Shade-class (B7_Shade-class), 34
- shadeplot (D_shadeplot-methods), 75
- shadeplot, Shade-method
(D_shadeplot-methods), 75
- shadeplot-methods
(D_shadeplot-methods), 75
- show, G0-method (B3_G0-class), 29
- show, Gef-method (B4_Gef-class), 30
- show, Meteo-method (B1_Meteo-class), 27
- show, ProdGCPV-method
(B5_ProdGCPV-class), 32
- show, ProdPVPS-method
(B6_ProdPVPS-class), 33
- show, Shade-method (B7_Shade-class), 34
- show, Sol-method (B2_Sol-class), 28
- Sol, 29–36, 54, 61
- Sol-class (B2_Sol-class), 28
- solaR.theme (E_solaR.theme), 81
- solaR2 (solaR2-package), 3
- solaR2-package, 3
- sunHour (C_solarAngles), 62
- sunrise (C_solarAngles), 62
- truncDay (C_utils-time), 64
- window (D_window-methods), 75
- window-methods (D_window-methods), 75
- write.table, 76, 77
- writeSolar (D_writeSolar-methods), 76
- writeSolar, Sol-method
(D_writeSolar-methods), 76
- writeSolar-methods
(D_writeSolar-methods), 76
- xyplot, data.table, missing-method
(D_xyplot-methods), 78
- xyplot, formula, G0-method
(D_xyplot-methods), 78
- xyplot, formula, Meteo-method
(D_xyplot-methods), 78
- xyplot, formula, Shade-method
(D_xyplot-methods), 78
- xyplot, formula, Sol-method
(D_xyplot-methods), 78
- xyplot, G0, missing-method
(D_xyplot-methods), 78
- xyplot, Meteo, missing-method
(D_xyplot-methods), 78
- xyplot, ProdGCPV, missing-method
(D_xyplot-methods), 78
- xyplot, ProdPVPS, missing-method
(D_xyplot-methods), 78
- xyplot-methods (D_xyplot-methods), 78
- zenith (C_solarAngles), 62
- zoo2Meteo, 7, 27, 42
- zoo2Meteo (A8_readBD), 23

Bibliografía

- [LJ60] B. Y. H. Liu y R. C. Jordan. “The interrelationship and characteristic distribution of direct, diffuse, and total solar radiation”. En: *Solar Energy* 4 (1960), págs. 1-19.
- [Pag61] J. K. Page. “The calculation of monthly mean solar radiation for horizontal and inclined surfaces from sunshine records for latitudes 40N-40S”. En: *U.N. Conference on New Sources of Energy*. Vol. 4. 98. 1961, págs. 378-390.
- [Coo69] P.I. Cooper. “The Absorption of Solar Radiation in Solar Stills”. En: *Solar Energy* 12 (1969).
- [Spe71] J.W. Spencer. “Fourier Series Representation of the Position of the Sun”. En: 2 (1971). URL: <http://www.mail-archive.com/sundial@uni-koeln.de/msg01050.html>.
- [CR79] M. Collares-Pereira y Ari Rabl. “The average distribution of solar radiation: correlations between diffuse and hemispherical and between daily and hourly insolation values”. En: *Solar Energy* 22 (1979), págs. 155-164.
- [Sta85] Richard Stallman. *GNU Emacs*. Un editor de texto extensible, personalizable, auto-documentado y en tiempo real. 1985. URL: <https://www.gnu.org/software/emacs/>.
- [Mic88] Joseph J. Michalsky. “The Astronomical Almanac’s algorithm for approximate solar position (1950-2050)”. En: *Solar Energy* 40.3 (1988), págs. 227-235. ISSN: 0038-092X. DOI: DOI:10.1016/0038-092X(88)90045-X.
- [RBD90] D.T. Reindl, W.A. Beckman y J.A. Duffie. “Evaluation of hourly tilted surface radiation models”. En: *Solar Energy* 45.1 (1990), págs. 9-17. ISSN: 0038-092X. DOI: [https://doi.org/10.1016/0038-092X\(90\)90061-G](https://doi.org/10.1016/0038-092X(90)90061-G). URL: <https://www.sciencedirect.com/science/article/pii/0038092X9090061G>.
- [Pan+91] D. Panico et al. “Backtracking: a novel strategy for tracking PV systems”. En: *IEEE Photovoltaic Specialists Conference*. 1991, págs. 668-673.
- [Dom+03] Carsten Dominik et al. *Org Mode*. Un sistema de organización de notas, planificación de proyectos y autoría de documentos con una interfaz de texto plano. 2003. URL: <https://orgmode.org>.
- [ZG05] Achim Zeileis y Gabor Grothendieck. “zoo: S3 Infrastructure for Regular and Irregular Time Series”. En: *Journal of Statistical Software* 14.6 (2005), págs. 1-27. DOI: 10.18637/jss.v014.i06.
- [Sar08] Deepayan Sarkar. *Lattice: Multivariate Data Visualization with R*. New York: Springer, 2008. ISBN: 978-0-387-75968-5. URL: <http://lmdvr.r-forge.r-project.org>.
- [Str11] L. Strous. *Position of the Sun*. 2011. URL: <http://aa.quae.nl/en/reken/zonpositie.html>.

- [Per12] Oscar Perpiñán. “solaR: Solar Radiation and Photovoltaic Systems with R”. En: *Journal of Statistical Software* 50.9 (2012), págs. 1-32. DOI: [10.18637/jss.v050.i09](https://doi.org/10.18637/jss.v050.i09).
- [Adr+17] T. Adrada Guerra et al. “Comparative Energy Performance Analysis of Six Primary Photovoltaic Technologies in Madrid (Spain)”. En: *Energies* 10.6 (2017), pág. 772. DOI: [10.3390/en10060772](https://doi.org/10.3390/en10060772). URL: <https://doi.org/10.3390/en10060772>.
- [Uni20] European Union. *NextGenerationEU*. 2020. URL: https://next-generation-eu.europa.eu/index_es.
- [BOE22a] BOE. *Real Decreto-ley 10/2022, de 13 de mayo, por el que se establece con carácter temporal un mecanismo de ajuste de costes de producción para la reducción del precio de la electricidad en el mercado mayorista*. 2022. URL: <https://www.boe.es/buscar/act.php?id=BOE-A-2022-7843>.
- [BOE22b] BOE. *Real Decreto-ley 6/2022, de 29 de marzo, por el que se adoptan medidas urgentes en el marco del Plan Nacional de respuesta a las consecuencias económicas y sociales de la guerra en Ucrania*. 2022. URL: <https://www.boe.es/buscar/doc.php?id=BOE-A-2022-4972>.
- [dem22] Ministerio para transición ecológica y el reto demográfico. *Plan + Seguridad Energética*. 2022. URL: <https://www.miteco.gob.es/es/ministerio/planes-estrategias/seguridad-energetica.html#planSE>.
- [Eur22] Consejo Europeo. *REPowerEU*. 2022. URL: <https://www.consilium.europa.eu/es/policies/eu-recovery-plan/repowereu/>.
- [Hac22] Ministerio de Hacienda. *Mecanismo de Recuperación y Resiliencia*. 2022. URL: <https://www.hacienda.gob.es/es-ES/CDI/Paginas/FondosEuropeos/Fondos-relacionados-COVID/MRR.aspx>.
- [Mer+23] Olaf Mersmann et al. *microbenchmark: Accurate Timing Functions*. Proporciona infraestructura para medir y comparar con precisión el tiempo de ejecución de las expresiones de R. 2023. URL: <https://github.com/joshuaulrich/microbenchmark>.
- [Min23] pesca y alimentación Ministerio de agricultura. *Sistema de Información Agroclimática para el Regadío*. 2023. URL: <https://servicio.mapa.gob.es/websiar/>.
- [Per23] O. Perpiñán. *Energía Solar Fotovoltaica*. 2023. URL: <https://oscarperpinan.github.io/esf/>.
- [R C23] R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. Vienna, Austria, 2023. URL: <https://www.R-project.org/>.
- [UNE23] UNEF. “Fomentando la biodiversidad y el crecimiento sostenible”. En: *Informe anual UNEF* (2023). URL: <https://www.unef.es/es/recursos-informes?idMultimediaCategoria=18>.
- [Wan+23] Chris Wanstrath et al. *GitHub*. 2023. URL: <https://github.com/>.
- [SAM24] System Advisor Model (SAM). *SAM: System Advisor Model*. <https://sam.nrel.gov/>. 2024.
- [Bar+24] Tyson Barrett et al. *data.table: Extension of ‘data.frame’*. R package version 1.15.99, <https://Rdatatable.gitlab.io/data.table>, <https://github.com/Rdatatable/data.table>. 2024. URL: <https://r-datatable.com>.
- [Nat24] National Renewable Energy Laboratory. *Best Research-Cell Efficiency Chart*. <https://www.nrel.gov/pv/cell-efficiency.html>. 2024.

- [Pro24] ESS Project. *Emacs Speaks Statistics (ESS)*. Un paquete adicional para GNU Emacs diseñado para apoyar la edición de scripts y la interacción con varios programas de análisis estadístico. 2024. URL: <https://ess.r-project.org/>.
- [PVG24] PVGIS. *PVGIS: Photovoltaic Geographical Information System*. <https://ec.europa.eu/jrc/en/pvgis>. 2024.
- [PVS24] PVSyst. *PVSyst: Software for Photovoltaic Systems*. <https://www.pvsyst.com/>. 2024.
- [Sis24] Sisifo. *Sisifo: Solar Energy Simulation Software*. <https://www.sisifo.org/>. 2024.
- [Wic+24] H. Wickham et al. *profvis: Interactive Visualizations for Profiling R Code*. R package version 0.3.8.9000. 2024. URL: <https://github.com/rstudio/profvis>.