



















Comment	Description	Designator	Footprint	LibRef	Quantity
C0603_0.1UF	CAP CER 0.1UF 16V	C1, C3, C5, C9, C10, C12, C13, C18, C25,	FP-C0603C-CF-MFG	CMP-03020-016578-1	1
cooda_u. IUF	X7R 0603	C12, C13, C18, C25, C26	i i -cuuusc-CF-IVIFG	UNIT-U3UZU-U10378-1	,
C0603_0.33UF	Chip Capacitor, 0.33 uF, +/- 10%, 50 V, -55 to 125 degC, 0603 (1608 Metric), RoHS, Tape and Reel	C2, C4, C6, C19	CAPC1608X90X20LL10	CMP-2000-07551-1	
C0603_1UF		C7, C8, C11, C22, C23	CAPC1608X87X35LL15 T15	CMP-2006-03318-1	
ECA-2AM220	Aluminum Electrolytic Capacitor, 22 uF, +/- 20%, 100 V, -40 to 85 degC, 2-Pin THD, RoHS, Bulk	C14, C15	CAPPR55-250- 1120X630X1220	CMP-1665-00035-2	:
C0805_10UF		C24, C29	CAPC2013X135X50LL1 0T20	CMP-2007-03453-1	
DIODE_1N5819	DIODE SCHOTTKY 40V 1A SOD123	D1, D2, D3, D5, D6, D7		CMP-12790-000018-1	
LED0603_BLUE	LED BLUE CLEAR CHIP SMD	D4, D9, D10, D11, D12, D13, D14, D15, D16, D17, D18, D19, D20, D21, D22, D23, D24, D25, D26, D27, D28, D29, D30, D31, D32, D33, D34, D35, D36	FP-LTST-C191TBKT- MFG	CMP-22017-000008-1	2
LED	LED GREEN CLEAR	D8	FP-LTST-C190GKT-	CMP-22017-000005-1	
47346-0001	CHIP SMD Micro-USB B Receptacle with Flange, -30 to 85 degC, 5-Pin SMD, RoHS, Tape and Reel	J1	MFG MOLX-47346-0001- 5_V	CMP-2000-05246-1	
282836-2	Female Header, Pitch 5 mm, 1 x 2 Position, Height 10 mm, Tail Length 3.5 mm, Rohs, Bulk	J5	TECO-282836-2_V	CMP-1684-00017-1	
ESP32-WROOM-32D	WIFI MODULE 32MBITS SPI FLASH	MD1	FP-ESP32-WROOM- 32D-MFG	CMP-194065-000003-	
Header 4	Header, 4-Pin	P1, P3	HDR1X4	Header 4	
Header 5	Header, 5-Pin	P2	HDR1X5	Header 5	
Header 6 Header 16	Header, 6-Pin Header, 16-Pin	P4 P5, P6, P7	HDR1X6 HDR1X16	Header 6 Header 16	
	Header, 6-Pin, Dual				
Header 6X2	row	P8	HDR2X6	Header 6X2	
Header 2 BCP56-16	Header, 2-Pin TRANS NPN 80V 1A	P9, P10, P11 Q1, Q2	HDR1X2 FP-SOT-223-P008-	Header 2 CMP-12195-000003-1	
R0603_10K	SOT-223 Chip Resistor, 10 KOhm, +/- 1%, 0.1 W, 55 to 155 degC, 0603 (1608 Metric), RoHS, Tape and Reel	R1, R2, R3, R4, R6, R7, R12, R13, R14, R15, R16, R17, R18, R19, R20, R21, R24, R25, R26, R27, R28, R29, R30, R31, R32, R33, R45, R48, R49, R63	MFG RESC1609X55X30LL15 T15	CMP-2000-07452-1	3
R0603_4.7K	Resistor	R5, R44	J1-0603	Res3	
R0603_120R		R8, R9, R10, R11, R43	RESC1608X55X30NL20 T20	CMP-2000-00896-1	
R0603_2.4K		R22. R23	RESC1608X50X30ML2	CMP-2000-02561-1	
R0603_470R		R34, R35, R36, R37, R38, R39, R40, R41, R42, R46, R47, R50, R51, R52, R53, R54, R55, R56, R57, R58, R59, R60, R61, R62, R64, R65, R66, R67, R68	0T20 RESC1608X55X30NL15 T15	CMP-2000-00795-1	2
push_button	FSMSM Push Button Switch, 50 mA, -35 to 85 degC, 2-Pin SMD, RoHS, Tape and Reel	SW1, SW2	TECO-FSMSMTR_V	CMP-2000-07501-1	:
L7806CD2T-TR	Positive Voltage Regulator, 3-Pin D2PAK, Tape and Reel 1000 mA, Low	U1, U2, U3, U8	TO-263_L	CMP-0244-00208-1	
MCP1826S-3302E/DB	Voltage, Low Quiescent Current LDO Regulator, 3-Pin SOT-223, Extended Temperature	U4	SOT-223-DB3_L	CMP-0136-00504-1	
CP2102N-A01- GQFN24	USBXpress(TM) Family, 4 GPIOs, 2.2 to 3.6 V, -40 to 85 degC, 24-Pin QFN, RoHS	U5	SLAB-QFN-24- 2550x2550TP_A_V	CMP-2000-07570-1	
ULN2803ADWR	Darlington Transistor Array, -40 to 85 degC, 18-Pin SOIC (DW), Green (RoHS & no Sb/Br), Tape and Reel	U6, U9, U10	DW0018A_L	CMP-2000-07354-1	:
PCA9685PW	16-Channel, 12-Bit PWM Fm+ I2C-Bus LED Controller, 2.3 to 5.5 V, -40 to 85 degC, 28-Pin TSSOP (SOT361-1), RoHS, Tape and Reel	U7	SOT361-1_V	CMP-1595-00004-2	