

```
layout: page
title: "Project Wikis"
author: susanna_persson-solidify
last_updated: 2022-08-09
search_exclude: false
```

The SyncHub Wiki Export/Wiki Import adapters migrates the following resources between ADO organizations:

- Project wikis

Notes:

- Work item references in the markdown files are replaced with their new id
- No support for code wikis at this time. Use the repo adapters instead and create the code wikis manually.

Permissions

- **required PAT scopes:** Wiki (Read & write)

Export: Sample config

Command

[illegible]

Configuration

```
{
  "configuration": {
    "source": "https://dev.azure.com/solidifydemo",
    "target": "C:\\Temp\\Wikis",
    "projects": [
      {
        "Name": "*"
      }
    ],
    "UseCloudFileShare": false,
    "AlreadyAuthenticatedInWindows": false,
    "UseCustomGitCredentials": false,
    "CustomGitUsername": "",
    "CustomGitPassword": "",
    "apiVersion": "6.0-preview.2"
  }
}
```

Feature flags

- **AlreadyAuthenticatedInWindows:** [true/false]
 - if **true**, no authentication will be used when running the **git** commands. Use this if git credentials are already stored in Windows Credential Manager.
 - if **false**, the default or custom git credentials will be used.
- **UseCustomGitCredentials:** [true/false]
 - if **true**, the **CustomGitUsername** and **CustomGitPassword** will be used as username and password by all **git** commands. You can set these to whatever you want.
 - if **false**, the ADO PAT will be used as authentication by all **git** commands.

Work Item mapping

A mapping file must be generated using [the work item mapping script here. \(https://github.com/solidify-internal/synhub-bootstraptrapper/blob/main/mapper-scripts/map-workitems.ps1\)](https://github.com/solidify-internal/synhub-bootstraptrapper/blob/main/mapper-scripts/map-workitems.ps1) The resulting file must then be specified in the import config below.

Import: Sample config

Command

[illegible]

Configuration

```
{
  "target": "https://dev.azure.com/demoorg",
  "SourceFilePath": "C:\\Temp\\Wikis\\ContosoAir",
  "TargetProject": "ContosoAir-Migrated",
  "WorkItemMapping": "C:\\Temp\\synchub-configs\\mapping_file.csv",
  "SourceProject": "ContosoAir",
  "AlreadyAuthenticatedInWindows": false,
  "UseCustomGitCredentials": false,
  "CustomGitUsername": "",
  "CustomGitPassword": "",
  "apiVersion": "6.0-preview.2"
}
```

Feature flags

- **AlreadyAuthenticatedInWindows:** [true/false]
 - if `true`, no authentication will be used when running the **git** commands. Use this if git credentials are already stored in Windows Credential Manager.
 - if `false`, the default or custom git credentials will be used.
- **UseCustomGitCredentials:** [true/false]
 - if `true`, the **CustomGitUsername** and **CustomGitPassword** will be used as username and password by all **git** commands. You can set these to whatever you want.
 - if `false`, the ADO PAT will be used as authentication by all **git** commands.