



SOLIDProof
Bring trust into your projects

**Blockchain Security | Smart Contract Audits | KYC
Development | Marketing**

MADE IN GERMANY

Butcoin

AUDIT

SECURITY ASSESSMENT

23. April, 2024

FOR



SolidProof.io



@solidproof_io



| | |
|--|----|
| Introduction | 3 |
| Disclaimer | 3 |
| Project Overview | 4 |
| Summary | 4 |
| Social Medias | 4 |
| Audit Summary | 5 |
| File Overview | 6 |
| Imported packages | 6 |
| Components | 7 |
| Exposed Functions | 7 |
| Capabilities | 8 |
| Inheritance Graph | 9 |
| Audit Information | 10 |
| Vulnerability & Risk Level | 10 |
| Auditing Strategy and Techniques Applied | 11 |
| Methodology | 11 |
| Overall Security | 12 |
| Upgradeability | 12 |
| Ownership | 13 |
| Ownership Privileges | 14 |
| Minting tokens | 14 |
| Burning tokens | 15 |
| Blacklist addresses | 16 |
| Fees and Tax | 17 |
| Lock User Funds | 18 |
| Centralization Privileges | 19 |
| Audit Results | 20 |



Introduction

SolidProof.io is a brand of the officially registered company MAKE Network GmbH, based in Germany. We're mainly focused on Blockchain Security such as Smart Contract Audits and KYC verification for project teams.

Solidproof.io assess potential security issues in the smart contracts implementations, review for potential inconsistencies between the code base and the whitepaper/documentation, and provide suggestions for improvement.

Disclaimer

SolidProof.io reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of the security or functionality of the technology we agree to analyze.



Project Overview

Summary

| | |
|--------------------------|--|
| Project Name | Butcoin |
| Website | https://buttchain.co/ |
| About the project | In the ever-evolving world of cryptocurrency, the market has been flooded with countless meme coins, each vying for a moment of fame. Butcoin emerges as a beacon of cheeky innovation, challenging the monotony with its unique blend of humour and technology. This document outlines the fundamentals of Butcoin, a cryptocurrency designed not just to ride the waves of blockchain tech but to introduce a playful twist into the blockchain space. |
| Chain | Polygon |
| Language | Solidity |
| Codebase | Butcoin: https://polygonscan.com/address/0x7f831b1f6ec6915fda914e970c4c813adf42ccb2#code Toiletpaper_Matic: https://polygonscan.com/address/0xd6a0aff314ca0031f32c44caa197e3e8a7ebf50#code |
| Commit | N/A |
| Unit Tests | Not Provided |

Social Medias

| | |
|------------------|---|
| Telegram | N/A |
| Twitter | https://twitter.com/ButcoinOfficial |
| Facebook | N/A |
| Instagram | N/A |
| GitHub | N/A |
| Reddit | N/A |
| Medium | N/A |
| Discord | N/A |
| YouTube | N/A |
| TikTok | N/A |
| LinkedIn | N/A |



Audit Summary

| Version | Delivery Date | Change Log |
|---------|----------------|---|
| v1.0 | 12. April 2024 | <ul style="list-style-type: none">· Layout Project· Automated/ Manual-Security Testing· Summary |
| v1.3 | 23. April 2024 | <ul style="list-style-type: none">· Reaudit |

Note – The following audit report presents a comprehensive security analysis of the smart contract utilized in the project that includes outside manipulation of the contract's functions in a malicious way. This analysis did not include functional testing (or unit testing) of the contract/s logic. We cannot guarantee 100% logical correctness of the contract as we did not functionally test it. This includes internal calculations in the formulae used in the contract.



File Overview

The Team provided us with the files that should be tested in the security assessment. This audit covered the following files listed below with an SHA-1 Hash.

| File Name | SHA-1 Hash |
|---------------------------------|--|
| contracts/Toiletpaper_Matic.sol | fe42357b6c5c9c00b7c34140f06af4301fa40f9d |
| contracts/Butcoin.sol | 9d8a6f06d0c60d3d75cd42a926b8db359ffbcad8 |

Please note: Files with a different hash value than in this table have been modified after the security check, either intentionally or unintentionally. A different hash value may (but need not) be an indication of a changed state or potential vulnerability that was not the subject of this scan.

Imported packages.

Used code from other Frameworks/Smart Contracts.

| Dependency / Import Path | Count |
|--|-------|
| @openzeppelin/contracts-upgradeable/access/OwnableUpgradeable.sol | 2 |
| @openzeppelin/contracts-upgradeable/math/SafeMathUpgradeable.sol | 2 |
| @openzeppelin/contracts-upgradeable/token/ERC20/ERC20Upgradeable.sol | 2 |
| @openzeppelin/contracts-upgradeable/utils/ReentrancyGuardUpgradeable.sol | 2 |
| @uniswap/v3-core/contracts/interfaces/IUniswapV3Factory.sol | 1 |
| @uniswap/v3-core/contracts/interfaces/IUniswapV3Pool.sol | 1 |
| @uniswap/v3-periphery/contracts/interfaces/INonfungiblePositionManager.sol | 1 |
| @uniswap/v3-periphery/contracts/interfaces/ISwapRouter.sol | 1 |

Note for Investors: We only audited contracts mentioned in the scope above. All contracts related to the project apart from that are not a part of the audit, and we cannot comment on its security and are not responsible for it in any way.



External/Public functions

External/public functions are functions that can be called from outside of a contract, i.e., they can be accessed by other contracts or external accounts on the blockchain. These functions are specified using the function declaration's external or public visibility modifier.

State variables

State variables are variables that are stored on the blockchain as part of the contract's state. They are declared at the contract level and can be accessed and modified by any function within the contract. State variables can be needed within visibility modifier, such as public, private or internal, which determines the access level of the variable.

Components

|  Contracts |  Libraries |  Interfaces |  Abstract |
|---|---|--|--|
| 2 | 0 | 0 | 0 |

Exposed Functions

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

|  Public |  Payable | | | |
|--|---|---------|------|------|
| 28 | 8 | | | |
| External | Internal | Private | Pure | View |
| 4 | 25 | 0 | 0 | 5 |

StateVariables


| Total |  Public |
|-------|--|
| 38 | 38 |

Capabilities

| Solidity Versions observed | Experimental Features | Can Receive Funds | Uses Assembly | Has Destroyable Contracts | |
|----------------------------|-----------------------|-------------------|---------------------|---------------------------|--------------------|
| ^0.7.6 | ----- | Yes | | ----- | |
| Transfer s ETH | Low-Level Calls | Delegate Call | Uses Hash Functions | ECRecover | New/Create/Create2 |
| Yes | | | Yes | yes | |

Inheritance Graph

An inheritance graph is a graphical representation of the inheritance hierarchy among contracts. In object-oriented programming, inheritance is a mechanism that allows one class (or contract, in the case of Solidity) to inherit properties and methods from another class. It shows the relationships between different contracts and how they are related to each other through inheritance.



Audit Information

Vulnerability & Risk Level

Risk represents the probability that a certain source threat will exploit the vulnerability and the impact of that event on the organization or system. The risk level is computed based on CVSS version 3.0.

| Level | Value | Vulnerability | Risk (Required Action) |
|----------------------|---------|---|---|
| Critical | 9 - 10 | A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken. | Immediate action to reduce risk level. |
| High | 7 - 8.9 | A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way. | Implementation of corrective actions as soon as possible. |
| Medium | 4 - 6.9 | A vulnerability that could affect the desired outcome of executing the contract in a specific scenario. | Implementation of corrective actions in a certain period. |
| Low | 2 - 3.9 | A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective. | Implementation of certain corrective actions or accepting the risk. |
| Informational | 0 - 1.9 | A vulnerability that has informational character but is not affecting any of the code. | An observation that does not determine a level of risk |



Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to check the repository for security-related issues, code quality, and compliance with specifications and best practices. To this end, our team of experienced pen-testers and smart contract developers reviewed the code line by line and documented any issues discovered.

We check every file manually. We use automated tools only so that they help us achieve faster and better results.

Methodology

The auditing process follows a routine series of steps:

1. Code review that includes the following:
 - a. Reviewing the specifications, sources, and instructions provided to SolidProof to ensure we understand the size, scope, and functionality of the smart contract.
 - b. Manual review of the code, i.e., reading the source code line by line to identify potential vulnerabilities.
 - c. Comparison to the specification, i.e., verifying that the code does what is described in the specifications, sources, and instructions provided to SolidProof.
2. Testing and automated analysis that includes the following:
 - a. Test coverage analysis determines whether test cases cover code and how much code is executed when those test cases are executed.
 - b. Symbolic execution, which is analysing a program to determine what inputs cause each part of a program to execute.
3. Review best practices, i.e., review smart contracts to improve efficiency, effectiveness, clarity, maintainability, security, and control based on best practices, recommendations, and research from industry and academia.
4. Concrete, itemized and actionable recommendations to help you secure your smart contracts.



Overall Security Upgradeability

Contract is an upgradable

✗ Deployer can update the contract with new functionalities.

| | |
|-------------|---|
| Description | The contract is an upgradeable contract. The Deployer is able to change or add any functionalities to the contract after deploying. |
| Comment | The deployer of the contract can deploy another eversion of the contract with the updated functionalities in the contract. |

File/Line(s): L95-102

Codebase: Butcoin.sol

```
ftrace | funcSig
function initialize()
    public
    initializer
{
    __ERC20_init("Butcoin", "BUTCOIN");
    __Ownable_init();
    __ReentrancyGuard_init();
```

File/Line(s): L61-67

Codebase: Toiletpaper_Matic.sol

```
ftrace | funcSig
function initialize()
    public
    initializer
{
    __ERC20_init("Toiletpaper_Matic", "TP MATIC");
    __Ownable_init();
```



Ownership

Contract ownership is not renounced.

 The ownership is not renounced.

Description

The owner has not renounced the ownership that means that the owner retains control over the contract's operations, including the ability to execute functions that may impact the contract's users or stakeholders. This can lead to several potential issues, including:

- Centralizations
- The owner has significant control over contract's operations.

Comment

N/A

Note – *The contract cannot be considered as renounced till it is not deployed or having some functionality that can change the state of the contract.*



Ownership Privileges

These functions can be dangerous. Please note that abuse can lead to financial loss. We have a guide where you can learn more about these Functions.

Minting tokens

Minting tokens refer to the process of creating new tokens in a cryptocurrency or blockchain network. This process is typically performed by the project's owner or designated authority, who has the ability to add new tokens to the network's total supply.

Contract owner cannot mint new tokens.

 **The owner cannot mint new tokens.**

| | |
|-------------|---|
| Description | The owner is not able to mint new tokens once the contract is deployed. |
| Comment | N/A |



Burning tokens

Burning tokens is the process of permanently destroying a certain number of tokens, reducing the total supply of a cryptocurrency or token. This is usually done to increase the value of the remaining tokens, as the reduced supply can create scarcity and potentially drive up demand.

| Contract owner cannot burn tokens |  The owner cannot burn tokens. |
|-----------------------------------|---|
| Description | The owner is not able burn tokens without any allowances. |
| Comment | N/A |



Blacklist addresses

Blacklisting addresses in smart contracts is the process of adding a certain address to a blacklist, effectively preventing them from accessing or participating in certain functionalities or transactions within the contract. This can be useful in preventing fraudulent or malicious activities, such as hacking attempts or money laundering.

Contract owner cannot blacklist addresses.

 **The owner cannot blacklist wallets.**

| | |
|-------------|---|
| Description | The owner cannot blacklist wallets from transferring of tokens. |
| Comment | N/A |



Fees and Tax

In some smart contracts, the owner or creator of the contract can set fees for certain actions or operations within the contract. These fees can be used to cover the cost of running the contract, such as paying for gas fees or compensating the contract's owner for their time and effort in developing and maintaining the contract.

Contract owner cannot set fees more than 25%.



The owner cannot set fees more than 25%.

| | |
|-------------|---|
| Description | The owner cannot set fees of more than 25%. |
| Comment | N/A |



Lock User Funds

In a smart contract, locking refers to the process of restricting access to certain tokens or assets for a specified period of time. When token or assets are locked in a smart contract, they cannot be transferred or used until the lock-up period has expired or certain conditions have been met.

Contract owner cannot lock function.



The owner cannot lock function.

| | |
|-------------|-------------------------------------|
| Description | The owner cannot lock the contract. |
| Comment | N/A |



Centralization Privileges

Centralization can arise when one or more parties have privileged access or control over the contract's functionality, data, or decision-making. This can occur, for example, if the contract is controlled by a single entity or if certain participants have special permissions or abilities that others do not.

In the project, there are authorities that have access to the following functions:

| File | Privileges |
|------------------------------|---|
| Butcoin.sol | <ul style="list-style-type: none">➤ The owner can update the interfaces in the contract.➤ The owner can mint the liquidity in the contract.➤ The owner can enable trading only once.➤ The owner can end the presale. |
| Toiletpaper_Matic.sol | <ul style="list-style-type: none">➤ The owner can update the butcoin and liquidity pool address to any arbitrary address.➤ The butcoin contract can burn tokens from the user wallet. |

Recommendations

To avoid potential hacking risks, it is advisable for the client to manage the private key of the privileged account with care. Additionally, we recommend enhancing the security practices of centralized privileges or roles in the protocol through a decentralized mechanism or smart-contract-based accounts, such as multi-signature wallets.

Here are some suggestions of what the client can do:

- Consider using multi-signature wallets: Multi-signature wallets require multiple parties to sign off on a transaction before it can be executed, providing an extra layer of security e.g. Gnosis Safe
- Use of a timelock at least with a latency of e.g. 48-72 hours for awareness of privileged operations
- Introduce a DAO/Governance/Voting module to increase transparency and user involvement
- Consider Renouncing the ownership so that the owner cannot modify any state variables of the contract anymore. Make sure to set up everything before renouncing.



Audit Result

Critical Issues

No critical issues

High Issues

No high issues

Medium Issue

#1 | Possible front running.

| File | Severity | Location | Status |
|---------|----------|------------------------------|--------|
| Butcoin | Medium | L336-384, L386-437, L574-607 | Fixed |

Description – The minimum amount out is set to zero in the contract which is not recommended as it is an analog for the slippage percentage, setting it to 0 allows for 100% slippage, which allows it to be front-runned for up to 100% of your trade value.

Remediation – It is recommended to use a time-weighted average price for that to avoid these circumstances.

#2 | Missing non-reentrant.

| File | Severity | Location | Status |
|---------|----------|----------|--------|
| Butcoin | Medium | L346-384 | Fixed |

Description – The non-reentrant check is commented in the sell functionality of the contract which is not recommended as this can lead to the reentrancy in the contract.

Remediation – Add the reentrant modifier in the function to avoid these circumstances.

#3 | Missing nonces.

| File | Severity | Location | Status |
|---------|----------|----------|--------|
| Butcoin | Medium | L635-652 | ACK |



Description – The function uses signature verification to execute the transaction in the contract but once the signature is verified the user will be able to execute the transaction with the same signature verification and it is recommended that the signature must be verified in each transaction.

Remediation – Add the nonce functionality in the contract to avoid these circumstances.

#4 | Missing isContract check.

| File | Severity | Location | Status |
|-------------------|----------|----------|--------|
| Toiletpaper_Matic | Medium | -- | Fixed |

Description – This contract is used by the butcoin contract to execute the transactions such as minting and burning of the tokens so it is recommended to add a require check so that only the token will be able to execute the transactions in this contract.

Low Issue

#1 | Missing zero or dead address check.

| File | Severity | Location | Status |
|-------------------|----------|----------|--------|
| Toiletpaper_Matic | Low | L73-82 | ACK |

Description – It is recommended to check that the address cannot be set to zero or dead address.

#2 | Old compiler version.

| File | Severity | Location | Status |
|------|----------|----------|--------|
| All | Low | -- | ACK |

Description – Adding the latest constant version of solidity is recommended, as this prevents the unintentional deployment of a contract with an outdated compiler that contains unresolved bugs.




Informational Issue

#1 | NatSpec Documentation missing.

| File | Severity | Location | Status |
|------|---------------|----------|--------|
| All | Informational | -- | ACK |

Description – If you started to comment on your code, also comment on all other functions, variables, etc.



Legend for the Issue Status

| Attribute or Symbol | Meaning |
|--------------------------|--|
| Open | The issue is not fixed by the project team. |
| Fixed | The issue is fixed by the project team. |
| Acknowledged(ACK) | The issue has been acknowledged or declared as part of business logic. |



**Blockchain Security | Smart Contract Audits | KYC
Development | Marketing**

MADE IN GERMANY