


# Changelog


## SGPA3

### Automated Process Management System



Changelog Version 2025/262  
 Period: 05/27/2025 to 06/02/2025  
 Revision 00  
 Date: 06/17/2025

Some applications mentioned in this report may not be available in the feature pack in your SGPA 3.0



Thank you for being a SGPA 3.0 user!

We update our system in order to fix bugs, improve performance and add new features to bring a better user experience and contribute to a management with greater quality and efficiency.

## Table of Contents

1. SGPA3 .....	4
1.1 Improvements .....	4
1.1.1 Maps – Depthmeter .....	4
1.1.2 PBI Reports – Alarms .....	6
1.1.3 PBI Reports – Harvester Benchmark .....	6
1.1.4 PBI Reports and Maps – CDA – Digital Cotton Certificate.....	8
1.1.5 PBI Reports – Efficiency (Grains).....	10
1.1.6 PBI Reports – Forest Efficiency (Perennials) .....	11
1.1.7 PBI Reports – Application of Fertigation.....	16
1.2 Bugs.....	18
1.2.1 Maps – Analytical .....	18
1.2.2 Modules – Telemetry .....	18
1.2.3 PBI Reports – Filters.....	18

## 1. SGPA3

### 1.1 Improvements

#### 1.1.1 Maps – Depthmeter

In order to optimize the analysis of sugarcane crop productivity data, a new analytical map, the “Depthmeter”, was implemented, with “Line” and “Interpolation” visualization. This map aims to present the data from the **soil depth sensor** present in the Implements, that is, to measure the resistance or compaction in different layers, indicating how much the subsoiling or harrowing implement penetrated the ground. The map displays this depth spatially, allowing analytical monitoring of the operation, helping to identify compacted areas and guiding specific interventions, thus optimizing soil management and operational efficiency.



Image 01 – Line View of the “Depthmeter” Map



Image 02 – Displaying “Depthmeter” values in the Details menu



Image 03 – Interpolation View of the “Depthmeter” Map




Go to Top menu > Maps > Line and Interpolation > Productivity > Depthmeter



Available for Sugarcane Vertical Environments. Release will be carried out on demand, through a request via call to IT Support.

## 1.1.2 PBI Reports – Alarms

Improvement applied to the PBI “Alarms” Report, from the Sugarcane, Grains and Perennials Verticals, to add the “Justified by” column, in the “Table” tab. With this new column, it is possible to check which user performed the Alarm Justification.



Operação	Alarme Duração (hh:mm:ss)	Alarme Duração (h)	Quantidade de Alarmes	Justificativa	Justificado por	Data Hora Ocorrência	Valor do Alarme	Valor do Alarme Máximo	Latitude	Longitude
LDO PEREIRA DE	-1 - * NÃO DEFINIDO *	00:02:00	0,03	1		16/06/2025 08:28:26	0,00	0,00		
SANTOS MENDONC	-1 - * NÃO DEFINIDO *	02:30:54	2,52	1		16/06/2025 01:19:38	0,00	0,00		
SANTOS MENDONC	-1 - * NÃO DEFINIDO *	00:01:00	0,02	1		16/06/2025 05:38:01	0,00	0,00		
SANTOS MENDONC	-1 - * NÃO DEFINIDO *	00:33:30	0,56	1		16/06/2025 21:39:30	0,00	0,00		
SANTOS MENDONC	-1 - * NÃO DEFINIDO *	00:50:00	0,83	1		16/06/2025 22:19:24	0,00	0,00		
SANTOS MENDONC	-1 - * NÃO DEFINIDO *	00:20:00	0,33	1		16/06/2025 23:59:47	0,00	0,00		
PILOTO DA SILV	-1 - * NÃO DEFINIDO *	00:13:43	0,23	1		16/06/2025 15:39:40	0,00	0,00		
PILOTO DA SILV	-1 - * NÃO DEFINIDO *	00:01:11	0,02	1		16/06/2025 15:54:43	0,00	0,00		
PILOTO DA SILV	-1 - * NÃO DEFINIDO *	00:13:00	0,22	1		16/06/2025 16:03:04	0,00	0,00		
PILOTO DA SILV	-1 - * NÃO DEFINIDO *	00:01:00	0,02	1		16/06/2025 16:37:52	0,00	0,00		
PILOTO DA SILV	-1 - * NÃO DEFINIDO *	00:02:00	0,03	1		16/06/2025 16:39:52	0,00	0,00		
tfimido *	-1 - * NÃO DEFINIDO *	00:10:00	0,17	1		16/06/2025 13:12:31	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:02:00	0,03	1		16/06/2025 14:43:31	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:07:00	0,12	1		16/06/2025 15:42:31	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:06:00	0,10	1		16/06/2025 17:22:31	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:01:00	0,02	1		16/06/2025 18:09:31	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:23:00	0,38	1		16/06/2025 20:38:29	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	01:59:08	1,99	1		16/06/2025 00:01:06	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	07:10:00	7,17	1		16/06/2025 02:05:08	0,00	0,00	-21,58	-50,43
tfimido *	-1 - * NÃO DEFINIDO *	00:48:00	0,80	1		16/06/2025 13:45:08	0,00	0,00	-21,58	-50,43
		2297183...	2.297.183,81	5551						

Image 04 – PBI “Alarms” report displaying the “Justified by” column in the “Table” tab



Go to Main Menu > Reports > PBI > Online Command and Alarms Menu > Alarms > Table Tab > Justify by Column



Available for Sugarcane, Grains and Perennials Vertical Environments.

## 1.1.3 PBI Reports – Harvester Benchmark

Improvements made to the PBI “Harvester Benchmark” Report, for the Sugarcane Vertical. As of this version, in addition to the existing “Top 10” button, a new view has been included, “Top 10 Ranking”, with an updated visual identity to

highlight the best-ranked units in a more intuitive and attractive way. The improvement aims to make it easier to read and compare performance between units, making the analysis more practical and visual.




Image 05 – “Benchmark Harvester” report showing “Top 10” and “Top 10 Ranking” options in the “Benchmark” tab




Image 06 – Overview of the “Top 10 Ranking” in the “Harvester Benchmark” report

In addition, the PBI “Harvester Benchmark” Report has received an update to the Outlier Rule for Mechanical Availability. The update is described below:

- The maximum limit, which was previously 95%, is now 98%, meaning that values above 98% will be considered outliers and will not be displayed in the indicators, ensuring greater accuracy and avoiding distortions. This change reflects the continuous improvement in the performance of the units. The new limit allows real data to be monitored in a way that is more consistent with the current reality.

OUTLIERS RULE APPLIED TO DATA

**These values have been set by our technical team based on their practical experience.**

Cuto ff Hours (h): Values greater than 20 hours or less than 2.4 hours are considered outliers

Productive Hours (h): Values greater than 20 hours or less than 2.4 hours are considered outliers

Operational Efficiency (%): Outliers are considered values greater than 90% or less than 10%

Maneuvering/Productive (%): Outliers are considered values greater than 60%


**Mechanical Availability (%): Outliers are considered values greater than 98% or less than 20%**

Lack of Overflow (%): Values greater than 40% or less than 2% are considered outliers

Motor On at Stop (%): Outliers are considered values lower than 2%

<b>Outlier&lt;2.4h --&gt;h</b> <small>Outlier Horas de Corte</small>	<b>Outlier&lt;2.4h --&gt;h</b> <small>Outlier Horas Produtivas</small>	<b>Outlier&lt;10% --&gt;%</b> <small>Outlier Eficiência Operacional (%)</small>
<b>--</b> <small>Outlier Manobra/Productiva (h)</small>	<b>Outlier&gt;98% --&gt;100,00%</b> <small>Outlier Disponibilidade Mecânica (%)</small>	<b>Outlier&lt;2% --&gt;%</b> <small>Outlier Falta de Transbordo (%)</small>
<b>Outlier&lt;2% --&gt;%</b> <small>Outlier Motor Ligado em Parada (%)</small>		

Image 07 – New Outlier Rule for Mechanical Availability


 Go to Main Menu > Reports > PBI > Benchmark Menu > Harvester Benchmark > Benchmark Tab > Top right corner > Top 10 Ranking Option and in Harvester Benchmark > Benchmark Tab > Top right corner > “i” Icon > Outliers Rule Applied to Data > Mechanical Availability

 Available for Sugarcane Vertical Environments that have the “Benchmark” solution active.

#### 1.1.4 PBI Reports and Maps – CDA – Digital Cotton Certificate

Improvement applied to the PBI Report “Digital Cotton Certificate”, from Grains Vertical, so that the data on “Number of Modules per Control Point” matches the “Traceability” data provided in the “CDA” module of Maps.





Images 08 and 09 – PBI “Digital Cotton Certificate” report and “CDA” module of maps displaying equivalent data



Go to Main menu > Reports > PBI > Digital Cotton Certificate and in Top menu > Maps > Top menu within the map > CDA



Available for Grains Vertical Environments that have the “CDA - Digital Cotton Certificate” solution active. Applied on 06/10/2025.

### 1.1.5 PBI Reports – Efficiency (Grains)

New PBI “Efficiency” Report implemented for the Grains Vertical. This report makes it possible to identify opportunities for improvement and minimize waste or inefficiencies in the operational process. The report provides a broad view of the performance of operations, bringing together several analyses, such as:

- Performance indicators by equipment and operation.
- Efficiency comparisons between different periods.
- Points of attention that may be impacting performance.

The report is divided into 9 (nine) tabs, namely: “General”, “Operational”, “Energy”, “Management”, “Mechanical Availability”, “Engine Idling”, “No Recording”, “Operational Area”, “Operational Quality”, “Workday Utilization” and “Analytical View”.




Image 10 – View of the “Efficiency” report with the “General” tab selected

Go to Main menu > Reports > PBI > Efficiency

Applied on 06/09/2025. Available for the Grains Vertical Environments.

### 1.1.6 PBI Reports – Forest Efficiency (Perennials)

The new PBI “Forest Efficiency” Report has been implemented for the Perennials Vertical. This report is based on the “Efficiency” report already available for this vertical, maintaining the same information base but presenting a simplification of management indicators, with a view focused on road operations and timber shipments.

The report is divided into 9 (nine) tabs, which are: “Operational Efficiency”, “Loaded / Available Time”, “Energy Efficiency”, “Loaded / Engine On”, “No Recording”, “Engine Idling / On Stopped”, “Average Consumption”, “Machine Availability” and “Summary by Equipment”.




Image 11 – Overview of the “Operational Efficiency” tab in the “Forest Efficiency” report




Image 12 – Overview of the “Loaded / Available Time” tab in the “Forest Efficiency” report

Image 13 – Overview of the “Energy Efficiency” tab in the “Forest Efficiency” report




Image 14 – Overview of the “Loaded / Engine Running” tab in the “Forest Efficiency” report




Image 15 – Overview of the “No entries” tab in the “Forest Efficiency” report




Image 16 – Overview of the “Engine Idling /On Stopped” tab in the “Forest Efficiency” report

Image 17 – Overview of the “Average Consumption” tab in the “Forest Efficiency” report






Image 18 – Overview of the “Machine Availability” tab in the “Forest Efficiency” report

Image 19 – Overview of the “Summary by Equipment” tab in the “Forest Efficiency” report



Go to Main menu > Reports > PBI > Forest Efficiency



Applied on 06/09/2025. Available for Perennial Vertical Environments, however, release will be carried out on demand, through a request via call to IT Support.

### 1.1.7 PBI Reports – Application of Fertigation

Improvement applied to the PBI Report “Application of Fertigation”, of the Sugarcane Vertical, to add two new tabs: “Status”, containing status graphs, and the “Status Table” tab, with descriptions of each status. These additions aim to facilitate the identification of inconsistencies in the data and ensure a more accurate analysis.

#### ➤ Status Definitions

In the “Status” tab, each line of data will be classified according to the integration status between the Spool (Hydro Roll) and the Stretcher Tractor. The statuses are:

- Waiting for Processing: When the data from both devices has arrived, but 24 hours have not yet passed since the last data arrived.
- Waiting for Stretcher Tractor Data: The Spool (Hydro Roll) data has arrived, but there are still no records of the Stretcher Tractor.
- Waiting for Spool Data: The data from the Stretcher Tractor has arrived, but there are still no records from the Spool (Hydro Roll).
- Spool Data with No Pressure Value: Spool (Hydro Roll) data has arrived, but the pressure field is zero (0) in all received data.
- Spool Data without Pressure Sensor Registration: Data from both devices is available, but there is no Pressure Sensor registered for the Spool (Hydro Roll).
- Spool Data without Sprinkler Factor Registration: Data from both equipment is available, but there is no Sprinkler Factor registered for the Spool (Hydro Roll).



- Complete: Data has passed all validations and is ready for analysis.





Image 20 – Overview of the new “Status” tab in the “Application of Fertigation” report



CD_ESTICAMENTO	Status Esticamento	Data	Fazenda Trator	Fazenda Hidro	Equipamento Trator	Equipamento Hidro
656.221.004.250.609.00	Aguardando processamento	10/04/2025	571 -	571 -	65622 - TRATOR ESTICADOR ASPERSAO	15141 - CARRETEL ASPI
142.542.804.250.126.00	Aguardando processamento	27/04/2025	2 -	2 -	14254 - TRATOR ESTICADOR ASPERSAO	11836 - CARRETEL ASPI
142.612.804.252.151.00	Aguardando processamento	28/04/2025	2 -	2 -	14261 - TRATOR ESTICADOR ASPERSAO	11249 - CARRETEL ASPI
656.220.105.251.242.00	Aguardando processamento	01/05/2025	83 -	83 -	65622 - TRATOR ESTICADOR ASPERSAO	15029 - CARRETEL ASPI
142.540.405.252.126.00	Aguardando processamento	04/05/2025	9 -	9 -	14254 - TRATOR ESTICADOR ASPERSAO	11329 - CARRETEL ASPI
151.580.405.250.907.00	Aguardando processamento	04/05/2025	2 -	2 -	15158 - TRATOR ESTICADOR ASPERSAO	11204 - CARRETEL ASPI
151.590.405.252.011.00	Aguardando processamento	04/05/2025	5 -	5 -	15159 - TRATOR ESTICADOR ASPERSAO	11255 - CARRETEL ASPI
656.180.405.250.402.00	Aguardando processamento	04/05/2025	575 -	575 -	65618 - TRATOR ESTICADOR ASPERSAO	12143 - CARRETEL ASPI
656.190.405.252.313.00	Aguardando processamento	04/05/2025	546 -	546 -	65619 - TRATOR ESTICADOR ASPERSAO	11750 - CARRETEL ASPI
656.190.505.251.657.00	Aguardando processamento	05/05/2025	575 -	575 -	65619 - TRATOR ESTICADOR ASPERSAO	11762 - CARRETEL ASPI
656.190.505.252.140.00	Aguardando processamento	05/05/2025	575 -	575 -	65619 - TRATOR ESTICADOR ASPERSAO	11829 - CARRETEL ASPI
656.220.505.251.005.00	Aguardando processamento	05/05/2025	518 -	518 -	65622 - TRATOR ESTICADOR ASPERSAO	15140 - CARRETEL ASPI
656.230.505.252.101.00	Aguardando processamento	05/05/2025	546 -	546 -	65623 - TRATOR ESTICADOR ASPERSAO	11750 - CARRETEL ASPI
656.230.505.252.309.00	Aguardando processamento	05/05/2025	546 -	546 -	65623 - TRATOR ESTICADOR ASPERSAO	11749 - CARRETEL ASPI
658.520.505.250.649.00	Aguardando processamento	05/05/2025	540 -	540 -	65852 - TRATOR ESTICADOR ASPERSAO	15027 - CARRETEL ASPI
658.520.505.250.703.00	Aguardando processamento	05/05/2025	540 -	540 -	65852 - TRATOR ESTICADOR ASPERSAO	15146 - CARRETEL ASPI

Image 21 – Overview of the new “Status Table” tab in the “Application of Fertigation” report



Go to Main Menu > Reports > PBI > Application of Fertigation > Status and Status

Table Tabs



Applied on 06/09/2025. Available for Sugarcane Vertical Environments that have the “Sprinkler Fertigation” solution active.

## 1.2 Bugs

### 1.2.1 Maps – Analytical

Adjustment made to the Analytical Map, on “Line” maps, to display only lines with values corresponding to the values selected in the Legend, that is, when selecting and removing intervals in the Legend, the information is updated on the map.



Go to Top menu > Maps > Lines > Legend

### 1.2.2 Modules – Telemetry

Adjustment made in the “Telemetry” module, in the “Group by Equipment Type” view of the dashboard’s home screen, in order to display only equipment configured with the types “1 – Harvester”, “2 – Transshipment” and “40- Light Tire Tractor”. In addition, in the Sensors tab, it was changed to display Hourmeter data with the maximum value.



Go to Top menu > Telemetry > Group by > Equipment Type > Equipment > Equipment > Sensors Tab > Hourmeter



Available for Environments that have the “Telemetry” solution active.

### 1.2.3 PBI Reports – Filters

Adjustment applied to PBI Reports to correctly display data in the “Equipment Group” filter.



Go to Main Menu > Reports > PBI > Filters > Equipment Group



Applied on 06/13/2025.

*In case of doubt or further clarification, please contact us via email  
[suporte@solinftec.com.br](mailto:suporte@solinftec.com.br) or call +55 18 3622 2270*