

Installation Configuration

Installation ID

A required field, to allow quick disambiguation between alternative configurations.

```
id: "soliplex-example"
```



Installation Metaconfiguration

The `meta` section allows you to register custom "kinds" of entities (tool configurations, MCP client toolset configurations, etc.), such that you can use them within your own configurations (e.g., to register a configuration class for use with a custom tool in a given room).

```
meta:
```



See [this page](#) for documentation on the meta-configuration schema.

Secrets

```
secrets:
```



Secrets are values used to authenticate access to different resources or APIs.

The may be kept in an external store, such as:

- ASW secret store
- GitHub secrets
- Docker Compose secrets files
- The user keyring

See [this page](#) for documentation on configuring installation secrets.

Environment

The `environment` section configures non-secret values used by various portions of the Soliplex application. Application code should use the `Installation.get_environment` API to fetch configured values, rather than using `os.environ`.

```
environment:
```

See [this page](#) for documentation on configuring the installation environment.

`haiku.rag` Configuration File

The `haiku_rag_config_file` entry points to a YAML file containing configuration values for the `haiku.rag` client

If not configured explicitly, the installation configuration expects to find this file in the same directory, with the default name `haiku.rag.yaml`.

Please see the `haiku.rag` configuration [docs](#) for details on how to configure the `haiku.rag` client used by Soliplex.

Agent Configurations

An installation can declare agent configurations (which are normally bound to rooms / completions) at the top-level, such that they can be looked up by ID from Python code using `the_installation.get_agent_by_id`.

```
agent_configs:

- id: "ollama_gpt_oss"
  model_name: "gpt-oss:20b"
  system_prompt: |
    You are an expert AI assistant specializing in information retrieval.
    ...
```

Please see [this page](#) for details on configuring agents. In addition to the values described there, note that the `id` element is required here.

OIDC Auth Provider Paths

The `oidc_paths` element specifies one or more filesystem paths to be searched for OIDC provider configs.

Please see [this page](#) for details on how to configure these providers.

```
oidc_paths:
  - "/path/to/oidc/config/dir"
```

Non-absolute paths will be evaluated relative to the installation directory.

By default, Soliplex loads provider configurations found under the path `./oidc`, just as though we had configured:

```
oidc_paths:
  - "./oidc"
```

To disable authentication, list a single, "null" path, e.g.:

```
oidc_paths:
  -
```

Or else run `'soliplex-cli serve --no-auth-mode'`

Room Configuration Paths

The `room_paths` element specify one or more filesystem paths to search for room configs.

Please see [this page](#) for details on how to configure these providers.

Each path can be either:

- a directory containing its own `room_config.yaml` file: this directory will be mapped as a single room.
- a directory whose immediate subdirectories will be treated as rooms IFF they contain a `room_config.yaml` file.

Non-absolute paths are evaluated relative to the installation directory.

The order of `room_paths` in this list controls which room configuration is used for any conflict on room ID: rooms found earlier in the list "win" over later ones with the same ID.

By default, Soliplex loads room configurations found under the path './rooms', just as though we had configured:

```
room_paths:
- "./rooms"
```

To disable all rooms, list a single, "null" path, e.g.:

```
room_paths:
-
```

Completion Configuration Paths

The `completion_paths` entry specifies one or more filesystem paths to search for completion configs.

Please see [this page](#) for details on how to configure these providers.

Each path can be either:

- a directory containing its own `completion_config.yaml` file: this directory will be mapped as a single completion.
- a directory whose immediate subdirectories will be treated as rooms IFF they contain a `room_config.yaml` file.

Non-absolute paths will be evaluated relative to the installation directory.

The order of entries in the `completion_paths` list controls which completion configuration is used for any conflict on completion ID: completions found earlier in the list "win" over later ones with the same ID.

By default, Soliplex loads completion configurations found under the path './completions', just as though we had configured:

```
completion_paths:
- "./completions"
```

To disable all completions, list a single, "null" path, e.g.:

```
completion_paths:
-
```