
From Agents to Coordination Cells: A Practical Agent/Skill Framework for Episode-Driven AI Systems

Subtitle: Artifact Contracts, Deficit-Led Wake-Up, Semantic Bosons, and Dual-Ledger Control



0. Reader Contract and Scope

0.1 Who this article is for

This article is written for AI engineers who already know the practical reality of building agent systems: once a workflow grows beyond a single prompt, the system starts to feel harder to reason about than it should. You may have multiple tools, a planner, a verifier, a retrieval stage, a few specialist prompts, maybe a critic, maybe a memory layer, and yet the whole system still behaves like a pile of half-visible heuristics. The goal here is to offer a cleaner runtime language for that situation. It is aimed at engineers who want systems that are more modular, more inspectable, and more stable than “just add another agent” architectures. The starting point is not metaphysics but runtime design: coordination episodes, skill cells, artifact contracts, deficit-led wake-up, and explicit state accounting.

0.2 What this framework is and is not

This framework is a proposal for how to organize advanced Agent/Skill systems. It is not a claim that we already possess a final theory of AGI. It is not a claim about consciousness. It is not a claim that every useful runtime must literally contain “Bosons” or “semantic fields” as ontological objects. Instead, it is an engineering proposal: use a better unit of decomposition,

use a better clock, and use a better state ledger. The decomposition unit is the **skill cell**. The clock is the **coordination episode**. The ledger is a **dual runtime ledger** that tracks maintained structure, active drive, health gap, structural work, and environmental drift. The article therefore stays at the level of operational architecture and measurable control, not speculative ontology.

0.3 Why the article starts from zero

A common failure mode in technical writing about agent systems is that the vocabulary is introduced too late. People say "agent," "router," "memory," "tool policy," or "planner" as if those units were already natural. In practice they are often not. Different systems use the same word for different things, and different words for the same thing. So this article starts from zero on purpose. It first asks a simpler question: what is the smallest useful runtime unit, what is the natural time variable for coordination, and what should count as the state of the system? Only after those questions are fixed does it become meaningful to talk about agents, skills, wake-up logic, or stability control. The article therefore builds the framework from the bottom up rather than from existing product labels.

0.4 The three claims of the paper

The framework rests on three claims.

First, capability should be decomposed into **skill cells** defined by bounded transformation responsibility rather than vague persona labels. A "research agent" or "debugging agent" is too broad to be the atomic runtime unit. What matters is a repeatable local transformation under a clear contract. The proposed skill-cell schema therefore centers on regime scope, phase role, input artifact contract, output artifact contract, wake mode, deficit conditions, Boson emission/reception, and failure states.

Second, higher-order reasoning should be indexed not primarily by token count or wall-clock time, but by **coordination episodes**. A coordination episode is a variable-duration semantic unit that begins when a meaningful trigger activates local processes and ends when a stable, transferable output is formed. This is a better clock for advanced agent systems because equal numbers of tokens do not correspond to equal amounts of semantic progress, while completed bounded closures often do.

Third, serious agent runtimes need not only orchestration but also accounting. The runtime should declare a maintained structure, a drive that is trying to shape that structure, a health gap between the two, a notion of inertia or mass, a notion of structural work, and an explicit environmental baseline. The dual-ledger view gives exactly that language: body as maintained structure s, soul as drive λ, health as gap G, mass as curvature-derived inertia, work as W_s, and environment as declared baseline q with declared features ϕ.

These three claims can be compressed into the following backbone:

$$x_{n+1} = F(x_n) \quad (0.1)$$

$$S_{k+1} = G(S_k, \Pi_k, \Omega_k) \quad (0.2)$$

$$\Delta W_s(k) = \lambda_k \cdot (s_k - s_{k-1}) \quad (0.3)$$

Equation (0.1) is the ordinary micro-step picture.
Equation (0.2) is the coordination-episode picture.
Equation (0.3) is the per-episode accounting picture.

0.5 The core equations and notation

To keep the article coherent, we fix a minimal notation at the start.

Let n denote a low-level computational step index and k denote a coordination-episode index. Let S_k denote the effective runtime state before episode k. Let Π_k denote the coordination program assembled during that episode: the active skill cells, routes, constraints, and policies. Let Ω_k denote observations encountered during the episode: retrieved evidence, tool outputs, memory fragments, or environment signals. This gives the episode-time update:

$$S_{k+1} = G(S_k, \Pi_k, \Omega_k) \quad (0.4)$$

At the control layer, let s_k denote the maintained runtime structure after episode k, λ_k the active coordination drive during that episode, q the declared baseline environment, and ϕ the declared feature map that specifies what counts as structure. Following the dual-ledger formulation:

$$\text{System} = (X, \mu, q, \varphi) \quad (0.5)$$

$$s(\lambda) = E_{p_\lambda}[\varphi(X)] \quad (0.6)$$

$$G(\lambda,s) = \Phi(s) + \psi(\lambda) - \lambda \cdot s \geq 0 \quad (0.7)$$

$$W_s = \int \lambda \cdot ds \quad (0.8)$$

The interpretation is deliberately practical. s is not "the soul of the machine." It is the maintained runtime structure. λ is not mystical intention. It is the active coordination pressure or drive. G is the measurable misalignment between active drive and maintained structure. W_s is the structural work performed while changing that structure.

The rest of the article explains why these abstractions are worth using in agent engineering.

---

1. Why Today's Agent Stacks Still Feel Ad Hoc

1.1 The hidden cost of "just add another agent"

When an AI workflow fails, one common response is to add another specialized agent. Add a critic. Add a planner. Add a verifier. Add a summarizer. Add a retrieval judge. Add a tool selector. In the short term this often works. In the long term it creates a system whose behavior is increasingly hard to inspect. The surface vocabulary improves faster than the runtime semantics. One ends up with more role names, more prompts, and more edges in the orchestration graph, but not necessarily a better account of why the system moved from one local state to another.

The hidden cost is not just complexity. It is loss of runtime legibility. When a system produces a good answer, it becomes difficult to say which bounded process actually produced the crucial closure. When it fails, it becomes difficult to say whether the failure was wrong routing, missing artifact production, unresolved contradiction, unstable local closure, drift in the operating environment, or simple over-triggering. The result is "agent theater": a system that appears architecturally rich but remains operationally blurry.

1.2 Why role names are too vague

Human naming convenience is not the same thing as runtime factorization. A label like "Research Agent" may hide many fundamentally different sub-capabilities:

- query disambiguation

- evidence retrieval
- source validation
- contradiction detection
- synthesis of findings
- packaging of a transferable artifact

Those are not one capability. They are several different transformations, each with different entry conditions, exit conditions, and failure modes. The same is true for labels like “Debugging Agent,” “Writer Agent,” or “Planner Agent.” These names are useful at the product or team level, but they are too coarse to serve as the atomic units of runtime coordination.

The new framework therefore treats a role name as, at most, a coordination shell. The true reusable unit is the **skill cell**: a bounded transformation whose inputs, outputs, triggers, and failures are explicit. This follows the design direction in the skill-cell and semantic-Boson material, which argues that skills should be decomposed by recurrently stable factorization under regime constraints rather than by naming convenience or arbitrary tool grouping.

1.3 Why prompt-only routing becomes brittle

Most current agent systems route by some mixture of semantic similarity, handcrafted rules, or an LLM-based planner that decides what should happen next. All of these are useful, but they often miss the most important question: **what is missing right now?**

Pure relevance is not enough. A skill can be relevant yet unnecessary. Another skill can be only moderately relevant in semantic space yet absolutely necessary because the current episode cannot advance without the artifact it produces. The semantic-Boson framework makes exactly this point: many current systems look only at relevance and ignore deficit, while wake-up should depend heavily on what the current episode still lacks. Missing required artifacts, high contradiction residue, unresolved uncertainty, blocked phase advancement, and unmet export conditions are stronger wake signals than topical similarity alone.

This distinction matters because routing failure usually happens in one of two forms:

wake_too_early(skill_i) (1.1)

wake_too_late(skill_j) (1.2)

In the first case a skill is triggered because it is semantically nearby, even though the episode is not ready for it. In the second case a skill is not triggered because the system fails to represent deficit pressure explicitly. Relevance-only routing therefore creates both noise and blindness.

1.4 Why chat history is a poor state model

Many production systems implicitly treat chat history as the main state of the runtime. That is convenient, but weak. A long message log mixes together several different categories of information:

- partial artifacts
- failed attempts
- side comments
- control decisions

- tool returns
- user corrections
- already-closed and not-yet-closed material

This is a poor substitute for an explicit runtime state. A history is a record of what happened. A state should say what is currently maintained, what is still unresolved, what phase the system is in, what artifacts are available, and what drives or pressures are active.

The coordination-episode view improves this by defining advancement in terms of bounded semantic closures rather than raw textual continuation. The dual-ledger view improves it further by making the maintained structure explicit as s, the drive explicit as λ, and the environment explicit as q with declared features ϕ. Together they imply that a serious runtime should not rely on history alone. It should maintain a structured state object, even if that object is only approximate.

1.5 The missing unit of coordination

All the above problems point to one deeper absence: the missing unit of coordination. If the runtime unit is too large, everything becomes a vague "agent." If the time unit is too small, everything becomes token churn. If the state unit is too loose, everything becomes message history. The framework proposed here replaces these three weak defaults with three stronger units:

skill cell instead of vague role (1.3)

coordination episode instead of token count (1.4)

maintained structure instead of raw history (1.5)

This is the central reason the article starts by rebuilding vocabulary. Without the correct units, even good tools end up inside an ad hoc operating model.

---

2. The Core Shift: From Roles to Skill Cells

2.1 Why a capability should be defined by transformation, not persona

A capability becomes reusable when it is defined by what it transforms, under what conditions, into what output. That is an engineering definition, not a social one. We do not need the runtime to "feel like" a researcher or a critic. We need it to know:

- what input artifact or state predicate activates the capability
- what output artifact or state change the capability is supposed to produce
- what evidence or constraints it requires
- what failure markers indicate it did not finish correctly

This is why the skill-cell material emphasizes artifact transformation rather than human-style naming. A good decomposition is based on repeated successful factorization patterns under regime constraints, not on generic AI buzzwords.

So the core shift can be written very simply:

Capability = bounded artifact/state transformation (2.1)

not:

Capability ≠ persona label (2.2)

2.2 Skill cell as the minimal runtime unit

A skill cell is the atomic reusable unit of capability in this framework. The minimal schema proposed in the source material includes regime scope, phase role, input artifact contract, output artifact contract, wake mode, required tags, forbidden tags, deficit conditions, emitted Bosons, receptive Bosons, and failure states.

In the more general coordination-episode language, a minimal semantic cell is described by intent, entry conditions, exit criteria, inputs, outputs, tensions, observables, and failure markers:

C = (I, En, Ex, X_in, X_out, T, Σ, F) (2.3)

That is already very close to an implementable skill-cell schema. The important point is not the exact letters but the shape of the object. A cell is not just "something the model can do." It is a bounded local process with a declared activation boundary and a declared export boundary.

A useful engineering restatement is:

Cell_i : (state/artifact predicate) -> (transferable artifact or stabilized local state) (2.4)

This is why the cell is a better primitive than the agent. An agent may contain many such cells. A cell should do one bounded thing well enough that the runtime can reason about when to wake it and how to judge its closure.

2.3 Agent as coordinator, not character

Once the cell is the atomic capability unit, the role of the agent changes. An agent is no longer the thing that "does the work" in a vague anthropomorphic sense. It becomes the thing that coordinates a family of cells inside one regime.

The source material states this directly: an agent should not be a vague persona; it should be a coordinator over a family of cells in one regime. Its main responsibilities are to modulate thresholds, decide phase transitions, resolve collisions, and escalate when needed.

So:

Agent := coordinator over cells (2.5)

A coordinator does not need to know how to perform every transformation itself. It needs to know:

- which cells are eligible
- which deficits are currently dominant
- which Boson-like transients matter, if any
- which phase transitions are legal
- when a local closure is robust enough to export
- when the system should freeze, escalate, or switch modes

This is a much cleaner and more auditable role.

2.4 Regimes, phases, and bounded local responsibility

A cell is not universal across every context. Its behavior depends on regime and phase. A retrieval-verification cell for legal evidence is not the same as a retrieval-verification cell for casual brainstorming. A formatting cell before final export is not the same as a synthesis cell in the middle of evidence assembly. The skill-cell schema therefore includes regime scope and phase role explicitly.

This matters because bounded responsibility is the only way to prevent runaway overlap. If every cell is allowed to respond to every nearby state, the runtime becomes noisy. But if each cell has a declared regime and phase, then eligibility becomes a structured predicate rather than an intuition.

We can write this abstractly as:

eligible_i(k) = E_i(regime_k, phase_k, artifacts_k, tags_k) (2.6)

Only after eligibility is true do we ask whether deficit pressure or Boson resonance should increase the chance of activation.

2.5 What becomes simpler once the unit is fixed

Once the cell is fixed as the atomic unit, several messy engineering problems become clearer.

First, wake-up becomes decomposable. Instead of asking “which agent should talk next?” we ask “which cells are eligible, which deficits are highest, and which transient signals, if any, recruit which cells?” The semantic-Boson framework explicitly recommends this layered wake-up logic: exact skill layer, deficit-based need layer, and optional resonance/coupling layer.

Second, debugging becomes more local. If an output is bad, one can ask whether the wrong cell woke, the right cell woke too late, the input contract was under-satisfied, the output artifact failed validation, or the closure was fragile.

Third, logging becomes more meaningful. Episode logs can be indexed by cell execution and artifact transition rather than only by message count.

Fourth, control becomes possible. A coordinator can adjust thresholds, guardrails, budgets, or phase transitions cell by cell, rather than trying to steer an undifferentiated “agent personality.”

This is why the framework’s decomposition rule is so important:

Decompose skills where successful episodes repeatedly factorize the same way, then build wake-up from exact eligibility, current deficit, and optional resonance signals.

That principle is the bridge from ad hoc orchestration to principled runtime architecture.

These three opening sections establish the full article’s foundation:

- Section 0 fixed the claim level and notation.
- Section 1 explained why current agent stacks remain ad hoc.
- Section 2 introduced the core runtime primitive: the skill cell.

The next natural move is Section 3, where artifact contracts become the real interface language

of the framework.

3. Artifact Contracts as the Real Units of Capability

3.1 Input artifact contract

Once the skill cell is accepted as the atomic runtime unit, the next question becomes unavoidable: what exactly enters a cell, and what exactly leaves it? If that question is answered loosely, the runtime immediately drifts back into prompt theater. If it is answered precisely, the system becomes much easier to test, compose, and debug.

The framework therefore treats an **input artifact contract** as a first-class object. An input artifact contract is not just "some context" or "whatever the previous agent said." It is a declared boundary condition for activation. A cell should know what artifact types, state keys, tags, or predicates must already exist before the cell is allowed to treat the current episode as ready for it. In the source material, this appears in two closely related forms: the semantic tick cell grammar, where a local unit has entry conditions, required inputs, signals, and failure markers, and the skill-cell schema, where each skill cell declares an input artifact contract, required tags, forbidden tags, deficit conditions, and wake mode.

So the minimal engineering principle is:

InputContract_i = {artifact types, state predicates, tags, exclusions} (3.1)

This matters because it makes a wake-up decision testable. Instead of saying "the retrieval agent feels relevant," the runtime can say:

eligible_i(k) = 1 iff InputContract_i is satisfied at episode k (3.2)

That is already a major improvement over chat-history-only routing.

3.2 Output artifact contract

The other half of capability is the **output artifact contract**. A skill cell is only useful if it can export something that another part of the runtime can consume. The export does not have to be a final answer. It can be a shortlist, a contradiction report, a candidate parse, a validation verdict, a risk flag, a repaired schema object, or a folded decision artifact. What matters is that the output has a declared type and declared completion conditions.

The semantic tick material makes this explicit by tying closure to transferable outputs: a local cell is not complete just because tokens were produced. It is complete when a sufficient local convergence condition is reached and the output artifact is transferable.

So:

OutputContract_i = {artifact type, completion criteria, transfer conditions} (3.3)

and the minimal cell-completion primitive can be written as:

$\chi_i(k) = 1$ iff $a_i(k) \geq a_i^*$ and $q_i(k) \geq q_i^*$ and X_{out} is transferable; 0 otherwise (3.4)

This distinction is central. A runtime that cannot distinguish "text was emitted" from "a transferable artifact now exists" will overestimate its own progress.

3.3 Why artifacts are better than vague "tasks"

A vague task label such as “research this topic” hides too many internal transitions. In a real runtime, the phrase may unfold into several distinct artifacts:

- query disambiguation artifact
- retrieval bundle
- evidence ranking artifact
- contradiction map
- synthesis draft
- confidence or fragility report
- final export

These are not interchangeable. Different cells need different subsets, and different failures happen at different boundaries. That is why the skill-cell and decomposition materials emphasize repeated artifact transitions and repeated handoff points as the correct way to discover useful decomposition factors. The proposal is not to decompose by generic role names, but by recurrently stable artifact-transform patterns under regime constraints.

So the practical rule is:

Decompose by repeated artifact transitions, not by broad human task names (3.5)

This is also why artifact contracts improve debuggability. If the output artifact is wrong, the fault can often be localized to one cell or one contract boundary. A vague task label does not give that leverage.

3.4 Transferable closure and exportable state

A coordination episode is valuable only if its local closure can be exported to the next stage. The semantic tick material is very clear on this point: a local process may converge, converge but remain fragile, loop, stall, or collapse into a false local basin. Only some of those conditions produce a genuinely usable output.

This lets us define a stronger notion of progress:

progress_k = exportable_closure_k, not merely local activity_k (3.6)

In other words, an episode is not credited because “reasoning happened.” It is credited because something now exists that can be composed downstream.

This leads to a useful discipline for engineering:

- every cell should declare what counts as “done enough”
- every cell should declare what counts as “transferable”
- every downstream cell should consume declared artifacts, not vague summaries

Without that discipline, the system keeps collapsing back into informal prompting.

3.5 Contract failure as a first-class signal

The most underrated advantage of artifact contracts is that they make failure visible. If a cell

activates too early, that is often an input-contract failure. If it activates and returns something unusable, that is often an output-contract failure. If it remains relevant but never wakes, the problem may be deficit representation or trigger logic. If it wakes repeatedly and still cannot export, the issue may be a convergence or fragility problem rather than a capability problem.

The semantic tick cell framework already names several local failure markers: never activating when needed, activating too early, looping without closure, stabilizing in the wrong basin, producing an unusable output, suppressing relevant alternatives, or exporting something that destabilizes downstream composition.

This can be summarized by:

Failure_i ∈ {inactive-too-long, early, looped, false-closure, unusable-output, downstream-destabilizing} (3.7)

The importance of this section is now clear. Artifact contracts do not just define interfaces. They define the real units of runtime accountability.

---

4. Why Relevance-Only Routing Fails

4.1 The limits of similarity-only wake-up

Many agent systems route by semantic similarity because similarity is easy to compute and often useful. If the current message looks like code, wake the coding skill. If it looks like retrieval, wake the search skill. If it looks like math, wake the calculator chain. This works surprisingly well for small systems. But as coordination depth increases, relevance-only routing starts to miss the real cause of progress or blockage.

The key problem is simple: semantic relevance is not the same as **structural necessity**. A cell may be topically nearby but not required. Another cell may be only weakly similar at the text level yet be absolutely necessary because the current episode cannot close without the artifact it produces.

This is exactly the point made in the semantic-Boson discussion. It states that many current systems ignore deficit and only look at relevance, while wake-up should depend heavily on what the episode still lacks. Required artifacts may be missing, contradiction residue may be high, uncertainty may be high, the phase may be unable to advance, or export conditions may remain unmet. Those are not mere topical cues. They are coordination conditions.

So:

relevance_i(k) ≠ necessity_i(k) (4.1)

4.2 The difference between relevance and necessity

This distinction becomes clearer when we separate three questions.

Question 1: Is this cell semantically related to the current local state?

Question 2: Is this cell eligible under the current contract and regime?

Question 3: Is this cell necessary to reduce the current deficit and permit closure?

These are different filters. The first is about similarity. The second is about contract satisfaction. The third is about current blockage.

A runtime that uses only Question 1 will keep waking cells that “make sense” in topic space while sometimes missing the cell that is actually needed to close the episode. A better architecture therefore layers wake-up.

The source material proposes three layers:

- exact-skill layer
- deficit-based need layer
- resonance / coupling layer

This can be rendered as:

wake_score_i(k) = f_exact_i(k) + f_deficit_i(k) + f_resonance_i(k) (4.2)

with the important design warning that the first two are usually more important than the third.

4.3 Why missingness matters more than topicality

An advanced agent runtime is not trying to mimic human association for its own sake. It is trying to reach bounded closure under constraints. That means that “what is missing” often matters more than “what is nearby.”

Examples:

- If `json_draft` exists but `schema_valid` is absent, a validator may be more necessary than a generative writer.
- If two incompatible evidence artifacts coexist, contradiction arbitration may be more necessary than more retrieval.
- If the phase cannot advance because no exportable summary exists, synthesis may be more necessary than additional brainstorming.

These are deficit conditions, not semantic-nearest-neighbor conditions. The semantic-Boson text gives a direct example: if a JSON draft exists and schema validity is absent, wake the validator candidate set. That is the exact-skill layer. Then, at the deficit layer, wake-up grows stronger when a required artifact is missing, contradiction residue is high, uncertainty is high, phase cannot advance, or export conditions are unmet.

So the runtime should privilege:

missingness_k > mere topicality_k (4.3)

in many routing decisions.

4.4 Routing failure as premature or delayed wake-up

Once routing is framed this way, common coordination failures become easier to describe.

Premature wake-up occurs when a semantically relevant cell is triggered before its required inputs are mature enough. Delayed wake-up occurs when a necessary cell remains dormant because the system only watches topical similarity or recent surface activity.

Using the trigger-routing-convergence-composition view from the coordination-episode framework, one can express this as a failure in the first two runtime mechanics. The framework explicitly notes that trigger can fail by activating the wrong cell, failing to activate a necessary

cell, or activating too many weakly relevant cells, while routing can fail by overcommitting too early, suppressing necessary rival cells, or fragmenting attention across too many candidates.

So routing error is not random. It has a geometry:

routing_error_k = premature_activation_k + missed_necessity_k + weak-cell_overactivation_k (4.4)

This is much more actionable than saying “the planner made a bad choice.”

4.5 Toward a deficit-led runtime

The natural conclusion is not that relevance is useless. Relevance remains a useful soft signal. The conclusion is that relevance should be subordinated to stronger coordination logic. The runtime should first ask:

- which cells are contractually eligible,
- which deficits are active,
- which transient signals, if any, recruit additional support,
- and which set of candidate cells can plausibly produce transferable closure.

The final principle from the decomposition material says this directly: decompose skills where successful episodes repeatedly factorize the same way, then build wake-up from exact eligibility, current deficit, and optional resonance signals.

That is the bridge from fuzzy routing to runtime control.

---

5. Deficit-Led Wake-Up

5.1 Deficit as “what the episode still lacks”

Deficit-led wake-up is the core operational upgrade of this framework. A deficit is not just an error count or a vague feeling that more work is needed. A deficit is a structured statement about why the current episode cannot yet export a stable output.

The semantic-Boson framework phrases this cleanly: the deficit layer answers the question, “What is missing in the episode right now?” It then names the primary cases:

- a required artifact is missing
- contradiction residue is high
- uncertainty is high
- phase cannot advance
- export conditions are unmet

So the basic runtime object is:

D_k = deficit vector at episode k (5.1)

The runtime should not only know what it has. It should know what it still lacks.

5.2 Required artifacts, unmet exit conditions, unresolved contradictions

The most straightforward deficits are contract deficits. A required artifact is absent. An input contract is only partially satisfied. An exit condition is not yet met. Those are strong wake signals because they define blocked progress directly.

But deficits can also be more structural. A contradiction map may exist, but contradiction residue remains too high for export. A candidate answer may exist, but novelty support is weak and fragility is high. A synthesis may exist, but phase transition criteria are still not satisfied.

The coordination-episode framework already describes completion in these terms. A semantic tick completes only if required cells converge, an output artifact is produced, contradiction remains below threshold, and no critical loop-lock dominates.

This suggests a deficit test of the form:

$$D_k = D_{artifact,k} + D_{exit,k} + D_{contradiction,k} + D_{phase,k} + D_{export,k} \quad (5.2)$$

The runtime does not need to pretend these are perfectly commensurable. It only needs to make them visible enough to influence wake-up.

5.3 Deficit markers and closure pressure

Once deficits are explicit, wake-up becomes teleological in a useful sense. The runtime is not simply reacting to the last message. It is moving toward closure by reducing the current deficit pattern.

This is why one can interpret deficit as **closure pressure**. If a phase cannot advance because artifact `X` is missing, the skills most likely to produce `X` should receive stronger activation scores. If contradiction residue remains high, contradiction resolution and arbitration cells should gain weight. If local closure exists but remains fragile, verifier or robustness-improver cells should gain weight.

The source material even names a “Deficit Boson” for this exact case: the signal “I cannot move to the next phase because Artifact X is missing,” which wakes generative or retrieval skills and acts as a primary driver of progress.

A generic scoring form is therefore:

$$a_i(k) = H_i(S_k, D_k, \Omega_k) \quad (5.3)$$

where $a_i(k)$ is the activation pressure for cell i, S_k is the current episode state, D_k is the current deficit vector, and Ω_k contains contextual observations, tool returns, or recent artifacts.

This gives deficit a proper place in the runtime rather than leaving it hidden inside a planner prompt.

5.4 Eligibility, deficit, and wake probability

Deficit-led wake-up should not ignore eligibility. A useful runtime does not wake every possibly relevant cell every time deficit is nonzero. Instead, it applies a staged logic.

First, determine contractual eligibility.

$$eligible_i(k) \in \{0,1\} \quad (5.4)$$

Second, estimate deficit relevance.

$need_i(k) = N_i(D_k)$ (5.5)

Third, optionally include resonance or recent-field excitation when that layer is warranted.

$res_i(k) = R_i(B_k, \Omega_k)$ (5.6)

Then combine them:

$a_i(k) = eligible_i(k) \cdot [\ \alpha_i \cdot need_i(k) + \beta_i \cdot res_i(k) + \gamma_i \cdot base_i(k)\ ]$ (5.7)

This is not a theorem from the source files. It is a practical compilation of their logic into a runtime scoring form. The critical part is the multiplication by eligibility. A deficit should intensify wake-up only among cells that are actually legal candidates under the current regime and contract boundary.

5.5 Why deficit-led routing is more auditable

Deficit-led routing is better not because it sounds more goal-directed, but because it makes coordination decisions explainable. If a cell wakes, the runtime can report:

- which contract conditions were satisfied,
- which deficits were active,
- which Boson-like signal, if any, contributed,
- what output artifact the cell was expected to produce,
- and which failure markers would be watched.

That is much more auditable than “the router judged it relevant.”

It also supports measurable system health. Once deficits are explicit, they can be related to the dual-ledger quantities. A persistent symbolic deficit usually corresponds to a persistent quantitative misalignment between maintained structure and active drive. The dual-ledger paper expresses that misalignment with the health gap:

$G(\lambda,s) = \Phi(s) + \psi(\lambda) - \lambda \cdot s \geq 0$ (5.8)

This suggests a natural engineering bridge:

high symbolic deficit D_k often implies rising quantitative gap G_k (5.9)

The two are not identical. A deficit ledger is a symbolic runtime object; a gap is a quantitative state-space object. But they often point in the same direction. If the system repeatedly cannot export the artifact needed for the current phase, then the active drive is likely outrunning the maintained structure. That is exactly the kind of unhealthy state a dual ledger is meant to make visible.

This is why deficit-led wake-up is the real center of the framework. It is where orchestration begins to turn into control.

These sections now complete the next layer of the article:

- Section 3 fixed artifact contracts as the real interfaces.

- Section 4 explained why relevance-only routing fails.
- Section 5 established deficit-led wake-up as the framework's central activation principle.

The next natural block is **Sections 6–8**: semantic Bosons, coordination episodes as the natural time variable, and the three-layer runtime of micro, meso, and macro ticks.

6. Semantic Bosons as Transient Coordination Signals

6.1 What a Boson means in runtime terms

At this point in the framework, the word "Boson" should be stripped of any mystical weight. The runtime meaning is much narrower and more useful. A Boson is a **transient wake signal** emitted when one local closure changes the semantic field in a way that makes another cell more worth considering. The key phrase is "more worth considering," not "must deterministically activate." Bosons belong to the wake-up layer, not to the worker layer. The source material says this explicitly: in runtime terms, a Boson can be treated as "a transient wake signal emitted when a skill changes the semantic field in a way that makes another skill more relevant."

So the basic runtime definition is:

b_k := transient coordination signal emitted during or after episode k (6.1)

A Boson is therefore not:

- a hidden planner
- a replacement for exact triggers
- a magical force carrier
- a vague metaphor for "context"

It is simply a low-cost, short-lived signal that modifies wake-up pressure among already plausible candidates.

6.2 Why Bosons are useful only in field-dependent wake-up

The source material is also clear that Bosons are **not always needed**. They are most useful where wake-up is not just contractual, but field-dependent. Exact utilities, deterministic tools, strict schema flows, and simple phase transitions often do not need a Boson layer. A direct event or contract trigger is enough. By contrast, Bosons become useful when the runtime must deal with semantic handoff, latent conflict, rival branch recruitment, phase-sensitive wake-up, partial closure, or fragility-driven reactivation.

So the rule is:

use Bosons where direct triggers are insufficient (6.2)

and avoid them where the system can stay exact:

if exact trigger is enough, Boson layer = OFF (6.3)

This design rule is important because otherwise the framework becomes over-decorated. Bosons are a selective mechanism for soft coordination, not a mandatory decoration for every skill.

6.3 Completion, ambiguity, conflict, fragility, and deficit Bosons

The source material proposes a compact and very usable Boson vocabulary. Each Boson type corresponds to a recurring coordination condition.

The five most useful Bosons are:

1. **Completion Boson**
   Emitted when a stable artifact appears.
   Typical effect: excite downstream consumer or exporter cells.

2. **Ambiguity Boson**
   Emitted when a parse, interpretation, or evidence set remains underdetermined.
   Typical effect: excite clarifier, rival-generator, or branch-expander cells.

3. **Conflict Boson**
   Emitted when incompatible artifacts coexist.
   Typical effect: excite contradiction checker, arbitration, or resolution cells.

4. **Fragility Boson**
   Emitted when closure exists but is unstable.
   Typical effect: excite verifier, robustness improver, or confidence repair cells.

5. **Deficit Boson**
   Emitted when the phase cannot advance because a required artifact is missing.
   Typical effect: excite the most likely artifact-producing cell.

A compact engineering notation is:

$b_k \in \{ \text{completion}, \text{ambiguity}, \text{conflict}, \text{fragility}, \text{deficit} \}$ (6.4)

and the effect of Boson emission can be modeled as a local perturbation of wake-up score:

$a_i(k+) = a_i(k) + \rho_i(b_k)$ (6.5)

where $\rho_i(b_k)$ is the sensitivity of cell i to Boson b_k.

This gives you a clean implementation handle. A Boson is not a symbolic flourish. It is a bounded increment to candidate-cell activation pressure.

6.4 Boson emission versus direct deterministic triggers

A useful runtime must clearly distinguish between **contract trigger** and **Boson excitation**. The first says a cell can legally be considered. The second says some recent event makes the cell more worth scoring highly.

So the proper control order is:

$\text{eligible}_i(k) \rightarrow \text{scored}_i(k) \rightarrow \text{activated}_i(k)$ (6.6)

where Bosons only affect the middle step.

More explicitly:

$\text{eligible}_i(k) = E_i(S_k)$ (6.7)

$\text{score}_i(k) = \alpha_i \cdot \text{need}_i(k) + \beta_i \cdot \text{res}_i(k) + \gamma_i \cdot \text{base}_i(k)$ (6.8)

$\text{res}_i(k) = R_i(B_k, \Omega_k)$ (6.9)

Here:

- `E_i` is contractual eligibility
- `need_i` is deficit relevance
- `res_i` is Boson-sensitive resonance
- `base_i` is any residual heuristic or prior score

This ordering prevents Bosons from turning into uncontrolled chaos. They are allowed to shape competition among eligible cells, not override hard constraints.

6.5 Keeping the Boson layer simple and non-mystical

The best practical discipline is to keep Bosons lightweight, typed, and short-lived. They should be:

- sparse
- semantically interpretable
- attached to concrete local changes
- decaying over time unless reinforced
- logged as part of the coordination trace

A simple decay rule is:

$w_b(k+1) = \eta_b \cdot w_b(k) + emit_b(k)$, with $0 \le \eta_b < 1$ (6.10)

where `w_b` is the current wake influence of Boson type `b`.

This means Bosons can recruit nearby cells for a short window without permanently distorting routing. They become part of local coordination memory, not permanent architecture.

The conceptual payoff is large. Bosons let the runtime represent a class of wake-up phenomena that are real in practice but awkward in simpler systems: one episode settles, and the settlement naturally recruits a next class of operations, not because the next class is topically nearest, but because the field has changed. That is exactly where Bosons belong.

---

7. Coordination Episodes as the Natural Time Variable

7.1 Why token-time is the wrong clock for high-order coordination

Modern LLM systems expose token-time naturally. At the substrate level, they are stepwise update machines:

$x_{n+1} = F(x_n)$ (7.1)

or, in hidden-state language,

$h_{n+1} = T(h_n, x_n)$ (7.2)

That micro-step view is real and indispensable. It is the right layer for mechanistic analysis,

latency profiling, and low-level decoding logic. But the coordination-episode framework argues that token-time is often the wrong explanatory clock for higher-order reasoning. Many tokens may simply elaborate a closure that was already formed earlier. Conversely, a crucial semantic reorganization may happen in a short bounded process whose importance is not proportional to token count. A system may emit many tokens while making no meaningful progress, or complete a crucial semantic reorganization in a short compact episode.

So the critique is:

n ≠ natural semantic clock for high-order coordination (7.3)

Token-time is real, but it is often too fine-grained to express what counts as one meaningful local or global semantic move.

7.2 Episode-time as closure-defined time

The alternative is **episode-time**. A coordination episode is a variable-duration semantic unit that begins when a meaningful trigger activates one or more local reasoning processes and ends when a stable, transferable output is formed. The source text states this very sharply: a coordination-episode tick is the minimal variable-duration unit of semantically meaningful closure, and therefore the natural time variable for higher-order AI reasoning.

So the higher-order state update is:

$S_{(k+1)} = G(S_k, \Pi_k, \Omega_k)$ (7.4)

where:

- k indexes completed coordination episodes
- S_k is the semantic/runtime state before episode k
- Π_k is the active coordination program during the episode
- Ω_k is the set of encountered observations, tool returns, retrieved evidence, or local perturbations

The important thing is that:

$\Delta t_k \neq$ constant (7.5)

Episode-time is not a metronome. It is a closure-based index. One episode may take a few seconds and another much longer, but each counts as one bounded semantic push if each reaches transferable closure.

7.3 The definition of a coordination episode

A good episode definition must be functional, not poetic. The source material defines the minimal semantic tick cell as a bounded local unit with intent, entry conditions, exit criteria, inputs, outputs, tensions, observables, and failure markers.

So a coordination episode can be described as one bounded process such that:

- some meaningful trigger activates one or more cells
- these cells operate under local tensions and constraints
- a convergence condition is reached, or a recognized failure state is entered

- a transferable artifact or usable local state is exported

This gives the completion primitive:

$\chi_k = 1$ iff episode k reaches transferable closure; 0 otherwise (7.6)

This also means that not every visible response block contains exactly one episode, and not every episode maps neatly onto one tool call, one paragraph, or one prompt. The source material emphasizes this strongly: fixed event counts such as "one tool call = one tick" are often wrong because several tool calls may belong to one semantic episode, while one tool result may end one episode and start another.

7.4 Why equal episode counts are better than equal seconds

The right time variable for a process is the one whose equal increments correspond, at least approximately, to comparable units of advancement. For higher-order coordination, episode-time satisfies this better than either token count or wall-clock time.

The coordination-episode material puts the point this way: if the real object of study is local stabilization, reasoning closure, basin competition, and coordination success or failure, then the time variable should be indexed by episode completion rather than low-level event count.

So the relevant progress increment is:

$\Delta P_k = P_{(k+1)} - P_k$ (7.7)

where P_k is semantic progress measured at episode index k, not token index n.

This matters because:

- a process noisy in token-time may become structured in episode-time
- a final failure may be traceable to an earlier failed episode closure
- a hidden loop may become visible only once segmented as repeated failed meso episodes

This is why the framework shifts the analysis from "what token came next?" to "what episode just completed, what local basin stabilized, and what transferable artifact did that closure produce?"

7.5 From micro updates to semantic ticks

The correct conclusion is not to abolish micro-time. It is to embed it. Episode-time is a coarse-graining of lower-level dynamics according to meaningful closure rules. The source text makes this explicit with coarse-graining operators:

$\text{meso_tick}_k = Cg_{\text{micro}\to\text{meso}}(\{\text{micro steps}\}_k)$ (7.8)

$\text{macro_tick}_K = Cg_{\text{meso}\to\text{macro}}(\{\text{meso ticks}\}_K)$ (7.9)

This means that semantic-time is not a denial of substrate updates. It is a more appropriate explanatory layer for the kinds of reasoning questions engineers actually care about once systems become agentic.

---

8. The Three-Layer Runtime: Micro, Meso, Macro

8.1 Micro-ticks: low-level generation and tool operations

The three-layer hierarchy exists because different runtime questions live at different scales. The source material explicitly defines a three-layer tick hierarchy: micro, meso, and macro.

A **micro tick** is the smallest explicit update unit exposed by the implementation. In a conventional autoregressive LLM this is the next-token or hidden-state update step:

$$h_{n+1} = T(h_n, x_n) \quad (8.1)$$

Micro ticks are indispensable for:

- mechanistic interpretability
- local inference profiling
- latency measurement
- decoder control
- tool-call internals
- strict format generation

But micro ticks have a well-defined limitation: many micro ticks belong to the same local semantic organization. A long verbal elaboration may contain dozens of micro ticks while corresponding to only one meaningful local stabilization. So micro time is substrate time, not always semantic time.

8.2 Meso-ticks: local coordination episodes

A **meso tick** is the first genuinely semantic tick. It corresponds to one bounded local reasoning episode: a contradiction resolution attempt, a retrieval-and-validation episode, a branch arbitration, a local reframing, a short reflection loop, or a bounded subgoal closure. The source text defines it as the level where local triggers, local convergence, local artifacts, local fragility, local basin lock, and local transfer become operationally sharp.

A meso update law can therefore be written as:

$$M_{k+1} = \Phi(M_k, A_k, R_k) \quad (8.2)$$

where:

- M_k is the meso-level semantic state
- A_k is the active local process set during meso episode k
- R_k is the set of relevant observations or tool returns encountered inside that episode

For this article's engineering language, the meso level is where the skill-cell framework becomes most useful. Each cell activation-and-closure is a meso-scale event.

8.3 Macro-ticks: multi-cell campaigns and larger closures

A **macro tick** is a larger coordination push composed of many meso ticks. It corresponds to a materially meaningful change in the global problem state: a full planning cycle, a multi-tool problem-solving attempt, a multi-agent negotiation round, a long-form revision campaign, or a full task decomposition-and-composition pass.

The macro update law is:

$S_{K+1} = \Psi(S_K, \{M_k\}_{k \in \text{episode}}, C_K)$ (8.3)

where:

- S_K is the global state after macro episode K
- $\{M_k\}$ is the ordered set of meso ticks inside macro episode K
- C_K is the higher-order context, policies, or constraints governing the whole macro push

A macro tick may contain dozens or hundreds of micro ticks and several meso ticks. Yet from the perspective of the overall task, it counts as one coherent semantic advance. That is why macro time matters for advanced agent systems with planning, memory, multi-tool interaction, or multi-agent coordination.

8.4 Temporal layering in real systems

The hierarchy is not competitive. It is nested. The source material says this explicitly:

micro ticks build meso ticks, and meso ticks build macro ticks (8.4)

Each layer answers different questions:

- Micro level: how is the computational substrate updating?
- Meso level: which local semantic episode just triggered, stabilized, and exported an output?
- Macro level: which larger coordination push just altered the global task state?

This layering also explains why attractor analysis often feels incomplete when done only at token level. Token-space reveals motion, but not necessarily the true semantic basins of interest. At the meso level one begins to see local attractor episodes. At the macro level one begins to see whole reasoning campaigns.

8.5 Why most agent engineering should live at the meso layer

For most practical agent engineering, the meso layer is the sweet spot. It is high enough to talk about closure, routing, artifacts, contradictions, and phase transitions. It is low enough to remain local, bounded, and loggable. Micro is often too fine-grained. Macro is often too overlapping and task-specific for first implementation.

This suggests a default design recommendation:

default runtime engineering layer = meso (8.5)

Use micro only when you need mechanistic or decoder control. Use macro when orchestrating whole campaigns, memory regimes, or cross-agent coordination. But design the reusable runtime grammar at the meso level: skill cells, contracts, deficits, Bosons, episode completion, outcome taxonomy, and ledger updates.

This is also where the dual-ledger layer snaps into place most naturally. The dual-ledger paper gives a per-tick accounting form:

$\Delta W_s(k) = \lambda_k \cdot (s_k - s_{k-1})$ (8.6)

That equation becomes most meaningful when k is a meso episode index rather than a raw token index. At meso scale, a step in s corresponds to a real bounded semantic change, and the work term reflects a real coordination push rather than surface language churn.

A full episode-level telemetry row can then be organized around:

$$\text{tick}_k = \{ s_k, \lambda_k, G_k, \kappa(I_k), \text{gate_flags}_k, \Delta W_s(k), \text{env_sentinels}_k \} \quad (8.7)$$

That is where orchestration starts becoming runtime physics rather than runtime theater.

These sections now establish the next major block of the article:

- Section 6 defined semantic Bosons as transient wake signals.
- Section 7 established coordination episodes as the natural higher-order clock.
- Section 8 built the micro/meso/macro temporal hierarchy and located most practical agent engineering at the meso layer.

The next natural block is **Sections 9–11**: the full skill-cell schema, the agent as coordinator, and the runtime state model of structure, drive, and alignment.

9. The Skill Cell Schema

9.1 Regime scope

A skill cell is not a free-floating capability that should wake everywhere. It always belongs to a regime. The regime may be defined by domain, safety level, task family, artifact graph, or operating mode. The source material repeatedly stresses this point: decomposition should not be done in a regime-free way. The same apparent skill factor can behave very differently across domains, and a useful cell must declare its scope explicitly. A cell that is valuable in a legal evidence workflow may be dangerous in a casual brainstorming workflow; a strict schema validator that is essential in a production API pipeline may be unnecessary in an informal note-taking assistant. This is why the proposed skill-cell schema includes regime scope as a first-class field.

So the first schema field is:

$$R_i := \text{regime scope of cell } i \quad (9.1)$$

A cell is therefore not just “available.” It is available under declared runtime conditions. This makes eligibility computation tractable and prevents a system from becoming a global soup of overly generic capabilities.

9.2 Phase role

A regime alone is not enough. Many cells are phase-sensitive. A retrieval cell in the evidence assembly phase is not the same as a retrieval cell in the late-stage robustness check phase. A synthesis cell at the point of evidence folding is not the same as a synthesis cell at the point of final export. The source material explicitly recommends including phase role in the cell definition, because higher-order coordination is not just about what cell exists, but when in the local cycle that cell should be relevant.

So we introduce:

$$P_i := \text{phase role of cell } i \quad (9.2)$$

A simple engineering interpretation is:

$P_i \in \{$ assemble, validate, arbitrate, synthesize, export, repair, escalate $\}$ (9.3)

The exact labels will vary by application, but the principle is constant. A skill cell does not merely say “what I do.” It also says “when in the local coordination cycle I am supposed to matter.”

This also makes it possible to express phase-sensitive routing:

$\text{eligible}_i(k) = 1$ only if $\text{phase}_k \in P_i$ and $\text{regime}_k \in R_i$ (9.4)

That single constraint often removes a surprising amount of runtime noise.

9.3 Input and output artifact contracts

The two most important schema fields remain the artifact contracts. As argued in Section 3, the input artifact contract defines what must already be present or true before a cell can treat the current episode as ready for it, while the output artifact contract defines what the cell is responsible for exporting if it completes successfully. The source material’s skill-cell and semantic-tick formulations strongly support this architecture: a bounded local process should always be defined in terms of entry conditions, required inputs, exit criteria, and transferable outputs.

So:

$In_i :=$ input artifact contract of cell i (9.5)

$Out_i :=$ output artifact contract of cell i (9.6)

The pair `(In_i, Out_i)` is the cell’s real runtime signature. It is more stable and more reusable than a role label.

A useful engineering reading is:

$\text{Cell}_i : In_i \to Out_i$ (9.7)

This notation is deliberately simple. It says that a skill cell should be understandable as a bounded transformation from one declared artifact boundary to another.

9.4 Wake mode: exact / hybrid / semantic

The source material proposes a particularly practical wake taxonomy:

- **exact**
- **hybrid**
- **semantic**

These three modes capture an important engineering reality. Not every cell should be triggered in the same way.

An **exact** wake mode means the cell is activated by a sharp, checkable predicate. Example: a `json_draft` exists and `schema_valid` does not. This is the best mode when the input contract is easy to evaluate and the runtime should remain tight.

A **hybrid** wake mode combines hard conditions with a softer score. Example: a contradiction map exists, two evidence bundles disagree, and the contradiction residue exceeds a threshold;

then a semantic relevance score ranks candidate arbitration cells.

A **semantic** wake mode is used where exact predicates are insufficient and the field must be interpreted more softly. This is where Bosons and resonance pressure become most relevant, though still under constraints.

So we define:

$W_i \in \{ \text{exact}, \text{hybrid}, \text{semantic} \}$ (9.8)

The runtime benefit of this field is large. It lets different cells live at different points on the precision–flexibility spectrum without collapsing the whole system into one uniform trigger logic.

9.5 Required tags and forbidden tags

A good runtime does not only know what a cell can do. It knows under what annotations or local markers the cell should or should not be considered. This is why the source material includes required and forbidden tag sets as part of the skill-cell schema.

So let:

$T_i^{(+)}$:= required tags for cell i (9.9)

$T_i^{(-)}$:= forbidden tags for cell i (9.10)

Tags are useful because they compress recurring runtime facts that may not deserve a whole artifact object. Examples include:

- `needs_grounding`
- `high_uncertainty`
- `schema_sensitive`
- `fragile_closure`
- `safety_restricted`
- `do_not_expand`
- `export_blocked`
- `human_review_required`

Then eligibility can be refined as:

$\text{eligible}_i(k) = 1$ iff $T_i^{(+)} \subseteq \text{Tags}_k$ and $T_i^{(-)} \cap \text{Tags}_k = \emptyset$ (9.11)

This keeps routing explainable. The runtime can say not only that a cell was in scope, but also that certain required local conditions were present and certain excluded conditions were absent.

9.6 Deficit conditions

A cell should not merely declare what it consumes and emits. It should also declare what kinds of deficit it is designed to reduce. This is the central link between the schema and the deficit-led wake-up logic of Section 5. The source material explicitly recommends attaching deficit conditions to skill cells, because deficit is one of the strongest activation drivers in advanced coordination systems.

So:

D_i := deficit conditions that cell i is able to reduce (9.12)

Examples:

- missing required artifact `x`
- unresolved contradiction
- insufficient confidence for export
- no valid schema object yet
- phase blocked by absent summary
- local closure too fragile for transfer

Then the runtime can compute not only general deficit pressure, but **deficit compatibility**:

need_i(k) = Compat(D_k, D_i) (9.13)

where `D_k` is the current deficit vector and `Compat` is any runtime-specific compatibility function.

This is one of the clearest ways to make routing more purposeful than similarity-only systems.

9.7 Emitted Bosons and receptive Bosons

The source material also includes Boson emission and reception as explicit cell fields. A cell is allowed to declare not only what it does, but which coordination signals it typically emits when it stabilizes or fails, and which signals make it more likely to wake.

So:

B_i^(emit) := Boson types emitted by cell i (9.14)

B_i^(recv) := Boson types cell i is sensitive to (9.15)

This matters because it gives the Boson layer a typed topology. Bosons are no longer generic "context ripples." They become typed wake relations between classes of cells.

A simple runtime rule is:

res_i(k) = Σ_(b ∈ B_i^(recv)) ρ_i(b) · w_b(k) (9.16)

where `w_b(k)` is the current decayed intensity of Boson `b`.

This is a clean place to stop the Boson layer from becoming vague. The relation is declared, typed, and local.

9.8 Failure states and recovery paths

The final schema field is the failure layer. The source material emphasizes that a semantic cell should declare failure markers rather than hiding all non-success outcomes under one generic "did not work" label. Examples include failing to activate when needed, activating too early, looping, stabilizing in the wrong basin, producing an unusable output, or destabilizing downstream composition.

So:

F_i := declared failure states for cell i (9.17)

and, ideally:

Rec_i := recovery paths for each major failure state (9.18)

This is what lets the runtime distinguish between:

- retry the same cell
- call a repair cell
- escalate to arbitration
- roll back
- lower confidence and continue
- enter quarantine or human-review mode

Putting all fields together, the full compact skill-cell schema can be written as:

$Cell_i = (R_i, P_i, In_i, Out_i, W_i, T_i^{(+)}, T_i^{(-)}, D_i, B_i^{(emit)}, B_i^{(recv)}, F_i, Rec_i)$ (9.19)

This is the true atomic runtime unit of the framework.

---

10. The Agent as Coordinator

10.1 Arbitration over multiple candidate cells

Once the runtime is composed of cells rather than vague agents, the main job of the agent is arbitration. At any given episode, several cells may be simultaneously eligible. The runtime therefore needs a policy for selecting among them or activating a bounded subset.

Let the candidate set be:

$C_k = \{ i : eligible_i(k) = 1 \}$ (10.1)

The coordinator then computes a score for each candidate using deficit, resonance, and any residual priors or heuristics:

$score_i(k) = \alpha_i \cdot need_i(k) + \beta_i \cdot res_i(k) + \gamma_i \cdot base_i(k)$ (10.2)

The activated set is then:

$A_k \subseteq C_k$ (10.3)

subject to coordination policy, cost constraints, phase rules, and conflict handling.

This is where the agent becomes essential. A cell does not know the whole competitive field. The coordinator does.

10.2 Thresholds, gates, and escalation logic

The source material says the agent should modulate thresholds, decide phase transitions, resolve collisions, and escalate when needed. This is one of the strongest and most useful statements in the whole framework, because it strips the agent of vague personhood and gives it a concrete governance role.

So the agent's policy object can be written as:

AgentPolicy_k = (Θ_k, Γ_k, Esc_k, Φtrans_k) (10.4)

where:

- `Θ_k` are current wake thresholds and budgets
- `Γ_k` are hard gates and guardrails
- `Esc_k` are escalation rules
- `Φtrans_k` are legal phase-transition rules

Then the coordinator chooses:

A_k = Select(C_k, score_k, Θ_k, Γ_k, Esc_k, Φtrans_k) (10.5)

The important thing is that the agent does not perform all capability transformations directly. It governs which local bounded transformations may proceed and under what controls.

10.3 Why one giant planner is often the wrong architecture

A common alternative is one central planner prompt that looks at the whole situation and decides what should happen next. This can work for small systems, but it tends to become brittle as the number of tools, states, and artifacts grows. The reasons are familiar:

- the planner becomes a bottleneck
- its decisions are hard to replay precisely
- its internal notion of state is often textually implicit
- local deterministic triggers get overshadowed by expensive global reasoning
- small changes in context can produce unstable rerouting

The source material repeatedly recommends using cheap exact triggers and local sensitivity first, and only using more semantic routing where needed. It also warns against collapsing everything into one vague planning authority.

So the framework's recommendation is:

Prefer layered coordination over monolithic global planning (10.6)

This does not prohibit global planning. It demotes it to one control resource among others.

10.4 Cheap local triggers before expensive LLM routing

A healthy runtime should check cheap information first. Exact contract satisfaction, tag conditions, deficit markers, and gate lamps are all cheaper and more auditable than invoking a large model to reinterpret the entire current state from scratch.

So the control order becomes:

1. evaluate exact eligibility
2. evaluate hard exclusions and gates
3. compute deficit compatibility
4. apply Boson-sensitive resonance if enabled
5. use semantic ranking only among surviving candidates
6. activate a bounded subset

This can be compressed as:

exact -> gated -> deficit-scored -> resonance-adjusted -> semantic-ranked (10.7)

This ordering is not merely an optimization trick. It is one of the framework's central engineering claims. It keeps the system from confusing "hard local facts" with "soft global interpretation."

10.5 Coordinator responsibilities in a production runtime

In production terms, the agent as coordinator is responsible for five things.

First, **cell arbitration**: choosing which cells run now, which are deferred, and which are suppressed.

Second, **phase governance**: ensuring that local closures occur in a legal and meaningful order.

Third, **stability control**: preventing oscillatory routing, runaway Boson excitation, or repeated fragile closure without repair.

Fourth, **safety and constraint enforcement**: making sure hard gates remain non-negotiable.

Fifth, **logging and replayability**: recording which candidates existed, why one set won, what deficits were active, and which gates were binding.

That whole bundle is more precise than "the agent thinks about what to do next." It is a runtime governance function.

---

11. Runtime State: Structure, Drive, and Alignment

11.1 Compiling artifact state into a maintained structure s

Up to now, the framework has talked about artifacts, deficits, Bosons, and episodes. To control the runtime quantitatively, these need to be compiled into a maintained state. This is where the dual-ledger framework becomes essential. It provides a language for turning the current maintained order of the system into a state variable s, given a declared environment baseline q and a declared feature map ϕ. The source paper defines the body as the maintained structure s, the environment as the baseline q, and the features ϕ as the declared measurements of structure.

So in the fused agent runtime:

s_k := maintained runtime structure after episode k (11.1)

This s_k is not meant to be mysterious. It is the current measurable summary of:

- which artifact types exist
- which contracts are satisfied
- which contradictions remain
- which confidence or fragility levels hold
- which route or phase conditions are active
- which export conditions are met

The exact feature map will differ across systems, but the architecture is the same. A runtime that wants to be stable should not only store history. It should maintain a state summary that reflects what is currently being held together.

11.2 Compiling coordination pressure into a drive λ

The dual-ledger framework defines the "soul" as the drive λ that selects which structure to maintain, together with a budget function $\psi(\lambda)$.

In the agent-runtime compilation, the natural counterpart is:

λ_k := active coordination drive during episode k (11.2)

This can include:

- phase pressure
- urgency of missing artifact closure
- routing preference weights
- export pressure
- caution pressure under fragility
- escalation pressure under repeated failure

So λ_k is not a hidden intention in a philosophical sense. It is the runtime's current directional pressure over what kind of structure it is trying to stabilize next.

A useful shorthand is:

drive_k = policy-conditioned deficit pressure over structure space (11.3)

This is what makes the dual-ledger fusion so valuable. It lets the runtime distinguish between what it has (s_k) and what it is currently trying to stabilize (λ_k).

11.3 The environment baseline q and feature map φ

A major contribution of the dual-ledger view is that it forces the environment to be declared rather than assumed. The source text is very explicit: a system becomes operationally analyzable only once it declares a baseline environment and a feature map for what counts as structure.

So the runtime must declare:

System = (X, μ, q, φ) (11.4)

where:

- x is the world of runtime events, artifacts, and observations
- q is the baseline environment or normal operating distribution
- ϕ is the declared feature map over structure-relevant measurements

In an agent system, q may encode the normal distribution of tasks, tool returns, or environment conditions. ϕ may encode artifact counts, contradiction scores, confidence fields, validation status, phase completeness, or other state summaries.

This declaration matters because it turns "drift" into something measurable rather than intuitive. It also makes state design explicit. You cannot stabilize what you never formally defined.

11.4 Health as alignment between maintained structure and active drive

Once s and λ are defined, the dual-ledger framework provides the health gap:

$G(\lambda,s) = \Phi(s) + \psi(\lambda) - \lambda \cdot s \geq 0$ (11.5)

The source text interprets this gap as misalignment: small G means the drive and the maintained structure are aligned, while rising G means the drive wants more or different structure than the current system is sustaining.

In the agent-runtime setting, this is exactly what we need. Many runtime failures are not simple execution failures. They are misalignment failures:

- the coordinator is pushing toward export, but the artifact graph is not ready
- the runtime wants to close the phase, but contradiction residue remains too high
- the system is trying to be confident, but supporting structure is still weak
- the environment has drifted, but the runtime is still using old assumptions

So:

G_k := runtime health gap after episode k (11.6)

A low G_k means the current drive and current maintained structure are well matched. A rising G_k means the runtime is operating with increasing strain.

This lets the framework talk about health in a much more concrete way than "the system seems unstable."

11.5 Symbolic deficit versus quantitative gap

The most important bridge in this whole section is the distinction between **symbolic deficit** and **quantitative gap**.

The symbolic deficit ledger says:

D_k = what the episode still lacks (11.7)

The quantitative health gap says:

G_k = how misaligned current drive and maintained structure are (11.8)

These are not the same object. A deficit is symbolic and local to coordination logic. A gap is quantitative and global to state accounting. But in practice they are deeply related.

If the same artifact remains missing across episodes, then symbolic deficit remains high. If the runtime continues to push toward closure or export anyway, then the active drive λ_k will increasingly outrun the maintained structure s_k, and G_k should rise. Likewise, if contradiction residue is never reduced, the runtime may keep activating synthesis or export pressure without the underlying structure becoming safe enough for those phases.

So the fused view is:

persistent D_k often induces rising G_k (11.9)

This is one of the framework's strongest design advantages. It connects orchestration logic with system health. The runtime does not merely know that a required artifact is absent. It can also know that the absence is now becoming a global misalignment problem.

That is the point where agent design becomes measurable control rather than just clever orchestration.

These sections now complete the next major structural block of the article:

- Section 9 defined the full skill-cell schema.
- Section 10 redefined the agent as a coordinator rather than a persona.
- Section 11 introduced the measurable runtime state model of structure, drive, and alignment.

The next natural block is **Sections 12–14**: the dual ledger for agent systems, runtime mass and brittleness, and environment/drift handling.

12. The Dual Ledger for Agent Systems

12.1 The health ledger

The previous sections gave the framework a coordination grammar: skill cells, artifact contracts, deficit-led wake-up, Boson-sensitive recruitment, and coordination episodes as the natural time variable. That is enough to describe how an advanced agent runtime is organized. It is not yet enough to measure whether the runtime is healthy.

This is where the dual-ledger layer becomes necessary. The source text proposes a compact language in which any complex system can be described by a maintained structure, a drive that pays to maintain that structure, an environment baseline, and a small set of conservation-like quantities. It explicitly defines two ledgers: an alignment or health ledger, and an energy–information or work ledger.

In the fused Agent/Skill framework, the health ledger is the layer that tracks whether the runtime's active coordination drive matches the structure it is actually maintaining. The central scalar is the gap:

$G(\lambda,s) = \Phi(s) + \psi(\lambda) - \lambda \cdot s \geq 0$ (12.1)

The interpretation is simple and operational. If `G` is small, the current drive and the current maintained structure are aligned. If `G` rises, the runtime is pushing toward states it is not yet structurally able to sustain. The source paper says this directly: small gap means aligned and healthy, while rising gap warns of drift and collapse risk.

In agent-runtime language, that means:

- the coordinator may be trying to close a phase too early
- export pressure may be rising while contradiction residue remains high
- validation pressure may be too weak for the fragility level
- the system may be carrying old assumptions into a drifted environment

So the health ledger gives the runtime a measurable version of something engineers already feel intuitively:

runtime strain_k ≈ rising G_k (12.2)

This is one of the biggest conceptual upgrades of the framework. A system no longer merely "feels brittle." It can register misalignment as a real runtime quantity.

12.2 The work ledger

The second ledger tracks what the runtime spent in order to move from one maintained structure to another. The source paper defines structural work as a line integral:

W_s = ∫ λ · ds (12.3)

and gives the per-tick increment form:

ΔW_s(k) = λ_k · (s_k − s_(k−1)) (12.4)

In the context of coordination episodes, this becomes immediately useful. One episode is no longer just "some reasoning happened." It is a bounded push that changed the maintained artifact-state and therefore incurred structural work.

That makes `ΔW_s(k)` the natural per-episode spend metric of the runtime.

In plain engineering terms, the work ledger answers questions like:

- how hard did the runtime push to achieve this local closure?
- did a large coordination effort produce only a tiny usable state change?
- are some parts of the runtime repeatedly spending work without moving structure enough?
- which episode classes are expensive but low-yield?

This is not just abstract accounting. It lets a team identify coordination waste, just as a production system identifies latency waste or compute waste.

12.3 Gap, margin, and drift alarms

A practical runtime needs not only a gap number but also gates and alarms. The source text gives exactly that language: a margin gate, a curvature gate, and a drift alarm, together with green/yellow/red regime logic and explicit default actions.

The most important gates are:

$g(\lambda;s) = \lambda \cdot s - \psi(\lambda) \geq \tau_1$ (12.5)

$\kappa(I) \leq \tau_3$ (12.6)

$d\hat{G}/dt \leq \gamma$ over a stability window (12.7)

These are useful even if implemented approximately. Equation (12.5) is a margin condition: the drive must be able to support the current structure with enough margin to justify action. Equation (12.6) is a curvature or conditioning gate: the local geometry of the runtime should not be too ill-conditioned. Equation (12.7) is a drift alarm on the smoothed gap: if health keeps worsening over a sequence of episodes, the system should stop pretending everything is fine.

This yields a minimal runtime lamp:

$\text{health_lamp}_k \in \{ \text{green}, \text{yellow}, \text{red} \}$ (12.8)

A green state means the runtime can proceed normally. A yellow state means one important quantity is near the boundary. A red state means the runtime should slow down, repair, or freeze before continuing.

12.4 Structural work per episode

Once k is treated as a coordination-episode index, the work ledger becomes much more meaningful than it would be at token scale. Token-level changes are often dominated by surface elaboration. Episode-level changes correspond to local closure, rivalry resolution, phase repair, validation success, or other bounded semantic acts. That is why the per-episode increment

$\Delta W_s(k) = \lambda_k \cdot (s_k - s_{(k-1)})$ (12.9)

is the right default runtime unit.

One can immediately derive several useful metrics:

$W_s(K) = \Sigma_{(k=1..K)} \Delta W_s(k)$ (12.10)

$\text{efficiency}_k = \text{useful_export_gain}_k / \max(\varepsilon, \Delta W_s(k))$ (12.11)

$\text{waste}_k = \Delta W_s(k)$ with low exportability or rising G_k (12.12)

These are engineering extensions rather than equations copied from the source paper, but they follow naturally from the source ledger logic.

In practice, a system may show several unhealthy patterns:

- high $\Delta W_s(k)$ with little improvement in transferable artifacts
- repeated positive work on the same blocked phase
- work rising while G_k also rises
- repeated work on fragile closure that later collapses

Those patterns are exactly the kinds of runtime pathologies that ordinary prompt orchestration hides.

12.5 Why an agent runtime needs accounting, not just orchestration

The deep point of the dual ledger is that orchestration alone is not enough. A system can have elegant cell decomposition and still remain operationally opaque if it cannot answer:

- what structure am I currently maintaining?
- what drive is currently active?
- how aligned are those two?
- how much work did the last episode spend?
- is the system becoming heavier, drifted, or unstable?

The source paper's opening claim is therefore highly relevant here: body, soul, health, mass, work, and environment are not metaphysical ornaments but quantities that can be logged, forecast, and falsified.

In the fused framework, this becomes:

coordination grammar + dual ledger = runtime you can both run and govern (12.13)

Without the ledger, the framework remains architecturally elegant but only partially controllable. With the ledger, it becomes a proper engineering runtime.

---

13. Mass, Rigidity, and Runtime Brittleness

13.1 Structural mass as resistance to changing state

The dual-ledger framework makes one further move that is especially valuable for agent engineering: it defines **mass** or **substance** not as size, but as resistance to changing structure. The source text defines the mass tensor as the curvature of the price of structure:

$M(s) = \nabla^2_{ss} \Phi(s) = I(\lambda)^{-1}$ (13.1)

where $I(\lambda)$ is the Fisher information or curvature on the drive side.

The interpretation is strikingly practical. A runtime has high structural mass when even significant coordination effort produces only small structural movement. It has low structural mass when the maintained structure can be redirected or improved more easily.

So in agent-runtime terms:

high mass = sticky, hard-to-move structure (13.2)

low mass = agile, easier-to-reconfigure structure (13.3)

This is one of the cleanest ways to talk about runtime brittleness without falling back on vague adjectives.

13.2 Why some runtimes feel "heavy"

Most engineering teams already know the phenomenon informally. Some systems are "heavy." A new requirement arrives, but the runtime adapts slowly. A contradiction is discovered, but the system keeps reusing the old closure. A small policy shift triggers large coordination overhead. A new environment condition appears, and the runtime seems unable to pivot without extensive replanning.

The dual-ledger framework says this should be understood as structural inertia. The source text even gives an operational reading: low mass means agile structure, while high mass means sticky structure. It recommends reducing condition number and decorrelating features to lighten the body.

So a runtime feels heavy when:

- its state features are badly entangled
- the same structural changes require repeated high coordination work
- small drive changes fail to produce usable movement in `s`
- curvature becomes ill-conditioned near certain operating regions

This is not a metaphor only. It is a direct engineering interpretation of the mass tensor.

13.3 Conditioning, collinearity, and bad feature choices

The source text is very practical on this point. It introduces conditioning and directional heaviness explicitly:

$\kappa(I) = \sigma_{max}(I) / \sigma_{min}(I)$ (13.4)

$H(u) = u^T M(s) u / \|u\|^2$ (13.5)

The most important operational message is that mass depends heavily on how the structure features are chosen. If the declared feature map ϕ is badly designed, highly collinear, or poorly scaled, then the resulting curvature becomes ill-conditioned. That means the runtime becomes difficult to control even if the underlying orchestration logic is good.

This is an underappreciated point. Bad runtime state design can make a coordination framework look worse than it is. If one mixes too many redundant state features, or if important tensions are not represented orthogonally enough, the runtime becomes geometrically heavy.

So the practical rule is:

bad φ design -> bad conditioning -> artificial runtime heaviness (13.6)

This is one reason the source paper emphasizes feature decorrelation, conditioning diagnostics, and explicit spectral analysis.

13.4 Soft and hard directions of change

A mass tensor is not only a scalar burden. It also has directional structure. Some directions in state space are soft and easy to move. Others are hard. The source paper explains this through the eigenstructure of `M(s)`: small eigenvalues correspond to easier directions of movement, while large eigenvalues correspond to harder directions.

So a runtime may be flexible in one respect and rigid in another. For example:

- it may easily alter formatting and output packaging
- but struggle to revise a deeply anchored planning assumption
- it may easily add retrieval evidence
- but struggle to unwind a false high-confidence basin

- it may easily produce more text
- but struggle to reduce contradiction residue

This can be expressed schematically as:

easy direction u_soft : u_soft^T M(s) u_soft small (13.7)

hard direction u_hard : u_hard^T M(s) u_hard large (13.8)

This is extremely useful for debugging. It means “brittleness” is often anisotropic rather than uniform.

13.5 How to lighten a runtime without dumbing it down

The source paper gives a clear practical recommendation: reduce condition number, decorrelate features, improve coverage balance, and keep updates inside safe curvature regions.

For the Agent/Skill framework, that translates into several concrete practices.

First, design state features that reflect real bounded runtime conditions rather than overlapping summary scores. If two state variables always move together, they are probably too entangled for good control.

Second, separate cells more clearly by contract and phase, so that state updates are more interpretable and less mutually confounding.

Third, use exact triggers where possible, because exact triggers reduce unnecessary curvature induced by soft semantic overlap.

Fourth, when a system is in a high-gap regime, prefer smaller and more local updates rather than wide speculative reconfiguration. The dual-ledger dynamics section explicitly recommends increasing damping or moving to an overdamped regime when drift persists.

So the anti-brittleness rule is:

lighter runtime ≠ simpler runtime (13.9)

lighter runtime = better factored state, better conditioning, safer update geometry (13.10)

This is a very important distinction. The framework is not arguing for crude minimalism. It is arguing for better geometry.

---

14. Environment, Drift, and Robust Mode

14.1 Declaring the baseline explicitly

The dual-ledger framework insists on a point that most agent architectures leave vague: the environment must be declared explicitly. The source text states this forcefully: declaring the environment is not optional; it is half the science.

In the fused runtime, the baseline environment is:

q := declared baseline distribution of normal operating conditions (14.1)

This may refer to:

- normal user request distribution
- normal tool latency and availability
- normal retrieval recall/precision regime
- normal policy and safety threshold regime
- normal artifact or workflow mix

Without such a baseline, the system cannot tell whether it is facing a real drift or just normal variation. So the framework requires every serious runtime to say what “normal” means.

14.2 Sentinel features and drift detection

Once the baseline exists, drift becomes measurable. The source paper gives two direct signals:

$$\hat{D}_f(t) = D_f(\hat{q}_t \| q) \quad (14.2)$$

$$\Delta_{env}(t) = \| E_{data}[\varphi_{env}] - E_q[\varphi_{env}] \|_2 \quad (14.3)$$

Equation (14.2) is a divergence alarm between the current estimated environment and the declared baseline. Equation (14.3) is a sentinel-feature deviation score. The source text then recommends a composite drift lamp that triggers when both signals indicate meaningful deviation within a window.

For an agent runtime, this is immensely useful. Drift can come from many places:

- retrieval index staleness
- tool outages or latency spikes
- policy changes
- prompt template shifts
- user-distribution changes
- new domain usage with old assumptions
- changed grounding conditions

All of these are field changes. They are not cell failures in isolation. That is why a runtime needs environment sentinels in addition to local cell logs.

14.3 Robust mode under changing task or data conditions

The source paper proposes a robust-mode construction using a neighborhood around the baseline:

$$U_f(q,\rho) = \{ q' : D_f(q' \| q) \le \rho \} \quad (14.4)$$

From this it defines robust counterparts to the main dual-ledger quantities:

$$\Phi_{rob}(s;\rho,f) \quad (14.5)$$

$$\psi_{rob}(\lambda;\rho,f) \quad (14.6)$$

$G_{rob}(\lambda,s) = \Phi_{rob} + \psi_{rob} - \lambda \cdot s$ (14.7)

and recommends replacing ordinary ledgers with robust ones when drift exceeds threshold.

The engineering meaning is clear:

when environment drift is significant, evaluate health and work under a more conservative baseline (14.8)

This prevents the runtime from acting as if old confidence and old geometry still hold in a changed world.

The source text also recommends hysteresis:

switch_to_robust when $\hat{D}_f \geq \rho^{*}\uparrow$ (14.9)

switch_back only when $\hat{D}_f \leq \rho^{*}\downarrow$, with $\rho^{*}\downarrow < \rho^{*}\uparrow$ (14.10)

This is important because otherwise the system can thrash between normal and robust mode.

14.4 Why environment accounting is part of agent design

Many engineers treat environment drift as a monitoring problem outside the agent architecture. The framework argued here says that is incomplete. Drift handling is not just an ops add-on. It is part of the coordination design itself.

Why? Because every episode's meaning depends on the current field. The same retrieval cell, validation cell, or export cell may be good or bad depending on tool health, retrieval quality, safety regime, and operating distribution. If these background conditions move, then the same coordination logic can begin to misfire even when the cells themselves have not changed.

This is also where the PFBT material becomes a useful parallel. It explicitly distinguishes plan traces from realized traces, models interior "face events" such as retrieval quality shocks and policy escalations, and recommends logging gap, flux, twist, coherence, and residual as runtime KPIs for AI operations.

The shared lesson is:

good agent design must include environment accounting (14.11)

Otherwise the runtime will misclassify environmental stress as local cell failure or user error.

14.5 Stable runtime behavior under nonstationary conditions

The practical playbook from the source text is very strong and can be adapted almost directly for agent systems:

1. Detect drift through divergence and sentinel features.
2. Freeze high-risk acts if drift is confirmed.
3. Switch health and work accounting to robust quantities.
4. Lower step sizes or coordination aggressiveness.
5. Use interim reweighting or temporary re-scoring if needed.
6. Update the baseline only slowly, with hysteresis.

7. Resume standard mode only after health returns to the green band.

This can be summarized as:

if drift_alarm_k = 1 then robust_mode = ON and high-risk export = OFF (14.12)

resume_normal only if G_rob ≤ τ_4^rob and drift signals fall below return thresholds (14.13)

This gives the framework a complete environmental control layer. It now knows:

- what the normal world is
- how to detect when the world moved
- how to keep accounting honest during drift
- how to avoid governance thrash while recovering

That is the point where the framework stops being just a coordination theory and becomes a serious runtime architecture.

These sections now complete the control and governance layer of the article:

- Section 12 introduced the dual ledger for agent systems.
- Section 13 explained runtime mass, rigidity, and brittleness.
- Section 14 added environment baselines, drift detection, and robust mode.

The next natural block is **Sections 15–17**: the minimal runtime loop, telemetry and replayability, and the main failure modes with safety gates.

15. Minimal Runtime Loop

15.1 Collect current artifacts and state

A runtime cannot coordinate well if it begins every cycle by pretending it does not know what it already has. The first step of the loop is therefore not “ask the model what to do next,” but **collect the current maintained state**. This means gathering:

- current artifact graph
- current phase and regime
- current tags and exclusions
- current deficit vector
- current Boson field, if enabled
- current maintained structure s_k
- current active drive λ_k
- current health and drift lamps

This is the point where the framework’s layers meet. The skill-cell side says the runtime must

know which contracts are already satisfied and which are still open. The coordination-episode side says the runtime must know which bounded semantic unit just completed and what it exported. The dual-ledger side says the runtime must know the maintained structure and its current health geometry.

A compact state-collection object is:

State_k = (Artifacts_k, Phase_k, Regime_k, Tags_k, D_k, B_k, s_k, λ_k, Gates_k) (15.1)

This should be the coordinator's true starting point at each episode boundary.

15.2 Evaluate eligibility

Once the current state is assembled, the runtime should evaluate contractual eligibility. This step must happen before semantic ranking or Boson-sensitive wake-up. A cell that is not in scope, not in phase, or missing required inputs should not enter serious competition.

For each cell `i`, evaluate:

eligible_i(k) = 1 iff Regime_k ∈ R_i and Phase_k ∈ P_i and In_i satisfied and T_i^(+) ⊆ Tags_k and T_i^(−) ∩ Tags_k = ∅ (15.2)

This is the framework's first anti-chaos measure. It keeps the candidate set small and local. It also preserves auditability, because the runtime can explain why a cell was even considered in the first place.

The decomposition and skill-cell materials strongly support this ordering: exact eligibility first, then deficit and resonance, not the other way around.

15.3 Evaluate deficit

After eligibility comes deficit. The runtime should ask: among the cells that are legally in scope, which ones are most relevant to what the episode still lacks?

Let the current deficit vector be:

D_k = (D_artifact,k, D_exit,k, D_contradiction,k, D_phase,k, D_export,k) (15.3)

Then compute each cell's deficit compatibility:

need_i(k) = Compat(D_k, D_i) (15.4)

This is where the framework becomes much more purposeful than relevance-only systems. Cells are not scored primarily because they are semantically nearby. They are scored because they are good candidates for reducing the currently dominant deficit. The semantic-Boson material is very explicit that the deficit layer should answer the question "What is missing in the episode right now?" and use that answer as a major activation driver.

15.4 Evaluate optional Boson resonance

Only after eligibility and deficit should the system check the Boson layer, if that layer is enabled. Bosons should not override hard boundaries. They should only alter wake pressure among already plausible candidates.

Let the decayed Boson field at episode `k` be:

B_k = { w_b(k) }_b (15.5)

Then for each candidate cell:

$$res_i(k) = \Sigma_{(b \in B_i^{(recv)})} \rho_i(b) \cdot w_b(k) \quad (15.6)$$

The runtime can now combine exact status, deficit compatibility, and Boson-sensitive resonance:

$$score_i(k) = \alpha_i \cdot need_i(k) + \beta_i \cdot res_i(k) + \gamma_i \cdot base_i(k) \quad (15.7)$$

This follows the layered wake-up logic already developed earlier in the article and supported by the source material: exact layer first, deficit layer second, resonance layer third.

15.5 Select candidate cells

The coordinator now has a scored candidate set. It must choose a bounded subset to activate. This choice should obey:

- wake thresholds
- concurrency limits
- conflict constraints
- cost or latency budgets
- phase legality
- health and drift gates

Formally:

$$C_k = \{ i : eligible_i(k) = 1 \} \quad (15.8)$$

$$A_k = Select(C_k, score_k, \Theta_k, \Gamma_k, Esc_k, \Phi trans_k) \quad (15.9)$$

Here A_k is the activated set for episode k. It may contain one cell or a small coordinated bundle. The coordination-episode framework warns against unconstrained parallel wake-up, because too many weakly relevant activations lead to fragmentation rather than bounded closure.

So the coordinator should prefer:

small bounded activated sets over diffuse activation clouds (15.10)

15.6 Run a bounded coordination episode

Once the activated set is chosen, the runtime executes one bounded coordination episode. This is the heart of the loop. A bounded episode may include:

- one exact transformation
- one short retrieval-and-validation sequence
- one contradiction arbitration pass
- one synthesis step followed by a validator
- one repair cycle under a small concurrency bundle

The important point is that the episode must remain bounded enough that it can be judged for closure. The coordination-episode source text emphasizes that a semantic tick is defined by bounded local convergence, not merely by elapsed time or token count.

So the episode execution primitive is:

$E_k = Run(A_k, State_k, \Omega_k)$ (15.11)

where Ω_k includes retrieved evidence, tool outputs, external observations, and environment signals encountered during the episode.

The episode ends when one of the following happens:

- transferable closure is reached
- a recognized failure state is reached
- a hard gate blocks further progress
- the bounded loop budget is exhausted

15.7 Export closure, update state, emit signals

At the end of the episode, the runtime must decide what, if anything, is now exportable. This is where the framework distinguishes real progress from mere internal activity.

Let the completion indicator be:

$\chi_k = 1$ iff transferable closure reached in episode k; 0 otherwise (15.12)

If $\chi_k = 1$, the runtime exports the relevant artifact or stabilized local state and updates the maintained runtime structure:

$s_{(k+1)} = UpdateStructure(s_k, X_{out,k})$ (15.13)

The runtime may also emit Bosons based on what just happened:

$emit_b(k) = Emit(X_{out,k}, Fragility_k, Conflict_k, Deficit_k)$ (15.14)

The emitted Bosons are then folded into the next-step field through their decay rule, for example:

$w_b(k+1) = \eta_b \cdot w_b(k) + emit_b(k)$, with $0 \le \eta_b < 1$ (15.15)

This completes the semantic handoff from one episode to the next.

15.8 Reconcile the ledger and log the tick

The final step of the runtime loop is accounting. Once the episode ends and the state is updated, the runtime should record:

- the new maintained structure $s_{(k+1)}$
- the drive used during the episode λ_k
- the structural work increment
- health and drift lamps

- artifacts produced or failed
- Bosons emitted
- failure states, if any
- replay metadata

The per-episode structural work is:

$$\Delta W_s(k) = \lambda_k \cdot (s_{(k+1)} - s_k) \quad (15.16)$$

The dual-ledger framework also provides the reconciliation identity:

$$\Delta\Phi = W_s - \Delta\psi \quad (15.17)$$

and a practical residual:

$$\varepsilon_{ledger}(k) = | [\Phi_k - \Phi_0] - [W_s(k) - (\psi_k - \psi_0)] | \quad (15.18)$$

This means the runtime loop does not end at “the system responded.” It ends at “the system closed one bounded episode, updated structure, emitted any relevant transients, and reconciled the accounting.”

That is what makes the framework operationally serious.

---

16. Telemetry, Logging, and Replayability

16.1 What to log per coordination episode

A runtime that cannot replay its own important episode boundaries cannot be trusted to improve systematically. The dual-ledger source text is unusually strong on this point: it specifies a minimal per-tick telemetry schema including time, seed, feature-map ID, baseline ID, structure s, drive λ, ledger quantities, curvature quantities, gate flags, work increment, and environment sentinels.

For the fused Agent/Skill framework, the minimal per-episode record should include:

- run ID and episode index k
- UTC timestamp
- activated cell set A_k
- artifact inputs and outputs
- phase and regime
- deficit vector D_k
- Boson field before and after
- maintained structure s_k, $s_{(k+1)}$
- drive λ_k
- health quantities G_k, g_k

- curvature quantities such as `eig(I_k)` and `κ(I_k)`
- per-episode work increment `ΔW_s(k)`
- gate flags
- environment sentinel values
- failure markers and recovery action, if any

A compact schema notation is:

Tick_k = (run_id, k, t_iso, A_k, Phase_k, Regime_k, D_k, B_k, s_k, s_(k+1), λ_k, G_k, g_k, eig(I_k), κ(I_k), ΔW_s(k), gate_flags_k, env_k, fail_k) (16.1)

This is not identical to the source schema, but it is a direct adaptation of its logic for the Agent/Skill runtime.

16.2 Episode index, state delta, and structural work

Three telemetry fields are especially important.

First, the **episode index** `k`. This is the runtime's natural semantic clock. If a system only logs wall-clock time or token count, it becomes difficult to reconstruct meaningful closure boundaries.

Second, the **state delta**:

Δs_k = s_(k+1) − s_k (16.2)

This records what the episode actually changed in maintained structure. It is much more informative than just logging a final response string.

Third, the **structural work increment**:

ΔW_s(k) = λ_k · Δs_k (16.3)

This gives a quantitative measure of how much coordination pressure was spent to move the system's maintained structure during that episode. The dual-ledger paper treats this as a central accounting quantity, and it becomes especially meaningful when `k` is a coordination-episode index.

These three fields together already give a much better replay story than ordinary conversational logs.

16.3 Gate lamps and freeze conditions

Telemetry is not only for analysis after the fact. It is also the live control surface of the runtime. The dual-ledger source text defines gate lamps and explicit freeze conditions, including margin, curvature, gap, and drift checks. It also recommends freezing publish/act behavior when ledger residuals exceed tolerance or when multiple hard gates fail.

In the fused runtime, gate flags should minimally include:

margin_ok_k = 1 iff g_k ≥ τ_1 (16.4)

curvature_ok_k = 1 iff κ(I_k) ≤ τ_3 and ‖I_k‖ ≤ τ_2 (16.5)

gap_ok_k = 1 iff G_k ≤ τ_4 (16.6)

drift_ok_k = 1 iff D^_f(k) < ρ* and Δ_env(k) < δ* (16.7)

A composite lamp is then easy to define:

health_lamp_k = Green if all hard gates pass; Yellow if one is marginal; Red otherwise (16.8)

Freeze conditions should be explicit rather than intuitive. For example:

publish_act_k = OFF if Red or ε_ledger(k) > ε_tol (16.9)

This is one of the framework's major practical advantages. Safety and control logic stop being scattered through prompts and become visible as runtime states.

16.4 Ledger residuals and audit checks

A serious runtime should not only claim that it is balancing work and structure. It should test that claim numerically. The dual-ledger source text therefore includes a reconciliation residual and a tolerance rule:

ε_ledger(k) = | [Φ_k − Φ_0] − [W_s(k) − (ψ_k − ψ_0)] | (16.10)

ε_tol = ε_abs + ε_rel·max{ 1, |ΔΦ|, |W_s|, |Δψ| } (16.11)

In the fused runtime, the exact quantities may be approximate at first, but the principle should remain: every important per-episode update should support replayable accounting.

Useful audit checks include:

- Was the activated set `A_k` consistent with eligibility and gates?
- Did the episode produce the declared output artifact?
- Did the state delta `Δs_k` make sense relative to the claimed output?
- Did structural work rise while exportability or health degraded?
- Did the gate lamps justify the follow-up action?
- Did the Boson emissions match the local closure or failure state?

Auditability is not a side feature. It is part of the framework's core value proposition.

16.5 Why replayable traces matter more than screenshots

Many agent systems are evaluated through screenshots, anecdotal outputs, or a few high-level benchmark numbers. Those are not useless, but they are poor debugging instruments. A replayable trace is much more valuable because it lets another engineer or another team ask:

- what was the current deficit state?
- which cells were even eligible?
- why did this candidate set win?
- what local closure actually happened?

- what did the system think it changed?
- was the runtime healthy at that moment?
- was the world drifting?

The dual-ledger source text says this beautifully and directly: with the right tick logs and footers, results become not just persuasive but replayable.

For the Agent/Skill framework, that means:

good trace > good screenshot (16.12)

because the trace can show the runtime mechanics, not just the final surface behavior.

---

17. Failure Modes and Safety Gates

17.1 False wake-up

The first major failure mode is **false wake-up**. A cell activates even though it is not truly needed for the current episode. This can happen because semantic similarity is overweighted, Boson resonance is too strong, or the phase and deficit model is too weak.

False wake-up is expensive because it consumes attention, compute, and coordination bandwidth without reducing the dominant deficit. It also tends to fragment the episode, because the runtime starts serving too many nearby but unnecessary local processes.

A simple condition for false wake-up is:

false_wake_i(k) = 1 iff activated_i(k) = 1 and useful_reduction_in_D_k ≈ 0 and transferable_output_i(k) = 0 (17.1)

This is not a theorem from the source files, but it is a very natural operationalization of the framework's logic.

The main protections are:

- exact eligibility first
- deficit weighting before semantic ranking
- bounded activated sets
- weak Boson defaults unless evidence justifies stronger coupling

17.2 Under-wake and stalled closure

The opposite failure is **under-wake**. A necessary cell never activates, or activates too late, because the runtime fails to represent the relevant deficit or phase condition clearly enough.

Under-wake is often more dangerous than false wake-up because it can look like calm. The runtime produces partial outputs, appears orderly, and even avoids speculative branching, yet the core blockage remains unresolved. The coordination-episode framework describes this as a trigger failure: the right local basin is never entered, so the episode cannot reach a real transferable closure.

A practical stalled-closure condition is:

stalled_k = 1 iff D_k remains high over T episodes and χ_k = 0 repeatedly (17.2)

The main protections are:

- explicit deficit vectors
- required-artifact tracking
- phase-block markers
- deficit Bosons for hard missingness
- escalation after repeated stalled episodes

17.3 Boson over-sensitivity

Bosons are useful only if they remain lightweight and local. A runtime can fail by becoming too sensitive to Boson emission. In that case, small local events recruit too many downstream candidates, or repeatedly reactivate cells whose usefulness is marginal.

A simple over-sensitivity symptom is:

boson_thrash_k = 1 iff Σ_i activated_i(k) rises mainly due to res_i(k) while deficit reduction remains poor (17.3)

This is why Bosons should decay, remain typed, and never override eligibility and hard gates. The source material strongly recommends keeping the Boson layer light and subordinate to exact and deficit logic.

The main protections are:

- short Boson half-life
- typed receiver sets
- capped resonance contribution
- Boson influence disabled in exact-only regimes
- audit logging of resonance versus deficit contribution

17.4 Oscillatory routing and coordination thrash

A higher-order failure mode is **oscillatory routing**. The runtime alternates between cells or local basins without achieving durable closure. This may happen because phase transitions are too permissive, contradictory Bosons are not damped, deficits are represented inconsistently, or the state model is too noisy.

A simple sign is:

oscillation_k = 1 iff route_(k−m:k) alternates repeatedly without durable χ_k = 1 or with recurring rise in $\hat{G}$_k (17.4)

This kind of thrash is especially damaging because it can consume a lot of structural work without moving the system toward exportable state. It is therefore one of the cases where the work ledger and health ledger together become especially valuable:

high W_s + no durable closure + rising G -> coordination thrash (17.5)

The main protections are:

- stricter phase gates
- bounded retry counts
- explicit arbitration cells
- damping under repeated near-closure failure
- fallback to smaller, more exact cells

17.5 Gap rise, curvature spikes, and quarantine mode

The most serious failures happen when the runtime continues to push while its health degrades. The dual-ledger framework gives the right language for this: rising gap, worsening curvature, drift alarms, and freeze conditions.

Three especially important red flags are:

$d\hat{G}/dt > \gamma$ for T episodes (17.6)

$\kappa(I_k) > \tau_3$ or $\sigma_{min}(I_k)$ near singularity (17.7)

$\varepsilon_{ledger}(k) > \varepsilon_{tol}$ or drift alarm persists (17.8)

If one or more of these persist, the runtime should not continue with normal autonomy. It should enter a more conservative mode. The source material already provides the policy template: slow down, cool the schedule, switch to robust mode if drift is present, and, if multiple gates fail, enter quarantine mode and block publish/act until health returns below threshold.

So the framework's final safety state is:

quarantine_mode_k = ON iff multiple hard gates fail or accounting becomes non-reconcilable (17.9)

In quarantine mode, the runtime should:

- stop high-risk export
- restrict activations to repair and diagnosis cells
- reduce coordination aggressiveness
- use robust accounting if drift is present
- require explicit recovery before resuming normal operation

That gives the framework a serious failure doctrine rather than merely a set of warning messages.

These sections now complete the framework's operational loop and failure logic:

- Section 15 defined the minimal runtime loop.
- Section 16 defined telemetry, logging, and replayability.

- Section 17 defined major failure modes and safety gates.

The next natural block is **Sections 18–20**: a minimal implementation path, benchmark and evaluation design, and comparison with standard agent frameworks.

18. A Minimal Implementation Path

18.1 Start with exact skills only

A common mistake in new agent frameworks is to begin with the most expressive version of the architecture. That is almost always the wrong implementation strategy. The right implementation path is incremental. The source material strongly suggests that the first useful layer is the **exact skill layer**: cells that activate under sharp, checkable conditions and produce sharply typed outputs. Only after those traces are stable should one add softer wake-up logic.

So the first build target is:

Version_0 = exact skill cells + artifact contracts + phase gates (18.1)

At this stage, a team should avoid Bosons entirely and keep semantic routing to a minimum. The main goal is to prove that the runtime can:

- represent artifacts explicitly
- evaluate eligibility correctly
- activate a bounded cell set
- produce transferable outputs
- log episode-level transitions

This is already enough to outperform many ad hoc prompt orchestration systems, because the gain comes first from factorization and bounded closure, not from fancy routing.

18.2 Add deficit markers next

Once exact cells are stable, the next upgrade is the deficit layer. This is the first point where the runtime becomes genuinely coordination-aware rather than merely event-reactive. The semantic-Boson material recommends exactly this ordering: after the exact layer, add deficit-based need because missingness is often a stronger wake signal than similarity.

So the next build target is:

Version_1 = Version_0 + explicit deficit vector D_k (18.2)

At this stage, the runtime should be able to represent at least:

- missing required artifact
- blocked phase transition
- unresolved contradiction residue
- unmet export condition
- fragile local closure

This gives the system a meaningful notion of "why progress is blocked." In practice, this step often yields the largest coordination improvement per unit engineering effort, because it shifts routing from vague relevance to local necessity.

18.3 Add semantic skills after traces stabilize

Only after exact cells and deficit signals produce stable traces should a team add **semantic skills**. These are cells whose input conditions cannot be fully captured by exact predicates and therefore require a softer wake mode. But semantic wake-up should be introduced only after the system already knows how to log, replay, and diagnose bounded exact episodes.

So:

Version_2 = Version_1 + hybrid / semantic wake modes for selected cells (18.3)

The key phrase is **selected cells**. Not every cell should become semantic. A large part of the framework's discipline comes from keeping many cells crisp and typed. Semantic wake-up is valuable where the field really is soft or underdetermined, such as:

- ambiguity-driven clarification
- rival-branch generation
- weak-evidence arbitration
- fragility-aware verification
- recovery from poorly typed upstream outputs

The implementation goal at this stage is not "make the system more intelligent" in a vague sense. It is "add softness only where the runtime's real structure requires it."

18.4 Add Bosons only where direct triggers are insufficient

Bosons should come even later. The earlier sections already argued that Bosons are useful only when direct triggers and deficit logic are still insufficient to capture field-sensitive wake-up. The source material is very explicit that Bosons are optional and should remain lightweight.

So the next target is:

Version_3 = Version_2 + sparse typed Bosons in field-sensitive zones (18.4)

This is the right stage to add Bosons for cases such as:

- completion signals that recruit downstream consumers
- ambiguity signals that recruit branch generators
- conflict signals that recruit arbitration cells
- fragility signals that recruit validators
- deficit signals that recruit artifact-producers

But Bosons should still obey three implementation constraints:

- they never override hard eligibility

- they decay unless reinforced
- they are logged separately from deficit and base scores

That keeps the Boson layer from becoming an excuse for opaque emergent behavior.

18.5 The smallest useful prototype

The smallest prototype that is still faithful to the framework is surprisingly modest. It does not need full dual-ledger geometry, full semantic routing, or a large Boson catalog. It only needs:

- a small typed artifact graph
- 5–12 exact skill cells
- phase roles
- input/output artifact contracts
- a deficit vector
- an episode loop
- replayable logs

In compact form:

Prototype_min = { cells, contracts, D_k, episode loop, logs } (18.5)

A team can get a lot of value from such a system before touching more advanced parts of the framework. The main thing to resist is the temptation to jump directly to “many agents with many personalities.” The framework’s whole point is that **better factors beat more theater**.

---

19. Benchmarks and Evaluation

19.1 Why final-answer accuracy is not enough

Standard evaluation practice often asks only whether the final answer is correct. That is necessary but insufficient for this framework. The whole architecture is motivated by the claim that advanced runtimes should be judged not only by end correctness, but by the quality of their bounded coordination episodes, their closure behavior, their recovery behavior, and their stability under drift.

If two systems produce the same final answer, but one does so through stable, auditable bounded closures while the other does so through brittle improvisation, the two systems are not equally good engineering artifacts.

So the framework needs richer metrics than:

final_accuracy only (19.1)

It needs metrics at episode, state, and runtime-governance level.

19.2 Episode-quality metrics

Because the coordination episode is the natural semantic tick of the framework, the first class of

evaluation metrics should live at episode scale.

Useful episode metrics include:

- eligibility precision: how often activated cells were truly in scope
- deficit reduction per episode
- transferable closure rate
- false-wake rate
- stalled-closure rate
- fragile-closure rate
- average activated-set size
- episode work efficiency

These can be expressed schematically as:

closure_rate = (# episodes with $\chi_k = 1$) / (# total episodes) (19.2)

false_wake_rate = (# episodes with activated cells but near-zero useful deficit reduction) / (# total episodes) (19.3)

deficit_reduction_k = $\|D_k\| - \|D_{(k+1)}\|$ (19.4)

efficiency_k = useful_export_gain_k / max(ε, $\Delta W_s(k)$) (19.5)

These are not all from the source papers verbatim, but they are natural runtime measures implied by the episode and dual-ledger designs.

The important shift is that “good system behavior” becomes observable at the meso layer rather than only at final-answer layer.

19.3 Closure success, recovery quality, and drift tolerance

A mature benchmark suite for this framework should test at least three capabilities.

First, **closure success**. Can the runtime repeatedly produce transferable artifacts under bounded episode constraints?

Second, **recovery quality**. When an episode fails, can the system detect the failure type and route into an appropriate recovery path rather than merely retrying blindly?

Third, **drift tolerance**. When environment conditions move, can the runtime detect that movement and switch to safer behavior or robust mode?

This yields three major benchmark families:

B_{close} = closure benchmark set (19.6)

$B_{recover}$ = recovery benchmark set (19.7)

B_{drift} = drift and robustness benchmark set (19.8)

These are more informative for this framework than a single undifferentiated leaderboard score.

They test the actual structural thesis of the runtime.

19.4 Compare token-time versus episode-time diagnostics

One especially important evaluation question is whether episode-time is actually a better explanatory clock than token-time. The coordination-episode papers explicitly argue that token count and wall-clock time often distort the natural semantic dynamics of advanced reasoning systems.

That claim should be tested, not merely asserted.

A useful experiment is to compare two diagnostic views of the same runtime trace:

View_A = token-indexed diagnostics (19.9)

View_B = episode-indexed diagnostics (19.10)

Then compare which view better predicts:

- failure events
- stall events
- recovery success
- fragile closure
- health-gap rise
- drift-triggered degradation

The framework predicts that episode-indexed diagnostics should often be sharper and more interpretable for higher-order coordination, especially in multi-cell and multi-tool settings.

19.5 What should count as a successful system

A successful system under this framework is not merely one that answers correctly sometimes. It is one that shows the following profile:

- high transferable-closure rate
- low false-wake and oscillation rates
- bounded activated-set size
- interpretable and replayable logs
- stable health-gap behavior in ordinary conditions
- reliable robust-mode behavior under drift
- structural work that maps to useful state change rather than repeated churn

A concise criterion is:

success = correctness + stable closure + recovery quality + drift robustness + replayability (19.11)

This is more demanding than most ordinary agent benchmarks. But it is also much more aligned

with what real engineering teams need once systems leave toy-demo scale.

---

20. Comparison with Standard Agent Frameworks

20.1 Prompt-driven orchestration versus contract-driven coordination

Most standard agent frameworks are primarily prompt-driven. They define one or more agent roles, connect them through messages, and rely on prompts plus perhaps a router to decide what happens next. The framework proposed here moves the center of gravity elsewhere: toward cells, contracts, phases, deficits, and episodes.

So the first major contrast is:

standard stack = prompt-driven orchestration (20.1)

this framework = contract-driven coordination (20.2)

This difference matters because prompt-driven systems often hide operational assumptions in natural language, while contract-driven systems make them explicit in runtime objects.

20.2 Chat history versus artifact graph

Standard agent stacks often treat chat history as the main state object. This framework treats the artifact graph and maintained structure as the main state object instead. That is a major architectural difference.

So:

standard state ≈ message log (20.3)

this framework's state ≈ artifact graph + maintained structure s (20.4)

A message log is still useful as trace evidence, but it is no longer the main thing the runtime reasons over. This makes the system more compositional and more debuggable.

20.3 Central router versus layered wake-up

Many existing systems use one large router or planner to choose the next action. The framework proposed here prefers a layered wake-up logic:

- exact eligibility
- deficit scoring
- optional Boson-sensitive resonance
- bounded activation selection

So the contrast is:

standard routing = central semantic router (20.5)

this framework's routing = layered wake-up over typed cells (20.6)

This is not just a stylistic difference. It changes where costs, errors, and auditability live.

20.4 More agents versus better factors

A lot of current practice scales systems by adding more named agents. The framework here argues that the better path is usually to improve factorization first. If the decomposition unit is wrong, adding more agents mostly adds more surface complexity.

So:

more agents ≠ better decomposition (20.7)

better factors -> better coordination, even with fewer visible agents (20.8)

This is one of the framework's clearest practical claims. It is better to have eight well-designed skill cells under a disciplined coordinator than thirty vaguely named agents whose boundaries are unclear.

20.5 Where this framework should outperform standard stacks

This framework should outperform ordinary prompt-centric agent stacks in situations where the real difficulty is not raw next-step generation but **bounded coordination under persistent structure**.

That includes:

- multi-stage artifact pipelines
- systems with repeated phase transitions
- workflows requiring validation and repair
- environments with drift or regime change
- systems where replayability and auditability matter
- systems with repeated local failure modes
- long tasks where hidden stall and thrash are common

The framework's expected edge is not necessarily that it always finds the best answer in one shot. Its edge is that it should produce:

- cleaner runtime traces
- fewer arbitrary activations
- better local recovery
- better visibility into blocked progress
- better environment handling
- more reliable governance under stress

In short:

standard stacks optimize visible behavior first (20.9)

this framework optimizes coordination structure first (20.10)

And in many real systems, better structure is what ultimately makes better behavior sustainable.

These sections complete the article's final implementation and comparison block:

- Section 18 gave the minimal implementation path.
- Section 19 defined the right evaluation logic.
- Section 20 compared the framework to standard agent stacks.

The next remaining block is the conclusion and appendices: **Sections 21–22** plus the compact notation, schema, Boson catalog, telemetry spec, and worked example.

21. Practical Adoption Roadmap

21.1 Solo builder path

A solo builder should adopt this framework in the narrowest possible way first. The goal is not to reproduce the whole architecture at once. The goal is to get one regime to produce clean, replayable coordination traces.

The recommended sequence is:

1. pick one regime only
2. collect successful traces
3. mark repeated artifact transitions
4. identify repeated handoff points
5. cluster those into candidate cells
6. define exact input/output contracts
7. run an episode loop with replay logs
8. only then add deficit markers
9. only later add semantic wake-up
10. only last add Bosons where direct triggers are insufficient

This sequence is not invented here; it is a direct practical restatement of the decomposition recipe in the source material, which says to begin from successful traces, mark repeated artifact transitions and handoff points, cluster prime-like factors, then assign phase, contracts, wake mode, and failure markers, and add Boson signals only where direct triggers are insufficient.

For a solo builder, the smallest good target is:

Solo_v1 = one regime + 5–12 exact cells + episode logs (21.1)

The solo path should resist two temptations:

- adding too many named "agents" too early
- adding semantic wake-up before exact traces are stable

The framework strongly favors structural clarity over visible cleverness.

21.2 Small team path

A small team can divide the framework more effectively, because different people can own different layers.

A practical team split is:

- one person owns the artifact graph and contracts
- one person owns the coordinator and wake logic
- one person owns telemetry, replay, and evaluation
- one person, if available, owns environment/drift handling and ops integration

The key rule is that the team should align on the same runtime unit. If one person thinks in "agents," another in "prompts," and another in "tools," the architecture will drift. Everyone should work from the same core decomposition:

Cell_i = (R_i, P_i, In_i, Out_i, W_i, T_i^(+), T_i^(−), D_i, B_i^(emit), B_i^(recv), F_i, Rec_i) (21.2)

and the same semantic clock:

S_(k+1) = G(S_k, Π_k, Ω_k) (21.3)

This matters because the framework's benefits come from shared runtime vocabulary as much as from code structure. The coordination-episode and skill-cell materials both emphasize that meaningful reasoning should be segmented into bounded coordination episodes and minimal semantic cells rather than treated as a single vague stream.

21.3 Enterprise path

An enterprise should adopt this framework differently from a solo builder. The main requirement is not intellectual neatness. It is governance.

The PFBT material is very relevant here because it already frames AI/AGI pipelines in terms of planned versus realized traces, face events such as retrieval and tool shocks, governance twists such as prompt or policy changes, and KPI rows such as Gap, Flux, Twist, Coherence, and Residual. It also provides production-facing guidance around dashboards, audit playbooks, versioning, and twist budgets.

For enterprise use, the framework should therefore be adopted as three linked layers:

Layer_A = coordination cells and contracts (21.4)

Layer_B = episode-time telemetry and dual ledger (21.5)

Layer_C = governance, audit, robust mode, and drift policy (21.6)

An enterprise rollout should begin with one workflow where replayability and bounded closure matter, such as:

- document extraction with validation
- retrieval-grounded answer generation

- structured case analysis
- tool-mediated workflow execution
- policy-sensitive report generation

The enterprise path should avoid treating the framework as only a “smarter agent prompt.” Its real advantage is that it provides a path from runtime behavior to governance surfaces.

21.4 What to build first

The first build should always include the following five elements:

- explicit artifact contracts
- exact skill cells
- one coordination-episode loop
- a basic deficit vector
- replayable per-episode logs

That minimum set is enough to make the architecture qualitatively different from standard prompt orchestration.

So the first serious milestone is:

M_1 = { contracts, exact cells, episode loop, D_k, trace logs } (21.7)

After that, the next items should be added in this order:

M_2 = hybrid or semantic wake-up for selected cells (21.8)

M_3 = typed Bosons in field-sensitive handoffs (21.9)

M_4 = dual-ledger state accounting and health lamps (21.10)

M_5 = drift sentinels and robust mode (21.11)

This order preserves interpretability. It ensures that every new layer lands on top of a runtime that already has stable traces.

21.5 What to postpone until later

Several things should be postponed even if they sound attractive.

First, do not begin with a large Boson catalog. Bosons are useful, but only after exact triggers and deficits are already working.

Second, do not begin with dense semantic routing across dozens of cells. Start exact, then selectively soften.

Third, do not attempt enterprise-wide baseline modeling before at least one regime has produced stable episode logs.

Fourth, do not make the dual ledger overcomplicated on day one. A coarse but replayable s_k, λ_k, G_k, and $\Delta W_s(k)$ is better than a mathematically ornate state model that nobody can

maintain.

So the postponement rule is:

defer expressive layers until exact layers are trace-stable (21.12)

This is the cleanest way to keep the framework practical.

---

22. Conclusion: From Agent Theater to Runtime Physics

22.1 The main conceptual shift

The central conceptual shift of this article is simple:

stop treating an advanced AI runtime as a set of named personas passing messages, and start treating it as a coordination system built from bounded transformation cells, explicit contracts, explicit deficits, and explicit closure events.

That shift changes almost everything. It changes what counts as a capability, what counts as progress, what counts as failure, and what counts as state.

The framework therefore replaces:

role personas -> skill cells (22.1)

message flow -> artifact transformation (22.2)

prompt similarity -> deficit-led wake-up (22.3)

token-time -> coordination episodes (22.4)

surface output -> replayable runtime trace (22.5)

This is why the article describes the move as a shift from “agent theater” to runtime structure.

22.2 The main engineering shift

The engineering shift is equally important. The framework does not stop at better decomposition. It also adds a state-and-control layer.

The runtime is no longer only asked:

“What should run next?” (22.6)

It is also asked:

“What structure am I maintaining?” (22.7)

“What drive is currently active?” (22.8)

“How aligned are those two?” (22.9)

“How much structural work did the last episode spend?” (22.10)

“Is the environment still the one I think I am in?” (22.11)

That is the dual-ledger contribution. The source paper explicitly frames body, soul, health, mass, work, and environment as measurable contracts rather than metaphors.

So the engineering shift is:

coordination + accounting + governance (22.12)

not just:

coordination alone (22.13)

22.3 Why episode-time and dual-ledger control belong together

The article made two unusually strong claims:

- the natural semantic clock of an advanced runtime is often the coordination episode
- a serious runtime needs a dual ledger of structure, drive, health, work, and environment

These two claims fit together unusually well.

Episode-time provides the correct semantic tick:

$S_{(k+1)} = G(S_k, \Pi_k, \Omega_k)$ (22.14)

The dual ledger provides the correct per-tick accounting:

$\Delta W_s(k) = \lambda_k \cdot (s_k - s_{(k-1)})$ (22.15)

The first tells you **when** a meaningful bounded semantic event has occurred. The second tells you **what that event changed and what it cost**.

That is why these two layers belong together. Without episode-time, ledger quantities are often too noisy or too substrate-bound. Without the ledger, episode-time remains descriptive but under-governed.

22.4 What this framework makes newly possible

This framework makes several things newly possible or at least much easier.

It makes it easier to:

- factor capabilities by recurrent artifact-transform patterns
- distinguish local closure from surface continuation
- route by what is missing, not only by what is nearby
- model field-sensitive handoff without mystifying it
- identify runtime brittleness as geometry rather than mood
- separate local cell failure from environmental drift
- replay meaningful semantic steps rather than only final outputs
- introduce governance surfaces without burying them in prompts

The PFBT AI/AGI pipeline material reinforces this point from a different angle: once a system

has explicit planned traces, realized traces, flux events, twist events, and KPI rows, AI orchestration becomes governable and auditable rather than merely clever.

That same engineering spirit is what this framework aims to bring to Agent/Skill systems.

22.5 The next step toward a semantic operating layer

The article should not be read as a final doctrine. It should be read as a strong candidate architecture for the next layer of runtime design.

The next step is not to ask whether the framework is elegant in the abstract. The next step is to implement it in a narrow regime and see whether it improves:

- bounded closure quality
- deficit reduction per episode
- replayability
- recovery quality
- drift tolerance
- governance clarity

If it does, then the framework is not merely a new way of describing agent systems. It is a more mature way of building them.

So the final compressed thesis of the article is:

An advanced AI runtime should be built from skill cells defined by artifact contracts, coordinated through deficit-led wake-up and bounded coordination episodes, optionally assisted by typed Boson signals, and governed through a dual ledger of structure, drive, health, work, and environment. (22.16)

That is the framework in one sentence.

Appendix A. Notation and Core Equations

A.1 Micro-step versus episode-step

$x_{n+1} = F(x_n)$ (A.1)

$S_{k+1} = G(S_k, \Pi_k, \Omega_k)$ (A.2)

Interpretation:

- n = micro-step index
- k = coordination-episode index

A.2 State, drive, and environment

$System = (X, \mu, q, \varphi)$ (A.3)

s_k = maintained runtime structure after episode k (A.4)

λ_k = active coordination drive during episode k (A.5)

Interpretation:

- `q` = declared baseline environment
- `ϕ` = declared feature map for what counts as structure

A.3 Gap, work, and drift quantities

G(λ,s) = Φ(s) + ψ(λ) − λ·s ≥ 0 (A.6)

ΔW_s(k) = λ_k · (s_k − s_(k−1)) (A.7)

W_s(K) = Σ_(k=1..K) ΔW_s(k) (A.8)

D^_f(k) = D_f(q^_k ‖ q_ref) (A.9)

Δ_env(k) = ‖ E_(data,k)[φ_env] − E_(q_ref)[φ_env] ‖2 (A.10)

A.4 Minimal symbols used in the article

- `Cell_i` = skill cell `i`
- `R_i` = regime scope
- `P_i` = phase role
- `In_i`, `Out_i` = input/output artifact contracts
- `W_i` = wake mode
- `D_i` = deficit conditions handled by cell `i`
- `B_i^(emit)`, `B_i^(recv)` = Boson emission/reception sets
- `A_k` = activated cell set in episode `k`
- `χ_k` = completion indicator for episode `k`

Appendix B. Skill Cell Reference Schema

B.1 JSON-like schema

Cell_i = {
"cell_id": "...",
"regime_scope": R_i,
"phase_role": P_i,
"input_contract": In_i,
"output_contract": Out_i,
"wake_mode": W_i,
"required_tags": T_i^(+),
"forbidden_tags": T_i^(−),
"deficit_conditions": D_i,
"emit_bosons": B_i^(emit),
"receive_bosons": B_i^(recv),

"failure_states": F_i,
"recovery_paths": Rec_i
} (B.1)

This matches the decomposition guidance in the source material, which says a skill should declare regime scope, phase role, input artifact contract, output artifact contract, wake mode, required tags, forbidden tags, deficit conditions, emitted Bosons, receptive Bosons, and failure states.

B.2 Required fields

The minimal required fields are:

- `cell_id`
- `regime_scope`
- `phase_role`
- `input_contract`
- `output_contract`
- `wake_mode`
- `failure_states`

B.3 Optional fields

The following fields are optional but strongly recommended:

- `required_tags`
- `forbidden_tags`
- `deficit_conditions`
- `emit_bosons`
- `receive_bosons`
- `recovery_paths`

B.4 Example cells

Example 1:

Cell_validator = {
"cell_id": "validator.schema.v1",
"regime_scope": {"structured_output"},
"phase_role": {"validate"},
"input_contract": {"json_draft": 1, "schema_valid": 0},
"output_contract": {"schema_validated_object": 1},
"wake_mode": "exact",
"required_tags": {"schema_sensitive"},
"forbidden_tags": {"export_blocked_by_policy"},
"deficit_conditions": {"missing_schema_validity"},
"emit_bosons": {"completion"},
"receive_bosons": {"fragility", "deficit"},

"failure_states": {"invalid_output", "looped_repair"},
"recovery_paths": {"invalid_output": "repair.json"}
} (B.2)

Example 2:

Cell_arbitration = {
"cell_id": "arbitration.conflict.v1",
"regime_scope": {"evidence_synthesis"},
"phase_role": {"arbitrate"},
"input_contract": {"conflict_report": 1},
"output_contract": {"arbitrated_state": 1},
"wake_mode": "hybrid",
"required_tags": {"conflict_present"},
"forbidden_tags": {"hard_export"},
"deficit_conditions": {"contradiction_residue_high"},
"emit_bosons": {"completion", "fragility"},
"receive_bosons": {"conflict"},
"failure_states": {"unresolved_conflict", "false_closure"}
} (B.3)

Appendix C. Boson Type Catalog

C.1 Completion Boson

b = completion (C.1)

Emitted when a stable artifact appears.
Typical wake targets: downstream consumer, exporter, next-phase cells.

C.2 Ambiguity Boson

b = ambiguity (C.2)

Emitted when a parse, interpretation, or evidence set remains underdetermined.
Typical wake targets: clarifier, rival-generator, disambiguator cells.

C.3 Conflict Boson

b = conflict (C.3)

Emitted when incompatible artifacts coexist.
Typical wake targets: contradiction checker, arbitration, resolution cells.

C.4 Fragility Boson

b = fragility (C.4)

Emitted when closure exists but is unstable.
Typical wake targets: verifier, robustness improver, confidence repair cells.

C.5 Deficit Boson

b = deficit (C.5)

Emitted when the phase cannot advance because a required artifact is missing.
Typical wake targets: most likely artifact-producing cells.

A minimal decay rule is:

$w_b(k+1) = \eta_b \cdot w_b(k) + emit_b(k)$, with $0 \le \eta_b < 1$ (C.6)

Appendix D. Minimal Telemetry Spec

D.1 Episode log fields

A compact per-episode record is:

Tick_k = (run_id, k, t_iso, A_k, Phase_k, Regime_k, D_k, B_k, s_k, s_(k+1), λ_k, G_k, g_k, eig(I_k), κ(I_k), ΔW_s(k), gate_flags_k, env_k, fail_k) (D.1)

The dual-ledger source text independently recommends per-tick fields including time, seed, `ϕ_id`, `q_id`, `s`, `λ`, `ψ`, `Φ`, `G`, `g`, eigenvalues of `I`, `κ(I)`, gate flags, `ΔW_s`, and environment sentinels.

D.2 Gate flags

margin_ok_k = 1 iff $g_k \ge \tau_1$ (D.2)

curvature_ok_k = 1 iff $\kappa(I_k) \le \tau_3$ and $\|I_k\| \le \tau_2$ (D.3)

gap_ok_k = 1 iff $G_k \le \tau_4$ (D.4)

drift_ok_k = 1 iff $\hat{D}_f(k) < \rho^*$ and $\Delta_{env}(k) < \delta^*$ (D.5)

These mirror the source gate logic for margin, curvature, gap, and drift monitoring.

D.3 Drift sentinels

$\hat{D}_f(k) = D_f(\hat{q}_k \| q_{ref})$ (D.6)

$\Delta_{env}(k) = \| E_{data,k}[\varphi_{env}] - E_{q_{ref}}[\varphi_{env}] \|_2$ (D.7)

robust_on_k = 1 if either (D.6) or (D.7) persists for ≥ T ticks (D.8)

D.4 Replay checklist

A replayable run should allow an independent team to reconstruct:

- activated cell set `A_k`
- state delta `Δs_k`
- Boson emissions and decay
- structural work `ΔW_s(k)`
- gate-lamp transitions
- drift/robust-mode transitions
- final closure/failure state

This follows the same replayability logic emphasized in the dual-ledger telemetry section.

Appendix E. Worked Runtime Example

E.1 A simple exact-only flow

Suppose the system is in a structured-output regime and the current artifact set contains:

Artifacts_k = { json_draft = 1, schema_valid = 0 } (E.1)

The exact validator cell has:

In_validator = { json_draft = 1, schema_valid = 0 } (E.2)

So:

eligible_validator(k) = 1 (E.3)

If the current dominant deficit is:

D_k = { missing_schema_validity = high } (E.4)

then:

need_validator(k) high (E.5)

The runtime activates only the validator:

A_k = { validator } (E.6)

and runs a bounded episode. If the validator succeeds:

χ_k = 1 (E.7)

X_out,k = { schema_validated_object = 1 } (E.8)

The state then updates:

s_(k+1) = UpdateStructure(s_k, X_out,k) (E.9)

and a completion Boson may be emitted:

emit_completion(k) = 1 (E.10)

This exact-only flow already demonstrates the framework's main virtues: typed eligibility, deficit-led activation, bounded closure, and replayable state change.

E.2 A semantic wake-up flow

Now consider a more semantic regime. Suppose a retrieval episode produced two partially conflicting evidence bundles, and an ambiguity Boson was emitted by an earlier retrieval cell:

B_k = { ambiguity: 0.7 } (E.11)

Two cells are now eligible:

C_k = { clarifier, arbitration } (E.12)

Their scores are computed as:

score_clarifier(k) = α·need_clarifier(k) + β·res_clarifier(k) + γ·base_clarifier(k) (E.13)

score_arbitration(k) = α·need_arbitration(k) + β·res_arbitration(k) + γ·base_arbitration(k) (E.14)

If contradiction residue is still low but interpretation underdetermination is high, the clarifier may win. If contradiction residue is already high, the arbitration cell may win.

This is exactly the kind of field-dependent wake-up for which the source material recommends Boson-sensitive routing.

E.3 A failed episode and recovery

Suppose the runtime activates a synthesis cell too early. The cell emits a draft, but the output is not transferable because contradiction residue remains high and novelty support is weak.

So:

χ_k = 0 (E.15)

fail_k = false_closure_attempt (E.16)

If a fragility Boson is emitted:

emit_fragility(k) = 1 (E.17)

then the next episode may recruit a verifier or arbitration cell instead of repeating synthesis blindly. This shows the framework's failure advantage: failure is not just "bad answer." It is a typed runtime state that can recruit an appropriate repair path.

E.4 Ledger reconciliation example

Suppose the maintained structure moved from `s_k` to `s_(k+1)` under drive `λ_k`. Then:

Δs_k = s_(k+1) − s_k (E.18)

ΔW_s(k) = λ_k · Δs_k (E.19)

Over several episodes:

W_s(K) = Σ_(k=1..K) ΔW_s(k) (E.20)

The runtime also tracks changes in ψ and Φ, then computes:

ε_ledger(K) = | [Φ_K − Φ_0] − [W_s(K) − (ψ_K − ψ_0)] | (E.21)

If `ε_ledger(K)` stays within tolerance, the runtime's structure/work accounting remains coherent. If not, the system should freeze high-risk actions and inspect state or logging drift, exactly as recommended in the source telemetry guidance.

© 2026 Danny Yeung. All rights reserved. 版权所有 不得转载

Disclaimer

This book is the product of a collaboration between the author and OpenAI's GPT-5.4, X's Grok,

Google Gemini 3, Claude's Sonnet 4.6 language model. While every effort has been made to ensure accuracy, clarity, and insight, the content is generated with the assistance of artificial intelligence and may contain factual, interpretive, or mathematical errors. Readers are encouraged to approach the ideas with critical thinking and to consult primary scientific literature where appropriate.

This work is speculative, interdisciplinary, and exploratory in nature. It bridges metaphysics, physics, and organizational theory to propose a novel conceptual framework—not a definitive scientific theory. As such, it invites dialogue, challenge, and refinement.

I am merely a midwife of knowledge.