

Bioinformatics Homework 2.1

De Bruijn Graph from K-mer Polymers

Problem Statement: Given a set of k-mers, construct the adjacency list of the corresponding De Bruijn graph, which *could* then be used to form a De Bruijn sequence by finding an Eulerian path in the respective graph.

Algorithm Description:

```
KmerEdgeList(Kmers)
  n <- | Kmers |
  // Adjacency list
  DB <- graph where every k-mer in Kmers is has edge between
  its prefix and suffix of size k-1. Graph resulting from
  gluing all nodes in DB with identical labels

  // Iterating through each k-mer
  for every integer i between 0 and n-1
    prefix = first k-1 characters of the kmer
    suffix = last k-1 characters of the kmer
    add edge in DB from prefix to suffix

  // Returning the finalized adjacency list
  return DB
```

This algorithm takes a set of k-mers, and creates a representation of the graph that could be used to do string reconstruction using the Eulerian Paths algorithm. To create the graph, we take each k-mer and add an edge in our graph from the node representing the first k-1 letters of the k-mer to the node representing the final k-1 letters in our k-mer. The resulting edge represents the full, original k-mer. By finding an Eulerian path on the resulting graph, we can ensure that all the k-mers will be used in the final string resulting from the path.

Time Analysis: Since this algorithm goes through each k-mer ($O(n)$), and adds a substring of those k-mers to a graph ($O(k)$), this algorithm runs in $O(nk)$ time. Since we are only adding one string of size $k-1$ to a list k times, the space complexity is also $O(nk)$

Implementation: [#1082623](#)

<https://cogniterra.org/submissions/202076/1082623?unit=45309>

Discussion: The algorithms in the program for creating the graph are simple and straight forward. Because we need to look through each letter in each k-mer, the best runtime for this algorithm is going to be $O(nk)$ which is what we get with this algorithm. Depending on the implementation, there might be a log factor because of the graph edge insertion function.