



University of Central Florida

# Samuel Oliveira

**UCF Locals**

September 13, 2025

- 1 Contest
- 2 Mathematics
- 3 Data structures
- 4 Numerical
- 5 Number theory
- 6 Combinatorial
- 7 Graphs
- 8 Geometry
- 9 Strings
- 10 Various

Contest (1)

template.cpp13 lines

```
#include <bits/stdc++.h>
using namespace std;
#define rep(i, a, b) for (ll i = a; i < (ll)(b); ++i)
#define all(x) (x).begin(), (x).end()
#define sz(x) (ll) x.size()
typedef long long ll;
typedef vector<ll> vll;

int main()
{
    cin.tie(0)->sync_with_stdio(0);
    cin.exceptions(cin.failbit);
}
```

.bashrc3 lines

```
alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++17 \
-fsanitize=undefined,address'
xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps =<
```

hash.sh3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum |cut -c-6
```

troubleshoot.txt57 lines

```
Pre-submit:

    Write a few test cases
    INCLUDE MAX CASES.
    Is memory fine?
    Overflow?
    Correct file?

Wrong answer:
```

Print your solution + Print debug  
Clearing all structures between test cases?  
Can your code handle the whole input range?  
Read the problem statement again.  
Do you handle all corner cases correctly?  
Have you understood the problem correctly?  
Uninitialized variables?  
Overflows?  
Confusing N and M, i and j, etc.?  
Are you sure your algorithm works?  
Any very special cases?  
Do you know how the STL functions you use work?  
Add some assertions, maybe resubmit.  
Create some testcases  
Go through the algorithm for a simple case.  
Go through this list again.  
Explain your algorithm to a teammate.  
Ask the teammate to look at your code.  
Go for a small walk, e.g. to the toilet.  
Is your output format correct? (whitespace)  
You/Teammate rewrite solution from the start

Runtime error:

Have you tested all corner cases locally?  
Any uninitialized variables?  
Are you reading or writing outside of range?  
Consider increasing the size of your vectors  
Any assertions that might fail?  
Any possible division by 0? (mod 0 for example)  
Any possible infinite recursion?  
Invalidated pointers or iterators?  
Are you using too much memory?

Time limit exceeded:

Do you have any possible infinite loops?  
What is the complexity of your algorithm?  
Are you copying a lot of unnecessary data?  
How big is the input and output?  
Avoid vector, map. (use arrays/unordered\_map)  
What do your teammates think about your algorithm?

Memory limit exceeded:

Max amount of memory your code should need?  
Clearing all data structures between test cases?

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by  $x = -b/2a$ .

$$\begin{aligned} ax + by &= e & \Rightarrow \quad x &= \frac{ed - bf}{ad - bc} \\ cx + dy &= f & \quad y &= \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation  $Ax = b$ , the solution to a variable  $x_i$  is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where  $A'_i$  is  $A$  with the  $i$ 'th column replaced by  $b$ .

2.2 Recurrences

If  $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$ , and  $r_1, \dots, r_k$  are distinct roots of  $x^k - c_1x^{k-1} - \dots - c_k$ , there are  $d_1, \dots, d_k$  s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots  $r$  become polynomial factors, e.g.  $a_n = (d_1n + d_2)r^n$ .

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$
$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$
$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$
$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where  $V, W$  are lengths of sides opposite angles  $v, w$ .

$$a \cos x + b \sin x = r \cos(x - \phi)$$
$$a \sin x + b \cos x = r \sin(x + \phi)$$

where  $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$ .

2.4 Geometry

2.4.1 Triangles

Side lengths:  $a, b, c$   
Semiperimeter:  $p = \frac{a + b + c}{2}$   
Area:  $A = \sqrt{p(p - a)(p - b)(p - c)}$   
Circumradius:  $R = \frac{abc}{4A}$   
Inradius:  $r = \frac{A}{p}$   
Length of median (divides triangle into two equal-area triangles):  
 $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$   
Length of bisector (divides angles in two):  
 $s_a = \sqrt{bc \left[ 1 - \left( \frac{a}{b + c} \right)^2 \right]}$

Law of sines:  $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines:  $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents:  $\frac{a+b}{a-b} = \frac{\tan \frac{\alpha+\beta}{2}}{\tan \frac{\alpha-\beta}{2}}$


### 2.4.2 Quadrilaterals

With side lengths  $a, b, c, d$ , diagonals  $e, f$ , diagonals angle  $\theta$ , area  $A$  and magic flux  $F = b^2 + d^2 - a^2 - c^2$ :

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is  $180^\circ$ ,  $ef = ac + bd$ , and  $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$ .

### 2.4.3 Spherical coordinates



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \operatorname{atan2}(y, x) \end{aligned}$$

## 2.5 Derivatives/Integrals

$$\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1-x^2}} \quad \frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1-x^2}}$$

$$\frac{d}{dx} \tan x = 1 + \tan^2 x \quad \frac{d}{dx} \arctan x = \frac{1}{1+x^2}$$

$$\int \tan ax = -\frac{\ln |\cos ax|}{a} \quad \int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$

$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \operatorname{erf}(x) \quad \int x e^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1)$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

## 2.6 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

## 2.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)$$

## 2.8 Probability theory

Let  $X$  be a discrete random variable with probability  $p_X(x)$  of assuming the value  $x$ . It will then have an expected value (mean)  $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$  and variance  $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$  where  $\sigma$  is the standard deviation. If  $X$  is instead continuous it will have a probability density function  $f_X(x)$  and the sums above will instead be integrals with  $p_X(x)$  replaced by  $f_X(x)$ .

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent  $X$  and  $Y$ ,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

### 2.8.1 Discrete distributions

#### Binomial distribution

The number of successes in  $n$  independent yes/no experiments, each which yields success with probability  $p$  is  $\operatorname{Bin}(n, p)$ ,  $n = 1, 2, \dots$ ,  $0 \leq p \leq 1$ .

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\operatorname{Bin}(n, p)$  is approximately  $\operatorname{Po}(np)$  for small  $p$ .

### First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability  $p$  is  $\operatorname{Fs}(p)$ ,  $0 \leq p \leq 1$ .

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

### Poisson distribution

The number of events occurring in a fixed period of time  $t$  if these events occur with a known average rate  $\kappa$  and independently of the time since the last event is  $\operatorname{Po}(\lambda)$ ,  $\lambda = t\kappa$ .

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

### 2.8.2 Continuous distributions

#### Uniform distribution

If the probability density function is constant between  $a$  and  $b$  and 0 elsewhere it is  $\operatorname{U}(a, b)$ ,  $a < b$ .

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

### Exponential distribution

The time between events in a Poisson process is  $\operatorname{Exp}(\lambda)$ ,  $\lambda > 0$ .

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

### Normal distribution

Most real random values with mean  $\mu$  and variance  $\sigma^2$  are well described by  $\mathcal{N}(\mu, \sigma^2)$ ,  $\sigma > 0$ .

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If  $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$  and  $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$  then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

## Data structures (3)

Note: if there are no updates, consider merges

### BitVector.h

**Description:** Given vector of bits, counts number of 0's in [0, r). Use with WaveletTree.h by using modifications in comments in that file and replacing bv[h][x] with bv[h].cnt0(x)  
**Time:**  $\mathcal{O}(1)$  time

afd9d2, 15 lines

```
struct BitVector {
    vector<pair<ll, int>> b;
    BitVector(vector<bool> a): b(sz(a) / 64 + 1) {
        rep(i, 0, sz(a))
            b[i >> 6].first |= ll(a[i]) << (i & 63);
        rep(i, 0, sz(b)-1)
            b[i + 1].second = __builtin_popcountll(b[i].first)
                + b[i].second;
    }
    int cnt0(int r) {
        auto [x, y] = b[r >> 6];
        return r - y
            - __builtin_popcountll(x & ((1ULL << (r & 63)) - 1));
    }
};
```

### OrderStatisticTree.h

**Description:** A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change null.type.  
**Time:**  $\mathcal{O}(\log N)$

782797, 16 lines

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2; t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
    assert(*t.find_by_order(0) == 8);
    t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

### HashMap.h

**Description:** Hash map with mostly the same API as unordered\_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

d77092, 7 lines

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = ll(4e18 * acos(0)) | 71;
    ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{1<16});
```

### KactlSegmentTree.h

**Description:** Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.  
**Time:**  $\mathcal{O}(\log N)$

1905ff, 19 lines

```
struct Tree {
    typedef ll T;
    static constexpr T unit = LLONG_MIN;
    T f(T a, T b) { return max(a, b); }
    vector<T> s; ll n;
    Tree(ll n = 0, T def = unit): s(2*n, def), n(n) {}
```

```
void update(ll pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
        s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
}
T query(ll b, ll e) {
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2) ra = f(ra, s[b++]);
        if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
}
};
```

### LazySegmentTree.h

**Description:** Segment tree with ability to add or set values of large intervals, and compute max of intervals. Can be changed to other things. Use with a bump allocator for better performance, and SmallPtr or implicit indices to save memory.  
**Usage:** Node\* tr = new Node(v, 0, sz(v));  
**Time:**  $\mathcal{O}(\log N)$ .

c97658, 50 lines

```
const int inf = 1e9;
struct Node {
    Node *l = 0, *r = 0;
    int lo, hi, mset = inf, madd = 0, val = -inf;
    Node(int lo,int hi):lo(lo),hi(hi){} // Large interval of -inf
    Node(vll& v, int lo, int hi) : lo(lo), hi(hi) {
        if (lo + 1 < hi) {
            int mid = lo + (hi - lo)/2;
            l = new Node(v, lo, mid); r = new Node(v, mid, hi);
            val = max(l->val, r->val);
        }
        else val = v[lo];
    }
    int query(int L, int R) {
        if (R <= lo || hi <= L) return -inf;
        if (L <= lo && hi <= R) return val;
        push();
        return max(l->query(L, R), r->query(L, R));
    }
    void set(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) mset = val = x, madd = 0;
        else {
            push(), l->set(L, R, x), r->set(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void add(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) {
            if (mset != inf) mset += x;
            else madd += x;
            val += x;
        }
        else {
            push(), l->add(L, R, x), r->add(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void push() {
        if (!l) {
            int mid = lo + (hi - lo)/2;
            l = new Node(lo, mid); r = new Node(mid, hi);
        }
        if (mset != inf)
            l->set(lo,hi,mset), r->set(lo,hi,mset), mset = inf;
        else if (madd)
```

```
        l->add(lo,hi,madd), r->add(lo,hi,madd), madd = 0;
    }
};
```

### NodeBasedSegmentTree.h

**Description:** Simple node based segment tree for quick typing on more unique problems

9aa4ab, 23 lines

```
struct node {
    pll val = {LLONG_MAX, LLONG_MAX};
    ll lo, hi, mid;
    node *left = nullptr, *right = nullptr;
    node (ll l, ll h) : lo(l), hi(h) {
        mid = (lo + hi) / 2;
        if (lo + 1 == hi) return;
        left = new node(lo, mid);
        right = new node(mid, hi);
    }
    void merge() { val = min(left->val, right->val); }
    void set(ll i, ll x) {
        if (lo + 1 == hi) { val = {x, i}; return; }
        if (i < mid) left->set(i, x);
        else right->set(i, x);
        merge();
    }
    pll query(ll l, ll r) {
        if (r <= lo || l >= hi) return { LLONG_MAX, LLONG_MAX };
        ;
        if (lo >= l && hi <= r) return val;
        return min(left->query(l, r), right->query(l, r));
    }
};
```

### DynamicSegmentTree.h

**Description:** Segment Tree that only create nodes for used values. Consider using offline value compression before using a DST

248be1, 27 lines

```
struct Node {
    ll lo, hi;
    ll val = 0;
    Node *left = nullptr, *right = nullptr;
    Node(ll lo, ll hi) : lo(lo), hi(hi) {}
    void extend() {
        if (!left && lo + 1 < hi) {
            ll t = (lo + hi) / 2;
            left = new Node(lo, t);
            right = new Node(t, hi);
        }
    }
    void add(ll k, ll x) {
        extend();
        val += x;
        if (left) {
            if (k < left->hi) left->add(k, x);
            else right->add(k, x);
        }
    }
    ll get_sum(ll lq, ll rq) {
        if (lq <= lo && hi <= rq) return val;
        if (max(lo, lq) >= min(hi, rq)) return 0;
        extend();
        return left->get_sum(lq, rq) + right->get_sum(lq, rq);
    }
};
```

### SegmentTree.h

**Description:** General Segment Tree with functionality for common problems.

**Usage:** set(i, v, 0, 0, SIZE)

ff3d11, 55 lines

```
typedef struct Tree {
    ll size;
    vll vals;
    ll NEUTRAL_ELEMENT = 0;
    ll f(ll a, ll b) { return a + b; }
    void init(ll n) {
        size = 1;
        while (size < n) size *= 2;
        vals.assign(2 * size, 0LL);
    }
    void build(vll &a, ll x, ll lx, ll rx) {
        if (lx + 1 == rx) {
            if (lx < (ll)a.size()) vals[x] = a[lx];
            return;
        }
        ll m = (lx + rx) / 2;
        build(a, 2 * x + 1, lx, m);
        build(a, 2 * x + 2, m, rx);
        vals[x] = f(vals[2 * x + 1], vals[2 * x + 2]);
    }
    void set(ll i, ll v, ll x, ll lx, ll rx) {
        if (lx + 1 == rx) {
            vals[x] = v;
            return;
        }
        ll m = (lx + rx) / 2;
        if (i < m) set(i, v, 2 * x + 1, lx, m);
        else set(i, v, 2 * x + 2, m, rx);
        vals[x] = f(vals[2 * x + 1], vals[2 * x + 2]);
    }
    ll calc(ll l, ll r, ll x, ll lx, ll rx) {
        if (lx >= r || l >= rx) return NEUTRAL_ELEMENT;
        if (lx >= l && rx <= r) return vals[x];
        ll m = (lx + rx) / 2;
        ll s1 = calc(l, r, 2 * x + 1, lx, m);
        ll s2 = calc(l, r, 2 * x + 2, m, rx);
        return f(s1, s2);
    }
    ll findKth(ll k, ll x, ll lx, ll rx) {
        if (lx + 1 == rx) return lx;
        ll m = (lx + rx) / 2;
        ll s1 = vals[2*x + 1];
        if (k < s1) return findKth(k, 2*x + 1, lx, m);
        else return findKth(k-s1, 2*x + 2, m, rx);
    }
    ll first_above(ll v, ll l, ll x, ll lx, ll rx) {
        if (vals[x] < v) return -1;
        if (rx <= l) return -1;
        if (rx - lx == 1) return lx;
        ll m = (lx + rx) / 2;
        ll res = first_above(v, l, 2*x + 1, lx, m);
        if (res == -1) res = first_above(v, l, 2*x + 2, m, rx);
        return res;
    }
} Tree;
```

### PST.h

**Description:** Persistent segment tree with laziness

**Time:**  $\mathcal{O}(\log N)$  per query,  $\mathcal{O}((n + q) \log n)$  memory

6e8af5, 39 lines

```
struct PST {
    PST *l = 0, *r = 0;
    int lo, hi;
    ll val = 0, lzadd = 0;
    PST(vl& v, int lo, int hi) : lo(lo), hi(hi) {
```

```
        if (lo + 1 < hi) {
            int mid = lo + (hi - lo)/2;
            l = new PST(v, lo, mid); r = new PST(v, mid, hi);
            val = l->val + r->val;
        }
        else val = v[lo];
    }
    ll query(int L, int R) {
        if (R <= lo || hi <= L) return 0; // idempotent
        if (L <= lo && hi <= R) return val;
        push();
        return l->query(L, R) + r->query(L, R);
    }
    PST* add(int L, int R, ll v) {
        if (R <= lo || hi <= L) return this;
        PST *n = new PST(*this);
        if (L <= lo && hi <= R) {
            n->val += v * (hi - lo);
            n->lzadd += v;
        } else {
            n->push();
            n->l = n->l->add(L, R, v);
            n->r = n->r->add(L, R, v);
            n->val = n->l->val + n->r->val;
        }
        return n;
    }
    void push() {
        if (lzadd == 0) return;
        l = l->add(lo, hi, lzadd);
        r = r->add(lo, hi, lzadd);
        lzadd = 0;
    }
}
```

### SqrtDecomp.h

**Description:** decomposes (l, r) range into pair of (list of fully covered blocks, list of partially covered blocks)

**Time:**  $\mathcal{O}(B + (r - l)/B)$

799a5b, 16 lines

```
template<int B>
pair<vi, vector<array<int, 3>>> decomp(int l, int r) {
    if (l/B == (r-1)/B) return {{}}, {{l/B, l, r}}};
    vi full;
    vector<array<int, 3>> subs;
    if (l%B != 0) {
        subs.push_back({l/B, l, (l/B+1)*B});
        l = subs.back()[2];
    }
    if (r%B != 0) {
        subs.push_back({r/B, r/B*B, r});
        r = subs.back()[1];
    }
    rep(i, l/B, r/B) full.push_back(i);
    return {full, subs};
}
```

### LiChao.h

**Description:** Creates a segment tree style data structure that supports adding a function to the set and query the min value at a given x. For any two added functions, they must intersect at most once. If queries can be floating point, consider line container instead.

**Time:** Both operations are  $\mathcal{O}(\log N)$ .

bdebe2, 27 lines

```
struct line {
    ll m, b;
    line(ll m = 0, ll b = LLONG_MAX) : m(m), b(b) {}
    ll operator() (ll x) { return m * x + b; }
};
```

```
struct node {
    int lo, md, hi;
    line f;
    node *left, *right;
    node(int L, int R) : lo(L), md((L+R)>>1), hi(R) {
        if (lo == hi) return;
        left = new node(lo, md);
        right = new node(md+1, hi);
    }
    void update(line g) {
        if (g(md) < f(md)) swap(f, g);
        if (lo == hi) return;
        if (f(lo) <= g(lo) && f(hi) <= g(hi)) return;
        if (f(lo) > g(lo)) left->update(g);
        else right->update(g);
    }
    ll query(ll x) {
        if (lo == hi) return f(x);
        return min(f(x), (x <= md ? left : right)->query(x));
    }
};
```

### UnionFindRollback.h

**Description:** Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().

**Usage:** int t = uf.time(); ...; uf.rollback(t);

**Time:**  $\mathcal{O}(\log(N))$

56286c, 21 lines

```
struct RollbackUF {
    vll e; vector<pll> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
    void rollback(int t) {
        for (int i = time(); i --> t;)
            e[st[i].first] = st[i].second;
        st.resize(t);
    }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        st.push_back({a, e[a]});
        st.push_back({b, e[b]});
        e[a] += e[b]; e[b] = a;
        return true;
    }
};
```

### SubMatrix.h

**Description:** Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).

**Usage:** SubMatrix<int> m(matrix);

m.sum(0, 0, 2, 2); // top left 4 elements

**Time:**  $\mathcal{O}(N^2 + Q)$

c59ada, 13 lines

```
template<class T>
struct SubMatrix {
    vector<vector<T>>> p;
    SubMatrix(vector<vector<T>>> v) {
        int R = sz(v), C = sz(v[0]);
        p.assign(R+1, vector<T>(C+1));
        rep(r,0,R) rep(c,0,C)
            p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
    }
    T sum(int u, int l, int d, int r) {
        return p[d][r] - p[d][l] - p[u][r] + p[u][l];
    }
};
```

```
    }
};

Matrix.h
Description: Basic operations on square matrices.
Usage: Matrix<int, 3> A;
A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}}};
array<int, 3> vec = {1,2,3};
vec = (A`N) * vec;
```

6ab5db, 26 lines

```
template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][j] += d[i][k]*m.d[k][j];
        return a;
    }
    array<T, N> operator*(const array<T, N>& vec) const {
        array<T, N> ret{};
        rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator^(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i,0,N) a.d[i][i] = 1;
        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p >>= 1;
        }
        return a;
    }
};
```

LineContainer.h

**Description:** Container where you can add lines of the form  $kx+m$ , and query maximum values at points  $x$ . Useful for dynamic programming (“convex hull trick”).

**Time:**  $\mathcal{O}(\log N)$

8ec1c7, 30 lines

```
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
```

```
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};

Treap.h
Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.
Time: O(log N)
1754b4, 53 lines

struct Node {
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template<class F> void each(Node* n, F f) {
    if (n) { each(n->l, f); f(n->val); each(n->r, f); }
}

pair<Node*, Node*> split(Node* n, int k) {
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
        auto [L,R] = split(n->l, k);
        n->l = R;
        n->recalc();
        return {L, n};
    } else {
        auto [L,R] = split(n->r, k - cnt(n->l) - 1); // and just "k"
        n->r = L;
        n->recalc();
        return {n, R};
    }
}

Node* merge(Node* l, Node* r) {
    if (!l) return r;
    if (!r) return l;
    if (l->y > r->y) {
        l->r = merge(l->r, r);
        return l->recalc(), l;
    } else {
        r->l = merge(l, r->l);
        return r->recalc(), r;
    }
}

Node* ins(Node* t, Node* n, int pos) {
    auto [l,r] = split(t, pos);
    return merge(merge(l, n), r);
}

// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h

**Description:** Computes partial sums  $a[0] + a[1] + \dots + a[\text{pos} - 1]$ , and updates single elements  $a[i]$ , taking the difference between the old and new value.

**Time:** Both operations are  $\mathcal{O}(\log N)$ .

be8dea, 22 lines

```
struct FT {
    vll s;
    FT(int n) : s(n) {}
    void update(int pos, ll dif) { // a[pos] += dif
        for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
    }
    ll query(int pos) { // sum of values in [0, pos)
        ll res = 0;
        for (; pos > 0; pos &= pos - 1) res += s[pos-1];
        return res;
    }
    int lower_bound(ll sum) { // min pos st sum of [0, pos] >= sum
        // Returns n if no sum is >= sum, or -1 if empty sum is.
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << 25; pw; pw >>= 1) {
            if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
                pos += pw, sum -= s[pos-1];
        }
        return pos;
    }
};
```

FenwickTree2d.h

**Description:** Computes sums  $a[i,j]$  for all  $i < I, j < J$ , and increases single elements  $a[i,j]$ . Requires that the elements to be updated are known in advance (call `fakeUpdate()` before `init()`).

**Time:**  $\mathcal{O}(\log^2 N)$ . (Use persistent segment trees for  $\mathcal{O}(\log N)$ .)

"FenwickTree.h" c31cc5, 22 lines

```
struct FT2 {
    vector<vll> ys; vector<FT> ft;
    FT2(int limx) : ys(limx) {}
    void fakeUpdate(int x, int y) {
        for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
    }
    void init() {
        for (vll& v : ys) sort(all(v)), ft.emplace_back(sz(v));
    }
    int ind(int x, int y) {
        return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
    void update(int x, int y, ll dif) {
        for (; x < sz(ys); x |= x + 1)
            ft[x].update(ind(x, y), dif);
    }
    ll query(int x, int y) {
        ll sum = 0;
        for (; x; x &= x - 1)
            sum += ft[x-1].query(ind(x-1, y));
        return sum;
    }
};
```

RMQ.h

**Description:** Range Minimum Queries on an array. Returns  $\min(V[a], V[a + 1], \dots V[b - 1])$  in constant time.

**Usage:** `RMQ rmq(values);`  
`rmq.query(inclusive, exclusive);`

**Time:**  $\mathcal{O}(|V| \log |V| + Q)$

510c32, 16 lines

```
template<class T>
struct RMQ {
    vector<vector<T>> jmp;
    RMQ(const vector<T>& V) : jmp(1, V) {
```



```

    for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
        jmp.emplace_back(sz(V) - pw * 2 + 1);
        rep(j, 0, sz(jmp[k]))
            jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
    }
T query(int a, int b) {
    assert(a < b); // or return inf if a == b
    int dep = 31 - __builtin_clz(b - a);
    return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
}
};

```

## MoQueries.h

**Description:** Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change step to add/remove the edge (a,c) and remove the initial add call (but keep in).

**Time:**  $\mathcal{O}(N\sqrt{Q})$

```

a12ef4, 49 lines
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

```

```

vi mo(vector<pii> Q) {
    int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s;
#define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K[Q[s]] < K[Q[t]]; });
    for (int qi : s) {
        pii q = Q[qi];
        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    }
    return res;
}

```

```

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
    int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    };
    dfs(root, -1, 0, dfs);
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K[Q[s]] < K[Q[t]]; });
    for (int qi : s) rep(end, 0, 2) {
        int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                    else { add(c, end); in[c] = 1; } a = c; }
        while (L[b] <= L[a] && R[a] <= R[b])
            I[i++] = b, b = par[b];
        while (a != b) step(par[a]);
        while (i--) step(I[i]);
        if (end) res[qi] = calc();
    }
    return res;
}

```

## PQUpdate.h

**Description:** T: value/update type. DS: Stores T. Same semantics as std::priority\_queue.

**Time:**  $\mathcal{O}(U \log N)$ .

```

35a7d2, 36 lines
template<class T, class DS, class Compare = less<T>>
struct PQUpdate {
    DS inner;
    multimap<T, int, Compare> rev_upd;
    using iter = decltype(rev_upd)::iterator;
    vector<iter> st;
    PQUpdate(DS inner, Compare comp={}) :
        inner(inner), rev_upd(comp) {}

    bool empty() { return st.empty(); }
    const T& top() { return rev_upd.rbegin()->first; }
    void push(T value) {
        inner.push(value);
        st.push_back(rev_upd.insert({value, sz(st)}));
    }
    void pop() {
        vector<iter> extra;
        iter curr = rev_upd.end();
        int min_ind = sz(st);
        do {
            extra.push_back(--curr);
            min_ind = min(min_ind, curr->second);
        } while (2*sz(extra) < sz(st) - min_ind);
        while (sz(st) > min_ind) {
            if (rev_upd.value_comp()(st.back(), *curr))
                extra.push_back(st.back());
            inner.pop(); st.pop_back();
        }
        rev_upd.erase(extra[0]);
        for (auto it : extra | views::drop(1) | views::reverse) {
            it->second = sz(st);
            inner.push(it->first);
            st.push_back(it);
        }
    }
};

```

## WaveletTree.h

**Description:** kth: finds k+1th smallest number in [l,r], count: rank of k (how many < k) in [l,r]. Doesn't support negative numbers, and requires a[i] <= maxval. Use BitVector to make 1.6x faster and 4x less memory.

**Time:**  $\mathcal{O}(\log MAX)$

```

11aeel, 38 lines
struct WaveletTree {
    int n; vvi bv; // vector<BitVector> bv;
    WaveletTree(vl a, ll max_val):
        n(sz(a)), bv(1+__lg(max_val), {{}}) {
        vl nxt(n);
        for (int h = sz(bv); h--;) {
            vector<bool> b(n);
            rep(i, 0, n) b[i] = ((a[i] >> h) & 1);
            bv[h] = vi(n+1); // bv[h] = b;
            rep(i, 0, n) bv[h][i+1] = bv[h][i] + b[i]; // delete
            array it(begin(nxt), begin(nxt) + bv[h][n]);
            rep(i, 0, n) *it[b[i]]++ = a[i];
            swap(a, nxt);
        }
    }
    ll kth(int l, int r, int k) {
        ll res = 0;
        for (int h = sz(bv); h--;) {
            int l0 = bv[h][l], r0 = bv[h][r];
            if (k < r0 - l0) l = l0, r = r0;
            else
                k -= r0 - l0, res |= 1ULL << h,

```

```

        l += bv[h][n] - l0, r += bv[h][n] - r0;
    }
    return res;
}
int count(int l, int r, ll ub) {
    int res = 0;
    for (int h = sz(bv); h--;) {
        int l0 = bv[h][l], r0 = bv[h][r];
        if ((~ub >> h) & 1) l = l0, r = r0;
        else
            res += r0 - l0, l += bv[h][n] - l0,
            r += bv[h][n] - r0;
    }
    return res;
}
};

```

## Numerical (4)

### 4.1 Polynomials and recurrences

#### Polynomial.h

```

c9b7b0, 17 lines
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val *= x) += a[i];
        return val;
    }
    void diff() {
        rep(i, 1, sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    }
};

```

## PolyRoots.h

**Description:** Finds the real roots to a polynomial.

**Usage:** polyRoots({{2,-3,1}},-1e9,1e9) // solve  $x^2-3x+2 = 0$

**Time:**  $\mathcal{O}(n^2 \log(1/\epsilon))$

```

b00bfe, 23 lines
"Polynomial.h"
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i, 0, sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it, 0, 60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
    }
    return ret;
}

```

```
}

```

### PolyInterpolate.h

**Description:** Given  $n$  points  $(x[i], y[i])$ , computes an  $n-1$ -degree polynomial  $p$  that passes through them:  $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$ . For numerical precision, pick  $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$ .  
**Time:**  $\mathcal{O}(n^2)$

```
08bf48, 13 lines
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

### BerlekampMassey.h

**Description:** Recovers any  $n$ -order linear recurrence relation from the first  $2n$  terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size  $\leq n$ .  
**Usage:** berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}  
**Time:**  $\mathcal{O}(N^2)$

```
53af5a, 20 lines
"../number-theory/ModPow.h"
vll berlekampMassey(vll s) {
    int n = sz(s), L = 0, m = 0;
    vll C(n), B(n), T;
    C[0] = B[0] = 1;

    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }

    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

### LinearRecurrence.h

**Description:** Generates the  $k$ 'th term of an  $n$ -order linear recurrence  $S[i] = \sum_j S[i - j - 1]tr[j]$ , given  $S[0 \dots \geq n - 1]$  and  $tr[0 \dots n - 1]$ . Faster than matrix multiplication. Useful together with Berlekamp-Massey.  
**Usage:** linearRec({0, 1}, {1, 1}, k) //  $k$ 'th Fibonacci number  
**Time:**  $\mathcal{O}(n^2 \log k)$

```
f4e444, 26 lines
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);

    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
    };
}
```

```
res.resize(n + 1);
return res;
};

Poly pol(n + 1), e(pol);
pol[0] = e[1] = 1;

for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
}

ll res = 0;
rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
return res;
}
```

## 4.2 Optimization

### GoldenSectionSearch.h

**Description:** Finds the argument minimizing the function  $f$  in the interval  $[a, b]$  assuming  $f$  is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is  $eps$ . Works equally well for maximization with a small change in the code. See Ternary-Search.h in the Various chapter for a discrete version.  
**Usage:** double func(double x) { return 4+x+.3\*x\*x; }  
double xmin = gss(-1000,1000,func);  
**Time:**  $\mathcal{O}(\log((b-a)/\epsilon))$

```
31d45b, 14 lines
double gss(double a, double b, double (*f)(double)) {
    double r = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
    return a;
}
```

### HillClimbing.h

**Description:** Poor man's optimization for unimodal functions. Seeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
    pair<double, P> cur(f(start), start);
    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
        rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
            P p = cur.second;
            p[0] += dx*jmp;
            p[1] += dy*jmp;
            cur = min(cur, make_pair(f(p), p));
        }
    }
    return cur;
}
```

### Integrate.h

**Description:** Simple integration of a function over an interval using Simpson's rule. The error should be proportional to  $h^4$ , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

```
4756fc, 7 lines
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

```
double h = (b - a) / 2 / n, v = f(a) + f(b);
rep(i,1,n*2)
    v += f(a + i*h) * (i&1 ? 4 : 2);
return v * h / 3;
}

IntegrateAdaptive.h
Description: Fast integration using an adaptive Simpson's rule.
Usage: double sphereVolume = quad(-1, 1, [](double x) {
return quad(-1, 1, [&](double y) {
return quad(-1, 1, [&](double z) {
return x*x + y*y + z*z < 1; });});});
92dd79, 15 lines
```

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}
template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}
```

### RungeKutta.h

**Description:** Numerically approximates the solution to a system of Differential Equations b068fd, 12 lines

```
template<class F, class T>
T solveSystem(F f, T x, double time, int iters) {
    double h = time / iters;
    for(int iter = 0; iter < iters; iter++) {
        T k1 = f(x);
        A k2 = f(x + 0.5 * h * k1);
        A k3 = f(x + 0.5 * h * k2);
        A k4 = f(x + h * k3);
        x = x + h / 6.0 * (k1 + 2.0 * k2 + 2.0 * k3 + k4);
    }
    return x;
}
```

### Simplex.h

**Description:** Solves a general linear maximization problem: maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ . Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of  $c^T x$  otherwise. The input vector is set to an optimal  $x$  (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that  $x = 0$  is viable.  
**Usage:** vvd A = {{1,-1}, {-1,1}, {-1,-2}};  
vd b = {1,1,-4}, c = {-1,-1}, x;  
T val = LPSolver(A, b, c).solve(x);  
**Time:**  $\mathcal{O}(NM * \#pivots)$ , where a pivot may be e.g. an edge relaxation.  $\mathcal{O}(2^n)$  in the general case. aa8530, 68 lines

```
typedef double T; // long double, Rational, double + modKP>...
typedef vector<T> vd;
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
    int m, n;
    vvd A, b, c, x;
    vd val;
    int piv;
    vd row, col;
    vd row2, col2;
    vd row3, col3;
    vd row4, col4;
    vd row5, col5;
    vd row6, col6;
    vd row7, col7;
    vd row8, col8;
    vd row9, col9;
    vd row10, col10;
    vd row11, col11;
    vd row12, col12;
    vd row13, col13;
    vd row14, col14;
    vd row15, col15;
    vd row16, col16;
    vd row17, col17;
    vd row18, col18;
    vd row19, col19;
    vd row20, col20;
    vd row21, col21;
    vd row22, col22;
    vd row23, col23;
    vd row24, col24;
    vd row25, col25;
    vd row26, col26;
    vd row27, col27;
    vd row28, col28;
    vd row29, col29;
    vd row30, col30;
    vd row31, col31;
    vd row32, col32;
    vd row33, col33;
    vd row34, col34;
    vd row35, col35;
    vd row36, col36;
    vd row37, col37;
    vd row38, col38;
    vd row39, col39;
    vd row40, col40;
    vd row41, col41;
    vd row42, col42;
    vd row43, col43;
    vd row44, col44;
    vd row45, col45;
    vd row46, col46;
    vd row47, col47;
    vd row48, col48;
    vd row49, col49;
    vd row50, col50;
    vd row51, col51;
    vd row52, col52;
    vd row53, col53;
    vd row54, col54;
    vd row55, col55;
    vd row56, col56;
    vd row57, col57;
    vd row58, col58;
    vd row59, col59;
    vd row60, col60;
    vd row61, col61;
    vd row62, col62;
    vd row63, col63;
    vd row64, col64;
    vd row65, col65;
    vd row66, col66;
    vd row67, col67;
    vd row68, col68;
    vd row69, col69;
    vd row70, col70;
    vd row71, col71;
    vd row72, col72;
    vd row73, col73;
    vd row74, col74;
    vd row75, col75;
    vd row76, col76;
    vd row77, col77;
    vd row78, col78;
    vd row79, col79;
    vd row80, col80;
    vd row81, col81;
    vd row82, col82;
    vd row83, col83;
    vd row84, col84;
    vd row85, col85;
    vd row86, col86;
    vd row87, col87;
    vd row88, col88;
    vd row89, col89;
    vd row90, col90;
    vd row91, col91;
    vd row92, col92;
    vd row93, col93;
    vd row94, col94;
    vd row95, col95;
    vd row96, col96;
    vd row97, col97;
    vd row98, col98;
    vd row99, col99;
    vd row100, col100;
    vd row101, col101;
    vd row102, col102;
    vd row103, col103;
    vd row104, col104;
    vd row105, col105;
    vd row106, col106;
    vd row107, col107;
    vd row108, col108;
    vd row109, col109;
    vd row110, col110;
    vd row111, col111;
    vd row112, col112;
    vd row113, col113;
    vd row114, col114;
    vd row115, col115;
    vd row116, col116;
    vd row117, col117;
    vd row118, col118;
    vd row119, col119;
    vd row120, col120;
    vd row121, col121;
    vd row122, col122;
    vd row123, col123;
    vd row124, col124;
    vd row125, col125;
    vd row126, col126;
    vd row127, col127;
    vd row128, col128;
    vd row129, col129;
    vd row130, col130;
    vd row131, col131;
    vd row132, col132;
    vd row133, col133;
    vd row134, col134;
    vd row135, col135;
    vd row136, col136;
    vd row137, col137;
    vd row138, col138;
    vd row139, col139;
    vd row140, col140;
    vd row141, col141;
    vd row142, col142;
    vd row143, col143;
    vd row144, col144;
    vd row145, col145;
    vd row146, col146;
    vd row147, col147;
    vd row148, col148;
    vd row149, col149;
    vd row150, col150;
    vd row151, col151;
    vd row152, col152;
    vd row153, col153;
    vd row154, col154;
    vd row155, col155;
    vd row156, col156;
    vd row157, col157;
    vd row158, col158;
    vd row159, col159;
    vd row160, col160;
    vd row161, col161;
    vd row162, col162;
    vd row163, col163;
    vd row164, col164;
    vd row165, col165;
    vd row166, col166;
    vd row167, col167;
    vd row168, col168;
    vd row169, col169;
    vd row170, col170;
    vd row171, col171;
    vd row172, col172;
    vd row173, col173;
    vd row174, col174;
    vd row175, col175;
    vd row176, col176;
    vd row177, col177;
    vd row178, col178;
    vd row179, col179;
    vd row180, col180;
    vd row181, col181;
    vd row182, col182;
    vd row183, col183;
    vd row184, col184;
    vd row185, col185;
    vd row186, col186;
    vd row187, col187;
    vd row188, col188;
    vd row189, col189;
    vd row190, col190;
    vd row191, col191;
    vd row192, col192;
    vd row193, col193;
    vd row194, col194;
    vd row195, col195;
    vd row196, col196;
    vd row197, col197;
    vd row198, col198;
    vd row199, col199;
    vd row200, col200;
    vd row201, col201;
    vd row202, col202;
    vd row203, col203;
    vd row204, col204;
    vd row205, col205;
    vd row206, col206;
    vd row207, col207;
    vd row208, col208;
    vd row209, col209;
    vd row210, col210;
    vd row211, col211;
    vd row212, col212;
    vd row213, col213;
    vd row214, col214;
    vd row215, col215;
    vd row216, col216;
    vd row217, col217;
    vd row218, col218;
    vd row219, col219;
    vd row220, col220;
    vd row221, col221;
    vd row222, col222;
    vd row223, col223;
    vd row224, col224;
    vd row225, col225;
    vd row226, col226;
    vd row227, col227;
    vd row228, col228;
    vd row229, col229;
    vd row230, col230;
    vd row231, col231;
    vd row232, col232;
    vd row233, col233;
    vd row234, col234;
    vd row235, col235;
    vd row236, col236;
    vd row237, col237;
    vd row238, col238;
    vd row239, col239;
    vd row240, col240;
    vd row241, col241;
    vd row242, col242;
    vd row243, col243;
    vd row244, col244;
    vd row245, col245;
    vd row246, col246;
    vd row247, col247;
    vd row248, col248;
    vd row249, col249;
    vd row250, col250;
    vd row251, col251;
    vd row252, col252;
    vd row253, col253;
    vd row254, col254;
    vd row255, col255;
    vd row256, col256;
    vd row257, col257;
    vd row258, col258;
    vd row259, col259;
    vd row260, col260;
    vd row261, col261;
    vd row262, col262;
    vd row263, col263;
    vd row264, col264;
    vd row265, col265;
    vd row266, col266;
    vd row267, col267;
    vd row268, col268;
    vd row269, col269;
    vd row270, col270;
    vd row271, col271;
    vd row272, col272;
    vd row273, col273;
    vd row274, col274;
    vd row275, col275;
    vd row276, col276;
    vd row277, col277;
    vd row278, col278;
    vd row279, col279;
    vd row280, col280;
    vd row281, col281;
    vd row282, col282;
    vd row283, col283;
    vd row284, col284;
    vd row285, col285;
    vd row286, col286;
    vd row287, col287;
    vd row288, col288;
    vd row289, col289;
    vd row290, col290;
    vd row291, col291;
    vd row292, col292;
    vd row293, col293;
    vd row294, col294;
    vd row295, col295;
    vd row296, col296;
    vd row297, col297;
    vd row298, col298;
    vd row299, col299;
    vd row300, col300;
    vd row301, col301;
    vd row302, col302;
    vd row303, col303;
    vd row304, col304;
    vd row305, col305;
    vd row306, col306;
    vd row307, col307;
    vd row308, col308;
    vd row309, col309;
    vd row310, col310;
    vd row311, col311;
    vd row312, col312;
    vd row313, col313;
    vd row314, col314;
    vd row315, col315;
    vd row316, col316;
    vd row317, col317;
    vd row318, col318;
    vd row319, col319;
    vd row320, col320;
    vd row321, col321;
    vd row322, col322;
    vd row323, col323;
    vd row324, col324;
    vd row325, col325;
    vd row326, col326;
    vd row327, col327;
    vd row328, col328;
    vd row329, col329;
    vd row330, col330;
    vd row331, col331;
    vd row332, col332;
    vd row333, col333;
    vd row334, col334;
    vd row335, col335;
    vd row336, col336;
    vd row337, col337;
    vd row338, col338;
    vd row339, col339;
    vd row340, col340;
    vd row341, col341;
    vd row342, col342;
    vd row343, col343;
    vd row344, col344;
    vd row345, col345;
    vd row346, col346;
    vd row347, col347;
    vd row348, col348;
    vd row349, col349;
    vd row350, col350;
    vd row351, col351;
    vd row352, col352;
    vd row353, col353;
    vd row354, col354;
    vd row355, col355;
    vd row356, col356;
    vd row357, col357;
    vd row358, col358;
    vd row359, col359;
    vd row360, col360;
    vd row361, col361;
    vd row362, col362;
    vd row363, col363;
    vd row364, col364;
    vd row365, col365;
    vd row366, col366;
    vd row367, col367;
    vd row368, col368;
    vd row369, col369;
    vd row370, col370;
    vd row371, col371;
    vd row372, col372;
    vd row373, col373;
    vd row374, col374;
    vd row375, col375;
    vd row376, col376;
    vd row377, col377;
    vd row378, col378;
    vd row379, col379;
    vd row380, col380;
    vd row381, col381;
    vd row382, col382;
    vd row383, col383;
    vd row384, col384;
    vd row385, col385;
    vd row386, col386;
    vd row387, col387;
    vd row388, col388;
    vd row389, col389;
    vd row390, col390;
    vd row391, col391;
    vd row392, col392;
    vd row393, col393;
    vd row394, col394;
    vd row395, col395;
    vd row396, col396;
    vd row397, col397;
    vd row398, col398;
    vd row399, col399;
    vd row400, col400;
    vd row401, col401;
    vd row402, col402;
    vd row403, col403;
    vd row404, col404;
    vd row405, col405;
    vd row406, col406;
    vd row407, col407;
    vd row408, col408;
    vd row409, col409;
    vd row410, col410;
    vd row411, col411;
    vd row412, col412;
    vd row413, col413;
    vd row414, col414;
    vd row415, col415;
    vd row416, col416;
    vd row417, col417;
    vd row418, col418;
    vd row419, col419;
    vd row420, col420;
    vd row421, col421;
    vd row422, col422;
    vd row423, col423;
    vd row424, col424;
    vd row425, col425;
    vd row426, col426;
    vd row427, col427;
    vd row428, col428;
    vd row429, col429;
    vd row430, col430;
    vd row431, col431;
    vd row432, col432;
    vd row433, col433;
    vd row434, col434;
    vd row435, col435;
    vd row436, col436;
    vd row437, col437;
    vd row438, col438;
    vd row439, col439;
    vd row440, col440;
    vd row441, col441;
    vd row442, col442;
    vd row443, col443;
    vd row444, col444;
    vd row445, col445;
    vd row446, col446;
    vd row447, col447;
    vd row448, col448;
    vd row449, col449;
    vd row450, col450;
    vd row451, col451;
    vd row452, col452;
    vd row453, col453;
    vd row454, col454;
    vd row455, col455;
    vd row456, col456;
    vd row457, col457;
    vd row458, col458;
    vd row459, col459;
    vd row460, col460;
    vd row461, col461;
    vd row462, col462;
    vd row463, col463;
    vd row464, col464;
    vd row465, col465;
    vd row466, col466;
    vd row467, col467;
    vd row468, col468;
    vd row469, col469;
    vd row470, col470;
    vd row471, col471;
    vd row472, col472;
    vd row473, col473;
    vd row474, col474;
    vd row475, col475;
    vd row476, col476;
    vd row477, col477;
    vd row478, col478;
    vd row479, col479;
    vd row480, col480;
    vd row481, col481;
    vd row482, col482;
    vd row483, col483;
    vd row484, col484;
    vd row485, col485;
    vd row486, col486;
    vd row487, col487;
    vd row488, col488;
    vd row489, col489;
    vd row490, col490;
    vd row491, col491;
    vd row492, col492;
    vd row493, col493;
    vd row494, col494;
    vd row495, col495;
    vd row496, col496;
    vd row497, col497;
    vd row498, col498;
    vd row499, col499;
    vd row500, col500;
    vd row501, col501;
    vd row502, col502;
    vd row503, col503;
    vd row504, col504;
    vd row505, col505;
    vd row506, col506;
    vd row507, col507;
    vd row508, col508;
    vd row509, col509;
    vd row510, col510;
    vd row511, col511;
    vd row512, col512;
    vd row513, col513;
    vd row514, col514;
    vd row515, col515;
    vd row516, col516;
    vd row517, col517;
    vd row518, col518;
    vd row519, col519;
    vd row520, col520;
    vd row521, col521;
    vd row522, col522;
    vd row523, col523;
    vd row524, col524;
    vd row525, col525;
    vd row526, col526;
    vd row527, col527;
    vd row528, col528;
    vd row529, col529;
    vd row530, col530;
    vd row531, col531;
    vd row532, col532;
    vd row533, col533;
    vd row534, col534;
    vd row535, col535;
    vd row536, col536;
    vd row537, col537;
    vd row538, col538;
    vd row539, col539;
    vd row540, col540;
    vd row541, col541;
    vd row542, col542;
    vd row543, col543;
    vd row544, col544;
    vd row545, col545;
    vd row546, col546;
    vd row547, col547;
    vd row548, col548;
    vd row549, col549;
    vd row550, col550;
    vd row551, col551;
    vd row552, col552;
    vd row553, col553;
    vd row554, col554;
    vd row555, col555;
    vd row556, col556;
    vd row557, col557;
    vd row558, col558;
    vd row559, col559;
    vd row560, col560;
    vd row561, col561;
    vd row562, col562;
    vd row563, col563;
    vd row564, col564;
    vd row565, col565;
    vd row566, col566;
    vd row567, col567;
    vd row568, col568;
    vd row569, col569;
    vd row570, col570;
    vd row571, col571;
    vd row572, col572;
    vd row573, col573;
    vd row574, col574;
    vd row575, col575;
    vd row576, col576;
    vd row577, col577;
    vd row578, col578;
    vd row579, col579;
    vd row580, col580;
    vd row581, col581;
    vd row582, col582;
    vd row583, col583;
    vd row584, col584;
    vd row585, col585;
    vd row586, col586;
    vd row587, col587;
    vd row588, col588;
    vd row589, col589;
    vd row590, col590;
    vd row591, col591;
    vd row592, col592;
    vd row593, col593;
    vd row594, col594;
    vd row595, col595;
    vd row596, col596;
    vd row597, col597;
    vd row598, col598;
    vd row599, col599;
    vd row600, col600;
    vd row601, col601;
    vd row602, col602;
    vd row603, col603;
    vd row604, col604;
    vd row605, col605;
    vd row606, col606;
    vd row607, col607;
    vd row608, col608;
    vd row609, col609;
    vd row610, col610;
    vd row611, col611;
    vd row612, col612;
    vd row613, col613;
    vd row614, col614;
    vd row615, col615;
    vd row616, col616;
    vd row617, col617;
    vd row618, col618;
    vd row619, col619;
    vd row620, col620;
    vd row621, col621;
    vd row622, col622;
    vd row623, col623;
    vd row624, col624;
    vd row625, col625;
    vd row626, col626;
    vd row627, col627;
    vd row628, col628;
    vd row629, col629;
    vd row630, col630;
    vd row631, col631;
    vd row632, col632;
    vd row633, col633;
    vd row634, col634;
    vd row635, col635;
    vd row636, col636;
    vd row637, col637;
    vd row638, col638;
    vd row639, col639;
    vd row640, col640;
    vd row641, col641;
    vd row642, col642;
    vd row643, col643;
    vd row644, col644;
    vd row645, col645;
    vd row646, col646;
    vd row647, col647;
    vd row648, col648;
    vd row649, col649;
    vd row650, col650;
    vd row651, col651;
    vd row652, col652;
    vd row653, col653;
    vd row654, col654;
    vd row655, col655;
    vd row656, col656;
    vd row657, col657;
    vd row658, col658;
    vd row659, col65
```



```
vi N, B;
vvd D;

LPSolver(const vvd& A, const vd& b, const vd& c) :
m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
    rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
    rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i]; }
    rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
    N[n] = -1; D[m+1][n] = 1;
}

void pivot(int r, int s) {
    T *a = D[r].data(), inv = 1 / a[s];
    rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
        T *b = D[i].data(), inv2 = b[s] * inv;
        rep(j,0,n+2) b[j] -= a[j] * inv2;
        b[s] = a[s] * inv2;
    }
    rep(j,0,n+2) if (j != s) D[r][j] *= inv;
    rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv;
    swap(B[r], N[s]);
}

bool simplex(int phase) {
    int x = m + phase - 1;
    for (;;) {
        int s = -1;
        rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
        if (D[x][s] >= -eps) return true;
        int r = -1;
        rep(i,0,m) {
            if (D[i][s] <= eps) continue;
            if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                < MP(D[r][n+1] / D[r][s], B[r])) r = i;
        }
        if (r == -1) return false;
        pivot(r, s);
    }
}

T solve(vd &x) {
    int r = 0;
    rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
    if (D[r][n+1] < -eps) {
        pivot(r, n);
        if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
        rep(i,0,m) if (B[i] == -1) {
            int s = 0;
            rep(j,1,n+1) ltj(D[i]);
            pivot(i, s);
        }
    }
    bool ok = simplex(1); x = vd(n);
    rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
    return ok ? D[m][n+1] : inf;
}
};
```

### 4.3 Matrices

#### Determinant.h

**Description:** Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.  
**Time:**  $\mathcal{O}(N^3)$

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
    int n = sz(a); ll ans = 1;
    rep(i,0,n) {
```

3313dc, 18 lines

```
        rep(j,i+1,n) {
            while (a[j][i] != 0) { // gcd step
                ll t = a[i][i] / a[j][i];
                if (t) rep(k,i,n)
                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
                swap(a[i], a[j]);
                ans *= -1;
            }
        }
        ans = ans * a[i][i] % mod;
        if (!ans) return 0;
    }
    return (ans + mod) % mod;
}
```

#### SolveLinear.h

**Description:** Solves  $A * x = b$ . If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in  $A$  and  $b$  is lost.  
**Time:**  $\mathcal{O}(n^2m)$

```
typedef vector<double> vd;
const double eps = 1e-12;
```

```
int solveLinear(vector<vd>& A, vd& b, vd& x) {
    int n = sz(A), m = sz(x), rank = 0, br, bc;
    if (n) assert(sz(A[0]) == m);
    vi col(m); iota(all(col), 0);

    rep(i,0,n) {
        double v, bv = 0;
        rep(r,i,n) rep(c,i,m)
            if ((v = fabs(A[r][c])) > bv)
                br = r, bc = c, bv = v;
        if (bv <= eps) {
            rep(j,i,n) if (fabs(b[j]) > eps) return -1;
            break;
        }
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) swap(A[j][i], A[j][bc]);
        bv = 1/A[i][i];
        rep(j,i+1,n) {
            double fac = A[j][i] * bv;
            b[j] -= fac * b[i];
            rep(k,i+1,m) A[j][k] -= fac*A[i][k];
        }
        rank++;
    }

    x.assign(m, 0);
    for (int i = rank; i--;) {
        b[i] /= A[i][i];
        x[col[i]] = b[i];
        rep(j,0,i) b[j] -= A[j][i] * b[i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

#### SolveLinear2.h

**Description:** To get all uniquely determined values of  $x$  back from SolveLinear, make the following changes:

```
"SolveLinear.h"
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
```

08e495, 7 lines

```
fail;; }
```

#### SolveLinearBinary.h

**Description:** Solves  $Ax = b$  over  $\mathbb{F}_2$ . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys  $A$  and  $b$ .  
**Time:**  $\mathcal{O}(n^2m)$

fa2d7a, 34 lines

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }

    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

#### MatrixInverse-mod.h

**Description:** Invert matrix  $A$  modulo a prime. Returns rank; result is stored in  $A$  unless singular (rank < n). For prime powers, repeatedly set  $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$  where  $A^{-1}$  starts as the inverse of  $A$  mod  $p$ , and  $k$  is doubled in each step.

**Time:**  $\mathcal{O}(n^3)$

"../number-theory/ModPow.h"

0b7b13, 37 lines

```
int matInv(vector<vector<ll>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<ll>> tmp(n, vector<ll>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n) if (A[j][k]) {
            r = j; c = k; goto found;
        }
        return i;
    }
found:
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
        swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    ll v = modpow(A[i][i], mod - 2);
    rep(j,i+1,n) {
        ll f = A[j][i] * v % mod;
```

```
    A[j][i] = 0;
    rep(k,i+1,n) A[j][k] = (A[j][k] - f*A[i][k]) % mod;
    rep(k,0,n) tmp[j][k] = (tmp[j][k] - f*tmp[i][k]) % mod;
}
rep(j,i+1,n) A[i][j] = A[i][j] * v % mod;
rep(j,0,n) tmp[i][j] = tmp[i][j] * v % mod;
A[i][i] = 1;
}

for (int i = n-1; i > 0; --i) rep(j,0,i) {
    ll v = A[j][i];
    rep(k,0,n) tmp[j][k] = (tmp[j][k] - v*tmp[i][k]) % mod;
}

rep(i,0,n) rep(j,0,n)
    A[col[i]][col[j]] = tmp[i][j] % mod + (tmp[i][j] < 0)*mod;
return n;
}
```

### Tridiagonal.h

**Description:**  $x = \text{tridiagonal}(d, p, q, b)$  solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, \quad 1 \leq i \leq n,$$

where  $a_0, a_{n+1}, b_i, c_i$  and  $d_i$  are known.  $a$  can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.

If  $|d_i| > |p_i| + |q_{i-1}|$  for all  $i$ , or  $|d_i| > |p_{i-1}| + |q_i|$ , or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.

**Time:**  $\mathcal{O}(N)$

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
    int n = sz(b); vi tr(n);
    rep(i,0,n-1) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
            diag[i+1] = sub[i]; tr[++i] = 1;
        } else {
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        }
    }
    for (int i = n; i--;) {
        if (tr[i]) {
            swap(b[i], b[i-1]);
            diag[i-1] = diag[i];
            b[i] /= super[i-1];
        } else {
            b[i] /= diag[i];
            if (i) b[i-1] -= b[i]*super[i-1];
        }
    }
    return b;
}
```

### JacobianMatrix.h

**Description:** Makes Jacobian Matrix using finite differences

```
75dc90, 15 lines
template<class F, class T>
vector<vector<T>> makeJacobian(F &f, vector<T> &x) {
    int n = sz(x);
    vector<vector<T>> J(n, vector<T>(n));
    vector<T> fX0 = f(x);
    rep(i, 0, n) {
        x[i] += eps;
        vector<T> fX1 = f(x);
        rep(j, 0, n){
            J[j][i] = (fX1[j] - fX0[j]) / eps;
        }
        x[i] -= eps;
    }
    return J;
}
```

### NewtonsMethod.h

**Description:** Solves a system on non-linear equations

```
6af945, 10 lines
jacobianMatrix.h
template<class F, class T>
void solveNonlinear(F f, vector<T> &x){
    int n = sz(x);
    rep(iter, 0, 100) {
        vector<vector<T>> J = makeJacobian(f, x);
        matInv(J);
        vector<T> dx = J * f(x);
        x = x - dx;
    }
}
```

## 4.4 Fourier transforms

### FastFourierTransform.h

**Description:** `fft(a)` computes  $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$  for all  $k$ .  $N$  must be a power of 2. Useful for convolution: `conv(a, b) = c`, where  $c[x] = \sum a[i]b[x-i]$ . For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by `n`, reverse(`start+1, end`), FFT back. Rounding is safe if  $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$  (in practice  $10^{16}$ ; higher for random inputs). Otherwise, use NTT/FFTMod.

**Time:**  $\mathcal{O}(N \log N)$  with  $N = |A| + |B|$  ( $\sim 1s$  for  $N = 2^{22}$ )

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (^ 10% faster if double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n); rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
}
vd conv(const vd& a, const vd& b) {
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);
    int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
    vector<C> in(n), out(n);
```

```
    copy(all(a), begin(in));
    rep(i,0,sz(b)) in[i].imag(b[i]);
    fft(in);
    for (C& x : in) x *= x;
    rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
    fft(out);
    rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
    return res;
}
```

### FastFourierTransformMod.h

**Description:** Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as  $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$  (in practice  $10^{16}$  or higher). Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$ , where  $N = |A| + |B|$  (twice as slow as NTT or FFT)

```
"FastFourierTransform.h"
b82773, 22 lines
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L, fft(R));
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl, fft(outs));
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

### NumberTheoreticTransform.h

**Description:** `ntt(a)` computes  $\hat{f}(k) = \sum_x a[x]g^{xk}$  for all  $k$ , where  $g = \text{root}^{(\text{mod}-1)/N}$ .  $N$  must be a power of 2. Useful for convolution modulo specific nice primes of the form  $2^a b + 1$ , where the convolution result has size at most  $2^a$ . For arbitrary modulo, see FFTMod. `conv(a, b) = c`, where  $c[x] = \sum a[i]b[x-i]$ . For manual convolution: NTT the inputs, multiply pointwise, divide by `n`, reverse(`start+1, end`), NTT back. Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$

```
"../number-theory/ModPow.h"
ced03d, 35 lines
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vl rt(2, 1);
    for (static int k = 2, s = 2; k < n; k *= 2, s++) {
        rt.resize(n);
        ll z[] = {1, modpow(root, mod >> s)};
        rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
            a[i + j + k] = ai - z + (z > ai ? mod : 0);
```

```
        ai += (ai + z >= mod ? z - mod : z);
    }
}
v1 conv(const v1 &a, const v1 &b) {
    if (a.empty() || b.empty()) return {};
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    v1 L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
}
```

### FastSubsetTransform.h

**Description:** Transform to a basis with fast convolutions of the form  $c[z] = \sum_{z=x\oplus y} a[x] \cdot b[y]$ , where  $\oplus$  is one of AND, OR, XOR. The size of  $a$  must be a power of two.

**Time:**  $\mathcal{O}(N \log N)$

```
void FST(vi& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                inv ? pii(v, u - v) : pii(u + v, u); // OR
                pii(u + v, u - v); // XOR
        }
    }
    if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
```

## Number theory (5)

### 5.1 Modular arithmetic

#### ModInverse.h

**Description:** Pre-computation of modular inverses. Assumes  $\text{LIM} \leq \text{mod}$  and that mod is a prime.

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

#### ModPow.h

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
    ll ans = 1;
    for (; e; b = b * b % mod, e /= 2)
        if (e & 1) ans = ans * b % mod;
    return ans;
}
```

#### ModLog.h

**Description:** Returns the smallest  $x > 0$  s.t.  $a^x = b \pmod m$ , or  $-1$  if no such  $x$  exists.  $\text{modLog}(a,1,m)$  can be used to calculate the order of  $a$ .

```
Time:  $\mathcal{O}(\sqrt{m})$ 
c040b8, 11 lines

ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(i,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

#### ModSum.h

**Description:** Sums of mod'ed arithmetic progressions.  $\text{modsum}(\text{to}, c, k, m) = \sum_{i=0}^{\text{to}-1} (ki + c) \% m$ .  $\text{divsum}$  is similar but for floored division.

```
Time:  $\log(m)$ , with a large constant.
5c5bc5, 14 lines

typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}
ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

#### ModMulLL.h

**Description:** Calculate  $a \cdot b \bmod c$  (or  $a^b \bmod c$ ) for  $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$ .

**Time:**  $\mathcal{O}(1)$  for  $\text{modmul}$ ,  $\mathcal{O}(\log b)$  for  $\text{modpow}$

```
a9c350, 5 lines

typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
```

#### ModSqrt.h

**Description:** Tonelli-Shanks algorithm for modular square roots. Finds  $x$  s.t.  $x^2 = a \pmod p$  ( $-x$  gives the other solution).

**Time:**  $\mathcal{O}(\log^2 p)$  worst case,  $\mathcal{O}(\log p)$  for most  $p$

```
"ModPow.h"
19a793, 24 lines

ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
    ll s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0)
        ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    ll x = modpow(a, (s + 1) / 2, p);
    ll b = modpow(a, s, p), g = modpow(n, s, p);
    for (; r = m) {
        ll t = b;
        for (m = 0; m < r && t != 1; ++m)
```

```
        t = t * t % p;
        if (m == 0) return x;
        ll gs = modpow(g, 1LL << (r - m - 1), p);
        g = gs * gs % p;
        x = x * gs % p;
        b = b * g % p;
    }
}
```

### 5.2 Primality

#### Eratosthenes.h

**Description:** Prime sieve for generating all primes up to a certain limit.  $\text{isprime}[i]$  is true iff  $i$  is a prime.

**Time:**  $\text{lim}=100'000'000 \approx 0.8$  s. Runs 30% faster if only odd indices are stored.

```
eb131a, 11 lines

const int MAX_PR = 5e6;
bitset<MAX_PR> isprime;
vll eratosthenesSieve(int lim) {
    isprime.set(); isprime[0] = isprime[1] = 0;
    for (int i = 4; i < lim; i += 2) isprime[i] = 0;
    for (int i = 3; i*i < lim; i += 2) if (isprime[i])
        for (int j = i*i; j < lim; j += i*2) isprime[j] = 0;
    vll pr;
    rep(i,2,lim) if (isprime[i]) pr.push_back(i);
    return pr;
}
```

#### MillerRabin.h

**Description:** Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to  $7 \cdot 10^{18}$ ; for larger numbers, use Python and extend A randomly.

**Time:** 7 times the complexity of  $a^b \bmod c$ .

```
"ModMulLL.h"
60dcd1, 12 lines

bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
        s = __builtin_ctzll(n-1), d = n >> s;
    for (ull a : A) { // ^ count trailing zeroes
        ull p = modpow(a%n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = modmul(p, p, n);
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}
```

#### FindPrimeFactors.h

**Description:** Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g.  $2299 \rightarrow \{11, 19, 11\}$ ).

**Time:**  $\mathcal{O}(n^{1/4})$ , less for numbers with small factors.

```
"ModMulLL.h", "MillerRabin.h"
d8d98d, 19 lines

ull pollard(ull n) {
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](ull x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}
```

```
vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
```

```
auto l = factor(x), r = factor(n / x);
l.insert(l.end(), all(r));
return l;
}
```

GetFactors.h  
**Description:** Gets all factors of a number  $N$  given the prime factorization of the number.  
**Time:**  $\mathcal{O}\left(\sqrt[3]{N}\right)$

```
void getFactors(auto &primes, auto &pows, auto &factors, int i
    = 0, ll n = 1) {
    if (i == sz(primes)) return void(factors.push_back(n));
    for (ll j = 0, pow = 1; j <= pows[i]; j++, pow *= primes[i])
        getFactors(primes, pows, factors, i+1, n * pow);
}
```

### 5.3 Divisibility

euclid.h  
**Description:** Finds two integers  $x$  and  $y$ , such that  $ax + by = \gcd(a, b)$ . If you just need gcd, use the built in `_gcd` instead. If  $a$  and  $b$  are coprime, then  $x$  is the inverse of  $a \pmod b$ .

```
ll euclid(ll a, ll b, ll &x, ll &y) {
    if (!b) return x = 1, y = 0, a;
    ll d = euclid(b, a % b, y, x);
    return y -= a/b * x, d;
}
```

CRT.h  
**Description:** Chinese Remainder Theorem.  
`crt(a, m, b, n)` computes  $x$  such that  $x \equiv a \pmod m$ ,  $x \equiv b \pmod n$ . If  $|a| < m$  and  $|b| < n$ ,  $x$  will obey  $0 \leq x < \text{lcm}(m, n)$ . Assumes  $mn < 2^{62}$ .  
**Time:**  $\log(n)$

```
"euclid.h"
ll crt(ll a, ll m, ll b, ll n) {
    if (n > m) swap(a, b), swap(m, n);
    ll x, y, g = euclid(m, n, x, y);
    assert((a - b) % g == 0); // else no solution
    x = (b - a) % n * x % n / g * m + a;
    return x < 0 ? x + m*n/g : x;
}
```

#### 5.3.1 Bézout’s identity

For  $a \neq 0, b \neq 0$ , then  $d = \gcd(a, b)$  is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If  $(x, y)$  is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h  
**Description:** *Euler’s  $\phi$*  function is defined as  $\phi(n) := \#$  of positive integers  $\leq n$  that are coprime with  $n$ .  $\phi(1) = 1$ ,  $p$  prime  $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$ ,  $m, n$  coprime  $\Rightarrow \phi(mn) = \phi(m)\phi(n)$ . If  $n = p_1^{k_1}p_2^{k_2}\dots p_r^{k_r}$  then  $\phi(n) = (p_1 - 1)p_1^{k_1-1}\dots(p_r - 1)p_r^{k_r-1}$ .  $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$ .  
 $\sum_{d|n} \phi(d) = n$ ,  $\sum_{1 \leq k \leq n, \gcd(k, n) = 1} k = n\phi(n)/2, n > 1$   
**Euler’s thm:**  $a, n$  coprime  $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$ .  
**Fermat’s little thm:**  $p$  prime  $\Rightarrow a^{p-1} \equiv 1 \pmod p \ \forall a$ .

```
const int LIM = 5000000;
```

```
int phi[LIM];

void calculatePhi() {
    rep(i, 0, LIM) phi[i] = i&1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if (phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

### 5.4 Fractions

ContinuedFractions.h  
**Description:** Given  $N$  and a real number  $x \geq 0$ , finds the closest rational approximation  $p/q$  with  $p, q \leq N$ . It will obey  $|p/q - x| \leq 1/qN$ .  
For consecutive convergents,  $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$ . ( $p_k/q_k$  alternates between  $> x$  and  $< x$ .) If  $x$  is rational,  $y$  eventually becomes  $\infty$ ; if  $x$  is the root of a degree 2 polynomial the  $a$ ’s eventually become cyclic.  
**Time:**  $\mathcal{O}(\log N)$

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
    ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
    for (;;) {
        ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
            a = (ll)floor(y), b = min(a, lim),
            NP = b*P + LP, NQ = b*Q + LQ;
        if (a > b) {
            // If b > a/2, we have a semi-convergent that gives us a
            // better approximation; if b = a/2, we *may* have one.
            // Return {P, Q} here for a more canonical approximation.
            return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
                make_pair(NP, NQ) : make_pair(P, Q);
        }
        if (abs(y = 1/(y - (d)a)) > 3*N) {
            return {NP, NQ};
        }
        LP = P; P = NP;
        LQ = Q; Q = NQ;
    }
}
```

FracBinarySearch.h  
**Description:** Given  $f$  and  $N$ , finds the smallest fraction  $p/q \in [0, 1]$  such that  $f(p/q)$  is true, and  $p, q \leq N$ . You may want to throw an exception from  $f$  if it finds an exact solution, in which case  $N$  can be removed.  
**Usage:** `fracBS([f](Frac f) { return f.p>=3*f.q; }, 10);` // {1, 3}  
**Time:**  $\mathcal{O}(\log(N))$

```
struct Frac { ll p, q; };
```

```
template<class F>
Frac fracBS(F f, ll N) {
    bool dir = 1, A = 1, B = 1;
    Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
    if (f(lo)) return lo;
    assert(f(hi));
    while (A || B) {
        ll adv = 0, step = 1; // move hi if dir, else lo
        for (int si = 0; step; (step *= 2) >= si) {
            adv += step;
            Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
            if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
                adv -= step; si = 2;
            }
            hi.p += lo.p * adv;
            hi.q += lo.q * adv;
            dir = !dir;
            swap(lo, hi);
            A = B; B = !adv;
        }
    }
```

```
return dir ? hi : lo;
}
```

### 5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \quad b = k \cdot (2mn), \quad c = k \cdot (m^2 + n^2),$$

with  $m > n > 0, k > 0, m \perp n$ , and either  $m$  or  $n$  even.

### 5.6 Primes

$p = 962592769$  is such that  $2^{21} \mid p - 1$ , which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power  $p^a$ , except for  $p = 2, a > 2$ , and there are  $\phi(\phi(p^a))$  many. For  $p = 2, a > 2$ , the group  $\mathbb{Z}_{2^a}^\times$  is instead isomorphic to  $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$ .

### 5.7 Estimates

$$\sum_{d|n} d = O(n \log \log n).$$

The number of divisors of  $n$  is at most around 100 for  $n < 5e4$ , 500 for  $n < 1e7$ , 2000 for  $n < 1e10$ , 200 000 for  $n < 1e19$ .

### 5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d)g(n/d)$$

Other useful formulas/forms:

$$\sum_{d|n} \mu(d) = [n = 1] \text{ (very useful)}$$

$$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n)g(d)$$

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m)g(\lfloor \frac{n}{m} \rfloor)$$

## Combinatorial (6)

### 6.1 Permutations

#### 6.1.1 Factorial

$n$	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
$n$	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
$n$	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

UCF

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.

Time:  $\mathcal{O}(n)$

044568, 6 lines

```
int permToInt(vi& v) {
    int use = 0, i = 0, r = 0;
    for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)),
        use |= 1 << x;
    return r;
}
```

**6.1.2 Cycles**

Let  $g_S(n)$  be the number of  $n$ -permutations whose cycle lengths all belong to the set  $S$ . Then

$$\sum_{n=0}^\infty g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$$

**6.1.3 Derangements**

Permutations of a set such that none of the elements appear in their original position.

$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$

derangements.h

Description: Finds number of derangements

664116, 2 lines

```
d[0] = 1; d[1] = 0;
rep (i, 2, n+1) d[i] = (i-1)*(d[i-1]+d[i-2]);
```

**6.1.4 Burnside’s lemma**

Given a group  $G$  of symmetries and a set  $X$ , the number of elements of  $X$  up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where  $X^g$  are the elements fixed by  $g$  ( $g.x = x$ ).

If  $f(n)$  counts “configurations” (of some sort) of length  $n$ , we can ignore rotational symmetry using  $G = \mathbb{Z}_n$  to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

6.2 Partitions and subsets

**6.2.1 Partition function**

Number of ways of writing  $n$  as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \quad p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$
$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

$n$	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	$\sim 2\text{e}5$	$\sim 2\text{e}8$

IntPerm derangements multinomial

6.2.2 Lucas’ Theorem

Let  $n, m$  be non-negative integers and  $p$  a prime. Write  $n = n_k p^k + \dots + n_1 p + n_0$  and  $m = m_k p^k + \dots + m_1 p + m_0$ . Then  $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$ .

6.2.3 Binomials

multinomial.h

Description: Computes  $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \dots k_n!}$ .

a0a312, 5 lines

```
ll multinomial(vi& v) {
    ll c = 1, m = v.empty() ? 1 : v[0];
    rep(i, 1, sz(v)) rep(j, 0, v[i]) c = c * ++m / (j+1);
    return c;
}
```

**6.2.4 Stars and Bars Formula**

The number of ways to distribute  $n$  identical objects into  $k$  distinct bins

$$\binom{n+k-1}{n} = \binom{n+k-1}{k-1}.$$

6.3 General purpose numbers

**6.3.1 Bernoulli numbers**

EGF of Bernoulli numbers is  $B(t) = \frac{t}{e^t - 1}$  (FFT-able).

$B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\begin{aligned} \sum_{i=m}^\infty f(i) &= \int_m^\infty f(x) dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m) \\ &\approx \int_m^\infty f(x) dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \end{aligned}$$

**6.3.2 Stirling numbers of the first kind**

Number of permutations on  $n$  items with  $k$  cycles.

$$c(n, k) = c(n-1, k-1) + (n-1)c(n-1, k), \quad c(0, 0) = 1$$
$$\sum_{k=0}^n c(n, k) x^k = x(x+1) \dots (x+n-1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$$
$$c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

**6.3.3 Eulerian numbers**

Number of permutations  $\pi \in S_n$  in which exactly  $k$  elements are greater than the previous element.  $k$   $j$ :s s.t.  $\pi(j) > \pi(j+1)$ ,  $k+1$   $j$ :s s.t.  $\pi(j) \geq j$ ,  $k$   $j$ :s s.t.  $\pi(j) > j$ .

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$
$$E(n, 0) = E(n, n-1) = 1$$
$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

**6.3.4 Stirling numbers of the second kind**

Partitions of  $n$  distinct elements into exactly  $k$  groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

**6.3.5 Bell numbers**

Total number of partitions of  $n$  distinct elements.  $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$ . For  $p$  prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$$

**6.3.6 Labeled unrooted trees**

# on  $n$  vertices:  $n^{n-2}$

# on  $k$  existing trees of size  $n_i$ :  $n_1 n_2 \dots n_k n^{k-2}$

**6.3.7 Catalan numbers**

# of Catalan numbers  $(d_1-1)! \dots (d_n-1)!$

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, \quad C_{n+1} = \frac{2(2n+1)}{n+2} C_n, \quad C_{n+1} = \sum C_i C_{n-i}$$

$$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$$

- sub-diagonal monotone paths in an  $n \times n$  grid.
- strings with  $n$  pairs of parenthesis, correctly nested.
- binary trees with with  $n+1$  leaves (0 or 2 children).
- ordered trees with  $n+1$  vertices.
- ways a convex polygon with  $n+2$  sides can be cut into triangles by connecting vertices with straight lines.
- permutations of  $[n]$  with no 3-term increasing subseq.

Graphs (7)

7.1 Fundamentals



BellmanFord.h

**Description:** Calculates shortest paths from  $s$  in a graph that might have negative edge weights. Unreachable nodes get  $\text{dist} = \text{inf}$ ; nodes reachable through negative-weight cycles get  $\text{dist} = -\text{inf}$ . Assumes  $V^2 \max |w_i| < \sim 2^{63}$ .  
**Time:**  $\mathcal{O}(VE)$

830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

    int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

TopoSort.h

**Description:** Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than  $n$  – nodes reachable from cycles will not be returned.  
**Time:**  $\mathcal{O}(|V| + |E|)$

d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
    vi indeg(sz(gr)), q;
    for (auto& li : gr) for (int x : li) indeg[x]++;
    rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
    rep(j,0,sz(q)) for (int x : gr[q[j]])
        if (--indeg[x] == 0) q.push_back(x);
    return q;
}
```

7.2 Network flow

Dinic.h

**Description:** Flow algorithm with complexity  $\mathcal{O}(VE \log U)$  where  $U = \max |\text{cap}|$ .  $\mathcal{O}(\min(E^{1/2}, V^{2/3})E)$  if  $U = 1$ ;  $\mathcal{O}(\sqrt{VE})$  for bipartite matching.

d7ff0f, 42 lines

```
struct Dinic {
    struct Edge {
        int to, rev;
        ll c, oc;
        ll flow() { return max(oc - c, 0LL); } // if you need flows
    };
    vi lvl, ptr, q;
    vector<vector<Edge>> adj;
    Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
    void addEdge(int a, int b, ll c, ll rcap = 0) {
        adj[a].push_back({b, sz(adj[b]), c, c});
        adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
    }
    ll dfs(int v, int t, ll f) {
        if (v == t || !f) return f;
        for (int& i = ptr[v]; i < sz(adj[v]); i++) {
            Edge& e = adj[v][i];
```

```
            if (lvl[e.to] == lvl[v] + 1)
                if (ll p = dfs(e.to, t, min(f, e.c))) {
                    e.c -= p, adj[e.to][e.rev].c += p;
                    return p;
                }
            return 0;
        }
    ll calc(int s, int t) {
        ll flow = 0; q[0] = s;
        rep(L,0,31) do { // 'int L=30' maybe faster for random data
            lvl = ptr = vi(sz(q));
            int qi = 0, qe = lvl[s] = 1;
            while (qi < qe && !lvl[t]) {
                int v = q[qi++];
                for (Edge e : adj[v])
                    if (!lvl[e.to] && e.c >> (30 - L))
                        q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
            }
            while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
        } while (lvl[t]);
        return flow;
    }
    bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCostMaxFlow.h

**Description:** Min-cost max-flow. Negative cost cycles not supported. To obtain the actual flow, look at positive values only.  
**Time:** Approximately  $\mathcal{O}(E^2)$ , actually  $\mathcal{O}(FS)$  where  $S$  is the time complexity of the SSSP alg used in find path (in this case SPFA)

27fafb, 55 lines

```
struct mcmf {
    const ll inf = LLONG_MAX >> 2;
    struct edge {
        int v;
        ll cap, flow, cost;
    };
    int n;
    vector<edge> edges;
    vvi adj; vii par; vi in_q;
    vector<ll> dist, pi;
    mcmf(int n) : n(n), adj(n), par(n), in_q(n), dist(n), pi(n) {}
    void add_edge(int u, int v, ll cap, ll cost) {
        int idx = sz(edges);
        edges.push_back({v, cap, 0, cost});
        edges.push_back({u, cap, cap, -cost});
        adj[u].push_back(idx);
        adj[v].push_back(idx ^ 1);
    }
    bool find_path(int s, int t) {
        fill(all(dist), inf);
        fill(all(in_q), 0);
        queue<int> q; q.push(s);
        dist[s] = 0, in_q[s] = 1;
        while (!q.empty()) {
            int cur = q.front(); q.pop();
            in_q[cur] = 0;
            for (int idx: adj[cur]) {
                auto [nxt, cap, fl, wt] = edges[idx];
                ll nxtD = dist[cur] + wt;
                if (fl >= cap || nxtD >= dist[nxt]) continue;
                dist[nxt] = nxtD;
                par[nxt] = {cur, idx};
                if (in_q[nxt]) continue;
                q.push(nxt); in_q[nxt] = 1;
            }
        }
    }
};
```

```
        return dist[t] < inf;
    }
    pair<ll, ll> calc(int s, int t) {
        ll flow = 0, cost = 0;
        while (find_path(s, t)) {
            ll f = inf;
            for (int i, u, v = t; tie(u, i) = par[v], v != s; v = u)
                f = min(f, edges[i].cap - edges[i].flow);
            flow += f;
            for (int i, u, v = t; tie(u, i) = par[v], v != s; v = u)
                edges[i].flow += f, edges[i^1].flow -= f;
        }
        rep(i, 0, sz(edges)>>1)
            cost += edges[i<<1].cost * edges[i<<1].flow;

        return {flow, cost};
    }
};
```

MinCut.h

**Description:** After running max-flow, the left side of a min-cut from  $s$  to  $t$  is given by all vertices reachable from  $s$ , only traversing edges with positive residual capacity.

GlobalMinCut.h

**Description:** Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.  
**Time:**  $\mathcal{O}(V^3)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
    rep(i,0,n) co[i] = {i};
    rep(ph,1,n) {
        vi w = mat[0];
        size_t s = 0, t = 0;
        rep(it,0,n-ph) { //  $\mathcal{O}(V^2) \rightarrow \mathcal{O}(E \log V)$  with prio. queue
            w[t] = INT_MIN;
            s = t, t = max_element(all(w)) - w.begin();
            rep(i,0,n) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), all(co[t]));
        rep(i,0,n) mat[s][i] += mat[t][i];
        rep(i,0,n) mat[i][s] = mat[s][i];
        mat[0][t] = INT_MIN;
    }
    return best;
}
```

GomoryHu.h

**Description:** Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.  
**Time:**  $\mathcal{O}(V)$  Flow Computations

"PushRelabel.h" 0418b3, 13 lines

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
    vi par(N);
    rep(i,1,N) {
        PushRelabel D(N); // Dinic also works
        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
        tree.push_back({i, par[i], D.calc(i, par[i])});
        rep(j,i+1,N)
            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
```



```
    }
    return tree;
}
```

### MatroidIntersection.h

**Description:** Given two matroids, finds the largest common independent set. For the color and graph matroids, this would be the largest forest where no two edges are the same color. A matroid has 3 functions

- check(int x): returns if current matroid can add x without becoming dependent
- add(int x): adds an element to the matroid (guaranteed to never make it dependent)
- clear(): sets the matroid to the empty matroid

The matroid is given an int representing the element, and is expected to convert it (e.g: the color or the endpoints) Pass the matroid with more expensive add/clear operations to M1.

**Time:**  $R^2N(M2.add+M1.check+M2.check)+R^3M1.add+R^2M1.clear+RNM2.clear$

```
"../data-structures/UnionFind.h"
9812a7, 60 lines

struct ColorMat {
    vi cnt, clr;
    ColorMat(int n, vector<int> clr) : cnt(n), clr(clr) {}
    bool check(int x) { return !cnt[clr[x]]; }
    void add(int x) { cnt[clr[x]]++; }
    void clear() { fill(all(cnt), 0); }
};

struct GraphMat {
    UF uf;
    vector<array<int, 2>> e;
    GraphMat(int n, vector<array<int, 2>> e) : uf(n), e(e) {}
    bool check(int x) { return !uf.sameSet(e[x][0], e[x][1]); }
    void add(int x) { uf.join(e[x][0], e[x][1]); }
    void clear() { uf = UF(sz(uf.e)); }
};

template <class M1, class M2> struct MatroidIsect {
    int n;
    vector<char> iset;
    M1 m1; M2 m2;
    MatroidIsect(M1 m1, M2 m2, int n) : n(n), iset(n + 1), m1(m1), m2(m2) {}
    vi solve() {
        rep(i,0,n) if (m1.check(i) && m2.check(i))
            iset[i] = true, m1.add(i), m2.add(i);
        while (augment());
        vi ans;
        rep(i,0,n) if (iset[i]) ans.push_back(i);
        return ans;
    }
    bool augment() {
        vector<int> frm(n, -1);
        queue<int> q({n}); // starts at dummy node
        auto fwdE = [&](int a) {
            vi ans;
            m1.clear();
            rep(v, 0, n) if (iset[v] && v != a) m1.add(v);
            rep(b, 0, n) if (!iset[b] && frm[b] == -1 && m1.check(b))
                ans.push_back(b), frm[b] = a;
            return ans;
        };
        auto backE = [&](int b) {
            m2.clear();
            rep(cas, 0, 2) rep(v, 0, n)
                if ((v == b || iset[v]) && (frm[v] == -1) == cas) {
                    if (!m2.check(v))
                        return cas ? q.push(v), frm[v] = b, v : -1;
                    m2.add(v);
                }
            return n;
        };
    };
};
```

```
while (!q.empty()) {
    int a = q.front(), c; q.pop();
    for (int b : fwdE(a))
        while((c = backE(b)) >= 0) if (c == n) {
            while (b != n) iset[b] ^= 1, b = frm[b];
            return true;
        }
    }
    return false;
}
};
```

### 7.3 Matching

#### hopcroftKarp.h

**Description:** Fast bipartite matching algorithm. Graph  $g$  should be a list of neighbors of the left partition, and  $btoa$  should be a vector full of -1's of the same size as the right partition. Returns the size of the matching.  $btoa[i]$  will be the match for vertex  $i$  on the right side, or -1 if it's not matched.

**Usage:** vi btoa(m, -1); hopcroftKarp(g, btoa);

**Time:**  $\mathcal{O}(\sqrt{VE})$

```
bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A, vi& B) {
    if (A[a] != L) return 0;
    A[a] = -1;
    for (int b : g[a]) if (B[b] == L + 1) {
        B[b] = 0;
        if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A, B))
            return btoa[b] = a, 1;
    }
    return 0;
}

int hopcroftKarp(vector<vi>& g, vi& btoa) {
    int res = 0;
    vi A(g.size()), B(btoa.size()), cur, next;
    for (;;) {
        fill(all(A), 0);
        fill(all(B), 0);
        cur.clear();
        for (int a : btoa) if (a != -1) A[a] = -1;
        rep(a,0,sz(g)) if(A[a] == 0) cur.push_back(a);
        for (int lay = 1;; lay++) {
            bool islast = 0;
            next.clear();
            for (int a : cur) for (int b : g[a]) {
                if (btoa[b] == -1) {
                    B[b] = lay;
                    islast = 1;
                }
            }
            else if (btoa[b] != a && !B[b]) {
                B[b] = lay;
                next.push_back(btoa[b]);
            }
        }
        if (islast) break;
        if (next.empty()) return res;
        for (int a : next) A[a] = lay;
        cur.swap(next);
    }
    rep(a,0,sz(g))
        res += dfs(a, 0, g, btoa, A, B);
}
};
```

#### DFSMatching.h

**Description:** Maximum bipartite matching algorithm. Graph  $g$  should be a list of neighbors of the left partition, and  $btoa$  should be a vector full of -1's of the same size as the right partition. Returns the size of the matching.  $btoa[i]$  will be the match for vertex  $i$  on the right side, or -1 if it's not matched.

**Usage:** vi btoa(m, -1); dfsMatching(g, btoa);

**Time:**  $\mathcal{O}(VE)$

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
    if (btoa[j] == -1) return 1;
    vis[j] = 1; int di = btoa[j];
    for (int e : g[di])
        if (!vis[e] && find(e, g, btoa, vis)) {
            btoa[e] = di; return 1;
        }
    return 0;
}

int dfsMatching(vector<vi>& g, vi& btoa) {
    vi vis;
    rep(i,0,sz(g)) {
        vis.assign(sz(btoa), 0);
        for (int j : g[i])
            if (find(j, g, btoa, vis)) {
                btoa[j] = i; break;
            }
    }
    return sz(btoa) - (int)count(all(btoa), -1);
}
```

#### MinimumVertexCover.h

**Description:** Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

```
"DFSMatching.h"
da4196, 20 lines

vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = dfsMatching(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    vi q, cover;
    rep(i,0,n) if (!lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1) {
            seen[e] = true;
            q.push_back(match[e]);
        }
    }
    rep(i,0,n) if (!lfound[i]) cover.push_back(i);
    rep(i,0,m) if (seen[i]) cover.push_back(n+i);
    assert(sz(cover) == res);
    return cover;
}
```

#### WeightedMatching.h

**Description:** Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j] and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires  $N \leq M$ .

**Time:**  $\mathcal{O}(N^2M)$

```
pair<int, vi> hungarian(const vector<vi> &a) {
    if (a.empty()) return {0, {}};
    int n = sz(a) + 1, m = sz(a[0]) + 1;
    vi u(n), v(m), p(m), ans(n - 1);
    rep(i,1,n) {
```

```
p[0] = i;
int j0 = 0; // add "dummy" worker 0
vi dist(m, INT_MAX), pre(m, -1);
vector<bool> done(m + 1);
do { // dijkstra
    done[j0] = true;
    int i0 = p[j0], j1, delta = INT_MAX;
    rep(j,1,m) if (!done[j]) {
        auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
        if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
        if (dist[j] < delta) delta = dist[j], j1 = j;
    }
    rep(j,0,m) {
        if (done[j]) u[p[j]] += delta, v[j] -= delta;
        else dist[j] -= delta;
    }
    j0 = j1;
} while (p[j0]);
while (j0) { // update alternating path
    int j1 = pre[j0];
    p[j0] = p[j1], j0 = j1;
}
}
rep(j,1,m) if (p[j]) ans[p[j] - 1] = j - 1;
return {-v[0], ans}; // min cost
}
```

GeneralMatching.h  
Description: Matching for general graphs. Fails with probability  $N/mod$ .  
Time:  $\mathcal{O}(N^3)$

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
    vector<vector<ll>> mat(N, vector<ll>(N)), A;
    for (pii pa : ed) {
        int a = pa.first, b = pa.second, r = rand() % mod;
        mat[a][b] = r, mat[b][a] = (mod - r) % mod;
    }

    int r = matInv(A = mat), M = 2*N - r, fi, fj;
    assert(r % 2 == 0);

    if (M != N) do {
        mat.resize(M, vector<ll>(M));
        rep(i,0,N) {
            mat[i].resize(M);
            rep(j,N,M) {
                int r = rand() % mod;
                mat[i][j] = r, mat[j][i] = (mod - r) % mod;
            }
        }
    } while (matInv(A = mat) != M);

    vi has(M, 1); vector<pii> ret;
    rep(it,0,M/2) {
        rep(i,0,M) if (has[i])
            rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
                fi = i; fj = j; goto done;
            }
        assert(0); done:
        if (fj < N) ret.emplace_back(fi, fj);
        has[fi] = has[fj] = 0;
        rep(sw,0,2) {
            ll a = modpow(A[fi][fj], mod-2);
            rep(i,0,M) if (has[i] && A[i][fj]) {
                ll b = A[i][fj] * a % mod;
                rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
            }
            swap(fi, fj);
        }
    }
}
```

```
return ret;
}

7.4 DFS algorithms
SCC.h
Description: Finds strongly connected components in a directed graph. If
vertices  $u, v$  belong to the same component, we can reach  $u$  from  $v$  and vice
versa.
Usage: scc(graph, [&](vi& v) { ... }) visits all components
in reverse topological order. comp[i] holds the component
index of a node (a component only has edges to components with
lower index). ncomps will contain the number of components.
Time:  $\mathcal{O}(E + V)$ 
```

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ?: dfs(e,g,f));

    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncomps++;
    }
    return val[j] = low;
}

template<class G, class F> void scc(G& g, F f) {
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BCCs.h  
Description: Finds all biconnected components in an undirected graph, and
runs a callback for the edges in each. In a biconnected component there are
at least two distinct paths between any two nodes. Note that a node can be
in several components. An edge which is not in a component is a bridge, i.e.,
not part of any cycle.
Usage: int eid = 0; ed.resize(N);
for each edge (a,b) {
 ed[a].emplace\_back(b, eid);
 ed[b].emplace\_back(a, eid++);
}
bicomps([&](const vi& edgelist) {...});
Time:  $\mathcal{O}(E + V)$

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, top = me;
    for (auto [y, e] : ed[at]) if (e != par) {
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me)
                st.push_back(e);
        } else {
            int si = sz(st);
            int up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
            }
        }
    }
}
```

```
f(vi(st.begin() + si, st.end()));
st.resize(si);
}
else if (up < me) st.push_back(e);
else { /* e is a bridge */
}
}
return top;
}

template<class F>
void bicomps(F f) {
    num.assign(sz(ed), 0);
    rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

ArticulationPoints.h  
Description: Finds the articulation points in a graph  
Time:  $\mathcal{O}(N + M)$

```
int n;
vector<vector<int>> adj;
vector<bool> visited;
vector<int> tin, low;
int timer;
void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = low[v] = timer++;
    int children = 0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            low[v] = min(low[v], tin[to]);
        } else {
            dfs(to, v);
            low[v] = min(low[v], low[to]);
            if (low[to] >= tin[v] && p!=-1)
                // V IS A CUTPOINT;
            ++children;
        }
    }
    if(p == -1 && children > 1) // V IS A CUTPOINT;
}

void findAP() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    low.assign(n, -1);
    for (int i = 0; i < n; ++i)
        if (!visited[i]) dfs (i);
}
```

2sat.h  
Description: Calculates a valid assignment to boolean variables a,
b, c,... to a 2-SAT problem, so that an expression of the type
 $(a||b)&&(!a||c)&&(d||b)&&...$  becomes true, or reports that it is unsatis-
fiable. Negated variables are represented by bit-inversions (~x).
Usage: TwoSat ts(number of boolean variables);
ts.either(0, ~3); // Var 0 is true or var 3 is false
ts.setValue(2); // Var 2 is true
ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true
ts.solve(); // Returns true iff it is solvable
ts.values[0..N-1] holds the assigned values to the vars
Time:  $\mathcal{O}(N + E)$ , where N is the number of boolean variables, and E is the
number of clauses.

```
struct TwoSat {
    int N;
    vector<vi> gr;
```

```
vi values; // 0 = false, 1 = true
TwoSat(int n = 0) : N(n), gr(2*n) {}
int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
}
void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
}
void setValue(int x) { either(x, x); }
void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
        int next = addVar();
        either(cur, ~li[i]);
        either(cur, next);
        either(~li[i], next);
        cur = ~next;
    }
    either(cur, ~li[1]);
}
vi val, comp, z; int time = 0;
int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
        low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
        x = z.back(); z.pop_back();
        comp[x] = low;
        if (values[x>>1] == -1)
            values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
}
bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
}
};
```

EulerWalk.h

**Description:** Eulerian undirected/directed path/cycle algorithm. (visits every edge once) Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

**Time:**  $\mathcal{O}(V + E)$

a07095, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nEdges, int src) {
    int n = sz(gr);
    vi D(n), its(n), eu(nEdges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
        if (it == end){ ret.push_back(x); s.pop_back(); continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back(y);
        }
    }
}
```

```
for (int x : D) if (x < 0 || sz(ret) != nEdges+1) return {};
return {ret.rbegin(), ret.rend()};
}
```

DominatorTree.h

**Description:** Builds a dominator tree on a directed graph. Output tree is a parent array with src as the root.

**Time:**  $\mathcal{O}(V + E)$

1d35d2, 46 lines

```
vi getDomTree(vvi &adj, int src) {
    int n = sz(adj), t = 0;
    vvi revAdj(n), child(n), sdomChild(n);
    vi label(n, -1), revLabel(n), sdom(n), idom(n), par(n), best(n);

    auto dfs = [&](int cur, auto &dfs) -> void {
        label[cur] = t, revLabel[t] = cur;
        sdom[t] = par[t] = best[t] = t; t++;
        for(int nxt: adj[cur]) {
            if(label[nxt] == -1) {
                dfs(nxt, dfs);
                child[label[cur]].push_back(label[nxt]);
            }
            revAdj[label[nxt]].push_back(label[cur]);
        }
    };
    dfs(src, dfs);

    auto get = [&](int x, auto &get) -> int {
        if(par[x] != x) {
            int t = get(par[x], get);
            par[x] = par[par[x]];
            if(sdom[t] < sdom[best[x]]) best[x] = t;
        }
        return best[x];
    };
}
```

```
for(int i = t-1; i >= 0; i--) {
    for(int j: revAdj[i]) sdom[i] = min(sdom[i], sdom[get(j, get)]);
    if(i > 0) sdomChild[sdom[i]].push_back(i);
    for(int j: sdomChild[i]) {
        int k = get(j, get);
        if(sdom[j] == sdom[k]) idom[j] = sdom[j];
        else idom[j] = k;
    }
    for(int j: child[i]) par[j] = i;
}

vi dom(n);
rep(i, 1, t) {
    if(idom[i] != sdom[i]) idom[i] = idom[idom[i]];
    dom[revLabel[i]] = revLabel[idom[i]];
}

return dom;
}
```

7.5 Coloring

EdgeColoring.h

**Description:** Given a simple, undirected graph with max degree  $D$ , computes a  $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. ( $D$ -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

**Time:**  $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
}
```

```
int u, v, ncols = *max_element(all(cc)) + 1;
vector<vi> adj(N, vi(ncols, -1));
for (pii e : eds) {
    tie(u, v) = e;
    fan[0] = v;
    loc.assign(ncols, 0);
    int at = u, end = u, d, c = free[u], ind = 0, i = 0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
        loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
        swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
        int left = fan[i], right = fan[++i], e = cc[i];
        adj[u][e] = left;
        adj[left][e] = u;
        adj[right][e] = -1;
        free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : {fan[0], u, end})
        for (int& z = free[y] = 0; adj[y][z] != -1; z++);
}
rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
return ret;
}
```

7.6 Heuristics

MaximalCliques.h

**Description:** Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

**Time:**  $\mathcal{O}\left(3^{n/3}\right)$ , much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h

**Description:** Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

**Time:** Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    }
}
```

```
sort(all(r), [](auto a, auto b) { return a.d > b.d; });
int mxD = r[0].d;
rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
}

void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
        if (sz(q) + R.back().d <= sz(qmax)) return;
        q.push_back(R.back().i);
        vv T;
        for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
        if (sz(T)) {
            if (S[lev]++ / ++pk < limit) init(T);
            int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
            C[1].clear(), C[2].clear();
            for (auto v : T) {
                int k = 1;
                auto f = [&](int i) { return e[v.i][i]; };
                while (any_of(all(C[k]), f)) k++;
                if (k > mxk) mxk = k, C[mxk + 1].clear();
                if (k < mnk) T[j++].i = v.i;
                C[k].push_back(v.i);
            }
            if (j > 0) T[j - 1].d = 0;
            rep(k,mnk,mxk + 1) for (int i : C[k])
                T[j].i = i, T[j++].d = k;
            expand(T, lev + 1);
        } else if (sz(q) > sz(qmax)) qmax = q;
        q.pop_back(), R.pop_back();
    }
}

vi maxClique() { init(V), expand(V); return qmax; }
MaxClique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
}
}
```

MaximumIndependentSet.h

**Description:** To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertex-Cover.

7.7 Trees

7.7.1 Number of Spanning Trees

Create an  $N \times N$  matrix  $\text{mat}$ , and for each edge  $a \rightarrow b \in G$ , do  $\text{mat}[a][b]--$ ,  $\text{mat}[b][b]++$  (and  $\text{mat}[b][a]--$ ,  $\text{mat}[a][a]++$  if  $G$  is undirected). Remove the  $i$ th row and column and take the determinant; this yields the number of directed spanning trees rooted at  $i$  (if  $G$  is undirected, remove any row/column).

7.7.2 Erdős–Gallai theorem

A simple graph with node degrees  $d_1 \geq \dots \geq d_n$  exists iff  $d_1 + \dots + d_n$  is even and for every  $k = 1 \dots n$ ,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

BinaryLifting.h

**Description:** Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.

**Time:** construction  $\mathcal{O}(N \log N)$ , queries  $\mathcal{O}(\log N)$

```
vector<vi> treeJump(vi& P){
    int on = 1, d = 1;
    while(on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i,1,d) rep(j,0,sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
    rep(i,0,sz(tbl))
        if(steps&(1<<i)) nod = tbl[i][nod];
    return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
    if (depth[a] < depth[b]) swap(a, b);
    a = jmp(tbl, a, depth[a] - depth[b]);
    if (a == b) return a;
    for (int i = sz(tbl); i--;) {
        int c = tbl[i][a], d = tbl[i][b];
        if (c != d) a = c, b = d;
    }
    return tbl[0][a];
}
```

KthPath.h

**Description:** kth on path, goes in tree.lift

**Time:**  $\mathcal{O}(\log N)$

```
int kth_path(int u, int v, int k) {
    int lca_d = t[lca(u, v)].d;
    int u_lca = t[u].d - lca_d;
    int v_lca = t[v].d - lca_d;
    if (k <= u_lca) return kth_par(u, k);
    if (k <= u_lca + v_lca)
        return kth_par(v, u_lca + v_lca - k);
    return -1;
}
```

CompressTree.h

**Description:** Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most  $|S| - 1$ ) pairwise LCA's and compressing edges. Returns a list of (par, orig\_index) representing a tree rooted at 0. The root points to itself.

**Time:**  $\mathcal{O}(|S| \log |S|)$

```
"LCA.h"
9775a0, 21 lines

typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i,0,m) {
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    }
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i,0,sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i,0,sz(li)-1) {
        int a = li[i], b = li[i+1];
```

```
ret.emplace_back(rev[lca.lca(a, b)], b);
    }
    return ret;
}
```

CentroidDecomp.h

**Description:** Calls callback function on undirected forest for each centroid

**Usage:** centroid(adj, [&](const vector<vector<int>>& adj, int cent) { ... });

**Time:**  $\mathcal{O}(n \log n)$

```
template <class F, class G> struct centroid {
    G adj;
    F f;
    vi sub_sz, par;
    centroid(const G& adj, F f)
        : adj(adj), f(f), sub_sz(sz(adj), -1), par(sz(adj), -1) {
        rep(i, 0, sz(adj))
            if (sub_sz[i] == -1) dfs(i);
    }
    void calc_sz(int u, int p) {
        sub_sz[u] = 1;
        for (int v : adj[u])
            if (v != p) calc_sz(v, u), sub_sz[u] += sub_sz[v];
    }
    int dfs(int u) {
        calc_sz(u, -1);
        for (int p = -1, sz_root = sub_sz[u];;) {
            auto big_ch = find_if(all(adj[u]), [&](int v) {
                return v != p && 2 * sub_sz[v] > sz_root;
            });
            if (big_ch == end(adj[u])) break;
            p = u, u = *big_ch;
        }
        f(adj, u);
        for (int v : adj[u]) {
            iter_swap(find(all(adj[v]), u), rbegin(adj[v]));
            adj[v].pop_back();
            par[dfs(v)] = u;
        }
        return u;
    }
};
```

EdgeCD.h

**Description:** Recursively splits a tree into two edge sets that share a centroid. Consider all paths that pass through the centroid and use at least one edge from each set. A node can be a centroid multiple times. Consider all length 1 paths separately. Callback takes the graph, centroid, and split, where edges  $[0, \textit{split})$  from  $\textit{adj}[\textit{centroid}]$  are in the first set and the rest are in the second set.

**Usage:** edge\_cd(adj, [&](const vector<vector<int>>& adj, int cent, int split) { ... });

**Time:**  $\mathcal{O}(n \log n)$

```
template <class F> struct edge_cd {
    vvi adj;
    F f;
    vi sub_sz;
    edge_cd(const vvi& adj, F f) : adj(adj), f(f),
        sub_sz(sz(adj)) {
        dfs(0, sz(adj) - 1);
    }
    int find_cent(int u, int p, int siz) {
        sub_sz[u] = 1;
        for (int v : adj[u]) if (v != p) {
            int cent = find_cent(v, u, siz);
            if (cent != -1) return cent;
            sub_sz[u] += sub_sz[v];
        }
```

```

    }
    return 2 * sub_sz[u] > siz ?
        p >= 0 && (sub_sz[p] = siz + 1 - sub_sz[u]), u : -1;
}
void dfs(int u, int siz) {
    if (siz < 2) return;
    u = find_cent(u, -1, siz);
    int sum = 0;
    auto it = partition(all(adj[u]), [&](int v) {
        ll x = sum + sub_sz[v];
        return x * x < siz * (siz - x) ? sum += sub_sz[v], 1 : 0;
    });
    f(adj, u, it - begin(adj[u]));
    vi oth(it, end(adj[u]));
    adj[u].erase(it, end(adj[u]));
    dfs(u, sum);
    swap(adj[u], oth);
    dfs(u, siz - sum);
}
};

```

## HLD.h

**Description:** Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most  $\log(n)$  light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS\_EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.

**Usage:** Maximum Values on path from any two arbitrary nodes

For node to root, use Euler Tour

**Time:**  $\mathcal{O}((\log N)^2)$

"../data-structures/LazySegmentTree.h" 9547af, 46 lines

```

template <bool VALS_EDGES> struct HLD {
    int N, tim = 0;
    vector<vi> adj;
    vi par, siz, rt, pos;
    Node *tree;
    HLD(vector<vi> adj_)
        : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
          rt(N), pos(N), tree(new Node(0, N)) { dfsSz(0); dfsHld(0); }
    void dfsSz(int v) {
        for (int& u : adj[v]) {
            adj[u].erase(find(all(adj[u]), v));
            par[u] = v;
            dfsSz(u);
            siz[v] += siz[u];
            if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
        }
    }
    void dfsHld(int v) {
        pos[v] = tim++;
        for (int u : adj[v]) {
            rt[u] = (u == adj[v][0] ? rt[v] : u);
            dfsHld(u);
        }
    }
    template <class B> void process(int u, int v, B op) {
        for (; v = par[rt[v]]) {
            if (pos[u] > pos[v]) swap(u, v);
            if (rt[u] == rt[v]) break;
            op(pos[rt[v]], pos[v] + 1);
        }
        op(pos[u] + VALS_EDGES, pos[v] + 1);
    }
    void modifyPath(int u, int v, int val) {
        process(u, v, [&](int l, int r) { tree->add(l, r, val); });
    }
    int queryPath(int u, int v) { // Modify depending on problem

```

## HLD LinkCutTree DirectedMST

```

    int res = -1e9;
    process(u, v, [&](int l, int r) {
        res = max(res, tree->query(l, r));
    });
    return res;
}
int querySubtree(int v) { // modifySubtree is similar
    return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
}
};

```

## LinkCutTree.h

**Description:** Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

**Time:** All operations take amortized  $\mathcal{O}(\log N)$ .

0fb462, 90 lines

```

struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
        if (c[1]) c[1]->p = this;
        // (+ update sum of subtree elements etc. if wanted)
    }
    void pushFlip() {
        if (!flip) return;
        flip = 0; swap(c[0], c[1]);
        if (c[0]) c[0]->flip ^= 1;
        if (c[1]) c[1]->flip ^= 1;
    }
    int up() { return p ? p->c[1] == this : -1; }
    void rot(int i, int b) {
        int h = i ^ b;
        Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
        if ((y->p = p)) p->c[up()] = y;
        c[i] = z->c[i ^ 1];
        if (b < 2) {
            x->c[h] = y->c[h ^ 1];
            y->c[h ^ 1] = x;
        }
        z->c[i ^ 1] = this;
        fix(); x->fix(); y->fix();
        if (p) p->fix();
        swap(pp, y->pp);
    }
    void splay() {
        for (pushFlip(); p; ) {
            if (p->p) p->p->pushFlip();
            p->pushFlip(); pushFlip();
            int c1 = up(), c2 = p->up();
            if (c2 == -1) p->rot(c1, 2);
            else p->p->rot(c2, c1 != c2);
        }
    }
    Node* first() {
        pushFlip();
        return c[0] ? c[0]->first() : (splay(), this);
    }
};

struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}

    void link(int u, int v) { // add an edge (u, v)
        assert(!connected(u, v));
        makeRoot(&node[u]);

```

```

        node[u].pp = &node[v];
    }
    void cut(int u, int v) { // remove an edge (u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {
            x->c[0] = top->p = 0;
            x->fix();
        }
    }
    bool connected(int u, int v) { // are u, v in the same tree?
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    }
    void makeRoot(Node* u) {
        access(u);
        u->splay();
        if (u->c[0]) {
            u->c[0]->p = 0;
            u->c[0]->flip ^= 1;
            u->c[0]->pp = u;
            u->c[0] = 0;
            u->fix();
        }
    }
    Node* access(Node* u) {
        u->splay();
        while (Node* pp = u->pp) {
            pp->splay(); u->pp = 0;
            if (pp->c[1]) {
                pp->c[1]->p = 0; pp->c[1]->pp = pp;
                pp->c[1] = u; pp->fix(); u = pp;
            }
            return u;
        }
    }
};

```

## DirectedMST.h

**Description:** Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

**Time:**  $\mathcal{O}(E \log V)$

"../data-structures/UnionFindRollback.h" 39e620, 60 lines

```

struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b : a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
    RollbackUF uf(n);
    vector<Node*> heap(n);

```



```

for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
ll res = 0;
vi seen(n, -1), path(n), par(n);
seen[r] = r;
vector<Edge> Q(n), in(n, {-1,-1}), comp;
deque<tuple<int, int, vector<Edge>>> cycs;
rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
        if (!heap[u]) return {-1,{};};
        Edge e = heap[u]->top();
        heap[u]->delta -= e.w, pop(heap[u]);
        Q[qi] = e, path[qi++] = u, seen[u] = s;
        res += e.w, u = uf.find(e.a);
        if (seen[u] == s) {
            Node* cyc = 0;
            int end = qi, time = uf.time();
            do cyc = merge(cyc, heap[w = path[--qi]]);
            while (uf.join(u, w));
            u = uf.find(u), heap[u] = cyc, seen[u] = -1;
            cycs.push_front({u, time, {&Q[qi], &Q[end]});
        }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
}

for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
}
rep(i,0,n) par[i] = in[i].a;
return {res, par};
}

```

## Geometry (8)

### 8.1 Geometric primitives

#### Point.h

**Description:** Class to handle points in the plane. T can be e.g. ld or long long. (Avoid int.)

```

template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct P {
    T x, y;
    explicit P(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    ld dist() const { return sqrt((ld)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    ld angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist()==1
    P perp() const { return P(-y, x); } // rotates +90 degrees
    P normal() const { return perp().unit(); }
    // returns point rotated 'a' RADIANS ccw around the origin
    P rotate(ld a) const { return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
}

```

```

friend ostream& operator<<(ostream& os, P p) { return os << "
    (" << p.x << ", " << p.y << ")"; }
};

```

#### lineDistance.h

##### Description:

Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.

```

"Point.h" f6bf6b, 4 lines
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a)/(b-a).dist();
}

```

#### LineProjectionReflection.h

**Description:** Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

```

"Point.h" b5562d, 5 lines
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}

```

#### inAngle.h

**Description:** Returns true if p is in the angle between b and c. The angle starts at point a (b and c are endpoints). The angle is assumed to be at most 180 and the points are not colinear. Modify equals sign for exclusive inAngle check.

```

"sideOf.h", "Point.h" 7131bb, 6 lines
bool inAngle(P a, P b, P c, P p)
{
    assert(sideOf(a, c, b) != 0);
    if (sideOf(a, c, b) < 0) swap(b, c);
    return sideOf(a, p, b) >= 0 && sideOf(a, p, c) <= 0;
}

```

#### Angle.h

**Description:** A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

**Usage:** vector<Angle> v = {w[0], w[0].t360() ...}; // sorted  
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }  
// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i

```

struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
};

```

```

bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
        make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

```

*// Given two points, this calculates the smallest angle between them, i.e., the angle that covers the defined line segment.*

```

pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180() ?
        make_pair(a, b) : make_pair(b, a.t360()));
}

```

```

Angle operator+(Angle a, Angle b) { // point a + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}

Angle angleDiff(Angle a, Angle b) { // angle b - angle a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}

```

#### polarSort.h

**Description:** Sorts vectors radially based on angles [0, 2pi). For parallel vectors, larger magnitude come later.

```

"Point.h" c5aa4b, 13 lines
template<typename T>
bool half(const P<T> &p) {
    // DO NOT INCLUDE (0, 0)
    assert(p.x != 0 || p.y != 0);
    return p.y < 0 || (p.y == 0 && p.x < 0);
    // Use if you want the polar sort to start from Point V
    // return cross(v,p) < 0 || (cross(v,p) == 0 && dot(v,p) < 0);
}

```

```

template<typename T>
bool comp(const P<T> &p, const P<T> &q) {
    return half(p) == half(q) ? cross(p, q) > 0 : half(p) <
        half(q);
}

```

#### lineSort.h

**Description:** Sorts points on a line s->e (or from their projections / parallel intersections) s and e represent the line we are comparing to

```

"Point.h" e353fa, 4 lines
bool cmpProj(P p, P q) {
    P v = e - s;
    return v.dot(p - s) < v.dot(q - s);
}

```

### 8.2 Lines and Segments

#### sideOf.h

**Description:** Returns where p is as seen from s towards e. 1/0/-1 ⇔ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

**Usage:** bool left = sideOf(p1,p2,q)==1;

```

"Point.h" 3af81c, 9 lines
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

```

```

template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {

```



```

auto a = (e-s).cross(p-s);
double l = (e-s).dist()*eps;
return (a > l) - (a < -l);
}

```

## OnSegment.h

**Description:** Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p) <= epsilon) instead when using Point<double>.

```

"Point.h"                                     c597e8, 3 lines

template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}

```

## lineIntersection.h

**Description:**

If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.

**Usage:** auto res = lineInter(s1,e1,s2,e2);

if (res.first == 1)


cout << "intersection point at " << res.second << endl;

```

"Point.h"                                     a01f81, 8 lines

template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)};
    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
}

```



## linearTransformation.h

**Description:**


Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.

```

"Point.h"                                     03a306, 6 lines

typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}

```



## SegmentDistance.h

**Description:**

Returns the shortest distance between point p and the line segment from point s to e. For SEGMENT-SEGMENT DISTANCE, check for intersection. If there is no intersection, the closest distance is between one of the four points and the other segment.


**Usage:** Point<double> a, b(2,2), p(1,1);  
bool onSegment = segDist(a,b,p) < 1e-10;

```

"Point.h"                                     5c88f4, 6 lines

typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0, (p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}

```



## SegmentIntersection.h

**Description:**

If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.

**Usage:** vector<P> inter = segInter(s1,e1,s2,e2);

if (sz(inter)==1)


cout << "segments intersect at " << inter[0] << endl;

```

"Point.h", "OnSegment.h"                     9d57f2, 13 lines

template<class P> vector<P> segInter(P a, P b, P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
    if (onSegment(a, b, d)) s.insert(d);
    return {all(s)};
}

```



## 8.3 Circles

### Circle-Circle-Intersection.h

**Description:** Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

```

"Point.h"                                     84d6d3, 11 lines

typedef Point<double> P;
bool circleInter(P a, P b, double r1, double r2, pair<P, P>*
    out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
}

```

### CircleTangents.h

**Description:** Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents - 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

```

"Point.h"                                     b0153d, 14 lines

template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    // r2 = -r2 // Use for inner tangents
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
}

```

```

return out;
}

```

## CircleLine.h

**Description:** Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.

```

"Point.h"                                     e0cfba, 9 lines

template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
    P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
    double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    P h = ab.unit() * sqrt(h2);
    return {p - h, p + h};
}

```

## CirclePolygonIntersection.h

**Description:** Returns the area of the intersection of a circle with a ccw polygon.

**Time:**  $\mathcal{O}(n)$

```

"../content/geometry/Point.h"               19add1, 19 lines


typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = q + d * (t-1);
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
    };
    auto sum = 0.0;
    rep(i,0,sz(ps))
        sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
    return sum;
}

```

## circumcircle.h

**Description:**

The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



```

"Point.h"                                     1caa3a, 9 lines

typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist() /
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}

```

## MinimumEnclosingCircle.h

**Description:** Computes the minimum circle that encloses a set of points.

**Time:** expected  $\mathcal{O}(n)$

```

"circumcircle.h"                             09dd0a, 17 lines

pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
}

```

```
P o = ps[0];
double r = 0, EPS = 1 + 1e-8;
rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
    o = ps[i], r = 0;
    rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
        o = (ps[i] + ps[j]) / 2;
        r = (o - ps[i]).dist();
        rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
            o = ccCenter(ps[i], ps[j], ps[k]);
            r = (o - ps[i]).dist();
        }
    }
}
return {o, r};
}
```

## 8.4 Polygons

**InsidePolygon.h**  
**Description:** Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.  
**Usage:** vector<P> v = {P{4,4}, P{1,2}, P{2,1}};  
bool in = inPolygon(v, P{3, 3}, false);  
**Time:**  $\mathcal{O}(n)$

```
"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = sz(p);
    rep(i,0,n) {
        P q = p[(i + 1) % n];
        if (onSegment(p[i], q, a)) return !strict;
        //or: if (segDist(p[i], q, a) <= eps) return !strict;
        cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
    }
    return cnt;
}
```

### PolygonArea.h

**Description:** Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

```
"Point.h" f12300, 6 lines

template<class T>
T polygonArea2(vector<Point<T>>& v) {
    T a = v.back().cross(v[0]);
    rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
    return a;
}
```

### triangleArea.h

**Description:** Finds the area of a triangle

```
f20dcb, 3 lines

ld triangleArea(P a, P b, P c) {
    return abs((b-a).cross(c-a)) / (ld)(2);
}
```

### PolygonCenter.h

**Description:** Returns the center of mass for a polygon.  
**Time:**  $\mathcal{O}(n)$

```
"Point.h" 9706dc, 9 lines

typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

```
}

PolygonCut.h
Description:
Returns a vector with the vertices of a polygon with every-
thing to the left of the line going from s to e cut away.
Usage: vector<P> p = ...;
p = polygonCut(p, P(0,0), P(1,0));
"Point.h" d07181, 13 lines

typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back();
        auto a = s.cross(e, cur), b = s.cross(e, prev);
        if ((a < 0) != (b < 0))
            res.push_back(cur + (prev - cur) * (a / (a - b)));
        if (a < 0)
            res.push_back(cur);
    }
    return res;
}
```

### PolygonUnion.h

**Description:** Calculates the area of the union of  $n$  polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed).  
**Time:**  $\mathcal{O}(N^2)$ , where  $N$  is the total number of points

```
"Point.h", "sideOf.h" 3931c6, 33 lines

typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
    double ret = 0;
    rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
        P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];
        vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
        rep(j,0,sz(poly)) if (i != j) {
            rep(u,0,sz(poly[j])) {
                P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];
                int sc = sideOf(A, B, C), sd = sideOf(A, B, D);
                if (sc != sd) {
                    double sa = C.cross(D, A), sb = C.cross(D, B);
                    if (min(sc, sd) < 0)
                        segs.emplace_back(sa / (sa - sb), sgn(sc - sd));
                } else if (!sc && !sd && j<i && sgn((B-A).dot(D-C))>0) {
                    segs.emplace_back(rat(C - A, B - A), 1);
                    segs.emplace_back(rat(D - A, B - A), -1);
                }
            }
        }
    }
    sort(all(segs));
    for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
    double sum = 0;
    int cnt = segs[0].second;
    rep(j,1,sz(segs)) {
        if (!cnt) sum += segs[j].first - segs[j - 1].first;
        cnt += segs[j].second;
    }
    ret += A.cross(B) * sum;
    return ret / 2;
}
```

### PolygonCut.h

**Description:**  
Returns a vector with the vertices of a polygon with every-  
thing to the left of the line going from s to e cut away.  
**Usage:** vector<P> p = ...;  
p = polygonCut(p, P(0,0), P(1,0));

```
"Point.h" d07181, 13 lines

typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back();
        auto a = s.cross(e, cur), b = s.cross(e, prev);
        if ((a < 0) != (b < 0))
            res.push_back(cur + (prev - cur) * (a / (a - b)));
        if (a < 0)
            res.push_back(cur);
    }
    return res;
}
```

### PolygonUnion.h

**Description:** Calculates the area of the union of  $n$  polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed).  
**Time:**  $\mathcal{O}(N^2)$ , where  $N$  is the total number of points

```
"Point.h", "sideOf.h" 3931c6, 33 lines

typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
    double ret = 0;
    rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
        P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];
        vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
        rep(j,0,sz(poly)) if (i != j) {
            rep(u,0,sz(poly[j])) {
                P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];
                int sc = sideOf(A, B, C), sd = sideOf(A, B, D);
                if (sc != sd) {
                    double sa = C.cross(D, A), sb = C.cross(D, B);
                    if (min(sc, sd) < 0)
                        segs.emplace_back(sa / (sa - sb), sgn(sc - sd));
                } else if (!sc && !sd && j<i && sgn((B-A).dot(D-C))>0) {
                    segs.emplace_back(rat(C - A, B - A), 1);
                    segs.emplace_back(rat(D - A, B - A), -1);
                }
            }
        }
    }
    sort(all(segs));
    for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
    double sum = 0;
    int cnt = segs[0].second;
    rep(j,1,sz(segs)) {
        if (!cnt) sum += segs[j].first - segs[j - 1].first;
        cnt += segs[j].second;
    }
    ret += A.cross(B) * sum;
    return ret / 2;
}
```

### HalfplaneIntersection.h

**Description:** Returns the intersection of halfplanes as a polygon  
**Time:**  $\mathcal{O}(n \log n)$

```
b9fb0f, 38 lines

const double eps = 1e-8;
typedef Point<double> P;
struct HalfPlane {
    P s, e, d;
    HalfPlane(P s = P(), P e = P()): s(s), e(e), d(e - s) {}
    bool contains(P p) { return d.cross(p - s) > -eps; }
    bool side() { return d.x<-eps || (abs(d.x)<=eps && d.y>0); }
    bool operator<(HalfPlane hp) {
        if(side() != hp.side()) return side();
        return d.cross(hp.d) > 0;
    }
}
P inter(HalfPlane hp) {
    auto p = hp.s.cross(e, hp.e), q = hp.s.cross(hp.e, s);
    return (s * p + e * q) / d.cross(hp.d);
}

vector<P> hpIntersection(vector<HalfPlane> hps) {
    sort(all(hps));
    int n = sz(hps), l = 1, r = 0;
    vector<HalfPlane> dq(n+1);
    rep(i, 0, n) {
        while(l<r && !hps[i].contains(dq[r].inter(dq[r-1]))) r--;
        while(l<r && !hps[i].contains(dq[l].inter(dq[l+1]))) l++;
        dq[++r] = hps[i];
        if(l < r && abs(dq[r].d.cross(dq[r-1].d)) < eps) {
            if(dq[r].d.dot(dq[r-1].d) < 0) return {};
            if(dq[--r].contains(hps[i].s)) dq[r] = hps[i];
        }
    }
    while(l<r-1 && !dq[l].contains(dq[r].inter(dq[r-1]))) r--;
    while(l<r-1 && !dq[r].contains(dq[l].inter(dq[l+1]))) l++;
    if(l > r-2) return {};
    vector<P> poly;
    rep(i, 1, r) poly.push_back(dq[i].inter(dq[i+1]));
    poly.push_back(dq[r].inter(dq[l]));
    return poly;
}
```

### ConvexHull.h

**Description:**  
Returns a vector of the points of the convex hull in counter-  
clockwise order. Points on the edge of the hull between two  
other points are not considered part of the hull.  
**Time:**  $\mathcal{O}(n \log n)$

```
"Point.h" e89ff2, 13 lines

typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(2*sz(pts)); // modified for cses hack
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
            h[++t] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```



### HullDiameter.h

**Description:** Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

**Time:**  $\mathcal{O}(n)$

"Point.h"	c571b8, 12 lines
<pre>typedef Point&lt;ll&gt; P; array&lt;P, 2&gt; hullDiameter(vector&lt;P&gt; S) {     int n = sz(S), j = n &lt; 2 ? 0 : 1;     pair&lt;ll, array&lt;P, 2&gt;&gt; res({0, {S[0], S[0]}});     rep(i,0,j)         for (; j = (j + 1) % n) {             res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});             if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) &gt;= 0)                 break;         }     return res.second; }</pre>	

### PointInsideHull.h

**Description:** Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

**Time:**  $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h"	4ef384, 14 lines
<pre>typedef Point&lt;ll&gt; P;  bool inHull(const vector&lt;P&gt;&amp; h, P p, bool strict = true) {     int a = 1, b = sz(h) - 1, r = !strict;     if (sz(h) &lt; 3) return r &amp;&amp; onSegment(h[0], h.back(), p);     if (sideOf(h[0], h[a], h[b]) &gt; 0) swap(a, b);     if (sideOf(h[0], h[a], p) &gt;= r    sideOf(h[0], h[b], p) &lt;= -r)         return false;     while (abs(a - b) &gt; 1) {         int c = (a + b) / 2;         (sideOf(h[0], h[c], p) &gt; 0 ? b : a) = c;     }     return sgn(h[a].cross(h[b], p)) &lt; r; }</pre>	

### ExtremeVertex.h

**Description:** returns the point of a hull with the max projection onto a line.

**Time:**  $\mathcal{O}(\log n)$

"Point.h"	ba41ca, 13 lines
<pre>#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n])) #define extr(i) cmp(i + 1, i) &gt;= 0 &amp;&amp; cmp(i, i - 1 + n) &lt; 0 template &lt;class P&gt; int extrVertex(vector&lt;P&gt;&amp; poly, P dir) {     int n = sz(poly), lo = 0, hi = n;     if (extr(0)) return m;     while (lo + 1 &lt; hi) {         int m = (lo + hi) / 2;         if (extr(m)) return m;         int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);         (ls &lt; ms    (ls == ms &amp;&amp; ls == cmp(lo, m)) ? hi : lo) = m;     }     return lo; }</pre>	

### LineHullIntersection.h

**Description:** Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon:  $\bullet(-1, -1)$  if no collision,  $\bullet(i, -1)$  if touching the corner  $i$ ,  $\bullet(i, i)$  if along side  $(i, i + 1)$ ,  $\bullet(i, j)$  if crossing sides  $(i, i + 1)$  and  $(j, j + 1)$ . In the last case, if a corner  $i$  is crossed, this is treated as happening on side  $(i, i + 1)$ . The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

**Time:**  $\mathcal{O}(\log n)$

"Point.h"	7cf45b, 39 lines
<pre>#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n])) #define extr(i) cmp(i + 1, i) &gt;= 0 &amp;&amp; cmp(i, i - 1 + n) &lt; 0 template &lt;class P&gt; int extrVertex(vector&lt;P&gt;&amp; poly, P dir) {     int n = sz(poly), lo = 0, hi = n;     if (extr(0)) return 0;     while (lo + 1 &lt; hi) {         int m = (lo + hi) / 2;         if (extr(m)) return m;         int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);         (ls &lt; ms    (ls == ms &amp;&amp; ls == cmp(lo, m)) ? hi : lo) = m;     }     return lo; }  #define cmpL(i) sgn(a.cross(poly[i], b)) template &lt;class P&gt; array&lt;int, 2&gt; lineHull(P a, P b, vector&lt;P&gt;&amp; poly) {     int endA = extrVertex(poly, (a - b).perp());     int endB = extrVertex(poly, (b - a).perp());     if (cmpL(endA) &lt; 0    cmpL(endB) &gt; 0)         return {-1, -1};     array&lt;int, 2&gt; res;     rep(i,0,2) {         int lo = endB, hi = endA, n = sz(poly);         while ((lo + 1) % n != hi) {             int m = ((lo + hi + (lo &lt; hi ? 0 : n)) / 2) % n;             (cmpL(m) == cmpL(endB) ? lo : hi) = m;         }         res[i] = (lo + !cmpL(hi)) % n;         swap(endA, endB);     }     if (res[0] == res[1]) return {res[0], -1};     if (!cmpL(res[0]) &amp;&amp; !cmpL(res[1]))         switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {             case 0: return {res[0], res[0]};             case 2: return {res[1], res[1]};         }     return res; }</pre>	

### HullTangents.h

**Description:** Finds the left and right, respectively, tangent points on convex hull from a point. If the point is colinear to side(s) of the polygon, the point further away is returned. Requires ccw,  $n \geq 3$ , and the point be on or outside the polygon. Can be used to check if a point is inside of a convex hull. Will return -1 if it is strictly inside. If the point is on the hull, the two adjacent points will be returned

**Time:**  $\mathcal{O}(\log n)$

"Point.h"	53d067, 16 lines
<pre>#define cmp(i, j) p.cross(h[i], h[j == n ? 0 : j]) * (R ? 1 : -1) template&lt;bool R, class P&gt; int getTangent(vector&lt;P&gt;&amp; h, P p) {     int n = sz(h), lo = 0, hi = n - 1, md;     if (cmp(0, 1) &gt;= R &amp;&amp; cmp(0, n - 1) &gt;= !R) return 0;     while (md = (lo + hi + 1) / 2, lo &lt; hi) {         auto a = cmp(md, md + 1), b = cmp(md, lo);         if (a &gt;= R &amp;&amp; cmp(md, md - 1) &gt;= !R) return md;         if (cmp(lo, lo + 1) &lt; R)             a &lt; R&amp;&amp; b &gt;= 0 ? lo = md : hi = md - 1;         else a &lt; R    b &lt;= 0 ? lo = md : hi = md - 1;     }     return -1; // point strictly inside hull }  template&lt;class P&gt; pii hullTangents(vector&lt;P&gt;&amp; h, P p) {     return {getTangent&lt;0&gt;(h, p), getTangent&lt;1&gt;(h, p)}; }</pre>	

### MinkowskiSum.h

**Description:** Returns the minkowski sum of a set of convex polygons

**Time:**  $\mathcal{O}(n \log n)$

```

#define side(p) (p.x > 0 || (p.x == 0 && p.y > 0))
template<class P>
vector<P> convolve(vector<vector<P>> &polys){
    P init; vector<P> dir;
    for(auto poly: polys) {
        int n = sz(poly);
        if(n) init = init + poly[0];
        if(n < 2) continue;
        rep(i, 0, n) dir.push_back(poly[(i+1)%n] - poly[i]);
    }
    if(size(dir) == 0) return { init };
    stable_sort(all(dir), [&](P a, P b)->bool {
        if(side(a) != side(b)) return side(a);
        return a.cross(b) > 0;
    });
    vector<P> sum; P cur = init;
    rep(i, 0, sz(dir))
        sum.push_back(cur), cur = cur + dir[i];
    return sum;
}

```

### lineTranslations.h

**Description:** Translates a line using a given translation vector u or given a distance dist

```
void vectorTransaltion (P &s, P &e, P u) {
    s += u; e+=u;
}

void shiftLeft (P &s, P &e, ld dist) {
    P v = e-s, n = P(-v.y, v.x);
    n = n * (dist / abs(n));
    s += u; e+=u;
}
```

## 8.5 Misc. Point Set Problems

### ClosestPair.h

**Description:** Finds the closest pair of points.

**Time:**  $\mathcal{O}(n \log n)$

"Point.h"	ac41a6, 17 lines
<pre>typedef Point&lt;ll&gt; P; pair&lt;P, P&gt; closest(vector&lt;P&gt; v) {     assert(sz(v) &gt; 1);     set&lt;P&gt; S;     sort(all(v), [](P a, P b) { return a.y &lt; b.y; });     auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);     for (; lo != hi; ++lo)         ret = min(ret, {(lo - p).dist2(), {lo, p}});     S.insert(p); } return ret.second; }</pre>	

### ManhattanMST.h

**Description:** Given N points, returns up to  $4*N$  edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights  $w(p, q) = -p.x - q.x - -p.y - q.y$ . Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST.

Time:  $\mathcal{O}(N \log N)$

"Point.h"

df6f59, 23 lines

```
typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
    vi id(sz(ps));
    iota(all(id), 0);
    vector<array<int, 3>> edges;
    rep(k,0,4) {
        sort(all(id), [&](int i, int j) {
            return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;});
        map<int, int> sweep;
        for (int i : id) {
            for (auto it = sweep.lower_bound(-ps[i].y);
                it != sweep.end(); sweep.erase(it++)) {
                int j = it->second;
                P d = ps[i] - ps[j];
                if (d.y > d.x) break;
                edges.push_back({d.y + d.x, i, j});
            }
            sweep[-ps[i].y] = i;
        }
        for (P& p : ps) if (k & 1) p.x = -p.x; else swap(p.x, p.y);
    }
    return edges;
}
```

kdTree.h

Description: KD-tree (2d, can be extended to 3d)

"Point.h"

bac5b0, 63 lines

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }
```

```
struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
    Node *first = 0, *second = 0;

    T distance(const P& p) { // min squared distance to a point
        T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
        T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
        return (P(x,y) - p).dist2();
    }

    Node(vector<P>&& vp) : pt(vp[0]) {
        for (P p : vp) {
            x0 = min(x0, p.x); x1 = max(x1, p.x);
            y0 = min(y0, p.y); y1 = max(y1, p.y);
        }
        if (vp.size() > 1) {
            // split on x if width >= height (not ideal...)
            sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
            // divide by taking half the array for each child (not
            // best performance with many duplicates in the middle)
            int half = sz(vp)/2;
            first = new Node({vp.begin(), vp.begin() + half});
            second = new Node({vp.begin() + half, vp.end()});
        }
    }
};

struct KDTree {
    Node* root;
    KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}
};
```

```
pair<T, P> search(Node *node, const P& p) {
    if (!node->first) {
        // uncomment if we should not find the point itself:
        // if (p == node->pt) return {INF, P()};
        return make_pair((p - node->pt).dist2(), node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
        best = min(best, search(s, p));
    return best;
}

// find nearest point to a point, and its squared distance
// (requires an arbitrary operator< for Point)
pair<T, P> nearest(const P& p) {
    return search(root, p);
}
};
```

DelaunayTriangulation.h

Description: Computes the Delaunay triangulation of a set of points. Each circumcircle contains none of the input points. If any three points are collinear or any four are on the same circle, behavior is undefined.

Time:  $\mathcal{O}(n^2)$

"Point.h", "3dHull.h"

c0e7bc, 10 lines

```
template<class P, class F>
void delaunay(vector<P>& ps, F trifun) {
    if (sz(ps) == 3) { int d = (ps[0].cross(ps[1], ps[2]) < 0);
        trifun(0,1+d,2-d); }
    vector<P3> p3;
    for (P p : ps) p3.emplace_back(p.x, p.y, p.dist2());
    if (sz(ps) > 3) for(auto t:hull3d(p3)) if ((p3[t.b]-p3[t.a]).
        cross(p3[t.c]-p3[t.a]).dot(P3(0,0,1)) < 0)
        trifun(t.a, t.c, t.b);
}
```

PlanarFaceExtraction.h

Description: Given a planar graph and where the points are, extract the set of faces that the graph makes. The inner faces will be returned in counter-clockwise order, and the outermost face will be returned in clockwise order.

Time:  $\mathcal{O}(E \log E)$

63f230, 39 lines

```
template<class P>
vector<vector<P>> extract_faces(vvi adj, vector<P> pts) {
    int n = sz(pts);
    #define cmp(i) [&](int pi, int qi) -> bool { \
        P p = pts[pi] - pts[i], q = pts[qi] - pts[i]; \
        bool sideP = p.y < 0 || (p.y == 0 && p.x < 0); \
        bool sideQ = q.y < 0 || (q.y == 0 && q.x < 0); \
        if(sideP != sideQ) return sideP; \
        return p.cross(q) > 0; }
    rep(i, 0, n)
        sort(all(adj[i]), cmp(i));
    vii ed;
    rep(i, 0, n) for(int j: adj[i])
        ed.emplace_back(i, j);
    sort(all(ed));
    auto get_idx = [&](int i, int j) -> int {
        return lower_bound(all(ed), pii(i, j))-begin(ed);
    };
    vector<vector<P>> faces;
    vi used(sz(ed));
    rep(i, 0, n) for(int j: adj[i]) {
```

```
    if(used[get_idx(i, j)])
        continue;
    used[get_idx(i, j)] = true;
    vector<P> face = {pts[i]};
    int prv = i, cur = j;
    while(cur != i) {
        face.push_back(pts[cur]);
        auto it = lower_bound(all(adj[cur]), prv, cmp(cur));
        if(it == begin(adj[cur]))
            it = end(adj[cur]);
        prv = cur, cur = *prev(it);
        used[get_idx(prv, cur)] = true;
    }
    faces.push_back(face);
}
#undef cmp
return faces;
}
```

8.6 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

3058c3, 6 lines

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

8058ae, 32 lines

```
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
    bool operator<(R p) const {
        return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const {
        return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const {
        return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
    }
}
```

```
T dist2() const { return x*x + y*y + z*z; }
double dist() const { return sqrt((double)dist2()); }
//Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
double phi() const { return atan2(y, x); }
//Zenith angle (latitude) to the z-axis in interval [0, pi]
double theta() const { return atan2(sqrt(x*x+y*y),z); }
P unit() const { return *this/(T)dist(); } //makes dist()==1
//returns unit vector normal to *this and p
P normal(P p) const { return cross(p).unit(); }
//returns point rotated 'angle' radians ccw around axis
P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
}
};
```



3dHull.h

**Description:** Computes all faces of the 3-dimension hull of a point set. \*No four points must be coplanar\*, or else random results will be returned. All times:  $\mathcal{O}(n^2)$

**Time:**  $\mathcal{O}(n^2)$

"Point3D.h"5b45fc, 49 lines

```
typedef Point3D<double> P3;

struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
    assert(sz(A) >= 4);
    vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
    vector<F> FS;
    auto mf = [&](int i, int j, int k, int l) {
        P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
        if (q.dot(A[l]) > q.dot(A[i]))
            q = q * -1;
        F f{q, i, j, k};
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.push_back(f);
    };
    rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
        mf(i, j, k, 6 - i - j - k);

    rep(i,4,sz(A)) {
        rep(j,0,sz(FS)) {
            F f = FS[j];
            if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
                E(a,b).rem(f.c);
                E(a,c).rem(f.b);
                E(b,c).rem(f.a);
                swap(FS[j--], FS.back());
                FS.pop_back();
            }
        }
        int nw = sz(FS);
        rep(j,0,nw) {
            F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
            C(a, b, c); C(a, c, b); C(b, c, a);
        }
        for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
            A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
        return FS;
    };
};
```

sphericalDistance.h

**Description:** Returns the shortest distance on the sphere with radius  $r$  between the points with azimuthal angles (longitude)  $\phi_1$  ( $\phi_1$ ) and  $\phi_2$  ( $\phi_2$ ) from  $x$  axis and zenith angles (latitude)  $\theta_1$  ( $\theta_1$ ) and  $\theta_2$  ( $\theta_2$ ) from  $z$  axis ( $0 =$  north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows.  $dx \cdot radius$  is then the difference between the two points in the  $x$  direction and  $d \cdot radius$  is the total distance between the points.

611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
```

```
double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
double dz = cos(t2) - cos(t1);
double d = sqrt(dx*dx + dy*dy + dz*dz);
return radius*2*asin(d/2);
}
```

## Strings (9)

### 9.1 Applications of String Functions

#### Searching for a Sub-string in a String (KMP)

- Concatenate the sub-string to the beginning of the string plus another character that does not occur in either string.
- Run the prefix function on the string and count the number of occurrences of the length of the original sub-string.

#### Counting the Number of Prefixes in a String

- Run the prefix function on the string.
- For each string of length  $i$ , do:  $ans[pi[i-1]] += ans[i]$  since each occurrence of a longer prefix implies the occurrence of the shorter prefix.
- Add one for each original (non-counted) prefix.

```
vll ans(n+1, 1); // Set to one for the actual prefix for (int i = 0; i < n; i++) ans[pi[i]]++; for (int i = n-1; i >= 0; i--) ans[pi[i-1]] += ans[i];
```

#### The Number of Different Substrings in a String

- Start with an empty string.
- Add the next character of the original string to our string and reverse the string.
- Run the prefix function to find the max length of the substrings we have already found.
- The number of new substrings =  $accumulate(|S| + 1 - \max Pi)$ .

#### Compressing a String

- Given a string  $s$  of length  $n$ , we want to find the shortest “compressed” representation of the string.
- If after running the prefix function,  $n$  is divisible by  $(n - pi[n-1])$ , then the string is compressible, with minimum size  $(n - pi[n-1])$ .
- Otherwise, it is not compressible.

#### Creating Automation for String Matching

- After running the prefix function on one or many strings, an automation should be able to preprocess the strings in  $\mathcal{O}(n)$  and then do matching in  $\mathcal{O}(m)$  per query.
- This is especially useful for **many repeated searches** with the same pattern (KMP runs in  $\mathcal{O}(n + m)$  per query).
- Build a table storing  $aut[state][charNumber]$ , where state is the index of the string we are searching for and char is the current character.
- Depending on the character we see, move forwards or backwards to a new state (e.g., seeing an  $a$  moves us from state  $1 \rightarrow 2$ , but seeing a  $b$  moves us from state  $2 \rightarrow 0$ ).

MatchingAutomation.h

**Description:** Creates substring searching automation

c3fe8a, 12 lines

```
void computeAutomaton(string s, vector<vector<int>>& aut)
{
    s += '#';
    int n = s.size();
    vector<int> pi = prefix_function(s);
    aut.assign(n, vector<int>(26));

    for (int i = 0; i < n; i++)
        for (int c = 0; c < 26; c++)
```

```
if (i > 0 && 'a' + c != s[i]) aut[i][c] = aut[pi[i-1]][c];
else aut[i][c] = i + ('a' + c == s[i]);
}
```

KMP.h

**Description:**  $pi[x]$  computes the length of the longest prefix of  $s$  that ends at  $x$ , other than  $s[0...x]$  itself (abacaba -> 0010123). Can be used to find all occurrences of a string.

**Time:**  $\mathcal{O}(n)$

d4375c, 16 lines

```
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}

vi match(const string& s, const string& pat) {
    vi p = pi(pat + '\0' + s), res;
    rep(i,sz(p)-sz(s),sz(p))
        if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
    return res;
}
```

Zfunc.h

**Description:**  $z[i]$  computes the length of the longest common prefix of  $s[i:]$  and  $s$ , except  $z[0] = 0$ . (abacaba -> 0010301) Used for Finding Periods CSES

**Time:**  $\mathcal{O}(n)$

ee09e2, 12 lines

```
vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
            z[i]++;
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    return z;
}
```

Manacher.h

**Description:** For each position in a string, computes  $p[0][i] =$  half length of longest even palindrome around pos  $i$ ,  $p[1][i] =$  longest odd (half rounded down).

**Time:**  $\mathcal{O}(N)$

e7ad79, 13 lines

```
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+l;z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}
```

### Eertree.h

**Description:** Generates an eertree on str. *cur* is accurate at the end of the main loop before the final assignment to *t*.

**Time:**  $\mathcal{O}(|S|)$

```
struct Eertree {
    vi slink = {0, 0}, len = {-1, 0};
    vvi down;
    int cur = 0, t = 0;
    Eertree(string &str) : down(2, vi(26, -1)) {
        for (int i = 0; i < sz(str); i++) {
            char c = str[i]; int ci = c - 'a';
            while (t <= 0 || str[t-1] != c)
                t = i - len[cur = slink[cur]];
            if (down[cur][ci] == -1) {
                down[cur][ci] = sz(slink);
                down.emplace_back(26, -1);
                len.push_back(len[cur] + 2);
                if (len.back() > 1) {
                    do t = i - len[cur = slink[cur]];
                    while(t <= 0 || str[t-1] != c);
                    slink.push_back(down[cur][ci]);
                } else slink.push_back(1);
                cur = sz(slink) - 1;
            } else cur = down[cur][ci];
            t = i - len[cur] + 1;
        }
    }
};
```

### MinRotation.h

**Description:** Finds the lexicographically smallest rotation of a string.

**Usage:** rotate(v.begin(), v.begin()+minRotation(v), v.end());

**Time:**  $\mathcal{O}(N)$

```
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) {a = b; break;}
    }
    return a;
}
```

### SuffixArray.h

**Description:** Builds suffix array for a string. *sa[i]* is the starting index of the suffix which is *i*'th in the sorted suffix array. The returned vector is of size *n* + 1, and *sa[0]* = *n*. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: *lcp[i]* = *lcp(sa[i], sa[i-1])*, *lcp[0]* = 0. The input string must not contain any nul chars.

**Time:**  $\mathcal{O}(n \log n)$

```
struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string s, int lim=256) { // or vector<int>
        s.push_back(0); int n = sz(s), k = 0, a, b;
        vi x(all(s)), y(n), ws(max(n, lim));
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
                (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
        for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
```

```
        for (k && k--, j = sa[x[i] - 1];
            s[i + k] == s[j + k]; k++);
    }
};
```

### SuffixAutomaton.h

**Description:** Creates a partial DFA (DAG) that accepts all suffixes, with suffix links. One-to-one map between a path from the root and a substring. *len* is the longest-length substring ending here. *pos* is the first index in the string matching here. term is whether this node is a terminal (aka a suffix)

**Time:** construction takes  $\mathcal{O}(N \log K)$ , where *K* = Alphabet Size

```
struct st {int len, pos, term, link=-1; map<char, int> next;};
struct SuffixAutomaton {
    vector<st> a;
    SuffixAutomaton(string &str) {
        a.resize(1);
        int last = 0;
        for(auto c : str) {
            int p = last, cur = last = sz(a);
            a.push_back({a[p].len + 1, a[p].len});
            while(p >= 0 && !a[p].next.count(c))
                a[p].next[c] = cur, p = a[p].link;
            if (p == -1) a[cur].link = 0;
            else {
                int q = a[p].next[c];
                if (a[p].len + 1 == a[q].len) a[cur].link = q;
                else {
                    a.push_back({a[p].len+1, a[q].pos, 0, a[q].link,
                        a[q].next});
                    for(; p >= 0 && a[p].next[c] == q; p = a[p].link)
                        a[p].next[c] = sz(a)-1;
                    a[q].link = a[cur].link = sz(a)-1;
                }
            }
        }
        while(last >= 0) a[last].term = 1, last = a[last].link;
    }
};
```

### SuffixTree.h

**Description:** Ukkonen's algorithm for online suffix tree construction. Each node contains indices [l, r] into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining [l, r] substrings. The root is 0 (has l = -1, r = 0), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).

**Time:**  $\mathcal{O}(26N)$

```
struct SuffixTree {
    enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALPHA], l[N], r[N], p[N], s[N], v=0, q=0, m=2;

    void ukkadd(int i, int c) { suff:
        if (r[v]<=q) {
            if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
                p[m++]=v; v=s[v]; q=r[v]; goto suff; }
            v=t[v][c]; q=l[v];
        }
        if (q==-1 || c==toi(a[q])) q++; else {
            l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
            p[m]=p[v]; t[m][c]=m+1; t[m][toi(a[q])]=v;
            l[v]=q; p[v]=m; t[p[m]][toi(a[l[m]])]=m;
            v=s[p[m]]; q=l[m];
            while (q<r[m]) { v=t[v][toi(a[q])]; q+=r[v]-l[v]; }
            if (q==r[m]) s[m]=v; else s[m]=m+2;
            q=r[v]-(q-r[m]); m+=2; goto suff;
        }
    }
```

```
    }
}

SuffixTree(string a) : a(a) {
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+ALPHA,0);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
}

// example: find longest common substring (uses ALPHA = 28)
pii best;
int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
        mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
        best = max(best, {len, r[node] - len});
    return mask;
}
static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
}
};
```

### Hashing.h

**Description:** Self-explanatory methods for string hashing.

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
    ull x; H(ull x=0) : x(x) {}
    H operator+(H o) { return x + o.x + (x + o.x < x); }
    H operator-(H o) { return *this + ~o.x; }
    H operator*(H o) { auto m = (__uint128_t)x * o.x;
        return H((ull)m + (ull)m >> 64); }
    ull get() const { return x + !~x; }
    bool operator==(H o) const { return get() == o.get(); }
    bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (11)1e11+3; // (order ~ 3e9; random also ok)
```

```
struct HashInterval {
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
};
```

```
vector<H> getHashes(string& str, int length) {
    if (sz(str) < length) return {};
    H h = 0, pw = 1;
    rep(i,0,length)
```



```
    h = h * C + str[i], pw = pw * C;
vector<H> ret = {h};
rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
}
return ret;
}
```

H hashString(string& s){H h{}; for(char c:s) h=h\*C+c;return h;}

### HashInterval.h

**Description:** Various self-explanatory methods for string hashing.

"Hashing.h"122649, 12 lines

```
struct HashInterval {
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
};
```

### AhoCorasick-Kactl.h

**Description:** AhoCorasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(−, word) finds all words (up to  $N\sqrt{N}$  many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.

**Time:** construction takes  $\mathcal{O}(26N)$ , where  $N$  = sum of length of patterns. find(x) is  $\mathcal{O}(N)$ , where  $N$  = length of x. findAll is  $\mathcal{O}(NM)$ .

f35677, 66 lines

```
struct AhoCorasick {
    enum {alpha = 26, first = 'A'}; // change this!
    struct Node {
        // (nmatches is optional)
        int back, next[alpha], start = -1, end = -1, nmatches = 0;
        Node(int v) { memset(next, v, sizeof(next)); }
    };
    vector<Node> N;
    vi backp;
    void insert(string& s, int j) {
        assert(!s.empty());
        int n = 0;
        for (char c : s) {
            int& m = N[n].next[c - first];
            if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
            else n = m;
        }
        if (N[n].end == -1) N[n].start = j;
        backp.push_back(N[n].end);
        N[n].end = j;
        N[n].nmatches++;
    }
    AhoCorasick(vector<string>& pat) : N(1, -1) {
        rep(i,0,sz(pat)) insert(pat[i], i);
        N[0].back = sz(N);
        N.emplace_back(0);

        queue<int> q;
        for (q.push(0); !q.empty(); q.pop()) {
            int n = q.front(), prev = N[n].back;
```

```
        rep(i,0,alpha) {
            int &ed = N[n].next[i], y = N[prev].next[i];
            if (ed == -1) ed = y;
            else {
                N[ed].back = y;
                (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
                    = N[y].end;
                N[ed].nmatches += N[y].nmatches;
                q.push(ed);
            }
        }
    }
}

vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
        n = N[n].next[c - first];
        res.push_back(N[n].end);
        // count += N[n].nmatches;
    }
    return res;
}

vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
        int ind = r[i];
        while (ind != -1) {
            res[i - sz(pat[ind]) + 1].push_back(ind);
            ind = backp[ind];
        }
    }
    return res;
}
};
```

### LyndonFactorization.h

**Description:** Computes the Lyndon Factorization of a string. A Lyndon word is a nonempty string that is strictly smaller in lexicographic order than any of its proper suffixes. Returns the starting indices of the Lyndon words in the string.

**Time:**  $\mathcal{O}(n)$

09e827, 12 lines

```
vi duval(string &s) {
    vi ans;
    for(int start = 0; start < sz(s);) {
        int i = start+1, j = start;
        for(; i < sz(s) && s[i] >= s[j]; i++)
            if(s[i] > s[j]) j = start;
            else j++;
        for(int sz = i-j; start + sz <= i; start += sz)
            ans.push_back(start);
    }
    return ans;
}
```

### SuffixAutomaton.h

**Description:** Creates a partial DFA (DAG) that accepts all suffixes, with suffix links. One-to-one map between a path from the root and a substring. len is the longest-length substring ending here. pos is the first index in the string matching here. term is whether this node is a terminal (aka a suffix)

**Time:** construction takes  $\mathcal{O}(N \log K)$ , where  $K$  = Alphabet Size

385afe, 27 lines

```
struct st {int len, pos, term, link=-1; map<char, int> next;};
struct SuffixAutomaton {
    vector<st> a;
    SuffixAutomaton(string &str) {
        a.resize(1);
```

```
int last = 0;
for(auto c : str) {
    int p = last, cur = last = sz(a);
    a.push_back({a[p].len + 1, a[p].len});
    while(p >= 0 && !a[p].next.count(c))
        a[p].next[c] = cur, p = a[p].link;
    if (p == -1) a[cur].link = 0;
    else {
        int q = a[p].next[c];
        if (a[p].len + 1 == a[q].len) a[cur].link = q;
        else {
            a.push_back({a[p].len+1, a[q].pos, 0, a[q].link,
                a[q].next});
            for(; p >= 0 && a[p].next[c] == q; p = a[p].link)
                a[p].next[c] = sz(a)-1;
            a[q].link = a[cur].link = sz(a)-1;
        }
    }
    while(last >= 0) a[last].term = 1, last = a[last].link;
};
```

## Various (10)

### 10.1 Intervals

#### IntervalContainer.h

**Description:** Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).

**Time:**  $\mathcal{O}(\log N)$

edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L,R});
}
```

```
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}
```

#### IntervalCover.h

**Description:** Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).

**Time:**  $\mathcal{O}(N \log N)$

9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
```

```
sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
T cur = G.first;
int at = 0;
while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
        mx = max(mx, make_pair(I[S[at]].second, S[at]));
        at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
}
return R;
}
```

ConstantIntervals.h

**Description:** Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.

**Usage:** constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});  
**Time:**  $\mathcal{O}(k \log \frac{n}{k})$

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}
```

10.2 Misc. algorithms

TernarySearch.h

**Description:** Find the smallest  $i$  in  $[a, b]$  that maximizes  $f(i)$ , assuming that  $f(a) < \dots < f(i) \geq \dots \geq f(b)$ . To reverse which of the sides allows non-strict inequalities, change the  $<$  marked with (A) to  $<=$ , and reverse the loop at (B). To minimize  $f$ , change it to  $>$ , also at (B).

**Usage:** int ind = ternSearch(0,n-1,[&](int i){return a[i];});  
**Time:**  $\mathcal{O}(\log(b-a))$

```
template<class F>
int ternSearch(int a, int b, F f) {
    assert(a <= b);
    while (b - a >= 5) {
        int mid = (a + b) / 2;
        if (f(mid) < f(mid+1)) a = mid; // (A)
        else b = mid+1;
    }
    rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
    return a;
}
```

LIS.h

**Description:** Compute indices for the longest increasing subsequence.  
**Time:**  $\mathcal{O}(N \log N)$

```
template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i,0,sz(S)) {
        // change 0 => i for longest non-decreasing subsequence
        auto it = lower_bound(all(res), p[S[i], 0]);
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = sz(res), cur = res.back().second;
    vi ans(L);
    while (L-->0) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

10.3 Dynamic programming

KnuthDP.h

**Description:** When doing DP on intervals:  $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$ , where the (minimal) optimal  $k$  increases with both  $i$  and  $j$ , one can solve intervals in increasing order of length, and search  $k = p[i][j]$  for  $a[i][j]$  only between  $p[i][j-1]$  and  $p[i+1][j]$ . This is known as Knuth DP. Sufficient criteria for this are if  $f(b, c) \leq f(a, d)$  and  $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$  for all  $a \leq b \leq c \leq d$ . Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.

**Time:**  $\mathcal{O}(N^2)$

DivideAndConquerDP.h

**Description:** Given  $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$  where the (minimal) optimal  $k$  increases with  $i$ , computes  $a[i]$  for  $i = L..R-1$ .

**Time:**  $\mathcal{O}((N + (hi-lo)) \log N)$

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best(LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```