ChemCurb System

The *ChemCurb* penetration pieces consist of the following sizes:



ChemCurb Straights

6" & 12" straight sections used to lengthen the *ChemCurb*. Fit both curb sizes.

F1304P (6" - Gray)
-Contains 8 straights per carton only.
F1303P (12" - Gray)
-Contains 8 straights per carton only.

ChemCurb Corners

2" corner pieces used with straight sections to make box shapes.

F1305P (Gray)

-Contains 8 Corners per carton only.







ChemCurb Diameter Rounds

5" diameter ID round consisting of (2) 2.5" radius pcs.

F1302P (Gray)

-Contains 6 curbs per carton only. F1307P (1-Part Gray Kit)

-Contains 3 curbs per carton with (1) 1/2 gallon pouch of 1-Part $^{\text{TM}}$ Pourable Sealant and (2) 10.1 oz. cartridges of M-1 $^{\text{®}}$ Structural Sealant.



7.5" Diameter ID round consisting of (2) 3.75" radius pcs.

F1301P (Gray)

-Contains 4 curbs per carton only.

F1306P (1-Part Gray Kit)

-Contains 2 cubs per carton with (2) $\frac{1}{2}$ gal. pouches of 1-PartTM Pourable Sealant and (2) 10.1 oz. cartridges of M-1[®] Structural Sealant.

F1300P (ProPack Kit)

-Contains 2 Curbs per carton with 1 gal. of PRO PACK[™] black, two-part urethane sealer and (2) 10.1 oz. cartridges of M-1[®] Structural Sealant.



Customer Service: 800.826.1681

www.ChemLink.com

ate: Sep 30, 2016 Title: ChemCurbs Sheet: 1 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

HOW TO CALCULATE CHEMCURB VOLUMES

Note: These figures represent volume of sealant needed for various sizes of curb combinations without displacement for penetrations. (To estimate exact volume needed, also figure volume of penetrations and subtract from volume of curbs.)

To figure volume of a square curb: Multiply length x width x depth, (2") x (quantity of curbs needed) the divide by 231 (in³ in a gal.) to get the number of gallons needed to fill the curb.

Note:

One gal. pourable sealer = 231 in³ One $\frac{1}{2}$ gal. pouch = 115.5 in³ One 28 oz cartridge = 50 in³ One 10.1 oz cartridge = 4.18 in³

Always figure 2" depth of ChemCurbs.

Less invalidates warranty.

A corner curb adds two inches to a straight curb on each end.

Examples:

Four 12" Straights + Four 2" Corners

Form a square 16" x 16" x 2" deep. Multiply 16" x 16" x 2" = 512 in³ Divide 512 in³ by 231 = 2.21 gal



Four 6" Straights + Four 2" Corners

Form a square 10" x 10" x 2" deep. Multiply 10" x 10" x 2" = 200 in³ Divide 200 in³ by 231 = 0.86 gal

7.5" round Curb + two 12" Straights

Form an oval 19.5" x 7.5" x 2" deep. Multiply 19.5" x 7.5" x 2" = 285 in³ Divide 285 in³ by 231 = 1.23 gal

7.5" round Curb + two 6" Straights

Form an oval 13.5" x 7.5" x 2" deep. Multiply 13.5" x 7.5" x 2" = 202.5 in³ Divide 202.5 in³ by 231 = 0.88 gal

5" round Curb + two 12" Straights

Form an oval 17" x 5" x 2" deep. Multiply 17" x 5" x 2" = 170 in³ Divide 170 in³ by 231 = 0.73 gal

5" round Curb + two 6" Straights

Form an oval 11" x 5" x 2" deep. Multiply 11" x 5" x 2" = 110 in³ Divide 110 in³ by 231 = 0.48 gal



To figure volume of a round curb: multiply (radius squared x 3.14 x depth) x (quantity of curbs needed) then divide by 231 (in³/gal) to get the number of gallons needed to fill the curb.

5" round Curb

Form a diameter 5" x 2" deep. Multiply 2.5" squared x 3.14 x 2" = 39.27 in³ Divide 39.27 in³ by 231 = 0.17 gal

7.5" round Curb

Form a diameter 7.5" x 2" deep.

Multiply 3.75" squared x 3.14 x 2" = 88.31 in³

Divide 88.31 in³ by 231 = 0.38 gal






Customer Service: 800.826.1681

www.ChemLink.com

Date: Sep 30, 2016 Title: ChemCurbs Sheet: 2 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

M-1 APPLICATION TO THE BOTTOM OF THE CHEMCURB SECTIONS







Customer Service: 800.826.1681
www.ChemLink.com

www.Chemilink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 3 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

SECTION VIEW








Customer Service: 800.826.1681

www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 4 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

STANDARD CHEMCURB DETAIL




A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.



Customer Service: 800.826.1681 www.ChemLink.com

late: May 12, 2013 Title: ChemCurbs Sheet: 5 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

L - SHAPED CONFIGURATION






Customer Service: 800.826.1681 www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 6 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

H - BEAM PENETRATION




A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.



Customer Service: 800.826.1681 www.ChemLink.com

ate: May 12, 2013 Title: ChemCurbs Sheet: 7 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

CABLE SUPPORT PENETRATION








Customer Service: 800.826.1681 www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 8 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

SOLAR PANEL MOUNT











Customer Service: 800.826.1681 www.ChemLink.com

ate: May 12, 2013 Title: ChemCurbs Sheet: 9 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

MACHINERY SCREEN








Customer Service: 800.826.1681 www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 10 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

VERTICAL WALL PENETRATIONS




A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.




Customer Service: 800.826.1681 www.ChemLink.com

May 12, 2013 Title: ChemCurbs Sheet: 11 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

ANGLE IRON PENETRATION








Customer Service: 800.826.1681 www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 12 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

SLOPED ROOF PENETRATION




A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.



Customer Service: 800.826.1681 www.ChemLink.com

ate: May 12, 2013 Title: ChemCurbs Sheet: 13 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold

PENETRATION NEAR WALL FLASHING



A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.




Customer Service: 800.826.1681

www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 14 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold

HOT STACK PENETRATION (200°F to 400°F)





A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.



Customer Service: 800.826.1681 www.ChemLink.com

ate: May 12, 2013 Title: ChemCurbs Sheet: 15 of 16 DRW#: CL-CC-02 Drawn by: Christian Appold





A minimum 1" space is required between all penetrations and the interior wall of all ChemCurbs.



Customer Service: 800.826.1681 www.ChemLink.com

Date: May 12, 2013 Title: ChemCurbs Sheet: 16 of 16 DRW #: CL-CC-02 Drawn by: Christian Appold