

Plotly Cheatsheet

Version 0.6.0 - May 2019



This work by Marco Torchiano is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

Live examples shown using Plotly.js v.1.48.1

Boilerplate

Importing the library

```
<script src="https://cdn.plot.ly/plotly-latest.min.js"></script>
```

Use the plotly CDN

Standard structure

```
var traces = [ ... ];  
var layout = { ... };  
Plotly.plot("divID",traces,layout);
```


Typical layout

```
layout = {margin:{          t:1,  
                        l:20,      r:2,  
                        b:30  
}};
```

Default margins are wide.


Basic plots

Lines



```
var traces = [{
  x:[1,2,3,4],
  y:[10,3,5,7],
  type:"scatter"}];
```


Dots



```
var traces = [{
  x:[1,2,3,4],
  y:[10,3,5,7],
  type:"scatter",
  mode:"markers",
}];
```


Mode can be any combination of "lines", "markers", "text" joined with a "+" OR "none".

Bars




```
var traces = [{
  x:['A','B','C','D'],
  y:[10,3,5,7],
  type:"bar"}];
```

Horizontal Bars




```
var traces = [{
  y:['A','B','C','D'],
  x:[10,3,5,7],
  orientation:"h", // default: "v"
  type:"bar"}];
```

Boxplots



```
var traces = [{
  x: ['A', 'A', 'A', 'B', 'B', 'B'],
  y: [10, 3, 5, 7, 5, 4],
  type: "box"}];
```


Histogram



```
var traces = [{
  x: [5, 3, 5, 3, 5, 4, 6, 6],
  type: "histogram"}];
```


Use `y` to have it horizontal.

Multiple data series




```
var traces = [{name: "First",
  x: [1, 2, 3, 4],
  y: [10, 3, 5, 7],
  type: "scatter",
},
{name: "Second",
  x: [.5, 2, 4.5, 6],
  y: [3, 2, 5, 8],
  type: "scatter",
}];
```

Multiple graph types



```
var traces = [{name: "First",
  x: [1, 2, 3, 4],
  y: [10, 3, 5, 7],
  type: "bar",
},
{name: "Second",
  x: [.5, 2, 4.5, 6],
  y: [3, 2, 5, 8],
  type: "scatter",
}];
```

Area



```
var traces = [{name:"First",
  x:[1,2,3,4],
  y:[10,3,5,7],
  type:"scatter",
  fill:"tozero",
  mode:"lines"
},{name:"Second",
  x:[1,2,3,4],
  y:[5,6,8,9],
  type:"scatter",
  fill:"tonext",
  mode:"lines"
}];
```


`fill` can be `tozero` x or y, `tonext` x or y or `none`

Scatter Geo



```
var traces = [{
  lat:[41.883,45.066],
  lon:[12.466,7.700],
  text:['Rome','Turin'],
  type:'scattergeo',
  mode:'markers'
}];
var layout = {
  geo : {
    projection: {type:"equiarectangular"},
    showocean: true, oceancolor: "navy",
    showrivers: true, scope:"europe",
    resolution: 50,
    lataxis:{range:[35,48]},
    lonaxis:{range:[6,19]}
  }
}
}}
```


Choropleth Map



```
var traces = [{  
  type: 'choropleth',  
  locations: ['ITA', 'DEU', 'FRA',  
             'USA', 'CHN'],  
  z: [2129, 3820, 2902, 17420, 10360],  
  text: ['Italy', 'Germany', 'France',  
        'USA', 'China'],  
  autocolorscale: true,  
  hoverinfo: 'z+text',  
  colorbar: {  
    tickprefix: '$',  
    title: 'GDP<br>109 US$'  
  }  
}];
```


Visual attributes

Lines and dots




```
var traces = [{
  x: ['A', 'l', 'p', 'h', 'a'],
  y: [1, 2, 4, 8, 3],
  type: "scatter",
  marker: {
    color: "orange",
    size: [10, 20, 30, 20, 10],
    line: {
      color: "purple",
      width: 2
    }
  },
  line: {
    color: "green",
    width: 1
  }
}];
```

Coloring bars



```
var traces = [{
  x: ['A', 'l', 'p', 'h', 'a'],
  y: [1, 2, 4, 8, 3],
  type: "bar",
  marker: {
    color: "orange",
    line: {
      color: "purple",
      width: 2
    }
  }
}];
```

Line shapes




```
var traces = [{name: "spline",
  y: [1, 2, 4, 8, 3],
  type: "scatter",
  line: {
    color: "green", shape: "spline"
  }
},
{name: "line",
  y: [10, 9, 8, 2, 1],
  type: "scatter",
  line: {
    color: "navy", shape: "line"
  }
},
{name: "hv",
  y: [3, 4, 6, 8, 10],
  type: "scatter",
  line: {
    color: "orange", shape: "hv"
  }
},
{name: "vh",
  y: [2, 2, 3, 5, 5],
  type: "scatter",
  line: {
    color: "purple", shape: "vh"
  }
}];
```

```
    },  
    {name:"hv",  
      y: [3, 4, 6, 8, 10],  
      type : "scatter",  
      line: {  
        color: "orange", shape: "hv"  
      }  
    },  
    {name:"vh",  
      y: [0,2, 1, 3, 5],  
      type : "scatter",  
      line: {  
        color: "purple", shape: "vh"  
      }  
    }  
  }  
};
```


Layout


Titles



```
var traces = [{type:"scatter",
  x:[1,2,3,4],y:[10,3,5,7],}],
var layout = {
  title: "Sample graph",
  xaxis: {title:"X axis"},
  yaxis: {title:"Vertical axis"},
  margin : {t:40,b:40,r:2,l:40}
}
```


Margin must be large enough to avoid overlap with the graph.

Ranges



```
var traces = [{type:"scatter",
  x:[1,2,3,4],y:[10,3,5,7],}],
var layout = {
  xaxis: {range:[0,5]},
  yaxis: {range:[-1,11]},
}
```


Ticks



```
var traces = [{type:"bar",
  x:["A","B","C","D"],
  y:[.10,.3,.45,.15],}],
var layout = {
  xaxis: {tickprefix:"cat ",
    showtickprefix:"first"},
  yaxis: {tickformat:"%"},
  margin : {t:10,b:30,r:10,l:40}
}
```


More info about `tickformat` can be found at <https://github.com/d3/d3/wiki/Formatting#numbers>

Reverse axis



```
var traces = [{
  y:['A','B','C','D'],
  x:[10,3,5,7],
  orientation:"h",
  type:"bar"}
];
var layout = {
  yaxis: {autorange:'reversed'}
}
```

Multiples




```
var traces = [{type:"bar",
  x:["A","B","C","D"],
  y:[.10,.3,.45,.15],},
{ type:"scatter",
  yaxis:"y2",
  x:["A","B","C","D"],
  y:[20,50,90,30],}
];
```

```
var layout = {
  xaxis: {title:"Category",
    anchor:"y"},
  yaxis: {title:"Proportion",
    tickformat:"%",
    domain:[0,0.49]},
  yaxis2:{title:"Absolute",
    domain:[0.51,1]},
  margin:{t:1,b:35,r:1,l:60},
  showlegend: false
}
```

The trace with y axis `y2` is define by `yaxis2`.

The `domain` property defines where the axis will be mapped.


Hover info



```
var traces = [{
  x: ['A', 'l', 'p', 'h', 'a'],
  y: [1, 2, 4, 8, 3],
  text : ["Alpha","Lambda","Pi",
    "Theta","alpha"],
  type : "scatter",
  hoverinfo:"text"
}];
```

Value for `hoverinfo` can be any combination of `"x"`, `"y"`, `"text"`, `"name"` joined with a `"+"` OR `"all"` or `"none"`


Annotations



```
var traces = [{
  x:[1,2,3,4],
  y:[10,3,5,7],
  type:"scatter"}];
var layout = {
  annotations:[{
    text:"This a multiline<br>"+
    "annotation",
    x:3, y:5, ax:-50, ay:-50
  }],
  margin:{l:20,r:2,t:1,b:30}};
```

By default, `x` and `y` are in graph coordinates, while `ax` and `ay` are in pixels.


Legends



```
var traces = [{name:"First",
  x:[1,2,3,4], y:[10,3,5,7],
  type:"scatter"},{
  name:"Second",
  x:[.5,2,4.5,6], y:[3,2,5,8],
  type:"scatter",
  }];
var layout = {legend:{
  y:1,x:0,
  yanchor:"bottom",
  orientation:"h"
},
  margin:{l:20,r:2,t:1,b:30}};
```

`x` and `y` are expressed in graph normalized units, 0 means left (bottom) side and 1 means right (top) side of the graph

Numbers as categories




```
var traces = [{name:"Vendite",  
  x:[2013,2014,2015],  
  y:[10,3,5],  
  type:"scatter",}],  
var layout = {  
  xaxis:{title:"Year",  
    type: 'category'},  
  margin:{l:20,r:2,t:1,b:40}};
```

Without the `type: 'category'`, x values even when reported as strings would be considered as numbers and the x axis would include meaningless mid values e.g. 2013.5


Complex Plots

Diverging bar plot



```
var traces = [{
  name: "Males",
  x: [8686278, 12731431, 7427114, 236912],
  y: ["0-29", "30-59", "60-89", "90-"],
  type: "bar", orientation: "h"
}, {
  name: "Females",
  x: [8247164, 12808134, 9073016, 590955],
  y: ["0-29", "30-59", "60-89", "90-"],
  type: "bar", orientation: "h",
  xaxis: "x2"
}];
var layout = {
  xaxis: { domain: [0, 0.43],
    autorange: 'reversed' },
  xaxis2: { domain: [0.57, 1] },
  yaxis: { position: 0.56 },
  legend: { y: 1, x: 0.5,
    yanchor: "bottom",
    xanchor: "center",
    orientation: "h"
  }
};
```

Slope plot



```
traces = [{
  name: "Over 40",
  x: ["Associate", "Full"],
  y: [30, 70],
  type: "scatter",
  hoverinfo: "x+y"
}, {
  name: "Under 40",
  x: ["Associate", "Full"],
  y: [90, 10],
  type: "scatter",
  hoverinfo: "x+y"
}];
layout = {
  annotations: [
    {x: "Associate", y: 30, text: "Over 40",
      xanchor: "right", xshift: -3,
      showarrow: false },
    {x: "Associate", y: 90, text: "Under 40",
      xanchor: "right", xshift: -3,
      showarrow: false },
    {x: "Full", y: 70, text: "Over 40",
      xanchor: "left", xshift: 3,
      showarrow: false},
    {x: "Full", y: 10, text: "Under 40",
      xanchor: "left", xshift: 3,
      showarrow: false}
  ],
  showlegend: false
};
```