

DCGAN

<https://youtu.be/9RgBhAdaEmY>


CNN

DCGAN


DCGAN code

Neural Network

인간의 뉴런의 구조에서 착안



Neural Network



Cat image by [CNX OpenStax](#) is licensed under [CC BY 4.0](#); changes made

Hierarchical Structure

Hierarchical organization





Illustration of hierarchical organization in early visual pathways by Lane McIntosh, copyright CS231n 2017


Simple cells:
Response to light
orientation

Complex cells:
Response to light
orientation and movement

Hypercomplex cells:
response to movement
with an end point




Fully Connected Layer




Convolution Layer

- filter




Convolution Layer

- filter



3	1	1
1	0	1
1	1	3

Convolution Layer



Zero padding

- Zero Padding

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

3x3 filter, applied with **stride 1**

pad with 1 pixel border => what is the output?

7x7 output!

in general, common to see CONV layers with stride 1, filters of size $F \times F$, and zero-padding with $(F-1)/2$. (will preserve size spatially)


e.g. $F = 3 \Rightarrow$ zero pad with 1

$F = 5 \Rightarrow$ zero pad with 2


$F = 7 \Rightarrow$ zero pad with 3

Slide Credit : Stanford CS231n


Pooling layer



Pooling layer




Convolution Neural Network




Convolution Neural Network

- 전체적인 과정



Generator



Loss function (objective function)

- Optimization

Alternate between:

1. **Gradient ascent** on discriminator


$$\max_{\theta_d} \left[\mathbb{E}_{x \sim p_{data}} \log D_{\theta_d}(x) + \mathbb{E}_{z \sim p(z)} \log(1 - D_{\theta_d}(G_{\theta_g}(z))) \right]$$

2. **Gradient descent** on generator

$$\min_{\theta_g} \mathbb{E}_{z \sim p(z)} \log(1 - D_{\theta_d}(G_{\theta_g}(z)))$$

2. Gradient ascent on generator

$$\max(\mathbb{E}_{z \sim p(z)} \log(D_{\theta_d}(G_{\theta_d}(z))))$$



Loss function (objective function)

- Optimization

Algorithm 1 Minibatch stochastic gradient descent training of generative adversarial nets. The number of steps to apply to the discriminator, k , is a hyperparameter. We used $k = 1$, the least expensive option, in our experiments.

for number of training iterations **do**

for k steps **do**

- Sample minibatch of m noise samples $\{z^{(1)}, \dots, z^{(m)}\}$ from noise prior $p_g(z)$.
- Sample minibatch of m examples $\{x^{(1)}, \dots, x^{(m)}\}$ from data generating distribution $p_{\text{data}}(x)$.
- Update the discriminator by ascending its stochastic gradient:

$$\nabla_{\theta_d} \frac{1}{m} \sum_{i=1}^m \left[\log D(x^{(i)}) + \log \left(1 - D(G(z^{(i)})) \right) \right].$$

end for

- Sample minibatch of m noise samples $\{z^{(1)}, \dots, z^{(m)}\}$ from noise prior $p_g(z)$.
- Update the generator by descending its stochastic gradient:

$$\nabla_{\theta_g} \frac{1}{m} \sum_{i=1}^m \log \left(1 - D(G(z^{(i)})) \right).$$

end for

The gradient-based updates can use any standard gradient-based learning rule. We used momentum in our experiments.

Q & A