

Depth-Optimized Quantum Implementation of ARIA

Yujin Yang, Kyungbae Jang, Yujin Oh, and Hwajeong Seo

Index

Our Contribution

Background

Proposed Quantum Implementation

Evaluation

Conclusion

Our Contribution

Low depth quantum implementation of ARIA

- Toffoli-depth and Full-depth reduction for the quantum circuit of Korean cryptosystems ARIA

Various techniques for optimization

- Use of optimized multiplication(Karatsuba), linear layer optimization method(XZLBZ), and parallel processing implementation

Evaluation of post-quantum security

- Evaluation of quantum security by comparing the estimated cost of Grover key search with the security level provided by NIST

Quantum Computer (Background)

- **Quantum computers** are built upon the principles of quantum mechanics (superposition and entanglement)
 - Can solve **specific problems** at a **faster** rate compared to **classical computers**
- The **advancement of large-scale quantum computers** has the potential to pose a **threat** to the **security** of current **cryptographic systems**.
 - **Symmetric-key ciphers** can be **compromised** by general attacks using the **Grover's search algorithm** (reduce the data search complexity $N \rightarrow \sqrt{N}$)
- In recent years, **studies** have been conducted to **evaluate post-quantum security** in existing **symmetric-key ciphers**.
 - Estimation the **complexity of recovering secret keys** using the **Grover's search algorithm**
 - Evaluation **security strength** based on these findings

ARIA Block Cipher (Background)

- **ARIA** is a **symmetric-key** cryptography algorithm
 - optimization for ultra-light environments and hardware implementation
- **ARIA** holds **significance** as symmetric key cipher included in the **validation subjects** of the **KCMVP** (Korean Cryptographic Module Validation Program).
 - For preparedness against emerging threats, **assessing** the **quantum security strength** of **ARIA** is **crucial**.
- There is already a study that measured the quantum security strength of **ARIA** in 2020 by Chauhan et al.^[1].
 - However, Chauhan et al.^[1] primarily focuses on **qubit optimization**.
 - **need** for research that addresses the recent emphasis on **optimizing depth**.

[1] Chauhan, A.K., Sanadhya, S.K.: Quantum resource estimates of grover's key search on aria. In: Security, Privacy, and Applied Cryptography Engineering: 10th International Conference, SPACE 2020, Kolkata, India, December 17–21, 2020, Proceedings 10, Springer (2020) 238–258

Quantum Gates (Background)

In the quantum computer environment, logic gates not available
→ Quantum gates are utilized as replacements for logic gates

- The X gate replaces classical NOT operation
- The CNOT gate replaces classical XOR operation
- The Toffoli gate replaces classical AND operation





Fig. 4: Quantum gates: X (left top), Swap (right top), CNOT (left bottom) and Toffoli (right bottom) gates.

Quantum Gates (Background)

- Toffoli gates are **highly complex** quantum gates.
 - one Toffoli gate = **8 Clifford gates** (CNOT, H) + **7 T gates**
- We employ the Toffoli gate construction proposed by Amy et al.^[2]




[Fig] Decomposition of Toffoli gate^[1]

[2] M. Amy, D. Maslov, M. Mosca, M. Roetteler, and M. Roetteler, "A meet-in-the-middle algorithm for fast synthesis of depth-optimal quantum circuits,"

Grover's Key Search Algorithm (Background)

1. [Initialization] n -qubit key has the same amplitude at all state of the qubits

$$|\psi\rangle = (H|0\rangle)^{\otimes n} = \left(\frac{|0\rangle + |1\rangle}{\sqrt{2}}\right)^{\otimes n} = \frac{1}{\sqrt{2^n}} \sum_{x=0}^{2^n-1} |x\rangle$$




2. [Oracle Operator] $f(x) = 1$, sign of the solution key is changed to negative.
Amplify the amplitude of the negative sign state.

repeat $\frac{\pi}{4} \sqrt{2^k}$

$$U_f(|\psi\rangle |-\rangle) = \frac{1}{\sqrt{2^n}} \sum_{x=0}^{2^n-1} (-1)^{f(x)} |x\rangle |-\rangle \quad f(x) = \begin{cases} 1 & \text{if } \text{prepared key } Enc(key) = c \\ 0 & \text{if } Enc(key) \neq c \end{cases}$$


ciphertext known ciphertext comparison



3. [Diffusion Operator] a key state (target key state) is transforming with a negative amplitude into a symmetric state.

$$D = 2 |s\rangle \langle s| - I$$

each key state
 average value



Proposed Quantum Implementation of S-box

In quantum computers, qubit states are unknown → Look-up table method can't be used
⇒ **Implement S-box circuit** based on **generation equation** using quantum gates

S-box generation equation

$$\begin{aligned} S_1(x) &= A \cdot x^{-1} \oplus [1, 1, 0, 0, 0, 1, 1, 0]^T \\ S_2(x) &= B \cdot x^{247} \oplus [0, 1, 0, 0, 0, 1, 1, 1]^T \end{aligned}$$

(input) 8-bit blocks 8 x 8 Matrix 8 x 1 Matrix

$$\begin{aligned} x^{-1} &= x^{254} \bmod m(x) \\ x^{247} &= (x^{-1})^8 \bmod m(x) \end{aligned}$$

irreducible polynomial

$$m(x) = x^8 + x^4 + x^3 + x + 1$$

Proposed Quantum Implementation of S-box

In quantum computers, qubit states are unknown → Look-up table method can't be used
⇒ **Implement S-box circuit** based on **generation equation** using quantum gates

S-box generation equation

(input) 8-bit blocks

8 x 8 Matrix

8 x 1 Matrix

$$S_1(x) = A \cdot x^{-1} \oplus [1, 1, 0, 0, 0, 1, 1, 0]^T$$
$$S_2(x) = B \cdot x^{247} \oplus [0, 1, 0, 0, 0, 1, 1, 1]^T$$

$$x^{-1} = x^{254} \bmod m(x)$$
$$x^{247} = (x^{-1})^8 \bmod m(x)$$

irreducible polynomial

$$m(x) = x^8 + x^4 + x^3 + x + 1$$

process

1. Get x^{-1}
2. Matrix-vector Multiplication
(8 x 8 Matrix) $\cdot x^n$
3. constant(vector) Multiplication

Proposed Quantum Implementation of S-box

Get x^{-1}

(1) Itoh Tsuji Inversion Algorithm

$$x^{-1} = x^{254} = ((x \cdot x^2) \cdot (x \cdot x^2)^4 \cdot (x \cdot x^2)^{16} \cdot x^{64})^2$$

(2) Squaring – XZLBZ^[3]

- XZLBZ^[3] proposed a heuristic search algorithm based on factorization in binary matrices
- implement in-place structure
→ consist of CNOT gates
- 10 CNOT gates, circuit depth of 7




Fig. 5: Quantum circuit implementation for Squaring in $\mathbb{F}_{2^8}/(x^8 + x^4 + x^3 + x + 1)$

Proposed Quantum Implementation of S-box

Get x^{-1}

(3) Multiplication – Karatsuba multiplication optimized for Toffoli depth (quantum-quantum multiplication)

Table 1: Quantum resources required for multiplication.

	Source	#Clifford	#T	Toffoli depth	Full depth
schoolbook	CMMP [2]	435	448	28	195
Karatsuba	J++ [13]	390	189	1	28

※: The multiplication size n is 8.

Matrix-vector Multiplication & constant(vector) Multiplication

classical-quantum multiplication → use **XZLBZ**

Proposed Quantum Implementation of Diff-layer

- Diffusion function A is expressed as 16 x 16 binary matrix multiplication

$$A : GF(2^8)^{16} \rightarrow GF(2^8)^{16} \quad \begin{pmatrix} y_0 \\ y_1 \\ y_2 \\ y_3 \\ y_4 \\ y_5 \\ y_6 \\ y_7 \\ y_8 \\ y_9 \\ y_{10} \\ y_{11} \\ y_{12} \\ y_{13} \\ y_{14} \\ y_{15} \end{pmatrix} = \begin{pmatrix} 0 & 0 & 0 & 1 & 1 & 0 & 1 & 0 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 1 & 1 & 0 & 0 & 1 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 0 & 1 & 1 & 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 1 & 0 & 1 & 1 & 0 \\ 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 0 & 0 & 1 & 1 \\ 1 & 0 & 1 & 0 & 0 & 0 & 0 & 1 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 1 & 1 & 0 & 0 \\ 1 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 \\ 1 & 1 & 0 & 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 1 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 1 & 0 & 0 & 0 & 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 0 & 1 & 0 & 1 & 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 & 1 & 1 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 1 & 1 & 1 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 1 & 0 & 1 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 0 & 0 & 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \\ x_8 \\ x_9 \\ x_{10} \\ x_{11} \\ x_{12} \\ x_{13} \\ x_{14} \\ x_{15} \end{pmatrix}$$

1byte (8-bit)

- 0 : 8 x 8 zero matrix
- 1 : 8 x 8 identity matrix

(maintaining qubits)

- Through using XZLBZ, reduction of 51.04% (CNOT gates) and 45.16% (depth)

Table 2: Quantum resources required for Diffusion layer.

Source	#CNOT	qubit	Depth
PLU factorization	768	128	31
XZLBZ [25]	376	128	17

$$768 (= 96 \times 8), 376 (= 47 \times 8)$$

Proposed Quantum Implementation of Key-Schedule

1) Key Initialization




Fig. 3: Key Initialization of ARIA

Algorithm 1: Quantum circuit implementation of key schedule for ARIA.

Input: master key MK , key length l , vector a, b , ancilla qubit anc , round number r

Output: round key ek

- 1: $W_1 \leftarrow F_o(\overset{K_L}{MK[:128]}, a, b, anc)$
- 2: $\text{Constant_XOR}(W_1[l-128:128], \overset{K_R}{MK[l-128:l]})$
- 3: $W_2 \leftarrow F_e(W_1, a, b, anc)$
- 4: $W_2 \leftarrow \text{CNOT128}(MK[:128], W_2)$
- 5: $W_3 \leftarrow F_o(W_2, a, b, anc)$
- 6: $W_3 \leftarrow \text{CNOT128}(W_1, W_3)$

▷ Key Initialization

▷ $MK[:128]$ is K_L

▷ $MK[l-128:l]$ is K_R

- K_L value is identical to W_0 value \rightarrow instead of generating W_0 , use K_L
 \Rightarrow reduce the number of qubits

- K_R is a constant \rightarrow replace CNOT gates with X gates
 \Rightarrow reduce the number of gates and gate cost

Proposed Quantum Implementation of Key-Schedule

2) Key Generation

Algorithm 1: Quantum circuit implementation of key schedule for ARIA.

Input: master key MK , key length l , vector a, b , ancilla qubit anc , round number r

Output: round key ek

```

    <<< → >>>
7:  $num = [19, 31, 67, 97, 109]$ 
8: for  $i \leftarrow 0$  to  $r$  do
9:   if  $i = 0 \pmod{4}$  then  $K_L = W_0$ 
10:  |   Constant_XOR( $ek, MK[:128]$ )
11:  |   else
12:  |      $ek \leftarrow \text{CNOT128}(W_{(i\%4)}, ek)$ 
13:  |      $ek \leftarrow \text{CNOT128}(W_{(i+1)\%4} \ggg num[i\%4], ek)$ 
14: return  $ek$ 
```

$$\begin{aligned} ek_1 &= (W_0) \oplus (W_1 \ggg 19), & ek_2 &= (W_1) \oplus (W_2 \ggg 19) \\ ek_3 &= (W_2) \oplus (W_3 \ggg 19), & ek_4 &= (W_0 \ggg 19) \oplus (W_3) \\ ek_5 &= (W_0) \oplus (W_1 \ggg 31), & ek_6 &= (W_1) \oplus (W_2 \ggg 31) \\ ek_7 &= (W_2) \oplus (W_3 \ggg 31), & ek_8 &= (W_0 \ggg 31) \oplus (W_3) \\ ek_9 &= (W_0) \oplus (W_1 \lll 61), & ek_{10} &= (W_1) \oplus (W_2 \lll 61) \\ ek_{11} &= (W_2) \oplus (W_3 \lll 61), & ek_{12} &= (W_0 \lll 61) \oplus (W_3) \\ ek_{13} &= (W_0) \oplus (W_1 \lll 31), & ek_{14} &= (W_1) \oplus (W_2 \lll 31) \\ ek_{15} &= (W_2) \oplus (W_3 \lll 31), & ek_{16} &= (W_0 \lll 31) \oplus (W_3) \\ ek_{17} &= (W_0) \oplus (W_1 \lll 19) \end{aligned} \quad (3)$$

- When assigning W to ek , since W_0 is equal to K_L (constant), the CNOT gate operation can be replaced with the X gate operation
 \Rightarrow reduce the number of gates and gate cost

Evaluation

(Clifford + T Level)

Table 4: Required decomposed quantum resources for ARIA quantum circuit implementation

Cipher	Source	#Clifford	#T	T-depth	M #Qubit	TD		$TD \times M$
						Full depth	Toffoli depth	$TD-M$ cost
ARIA-128	CS [2] [◇]	1,494,287	1,103,872	17,248	1,560	37,882	4,312	6,726,720
	This work	481,160	181,440	240	29,216	4,241	60	1,752,960
ARIA-192	CS [2] [◇]	1,742,059	1,283,576	20,376	1,560	44,774	5,096	7,949,760
	This work	551,776	205,632	272	32,928	5,083	68	2,239,104
ARIA-256	CS [2] [◇]	2,105,187	1,555,456	24,304	1,688	51,666	6,076	10,256,288
	This work	616,920	229,824	304	36,640	5,693	76	2,784,640

◇ Extrapolated result

88.8% **98.7%** **72.9%**
reduction **reduction** **reduction**

- In CS's paper^[1], the decomposed quantum resources were not explicitly provided.
 → the quantum resources are extrapolated based on the information provided in the paper
- Significantly reduces depth-related metrics (Full depth, Toffoli depth, TD-M cost) while considering the trade-off between qubit and depth.

[1] Chauhan, A.K., Sanadhya, S.K.: Quantum resource estimates of grover's key search on aria. In: Security, Privacy, and Applied Cryptography Engineering: 10th International Conference, SPACE 2020, Kolkata, India, December 17–21, 2020, Proceedings 10, Springer (2020) 238–258

Evaluation

$$[\text{Table 5}] = [\text{Table 4}] \times \left\lceil \frac{\text{key size}}{\text{block size}} \right\rceil \times 2 \times \left\lceil \frac{\pi}{4} \sqrt{2^k} \right\rceil$$

Total gates X Full depth = Cost(complexity)

Table 5: Cost of the Grover's key search for ARIA

Cipher	Source	Total gates	Full depth	Cost (complexity)	#Qubit	<i>TD-M</i> cost	NIST Level ^[6,7]
ARIA-128	CS [2]	$1.946 \cdot 2^{85}$	$1.816 \cdot 2^{79}$	$1.767 \cdot 2^{165}$	1,561	$1.26 \cdot 2^{87}$	(Level 1) 2^{157}
	This work	$1.985 \cdot 2^{83}$	$1.626 \cdot 2^{76}$	$1.614 \cdot 2^{160}$	29,217	$1.313 \cdot 2^{84}$	
ARIA-192	CS [2]	$1.133 \cdot 2^{119}$	$1.073 \cdot 2^{113}$	$1.216 \cdot 2^{232}$	3,121	$1.489 \cdot 2^{121}$	(Level 3) $2^{192}, 2^{221}$
	This work	$1.135 \cdot 2^{117}$	$1.949 \cdot 2^{109}$	$1.106 \cdot 2^{227}$	65,857	$1.672 \cdot 2^{119}$	
ARIA-256	CS [2]	$1.371 \cdot 2^{151}$	$1.238 \cdot 2^{145}$	$1.698 \cdot 2^{296}$	3,377	$1.921 \cdot 2^{153}$	(Level 5) $2^{274}, 2^{285}$
	This work	$1.268 \cdot 2^{149}$	$1.092 \cdot 2^{142}$	$1.385 \cdot 2^{291}$	73,281	$1.04 \cdot 2^{152}$	

NIST Level Achieve

[6] Jang, K., Baksi, A., Song, G., Kim, H., Seo, H., Chattopadhyay, A.: Quantum analysis of aes. Cryptology ePrint Archive (2022)

[7] Jaques, S., Naehrig, M., Roetteler, M., Virdia, F.: Implementing grover oracles for quantum key search on aes and lowmc. Cryptology ePrint Archive, Report 2019/1146 (2019)

Evaluation

Table 5: Cost of the Grover's key search for ARIA

Cipher	Source	Total gates	Full depth	Cost (complexity)	#Qubit	$TD-M$ cost
ARIA-128	CS [2]	$1.946 \cdot 2^{85}$	$1.816 \cdot 2^{79}$	$1.767 \cdot 2^{165}$	1,561	$1.26 \cdot 2^{87}$
	This work	$1.985 \cdot 2^{83}$	$1.626 \cdot 2^{76}$	$1.614 \cdot 2^{160}$	29,217	$1.313 \cdot 2^{84}$
ARIA-192	CS [2]	$1.133 \cdot 2^{119}$	$1.073 \cdot 2^{113}$	$1.216 \cdot 2^{232}$	3,121	$1.489 \cdot 2^{121}$
	This work	$1.135 \cdot 2^{117}$	$1.949 \cdot 2^{109}$	$1.106 \cdot 2^{227}$	65,857	$1.672 \cdot 2^{119}$
ARIA-256	CS [2]	$1.371 \cdot 2^{151}$	$1.238 \cdot 2^{145}$	$1.698 \cdot 2^{296}$	3,377	$1.921 \cdot 2^{153}$
	This work	$1.268 \cdot 2^{149}$	$1.092 \cdot 2^{142}$	$1.385 \cdot 2^{291}$	73,281	$1.04 \cdot 2^{152}$

NIST MAXDEPTH^[8]

$2^{40}, 2^{64}, 2^{96}$

- ARIA-128 meets the MAXDEPTH requirement ($\text{ARIA-128} < 2^{96}$)
- In the case of exceeding MAXDEPTH (ARIA-192, 256), the focus should be on minimizing the costs of relevant metrics ($FD^2 \times M, TD^2 \times M$) instead of directly imposing a MAXDEPTH limit on the cost.

[8] NIST.: Call for additional digital signature schemes for the post-quantum cryptography standardization process (2022) <https://csrc.nist.gov/csrc/media/Projects/pqc-dig-sig/documents/call-for-proposals-dig-sig-sept-2022.pdf>.

Conclusion

- We propose the quantum circuit for ARIA, focusing on circuit depth optimization.
 - Our quantum circuit implementation achieves the full depth improvement of over 88.8% and Toffoli depth by more than 98.7% compared to the previous work (Chauhan et al.)
- We estimate the cost of Grover's attacks for the proposed circuit, and then evaluate the security strength based on the criteria provided by NIST.
 - ARIA achieves post-quantum security levels 1, 3, and 5 for all key sizes.
 - Only ARIA-128 satisfies the MAXDEPTH limit.
- Future work
 - Optimization of ARIA's quantum circuit further with consideration for the MAXDEPTH limit

Thank you