Twinfield Web services Sales invoices

version 5.4

April 2010

For general information about our webservices see the Twinfield Webservices Manual

Twinfield International NV
De Beek 9-15
3871 MS Hoevelaken
Netherlands

copyright © 2005 – 2011 - Twinfield International N.V.

the no. 1 in online accounting

Table of contents

Sales Invoice XML 3

Article XML 8

Header 8

Lines 9

the no. 1 in online accounting

Sales Invoice XML

Root
(base path=salesinvoice)

node name	comment	
@calculateonly	Attribute to indicate that invoice should not be saved but only checked and calculated (@calculateonly must be 'true' for that).	
@raisewarning	Should warnings be given (true) or not (false)? Default true.	
header	No change	
lines	No change	
totals	taxline (vatline) elements were moved to (new) vatlines container element.	
vatlines	New container element for the taxline (vatline) elements, which were previously part of the calclines tree.	
financials	Only present if the invoice has status 'final', see further below for the structure.	
userdefinedtag	Will be ignored by the core, can be used for integrations.	

the no. 1 in online accounting

Header
Structure
(base path=salesinvoice/header)

Node	Description	Type
office	Office code	CODE, optional
invoicetype	Invoice code	CODE, mandatory
invoicenumber	Invoice number, if empty Twinfield will generate an invoice number, when filled	INTEGER
status	Enumeration of the invoice status.	ENUMERATION - default; Can only be returned when retrieving a sales invoice. You cannot use this status when creating or updating an invoice. - concept; Saves the invoice as concept. - final; After saving as final, no changes can be made anymore. When posting an invoice final, a financial transaction is generated and posted automatically.
customer	Customer code	CODE, mandatory
currency	Currency code	CODE
period	Period	PERIOD
invoicedate	Invoice date	DATE, optional; when the invoicedate is not supplied Twinfield uses the system date as the invoice date
duedate	Due date (invoice date + 1 day)	DATE
performancedate	Performance date, when set-up on invoice header	DATE
paymentmethod	Is now an enum element instead of a numeric element, see further below.	ENUMERATION - cash - bank - cheque - cashondelivery - DA; D/A or 'documents against acceptance', http://www.aibtradefinance.com/tf/ProductDiag2.asp
bank	Bank code	CODE
invoiceaddressnumber	If you want the default address, omit the tag or leave it empty.	INTEGER
deliveraddressnumber	If you want the default address, omit the tag or leave it empty.	INTEGER
headertext	Header text on the invoice	STRING(256)
footertext	Footer text on the invoice	STRING(256)
userdefinedtag	Will be ignored by Twinfield, can be used for integrations.	-

the no. 1 in online accounting

Lines
(base path=salesinvoice/lines/line)

Node	Description	Type
@id	Line id	INTEGER
allowdiscountorpremium	Calculate discount on this line. Must be 'false' or 'true'	BOOLEAN
article	Article code	CODE, mandatory
subarticle	Sub-article code	CODE
quantity	Value must always be numeric.	INTEGER, mandatory
units	Value must always be numeric.	INTEGER
unitspriceexcl	Only valid for invoice types with VAT exclusive units prices.	MONEY
unitspriceinc	Only valid for invoice types with VAT inclusive units prices.	MONEY
vatcode	VAT code	CODE
freetext[1..3]	Reduced number of supported freetext elements to 3 (to match the GUI)	STRING(40), or CODE when connected to a dimension.
dim[1..4]	Only dim1 is 'writable' if this is a one-off (article code '0') AND the invoice type allows changing the ledger account.	CODE; read-only
description	Invoice line description, only on the lines with article '0' or '-'	STRING(80)
performancedate	Performance date, when set-up on invoice lines	DATE
valueexcl	Calculated element	MONEY; read-only
vatvalue	Calculated element	MONEY; read-only
valueinc	Calculated element	MONEY; read-only
userdefinedtag	Will be ignored by the Twinfield, can be used for integrations.	-

Totals
(base path=salesinvoice/totals)

Node	Description	Type
valueexcl	Value without VAT	MONEY; read-only
valueinc	Value with VAT	MONEY; read-only

VAT lines
(base path=salesinvoice/vatlines/vatline)

Node	Description	Type
vatcode	VAT code	CODE; read-only
vatcode/@name	VAT name	STRING(40); read-only
vatcode/@percentage	VAT used percentage	MONEY; read-only
vatvalue	VAT value	MONEY; read-only

the no. 1 in online accounting

Link to financial journal
(base path=salesinvoice/financials)

Node	Description	Type
code	Previously located at salesinvoice/header/@financial-code	CODE; read-only
number	Previously located at salesinvoice/header/@financial-number	INTEGER;read-only

the no. 1 in online accounting

Example Xml

```
<salesinvoices>
      <salesinvoice>
            <header>
                  <invoicetype>FACTUUR</invoicetype>
                  <customer>1000</customer>
            </header>
            <lines>
                  <line>
                        <quantity>1</quantity>
                        <article>abonnement</article>
                        <subarticle>telegraaf</subarticle>
                        <freetext1>P0001</freetext1>
                        <freetext2>001</freetext2>
                  </line>
                  <line>
                        <quantity>1</quantity>
                        <article>0</article>
                        <description>spec. service</description>
                        <unitspriceexcl>20</unitspriceexcl>
                        <units>1</units>
                        <vatcode>VL</vatcode>
                        <freetext1>P0002</freetext1>
                        <freetext2>000</freetext2>
                  </line>
                  <line>
                        <quantity>1</quantity>
                        <article>korting10</article>
                        <freetext1>P0002</freetext1>
                        <freetext2>000</freetext2>
                  </line>
            </lines>
      </salesinvoice>
</salesinvoices>
```


the no. 1 in online accounting

Article XML

Root

(base path=article)

Node name	Description
	Element is obsolete, use header/@status instead
header	No change
lines	No change

Header

Structure

(base path=article/header)

Node name	Comment	Type
@status	Attribute, either 'default' (non-existent)	ENUMERATION - active - deleted
office	Office code	CODE
code	Article code	CODE
name	Article description	STRING(40)
shortname	Short article description	STRING(20)
type	Article type	ENUMERATION - normal - discount - premium
percentage	Only available when article type is ‘discount’ or ‘premium’	BOOLEAN
allowdiscountorpremium	'false' or 'true'	BOOLEAN
allowchangeunitsprice	'true' or 'false'	BOOLEAN
allowchangevatcode	'true' or 'false'	BOOLEAN
vatcode	Default VAT code	CODE
unitnamesingular	Unit name for a single item	STRING(20)
unitnameplural	Unit name for multiple items	STRING(20)
allowdecimalquantity	Are decimals allowed	BOOLEAN

the no. 1 in online accounting

Lines

Structure

(base path=article/lines/line)

Node name	Description	Type
@id	Line id	INTEGER
@inuse	Read-only attribute ('true' or 'false'). Indicates that the sub item has been used in an invoice.	BOOLEAN
@status	'active' or 'deleted'. Allows you to delete sub items and to recover them (if sub item is @inuse).	ENUMERATION - active - deleted
subcode	Can only be empty if there is just one sub article	CODE
name	Article name	STRING(80)
shortname	Article name	STRING(20)
units	No change	INTEGER
unitspriceexcl	Price excluding VAT	DECIMAL(15,2)
unitspriceinc	Price including VAT	DECIMAL(15,2)
freetext[1..3]	Free text elements to 3	STRING(40)

the no. 1 in online accounting