Webservices Validations

manual, version 5.3

April 2007

For general information about our webservices see the Twinfield Webservices Manual

Twinfield International NV
De Beek 9-15
3871 MS Hoevelaken
Netherlands

copyright © 2005 – 2011 - Twinfield International N.V.

Table of contents

1. Validation functions 3
   1.1 List functions 3
   1.2 Retrieving master settings 3
   1.3 Other Validations 3
2. List functions 4
   2.1 List of offices 4
   2.2 List of dimensions 5
   2.3 Budget vs Actuals 6
3. Retrieving master data 8
   3.1 Office master 8
   3.2 Dimension master 9
   3.3 Dimension type master 9
   3.4 Dimension group master 10
   3.5 Credit management actions master 10
   3.6 Currency master 11
   3.7 VAT master 11
4. Validations 12
   4.1 Year/period validation 12
   4.2 Validate the account structure 14

1. Validation functions

Before posting any data into Twinfield it is good practice to validate that the posting will be successful. Twinfield has several functions available which will validate that the data in the posting exists and is valid. For example: before posting a purchase invoice it would be good practice to build a check that will validate the existence of the supplier code, the nominal codes used and if the year period setting is open. In the next paragraphs we describe the different validation functions that are available.

There are different levels of validation that can be done. The following functions are used for validation purposes

1. List functions – returning values in a list format
2. Retrieving master settings – returns configuration settings
3. Other Validations – year period availability check / account structure validation

1.1 List functions

There are two list functions

1. Offices – which companies are setup in the database
2. Dimensions – which nominal codes, cost centers, projects are setup in a company

1.2 Retrieving master settings

The following functions allows you to determine the configuration settings in Twinfield

1. Office
2. Dimension
3. Dimension type
4. Dimension groups
5. Credit Management Actions
6. Currency
7. VAT

1.3 Other Validations

The following validation functions are available

1. Year/period validation
2. Validate the account structure between dimensions

2. List functions

There are circumstances whereby you want to review a listing of the available companies or dimensions. In that case you should use the list functions.

2.1 List of offices

Description of the offices list elements

Tag	Parent node	Description	Type definition
List	-	root node	-
Type	list	List type, fixed value: “offices”	FIXED VALUE

2.1.1. Example – List of offices

This example gives a list of available companies in a certain database. In this case it is not required to specify an office code as the query returns a listing of all companies.

2.1.2. Request XML – List of offices

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<list>
  <type>offices</type>
</list>
```

2.1.3. Response XML – List of offices

```
<offices result="1">
  <office name="Webshop JJLammers.com" shortname="">0000</office>
  <office name="Fotowinkel.nl" shortname="">0001</office>
</offices>
```

2.2 List of dimensions

In the standard Twinfield template there are 8 dimension types. To retrieve a listing of all the codes linked to each dimension type you can use the following XML.

Description of the dimension list elements

Tag	Parent node	Description	Type definition
list	-	root node	-
type	list	List type, fixed value: “dimensions”	FIXED VALUE
office	list	Office code	CODE
dimtype	list	Dimension type	ENUMERATION: - BAS ➔ Balancesheet - PNL ➔ Profit & Loss - DEB ➔ Customers - CRD ➔ Suppliers - KPL ➔ Cost Centers - PRJ ➔ Projects - AST ➔ Assets - ACT ➔ Activity (time & expenses)

2.2.1. Example

This example gives a list of all cost centers (Dimension type: KPL).

2.2.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<list>
  <type>dimensions</type>
  <office>0000</office>
  <dimtype>KPL</dimtype>
</list>
```

2.2.3. Response XML

```
<dimensions office="0000" type="KPL" result="1">
  <dimension name="Sales & Markerting" shortname="">00001</dimension>
  <dimension name="" shortname="">KPL</dimension>
</dimensions>
```

The company “0000” has 1 cost centre called “Sales & Marketing”. The 2nd dimension name that is returned with the code KPL is a template record in Twinfield meaning that this record is used to create new cost centres

2.3 Budget vs Actuals

Description of the Budget vs Actuals list elements

Tag	Parent node	Description	Type definition
list	-	root node	-
type	list	List type, fixed value: “budgets”	FIXED VALUE
year	list	Fiscal year	INTEGER
periodfrom	list	Fiscal period from	INTEGER
periodto	list	Fiscal period to	INTEGER
budget	list	Budget code	CODE
dim1from	list	GL Account code from	CODE
dim1to	list	GL Account code to	CODE
status	list	Transaction status.	ENUMERATION: - final - concept - both

2.3.1. Example

This example returns a list dimensions with the group hierarchy of the posted actuals compared to the available budgets. If there is no budget available the budget values are ‘0.00’.

2.3.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<list>
  <type>budgets</type>
  <office>0000</office>
  <year>2007</year>
  <periodfrom>0</periodfrom>
  <periodto>12</periodto>
  <budget>0000</budget>
  <budget>001</budget>
  <dim1from>0000</dim1from>
  <dim1to>9999</dim1to>
  <status>both</status>
</list>
```

2.3.3. Response XML

```
<budgets
     office="0000" officename="Webshop JJLammers.com" year="2007"
     result="1">
  <budget>
    <period>3</period>
    <dim1 type="BAS" name="Debiteuren">1300</dim1>
  <groups>
    <group id="1" name="Vorderingen">GLB40</group>
    <group id="2" name="Debiteuren">SLB40.10</group>
    <group id="3" name="" />
    </groups>
    <current>
      <debit>578.00</debit>
      <credit>0.00</credit>
      <balance>578.00</balance>
    </current>
    <budget>
      <debit>200.00</debit>
      <credit>0.00</credit>
      <balance>200.00</balance>
    </budget>
    <balance>-378.00</balance>
  </budget>
  <budget>…</budget>
</budgets>
```

3. Retrieving master data

There are many configuration settings in Twinfield that determine how data should be posted. The following master data functions allow you to retrieve settings

3. Office master settings – all configuration settings on a company level
4. Dimension master – configuration settings on a dimension (code) level
5. Dimension type – settings on dimension type level
6. Dimension groups – dimension groups
7. Credit Management Actions – available credit management settings
8. Currency – currency exchange rates
9. VAT – VAT settings

3.1 Office master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
office	-	root node	- (optional)
code	office	Office code	CODE

3.1.1. Example

This example returns the settings of office 0000.

3.1.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<office>
  <code>0000</code>
</office>
```

3.2 Dimension master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
dimension	-	root node	- (optional)
office	-	Office code	CODE, optional
code	dimension	Dimension code	CODE
type	dimension	Dimension type	CODE

3.2.1. Example

This example returns the settings of customer 1001. The description and definition of the result XML is described in the document MAN-DIMENSIONS.

3.2.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<dimension>
  <office>0000</office>
  <code>1001</code>
  <type>DEB</type>
</dimension>
```

3.3 Dimension type master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
dimensiontype	-	root node	- (optional)
Office	dimensiontype	Office code	CODE
Code	dimensiontype	Dimension type	CODE

3.3.1. Example

This example returns the settings of customer 1001. The description and definition of the result XML is described in the document MAN-DIMENSIONS.

3.3.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<dimensiontype>
  <office>0000</office>
  <code>DEB</code>
</dimensiontype>
```

3.4 Dimension group master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
dimensiongroup	-	root node	- (optional)
Office	dimensiongroup	Office code	CODE
Code	dimensiongroup	Dimension group	CODE

3.4.1. Example

This example returns the settings and list of related dimensions of dimension group LOC_CUST. The description and definition of the result XML is described in the document MAN-DIMENSIONS.

3.4.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<dimensiongroup>
  <office>0000</office>
  <code>LOC_CUST</code>
</dimensiongroup>
```

3.5 Credit management actions master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
Cmaction	-	root node	- (optional)
office	cmaction	Office code	CODE
code	cmaction	Credit management action	CODE

3.5.1. Example

This example returns the settings of customer 1001. The description and definition of the result XML is described in the document MAN-DIMENSIONS.

3.5.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<cmaction>
  <office>0000</office>
  <code>100</code>
</cmaction>
```

3.6 Currency master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
Currency	-	root node	- (optional)
Office	currency	Office code	CODE, optional
code	currency	ISO currency code	CODE

3.6.1 Example

This example returns the currency settings and rates of the USD.

3.6.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<currency>
  <office>0000</office>
  <code>USD</code>
</currency>
```

3.7 VAT master

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
Vat	-	root node	- (optional)
Office	vat	Office code	CODE
Code	vat	VAT code	CODE

3.7.1. Example

This example returns the VAT settings of the IH (purchase high 19%).

3.7.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<vat>
  <office>0000</office>
  <code>100</code>
</vat>
```

4. Validations

The following validation functions are available:

1. Year/period validation
2. Validate the account structure

4.1 Year/period validation

Description of the year/period validation elements

Tag	Parent node	Description	Type definition
periods	-	root node	- (optional)
period	periods	node	
office	period	Office code	CODE, optional
year	period	Fiscal year	INTEGER, optional
period	period	Fiscal period	INTEGER, optional
yearperiod	period	Fiscal year and period	PERIOD

4.1.1. Example

This example validates weather the period 2003/1 and 2007/1 is open for posting journals in the offices 0000 Webshop JJLammers.com and 0001 PhotoPrint.com.

4.1.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<periods>
  <period>
    <office>0000</office>
    <yearperiod>2003/1</yearperiod>
  </period>
  <period>
    <year>2003</year>
    <period>1</period>
  </period>
  <period>
    <office>0001</office>
    <yearperiod>2003/1</yearperiod>
  </period>
  <period>
    <office>0000</office>
    <yearperiod>2007/1</yearperiod>
  </period>
</periods>
```

4.1.3. Response XML

```
<periods result="1">
  <period msg="Period (2003/1) is closed." msgtype="error" result="0">
    <office>0000</office>
    <yearperiod>2003/1</yearperiod>
    <year>2003</year>
    <period>1</period>
  </period>
  <period msg="Period (2003/1) is closed." msgtype="error" result="0">
    <year>2003</year>
    <period>1</period>
    <office name="Webshop JJLammers.com" shortname="">0000</office>
    <yearperiod>2003/1</yearperiod>
  </period>
  <period msg="Period (2003/1) is closed." msgtype="error" result="0">
    <office name="PhotoPrint.com" shortname="">0001</office>
    <yearperiod>2003/1</yearperiod>
    <year>2003</year>
    <period>1</period>
  </period>
  <period result="1">
    <office>0000</office>
    <yearperiod>2007/1</yearperiod>
    <year>2007</year>
    <period>1</period>
  </period>
</periods>
```

4.2 Validate the account structure

Description of the dimension account validation elements

Tag	Parent node	Description	Type definition
accountcodes	-	root node	- (optional)
accountcode	accountcodes	node	-
office	accountcode	Office code	CODE, optional
period	accountcode	Fiscal period	PERIOD, optional
dimension1	accountcode	GL Account code	CODE, optional
dimension2	accountcode	Customer-, Supplier- or Cost Center code	CODE, optional
dimension3	accountcode	Project- or Asset code	CODE, optional
dimension4	accountcode	Activity code (time & expenses	CODE, optional

4.2.1. Example

This example validates the following issues:

1. Is period 2003/1 available for GL Account 1000, results in an error message.
2. Does dimension 1200 exists, results in an error message.
3. Determine the default GL Account for customer 1001, fills in the GL Account (1301)
4. Is the combination of GL Account 1300 and Customer 1001 valid, which is valid.
5. Is the combination of GL Account 1600 and Customer 1001 valid, results in an error message.

4.2.2. Request XML

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<accountcodes>
  <accountcode section="financials"> <!-- Validation #1 -->
    <period>2003/1</period>
    <dimension1>1000</dimension1>
  </accountcode>
  <accountcode section="financials"> <!-- Validation #2 -->
    <dimension1>1200</dimension1>
  </accountcode>
  <accountcode section="financials"> <!-- Validation #3 -->
    <office>0000</office>
    <dimension1/>
    <dimension2>1001</dimension2>
  </accountcode>
  <accountcode section="financials"> <!-- Validation #4 -->
    <dimension1>1300</dimension1>
    <dimension2>1001</dimension2>
  </accountcode>
  <accountcode section="financials"> <!-- Validation #5 -->
    <dimension1>1600</dimension1>
    <dimension2>1001</dimension2>
  </accountcode>
</accountcodes>
```

4.2.3. Response XML

```
<accountcodes result="0">
  <accountcode section="financials"
     msg="Period (2003/1) is closed." msgtype="error" result="0">
  <office>0000</office>
  <period>2003/1</period>
  <dimension1 type="BAS" inuse="false"
     name="Kas" shortname="Kas" vatcode=""
     vatobligatory="false">1000</dimension1>
  </accountcode>
  <accountcode section="financials" result="0">
    <office>0000</office>
    <dimension1
     msg="Dimension (1200) does not exist in company (0000)."
     msgtype="error" result="0">1200</dimension1>
  </accountcode>
  <accountcode section="financials" result="1">
    <office>0000</office>
    <dimension1 type="BAS" inuse="true"
     name="Deb. buitenland" shortname="" vatcode=""
     vatobligatory="false">1301</dimension1>
    <dimension2 type="DEB" inuse="true"
     name="Customer 1001" shortname="" vatcode=""
     vatobligatory="false">1001</dimension2>
  </accountcode>
  <accountcode section="financials" result="1">
    <office>0000</office>
    <dimension1 type="BAS" inuse="true"
     name="Debiteuren" shortname="Debiteuren" vatcode=""
     vatobligatory="false">1300</dimension1>
    <dimension2 type="DEB" inuse="true"
     name="Customer 1001" shortname="" vatcode=""
     vatobligatory="false">1001</dimension2>
  </accountcode>
  <accountcode section="financials" result="0">
    <office>0000</office>
    <dimension1 type="BAS" inuse="true"
     name="Crediteuren" shortname="Crediteuren" vatcode=""
     vatobligatory="false">1600</dimension1>
    <dimension2 type="DEB" inuse="true"
     name="Customer 1001" shortname="" vatcode="" vatobligatory="false"
     msg="The format of the dimension type 'DEB' of dimension 'Customer
     1001' (1001) at level 2 must comply with 'CRD'."
     msgtype="error" result="0">1001</dimension2>
  </accountcode>
</accountcodes>
```