



Test your
knowledge
on working
with
subqueries

1. Which of the following queries contain subqueries? Select all that apply.

1 / 1 point



```
1 SELECT call
2 FROM recordings
3 ORDER BY call.employee_id, call.start_time
```



```
1 SELECT price
2 FROM sales
3 WHERE price = (SELECT MAX (salary)
4 FROM sales)
```



Correct

The two queries with statements in parentheses contain subqueries. A subquery is a SQL query that is nested inside a larger query.



```
1 SELECT employee_id
2 FROM employees
3 WHERE department_id IN (SELECT department_id
4 FROM departments
5 WHERE location_id = 1000)
```



Correct

The two queries with statements in parentheses contain subqueries. A subquery is a SQL query that is nested inside a larger query.



```
1 SELECT product_name,
2 CASE
3 WHEN price < 10 THEN 'Low price'
4 WHEN price >= 10 AND price < 20 THEN 'Medium price'
5 ELSE 'High price'
6 END AS price_category
7 FROM products
```

2. When working with subqueries, which query will execute first?

1 / 1 point

- ☐ Outermost
- ☐ Rightmost
- ☐ Leftmost
- ☒ Innermost

✓ Correct

When working with subqueries, the innermost query will execute first.

3. Which **HAVING** clause indicates to only retrieve products that have been sold more than 100 times?

1 / 1 point

- ☒ **HAVING** COUNT (order_items.product_id) > 100
- ☐ **HAVING** COUNT (order_items.product_id) < 100
- ☐ **HAVING** (order_items.product_id) > 100
- ☐ **HAVING** (order_items.product_id > 100)

✓ Correct

The **HAVING** clause **HAVING** COUNT (order_items.product_id) > 100 indicates to only retrieve products that have been sold more than 100 times.

4. Fill in the blank: A data professional uses the SQL _____ statement to return records that meet conditions by including an if/then statement in a query.

1 / 1 point

- ☒ **CASE**
- ☐ **HAVING**
- ☐ **WHEN**
- ☐ **CONCAT**

✓ Correct

A data professional uses the SQL **CASE** statement to return records that meet conditions by including an if/then statement in a query.