

```
hive> show databases;
```

```
hive> use flights_info;
```

```
hive> CREATE TABLE flight (flight_id INT, flight_date STRING, carrier STRING, origin  
STRING, destination STRING, dep_delay INT, arr_delay INT) row format delimited fields  
terminated by ',' stored as textfile;
```

```
OK
```

```
Time taken: 0.268 seconds
```

```
hive> INSERT INTO TABLE flight VALUES (1001, '2008-01-01', 'AA', 'JFK', 'LAX', 10, 5);
```

```
hive> select * from flight;
```

```
hive> ALTER TABLE flight ADD COLUMNS (flight_duration INT);
```

```
OK
```

```
Time taken: 0.081 seconds
```

```
hive> CREATE EXTERNAL TABLE IF NOT EXISTS external_airports (airport_code  
STRING, airport_name STRING, city STRING, state string) row format delimited fields terminated  
by ',' stored as textfile;
```

```
OK
```

```
hive> insert into table external_airports values("CSTM", "shivaji maharaj", "mumbai", "MH");
```

```
Time taken: 9.671 seconds
```

```
hive> LOAD DATA LOCAL INPATH '/home/parallels/external_airports.txt' INTO TABLE  
external_airports;
```

```
Loading data to table flights_info.external_airports
```

```
Table flights_info.external_airports stats: [numFiles=1, totalSize=298]
```

```
OK
```

```
hive> select * from external_airports;
```

```
OK
```

```
hive> LOAD DATA LOCAL INPATH '/home/parallels/flights.txt' INTO TABLE flights;
```

```
hive> select * from flights;
```

```
OK
```

```
Hive> SELECT f.flight_id, a.airport_name FROM flights f JOIN external_airports a ON f.origin =  
a.airport_code;
```

```
hive> SELECT AVG(dep_delay) AS avg_departure_delay FROM flights;
```

```
hive> CREATE INDEX idx_airport_code ON TABLE external_airports(airport_code) AS  
'COMPACT' WITH DEFERRED REBUILD;
```

```
hive> ALTER INDEX idx_airport_code ON external_airports REBUILD;
```