

A

B

C


D

A


B

C


D



Title		
Size	Number	Revision
A4		
Date:	2019. 07. 02.	Sheet of
File:	D:\Work\Soma\main.SchDoc	Drawn By:



Title		
Size A3	Number	Revision
Date: 2019. 07. 02.	Sheet of	
File: D:\Work\Soma\power.SchDoc	Drawn By:	



Comment	Description	Designator	Footprint	LibRef	Quantity
R60DF4220506AJ	General Purpose Metallized Polyester Film Capacitor, 2.2 uF, 40 VAC, 63 VDC, 5 %	C1, C10	10mm lead spacing CAP	R60DF4220506AJ	2
VJ0805Y104JXATW1BC	SMD Multilayer Ceramic Capacitor, 0805 [2012 Metric], 0.1 uF, 50 V, ± 5%, X7R, VJ Series	C2, C11	0805	VJ0805Y104JXATW1BC	2
EEU-FR1V471	Aluminum Electrolytic Capacitors, 470uF, Low ESR	C3, C12	5mm lead spacing ELCAP	EEU-FR1V471	2
100nF	Capacitor	C4, C5, C6, C14, C15, C30, C46	FP_0805_CAP_085	CAP 100nF	7
VJ0805Y105KXQTW1BC	SMD Multilayer Ceramic Capacitor, 0805 [2012 Metric], 1 uF, 10 V, ± 10%, X7R, VJ Series	C7, C13, C24, C28, C36, C52	0805	VJ0805Y105KXQTW1BC	6
22pF	Capacitor	C8, C9, C16, C17, C31, C47	FP_0805_CAP_085	CAP 22pF	6
CL32A226KOJNNNE	22uF 1210 10% 16V XSR CL32A226KOJNNNE (SAM) [ 82-08-05 ]	C18, C19, C20, C21, C32, C33, C48, C49	1210	CL32A226KOJNNNE	8
885012209005	SMD Multilayer Ceramic Capacitor, 1210 [3225 Metric], 10 uF, 10 V, ± 10%, X7R, WCAP-CSGP Series	C22, C23, C26, C27, C34, C35, C50, C51	1210	885012209005	8
CC0805JRNPO8BN332	3.3nF 0805 5% 25V NPO CC0805JRNPO8BN332 (VAG) [ 82-04-69 ]	C25, C29, C37, C53	0805	CC0805JRNPO8BN332	4
SS32A	3A 40V DO-214AC SCH RECT. SS34A (QET) SMA (SK34A-SX34) [ 83-02-56 ]	D1, D2	DO-214AC(SMA)	SS32A	2
M3 screw drillhole	5mm diameter via with 3mm hole	I1, I2, I3, I4	3mm diameter drill	M3 screw drillhole	4
43-17-42	TAPCSATL 2.00mm 4P APA 90° NCW2005-04R (G-S) FORR [ 43-17-42 ]	Inkrement	43-17-42	43-17-42	1
1935776	PCB terminal block, nominal current: 32 A, nom. voltage: 400 V, pitch: 5 mm, number of positions: 2	J1, J8	PT 2,5/ 2-5,0-H	1935776	2
3-Pin HEADER		J2, J3	3-Pin HEADER	3-Pin HEADER	2
4-Pin Header		J4, J5, PRG	4-Pin Header	4-Pin Header	3
2-Pin Header	TUSKESOR 2 P SMD SPHSS220-802-4/3 (T-T) 2mm PIN 0.5x0.5 TORDELHETO [ 43-10-37 ]	JUMP, JUMP1, JUMP2, JUMP3, JUMP4, UART	2-Pin Header	2-Pin Header	6
VLS6045EX-4R7M	Power Inductor (SMD), 4.7 uH, 4.2 A, Wirewound, 5.8 A, VLS-EX Series, 6mm x 6mm x 4.5mm	L1, L2, L3	TDK_IND_6045	VLS6045EX-4R7M	3
VLS5045EX-3R3N	Power Inductor (SMD), 3.3 uH, 4.2 A, Wirewound, 5.2 A, VLS-EX series, 5mm x 5mm x 4.5mm	L5	TDK_IND_5045	VLS5045EX-3R3N	1
KPT-2012SURCK	LED, Low Power, Red, SMD, 2 mA, 1.95 V, 630 nm	L6	0808-LED	KPT-2012SURCK	1
10K	Resistor	R1, R2, R3, R8, R14, R17, R18, R19, R20, R21, R22, R23, R24, R25	FP_0805_RES	RES 10K	14
CR0805-FX-1963ELF	SMD Chip Resistor, 196kOhm, 0805	R4, R9	0805-W	CR0805-FX-1963ELF	2
CR0805-FX-1333ELF	SMD Chip Resistor, 133kOhm, 0805	R5	0805-W	CR0805-FX-1333ELF	1
CR0805-FX-240ZELF	SMD Chip Resistor, 24kOhm, 0805	R6, R7, R10	0805-W	CR0805-FX-240ZELF	3
CRCW0805B4K5FKEA	SMD Chip Resistor, 84.5 kohm, CRCW Series, 150 V, Thick Film, 0805 [2012 Metric], 125 mW	R15	0805-W	CRCW0805B4K5FKEA	1
MCMR08X2552FTL	SMD Chip Resistor, Ceramic, 25.5 kohm, MCMR Series, 150 V, Thick Film, 0805 [2012 Metric], 125 mW	R16	0805-W	MCMR08X2552FTL	1
IRLR8743TRLPBF	HEXFET 2Power MOSFET, Vdss=30V, Rdson=3.1mOhm, Qg=39nC, Id=1A0A	U1, U3, U4, U7	TO-252 (DPAK)	IRLR8743TRLPBF	4
IRS21865TRPBF	High and Low Side Driver	U2, U6	8-Pin SOIC	IRS21865TRPBF	2
STM32F030K6t6	Value-line ARM®-based 32-bit MCU with up to 256 KB Flash, timers, ADC, communication interfaces, 2.4-3.6 V operation	U5	LOFP-32	STM32F030K6t6	1
TPS54227DDAR	DC-DC Switching (Step Down) Regulator, Adjustable, 700 kHz, 4.5-18Vin, up to 7V/2Aout, SO PowerPAD-8	U8, U9, U10, U12	8-Pin HSOP with ThermalPad	TPS54227DDAR	4
BCV72	NPN general purpose transistors	U13	SOT23	BCV72	1
ABLS-8.000MHZ-B4-T	Crystal, 8 MHz, SMD, 11.5mm x 4.7mm, 50 ppm, 18 pF, 30 ppm, ABLS Series	Y1	HC/49US (AT49)	ABLS-8.000MHZ-B4-T	1