

# CS685: DATA MINING CLUSTERING

Arnab Bhattacharya  
arnabb@cse.iitk.ac.in

Computer Science and Engineering,  
Indian Institute of Technology, Kanpur  
<http://web.cse.iitk.ac.in/~cs685/>

1<sup>st</sup> semester, 2020-21  
Mon 1030-1200 (online)

# Clustering

- A dataset of  $n$  objects  $O_i, i = 1, \dots, n$
- Partitioning of the dataset into  $k$  clusters or groups
- Can be
  - **Crisp**: Each object belongs to one and only one cluster
  - **Fuzzy**: An object belongs to a cluster with a probability; such probabilities add up to 1
- **Unsupervised learning**
- Sometimes very useful to learn structures in the data

# Clustering

- A dataset of  $n$  objects  $O_i, i = 1, \dots, n$
- Partitioning of the dataset into  $k$  **clusters** or groups
- Can be
  - **Crisp**: Each object belongs to one and only one cluster
  - **Fuzzy**: An object belongs to a cluster with a probability; such probabilities add up to 1
- **Unsupervised learning**
- Sometimes very useful to learn structures in the data
- Five main types
  - Partitioning-based
  - Hierarchical
    - *Agglomerative* or bottom-up
    - *Divisive* or top-down
  - Density-based
  - Grid-based
  - Model-based

# Clustering Issues

- Scalability
  - Dealing with large datasets

# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets

# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets
- Measure of similarity
  - Euclidean distance
  - Similarity (or equivalently, distance) matrix

# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets
- Measure of similarity
  - Euclidean distance
  - Similarity (or equivalently, distance) matrix
- Shape of cluster
  - Convex versus arbitrary

# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets
- Measure of similarity
  - Euclidean distance
  - Similarity (or equivalently, distance) matrix
- Shape of cluster
  - Convex versus arbitrary
- Incremental
  - Ability to handle new data objects



# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets
- Measure of similarity
  - Euclidean distance
  - Similarity (or equivalently, distance) matrix
- Shape of cluster
  - Convex versus arbitrary
- Incremental
  - Ability to handle new data objects
- Data input order
  - Sensitivity to order of input

# Clustering Issues

- Scalability
  - Dealing with large datasets
- Types of objects
  - Vectors
  - Images
  - Documents
  - Sets
- Measure of similarity
  - Euclidean distance
  - Similarity (or equivalently, distance) matrix
- Shape of cluster
  - Convex versus arbitrary
- Incremental
  - Ability to handle new data objects
- Data input order
  - Sensitivity to order of input
- Noise
  - Detection of outliers
  - Noise objects as separate cluster

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better
  - *Cluster completeness*: A more complete cluster, i.e., one that contains more points from the same category, is better

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better
  - *Cluster completeness*: A more complete cluster, i.e., one that contains more points from the same category, is better
  - *Rag bag*: It is better to cluster “heterogeneous” points in a separate “others” cluster

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better
  - *Cluster completeness*: A more complete cluster, i.e., one that contains more points from the same category, is better
  - *Rag bag*: It is better to cluster “heterogeneous” points in a separate “others” cluster
  - *Small cluster preservation*: Smaller clusters should be preserved more as otherwise they break into noise pieces



# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better
  - *Cluster completeness*: A more complete cluster, i.e., one that contains more points from the same category, is better
  - *Rag bag*: It is better to cluster “heterogeneous” points in a separate “others” cluster
  - *Small cluster preservation*: Smaller clusters should be preserved more as otherwise they break into noise pieces
- When no “ground” truth is available, i.e, the actual clusters are not known,

# Cluster Evaluation Methods

- When *ground truth* is known, **extrinsic** methods or *supervised* methods are used
- Extrinsic methods evaluate based on four criteria
  - *Cluster homogeneity*: A purer cluster is better
  - *Cluster completeness*: A more complete cluster, i.e., one that contains more points from the same category, is better
  - *Rag bag*: It is better to cluster “heterogeneous” points in a separate “others” cluster
  - *Small cluster preservation*: Smaller clusters should be preserved more as otherwise they break into noise pieces
- When no “ground” truth is available, i.e, the actual clusters are not known, use **silhouette coefficient**
- These are called **intrinsic** methods or *unsupervised* methods

# Neighboring Cluster of an Object

- Suppose object  $O_i$  is in cluster  $A$ , i.e.,  $O_i \in A$
- Define  $a_i$  as the *average* distance of  $O_i$  to  $A$

$$a_i = \frac{\sum_{p \in A} d(o_i, p)}{|A|}$$

- Similarly, define  $d_i(C)$  to be the *average* distance of  $O_i$  to any other cluster  $C$

$$d_i(C) = \frac{\sum_{q \in C} d(o_i, q)}{|C|}$$

# Neighboring Cluster of an Object

- Suppose object  $O_i$  is in cluster  $A$ , i.e.,  $O_i \in A$
- Define  $a_i$  as the *average* distance of  $O_i$  to  $A$

$$a_i = \frac{\sum_{p \in A} d(o_i, p)}{|A|}$$

- Similarly, define  $d_i(C)$  to be the *average* distance of  $O_i$  to any other cluster  $C$

$$d_i(C) = \frac{\sum_{q \in C} d(o_i, q)}{|C|}$$

- Suppose  $B$  is the cluster that minimizes this distance and  $b_i$  be the corresponding distance, i.e.,

$$b_i = \min d_i(C)$$

$$B = \arg \min d_i(C)$$

# Neighboring Cluster of an Object

- Suppose object  $O_i$  is in cluster  $A$ , i.e.,  $O_i \in A$
- Define  $a_i$  as the *average* distance of  $O_i$  to  $A$

$$a_i = \frac{\sum_{p \in A} d(o_i, p)}{|A|}$$

- Similarly, define  $d_i(C)$  to be the *average* distance of  $O_i$  to any other cluster  $C$

$$d_i(C) = \frac{\sum_{q \in C} d(o_i, q)}{|C|}$$

- Suppose  $B$  is the cluster that minimizes this distance and  $b_i$  be the corresponding distance, i.e.,

$$b_i = \min d_i(C)$$

$$B = \arg \min d_i(C)$$

- In a sense, cluster  $B$  is the “neighbor” of  $O_i$
- $O_i$  could have been in cluster  $B$  instead of  $A$

# Silhouette Index

- **Silhouette index** or **silhouette coefficient** of object  $O_i$  captures the difference of these two distances

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

# Silhouette Index

- **Silhouette index** or **silhouette coefficient** of object  $O_i$  captures the difference of these two distances

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

- $-1 \leq s_i \leq +1$ 
  - If  $s_i \rightarrow +1$ ,  $b_i \gg a_i$  and  $O_i$  is in a good cluster
  - If  $s_i \approx 0$ ,  $b_i \approx a_i$  and  $O_i$  could have been in  $B$  as well
  - If  $s_i < 0$ ,  $b_i < a_i$  and  $O_i$  is better in  $B$  than current cluster

# Silhouette Index

- **Silhouette index** or **silhouette coefficient** of object  $O_i$  captures the difference of these two distances

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

- $-1 \leq s_i \leq +1$ 
  - If  $s_i \rightarrow +1$ ,  $b_i \gg a_i$  and  $O_i$  is in a good cluster
  - If  $s_i \approx 0$ ,  $b_i \approx a_i$  and  $O_i$  could have been in  $B$  as well
  - If  $s_i < 0$ ,  $b_i < a_i$  and  $O_i$  is better in  $B$  than current cluster
- Using these, **average silhouette width** of a cluster and of the entire dataset can be defined



# Silhouette Index

- **Silhouette index** or **silhouette coefficient** of object  $O_i$  captures the difference of these two distances

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

- $-1 \leq s_i \leq +1$ 
  - If  $s_i \rightarrow +1$ ,  $b_i \gg a_i$  and  $O_i$  is in a good cluster
  - If  $s_i \approx 0$ ,  $b_i \approx a_i$  and  $O_i$  could have been in  $B$  as well
  - If  $s_i < 0$ ,  $b_i < a_i$  and  $O_i$  is better in  $B$  than current cluster
- Using these, **average silhouette width** of a cluster and of the entire dataset can be defined
- Choose  $k$  that *maximizes* average silhouette width of the dataset,  $\bar{s}_k$

# Silhouette Index

- **Silhouette index** or **silhouette coefficient** of object  $O_i$  captures the difference of these two distances

$$s_i = \frac{b_i - a_i}{\max\{a_i, b_i\}}$$

- $-1 \leq s_i \leq +1$ 
  - If  $s_i \rightarrow +1$ ,  $b_i \gg a_i$  and  $O_i$  is in a good cluster
  - If  $s_i \approx 0$ ,  $b_i \approx a_i$  and  $O_i$  could have been in  $B$  as well
  - If  $s_i < 0$ ,  $b_i < a_i$  and  $O_i$  is better in  $B$  than current cluster
- Using these, **average silhouette width** of a cluster and of the entire dataset can be defined
- Choose  $k$  that *maximizes* average silhouette width of the dataset,  $\bar{s}_k$
- Different ranges of silhouette index
  - $> 0.75$ : strong clustering
  - $0.5 - 0.75$ : reasonable clustering
  - $0.25 - 0.5$ : weak clustering
  - $< 0.25$ : no structure

# BCubed Measures

- $C$  is a clustering on  $D$
- Labels  $I(O_i)$  are given as ideal (ground truth) for each  $O_i \in D$
- For points  $O_i$  and  $O_j$ , **correctness** is agreement in ground truth

$$correctness(O_i, O_j) = \begin{cases} 1 & \text{if } I(O_i) = I(O_j) \Leftrightarrow C(O_i) = C(O_j) \\ 0 & \text{otherwise} \end{cases}$$

# BCubed Measures

- $C$  is a clustering on  $D$
- Labels  $I(O_i)$  are given as ideal (ground truth) for each  $O_i \in D$
- For points  $O_i$  and  $O_j$ , **correctness** is agreement in ground truth

$$correctness(O_i, O_j) = \begin{cases} 1 & \text{if } I(O_i) = I(O_j) \Leftrightarrow C(O_i) = C(O_j) \\ 0 & \text{otherwise} \end{cases}$$

- **BCubed precision** measures fraction of same-cluster points that agree in ground truth

$$bcprecision = \frac{1}{n} \sum_{i=1}^n \frac{\sum_{O_j, i \neq j, C(O_i)=C(O_j)} correctness(O_i, O_j)}{|\{O_j, i \neq j, C(O_i) = C(O_j)\}|}$$

# BCubed Measures

- $C$  is a clustering on  $D$
- Labels  $I(O_i)$  are given as ideal (ground truth) for each  $O_i \in D$
- For points  $O_i$  and  $O_j$ , **correctness** is agreement in ground truth

$$\text{correctness}(O_i, O_j) = \begin{cases} 1 & \text{if } I(O_i) = I(O_j) \Leftrightarrow C(O_i) = C(O_j) \\ 0 & \text{otherwise} \end{cases}$$

- **BCubed precision** measures fraction of same-cluster points that agree in ground truth

$$\text{bcprecision} = \frac{1}{n} \sum_{i=1}^n \frac{\sum_{O_j, i \neq j, C(O_i)=C(O_j)} \text{correctness}(O_i, O_j)}{|\{O_j, i \neq j, C(O_i) = C(O_j)\}|}$$

- **BCubed recall** measures fraction of same-ground truth points that agree in clustering

$$\text{bcrecall} = \frac{1}{n} \sum_{i=1}^n \frac{\sum_{O_j, i \neq j, I(O_i)=I(O_j)} \text{correctness}(O_i, O_j)}{|\{O_j, i \neq j, I(O_i) = I(O_j)\}|}$$

- Can define **BCubed F-measure** using these

# RAND Index

- **RAND Index** or **RAND Measure** measures how similar two cluster outputs are
- If *ideal* clusters are known, this measures *quality* of a cluster output

# RAND Index

- **RAND Index** or **RAND Measure** measures how similar two cluster outputs are
- If *ideal* clusters are known, this measures *quality* of a cluster output
- Suppose (ideal) clustering is  $I = I_1, \dots, I_m$  where  $I_i$  are partitions
- Cluster to be measured is  $C = C_1, \dots, C_k$
- Consider pairs of objects
  - $a$ : Number of object pairs that are in the same cluster in both  $I$  and  $C$
  - $b$ : Number of object pairs that are in different clusters in both  $I$  and  $C$
  - $c$ : Number of object pairs that are in the same cluster in  $I$  but not in  $C$
  - $d$ : Number of object pairs that are in the same cluster in  $C$  but not in  $I$

# RAND Index

- **RAND Index** or **RAND Measure** measures how similar two cluster outputs are
- If *ideal* clusters are known, this measures *quality* of a cluster output
- Suppose (ideal) clustering is  $I = I_1, \dots, I_m$  where  $I_i$  are partitions
- Cluster to be measured is  $C = C_1, \dots, C_k$
- Consider pairs of objects
  - $a$ : Number of object pairs that are in the same cluster in both  $I$  and  $C$
  - $b$ : Number of object pairs that are in different clusters in both  $I$  and  $C$
  - $c$ : Number of object pairs that are in the same cluster in  $I$  but not in  $C$
  - $d$ : Number of object pairs that are in the same cluster in  $C$  but not in  $I$
- RAND Index is

$$R = \frac{a + b}{a + b + c + d} = \frac{a + b}{\binom{n}{2}} = \frac{TP + TN}{D}$$



# Adjusted RAND Index

- Adjusted RAND Index (ARI) guards against random matches

# Adjusted RAND Index

- Adjusted RAND Index (ARI) guards against random matches

$$ARI = \frac{\text{RAND Index} - \text{Expected RAND Index}}{\text{Maximum RAND Index} - \text{Expected RAND Index}}$$

# Adjusted RAND Index

- Adjusted RAND Index (ARI) guards against random matches

$$ARI = \frac{\text{RAND Index} - \text{Expected RAND Index}}{\text{Maximum RAND Index} - \text{Expected RAND Index}}$$

- Contingency table of common objects

| Clusters | $C_1$    | $\cdots$ | $C_k$    | Total    |
|----------|----------|----------|----------|----------|
| $I_1$    | $n_{11}$ | $\cdots$ | $n_{1k}$ | $i_1$    |
| $\vdots$ | $\vdots$ | $\ddots$ | $\vdots$ | $\vdots$ |
| $I_m$    | $n_{m1}$ | $\cdots$ | $n_{mk}$ | $i_m$    |
| Total    | $c_1$    | $\cdots$ | $c_k$    | $n$      |

# Adjusted RAND Index

- Adjusted RAND Index (ARI) guards against random matches

$$ARI = \frac{\text{RAND Index} - \text{Expected RAND Index}}{\text{Maximum RAND Index} - \text{Expected RAND Index}}$$

- Contingency table of common objects

| Clusters | $C_1$    | $\cdots$ | $C_k$    | Total    |
|----------|----------|----------|----------|----------|
| $I_1$    | $n_{11}$ | $\cdots$ | $n_{1k}$ | $i_1$    |
| $\vdots$ | $\vdots$ | $\ddots$ | $\vdots$ | $\vdots$ |
| $I_m$    | $n_{m1}$ | $\cdots$ | $n_{mk}$ | $i_m$    |
| Total    | $c_1$    | $\cdots$ | $c_k$    | $n$      |

- Expected number of pair matches assuming the same total distribution is

$$E \left[ \sum_{i,j} \binom{n_{ij}}{2} \right] = \left[ \sum_i \binom{n_{i\cdot}}{2} \cdot \sum_j \binom{n_{\cdot j}}{2} \right] / \binom{n}{2}$$

# Adjusted RAND Index

- ARI can be written as

$$ARI = \frac{\sum_{i,j} \binom{n_{ij}}{2} - \left[ \sum_i \binom{n_{i\cdot}}{2} \cdot \sum_j \binom{n_{\cdot j}}{2} \right] / \binom{n}{2}}{\frac{1}{2} \left[ \sum_i \binom{n_{i\cdot}}{2} + \sum_j \binom{n_{\cdot j}}{2} \right] - \left[ \sum_i \binom{n_{i\cdot}}{2} \cdot \sum_j \binom{n_{\cdot j}}{2} \right] / \binom{n}{2}}$$

- RAND Index is always between 0 and 1
- ARI is between  $-1$  and  $+1$
- ARI is negative when clustering is worse than random

# Example

| Clusters | $C_1$ | $C_2$ | $C_3$ | Total |
|----------|-------|-------|-------|-------|
| $I_1$    | 1     | 1     | 0     | 2     |
| $I_2$    | 1     | 2     | 1     | 4     |
| $I_3$    | 0     | 0     | 4     | 4     |
| Total    | 2     | 3     | 5     | 10    |

- Number of pairs agreeing, i.e.,  $a = \binom{1}{2} + \dots + \binom{4}{2} = 7$

# Example

| Clusters | $C_1$ | $C_2$ | $C_3$ | Total |
|----------|-------|-------|-------|-------|
| $I_1$    | 1     | 1     | 0     | 2     |
| $I_2$    | 1     | 2     | 1     | 4     |
| $I_3$    | 0     | 0     | 4     | 4     |
| Total    | 2     | 3     | 5     | 10    |

- Number of pairs agreeing, i.e.,  $a = \binom{1}{2} + \dots + \binom{4}{2} = 7$
- Number of pairs agreeing in  $I$  but not in  $C$ , i.e.,  
 $c = \binom{2}{2} + \binom{4}{2} + \binom{4}{2} - 7 = 13 - 7 = 6$
- Number of pairs agreeing in  $C$  but not in  $I$ , i.e.,  
 $d = \binom{2}{2} + \binom{3}{2} + \binom{5}{2} - 7 = 14 - 7 = 7$

# Example

| Clusters | $C_1$ | $C_2$ | $C_3$ | Total |
|----------|-------|-------|-------|-------|
| $I_1$    | 1     | 1     | 0     | 2     |
| $I_2$    | 1     | 2     | 1     | 4     |
| $I_3$    | 0     | 0     | 4     | 4     |
| Total    | 2     | 3     | 5     | 10    |

- Number of pairs agreeing, i.e.,  $a = \binom{1}{2} + \dots + \binom{4}{2} = 7$
- Number of pairs agreeing in  $I$  but not in  $C$ , i.e.,  
 $c = \binom{2}{2} + \binom{4}{2} + \binom{4}{2} - 7 = 13 - 7 = 6$
- Number of pairs agreeing in  $C$  but not in  $I$ , i.e.,  
 $d = \binom{2}{2} + \binom{3}{2} + \binom{5}{2} - 7 = 14 - 7 = 7$
- Therefore, number of pairs not agreeing, i.e.,  
 $b = \binom{10}{2} - 7 - 6 - 7 = 45 - 20 = 25$



## Example

| Clusters | $C_1$ | $C_2$ | $C_3$ | Total |
|----------|-------|-------|-------|-------|
| $I_1$    | 1     | 1     | 0     | 2     |
| $I_2$    | 1     | 2     | 1     | 4     |
| $I_3$    | 0     | 0     | 4     | 4     |
| Total    | 2     | 3     | 5     | 10    |

- Number of pairs agreeing, i.e.,  $a = \binom{1}{2} + \dots + \binom{4}{2} = 7$
- Number of pairs agreeing in  $I$  but not in  $C$ , i.e.,  
 $c = \binom{2}{2} + \binom{4}{2} + \binom{4}{2} - 7 = 13 - 7 = 6$
- Number of pairs agreeing in  $C$  but not in  $I$ , i.e.,  
 $d = \binom{2}{2} + \binom{3}{2} + \binom{5}{2} - 7 = 14 - 7 = 7$
- Therefore, number of pairs not agreeing, i.e.,  
 $b = \binom{10}{2} - 7 - 6 - 7 = 45 - 20 = 25$
- RAND Index is  $\frac{7+25}{45} = 0.71$

## Example

| Clusters | $C_1$ | $C_2$ | $C_3$ | Total |
|----------|-------|-------|-------|-------|
| $I_1$    | 1     | 1     | 0     | 2     |
| $I_2$    | 1     | 2     | 1     | 4     |
| $I_3$    | 0     | 0     | 4     | 4     |
| Total    | 2     | 3     | 5     | 10    |

- Number of pairs agreeing, i.e.,  $a = \binom{1}{2} + \dots + \binom{4}{2} = 7$
- Number of pairs agreeing in  $I$  but not in  $C$ , i.e.,  
 $c = \binom{2}{2} + \binom{4}{2} + \binom{4}{2} - 7 = 13 - 7 = 6$
- Number of pairs agreeing in  $C$  but not in  $I$ , i.e.,  
 $d = \binom{2}{2} + \binom{3}{2} + \binom{5}{2} - 7 = 14 - 7 = 7$
- Therefore, number of pairs not agreeing, i.e.,  
 $b = \binom{10}{2} - 7 - 6 - 7 = 45 - 20 = 25$
- RAND Index is  $\frac{7+25}{45} = 0.71$
- ARI is  $\frac{7 - (13 \times 14)/45}{(13+14)/2 - (13 \times 14)/45} = 0.31$

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor
- Hopkin's statistic is

$$H = \frac{\sum_{i=1}^p w_i}{\sum_{i=1}^p u_i + \sum_{i=1}^p w_i}$$

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor
- Hopkin's statistic is

$$H = \frac{\sum_{i=1}^p w_i}{\sum_{i=1}^p u_i + \sum_{i=1}^p w_i}$$

- If  $H \approx 0.5$ ,



# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor
- Hopkin's statistic is

$$H = \frac{\sum_{i=1}^p w_i}{\sum_{i=1}^p u_i + \sum_{i=1}^p w_i}$$

- If  $H \approx 0.5$ , then data is mostly uniform
- If  $H \rightarrow 0$ ,

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor
- Hopkin's statistic is

$$H = \frac{\sum_{i=1}^p w_i}{\sum_{i=1}^p u_i + \sum_{i=1}^p w_i}$$

- If  $H \approx 0.5$ , then data is mostly uniform
- If  $H \rightarrow 0$ , then data is clustered
- If  $H \rightarrow 1$ ,

# Clustering Tendency

- Uniform data is poorly clustered
- **Clustering tendency** measures how likely that clusters exist
- Measures how close it is to the *uniform distribution*
- **Hopkin's statistic**
- Generate  $p$  uniformly random points from the data space
- For each point, measure its distance  $u_i$  to nearest neighbor
- Sample  $p$  points from the dataset
- For each point, measure its distance  $w_i$  to nearest neighbor
- Hopkin's statistic is

$$H = \frac{\sum_{i=1}^p w_i}{\sum_{i=1}^p u_i + \sum_{i=1}^p w_i}$$


- If  $H \approx 0.5$ , then data is mostly uniform
- If  $H \rightarrow 0$ , then data is clustered
- If  $H \rightarrow 1$ , then data is regular or sparse

# Subspace Clustering

- Clustering is typically applied on all the dimensions
- May *miss* out structures present in lower dimensional subspaces
- Clusters in lower dimensional spaces are *not* identified in higher dimensions due to randomness in other values



# Subspace Clustering

- Clustering is typically applied on all the dimensions
- May *miss* out structures present in lower dimensional subspaces
- Clusters in lower dimensional spaces are *not* identified in higher dimensions due to randomness in other values
- $\diamond$ ,  $\square$  and  $\triangle$  points cluster
- $\circ$  points weakly cluster





# Clusters in xy Subspace

- In  $x$  space:  $\diamond$ ,  $\square$  and  $\triangle$  points cluster but  $\circ$  acts as noise
- In  $y$  space:  $\square$  separate,  $\circ$  separate,  $\diamond$  and  $\triangle$  together
- In  $xy$  space:  $\diamond$ ,  $\square$  and  $\triangle$  points cluster and  $\circ$  points weakly cluster



# Clusters in xz Subspace

- In  $x$  space:  $\diamond$ ,  $\square$  and  $\triangle$  points cluster but  $\circ$  acts as noise
- In  $z$  space:  $\circ$  separate,  $\square$ ,  $\diamond$  and  $\triangle$  together
- In  $xz$  space:  $\diamond$ ,  $\square$  and  $\triangle$  points cluster and  $\circ$  points weakly cluster



# Clusters in yz Subspace

- In y space: ○ separate, □ separate, ◇ and △ together
- In z space: ○ separate, □, ◇ and △ together
- In yz space: ○ separate, □ separate, ◇ and △ together

