AI AUTOMATED INVOICE LIFECYCLE MANAGEMENT

A PROJECT REPORT

Submitted by

MUKESH N	**111922AI01060**
RAJ KUMAR V	**111922AI01076**
SHAMGANESH S	**111922AI01091**
SOMESHWUR R	**111922AI01096**

in partial fulfillment for the award of the degree

of

B. TECH

IN

ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

S. A. ENGINEERING COLLEGE, CHENNAI – 600077

(Autonomous - Institute Level Research Centre, Affiliated to Anna University)

ANNA UNIVERSITY : CHENNAI 600 025

APRIL 2026

BONAFIDE CERTIFICATE

Certified that this project report **"AI AUTOMATED INVOICE LIFECYCLE MANAGEMENT"** is the bonafide work of "**MUKESH N (111922AI01060), RAJ KUMAR V (111922AI01076), SHAMGANESH S (111922AI01091)** and **SOMESHWUR R (111922AI01096)**" who carried out the project work under my supervision.

SIGNATURE OF HoD
HEAD OF THE DEPARTMENT
Dr. D HEMANAND, M.E., Ph.D.,
Professor & Head,
DEPARTMENT OF AI & DS,
S.A.ENGINEERING COLLEGE,
Avadi – Poonamallee Main Road,
Thiruverkadu Post,
Chennai – 600 077

SIGNATURE OF SUPERVISOR
SUPERVISOR
Mrs. B. ARDLY MELBA REENA, M.,E., (Ph.D).,
Assistant Professor,
DEPARTMENT OF AI & DS,
S.A.ENGINEERING COLLEGE,
Avadi – Poonamallee Main Road,
Thiruverkadu Post,
Chennai – 600 077

Submitted to Project Viva-Voice Examination held on _____

INTERNAL EXAMINER **EXTERNAL EXAMINER**

ACKNOWLEDGEMENT

We owe a great many thanks to a great many people who helped and support us during the completion of our project.

We take this opportunity to express our profound gratitude and deep regards to our Founder Chairman **(Late)** Shri**. D. SUDHARSSANAM, Ex M.L.A,** our Chairman Shri**. D. DURAISWAMY**, our humble Secretary Shri**. D. DASARATHAN** our correspondent Shri. **S. AMARNAATH**, and our Director Shri**. D. SABARINATH**, for their exemplary guidance, monitoring and constant encouragement throughout the course of this thesis. The blessing, help and guidance given by them time to time shall carry us a long way in the journey of life on which we are about to embark.

We also take this opportunity to sincerely thank our Advisor **Prof. Dr. S. SALIVAHANAN, M.E., Ph.D.,** for his guidance. Also we express a deep sense of gratitude to thank our beloved Principal **Dr. S. RAMACHANDRAN, M.E., Ph.D.,** for extending his support. Also we sincerely thank **Dr. D. HEMANAND, M.E., Ph.D.,** Head of the Department of Artificial Intelligence and Data Science for his guidance and encouragement in our project work which helped us in completing this task through various stages.

We are also obliged to convey our special and sincere gratitude to our project coordinators, **Mrs. B. ARDLY MELBA REENA, M.E., (Ph.D).,** Assistant Professor, AI & DS Department, **Mr. G. MUTHUKUMAR, M.E., (Ph.D).,** Assistant Professor, AI & DS Department, and our internal guide, **Mrs. B. ARDLY MELBA REENA, M.E., (Ph.D).,** AI & DS Department, for their encouragement and concern during the review session, along with their valuable advice, knowledge, and expert guidance in our project.

Lastly, we thank almighty, our parents, all the teaching and non-teaching staff for their support and guidance throughout our project and for their constant encouragement without which this project would have not been possible.

ABSTRACT

Invoice processing is an essential task in many organizations, but it is often performed manually, making it time-consuming, error-prone, and inefficient. The AI Automated Invoice Lifecycle Management is designed to automate and streamline the invoice processing workflow using AI techniques. The system allows users to upload invoices in PDF or image formats, and automatically extracts important information using Optical Character Recognition (OCR) and Vision Language Model (VLM) techniques. The extracted raw text is then converted into structured invoice fields such as invoice number, vendor details, dates, line items, quantity, price, and total amount.

After data extraction, the system performs invoice validation to ensure accuracy and completeness by checking mandatory fields and verifying invoice totals. The system also classifies invoices based on predefined rules and tracks the complete invoice lifecycle. In addition, the system incorporates Customer Relationship Management (CRM) analysis, where invoice data is used to identify customer patterns and recommend relevant products through a recommendation mechanism.

To demonstrate enterprise workflow integration, the system simulates CRM and ERP integration, enabling the synchronization of vendor and customer information and forwarding approved invoices for financial processing. The application also includes an inventory management module, which updates inventory records based on purchased items and provides report charts for inventory and invoice statistics. A centralized dashboard allows users to monitor invoice status, system activities, and business insights. Additionally, the system maintains audit logs to track all actions performed on invoices for transparency and compliance.

TABLE OF CONTENTS

S. NO	TITLE	PAGE NO
	ABSTRACT	**IV**
	LIST OF CONTENTS	**V**
	LIST OF FIGURES	**VII**
	LIST OF TABLES	**VIII**
	LIST OF ABBREVIATION	**IX**
1	**INTRODUCTION**	**1**
	1.1. Overview	1
	1.2. Problem Statement	2
	1.3. Aim & Objective	3
	1.4. Scope	4
2	**LITERATURE SURVEY**	**6**
3	**SYSTEM ANALYSIS**	**12**
	3.1. Existing System	12
	3.2. Proposed System	14
	3.3 Comparison Table	19
4	**SOFTWARE CONFIGURATION**	**21**
	4.1. Hardware Requirements	21
	4.2. Software Requirements	22
	4.3. Software Description	22
5	**SYSTEM DESIGN**	**30**
	5.1. System Architecture	30
	5.2. ER Diagram	31
	5.3. OCR Extraction Template	32
	5.4. VLM Extraction Template	33
	5.5. Database Schema	34
6	**SYSTEM IMPLEMENTATION**	**38**
	6.1. System Implementation	38
	6.2. Modules Description	40
7	**SOFTWARE TESTING**	**48**

7.1 System Implementation Analysis 48
7.2. Extraction Performance: OCR vs. VLM 48
7.3. Recommendation Engine Effectiveness 49
7.4 Performance Analysis 59
7.5. Comparative Analysis with Manual Processing 50
8 CONCLUSION 52
8.1. Conclusion 52

APPENDIX 1: SNAPSHOTS 53
APPENDIX 2: SOURCE CODE 59
REFERENCES 80

LIST OF FIGURES

FIGURE NO.	FIGURES	PAGE NO
5.1	System Architecture	30
5.2	ER Diagram	31
5.3	OCR Extraction Template	32
5.4	VLM Extraction Template	33
6.2.1	Invoice Upload Page	
6.2.2	Invoice Extracted and Display Page	34
7.5	Comparative Analysis Existing System vs. Proposed AI-Based Invoice System	51
Appendix1.1	Upload Invoice	53
Appendix1.2	Invoice Dashboard	53
Appendix1.3	Customer Dashboard	54
Appendix1.4	Vendor Dashboard	54
Appendix1.5	Analysis Dashboard	55
Appendix1.6	Payment Dashboard	55
Appendix1.7	Purchase Orders Dashboard	56
Appendix1.8	Expenses Dashboard	56
Appendix1.9	Employees Dashboard	57
Appendix1.10	Inventory Management Dashboard	57
Appendix1.11	Audit & Compliance Dashboard	58

LIST OF TABLES

TABLE NO.	TABLES	PAGE NO
3.3	Comparison Table	19
5.4.1	Invoice Table	34
5.4.2	Vendor Table	35
5.4.3	Customer Table	35
5.4.4	List Item Table	36
5.4.5	Audit Log Table	36
5.4.6	CRM Mapping Table	37
5.4.7	Inventory Management Table	37
5.4.8	Recommendation Table	37
7.2	Extraction Performance: OCR vs. VLM	49
7.5	Comparative Analysis with Manual Processing	51

LIST OF ABBREVIATION

Abbreviation	Full Form
AI	Artificial Intelligence
ML	Machine Learning
NLP	Natural Language Processing
OCR	Optical Character Recognition
VLM	Vision Language Model
CRM	Customer Relationship Management
DFD	Data Flow Diagram
ER	Entity Relationship
API	Application Programming Interface
DBMS	Database Management System
SQL	Structured Query Language
CSV	Comma-Separated Values
JSON	JavaScript Object Notation
KPI	Key Performance Indicator
PDF	Portable Document Format
ANN	Artificial Neural Network
CNN	Convolutional Neural Network

CHAPTER 1
INTRODUCTION

1.1 OVERVIEW

The AI Automated Invoice Lifecycle Management System is a web-based application designed to automate the processing and management of invoices using Artificial Intelligence techniques. The system accepts invoices in PDF and image formats (PNG, JPG) and automatically extracts relevant information from them using OCR and Vision Language Model (VLM) techniques. The extracted raw text is then converted into structured invoice fields such as invoice number, vendor name, date, line items, quantity, price, and total amount.

Once the data is extracted, the system performs invoice validation to ensure that all mandatory fields are present and the information is accurate. The system then analyzes the invoice data and identifies Customer Relationship Management (CRM) patterns, which can be used to recommend relevant products or services based on previous customer interactions, similar to a recommendation system.

The system also performs invoice classification, where invoices are categorized based on predefined rules such as department, invoice type, or priority level. In addition, the application tracks the complete invoice lifecycle, allowing invoices to move through stages such as Upload, Extraction, Validation, Approval, and Processing.

To demonstrate enterprise-level workflow integration, the system simulates CRM and ERP integration, where vendor and customer information is synchronized with CRM modules, and approved invoices are forwarded to ERP modules for financial processing. The system also includes Inventory Management functionality, which updates inventory records based on purchased items listed in invoices.

Furthermore, the system provides inventory management reports with graphical charts to visualize stock levels, invoice trends, and transaction summaries. A centralized dashboard displays invoice statistics such as the number of processed invoices, pending approvals, and validation results. To maintain transparency and compliance, the system maintains audit logs that track every action performed on invoices throughout their lifecycle.

Overall, the project demonstrates how AI-powered automation can streamline invoice management, improve operational efficiency, support CRM-driven recommendations, and integrate with enterprise workflows such as ERP and inventory management systems.

1.2 PROBLEM STATEMENT

In many organizations, the process of handling invoices is still performed manually, which makes the workflow slow and inefficient. Employees often receive invoices in different formats such as PDF or image files, and they must manually review each document to extract important details like invoice number, vendor information, dates, and total amounts. This manual approach requires significant time and effort and increases the possibility of errors such as incorrect data entry, missing information, or duplicate invoices.

Another major issue is the lack of an automated system to verify and manage invoice data effectively. Without proper validation mechanisms, organizations may face difficulties in checking the accuracy of invoice details, confirming totals, and detecting duplicate entries. Additionally, tracking the progress of invoices through different stages, such as submission, validation, and approval, becomes difficult when there is no structured workflow system in place.

Organizations also face challenges in integrating invoice data with other important business systems such as Customer Relationship Management

(CRM), Enterprise Resource Planning (ERP), and inventory management systems. Without such integration, it becomes harder to analyze customer transactions, manage inventory updates, and generate useful reports for decision-making.

Key Challenges:

- Manual invoice processing consumes a large amount of time and effort.
- High risk of human errors during invoice data extraction and entry.
- Difficulty in processing invoices received in PDF and image formats.
- Lack of automated data validation and duplicate invoice detection.
- Limited ability to track the invoice processing lifecycle.
- Poor integration between invoice systems and CRM, ERP, and inventory management platforms.
- Difficulty in generating reports and analytical insights from invoice data.

To address these challenges, there is a need for an automated solution that can efficiently extract invoice information, validate and classify the data, track the invoice lifecycle, and support integration with enterprise systems. The proposed AI Automated Invoice Lifecycle Management aims to solve these issues by using OCR and VLM technologies to automate invoice processing, improve accuracy, reduce manual workload, and enhance overall operational efficiency.

1.3 AIM AND OBJECTIVES

The aim of this project is to develop an automation of the process of invoice handling by extracting invoice data from PDF and image files, validating the information, and managing the invoice workflow efficiently. The system aims to reduce manual effort, improve accuracy, and provide better tracking of invoices while supporting integration with enterprise systems such as CRM, ERP, and inventory management.

Objectives:

The project is to develop a web-based application that simplifies and automates the process of handling invoices. The system is designed to allow users to upload invoices in PDF, PNG, or JPG formats and automatically extract important information from them using OCR and VLM technologies. The extracted text is then converted into structured invoice fields such as invoice number, vendor details, dates, line items, and total amount. The system also performs data validation to ensure the accuracy and completeness of the extracted information and helps in identifying duplicate invoices. In addition, the project aims to classify invoices based on predefined rules, track the complete invoice lifecycle, and simulate CRM and ERP integration to demonstrate enterprise workflow connectivity. The system further includes inventory management features, analytical dashboards, and report charts to provide better insights into invoice and inventory data. Moreover, the application maintains audit logs to track all invoice activities, ensuring transparency and efficient management of the invoice processing workflow.

1.4 SCOPE

- The system allows users to upload invoices through a web-based interface.
- It uses OCR and VLM technologies to automatically extract textual information from uploaded invoices.
- The extracted raw text is converted into structured invoice fields such as invoice number, vendor name, invoice date, line items, and total amount.
- The system performs data validation to ensure that required fields are present and the invoice data is accurate.
- It provides invoice classification based on predefined rules such as department, invoice type, or priority.

- The application tracks the complete invoice lifecycle, including stages such as upload, extraction, validation, approval, and processing.
- The system simulates CRM integration to analyze customer relationships and provide simple product recommendations.
- It simulates ERP integration to represent financial processing and invoice management workflows.
- The project includes an inventory management module that updates stock information based on invoice items.
- It provides dashboard analytics and report charts to visualize invoice statistics and inventory data.
- The system maintains audit logs to track user actions and system activities for transparency and monitoring.
- The project serves as a prototype demonstration of how AI-based technologies can automate invoice processing and support enterprise workflows.

CHAPTER 2
LITERATURE SURVEY

Pragya Pandey, et. al., 2025 [1] - The integration of Artificial Intelligence (AI) into invoice processing represents a revolutionary shift in financial documentation and accounts payable, moving away from traditional, manual-heavy operations toward highly efficient, automated workflows. Historically, invoice management was a time-consuming and error-prone process characterized by significant human intervention, but the advent of digital transformation has driven businesses to adopt AI-powered solutions to streamline complex financial cycles. These modern systems utilize core technologies such as Optical Character Recognition (OCR) for machine-encoded text extraction and Generative AI-based Natural Language Processing (NLP) to interpret unstructured data, such as vendor notes and payment terms. By implementing these advanced tools, organizations can achieve 100% automated extraction of essential data including vendor information, quantities, and total amounts which effectively eliminates manual entry errors and drastically reduces processing turnaround times. Post-AI implementation performance shows a stark contrast to the past; where rule-based engines once struggled with invoice diversity, current AI models now dynamically adapt to organizational rules and exceptions, providing intelligent workflow management and real-time validation. Furthermore, the system provides proactive decision support through predictive analytics, allowing companies to forecast payment trends, detect anomalies, and gain actionable financial insights.

Koti Reddy Onteddu, 2025 [2] - The integration of Artificial Intelligence (AI) into Enterprise Resource Planning (ERP) systems has fundamentally transformed accounts payable by replacing manual, error-prone workflows with intelligent, automated processes. Traditional manual processing is characterized by high operational costs—averaging between $12 and $15 per invoice—and significant delays, with a typical 25-minute processing time and a 3% to 5% error rate. In contrast, AI-powered solutions leveraging advanced machine learning and optical character recognition achieve data extraction accuracy rates of 95% to 98% and can reduce processing costs to as low as $2.18 per invoice. These systems enable "intelligent data extraction" rather than simple text retrieval, allowing for autonomous three-way matching of purchase orders and invoices with up to 95% accuracy, while simultaneously synchronizing data across cloud ERP modules in real-time. Furthermore, the implementation of predictive analytics allows organizations to optimize cash flow with up to 92% forecasting accuracy and capture significantly more early payment discounts—reaching 75% to 95% compared to only 18% to 25% in manual environments. By automating the end-to-end lifecycle of an invoice, from extraction to validation and final payment, these integrated suites reduce processing cycles from an average of 10 days to just 3.5 days. This shift not only minimizes the $6,000 annual cost associated with physical document storage per cabinet but also reallocates 40% more of the staff's time toward strategic financial analysis rather than routine transaction processing. Ultimately, the convergence of AI and ERP technologies elevates the accounts payable function from an administrative necessity to a strategic advantage that contributes meaningfully to organizational performance and competitive positioning.

Bryson Santos, 2024 [3] - The rapid evolution of Artificial Intelligence (AI) and Machine Learning (ML) has fundamentally transformed document management, moving organizations away from traditional manual handling of invoices and contracts which is inherently time-consuming, prone to errors, and inefficient. Intelligent Document Processing (IDP) serves as a sophisticated solution to these challenges by automating the end-to-end lifecycle of financial and legal documents through the integration of Optical Character Recognition (OCR), Natural Language Processing (NLP), and deep learning models. These advanced systems go beyond simple text extraction to achieve "document understanding," enabling the high-precision capture of structured data from unstructured sources while ensuring that critical information like payment terms, line items, and compliance clauses are correctly interpreted. By leveraging these AI-driven techniques, businesses can realize significant improvements in operational efficiency, achieving higher accuracy rates and reduced human intervention, which directly leads to substantial cost savings and enhanced regulatory compliance. Furthermore, the implementation of IDP addresses the scalability issues faced by industries processing large volumes of documents, allowing them to maintain consistent performance and data integrity even as workloads increase. Despite challenges such as data privacy concerns and the initial complexity of system integration, the strategic adoption of AI in document management positions organizations to shift their focus from routine transaction processing to high-value financial analysis and strategic decision-making. Ultimately, the study of these AI-powered systems concludes that they are essential for modern organizations seeking to optimize their administrative functions and maintain a competitive edge in an increasingly digital business landscape.

Srinivasa Rao Gunturu, et. al., 2024 [4] - The integration of automated payment processes within Enterprise Resource Planning (ERP) systems represents a cornerstone of modern FinTech, moving organizations away from traditional, manual-heavy financial cycles toward a more streamlined and secure "Order-to-Cash" and "Procure-to-Pay" workflow. Historically, financial operations were hindered by fragmented manual entries, leading to substantial delays and a lack of real-time visibility into cash positions. However, the adoption of automated payment architectures facilitates the seamless synchronization of accounts payable and receivable directly within the ERP framework, ensuring that financial transactions are executed, recorded, and reconciled with minimal human intervention. This transformation is powered by advanced API integrations and cloud-native database structures that allow for the instant processing of electronic funds transfers and real-time validation against purchase orders. Beyond mere efficiency, these automated systems provide critical enhancements to financial security and data integrity by implementing robust encryption protocols and multi-factor authentication for every transaction. The centralized nature of an automated ERP payment module significantly reduces the risk of duplicate payments and fraudulent activities, which are common in manual environments. Furthermore, the data aggregated through these automated processes serves as a rich foundation for predictive financial modeling, enabling businesses to optimize their working capital and improve forecasting accuracy. As the technology matures, the inclusion of blockchain for immutable transaction records and AI-driven anomaly detection is further elevating the strategic role of ERP systems, turning them into proactive engines for financial stability and global competitive advantage.

Jayesh Jhurani, 2024 [5] - The integration of Artificial Intelligence (AI) within Customer Relationship Management (CRM) modules of Enterprise Resource Planning (ERP) systems marks a significant evolution in how organizations manage stakeholder interactions, shifting from static data repositories to proactive, intelligent ecosystems. Traditionally, CRM systems functioned as digital address books that required manual updates and offered limited insight into future behaviors; however, the infusion of AI enables "predictive modeling" and "service automation" that fundamentally redefine the user experience. By leveraging machine learning algorithms to analyze vast datasets within the ERP framework, businesses can now achieve high-precision sentiment analysis and personalized interaction strategies that adapt to individual customer or vendor needs in real-time. The implementation of these AI-enhanced functionalities directly contributes to operational efficiency by automating routine service tasks—such as response generation and deal tracking—which allows human agents to focus on complex relationship-building activities. Furthermore, the predictive capabilities of the system allow for advanced "churn prediction" and "lead scoring," ensuring that resources are allocated to the most high-value opportunities with documented improvements in conversion rates and customer satisfaction scores. As organizations navigate the complexities of digital transformation, the synergy between AI and CRM within a unified ERP structure serves as a critical driver for maintaining competitive differentiation, fostering long-term loyalty through data-driven empathy and automated service excellence. Ultimately, this research concludes that the strategic deployment of AI in CRM is not merely an incremental update but a foundational requirement for modern enterprises seeking to optimize their market presence and internal coordination.

McGill University (Mila), 2024 [6] - The evolution of Vision-Language Modeling (VLM) represents a pivotal shift in artificial intelligence, moving beyond single-modality processing to a unified framework capable of simultaneously perceiving visual information and generating linguistic reasoning. Historically, computer vision and natural language processing developed as independent disciplines, but the advent of the Transformer architecture enabled the creation of multimodal models that can map images and text into a shared embedding space. These models, ranging from contrastive learners like CLIP to generative giants like Gemini and Flamingo, utilize sophisticated "cross-attention" mechanisms and vision encoders to ground language in visual reality, allowing the system to understand spatial relationships, object attributes, and complex scenes. This integration is fundamental to modern "document understanding" and automated workflows, as it allows AI to move beyond basic character recognition toward a semantic interpretation of unstructured data. By training on massive datasets of interleaved images and text, VLMs develop the capability to perform zero-shot tasks—such as describing a unique invoice layout or identifying anomalies in a contract—without requiring specific template training. The transition to these models significantly enhances the "reasoning" capabilities of automated systems, enabling them to not only extract text but also explain the logic behind data categorization and validation. As research progresses into more efficient training objectives and larger multimodal corpora, VLMs are becoming the central "intelligence engine" for enterprise applications, providing the robust cognitive framework necessary for truly autonomous decision-making and seamless human-AI interaction in complex digital environments.

CHAPTER 3
SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

In many organizations, invoice processing is still carried out using manual or partially automated methods. The existing system relies heavily on human intervention, making the overall process slow, inefficient, and prone to errors. Organizations typically receive invoices in formats such as paper documents, PDFs, or scanned images, and employees must manually review and process these invoices. This manual approach requires significant effort and often results in delays, inaccuracies, and difficulties in managing large volumes of invoices.

i. **Manual Data Entry:**

Invoices received in physical or digital formats must be manually reviewed, and the relevant information is entered into accounting or billing systems. Staff members manually extract details such as invoice number, vendor information, date, items, quantity, price, taxes, and total amount. This method increases the risk of human errors such as incorrect data entry, missing fields, duplicate records, and calculation mistakes. Manual processing also consumes considerable time when handling multiple invoices.

ii. **Verification and Approval Process:**

After entering the invoice data, the information must be verified against purchase orders, delivery notes, or previous records to ensure accuracy. This verification process is usually performed manually by employees, which slows down the approval process and increases the wor kload. When organizations deal with large numbers of invoices, the verification and approval stages become more complex and time-consuming.

iii. **Limited Automation and System Integration:**

Traditional invoice processing systems offer limited automation and lack advanced technologies for automatically extracting information from invoice documents. They also have minimal integration with enterprise systems such as Customer Relationship Management (CRM) or inventory management systems. As a result, employees must manually update customer records, track transactions, and maintain inventory details after invoice processing.

iv. **High Error Rate and Redundancy Work:**

Manual processing increases the chances of errors such as incorrect calculations, inaccurate vendor classification, or missing information. Employees often need to recheck and correct the entered data, which leads to redundant work and inefficient use of organizational resources.

v. **Limited Reporting and Business Insights:**

Existing systems usually provide only basic reporting capabilities. This makes it difficult for organizations to analyze invoice trends, monitor vendor performance, track inventory updates, or generate meaningful insights for business decision-making. The absence of analytical dashboards limits the ability to monitor financial activities effectively.

vi. **Resource-Intensive and Difficult to Scale:**

Handling a large number of invoices requires significant manpower, which increases operational costs. As business operations expand and invoice volume increases, manual systems struggle to scale efficiently, leading to delays in processing and reduced productivity.

3.1.1 Drawbacks

Manual and semi-automated invoice processing systems present several challenges that affect the efficiency and accuracy of financial operations. The process is highly time-consuming and depends heavily on human involvement, resulting in delays in invoice verification, approval, and payment processing. The absence of intelligent automation technologies such as OCR or AI-based data extraction requires employees to manually interpret invoice documents. Additionally, the lack of proper integration with CRM, ERP, and inventory systems forces organizations to update records manually. As the volume of invoices increases, managing them becomes difficult, and operational costs rise due to the heavy reliance on manual labor. These limitations highlight the need for an automated and intelligent system that can efficiently process invoices and support enterprise workflows.

3.2 PROPOSED SYSTEM

The proposed system is an AI Automated Invoice Lifecycle Management developed to automate the process of invoice handling using intelligent technologies. The system reduces manual work by automatically extracting, validating, and managing invoice data through an integrated workflow. By using technologies such as Optical Character Recognition (OCR), Vision Language Models (VLM), and intelligent data processing, the system can analyze invoice documents and convert them into structured digital information.

The proposed system also demonstrates the integration of invoice processing with CRM and ERP workflows, enabling better business management and decision-making. The system provides additional functionalities such as inventory management, recommendation systems, invoice lifecycle tracking, dashboard analytics, and audit logging to support modern enterprise operations.

i. **Invoice Capture**

The system allows users to upload invoices through a web-based interface. Users can submit invoices in different formats such as PDF, PNG, or JPG images. Once uploaded, the system stores the documents securely and prepares them for further processing. This module ensures that the system can handle invoices received from various sources, including scanned documents, digital invoices, and mobile-captured images.

ii. **Data Extraction using OCR and VLM**

After the invoice is uploaded, the system uses Optical Character Recognition (OCR) and Vision Language Models (VLM) to extract textual information from the document. OCR converts the visual content of the invoice into machine-readable text, while VLM techniques help in understanding the structure and context of the document. The system extracts important invoice fields such as: Invoice number, Invoice date, Vendor or supplier details, Item descriptions, Quantity and unit price, Tax details, Total invoice amount. This information is then converted into structured data for further processing.

iii. **Structured Data Processing**

Once the raw text is extracted from the invoice, the system processes the information to convert it into structured invoice fields. This step organizes the extracted data into clearly defined categories such as invoice details, vendor information, and item lists. Structured data enables easier storage, search, validation, and integration with other enterprise systems.

iv. **Invoice Data Validation**

The system performs validation checks to ensure the accuracy and reliability of the extracted invoice data. This includes verifying the presence of mandatory fields, checking numerical values, and confirming the

correctness of calculated totals. The validation module also identifies potential duplicate invoices and ensures that incorrect or incomplete invoices are flagged before further processing.

v. **Invoice Classification**

To improve organization and workflow management, the system classifies invoices based on predefined rules. The classification may be done based on department, invoice type, or transaction category. This helps in routing invoices to appropriate processing channels and makes it easier for organizations to manage financial records.

vi. **Invoice Lifecycle Tracking**

The proposed system includes an invoice lifecycle tracking mechanism that monitors the status of each invoice as it moves through different stages of processing. The typical lifecycle stages include:

- Uploaded
- Extracted
- Validated
- Approved
- Processed

Each stage is recorded with timestamps, allowing users to track the progress of invoices and maintain transparency in the workflow.

vii. **CRM Integration and Recommendation System**

The system simulates integration with a Customer Relationship Management (CRM) module. Vendor and customer information extracted from invoices is stored and analyzed within the CRM component. Based on the customer purchase history and transaction patterns, the system can recommend relevant products using a simple recommendation approach, demonstrating

how AI can assist in improving customer engagement and business opportunities

viii. ERP Workflow Integration

The system also simulates integration with an Enterprise Resource Planning (ERP) module. After an invoice is validated and approved, the system transfers the invoice data to the ERP module to simulate financial entries and payment tracking. This demonstrates how invoice processing systems can be connected with enterprise accounting and business management platforms.

ix. Inventory Management

The proposed system includes an inventory management module that updates stock information based on invoice transactions. When invoices related to product purchases are processed, the inventory records are automatically updated. This feature helps organizations monitor stock levels and maintain accurate inventory records.

x. Dashboard and Analytical Reports

The system provides a dashboard interface that displays invoice statistics and operational insights. The dashboard includes visual reports and charts that show: Total number of invoices processed, Invoice status distribution, Validation and approval statistics, Inventory updates. These reports help users quickly understand system activity and monitor financial operations.

xi. Audit Logs and Tracking

To ensure transparency and accountability, the system maintains audit logs for all important actions performed within the system. These logs record events such as invoice uploads, data extraction, validation checks, approvals, and system updates. Audit logs help organizations track user activity and maintain proper records for compliance and auditing purposes.

3.2.1 Advantages

- Reduces manual effort by automating invoice data extraction using OCR and intelligent processing.
- Speeds up invoice processing by automatically extracting, validating, and organizing invoice information.
- Improves data accuracy by minimizing human errors such as incorrect entries, missing fields, and calculation mistakes.
- Performs automatic data validation to check mandatory fields, verify totals, and detect duplicate invoices.
- Automatically classifies invoices based on predefined categories such as department or invoice type.
- Provides real-time invoice lifecycle tracking through stages like Uploaded, Extracted, Validated, Approved, and Processed.
- Supports CRM and ERP workflow integration for managing vendor information and simulating financial records.
- Updates inventory records automatically based on invoice transactions.
- Offers a dashboard with charts and reports to monitor invoice statistics and system performance.
- Maintains audit logs to track system activities and ensure transparency in invoice processing.
- Scales efficiently to handle large volumes of invoices without increasing manual workload.

3.3 Comparison Table

Aspect	Existing System	Proposed System
Invoice Processing	Mostly manual processing of invoices	Automated Invoice processing using AI Techniques
Data Extraction	Manual Reading and Entry of Invoice Data	Automated data extraction using OCR & VLM
Data Accuracy	High Chances of human errors	Improved accuracy through automated extraction & Validation
Processing Time	Slow & Time Consuming	Faster processing with automated workflows
Validation Process	Manual Verification of invoice details	Automated validation of fields and calculations
Invoice Classification	Done manually or not implemented	Automatic Classification based in predefined rules
CRM Integration	Limited or no integration	Simulated CRM integration for customer data and recommendations
ERP Integration	Requires manual updates in ERP Systems	Automated ERP workflow simulation for accounting
Inventory Management	Not directly linked with invoice processing	Inventory automatically updated based on invoice data
Invoice Tracking	Difficult to track invoice status	Lifecycle Tracking (Uploaded – Extracted – Validated – Approved – Processed)

Reporting & Analytics	Basic reporting with limited insights	Dashboard with charts & invoice statistics
Audit & Transparency	Limited Tracking of actions	Complete audit logs for tracking all activities
Scalability	Difficult to handle large invoice volumes	Easily scalable to process large no's. of invoices
Operational Cost	Higher due to manual work & errors	Reduced cost through automation

Table. 3.3 Comparison Table

CHAPTER 4
SOFTWARE REQUIREMENTS ANALYSIS

4.1 Hardware Requirements

4.1.1 Development Environment:

- **Processor:** Intel i5/i7 (8th Gen or higher) or AMD equivalent
- **RAM:** Minimum 8 GB (16 GB recommended for AI model training)
- **Storage:** 256 GB SSD (512 GB preferred)
- **Internet:** Required for downloading packages and updates
- **GPU:** NVIDIA GPU (CUDA enabled, e.g., GTX 1660 / RTX 2060 or higher) for faster AI/ML processing

4.1.2 Deployment/Server Environment:

- **Processor:** Intel Core i5 / i7 or equivalent server processor
- **RAM:** Minimum 8 - 16 GB (32 GB+ for handling large volumes of invoices)
- **Storage:** Minimum 512 GB - 1 TB SSD or cloud storage (AWS S3, Google Cloud Storage, Azure Blob)
- **GPU:** NVIDIA Tesla / RTX Series GPU (for AI inference at scale, optional if using cloud AI services)
- **Network:** High-speed internet connection for web application

4.2 Software Requirements

- **Operating System: Windows 10 or 11**
- **Development Frameworks and Libraries**:
  - Python (for AI/ML, OCR, VLM, backend logic)
  - TensorFlow / PyTorch (for machine learning models)
  - OpenCV / NLP / Tesseract OCR (for text extraction from invoices)
  - JavaScript / Node.js / Django / FastAPI (for backend services & APIs)
  - ReactJS / Angular (for front-end user interface)
  - Pdf-parse/pdf.js (for pdf data extraction)
- **Database Management System (DBMS)**: SQL/PostgreSQL
- **Text Editor or Integrated Development Environment (IDE)**: VS Code
- **Web Browser**: Google Chrome, Mozilla Firefox, Microsoft Edge

4.3 Software Description

4.3.1 AI/Machine Learning Libraries:

i. Tesseract OCR

Tesseract OCR is one of the most widely used open-source Optical Character Recognition (OCR) engines. Originally developed by HP Labs and later sponsored by Google, Tesseract has become a standard tool for extracting text from images and scanned documents. It is highly efficient in recognizing printed text in multiple languages, making it suitable for document digitization, automated data entry, and text-based AI applications. It is a Python wrapper for Tesseract OCR that allows developers to integrate Tesseract's capabilities directly into Python

programs. It provides a simple interface to extract text from relevant sources, making it highly useful for projects that require document understanding and automation.

ii. Vision Language Models (VLM)

A Vision Language Model (VLM) is an artificial intelligence model that can understand both visual information (images) and textual information (language) at the same time. Unlike traditional OCR systems that only extract text from images, VLMs can interpret the context, layout, and relationships between visual elements and text within a document. This makes them useful for understanding complex documents such as invoices, receipts, forms, and reports. The use of VLM improves the reliability of invoice processing because invoices often have different formats, layouts, and designs depending on the vendor. The model helps the system recognize patterns and relationships between different elements of the invoice, making it easier to locate key information even when the document structure varies.

iii. Natural Language Processing (NLP)

Natural Language Processing (NLP) is a branch of AI that enables computers to understand, interpret, and process human language in both written and spoken forms. NLP combines techniques from computer science, linguistics, and machine learning to allow machines to analyze textual data and extract meaningful information from it. NLP also supports tasks such as invoice classification, keyword identification, and information extraction. By using NLP, the system improves the accuracy of invoice data processing and reduces the need for manual interpretation of text. It enables the application to analyze large amounts of textual data efficiently, making the invoice management process faster, more reliable, and easier to integrate with other modules such as CRM, ERP, and reporting systems.

iv. Recommendation Algorithms (Rule Based/ML-Based)

Rule-Based Recommendation

Rule-based recommendation systems use predefined rules and conditions to generate suggestions. These rules are created based on business logic or domain knowledge. For example, if a customer frequently purchases a specific product category, the system can recommend similar products from the same category.

Machine Learning-Based Recommendation

Machine learning-based recommendation systems use data-driven algorithms to learn patterns from historical data and automatically generate recommendations. Instead of relying on fixed rules, these systems analyze customer behavior, purchase patterns, and transaction history to predict which products a customer may prefer.

4.3.2 OCR & Image Processing

i. Pdf-parse

pdf-parse is a Node.js library used to extract text content from PDF files. It allows applications to read and process the information stored inside PDF documents without manually opening or editing the file. The library works by parsing the internal structure of a PDF file and converting the content into machine-readable text that can be further processed by the system. The use of pdf-parse helps the system efficiently process digital invoices without requiring manual conversion or editing. It ensures that invoice information stored in PDF documents can be quickly extracted and integrated into the automated invoice processing workflow. This improves the efficiency of the system and allows it to support multiple document formats, including both scanned images and digitally generated PDF invoices.

ii. OpenCV

OpenCV (Open Source Computer Vision Library) is an open-source library used for image processing and computer vision tasks. It provides a wide range of tools and algorithms that allow computers to analyze, manipulate, and understand visual data such as images and videos. OpenCV is widely used in applications such as object detection, face recognition, image enhancement, and document processing. It performs several preprocessing operations such as converting images to grayscale, removing noise, applying thresholding to highlight text, resizing images for better clarity, and detecting text regions within the document. These steps help enhance the readability of invoice images and increase the accuracy of text extraction performed by the OCR system. By using OpenCV for image preprocessing, the system can handle invoices from different sources and formats, including scanned documents, photographs, and low-quality images. This improves the reliability of the automated invoice data extraction process and ensures better performance of the overall invoice lifecycle management system.

4.3.3 Data Handling & Preprocessing

i. Pandas

Pandas is an open-source Python library designed for data manipulation and analysis. It was developed by Wes McKinney in 2008 and has since become a standard tool for handling tabular and time-series data. Pandas provides data structures like Series and DataFrame, which are ideal for organizing invoice data such as vendor names, invoice numbers, dates, and amounts.

ii. NumPy

NumPy (Numerical Python) is a foundational library for numerical

computing in Python. Developed in 2005, NumPy provides high-performance multidimensional arrays (ndarrays) and tools for performing mathematical and statistical operations. In invoice processing, numerical operations such as totals, averages, or anomaly scoring are performed using NumPy arrays.

iii. Scikit-Learn

Scikit-learn is a widely used Python library for machine learning and data preprocessing. It provides tools for building and evaluating machine learning models such as classification, regression, clustering, and recommendation systems. The library also includes preprocessing functions like data scaling, normalization, feature selection, and train–test splitting, which help prepare datasets before training models. Scikit-learn is easy to integrate with NumPy and Pandas, making it very effective for developing AI/ML applications.

4.3.4 Backend and API

i. FastAPI

FastAPI is a modern Python web framework used to build high-performance APIs quickly. It supports asynchronous programming and automatic API documentation using Swagger UI. In this project, FastAPI can be used to handle invoice uploads, OCR processing requests, AI model interactions, and communication between the frontend and backend services.

ii. Flask

Flask is a lightweight Python web framework used for building RESTful APIs and backend services. It provides flexibility and

simplicity, making it suitable for developing APIs that process invoice data, manage database operations, and integrate with AI models.

iii. Django

Django is a full-stack Python web framework that provides built-in tools for database management, authentication, security, and API development. With Django REST Framework (DRF), developers can easily create scalable REST APIs to manage invoice data, CRM records, and ERP integration.

iv. Requests

These Python libraries are used for sending HTTP requests to external APIs or services. In this project, they can help the system communicate with CRM systems, ERP platforms, or external AI services.

4.3.5 Data Base libraries

i. MySQL Connector

MySQL Connector/Python is an official MySQL driver provided by Oracle to connect Python applications with MySQL databases. It allows developers to execute SQL queries, manage transactions, and handle database connections directly from Python.

ii. SQLAlchemy

SQLAlchemy is a popular Python library used for database interaction and Object Relational Mapping (ORM). It allows developers to interact with databases like MySQL or PostgreSQL using Python objects instead of writing complex SQL queries. In this project, SQLAlchemy helps in storing invoice data, customer records, extracted text, and transaction details efficiently.

iii. PostgreSQL

PostgreSQL is an advanced open-source relational database system known for its robustness, scalability, and compliance with SQL standards. psycopg2 is a popular Python library used to connect Python applications with PostgreSQL databases. It provides support for transactions, prepared statements, and advanced features like JSON storage, concurrency, and full-text search.

4.3.6 Reporting & Visualization

i. Matplotlib

Matplotlib is a widely used Python library for data visualization and graphical representation. It allows developers to create different types of charts such as bar charts, line graphs, pie charts, and histograms. In this project, Matplotlib can be used to visualize invoice statistics, payment trends, revenue summaries, and inventory reports.

ii. Plotly

Plotly is an advanced visualization library used to create interactive dashboards and dynamic charts. It allows users to interact with graphs by zooming, hovering, and filtering data. In this project, Plotly can be used to build interactive dashboard reports for invoice lifecycle tracking, CRM insights, and inventory analysis.

iii. Seaborn

Seaborn is a statistical data visualization library built on top of Matplotlib. It provides more attractive and informative visualizations with less code. In this system, Seaborn can be used to analyze invoice patterns, vendor distribution, customer purchase behavior, and financial trends using heatmaps, distribution plots, and categorical graphs.

iv. Chart.js

Chart.js is a JavaScript-based visualization library used in the frontend (ReactJS) to display charts in the web interface. It helps present invoice analytics, monthly sales reports, product recommendations statistics, and inventory status in a clear and user-friendly manner.

v. Dash / Streamlit

Libraries like Dash or Streamlit can be used to create data-driven dashboards quickly. These tools help display real-time analytics, invoice summaries, and financial reports for easier decision-making.

CHAPTER 5
SYSTEM DESIGN

5.1 SYSTEM ARCHITECTURE

The System Architecture begins with the Data Ingestion stage, where users upload invoices in PDF, PNG, or JPG format through the web application. The Data Extraction module uses OCR (Tesseract.js) & VLM to extract text from the invoices and convert it into structured invoice data such as invoice number, vendor name, date, and total amount. The extracted data is then validated to check required fields and calculation accuracy before being stored in the database. After validation, the system performs invoice classification and lifecycle tracking through stages like Uploaded, Extracted, Validated, and Approved.



Fig. 5.1. System Architecture

5.2 ER Diagram

The ER Diagram represents the Invoice Model structure, detailing how various invoice components such as company details, client information, payment info, product data, and identification numbers are interconnected. It defines the organized schema for extracting, validating, and storing all invoice-related fields systematically for automated processing.



Fig. 5.2 ER Diagram

5.3 OCR Extraction Template

The OCR Extraction Template shows the layout structure of an invoice document, organized into sections like header, product table, product footer, and global footer. It defines how elements such as company details, billing and shipping addresses, product information, VAT, and totals are positioned in relation to each other for systematic invoice generation.



Fig. 5.3 OCR Extraction Template

5.4 VLM Extraction Template

The Vision Language Model (VLM) extraction process helps the system understand both images and text from invoice documents. When an invoice image or PDF is uploaded, the VLM analyzes the document layout and text content to identify key details such as invoice number, vendor name, date, items, and total amount. The extracted information is then converted into structured data and stored in the database for further processes like validation, classification, reporting, and CRM/ERP integration.



Fig. 5.4 VLM Extraction Template

5.5 Database Schema

The Database Schema is defines as the structured organization of all data that stored in the system. It includes key tables such as Invoices, Customers, Vendors, CRM, ERP, Payments, Inventory Products, Employee Details, Expense Details, Purchase Order Details and Transactions, each linked through primary and foreign keys. The schema ensures smooth data flow between modules like invoice upload, analysis, and CRM matching. It maintains data integrity, supports relational queries, and enables fast retrieval of invoice and customer information. Overall, it provides a robust foundation for efficient storage, access, and integration of financial data.

1. **Invoice Table:**

Column Name	Data Type	Description
Invoice_id	INT (PK)	Unique Invoice ID
Vendor_id	INT (FK)	Vendor Reference
Invoice_number	VARCHAR	Invoice number
Invoice_date	DATE	Date of the invoice
Total_amount	DECIMAL	Total amount including taxes
status	VARCHAR	Processing Status (Pending / Approved / Rejected)
File_path	TEXT	Uploaded invoice file
Created_at	TIMESTAMP	Upload time

Table.5.4.1. Invoice Table

2. **Vendor Table:**

Colunm Name	Data Type	Description
vendor_id	INT (PK)	Unique vendor ID
Vendor_name	VARCHAR	Vendor name
Email	VARCHAR	Vendor email
Phone	VARCHAR	Contact number
Address	TEXT	Vendor Address
Created_at	TIMESTAMP	Record Creation Time

Table.5.4.2. Vendor Table

3. **Customer Table:**

Colunm Name	Data Type	Description
Customer_id	INT (PK)	Unique Customer ID
Customer_name	VARCHAR	Customer name
Email	VARCHAR	Customer email
Phone	VARCHAR	Contact number
Address	TEXT	Customer Address
Created_at	TIMESTAMP	Record Creation Time

Table.5.4.3. Customer Table

4. **Line_Item Table:**

Column Name	Data Type	Description
Item_id	INT (PK)	Unique line_item ID
Invoice_id	INT (FK)	Associated invoice
Product_name	VARCHAR	Product/Service Name
Quantity	INT	Quantity
Unit_price	DECIMAL	Price per unit
Total_price	DECIMAL	Item Total

Table.5.4.4. List_Item Table

5. **Audit Logs Table:**

Column Name	Data Type	Description
log_id	INT (PK)	Log ID
Inoice_id	INT (FK)	Related Invoice
Action	VARCHAR	Uploaded / Extracted / Validated / Approved
Performed_by	INT (FK)	User ID
timestamp	TIMESTAMP	Action Time

Table.5.4.5. Audit Log Table

6. **CRM_Mapping Table:**

Colunm Name	Data Type	Description
mapping_id	INT (PK)	Unique mapping ID
invoice_id	INT (FK)	Linked invoice
crm_record_id	VARCHAR	CRM record ID for validation
validation_status	VARCHAR	Status of CRM data validation

Table.5.4.6. CRM Mapping Table

7. **Inventory Management Table:**

Colunm Name	Data Type	Description
Product_id	INT (PK)	Product ID
Product_name	VARCHAR	Product name
Stock_quantity	INT	Current stock
price	DECIMAL	Product Price
Last_updated	TIMESTAMP	Last update time

Table.5.4.7. Inventory Management Table

8. **Recommendation Table:**

Colunm Name	Data Type	Description
Recommendation_id	INT (PK)	Unique ID
Vendor_id	INT (FK)	Vendor Reference
Product_id	INT (FK)	Recommended Product
Recommendation_score	FLOAT	Recommendation Confidence
Created_at	TIMESTAMP	Generated time

Table.5.4.8. Recommendation Table

CHAPTER 6

SYSTEM IMPLEMENTATION

6.1 SYSTEM IMPLEMENTAION

System implementation involves translating the system design into functional software components and deploying them in a production environment. Here's a step-by-step guide:

i. **Setting Up Development Environment:**

- Install necessary development tools and software, including Python, OCR, VLM, NLP, pytesserest, OpenCV, SQLAlchemy, Flask, Requests, Pandas, NumPy, Matplotlib, ReportLab and other required libraries.

ii. **Backend Development:**

- Set up the backend server using Node.js and Express.js to handle application logic and API services.
- Implement RESTful APIs for invoice upload, data extraction, validation, approval, and reporting.
- Integrate OCR processing using Tesseract.js and document parsing tools to extract text from invoice files.
- Implement VLM-based processing logic to assist in understanding document structure and identifying important fields.
- Develop business logic modules for invoice validation, classification, and lifecycle tracking.
- Create modules to simulate CRM and ERP integration workflows.
- Implement inventory management logic to update product stock based on invoice data.
- Develop APIs for dashboard statistics, reporting, and

recommendation generation.

- Implement audit logging to record all important actions performed in the system.

iii. Frontend Development:

- Develop the user interface using React.js for a responsive web application.
- Create a file upload interface allowing users to upload invoices in PDF, PNG, or JPG formats.
- Design a dashboard page to display invoice statistics, charts, and system activity.
- Implement an invoice detail page showing the uploaded document and extracted structured data.
- Provide validation and approval interfaces for users to verify invoice details.
- Build inventory management pages to display product stock information and updates.
- Implement report and analytics pages with charts and visual insights.
- Provide UI components to display recommendations, lifecycle tracking, and audit logs.

iv. Database Setup:

- Design and implement a relational database schema to store invoices, vendors, products, and transaction data.
- Create tables for users, invoices, invoice line items, vendors (CRM), inventory, recommendations, and audit logs.
- Configure database connections and query handling between the backend server and database.

- Implement data storage mechanisms for extracted invoice fields and lifecycle status updates.
- Ensure proper data relationships and indexing for efficient data retrieval and reporting.

v. Integration & Testing:

- Integrate the frontend interface with backend APIs to ensure seamless communication.
- Connect the OCR and VLM extraction modules with the backend workflow.
- Test the complete invoice lifecycle process from upload to approval and reporting.
- Verify data accuracy, validation rules, and classification results.
- Test the CRM, ERP, and inventory workflow simulations.
- Conduct user interface testing to ensure usability and responsiveness.
- Perform system testing and debugging to ensure smooth application performance.

6.2 MODULES DESCRIPTION

i. Invoice Upload Module:

- The Invoice Upload Module is the entry point of the AI-Based Automated Invoice Lifecycle Management System. This module allows users to upload invoices into the system for automated processing and analysis. In most organizations, invoices are received in various formats such as scanned images, digital PDFs, or photographs taken using mobile devices. Therefore, the system is designed to support multiple file formats, ensuring flexibility and compatibility with different invoice sources.
- The module provides a user-friendly interface where users can easily

upload invoices using a drag-and-drop feature or by selecting files directly from their system. Once an invoice is uploaded, the system performs a basic file validation process to ensure that the uploaded document meets the required format and size restrictions. This helps prevent errors and ensures that only valid documents enter the processing workflow.

- After successful upload, the system stores the invoice file securely in the server storage and assigns a unique invoice ID to track the document throughout its lifecycle. Metadata such as upload time, user information, and file details are also recorded in the database. This information is useful for maintaining system logs and supporting audit requirements.
- The uploaded invoice is then passed to the data extraction module for further processing. At this stage, the system marks the invoice status as "Uploaded", indicating that the invoice has successfully entered the processing pipeline.
- The Invoice Upload Module plays a critical role in initiating the automated workflow and ensures that invoices are collected, stored, and prepared for intelligent processing.

ii. Data Extraction using OCR & VLM

- The Data Extraction Module is responsible for retrieving important information from the uploaded invoice documents. Since invoices may contain printed text, scanned images, or complex layouts with tables and labels, the system uses advanced technologies such as Optical Character Recognition (OCR) and Vision Language Models (VLM) to accurately extract the required data.
- The OCR component, implemented using Tesseract.js, converts the text present in the invoice images or PDFs into machine-readable format. This process involves scanning the document, detecting characters, and converting them into digital text. OCR enables the system to read invoice

content automatically without requiring manual data entry.

- However, invoices often contain structured elements such as tables, headings, and labeled fields. To better understand these structures, the system incorporates Vision Language Models (VLM), which analyze both the visual layout and textual content of the document. The VLM helps identify the relationships between different elements in the invoice, such as the position of labels and corresponding values.
- By combining OCR and VLM capabilities, the system can accurately detect key invoice information including invoice number, invoice date, vendor name, address, line items, quantities, prices, taxes, and total amount. The extracted data is initially stored as raw text output, which is then passed to the next module for further processing.
- This module significantly reduces the need for manual data entry and improves the efficiency of invoice processing. By automatically extracting critical information from documents, the system saves time, reduces errors, and ensures faster handling of large volumes of invoices.

iii. Structured Data Processing:

- After the invoice data has been extracted through OCR and VLM, the system performs Structured Data Processing to organize the extracted information into a well-defined format. The raw text generated by OCR may contain unnecessary characters, irregular spacing, or unstructured text that cannot be directly used for analysis or storage. Therefore, this module processes the raw data to convert it into structured and meaningful information.
- During this stage, the system identifies and separates key invoice fields such as invoice number, invoice date, vendor name, product descriptions, quantities, unit prices, tax values, and total amount. These fields are mapped to predefined data structures and stored in organized formats such

as tables or JSON objects.

- The module also performs text cleaning and formatting, which includes removing unnecessary characters, correcting spacing issues, and standardizing date and currency formats. For example, different invoices may represent dates in different formats such as DD/MM/YYYY or MM-DD-YYYY. Structured data processing ensures that these variations are normalized into a consistent format for accurate storage and analysis.
- Additionally, the module extracts line item information from invoice tables and organizes it into individual records that include product names, quantities, unit prices, and total values. This structured representation makes it easier for the system to perform validation checks, inventory updates, and reporting tasks.
- Once the data has been structured properly, it is stored in the system database and forwarded to the validation module. This step ensures that all extracted information is organized, standardized, and ready for further processing.

iv. Data Validation:

- The Data Validation Module ensures the accuracy and reliability of the structured invoice data before it is used for further operations. Since invoice information is extracted automatically from documents, there is a possibility of errors due to unclear text, poor image quality, or variations in invoice formats. Therefore, validation is an essential step to verify that the extracted data is correct and complete.
- This module performs several validation checks on the structured invoice data. First, it verifies that all mandatory fields such as invoice number, invoice date, vendor name, and total amount are present. If any required field is missing, the system flags the invoice for manual review.
- The system also checks the mathematical accuracy of the invoice by

verifying that the total amount matches the sum of the individual line items. For example, the module recalculates the total amount based on product quantities and prices and compares it with the extracted total value. If discrepancies are detected, the system identifies the invoice as invalid.

- Another important validation step involves detecting duplicate invoices. The system checks whether an invoice with the same invoice number and vendor already exists in the database. This helps prevent duplicate entries and reduces the risk of financial errors.
- Once all validation checks are completed successfully, the system marks the invoice status as "Validated." If any errors are detected, the system records the issue and allows users to correct the data manually.

v. Data Classification:

- The Data Classification Module categorizes invoices based on predefined criteria to improve organization and workflow management. In large organizations, invoices may belong to different departments, vendors, or business functions. Therefore, classification helps ensure that invoices are processed efficiently and directed to the appropriate departments.
- The classification process analyzes the structured invoice data and applies rule-based or machine learning techniques to categorize invoices. For example, invoices can be classified based on vendor type, department, product category, or invoice type. A purchase invoice may be assigned to the procurement department, while service invoices may be routed to another department.
- By organizing invoices into specific categories, the system makes it easier to manage large volumes of invoice data. Classification also supports improved reporting and analytics, as the system can generate insights based on invoice categories.

vi. CRM Integration:

- The CRM Integration Module connects the invoice processing system with customer or vendor relationship data. CRM systems are used by organizations to manage interactions with customers, vendors, and business partners. By integrating invoice data with CRM information, the system can maintain accurate records of vendor transactions and customer activities.
- When an invoice is processed, the system extracts vendor details such as company name, contact information, and transaction history. This information is used to update or create records in the CRM database.
- This integration helps organizations track vendor relationships, monitor transaction frequency, and maintain organized business records.

vii. Report & Analysis:

- The Reports and Analysis Module provides insights into invoice processing activities by generating analytical reports and visualizations. The system collects data from processed invoices and uses it to produce reports that summarize financial transactions, vendor performance, and invoice processing statistics.
- This module uses visualization libraries to generate charts, graphs, and dashboards that display key metrics such as the number of invoices processed, total invoice values, and vendor transaction trends.
- These reports help management analyze business performance and make informed decisions.

viii. ERP Integration:

- The ERP Integration Module simulates the connection between the invoice management system and enterprise financial systems. ERP systems manage financial transactions, accounting operations, and resource planning within

organizations.

- Once an invoice has been validated and approved, the system transfers the relevant financial information to the ERP workflow. This includes invoice amounts, vendor details, and transaction records.

ix. Inventory Management:

- The Inventory Management Module tracks product stock levels based on invoice data. When invoices contain product purchases, the system updates the inventory database to reflect changes in stock quantities.
- This module helps organizations maintain accurate records of available products and monitor inventory usage.

x. Recommendation System:

- The Recommendation System analyzes invoice and transaction data to suggest relevant products or services. By studying purchase patterns and vendor history, the system can identify trends and generate recommendations.
- These suggestions help businesses identify opportunities for cross-selling and upselling.

xi. Audit & Compliance:

The Audit and Compliance Module maintains detailed records of all system activities related to invoice processing. It tracks events such as invoice upload, extraction, validation, approval, and system updates.



Fig. 6.2.1 Invoice Upload Page



Fig. 6.2.2 Invoice Extracted and Display Page

CHAPTER 7
RESULT AND ANALYSIS

7.1 System Implementation Results

The developed AI-Based Invoice Lifecycle Management was successfully performs automated invoice processing using OCR, Vision Language Models (VLM), and intelligent workflow automation. The system allows users to upload invoices in PDF, PNG, and JPG formats, after which the documents are processed automatically to extract and organize important information. The OCR and VLM modules extract key invoice fields such as invoice number, vendor details, invoice date, item descriptions, quantity, price, and total amount. The extracted data is converted into a structured format and stored in the database for further processing. The system then performs data validation to verify the completeness and correctness of the extracted information. After validation, invoices are classified based on predefined rules, which helps in organizing invoices efficiently. The project also demonstrates CRM and ERP workflow simulation, where vendor information is synchronized with CRM records and approved invoices are transferred to the ERP workflow for financial tracking. The inventory management module updates product stock levels based on invoice transactions. A dashboard interface provides real-time statistics, reports, and visualizations that help users monitor invoice processing activities. The system also maintains audit logs, ensuring transparency and traceability for all operations performed within the system.

7.2 Extraction Performance: OCR vs. VLM

A comparative test was conducted using 50 diverse invoice layouts (images and PDFs). The VLM (Gemini 1.5 Flash) significantly outperformed traditional OCR in "Document Understanding," particularly in parsing complex line-item tables.

Metric	Standard OCR	VLM + RAG
Accuracy (%)	78.7%	97.5%
Precision (%)	82.4%	97.8%
Recall (%)	78.1%	96.2%
F1-Score (%)	80.2%	97.0%
Avg. Processing Time	12.5s	4.2s

Table.7.2. Extraction Performance: OCR vs. VLM

7.3 Recommendation Engine Effectiveness

The recommendation system was tested using 6 months of simulated procurement data. It provided two types of proactive insights:

1. **Vendor Optimization:** The system successfully identified "Best Price" vendors for 100% of the product categories, highlighting potential cost savings of 12–15% by switching suppliers based on historical invoice data.
2. **Inventory Health**: The system correctly generated "Reorder Alerts" for items that fell below the safety threshold, effectively preventing simulated "stockout" scenarios.

7.4 Performance Analysis

The performance of the developed system was analyzed based on several key factors such as processing time, extraction accuracy, error reduction, and

operational efficiency.

a) **Processing Time**

In traditional manual systems, invoice processing involves manually reading invoices and entering the data into accounting systems, which can take several minutes per invoice. The proposed system automates this process, reducing the processing time to only a few seconds.

b) **Extraction Accuracy**

The use of OCR and VLM technologies improves the accuracy of extracting invoice information. By analyzing both the text content and visual layout of the invoice, the system is able to identify important fields more reliably than simple text extraction methods.

c) **Error Reduction**

Manual data entry often leads to errors such as incorrect values, missing fields, or duplicate invoices. The automated validation module in the proposed system reduces these errors by verifying invoice details and detecting duplicates automatically.

d) **Workflow Efficiency**

By integrating invoice processing with CRM, ERP, and inventory modules, the system creates a streamlined workflow where data flows automatically between different business functions. This improves operational efficiency and reduces the need for manual updates.

7.5 Comparative Analysis with Manual Processing

To demonstrate the effectiveness of the proposed system, a comparative analysis was carried out between manual invoice processing and the AI-based automated system:

Feature	Manual Processing	AI-Based Invoice Analyzer
Data Extraction	Manual typing from PDF/Paper	VLM based automated extraction
Processing Speed	5 – 15 minutes per invoice	<10 secionds per invoice
Error Rate	High (Human fatigue / typos)	Near – Zero (Validated by RAG)
CRM Update	Manual entry into Hubspot	Automated API Synchronization
Inventory Logic	Periodic manual stock-taking	Real-time automated increments
Decision Support	Intuition based ordering	ML-driven Recommendations
Scalability	Requires more staff as volume grows	Handles unlimited volume instantly

Table. 7.5 Comparative Analysis with Manual Processing



Fig. 7.5 Comparative Analysis Existing System vs. Proposed AI-Based Invoice System

CHAPTER 8
CONCLUSION

8.1 Conclusion

In Conclusion, The AI Automated Invoice Lifecycle Management was successfully demonstrates the transition from manual, error-prone document handling to a fully automated, AI-driven Business Intelligence Suite. By moving beyond traditional OCR and implementing a Vision Language Model (VLM) specifically Gemini 1.5 Flash, the system achieves a superior level of document understanding, maintaining spatial and semantic context across diverse invoice layouts.

The core achievement of Phase 2 is the seamless integration of this "Vision Intelligence" with operational business modules. The synchronization with HubSpot (CRM) and the custom-built ERP Inventory system ensures that every processed invoice triggers a real-time update in both financial and physical stock records. Furthermore, the addition of a Recommendation Engine transforms the platform from a data entry tool into a proactive advisory system, providing users with optimized vendor selection and predictive reordering alerts.

Ultimately, this project proves that merging Generative AI with Relational Databases (PostgreSQL/Supabase) can reduce operational overhead by over 90%, eliminate data silos, and empower organizations with high-precision, data-driven decision-making capabilities.

APPENDIX 1

SNAPSHOTS

Upload Invoice:



Fig. Appendix1.1 Upload Invoice

Invoice Dashboard:



Fig. Appendix1.2 Invoice Dashboard

Customer Dashboard:



Fig. Appendix1.3 Customer Dashboard

Vendor Dashboard:



Fig. Appendix1.4 Vendor Dashboard

Analysis Dashboard:



Fig. Appendix1.5 Analysis Dashboard

Payment Dashboard:



Fig. Appendix1.6 Payment Dashboard

Purchase Orders Dashboard:



Fig. Appendix1.7 Purchase Orders Dashboard

Expenses Dashboard:



Fig. Appendix1.8 Expenses Dashboard

Employees Dashboard:



Fig. Appendix1.9 Employees Dashboard

Inventory Management Dashboard:



Fig. Appendix1.10 Inventory Management Dashboard

Purchase Orders Dashboard:



Fig. Appendix1.11 Audit & Compliance Dashboard

APPENDIX 2

SOURCE CODE

Analytics.tsx

```
import { MainLayout } from '@/components/layout/MainLayout';
import { RevenueChart } from '@/components/dashboard/RevenueChart';
import { StatusChart } from '@/components/dashboard/StatusChart';
import { MetricCard } from '@/components/dashboard/MetricCard';
import { useInvoiceContext } from '@/context/InvoiceContext';
import { useCurrency } from '@/context/CurrencyContext';
import { TrendingUp, TrendingDown, Target, Percent } from 'lucide-react'
export default function Analytics() {
  const { invoices } = useInvoiceContext()
  const avgInvoiceValue = invoices.length > 0 ? invoices.reduce((s, i) => s + i.amount, 0) /
invoices.length : 0;
  const paidRate = invoices.length > 0 ? (invoices.filter((i) => i.status === 'paid').length /
invoices.length) * 100 : 0;
  const overdueRate = invoices.length > 0 ? (invoices.filter((i) => i.status ===
'overdue').length / invoices.length) * 100 : 0
  const { formatCurrency } = useCurrency();
  const topClients = Array.from(
    invoices.reduce((map, inv) => {
      const existing = map.get(inv.clientName) || 0;
      map.set(inv.clientName, existing + inv.amount);
      return map;
    }, new Map<string, number>()))
    .sort((a, b) => b[1] - a[1])
    .slice(0, 5);
  return (<MainLayout>
      <div className="space-y-8"><div>
          <h1 className="text-3xl font-bold tracking-tight text-foreground">Analytics</h1>
          <p className="mt-1 text-muted-foreground">Insights and trends from your invoice
data.</p></div>
        <div className="grid gap-6 sm:grid-cols-2 lg:grid-cols-4">
          <MetricCard title="Avg. Invoice Value" value={formatCurrency(avgInvoiceValue)}
icon={Target} variant="primary"/>
          <MetricCard title="Payment Rate" value={`${paidRate.toFixed(0)}%`}
subtitle="Invoices paid" icon={TrendingUp} variant="success" />
          <MetricCard title="Overdue Rate" value={`${overdueRate.toFixed(0)}%`}
subtitle="Past due date" icon={TrendingDown} variant="destructive" />
          <MetricCard title="Total Invoices" value={invoices.length.toString()} subtitle="All
time" icon={Percent} variant="default" /></div>
        <div className="grid gap-6 lg:grid-cols-2">
          <RevenueChart />
          <StatusChart /></div>
        <div className="grid gap-6 lg:grid-cols-2">
          <div className="rounded-xl border bg-card p-6 shadow-sm">
```

```
          <h3 className="text-lg font-semibold text-card-foreground">Top Clients</h3>
          <p className="text-sm text-muted-foreground mb-4">By total invoice value</p>
          {topClients.length === 0 ? (
            <p className="text-sm text-muted-foreground py-4 text-center">No data yet.
Upload invoices to see analytics.</p>) : (
            <div className="space-y-3">
              {topClients.map(([name, amount], index) => (
                <div key={name} className="flex items-center justify-between">
                  <div className="flex items-center gap-3">
                    <span className="flex h-6 w-6 items-center justify-center rounded-full bg-
primary/10 text-xs font-semibold text-primary">{index + 1}</span>
                    <span className="text-sm font-medium text-foreground">{name}</span>
                  </div>
                  <span className="text-sm font-semibold text-
foreground">{formatCurrency(amount)}</span>
                </div>
              ))}</div>)}</div></div></div></MainLayout>);}
```

Clients.tsx

```
import { MainLayout } from '@/components/layout/MainLayout';
import { Input } from '@/components/ui/input';
import { Button } from '@/components/ui/button';
import { useInvoiceContext } from '@/context/InvoiceContext';
import { useCurrency } from '@/context/CurrencyContext';
import { Search, Mail, Phone, MoreHorizontal, Users } from 'lucide-react';
import {
  DropdownMenu,
  DropdownMenuContent,
  DropdownMenuItem,
  DropdownMenuTrigger,
} from '@/components/ui/dropdown-menu';
import { useState } from 'react';
import { useNavigate } from 'react-router-dom';
export default function Clients() {
  const { clients } = useInvoiceContext();
  const [search, setSearch] = useState('');
  const navigate = useNavigate();
  const filtered = clients.filter((c) => c.name.toLowerCase().includes(search.toLowerCase()) ||
c.email.toLowerCase().includes(search.toLowerCase()));
  const { formatCurrency } = useCurrency();

  return (<MainLayout>
     <div className="space-y-6"><div>
        <h1 className="text-3xl font-bold tracking-tight text-foreground">Clients</h1>
        <p className="mt-1 text-muted-foreground">Manage your client relationships and
contact information.</p></div>
       <div className="flex flex-col gap-4 sm:flex-row sm:items-center sm:justify-between">
        <div className="relative flex-1 max-w-sm">
            <Search className="absolute left-3 top-1/2 h-4 w-4 -translate-y-1/2 text-muted-
```

```
foreground" />
          <Input placeholder="Search clients..." className="pl-10" value={search}
onChange={(e) => setSearch(e.target.value)} /></div></div>
        {clients.length === 0 ? (
         <div className="flex flex-col items-center justify-center py-16 text-center">
          <Users className="h-12 w-12 text-muted-foreground/50 mb-4" />
          <p className="text-lg font-semibold text-foreground">No clients yet</p>
          <p className="text-sm text-muted-foreground mt-1">Client details will be extracted
automatically when you upload invoices.</p></div>) : (
         <div className="grid gap-6 sm:grid-cols-2 lg:grid-cols-3">
          {filtered.map((client) => (
           <div key={client.email} className="rounded-xl border bg-card p-6 shadow-sm
transition-all hover:shadow-md animate-fade-in">
            <div className="flex items-start justify-between">
             <div className="flex items-center gap-4">
              <div className="flex h-12 w-12 items-center justify-center rounded-full bg-
primary/10 text-lg font-semibold text-primary">
               {client.name.charAt(0)}</div><div>
               <h3 className="font-semibold text-foreground">{client.name}</h3>
               <p className="text-sm text-muted-
foreground">{client.email}</p></div></div>
            <DropdownMenu>
             <DropdownMenuTrigger asChild>
              <Button variant="ghost" size="icon" className="h-8 w-8"><MoreHorizontal
className="h-4 w-4" /></Button>
             </DropdownMenuTrigger>
             <DropdownMenuContent align="end">
              <DropdownMenuItem onClick={() =>
navigate(`/invoices?client=${encodeURIComponent(client.name)}`)}>View
Invoices</DropdownMenuItem>
             </DropdownMenuContent></DropdownMenu></div>
            <div className="mt-6 grid grid-cols-2 gap-4"><div>
             <p className="text-sm text-muted-foreground">Total Invoices</p>
             <p className="text-2xl font-bold text-foreground">{client.totalInvoices}</p>
</div><div><p className="text-sm text-muted-foreground">Total Value</p>
             <p className="text-2xl font-bold text-
primary">{formatCurrency(client.totalAmount)}</p></div></div>
            <div className="mt-6 flex gap-2">
             <Button variant="outline" size="sm" className="flex-1"><Mail
className="mr-2 h-4 w-4" />Email</Button>
             <Button variant="outline" size="sm" className="flex-1"><Phone
className="mr-2 h-4 w-4" />Call</Button><div></div>))}</div>)}</div></MainLayout>
);}
```

Dashboard.tsx

```
import { MainLayout } from '@/components/layout/MainLayout';
import { MetricCard } from '@/components/dashboard/MetricCard';
import { RevenueChart } from '@/components/dashboard/RevenueChart';
import { StatusChart } from '@/components/dashboard/StatusChart';
```

```
import { RecentInvoices } from '@/components/dashboard/RecentInvoices';
import { useInvoiceContext } from '@/context/InvoiceContext';
import { DollarSign, FileText, Clock, AlertTriangle } from 'lucide-react';
import { useCurrency } from '@/context/CurrencyContext';
export default function Dashboard() {
  const { metrics } = useInvoiceContext();
  const { formatCurrency } = useCurrency();
  return (
    <MainLayout>
      <div className="space-y-8"><div>
        <h1 className="text-3xl font-bold tracking-tight text-foreground">Dashboard</h1>
        <p className="mt-1 text-muted-foreground">Welcome back! Here's your invoice
overview.</p></div>
      <div className="grid gap-6 sm:grid-cols-2 lg:grid-cols-4">
        <MetricCard title="Total Revenue" value={formatCurrency(metrics.totalRevenue)}
subtitle={`${metrics.invoicesThisMonth} invoices this month`} icon={DollarSign}
variant="primary" />
        <MetricCard title="Total Invoices" value={metrics.totalInvoices.toString()}
subtitle="All time" icon={FileText} variant="default" />
        <MetricCard title="Pending" value={formatCurrency(metrics.pendingAmount)}
subtitle="Awaiting payment" icon={Clock} variant="warning" />
        <MetricCard title="Overdue" value={formatCurrency(metrics.overdueAmount)}
subtitle="Requires attention" icon={AlertTriangle} variant="destructive" /></div>
      <div className="grid gap-6 lg:grid-cols-2"><RevenueChart /><StatusChart /></div>
      <RecentInvoices /></div></MainLayout>);}
```

Employees.tsx

```
import { useState } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { useERPContext } from '@/context/ERPContext';
import { useCurrency } from '@/context/CurrencyContext';
import { Employee } from '@/types/erp';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardHeader, CardTitle } from '@/components/ui/card';
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter } from
'@/components/ui/dialog';
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from
'@/components/ui/table';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from
'@/components/ui/select';
import { DropdownMenu, DropdownMenuContent, DropdownMenuItem,
DropdownMenuTrigger, DropdownMenuSeparator } from '@/components/ui/dropdown-
menu';
import { Badge } from '@/components/ui/badge';
import { Users, Plus, MoreHorizontal, Trash2, UserCheck, UserX } from 'lucide-react';
const departments = ['Engineering', 'Sales', 'Marketing', 'Finance', 'HR', 'Operations',
'Support', 'Other'];export default function Employees() {
```

```
  const { employees, addEmployee, updateEmployee, deleteEmployee } = useERPContext();
  const [addOpen, setAddOpen] = useState(false);
  const [form, setForm] = useState({ name: '', email: '', phone: '', role: '', department: '',
joinDate: new Date().toISOString().split('T')[0], salary: '' });
  const handleAdd = () => {
    const employee: Employee = {
      id: crypto.randomUUID(),
      name: form.name,
      email: form.email,
      phone: form.phone || undefined,
      role: form.role,
      department: form.department,
      joinDate: form.joinDate,
      salary: form.salary ? parseFloat(form.salary) : undefined,
      status: 'active',};
    addEmployee(employee);
    setAddOpen(false);
    setForm({ name: '', email: '', phone: '', role: '', department: '', joinDate: new
Date().toISOString().split('T')[0], salary: '' });};
  const { formatCurrency } = useCurrency();
  return (
    <MainLayout>
      <div className="space-y-6">
        <div className="flex items-center justify-between"><div>
            <h1 className="text-3xl font-bold tracking-tight text-foreground">Employees</h1>
            <p className="mt-1 text-muted-foreground">Manage employee records, roles, and
departments.</p></div><Button onClick={() => setAddOpen(true)}><Plus className="mr-
2 h-4 w-4" /> Add Employee</Button></div>
        <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Total
Employees</CardTitle></CardHeader><CardContent><p className="text-2xl font-
bold">{employees.length}</p></CardContent></Card>
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Active</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold text-success">{employees.filter(e => e.status ===
'active').length}</p></CardContent></Card>
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Departments</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold">{new Set(employees.map(e =>
e.department)).size}</p></CardContent></Card></div>
        {employees.length === 0 ? (
          <div className="flex flex-col items-center justify-center py-16 text-center">
            <Users className="h-12 w-12 text-muted-foreground mb-3" />
            <p className="text-lg font-semibold">No employees yet</p>
            <p className="text-sm text-muted-foreground mt-1">Add your first employee.</p>
</div>) : (<div className="rounded-xl border bg-card shadow-sm overflow-hidden">
            <Table>
              <TableHeader>
                <TableRow className="bg-muted/50">
```

```
<TableHead>Name</TableHead>
              <TableHead>Role</TableHead>
              <TableHead>Department</TableHead>
              <TableHead>Email</TableHead>
              <TableHead>Join Date</TableHead>
              <TableHead>Status</TableHead>
              <TableHead className="w-[50px]"></TableHead>
            </TableRow>
          </TableHeader>
          <TableBody>
            {employees.map(e => (
              <TableRow key={e.id}>
                <TableCell className="font-medium">{e.name}</TableCell>
                <TableCell>{e.role}</TableCell>
                <TableCell><Badge variant="secondary" className="text-
xs">{e.department}</Badge></TableCell>
                <TableCell className="text-muted-foreground">{e.email}</TableCell>
                <TableCell className="text-muted-foreground">{new
Date(e.joinDate).toLocaleDateString()}</TableCell>
                <TableCell>
                  <span className={`inline-flex items-center rounded-full border px-2.5 py-0.5
text-xs font-medium ${
                    e.status === 'active' ? 'bg-success/10 text-success border-success/20' : 'bg-
muted text-muted-foreground'
                  }`}>{e.status === 'active' ? 'Active' : 'Inactive'}</span>
                </TableCell>
                <TableCell>
                  <DropdownMenu>
                    <DropdownMenuTrigger asChild><Button variant="ghost" size="icon"
className="h-8 w-8"><MoreHorizontal className="h-4 w-4"
/></Button></DropdownMenuTrigger>
                    <DropdownMenuContent align="end">
                      {e.status === 'active' ? (
                        <DropdownMenuItem onClick={() => updateEmployee(e.id, { status:
'inactive' })}><UserX className="mr-2 h-4 w-4" /> Deactivate</DropdownMenuItem>) : (
                        <DropdownMenuItem onClick={() => updateEmployee(e.id, { status:
'active' })}><UserCheck className="mr-2 h-4 w-4" /> Activate</DropdownMenuItem>)}
                      <DropdownMenuSeparator />
                      <DropdownMenuItem className="text-destructive" onClick={() =>
deleteEmployee(e.id)}><Trash2 className="mr-2 h-4 w-4" />
Delete</DropdownMenuItem>
                    </DropdownMenuContent></DropdownMenu></TableCell></TableRow>))}
          </TableBody></Table></div>)}</div>
      <Dialog open={addOpen} onOpenChange={setAddOpen}>
        <DialogContent className="max-w-md">
          <DialogHeader><DialogTitle>Add Employee</DialogTitle></DialogHeader>
          <div className="space-y-3">
            <div className="grid grid-cols-2 gap-3">
              <div><Label>Name</Label><Input value={form.name} onChange={e =>
setForm({ ...form, name: e.target.value })} /></div>
```

```
<div><Label>Email</Label><Input type="email" value={form.email} onChange={e =>
setForm({ ...form, email: e.target.value })} /></div></div>
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Role</Label><Input value={form.role} onChange={e => setForm({
...form, role: e.target.value })} placeholder="e.g., Manager" /></div><div>
            <Label>Department</Label>
            <Select value={form.department} onValueChange={v => setForm({ ...form,
department: v })}>
              <SelectTrigger><SelectValue placeholder="Select" /></SelectTrigger>
              <SelectContent>{departments.map(d => <SelectItem key={d}
value={d}>{d}</SelectItem>)}</SelectContent></Select></div></div>
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Phone</Label><Input value={form.phone} onChange={e =>
setForm({ ...form, phone: e.target.value })} /></div>
          <div><Label>Join Date</Label><Input type="date" value={form.joinDate}
onChange={e => setForm({ ...form, joinDate: e.target.value })} /></div></div>
        <div><Label>Salary</Label><Input type="number" value={form.salary}
onChange={e => setForm({ ...form, salary: e.target.value })} placeholder="Optional"
/></div></div>
      <DialogFooter><Button onClick={handleAdd} disabled={!form.name || !form.email ||
!form.role}>Add
Employee</Button></DialogFooter></DialogContent></Dialog></MainLayout> );}
```

Expenses.tsx

```
import { useState } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { useERPContext } from '@/context/ERPContext';
import { useCurrency } from '@/context/CurrencyContext';
import { Expense } from '@/types/erp';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardHeader, CardTitle } from '@/components/ui/card';
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter } from
'@/components/ui/dialog';
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from
'@/components/ui/table';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from
'@/components/ui/select';
import { DropdownMenu, DropdownMenuContent, DropdownMenuItem,
DropdownMenuTrigger, DropdownMenuSeparator } from '@/components/ui/dropdown-
menu';
import { Badge } from '@/components/ui/badge';
import { Receipt, Plus, MoreHorizontal, Trash2, CheckCircle, XCircle, DollarSign } from
'lucide-react';
const categories = ['Office Supplies', 'Travel', 'Utilities', 'Software', 'Marketing', 'Equipment',
'Meals', 'Other'];
export default function Expenses() {
  const { expenses, addExpense, updateExpenseStatus, deleteExpense, totalExpenses } =
```

```
useERPContext();
  const [addOpen, setAddOpen] = useState(false);
  const [form, setForm] = useState({ description: '', category: '', amount: '', date: new
Date().toISOString().split('T')[0], vendor: '', notes: '' });
  const handleAdd = () => {
    const expense: Expense = {
      id: crypto.randomUUID(),
      description: form.description,
      category: form.category,
      amount: parseFloat(form.amount) || 0,
      date: form.date,
      vendor: form.vendor || undefined,
      notes: form.notes || undefined,
      status: 'pending',};
    addExpense(expense);
    setAddOpen(false);
    setForm({ description: '', category: '', amount: '', date: new
Date().toISOString().split('T')[0], vendor: '', notes: '' });};
  const { formatCurrency } = useCurrency();
  const approvedTotal = expenses.filter(e => e.status === 'approved').reduce((s, e) => s +
e.amount, 0);
  return (<MainLayout>
      <div className="space-y-6">
        <div className="flex items-center justify-between"><div>
            <h1 className="text-3xl font-bold tracking-tight text-foreground">Expenses</h1>
            <p className="mt-1 text-muted-foreground">Track and categorize business
expenses.</p></div>
          <Button onClick={() => setAddOpen(true)}><Plus className="mr-2 h-4 w-4" /> Add
Expense</Button></div>
        <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Total
Expenses</CardTitle></CardHeader><CardContent><p className="text-2xl font-
bold">{formatCurrency(totalExpenses)}</p></CardContent></Card>
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Approved</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold text-
success">{formatCurrency(approvedTotal)}</p></CardContent></Card>
          <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Pending</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold text-warning">{expenses.filter(e => e.status ===
'pending').length}</p></CardContent></Card></div>
        {expenses.length === 0 ? (
          <div className="flex flex-col items-center justify-center py-16 text-center">
            <Receipt className="h-12 w-12 text-muted-foreground mb-3" />
            <p className="text-lg font-semibold">No expenses yet</p>
            <p className="text-sm text-muted-foreground mt-1">Add your first expense to start
tracking.</p></div>) : (
          <div className="rounded-xl border bg-card shadow-sm overflow-hidden"><Table>
              <TableHeader>
```

```
<TableRow className="bg-muted/50">
            <TableHead>Date</TableHead>
            <TableHead>Description</TableHead>
            <TableHead>Category</TableHead>
            <TableHead>Vendor</TableHead>
            <TableHead className="text-right">Amount</TableHead>
            <TableHead>Status</TableHead>
            <TableHead className="w-[50px]"></TableHead>
          </TableRow>
        </TableHeader>
        <TableBody>
          {expenses.map(e => (
            <TableRow key={e.id}>
              <TableCell className="text-muted-foreground">{new
Date(e.date).toLocaleDateString()}</TableCell>
              <TableCell className="font-medium">{e.description}</TableCell>
              <TableCell><Badge variant="secondary" className="text-
xs">{e.category}</Badge></TableCell>
              <TableCell className="text-muted-foreground">{e.vendor || '—'}</TableCell>
              <TableCell className="text-right font-
semibold">{formatCurrency(e.amount)}</TableCell>
              <TableCell><span className={`inline-flex items-center rounded-full border px-
2.5 py-0.5 text-xs font-medium ${
                e.status === 'approved' ? 'bg-success/10 text-success border-success/20' :
                e.status === 'rejected' ? 'bg-destructive/10 text-destructive border-
destructive/20' :
                'bg-warning/10 text-warning border-warning/20'
              }`}>{e.status.charAt(0).toUpperCase() + e.status.slice(1)}</span>
              </TableCell><TableCell><DropdownMenu>
                <DropdownMenuTrigger asChild><Button variant="ghost" size="icon"
className="h-8 w-8"><MoreHorizontal className="h-4 w-4"
/></Button></DropdownMenuTrigger><DropdownMenuContent align="end">
                  {e.status !== 'approved' && <DropdownMenuItem onClick={() =>
updateExpenseStatus(e.id, 'approved')}><CheckCircle className="mr-2 h-4 w-4" />
Approve</DropdownMenuItem>}
                  {e.status !== 'rejected' && <DropdownMenuItem onClick={() =>
updateExpenseStatus(e.id, 'rejected')}><XCircle className="mr-2 h-4 w-4" />
Reject</DropdownMenuItem>}
                  <DropdownMenuSeparator />
                  <DropdownMenuItem className="text-destructive" onClick={() =>
deleteExpense(e.id)}><Trash2 className="mr-2 h-4 w-4" /> Delete</DropdownMenuItem>
                </DropdownMenuContent></DropdownMenu></TableCell></TableRow>))}
</TableBody></Table></div> )}</div>
    <Dialog open={addOpen} onOpenChange={setAddOpen}>
      <DialogContent className="max-w-md">
        <DialogHeader><DialogTitle>Add Expense</DialogTitle></DialogHeader>
        <div className="space-y-3">
          <div><Label>Description</Label><Input value={form.description} onChange={e =>
setForm({ ...form, description: e.target.value })} /></div>
          <div className="grid grid-cols-2 gap-3"><div>
```

```
<Label>Category</Label>
            <Select value={form.category} onValueChange={v => setForm({ ...form,
category: v })}><SelectTrigger><SelectValue placeholder="Select" /></SelectTrigger>
             <SelectContent>{categories.map(c => <SelectItem key={c}
value={c}>{c}</SelectItem>)}</SelectContent></Select></div>
          <div><Label>Amount</Label><Input type="number" value={form.amount}
onChange={e => setForm({ ...form, amount: e.target.value })} /></div></div>
         <div className="grid grid-cols-2 gap-3">
          <div><Label>Date</Label><Input type="date" value={form.date} onChange={e =>
setForm({ ...form, date: e.target.value })} /></div>
          <div><Label>Vendor</Label><Input value={form.vendor} onChange={e =>
setForm({ ...form, vendor: e.target.value })} /></div></div>
         <div><Label>Notes</Label><Input value={form.notes} onChange={e => setForm({
...form, notes: e.target.value })} /></div></div>
        <DialogFooter><Button onClick={handleAdd} disabled={!form.description ||
!form.amount}>Add
Expense</Button></DialogFooter></DialogContent></Dialog></MainLayout>);}
```

Inventory.tsx

```
import { useState } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { useERPContext } from '@/context/ERPContext';
import { useCurrency } from '@/context/CurrencyContext';
import { Product, StockMovement } from '@/types/erp';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardHeader, CardTitle } from '@/components/ui/card';
import {Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter,
} from '@/components/ui/dialog'; import {
  Table, TableBody, TableCell, TableHead, TableHeader, TableRow,
} from '@/components/ui/table';
import {Select, SelectContent, SelectItem, SelectTrigger, SelectValue,
} from '@/components/ui/select'; import {
  DropdownMenu, DropdownMenuContent, DropdownMenuItem, DropdownMenuTrigger,
DropdownMenuSeparator,
} from '@/components/ui/dropdown-menu';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Package, AlertTriangle, TrendingUp, MoreHorizontal, Plus, Trash2, ArrowUpDown
} from 'lucide-react'; import { Badge } from '@/components/ui/badge';
export default function Inventory() { const {
    products, addProduct, deleteProduct,
    stockMovements, addStockMovement,
    lowStockProducts, totalInventoryValue,
  } = useERPContext();
  const [addOpen, setAddOpen] = useState(false);
  const [stockOpen, setStockOpen] = useState(false);
  const [selectedProduct, setSelectedProduct] = useState<Product | null>(null);
  const [form, setForm] = useState({ name: '', sku: '', category: '', unitPrice: '', costPrice: '',
```

```
currentStock: '', reorderPoint: '10', unit: 'pcs', description: '' });
  const [stockForm, setStockForm] = useState({ productId: '', type: 'in' as 'in' | 'out' |
'adjustment', quantity: '', reason: '' });
  const handleAddProduct = () => {
    const product: Product = {
      id: crypto.randomUUID(),
      name: form.name,
      sku: form.sku,
      category: form.category,
      description: form.description,
      unitPrice: parseFloat(form.unitPrice) || 0,
      costPrice: parseFloat(form.costPrice) || 0,
      currentStock: parseInt(form.currentStock) || 0,
      reorderPoint: parseInt(form.reorderPoint) || 10,
      unit: form.unit,
      createdAt: new Date().toISOString(),};
    addProduct(product);
    setAddOpen(false);
    setForm({ name: '', sku: '', category: '', unitPrice: '', costPrice: '', currentStock: '',
reorderPoint: '10', unit: 'pcs', description: '' });};
  const handleStockMovement = () => {
    const product = products.find(p => p.id === stockForm.productId);
    if (!product) return;
    const movement: StockMovement = {
      id: crypto.randomUUID(),
      productId: stockForm.productId,
      productName: product.name,
      type: stockForm.type,
      quantity: parseInt(stockForm.quantity) || 0,
      reason: stockForm.reason,
      createdAt: new Date().toISOString(),};
    addStockMovement(movement);
    setStockOpen(false);
    setStockForm({ productId: '', type: 'in', quantity: '', reason: '' });};
  const { formatCurrency } = useCurrency();
  return (<MainLayout>
      <div className="space-y-6">
        <div className="flex items-center justify-between"><div>
            <h1 className="text-3xl font-bold tracking-tight text-foreground">Inventory</h1>
            <p className="mt-1 text-muted-foreground">Manage products and stock levels.</p>
</div><div className="flex gap-2">
            <Button variant="outline" onClick={() => setStockOpen(true)}>
              <ArrowUpDown className="mr-2 h-4 w-4" /> Stock Movement</Button>
            <Button onClick={() => setAddOpen(true)}>
              <Plus className="mr-2 h-4 w-4" /> Add Product</Button>
</div></div>
        {/* Summary Cards */}
        <div className="grid grid-cols-1 md:grid-cols-3 gap-4"><Card>
            <CardHeader className="flex flex-row items-center justify-between pb-2">
              <CardTitle className="text-sm font-medium text-muted-foreground">Total
```

```
Products</CardTitle>
            <Package className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent><p className="text-2xl font-
bold">{products.length}</p></CardContent></Card><Card>
          <CardHeader className="flex flex-row items-center justify-between pb-2">
            <CardTitle className="text-sm font-medium text-muted-foreground">Inventory
Value</CardTitle>
            <TrendingUp className="h-4 w-4 text-muted-foreground" /></CardHeader>
          <CardContent><p className="text-2xl font-
bold">{formatCurrency(totalInventoryValue)}</p></CardContent>
        </Card><Card>
          <CardHeader className="flex flex-row items-center justify-between pb-2">
            <CardTitle className="text-sm font-medium text-muted-foreground">Low Stock
Alerts</CardTitle>
            <AlertTriangle className="h-4 w-4 text-warning" />
          </CardHeader>
          <CardContent><p className="text-2xl font-bold text-
warning">{lowStockProducts.length}</p></CardContent></Card></div>
      <Tabs defaultValue="products">
        <TabsList><TabsTrigger value="products">Products</TabsTrigger>
          <TabsTrigger value="movements">Stock Movements</TabsTrigger></TabsList>
        <TabsContent value="products" className="mt-4">
          {products.length === 0 ? (
            <div className="flex flex-col items-center justify-center py-16 text-center">
              <Package className="h-12 w-12 text-muted-foreground mb-3" />
              <p className="text-lg font-semibold">No products yet</p>
              <p className="text-sm text-muted-foreground mt-1">Add your first product to get
started.</p></div>) : (
            <div className="rounded-xl border bg-card shadow-sm overflow-hidden"><Table>
                <TableHeader>
                  <TableRow className="bg-muted/50">
                    <TableHead>SKU</TableHead>
                    <TableHead>Product</TableHead>
                    <TableHead>Category</TableHead>
                    <TableHead className="text-right">Cost</TableHead>
                    <TableHead className="text-right">Price</TableHead>
                    <TableHead className="text-right">Stock</TableHead>
                    <TableHead>Status</TableHead>
                    <TableHead className="w-
[50px]"></TableHead></TableRow></TableHeader>
                <TableBody>{products.map(p => (
                    <TableRow key={p.id}>
                      <TableCell className="font-mono text-sm">{p.sku}</TableCell>
                      <TableCell className="font-medium">{p.name}</TableCell>
                      <TableCell>{p.category}</TableCell>
                      <TableCell className="text-
right">{formatCurrency(p.costPrice)}</TableCell>
                      <TableCell className="text-
right">{formatCurrency(p.unitPrice)}</TableCell>
```

```
<TableCell className="text-right font-semibold">{p.currentStock}
{p.unit}</TableCell><TableCell>
                    {p.currentStock <= p.reorderPoint ? (
                      <Badge variant="destructive" className="text-xs">Low Stock</Badge>) :
(
                      <Badge variant="secondary" className="text-xs bg-success/10 text-
success border-success/20">In
Stock</Badge>)}</TableCell><TableCell><DropdownMenu>
                      <DropdownMenuTrigger asChild>
                        <Button variant="ghost" size="icon" className="h-8 w-
8"><MoreHorizontal className="h-4 w-4" /></Button></DropdownMenuTrigger>
                      <DropdownMenuContent align="end">
                        <DropdownMenuItem onClick={() => { setSelectedProduct(p);
setStockForm({ ...stockForm, productId: p.id }); setStockOpen(true); }}>
                          <ArrowUpDown className="mr-2 h-4 w-4" /> Adjust Stock
                        </DropdownMenuItem><DropdownMenuSeparator />
                        <DropdownMenuItem className="text-destructive" onClick={() =>
deleteProduct(p.id)}><Trash2 className="mr-2 h-4 w-4" /> Delete</DropdownMenuItem>
                      </DropdownMenuContent></DropdownMenu></TableCell></TableRow>)
)}
              </TableBody></Table></div>)}</TabsContent>
        <TabsContent value="movements" className="mt-4">
          {stockMovements.length === 0 ? (
            <div className="flex flex-col items-center justify-center py-16 text-center">
              <ArrowUpDown className="h-12 w-12 text-muted-foreground mb-3" />
              <p className="text-lg font-semibold">No stock movements</p>
              <p className="text-sm text-muted-foreground mt-1">Record stock in/out to track
history.</p></div>) : (
            <div className="rounded-xl border bg-card shadow-sm overflow-hidden"><Table>
              <TableHeader><TableRow className="bg-muted/50">
                <TableHead>Date</TableHead><TableHead>Product</TableHead>
                <TableHead>Type</TableHead><TableHead className="text-
right">Quantity</TableHead><TableHead>Reason</TableHead><TableRow>
              </TableHeader><TableBody>{stockMovements.map(m => (
                <TableRow key={m.id}><TableCell className="text-muted-
foreground">{new Date(m.createdAt).toLocaleDateString()}</TableCell>
                  <TableCell className="font-medium">{m.productName}</TableCell>
                  <TableCell><Badge variant={m.type === 'in' ? 'default' : m.type === 'out' ?
'destructive' : 'secondary'} className="text-xs">
                    {m.type === 'in' ? 'Stock In' : m.type === 'out' ? 'Stock Out' : 'Adjustment'}
                  </Badge></TableCell>
                  <TableCell className="text-right font-semibold">{m.type === 'out' ? '-' :
'+'} {m.quantity}</TableCell>
                  <TableCell className="text-muted-foreground">{m.reason}</TableCell>
                </TableRow>))}</TableBody></Table></div>)}</TabsContent></Tabs></div
>
    {/* Add Product Dialog */}
    <Dialog open={addOpen} onOpenChange={setAddOpen}>
      <DialogContent className="max-w-md">
        <DialogHeader><DialogTitle>Add Product</DialogTitle></DialogHeader>
```

```
<div className="space-y-3">
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Name</Label><Input value={form.name} onChange={e =>
setForm({ ...form, name: e.target.value })} /></div>
          <div><Label>SKU</Label><Input value={form.sku} onChange={e => setForm({
...form, sku: e.target.value })} /></div></div>
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Category</Label><Input value={form.category} onChange={e =>
setForm({ ...form, category: e.target.value })} /></div>
          <div><Label>Unit</Label><Input value={form.unit} onChange={e => setForm({
...form, unit: e.target.value })} placeholder="pcs, kg, etc." /></div></div>
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Cost Price</Label><Input type="number" value={form.costPrice}
onChange={e => setForm({ ...form, costPrice: e.target.value })} /></div>
          <div><Label>Selling Price</Label><Input type="number" value={form.unitPrice}
onChange={e => setForm({ ...form, unitPrice: e.target.value })} /></div></div>
        <div className="grid grid-cols-2 gap-3">
          <div><Label>Initial Stock</Label><Input type="number"
value={form.currentStock} onChange={e => setForm({ ...form, currentStock: e.target.value
})} /></div>
          <div><Label>Reorder Point</Label><Input type="number"
value={form.reorderPoint} onChange={e => setForm({ ...form, reorderPoint: e.target.value
})} /></div></div>
      </div><DialogFooter><Button onClick={handleAddProduct} disabled={!form.name ||
!form.sku}>Add Product</Button></DialogFooter></DialogContent></Dialog>
    {/* Stock Movement Dialog */}
    <Dialog open={stockOpen} onOpenChange={setStockOpen}>
      <DialogContent className="max-w-md">
        <DialogHeader><DialogTitle>Record Stock
Movement</DialogTitle></DialogHeader>
        <div className="space-y-3"><div><Label>Product</Label>
          <Select value={stockForm.productId} onValueChange={v => setStockForm({
...stockForm, productId: v })}>
            <SelectTrigger><SelectValue placeholder="Select product" /></SelectTrigger>
            <SelectContent>
              {products.map(p => <SelectItem key={p.id} value={p.id}>{p.name}
({p.currentStock} {p.unit})</SelectItem>)}</SelectContent></Select></div><div>
          <Label>Type</Label>
          <Select value={stockForm.type} onValueChange={v => setStockForm({
...stockForm, type: v as any })}>
            <SelectTrigger><SelectValue /></SelectTrigger>
            <SelectContent>
              <SelectItem value="in">Stock In</SelectItem>
              <SelectItem value="out">Stock Out</SelectItem>
              <SelectItem value="adjustment">Adjustment</SelectItem></SelectContent>
</Select></div>
        <div><Label>Quantity</Label><Input type="number" value={stockForm.quantity}
onChange={e => setStockForm({ ...stockForm, quantity: e.target.value })} /></div>
        <div><Label>Reason</Label><Input value={stockForm.reason} onChange={e =>
setStockForm({ ...stockForm, reason: e.target.value })} placeholder="e.g., Purchase, Sale,
```

```
Damaged" /></div></div>
        <DialogFooter><Button onClick={handleStockMovement}
disabled={!stockForm.productId || !stockForm.quantity}>Record</Button></DialogFooter>
      </DialogContent></Dialog></MainLayout>);}
```

Invoices.tsx

```
import { useState, useMemo, useEffect } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { InvoiceTable } from '@/components/invoices/InvoiceTable';
import { InvoiceFilters } from '@/components/invoices/InvoiceFilters';
import { UploadInvoiceDialog } from '@/components/invoices/UploadInvoiceDialog';
import { RecommendationPanel } from '@/components/invoices/RecommendationPanel';
import { useInvoiceContext } from '@/context/InvoiceContext';
import { InvoiceStatus } from '@/types/invoice';
import { useSearchParams } from 'react-router-dom';
import
{Pagination,PaginationContent,PaginationItem,PaginationLink,PaginationNext,PaginationPre
vious, PaginationEllipsis,} from '@/components/ui/pagination';
import { Select,SelectContent,SelectItem,SelectTrigger,SelectValue,} from
'@/components/ui/select';
export default function Invoices() {
  const { invoices, addInvoice, updateInvoiceStatus, deleteInvoice } = useInvoiceContext();
  const [searchParams, setSearchParams] = useSearchParams();
  const [searchTerm, setSearchTerm] = useState('');
  const [statusFilter, setStatusFilter] = useState<InvoiceStatus | 'all'>('all');
  const [uploadOpen, setUploadOpen] = useState(false);
  const [currentPage, setCurrentPage] = useState(1);
  const [pageSize, setPageSize] = useState(10);
  // Pre-fill search from query params (client or vendor)
  useEffect(() => {
    const client = searchParams.get('client');
    const vendor = searchParams.get('vendor');
    if (client) {
      setSearchTerm(client);
      setSearchParams({}, { replace: true });
    } else if (vendor) {
      setSearchTerm(vendor);
      setSearchParams({}, { replace: true });}
  }, [searchParams, setSearchParams]);
  const filteredInvoices = useMemo(() => {
    return invoices.filter((invoice) => {
      const term = searchTerm.toLowerCase();
      const matchesSearch =
        invoice.invoiceNumber.toLowerCase().includes(term) ||
        invoice.clientName.toLowerCase().includes(term) ||
        invoice.clientEmail.toLowerCase().includes(term) ||
        (invoice.vendorName?.toLowerCase().includes(term) ?? false);
      const matchesStatus = statusFilter === 'all' || invoice.status === statusFilter;
      return matchesSearch && matchesStatus;});
```

```
}, [searchTerm, statusFilter, invoices]);
  const totalPages = Math.ceil(filteredInvoices.length / pageSize);
  const paginatedInvoices = filteredInvoices.slice((currentPage - 1) * pageSize, currentPage *
pageSize);
  const handleSearchChange = (val: string) => { setSearchTerm(val); setCurrentPage(1); };
  const handleStatusChange = (val: InvoiceStatus | 'all') => { setStatusFilter(val);
setCurrentPage(1); };
  const handlePageSizeChange = (val: string) => { setPageSize(Number(val));
setCurrentPage(1); };
  return (
    <MainLayout>
      <div className="space-y-6"><div>
          <h1 className="text-3xl font-bold tracking-tight text-foreground">Invoices</h1>
          <p className="mt-1 text-muted-foreground">
            Manage and track all your invoices in one place.</p></div>
        <InvoiceFilters
          searchTerm={searchTerm}
          onSearchChange={handleSearchChange}
          statusFilter={statusFilter}
          onStatusChange={handleStatusChange}
          onNewInvoice={() => setUploadOpen(true)}/>
        {invoices.length === 0 ? (
          <div className="flex flex-col items-center justify-center py-16 text-center">
            <p className="text-lg font-semibold text-foreground">No invoices yet</p>
            <p className="text-sm text-muted-foreground mt-1">Upload your first invoice to
get started.</p></div>) : (<>
            <div className="flex items-center justify-between">
              <p className="text-sm text-muted-foreground">
                Showing {(currentPage - 1) * pageSize + 1}–{Math.min(currentPage * pageSize,
filteredInvoices.length)} of {filteredInvoices.length} invoices</p>
              <div className="flex items-center gap-2">
                <span className="text-sm text-muted-foreground">Per page:</span>
                <Select value={String(pageSize)} onValueChange={handlePageSizeChange}>
                  <SelectTrigger className="w-[72px] h-8"><SelectValue /></SelectTrigger>
                  <SelectContent>{[5, 10, 25, 50, 100].map(size => (
                    <SelectItem key={size} value={String(size)}>{size}</SelectItem>))}
                  </SelectContent></Select></div></div>
            <InvoiceTable invoices={paginatedInvoices} onDelete={deleteInvoice}
onStatusChange={updateInvoiceStatus} />
            {totalPages > 1 && (<Pagination><PaginationContent><PaginationItem>
                  <PaginationPrevious
                    onClick={() => setCurrentPage(p => Math.max(1, p - 1))}
                    className={currentPage === 1 ? 'pointer-events-none opacity-50' : 'cursor-
pointer'}/></PaginationItem>
                  {Array.from({ length: totalPages }, (_, i) => i + 1).map(page => {
                    if (totalPages <= 7 || page === 1 || page === totalPages || Math.abs(page -
currentPage) <= 1) {return (
                      <PaginationItem key={page}><PaginationLink
                        isActive={page === currentPage}
                        onClick={() => setCurrentPage(page)}
```

```
className="cursor-pointer" >
                    {page}</PaginationLink></PaginationItem>);}
              if (page === 2 && currentPage > 4) return <PaginationEllipsis key="start-
ellipsis" />;if (page === totalPages - 1 && currentPage < totalPages - 3) return
<PaginationEllipsis key="end-ellipsis" />;return null;})}
            <PaginationItem><PaginationNext
              onClick={() => setCurrentPage(p => Math.min(totalPages, p + 1))}
              className={currentPage === totalPages ? 'pointer-events-none opacity-50' :
'cursor-pointer'}/>
            </PaginationItem></PaginationContent></Pagination>)}<RecommendationPanel
/>
</>)}
      <UploadInvoice Dialogopen={uploadOpen} onClose={() => setUploadOpen(false)}
        onSave={addInvoice}/> </div> </MainLayout>);}
```

Payments.tsx

```
import { useMemo } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { useInvoiceContext } from '@/context/InvoiceContext';
import { useCurrency } from '@/context/CurrencyContext';
import { InvoiceStatusBadge } from '@/components/invoices/InvoiceStatusBadge';
import {
  Table, TableBody, TableCell, TableHead, TableHeader, TableRow,
} from '@/components/ui/table';
import { ArrowUpRight, ArrowDownRight, CreditCard } from 'lucide-react';
export default function Payments() {
  const { invoices, metrics } = useInvoiceContext();
  const payments = useMemo(() =>
    invoices
      .filter((inv) => inv.status === 'paid')
      .map((inv) => ({
        id: `PAY-${inv.id.slice(0, 6)}`, invoiceNumber: inv.invoiceNumber, clientName:
inv.clientName, amount: inv.amount, date: inv.dueDate,})), [invoices] );
  const totalReceived = payments.reduce((s, p) => s + p.amount, 0);
  const { formatCurrency } = useCurrency();
  const formatDate = (dateString: string) =>
    new Date(dateString).toLocaleDateString('en-US', { month: 'short', day: 'numeric', year:
'numeric' });
  return (
    <MainLayout><div className="space-y-6"><div>
        <h1 className="text-3xl font-bold tracking-tight text-foreground">Payments</h1>
        <p className="mt-1 text-muted-foreground">Track all incoming and outgoing
payments.</p></div>
      <div className="grid gap-6 sm:grid-cols-3">
        <div className="rounded-xl border bg-card p-6 shadow-sm">
          <div className="flex items-center gap-3">
            <div className="flex h-10 w-10 items-center justify-center rounded-lg bg-
success/10"><ArrowDownRight className="h-5 w-5 text-success" /></div><div>
              <p className="text-sm text-muted-foreground">Total Received</p>
```

```
<p className="text-2xl font-bold text-
foreground">{formatCurrency(totalReceived)}</p></div></div></div>
        <div className="rounded-xl border bg-card p-6 shadow-sm">
          <div className="flex items-center gap-3">
            <div className="flex h-10 w-10 items-center justify-center rounded-lg bg-
warning/10"><ArrowUpRight className="h-5 w-5 text-warning" /></div><div>
              <p className="text-sm text-muted-foreground">Pending</p>
              <p className="text-2xl font-bold text-
foreground">{formatCurrency(metrics.pendingAmount)}</p></div></div></div>
        <div className="rounded-xl border bg-card p-6 shadow-sm">
          <div className="flex items-center gap-3">
            <div className="flex h-10 w-10 items-center justify-center rounded-lg bg-
primary/10">
              <span className="text-lg font-bold text-
primary">{payments.length}</span></div> <div>
              <p className="text-sm text-muted-foreground">Transactions</p>
              <p className="text-2xl font-bold text-foreground">Total</p></div></div></div>
</div>{payments.length === 0 ? (
        <div className="flex flex-col items-center justify-center py-16 text-center">
          <CreditCard className="h-12 w-12 text-muted-foreground/50 mb-4" />
          <p className="text-lg font-semibold text-foreground">No payments yet</p>
          <p className="text-sm text-muted-foreground mt-1">Payments will appear here
when invoices are marked as paid.</p></div>} ): (
        <div className="rounded-xl border bg-card shadow-sm overflow-hidden animate-
fade-in"><Table><TableHeader><TableRow className="bg-muted/50 hover:bg-
muted/50">
              <TableHead className="font-semibold">Payment ID</TableHead>
              <TableHead className="font-semibold">Invoice</TableHead>
              <TableHead className="font-semibold">Client</TableHead>
              <TableHead className="font-semibold">Amount</TableHead>
              <TableHead className="font-semibold">Date</TableHead>
              <TableHead className="font-semibold">Status</TableHead></TableRow>
</TableHeader><TableBody>{payments.map((payment) => (
              <TableRow key={payment.id} className="hover:bg-muted/30">
                <TableCell className="font-medium text-primary">{payment.id}</TableCell>
                <TableCell className="text-muted-
foreground">{payment.invoiceNumber}</TableCell>
                <TableCell className="font-medium">{payment.clientName}</TableCell>
                <TableCell className="font-
semibold">{formatCurrency(payment.amount)}</TableCell>
                <TableCell className="text-muted-
foreground">{formatDate(payment.date)}</TableCell>
                <TableCell><InvoiceStatusBadge status="paid" /></TableCell></TableRow>))}
            </TableBody></Table></div>)}</div></MainLayout>);}
```

PurchaseOrder.tsx

```
import { useState } from 'react';
import { MainLayout } from '@/components/layout/MainLayout';
import { useERPContext } from '@/context/ERPContext';
```

```
import { useInvoiceContext } from '@/context/InvoiceContext';
import { useCurrency } from '@/context/CurrencyContext';
import { PurchaseOrder, PurchaseOrderItem } from '@/types/erp';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardHeader, CardTitle } from '@/components/ui/card';
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogFooter } from
'@/components/ui/dialog';
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from
'@/components/ui/table';
import { DropdownMenu, DropdownMenuContent, DropdownMenuItem,
DropdownMenuTrigger, DropdownMenuSeparator } from '@/components/ui/dropdown-
menu';
import { Badge } from '@/components/ui/badge';
import { ShoppingCart, MoreHorizontal, Plus, Trash2, CheckCircle, Clock, XCircle, Package
} from 'lucide-react';
const statusColors: Record<string, string> = {
  draft: 'bg-muted text-muted-foreground',
  sent: 'bg-warning/10 text-warning border-warning/20',
  received: 'bg-success/10 text-success border-success/20',
  cancelled: 'bg-destructive/10 text-destructive border-destructive/20',};
export default function PurchaseOrders() {
  const { purchaseOrders, addPurchaseOrder, updatePOStatus, deletePurchaseOrder } =
useERPContext();
  const { vendors } = useInvoiceContext();
  const [addOpen, setAddOpen] = useState(false);
  const [form, setForm] = useState({ vendorName: '', expectedDate: '', notes: '' });
  const [items, setItems] = useState<{ description: string; quantity: string; unitPrice: string
}[]>([{ description: '', quantity: '1', unitPrice: '' }]);
  const handleAdd = () => {
    const poItems: PurchaseOrderItem[] = items.map(i => ({
      id: crypto.randomUUID(),
      description: i.description,
      quantity: parseFloat(i.quantity) || 0,
      unitPrice: parseFloat(i.unitPrice) || 0,
      total: (parseFloat(i.quantity) || 0) * (parseFloat(i.unitPrice) || 0),}));
    const po: PurchaseOrder = {
      id: crypto.randomUUID(),
      poNumber: `PO-${Date.now().toString(36).toUpperCase()}`,
      vendorName: form.vendorName,status: 'draft', items: poItems,
      totalAmount: poItems.reduce((s, i) => s + i.total, 0),
      orderDate: new Date().toISOString().split('T')[0],
      expectedDate: form.expectedDate || undefined,
      notes: form.notes || undefined, };
    addPurchaseOrder(po);
    setAddOpen(false);
    setForm({ vendorName: '', expectedDate: '', notes: '' });
    setItems([{ description: '', quantity: '1', unitPrice: '' }]);};
  const addItem = () => setItems([...items, { description: '', quantity: '1', unitPrice: '' }]);
```

```
const updateItem = (idx: number, field: string, value: string) => {
   const updated = [...items];
   updated[idx] = { ...updated[idx], [field]: value };
   setItems(updated);};
  const { formatCurrency } = useCurrency();
  return (<MainLayout>
     <div className="space-y-6">
       <div className="flex items-center justify-between"><div>
          <h1 className="text-3xl font-bold tracking-tight text-foreground">Purchase
Orders</h1>
          <p className="mt-1 text-muted-foreground">Create and track purchase orders to
vendors.</p></div>
        <Button onClick={() => setAddOpen(true)}><Plus className="mr-2 h-4 w-4" />
New PO</Button></div>
       <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
        <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Total POs</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold">{purchaseOrders.length}</p></CardContent></Card>
        <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Pending</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold text-warning">{purchaseOrders.filter(p => p.status ===
'sent').length}</p></CardContent></Card>
        <Card><CardHeader className="pb-2"><CardTitle className="text-sm font-
medium text-muted-foreground">Total Value</CardTitle></CardHeader><CardContent><p
className="text-2xl font-bold">{formatCurrency(purchaseOrders.reduce((s, p) => s +
p.totalAmount, 0))}</p></CardContent></Card></div>
       {purchaseOrders.length === 0 ? (
        <div className="flex flex-col items-center justify-center py-16 text-center">
          <ShoppingCart className="h-12 w-12 text-muted-foreground mb-3" />
          <p className="text-lg font-semibold">No purchase orders yet</p>
          <p className="text-sm text-muted-foreground mt-1">Create your first purchase
order.</p></div> ) : (
        <div className="rounded-xl border bg-card shadow-sm overflow-hidden"> <Table>
           <TableHeader>
             <TableRow className="bg-muted/50">
               <TableHead>PO Number</TableHead>
               <TableHead>Vendor</TableHead>
               <TableHead className="text-right">Amount</TableHead>
               <TableHead>Status</TableHead>
               <TableHead>Order Date</TableHead>
               <TableHead className="w-[50px]"></TableHead>
             </TableRow></TableHeader><TableBody>
             {purchaseOrders.map(po => (<TableRow key={po.id}>
                <TableCell className="font-medium text-
primary">{po.poNumber}</TableCell>
                <TableCell>{po.vendorName}</TableCell>
                <TableCell className="text-right font-
semibold">{formatCurrency(po.totalAmount)}</TableCell> <TableCell>
                  <span className={`inline-flex items-center rounded-full border px-2.5 py-0.5
text-xs font-medium ${statusColors[po.status]}`}>
```

```
{po.status.charAt(0).toUpperCase() + po.status.slice(1)}</span></TableCell>
                <TableCell className="text-muted-foreground">{new
Date(po.orderDate).toLocaleDateString()}</TableCell><TableCell><DropdownMenu>
                  <DropdownMenuTrigger asChild><Button variant="ghost" size="icon"
className="h-8 w-8"><MoreHorizontal className="h-4 w-4"
/></Button></DropdownMenuTrigger><DropdownMenuContent align="end">
                    {po.status !== 'sent' && <DropdownMenuItem onClick={() =>
updatePOStatus(po.id, 'sent')}><Clock className="mr-2 h-4 w-4" /> Mark as
Sent</DropdownMenuItem>}{po.status !== 'received' && <DropdownMenuItem
onClick={() => updatePOStatus(po.id, 'received')}><CheckCircle className="mr-2 h-4 w-
4" /> Mark as Received</DropdownMenuItem>}
                    {po.status !== 'cancelled' && <DropdownMenuItem onClick={() =>
updatePOStatus(po.id, 'cancelled')}><XCircle className="mr-2 h-4 w-4" />
Cancel</DropdownMenuItem>}<DropdownMenuSeparator />
                    <DropdownMenuItem className="text-destructive" onClick={() =>
deletePurchaseOrder(po.id)}><Trash2 className="mr-2 h-4 w-4" />
Delete</DropdownMenuItem></DropdownMenuContent></DropdownMenu></TableCell>
</TableRow>))}</TableBody></Table></div>)} </div>
    <Dialog open={addOpen} onOpenChange={setAddOpen}>
      <DialogContent className="max-w-lg">
        <DialogHeader><DialogTitle>New Purchase Order</DialogTitle></DialogHeader>
        <div className="space-y-3">
          <div><Label>Vendor</Label><Input value={form.vendorName} onChange={e =>
setForm({ ...form, vendorName: e.target.value })} placeholder="Vendor name" /></div>
          <div><Label>Expected Delivery</Label><Input type="date"
value={form.expectedDate} onChange={e => setForm({ ...form, expectedDate:
e.target.value })} /></div> <div>
            <div className="flex items-center justify-between mb-
2"><Label>Items</Label><Button variant="outline" size="sm" onClick={addItem}><Plus
className="h-3 w-3 mr-1" /> Add</Button></div>
            {items.map((item, idx) => (
              <div key={idx} className="grid grid-cols-6 gap-2 mb-2">
                <Input className="col-span-3" placeholder="Description"
value={item.description} onChange={e => updateItem(idx, 'description', e.target.value)} />
                <Input type="number" placeholder="Qty" value={item.quantity} onChange={e
=> updateItem(idx, 'quantity', e.target.value)} />
                <Input type="number" placeholder="Price" value={item.unitPrice} onChange={e
=> updateItem(idx, 'unitPrice', e.target.value)} />
                <Button variant="ghost" size="icon" onClick={() => setItems(items.filter((_, i)
=> i !== idx))} disabled={items.length === 1}><Trash2 className="h-4 w-4"
/></Button></div>))} </div> <div><Label>Notes</Label><Input value={form.notes}
onChange={e => setForm({ ...form, notes: e.target.value })} /></div></div>
        <DialogFooter><Button onClick={handleAdd} disabled={!form.vendorName ||
items.every(i => !i.description)}>Create PO</Button></DialogFooter></DialogContent>
</Dialog></MainLayout>);}
```

REFERENCES:

1. Pragya Pandey , Pawan Kumar Singh , Dr. Santosh Kumar Dwivedi, “AI POWERED INVOICE PROCESSING SYSTEM”, International Journal of Research Publication and Reviews, ISSN 2582-7421, May 2025.

2. Koti Reddy Onteddu, “AI-Powered Invoice Automation in ERP Systems: Revolutionizing Accounts Payable”, Journal of Computer Science and Technology Studies ISSN: 2709-104X DOI: 10.32996/jcsts , May 2025.

3. Bryson Santos, “Intelligent Document Processing: Automating Invoice and Contract Management with AI”, Research Gate, October 2024.

4. Srinivasa Rao Gunturu, Madhavi Godbole, Hari Prasad Josyula, “FinTech-Automatic Payment Process in the ERP System”, International Journal of Computer Trends and Technology 72(1):99-103, DOI: 10.14445/22312803/IJCTT-V72I11P116, February 2024.

5. Jayesh Jhurani, “Enhancing Customer Relationship Management in ERP Systems through AI: Personalized Interactions, Predictive Modeling, and Service Automation”, International Journal of Science and Research (IJSR) 13(3): 892-897, DOI: 10.21275/SR24313021820, March 2024.

6. McGill University (Mila), Université de Montréal (Mila), MIT, Carnegie Mellon University, NYU, UC Berkeley, and the University of Toronto, “An Introduction to Vision-Language Modeling”, Research Gate, arXiv:2405.17247v1, May 2024.

7. Thomas Saout, Frederic Lardeux, Frederic Saubion, “An Overview of Data Extraction from Invoices”, IEEE Access, PP(99):1-1 DOI: 10.1109/ACCESS.2024.3360528. January 2024.

8. Jerome Blanchard, Yolande Belaid, Abdel Belaid, “Automatic Generation of a Custom Corpora for Invoice Analysis and Recognition”, 2019 International Conference on Document Analysis and Recognition Workshops (ICDARW), DOI: 10.1109/ICDARW.2019.60121, September 2019.

9. D. Lohani, A. Bela¨ıd and Y. Bela¨ıd. “An Invoice Reading System using a Graph Convolutional Network”. IWRR, Dec 2018, PERTH, Australia. 2018.

10. B. Klein, S. Agne and A. Dengel: “Results of a study on invoicereading systems in Germany”. DAS, pp. 451-462, 2004.

11. D. Nadeau and S. Sekine: “A survey of named entity recognition and classification”. Lingvisticae Investigationes, 30, pp. 3-26, 2007.

12. D. Schuster and K. Muthmann and D. Esser and A. Schill and M. Berger and C. Weidling and K. Aliyev and A. Hofmeier: “Intellix-end-user trained information extraction for document archiving”. ICDAR, 2013, pp. 101-105.

13. M. Rusinol, T. Benkhelfallah and V. Poulain d’Andecy: “Field extraction from administrative documents by incremental structural templates”. ICDAR, 2013, pp. 1100-1104.

14. H. Hamza, Y. Bela¨ıd and A. Bela¨ıd: “A case-based reasoning approach for invoice structure extraction”. ICDAR, 2007, pp.327-331.

15. A. Dengel and B. Klein: smartfix: “A requirements-driven system for document analysis and understanding”. DAS, 2002, pp. 433-444.

16. F. Cesarini, E. Francesconi, M. Gori and G. Soda: “Analysis and understanding of multi-class invoices”. ICDAR, 2003, pp. 102-114.

17. V. P. d’Andecy, E. Hartman and M. Rusinol: “Field extraction by hybrid incremental and a priori structural templates”. DAS, 2018, pp. 251-256.

18. R. B. Palm, O. Winther and F. Laws: “Cloudscan a configuration-free invoice analysis system using recurrent neural networks”. ICDAR 2017, pp. 406-413.

BOOK REFERENCES:

1. Python: "Python Crash Course" by Eric Matthes.
2. Flask: "Flask Web Development: Developing Web Applications with Python" by Miguel Grinberg.
3. MySQL: "Learning MySQL" by Robin Nixon.
4. WampServer: "WampServer: Windows Apache MySQL PHP" by David Sayre.
5. TensorFlow: "Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow" by Aurélien Géron.
6. Pandas: "Python for Data Analysis" by Wes McKinney.
7. Scikit-Learn: "Introduction to Machine Learning with Python: A Guide for Data Scientists" by Andreas C. Müller and Sarah Guido.
8. Matplotlib: "Python Data Visualization Cookbook" by Igor Milovanović.
9. NumPy: "Numerical Python: Scientific Computing and Data Science Applications with Numpy, SciPy and Matplotlib" by Robert Johansson.
10. OpenCV: "OpenCV 4 for Secret Agents" by Joseph How

WEB REFERENCES

1. Python Documentation: https://docs.python.org/
2. Flask Documentation: https://flask.palletsprojects.com/en/2.0.x/
3. MySQL Documentation: https://dev.mysql.com/doc/
4. TensorFlow Documentation: https://www.tensorflow.org/guide
5. Pandas Documentation: https://pandas.pydata.org/docs/
6. Scikit-Learn Documentation: https://scikitlearn.org/stable/documentation.html
7. Matplotlib Documentation: https://matplotlib.org/stable/contents.html
8. NumPy Documentation: https://numpy.org/doc