

BINGR.ONE CLONE — REPLIT AGENT INSTRUCTION MANUAL

Project: Movietalk (artifacts/allrated)

Target: https://bingr.one

Date: 2026-08-01

Author: Senior Engineer Analysis

⚠ CRITICAL RULES FOR THE AGENT

- 1. DO NOT change architecture (React 19, Vite, Tailwind v4, Wouter)
- 2. DO NOT remove existing features — only ADD/MODIFY
- 3. Every change must match bingr.one pixel-for-pixel
- 4. Test on mobile AND desktop before marking complete
- 5. Use EXACT color values, spacing, timing — no approximations
- 6. Preserve all existing data-testid attributes
- 7. Maintain accessibility (aria-labels, roles, focus states)

SECTION 0: PROJECT STRUCTURE (DO NOT CHANGE)

```
artifacts/allrated/src/
├─ components/
│  ├─ HeroBanner.tsx      ← MODIFY
│  ├─ TitleCard.tsx      ← MODIFY
│  ├─ Row.tsx             ← MODIFY
│  ├─ Sidebar.tsx        ← MODIFY
│  ├─ MobileHeader.tsx   ← MODIFY
│  ├─ MobileNav.tsx      ← VERIFY (already good)
│  ├─ CategoryRow.tsx    ← CREATE
│  ├─ SkeletonCard.tsx   ← CREATE
│  └─ ...
├─ pages/
│  ├─ Home.tsx           ← MODIFY
│  └─ ...
├─ index.css             ← MODIFY (add styles)
└─ App.tsx               ← VERIFY (already good)
```

SECTION 1: CRITICAL FIXES (DO FIRST — 30 MIN)

FIX 1.1 — Card Hover Glow Shadow

File: src/components/TitleCard.tsx **Line:** ~45 (className on root div) **Current:**

```
className={cn(
  'relative flex-shrink-0 cursor-pointer rounded-md overflow-hidden',
  'transition-transform duration-300 ease-out group',
```

Replace with:

```
className={cn(
  'relative flex-shrink-0 cursor-pointer rounded-md overflow-hidden',
  'transition-all duration-200 ease-out group',
  'hover:shadow-[0_0_20px_rgba(255,255,255,0.15)] hover:z-10',
```

Why: bingr.one cards glow white on hover. Current code only scales. **Verify:** Hover any poster card → should see white glow, not just scale.

FIX 1.2 — Add snap-start to Row Cards

File: src/components/Row.tsx **Lines:** Where TitleCard and NumberedTitleCard are rendered inside the scroller **Current:**

```
{!loading && titles?.map((title, i) =>
  numbered ? (
    <NumberedTitleCard key={title.id} title={title} index={i} />
  ) : (
    <TitleCard key={title.id} title={title} />
  ),
)}
```

Replace with:

```
{!loading && titles?.map((title, i) =>
  numbered ? (
    <div key={title.id} className="snap-start flex-shrink-0">
      <NumberedTitleCard title={title} index={i} />
    </div>
  ) : (
    <div key={title.id} className="snap-start flex-shrink-0">
      <TitleCard title={title} index={i} />
    </div>
  ),
)}
```

Also fix skeleton loaders (same file):

```
// Current skeleton:
<div key={i} className={`flex-shrink-0 animate-pulse ...`} />

// Replace with:
```

```
<div key={i} className={`snap-start flex-shrink-0 animate-pulse ...`} />
```

Why: Scroll-snap requires snap points on children. Currently snap has no targets. **Verify:** Scroll horizontally on any row → cards should snap into place, not free-scroll.

FIX 1.3 — Hero Banner Title Font Fix

File: src/components/HeroBanner.tsx **Line:** ~95 (h1 element) **Current:**

```
<h1 className="font-display text-3xl sm:text-4xl md:text-6xl lg:text-7xl text-white leading-[0.92]
  ↳ tracking-wider mb-4 md:mb-5 drop-shadow-2xl">
```

Replace with:

```
<h1
  className="text-white leading-[0.92] mb-4 md:mb-5 drop-shadow-2xl"
  style={{
    fontFamily: "'Bebas Neue', 'Anton', Impact, system-ui, sans-serif",
    fontSize: 'clamp(2.5rem, 5vw, 5rem)',
    letterSpacing: '0.02em',
    fontWeight: 400,
  }}
>
```

Why: bingr.one uses Bebas Neue with tight tracking. Current uses generic font-display with wide tracking. **Verify:** Hero title should look like bingr.one — tall, condensed, tight letter spacing.

FIX 1.4 — Sidebar Expanded Width

File: src/components/Sidebar.tsx **Line:** ~23 (aside className) **Current:**

```
expanded ? "w-56" : "w-20"
```

Replace with:

```
expanded ? "w-60" : "w-20"
```

Why: bingr.one expanded sidebar is exactly 240px. $w-56 = 224\text{px}$, $w-60 = 240\text{px}$. **Verify:** Hover sidebar on desktop → should expand to match bingr.one width exactly.

FIX 1.5 — Mobile Header Backdrop Blur

File: src/components/MobileHeader.tsx **Line:** ~12 (header className) **Current:**

```
className="md:hidden fixed top-0 left-0 right-0 z-50 bg-[#0f1014]/80 backdrop-blur-md ..."
```

Replace with:

```
className="md:hidden fixed top-0 left-0 right-0 z-50 bg-[#0f1014]/80 backdrop-blur-lg ..."
```

Why: bingr.one uses 16px blur on mobile header. Current is 12px (md). **Verify:** Open site on mobile → header blur should match bingr.one intensity.

FIX 1.6 — Hero Bottom Gradient Height

File: src/components/HeroBanner.tsx **Line:** ~65 (bottom gradient div) **Current:**

```
<div className="absolute bottom-0 left-0 right-0 h-48 bg-gradient-to-t from-[#0f1014] to-transparent
  ↪  z-[1]" />
```

Replace with:

```
<div className="absolute bottom-0 left-0 right-0 h-[35vh] bg-gradient-to-t from-[#0f1014]
  ↪  via-[#0f1014]/60 to-transparent z-[1]" />
```

Why: bingr.one has a much taller, smoother fade from hero to content. Current is too abrupt. **Verify:** Hero should blend smoothly into content below, no hard edge.

SECTION 2: HIGH PRIORITY FIXES (NEXT 30 MIN)

FIX 2.1 — CategoryRow snap-mandatory Fix

File: src/pages/Home.tsx **In** CategoryRow component, scroller div: **Current:**

```
className="flex overflow-x-auto gap-3 py-4 [-ms-overflow-style:none] [scrollbar-width:none]
  ↪  [&::-webkit-scrollbar]:hidden scroll-smooth snap-x"
```

Replace with:

```
className="flex overflow-x-auto gap-3 py-4 [-ms-overflow-style:none] [scrollbar-width:none]
  ↪  [&::-webkit-scrollbar]:hidden scroll-smooth snap-x snap-mandatory"
```

Also verify items have snap-start:

```
// Should already exist:
<div key={item.name} className="snap-start flex-none w-[160px] ...">
```

Why: CategoryRow missing snap-mandatory. Items already have snap-start.

FIX 2.2 — Add Page Transition Animation

File: src/App.tsx **Line:** ~82 (main element) **Current:**

```
<main className="md:pl-[80px] flex-1 mobile-content md:pb-0">
```

Replace with:

```
<main className="md:pl-[80px] flex-1 mobile-content md:pb-0 animate-slide-up">
```

File: src/index.css **Add at the END of the file:**

```

/* =====
Page Transitions — bingr.one Match
===== */

@keyframes slideUpFade {
  from { opacity: 0; transform: translateY(12px); }
  to   { opacity: 1; transform: translateY(0); }
}

@keyframes slideDownFade {
  from { opacity: 0; transform: translateY(-8px); }
  to   { opacity: 1; transform: translateY(0); }
}

.animate-slide-up {
  animation: slideUpFade 0.3s cubic-bezier(0.4, 0, 0.2, 1) forwards;
}

.animate-slide-down {
  animation: slideDownFade 0.2s cubic-bezier(0.4, 0, 0.2, 1) forwards;
}

/* Staggered children for rows */
.stagger-children > * {
  opacity: 0;
  animation: slideUpFade 0.4s cubic-bezier(0.4, 0, 0.2, 1) forwards;
}

.stagger-children > *:nth-child(1) { animation-delay: 0ms; }
.stagger-children > *:nth-child(2) { animation-delay: 50ms; }
.stagger-children > *:nth-child(3) { animation-delay: 100ms; }
.stagger-children > *:nth-child(4) { animation-delay: 150ms; }
.stagger-children > *:nth-child(5) { animation-delay: 200ms; }
.stagger-children > *:nth-child(6) { animation-delay: 250ms; }

```

Why: bingr.one pages fade in smoothly. Current app has no transitions.

FIX 2.3 — Toast Notifications on Watchlist Toggle

File: src/components/TitleCard.tsx **Add import:**

```
import { toast } from 'sonner';
```

In handleWatchlistClick: Current:

```

const handleWatchlistClick = useCallback(
  (e: React.MouseEvent) => {
    e.preventDefault();
    e.stopPropagation();
    onWatchlistToggle?.(id, mediaType);
  },

```

```
[id, mediaType, onWatchlistToggle]
);
```

Replace with:

```
const handleWatchlistClick = useCallback(
  (e: React.MouseEvent) => {
    e.preventDefault();
    e.stopPropagation();
    onWatchlistToggle?.(id, mediaType);
    toast.success(
      isInWatchlist
        ? 'Removed from My List'
        : 'Added to My List',
      { duration: 2000 }
    );
  },
  [id, mediaType, onWatchlistToggle, isInWatchlist]
);
```

Why: bingr.one shows toast confirmation on watchlist actions. Current code is silent.

FIX 2.4 — Hero Rating Star Color

File: src/components/HeroBanner.tsx **Line:** ~105 (rating span) **Current:**

```
<span className="flex items-center gap-1 text-amber-400 font-semibold">
```

Replace with:

```
<span className="flex items-center gap-1 text-[#00bb7f] font-semibold">
```

Why: bingr.one uses mint green (#00bb7f) for ratings, not amber.

FIX 2.5 — Filmstrip Active Border Color

File: src/components/HeroBanner.tsx **Line:** ~170 (filmstrip active indicator) **Current:**

```
style={{ boxShadow: 'inset 0 0 0 2.5px rgba(255,255,255,0.9)' }}
```

Replace with:

```
style={{ boxShadow: 'inset 0 0 0 2px #00bb7f' }}
```

Why: bingr.one uses mint border for active filmstrip thumb, not white.

SECTION 3: MEDIUM PRIORITY FIXES (POLISH)

FIX 3.1 — Custom Desktop Scrollbar

File: src/index.css Add at END:

```
/* =====  
Custom Scrollbar — Desktop Only  
===== */  
  
@media (min-width: 768px) {  
  ::-webkit-scrollbar {  
    width: 8px;  
    height: 8px;  
  }  
  ::-webkit-scrollbar-track {  
    background: transparent;  
  }  
  ::-webkit-scrollbar-thumb {  
    background: #ffffff1a;  
    border-radius: 4px;  
  }  
  ::-webkit-scrollbar-thumb:hover {  
    background: #ffffff40;  
  }  
  * {  
    scrollbar-width: thin;  
    scrollbar-color: #ffffff1a transparent;  
  }  
}
```

Why: bingr.one has subtle scrollbar on desktop. Current code hides it completely.

FIX 3.2 — Focus Ring Color Change

File: src/index.css Find existing:

```
button:focus-visible,  
a:focus-visible,  
input:focus-visible {  
  outline: 2px solid #f5c518;  
  outline-offset: 2px;  
}
```

Replace with:

```
button:focus-visible,  
a:focus-visible,  
input:focus-visible {  
  outline: 2px solid #00bb7f;  
  outline-offset: 2px;  
}
```

```
}
```

Why: bingr.one uses mint for focus rings, matching the brand accent.

FIX 3.3 — TitleCard Hover Scale Speed

File: src/components/TitleCard.tsx **Line:** ~45 **Current:**

```
'transition-transform duration-300 ease-out group',
```

Already fixed in FIX 1.1 (changed to duration-200). If not applied:

```
'transition-all duration-200 ease-out group',
```

Why: bingr.one hover is snappier (200ms vs 300ms).

FIX 3.4 — Row Scroll Button Width

File: src/components/Row.tsx **Lines:** Left and right scroll buttons **Current:**

```
className="... w-10 ..."
```

Replace with:

```
className="... w-12 ..."
```

Why: Easier to click, matches bingr.one proportions.

FIX 3.5 — Add Reduced Motion Support

File: src/index.css **Add at END:**

```
/* =====  
Accessibility — Reduced Motion  
===== */  
  
@media (prefers-reduced-motion: reduce) {  
  *, *::before, *::after {  
    animation-duration: 0.01ms !important;  
    animation-iteration-count: 1 !important;  
    transition-duration: 0.01ms !important;  
  }  
}
```

Why: Accessibility requirement. bingr.one respects this preference.

SECTION 4: NEW COMPONENTS TO CREATE

CREATE 4.1 — SkeletonCard Component

File: src/components/SkeletonCard.tsx

```
import { cn } from '@lib/utils';

interface SkeletonCardProps {
  className?: string;
  aspectRatio?: string;
}

export function SkeletonCard({
  className,
  aspectRatio = '2/3'
}: SkeletonCardProps) {
  return (
    <div className={cn("shrink-0 w-[110px] sm:w-[130px] md:w-[160px] lg:w-[185px]", className)}>
      <div
        className="rounded-lg bg-[#1a1c20] animate-pulse"
        style={{ aspectRatio }}
      />
      <div className="mt-2 h-3 bg-[#1a1c20] rounded animate-pulse w-3/4" />
      <div className="mt-1 h-2 bg-[#1a1c20] rounded animate-pulse w-1/2" />
    </div>
  );
}
```

CREATE 4.2 — CategoryTray Component (Optional Enhancement)

File: src/components/CategoryTray.tsx

```
import { Link } from 'wouter';
import { cn } from '@lib/utils';

interface Category {
  id: string;
  name: string;
  href: string;
}

interface CategoryTrayProps {
  categories: Category[];
  activeId?: string;
}

export function CategoryTray({ categories, activeId }: CategoryTrayProps) {
  return (
    <div className="flex overflow-x-auto snap-x snap-mandatory gap-2 px-4 md:px-8 pb-2 no-scrollbar">
      {categories.map((cat) => {
```

```

const isActive = cat.id === activeId;
return (
  <Link key={cat.id} href={cat.href}>
    <button
      className={cn(
        "snap-start shrink-0 px-4 py-1.5 rounded-full text-xs font-medium",
        "transition-all duration-200 whitespace-nowrap",
        isActive
          ? 'bg-[#00bb7f] text-[#0f1014]'
          : 'bg-[#ffffff0d] text-[#ffffffb3] hover:bg-[#ffffff1a] hover:text-white border
            ↪ border-[#ffffff0d]'
        )}
    >
      {cat.name}
    </button>
  </Link>
);
  )}}
</div>
);
}

```

SECTION 5: VERIFICATION CHECKLIST

After all fixes, verify EACH of these against bingr.one:

Desktop:

- Sidebar expands to 240px on hover
- Sidebar has left yellow bar on active item
- Content rows snap horizontally (not free-scroll)
- Cards glow white on hover + scale 1.05
- Hero title uses Bebas Neue, tight tracking
- Hero bottom fades smoothly into content
- Filmstrip active thumb has mint border
- Scrollbar visible on desktop (thin, subtle)
- Page transitions fade in smoothly
- Focus rings are mint green

Mobile:

- Mobile header has strong blur (16px)
- Bottom nav hides on scroll down, shows on scroll up
- Cards are same size as bingr.one
- Horizontal scroll works with snap
- No horizontal page scroll (overflow-x hidden)
- Safe area insets work on notched phones
- Tap highlight is transparent

Both:

- Colors match exactly (#0f1014, #16181f, #f5c518, #00bb7f)
 - Text opacity levels correct (90%, 70%, 50%, 30%, 10%)
 - Border opacity levels correct (5%, 10%, 15%, 25%)
 - All animations respect prefers-reduced-motion
 - No console errors
 - Lighthouse score > 90
-

SECTION 6: BINGR.ONE EXACT REFERENCE VALUES

Colors:

Background primary:	#0f1014
Background card:	#16181f
Background elevated:	#1a1c20
Background deep:	#111116
Text primary:	#ffffffe6 (90% white)
Text secondary:	#ffffffb3 (70% white)
Text tertiary:	#ffffff80 (50% white)
Text muted:	#ffffff4d (30% white)
Text faint:	#ffffff1a (10% white)
Border subtle:	#ffffff0d (5% white)
Border light:	#ffffff1a (10% white)
Border medium:	#ffffff26 (15% white)
Border strong:	#ffffff40 (25% white)
Accent yellow:	#f5c518
Accent mint:	#00bb7f
Accent red:	#ef4444

Spacing:

Sidebar collapsed:	80px
Sidebar expanded:	240px
Mobile nav height:	56px (h-14)
Mobile header height:	56px (h-14)
Card width mobile:	110px
Card width sm:	130px
Card width md:	160px
Card width lg:	185px
Card aspect ratio:	2/3
Gap between cards:	12px (gap-3)
Row padding left:	16px mobile / 80px desktop

Timing:

Sidebar expand:	300ms ease-out
Card hover:	200ms cubic-bezier(0.4, 0, 0.2, 1)
Page transition:	300ms cubic-bezier(0.4, 0, 0.2, 1)
Mobile nav hide:	300ms ease-out

Search overlay:	300ms
Hero auto-rotate:	7000ms (7 seconds)

Z-Index:

Sidebar:	40
Mobile nav:	50
Mobile header:	50
Search overlay:	60
Modal/dialog:	100
Toast:	200
Tooltip:	300

SECTION 7: COMMON MISTAKES TO AVOID

1. **DON'T** use !important in CSS — use specificity
2. **DON'T** change the API client or data fetching logic
3. **DON'T** remove existing test IDs
4. **DON'T** use approximate colors — use EXACT hex values
5. **DON'T** forget to test on actual mobile device (not just responsive mode)
6. **DON'T** add heavy libraries — keep bundle size low
7. **DON'T** break existing keyboard navigation
8. **DON'T** remove the no-scrollbar utility — it's needed for clean trays

SECTION 8: TROUBLESHOOTING

Problem: Cards don't snap

Cause: Missing snap-start on children OR missing snap-mandatory on parent. **Fix:** Verify both are present. Check with DevTools → Elements → Computed → scroll-snap-type.

Problem: Hover glow clipped

Cause: Parent container has overflow-hidden and no padding. **Fix:** Add py-4 (vertical padding) to scroller container so glow has room.

Problem: Hero title looks wrong

Cause: Font not loading or wrong weight/tracking. **Fix:** Verify Bebas Neue loads in Network tab. Check letter-spacing: 0.02em.

Problem: Sidebar too narrow when expanded

Cause: Using w-56 instead of w-60. **Fix:** See FIX 1.4.

Problem: Mobile header blur looks weak

Cause: Using backdrop-blur-md (12px) instead of backdrop-blur-lg (16px). **Fix:** See FIX 1.5.

END OF MANUAL

Total estimated time: 60-90 minutes

Expected result: 95%+ visual parity with bingr.one