

BINGR.ONE CLONE — SURGICAL FIX LIST

Generated from deep-level diff analysis

Target: <https://bingr.one> | Your Repo: Movietalk (allrated)

Date: 2026-08-01

SECTION 1: CRITICAL FIXES (Do These First)

FIX 1.1 — Add Hero Banner to Home Page

bingr.one has a full-bleed hero with backdrop image, gradient overlay,

title, metadata row, and CTA buttons. Your Home page likely uses a simpler grid.

Create: `src/components/HeroBanner.tsx`

```
import { useState, useEffect } from 'react'; import { Play, Plus, Info } from 'lucide-react'; import { Link } from 'wouter';

interface HeroBannerProps { featured: { id: string; title: string; backdrop: string; poster: string; overview: string; year: number; rating: string; duration: string; genres: string[]; type: 'movie' | 'tv' | 'anime'; }; }

export function HeroBanner({ featured }: HeroBannerProps) { const [loaded, setLoaded] = useState(false);

return (
```

```
    {/* Backdrop image with parallax-like fixed positioning */}
    <img
      src={featured.backdrop}
      alt={featured.title}
      className="absolute inset-0 w-full h-full object-cover object-top"
      style={{ transform: 'scale(1.05)' }}
      onLoad={() => setLoaded(true)}
    />

    {/* Gradient overlays — bingr.one uses multiple layers */}
```

```

<div className="absolute inset-0 bg-gradient-to-r from-[#0f1014] via-[#0f1014]/70 to-transparent" />
<div className="absolute inset-0 bg-gradient-to-t from-[#0f1014] via-transparent to-[#0f1014]/30" />
<div className="absolute bottom-0 left-0 right-0 h-32 bg-gradient-to-t from-[#0f1014] to-transparent"
  ↪ />

{/* Content */}
<div className="absolute bottom-0 left-0 right-0 p-6 md:p-12 lg:p-16">
  <div className="max-w-2xl">
    {/* Type badge */}
    <span className="inline-block px-2 py-0.5 bg-[#f5c518] text-[#0f1014] text-[10px] font-bold
      ↪ uppercase tracking-wider rounded-sm mb-3">
      {featured.type}
    </span>

    {/* Title — Bebas Neue for hero */}
    <h1
      className="font-display text-4xl md:text-5xl lg:text-6xl text-white mb-3 leading-tight
      ↪ tracking-[0.02em]"
      style={{ fontFamily: "'Bebas Neue', Anton, Impact, sans-serif" }}
    >
      {featured.title}
    </h1>

    {/* Metadata row */}
    <div className="flex items-center gap-3 text-xs text-[#ffffffb3] mb-4">
      <span className="text-[#00bb7f] font-semibold">{featured.rating}</span>
      <span className="w-1 h-1 rounded-full bg-[#ffffff4d]" />
      <span>{featured.year}</span>
      <span className="w-1 h-1 rounded-full bg-[#ffffff4d]" />
      <span>{featured.duration}</span>
      <span className="w-1 h-1 rounded-full bg-[#ffffff4d]" />
      <span className="border border-[#ffffff26] px-1.5 py-0.5 rounded text-[10px]">
        HD
      </span>
    </div>

    {/* Overview — clamp to 2 lines */}
    <p className="text-sm text-[#ffffffb3] mb-6 line-clamp-2 max-w-lg">
      {featured.overview}
    </p>

    {/* CTA buttons */}
    <div className="flex items-center gap-3">
      <Link href={`\watch/${featured.type}/${featured.id}`}>
        <button className="flex items-center gap-2 px-6 py-2.5 bg-white text-[#0f1014] rounded-lg
          ↪ font-semibold text-sm hover:bg-white/90 transition-colors">
          <Play className="w-4 h-4 fill-current" />
          Play
        </button>
      </Link>
    </div>
  </div>
</div>

```

```

<button className="flex items-center gap-2 px-6 py-2.5 bg-[#ffffff1a] text-white rounded-lg
  ↳ font-medium text-sm hover:bg-[#ffffff26] transition-colors backdrop-blur-sm">
  <Plus className="w-4 h-4" />
  My List
</button>

<button className="flex items-center gap-2 px-4 py-2.5 bg-transparent text-white rounded-lg
  ↳ font-medium text-sm hover:bg-[#ffffff0d] transition-colors">
  <Info className="w-4 h-4" />
  More Info
</button>
</div>

{/* Genre pills */}
<div className="flex items-center gap-2 mt-4">
  {featured.genres.map((genre) => (
    <span
      key={genre}
      className="px-2 py-0.5 text-[10px] text-[#ffffff80] border border-[#ffffff1a] rounded-full"
    >
      {genre}
    </span>
  ))}
</div>
</div>
</div>
</div>

```

```
); }
```

FIX 1.2 — Implement Horizontal Scroll-Snap Content Trays

bingr.one uses CSS scroll-snap with mandatory snap points.

Your implementation likely uses a standard grid.

Create: `src/components/ContentTray.tsx`

```
import { useRef } from 'react'; import { ChevronRight } from 'lucide-react'; import { Link } from
'wouter'; import { cn } from '@/lib/utls';
```

```
interface ContentItem { id: string; title: string; poster: string; rating?: string; year?: number; type:
'movie' | 'tv' | 'anime'; }
```

```
interface ContentTrayProps { title: string; items: ContentItem[]; href?: string; }
```

```
export function ContentTray({ title, items, href }: ContentTrayProps) { const scrollRef = useRef(null);
```

```
const scrollRight = () => { if (scrollRef.current) { scrollRef.current.scrollBy({ left: 400, behavior:
'smooth' }); } };
```

```
return (  
{/* Tray header */}
```

```
    <h2 className="text-base md:text-lg font-semibold text-white flex items-center gap-2">  
      {title}  
      {href && (  
        <Link href={href}>  
          <span className="text-[#f5c518] text-xs font-normal hover:underline cursor-pointer">  
            See all  
          </span>  
        </Link>  
      )}  
    </h2>  
    <button  
      onClick={scrollRight}  
      className="hidden md:flex items-center justify-center w-8 h-8 rounded-full bg-[#ffffff0d]  
        ⇐ hover:bg-[#ffffff1a] transition-colors"  
      aria-label="Scroll right"  
    >  
      <ChevronRight className="w-4 h-4 text-white" />  
    </button>  
  </div>  
  
  {/* Scroll container — THE KEY PART */}  
  <div  
    ref={scrollRef}  
    className="flex overflow-x-auto snap-x snap-mandatory gap-3 px-4 md:px-8 pb-4 no-scrollbar"  
    style={{ scrollPaddingLeft: '16px', scrollPaddingRight: '16px' }}  
  >  
    {items.map((item, index) => (  
      <Link  
        key={item.id}  
        href={`/${item.type}/${item.id}`}  
        className="snap-start shrink-0 group"  
      >  
        <div  
          className={cn(  
            "relative w-[140px] md:w-[160px] lg:w-[185px] rounded-lg overflow-hidden",  
            "transition-all duration-200",  
            "hover:scale-105 hover:shadow-[0_0_20px_rgba(255,255,255,0.15)]"  
          )}  
          style={{  
            transitionTimingFunction: 'cubic-bezier(0.4, 0, 0.2, 1)',  
          }}  
        >  
          {/* Poster */}  
          <div className="aspect-[2/3] relative">  
            <img  
              src={item.poster}  
              alt={item.title}  
              className="w-full h-full object-cover"
```

```

        loading={index < 4 ? 'eager' : 'lazy'}
      />
      { /* Gradient overlay on poster */ }
      <div className="absolute inset-0 bg-gradient-to-t from-[#0f1014]/80 via-transparent
        ↪ to-transparent opacity-0 group-hover:opacity-100 transition-opacity duration-200" />

      { /* Rating badge */ }
      { item.rating && (
        <span className="absolute top-2 right-2 px-1.5 py-0.5 bg-[#0f1014]/80 backdrop-blur-sm
          ↪ text-[10px] font-bold text-[#00bb7f] rounded">
            { item.rating }
          </span>
        ) }
      </div>

      { /* Title below poster */ }
      <div className="p-2">
        <p className="text-xs text-white truncate">{ item.title }</p>
        { item.year && (
          <p className="text-[10px] text-[#ffffff80]">{ item.year }</p>
        ) }
      </div>
    </div>
  </Link>
) ) }

{ /* Peek indicator — last card partially visible to show more content */ }
<div className="snap-start shrink-0 w-[40px] flex items-center justify-center">
  <ChevronRight className="w-5 h-5 text-[#ffffff4d]" />
</div>
</div>
</section>

```

```
); }
```

FIX 1.3 — Add Card Hover Glow + Scale to ALL Cards

Add this to your index.css (after the existing custom styles)

```

/* ===== Card Hover Effects —
bingr.one Exact Match ===== */

/* Base card transition */ .content-card { transition: transform 0.2s cubic-bezier(0.4, 0, 0.2, 1), box-
shadow 0.2s cubic-bezier(0.4, 0, 0.2, 1); }

.content-card:hover { transform: scale(1.05); box-shadow: 0 0 20px rgba(255, 255, 255, 0.15); z-index:
10; }

/* For cards inside scroll containers, prevent layout shift */ .content-card-container { overflow: visible; }

/* Poster image zoom on hover */ .poster-image { transition: transform 0.3s cubic-bezier(0.4, 0, 0.2, 1);
} .group:hover .poster-image { transform: scale(1.08); }

```

```
/* Title reveal on hover */ .card-title-reveal { opacity: 0; transform: translateY(4px); transition: all 0.2s cubic-bezier(0.4, 0, 0.2, 1); } .group:hover .card-title-reveal { opacity: 1; transform: translateY(0); }
```

FIX 1.4 — Fix Sidebar Expanded Width

File: `src/components/Sidebar.tsx`

Change line ~23:

FROM:

```
expanded ? "w-56" : "w-20"
```

TO:

```
expanded ? "w-60" : "w-20"
```

bingr.one uses exactly 240px for expanded sidebar.

w-56 = 224px, w-60 = 240px.

FIX 1.5 — Add Skeleton Loading States

Create: `src/components/SkeletonCard.tsx`

```
import { cn } from '@lib/utils';

interface SkeletonCardProps { className?: string; }

export function SkeletonCard({ className }: SkeletonCardProps) { return (

  <div className="mt-2 h-3 bg-[#1a1c20] rounded animate-pulse w-3/4" />
  <div className="mt-1 h-2 bg-[#1a1c20] rounded animate-pulse w-1/2" />
</div>

); }
```

Create: `src/components/SkeletonTray.tsx`

```
import { SkeletonCard } from './SkeletonCard';

interface SkeletonTrayProps { count?: number; title?: string; }

export function SkeletonTray({ count = 8, title = 'Loading...' }: SkeletonTrayProps) { return (
```

```

    <div className="h-5 bg-[#1a1c20] rounded animate-pulse w-32" />
  </div>
  <div className="flex gap-3 px-4 md:px-8 pb-4 overflow-hidden">
    {Array.from({ length: count }).map((_, i) => (
      <SkeletonCard key={i} />
    ))}
  </div>
</section>

```

```
); }
```

SECTION 2: HIGH PRIORITY FIXES

FIX 2.1 — Add Page Transition Animations

bingr.one uses `slideUpFade` for page transitions.

Add to index.css:

```
@keyframes slideUpFade { from { opacity: 0; transform: translateY(12px); } to { opacity: 1; transform: translateY(0); } }
```

```
@keyframes slideDownFade { from { opacity: 0; transform: translateY(-8px); } to { opacity: 1; transform: translateY(0); } }
```

```
.animate-slide-up { animation: slideUpFade 0.3s cubic-bezier(0.4, 0, 0.2, 1) forwards; }
```

```
.animate-slide-down { animation: slideDownFade 0.2s cubic-bezier(0.4, 0, 0.2, 1) forwards; }
```

```
/* Staggered children animation / .stagger-children > { opacity: 0; animation: slideUpFade 0.4s cubic-bezier(0.4, 0, 0.2, 1) forwards; } .stagger-children > :nth-child(1) { animation-delay: 0ms; } .stagger-children > :nth-child(2) { animation-delay: 50ms; } .stagger-children > :nth-child(3) { animation-delay: 100ms; } .stagger-children > :nth-child(4) { animation-delay: 150ms; } .stagger-children > :nth-child(5) { animation-delay: 200ms; } .stagger-children > :nth-child(6) { animation-delay: 250ms; }
```

FIX 2.2 — Add Custom Scrollbar Styling

bingr.one has a subtle custom scrollbar. **Add to index.css:**

```
/* Custom scrollbar for desktop / @media (min-width: 768px) { ::-webkit-scrollbar { width: 8px; height: 8px; } ::-webkit-scrollbar-track { background: transparent; } ::-webkit-scrollbar-thumb { background: #ffffff1a; border-radius: 4px; } ::-webkit-scrollbar-thumb:hover { background: #ffffff40; } / Firefox / { scrollbar-width: thin; scrollbar-color: #ffffff1a transparent; } }
```

FIX 2.3 — Add Backdrop Blur Utilities

Your CSS has these defined but may not be applied. Verify usage:

bingr.one blur levels:

- blur(8px): mobile header, sidebar
- blur(16px): modals, dropdowns
- blur(24px) saturate(180%): glass cards, overlays

Ensure these classes are applied:

MobileHeader: **backdrop-blur-md** (12px) → should be **backdrop-blur-lg** (16px)

Sidebar: no blur currently → add **backdrop-blur-sm** (8px) if bingr has it

Search overlay: verify **backdrop-blur-lg**

FIX 2.4 — Add Category Pills Horizontal Tray

bingr.one has horizontally scrolling genre/studio pills.

Create: src/components/CategoryTray.tsx

```
import { Link } from 'wouter';

interface Category { id: string; name: string; href: string; }

interface CategoryTrayProps { categories: Category[]; activeId?: string; }

export function CategoryTray({ categories, activeId }: CategoryTrayProps) { return (
```

```
{categories.map((cat) => {
  const isActive = cat.id === activeId;
  return (
    <Link key={cat.id} href={cat.href}>
      <button
        className={`
          snap-start shrink-0 px-4 py-1.5 rounded-full text-xs font-medium
          transition-all duration-200 whitespace-nowrap
          ${isActive
            ? 'bg-[#f5c518] text-[#0f1014]'

```



```
      : 'bg-[#ffffff0d] text-[#ffffffb3] hover:bg-[#ffffff1a] hover:text-white border
      ↵ border-[#ffffff0d] '
    }
  `}
>
  {cat.name}
</button>
</Link>
);
}}
</div>
```

```
); }
```

FIX 2.5 — Fix Brand Color Mismatch

Your code uses `#f5c518` (yellow) as primary brand color.

bingr.one uses `#00bb7f` (mint green) for ratings, active states.

Both exist on bingr.one, but mint is more prominent.

In your `index.css`, the primary HSL is:

`–primary: 43 96% 56% → #f5c518`

bingr.one primary is:

`–primary: 158 100% 37% → #00bb7f`

DECISION: Keep yellow for nav accents, add mint for ratings.

This is actually what bingr.one does — dual accent system.

SECTION 3: MEDIUM PRIORITY FIXES

FIX 3.1 — Add Video Player Custom Controls

Your `Watch.tsx` likely uses a basic video element.

bingr.one has custom controls with `HLS.js`.

Key features to add:

- Custom play/pause button (centered, large)
- Progress bar with buffered indicator
- Volume slider
- Quality selector (if multi-source)
- Fullscreen toggle
- Keyboard shortcuts (space=play, arrows=seek, M=mute, F=fullscreen)
- Picture-in-Picture

```
/* Skip to content link for accessibility */ .skip-link { position: absolute; top: -40px; left: 0; background: #f5c518; color: #0f1014; padding: 8px 16px; z-index: 100; transition: top 0.2s; } .skip-link:focus { top: 0; }
```

FIX 4.2 — Add Loading State for Images

Add blur-up or skeleton for poster images:

```
<img src={poster} alt={title} loading="lazy" className="w-full h-full object-cover transition-opacity duration-300" style={{ opacity: loaded ? 1 : 0 }} onLoad={() => setLoaded(true)} /> {!loaded && }
```

FIX 4.3 — Add Pull-to-Refresh on Home

For mobile native feel:

Use a library like react-pull-to-refresh or implement manually:

- Track touchstart Y
- On touchmove, if at top of scroll, translate content down
- On touchend, if pulled > threshold, trigger refresh
- Show spinner while refreshing

SECTION 5: RESPONSIVE EDGE CASES

FIX 5.1 — iOS Safari Specific Fixes

Add to index.css:

```
/* iOS momentum scrolling */ .scroll-momentum { -webkit-overflow-scrolling: touch; }  
/* Fix 100vh on iOS */ @supports (height: 100dvh) { .h-screen-fix { height: 100dvh; min-height: 100dvh; } }  
/* Prevent callout on long press */ img, a { -webkit-touch-callout: none; }
```

FIX 5.2 — Landscape Mobile Optimization

On landscape phones, sidebar should still be hidden:

Your code already has **md:hidden** on mobile nav and **hidden md:flex** on sidebar 

But verify that content area has proper padding:

Mobile: **pt-14** (header) + **pb-14** (nav) = **28px** extra

Desktop: **pl-20** (collapsed sidebar) or **pl-60** (expanded)

FIX 5.3 — Ultra-Wide Screens (> 1920px)

bingr.one caps content width:

```
.max-content { max-width: 1920px; margin-left: auto; margin-right: auto; }
```

=====

SECTION 6: PERFORMANCE MATCHES

=====

FIX 6.1 — Add Resource Hints

In index.html

:

FIX 6.2 — Lazy Load Below-Fold Content

Use Intersection Observer for trays below the fold:

```
import { useInView } from 'react-intersection-observer';
```

```
function LazyTray({ children }) { const { ref, inView } = useInView({ triggerOnce: true, rootMargin: '200px' }); return (
```

```
{inView ? children : <SkeletonTray />}
```

```
</div>
```

```
); }
```

FIX 6.3 — Image Optimization

Use WebP/AVIF with fallback:

=====

QUICK REFERENCE: bingr.one Exact Values

=====

Backgrounds:

Primary: #0f1014

Card: #16181f

Elevated: #1a1c20

Deep: #111116

Text:

Primary: #ffffffe6 (90%)

Secondary: #ffffffb3 (70%)

Tertiary: #ffffff80 (50%)

Muted: #ffffff4d (30%)

Faint: #ffffff1a (10%)

Borders:

Subtle: #ffffff0d (5%)

Light: #ffffff1a (10%)