```
mysql> CREATE TABLE clss(name VARCHAR (10), id INT(5));
Query OK, 0 rows affected, 1 warning (0.05 sec)

mysql> INSERT INTO clss VALUES('dj',5);
Query OK, 1 row affected (0.01 sec)

mysql> COMMIT;
Query OK, 0 rows affected (0.00 sec)

mysql> UPDATE clss SET name ='bravo' WHERE id=5 ;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> SAVEPOINT A;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO clss VALUES('balu',7);
Query OK, 1 row affected (0.02 sec)

mysql> SAVEPOINT B;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO clss VALUES('UPPAL',6);
Query OK, 1 row affected (0.01 sec)

mysql> SAVEPOINT C;
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT*FROM clss;
+-------+------+
| name  | id   |
+-------+------+
| bravo |    5 |
| balu  |    7 |
| UPPAL |    6 |
+-------+------+
3 rows in set (0.01 sec)
```

```
mysql> ROLLBACK TO B;
ERROR 1305 (42000): SAVEPOINT B does not exist
mysql> ROLLBACK TO B;
ERROR 1305 (42000): SAVEPOINT B does not exist
mysql> SELECT*FROM clss;
+-------+------+
| name  | id   |
+-------+------+
| bravo |    5 |
| balu  |    7 |
| UPPAL |    6 |
+-------+------+
3 rows in set (0.00 sec)
```