

# CN101

## Lecture 13-14 More About Strings

2

## Topics

- Basic String Operations
- String Slicing
- Testing, Searching, and Manipulating Strings

## Basic String Operations

3

- Many types of programs perform operations on strings
- In Python, many tools for examining and manipulating strings
  - Strings are sequences, so many of the tools that work with sequences work with strings

## Accessing the Individual Characters in a String

4

- To access an individual character in a string:
  - Use a `for` loop
    - Format: `for character in string:`
    - Useful when need to iterate over the whole string, such as to count the occurrences of a specific character

```
>>> name = 'Juliet'
>>> for ch in name:
>>>     print(ch)

J
u
l
i
e
t
```

1st Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 'J'

2nd Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 'u'

3rd Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 'l'

4th Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 'i'

5th Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 'e'

6th Iteration    for ch in name:  
                  print(ch)

name → 'Juliet'  
ch → 't'

5

### Program 8-1 (count\_Ts.py)

6

```
1 # This program counts the number of times
2 # the letter T (uppercase or lowercase)
3 # appears in a string.
4
5 def main():
6     # Create a variable to use to hold the count.
7     # The variable must start with 0.
8     count = 0
9
10    # Get a string from the user.
11    my_string = input('Enter a sentence: ')
12
13    # Count the Ts.
14    for ch in my_string:
15        if ch == 'T' or ch == 't':
16            count += 1
17
18    # Print the result.
19    print('The letter T appears', count, 'times.')
20
21 # Call the main function.
22 main()
```

#### Program Output (with input shown in bold)


Enter a sentence: **Today we sold twenty-two toys.** **Enter**  
The letter T appears 5 times.

## Accessing the Individual Characters in a String

7

- To access an individual character in a string:
  - Use indexing
    - Each character has an index specifying its position in the string, starting at 0
    - Format: `character = my_string[i]`

```
>>> my_string = 'Roses are red'
>>> ch = my_string[6]
>>> print(my_string)
Roses are red
>>> print(ch)
a
```



## Accessing the Individual Characters in a String (cont'd.)

8

- `IndexError` exception will occur if:
  - You try to use an index that is out of range for the string
    - Likely to happen when loop iterates beyond the end of the string
- `len(string)` function can be used to obtain the length of a string
  - Useful to prevent loops from iterating beyond the end of a string

```
>>> my_string = 'Roses are red'
>>> my_string[20]
Traceback (most recent call last):
  File "<pyshell#86>", line 1, in <module>
    my_string[20]
IndexError: string index out of range
>>> len(my_string)
13
```

## String Concatenation

9

- **Concatenation**: appending one string to the end of another string
  - Use the `+` operator to produce a string that is a combination of its operands
  - The augmented assignment operator `+=` can also be used to concatenate strings
    - The operand on the left side of the `+=` operator must be an existing variable; otherwise, an exception is raised

```
>>> first_name = 'Emily'
>>> last_name = 'Yeager'
>>> full_name = first_name + ' ' + last_name
>>> print(full_name)
Emily Yeager
```

```
>>> letters = 'abc'
>>> letters += 'def'
>>> print(letters)
abcdef
```

## Strings Are Immutable

10

- Strings are immutable
  - Once they are created, they cannot be changed
    - Concatenation doesn't actually change the existing string, but rather creates a new string and assigns the new string to the previously used variable
  - Cannot use an expression of the form `string[index] = new_character`
    - Statement of this type will raise an exception



## Strings Are Immutable (cont'd.)



11

### Program 8-2 (concatenate.py)

```
1 # This program concatenates strings.
2
3 def main():
4     name = 'Carmen'
5     print('The name is', name)
6     name = name + ' Brown'
7     print('Now the name is', name)
8
9 # Call the main function.
10 main()
```

### Program Output

```
The name is Carmen
Now the name is Carmen Brown
```



## String Slicing

12

- **Slice**: span of items taken from a sequence, known as *substring*
  - Slicing format: `string[start : end]`
    - Expression will return a string containing a copy of the characters from `start` up to, but not including, `end`
    - If `start` not specified, 0 is used for start index
    - If `end` not specified, `len(string)` is used for end index
  - Slicing expressions can include a step value and negative indexes relative to end of string

```

>>> full_name = 'Patty Lynn Smith'
>>> middle_name = full_name[6:10]
>>> print(middle_name)
Lynn
>>> first_name = full_name[:5]
>>> print(first_name)
Patty
>>> last_name = full_name[11:]
>>> print(last_name)
Smith
>>> last_name = full_name[-5:]
>>> print(last_name)
Smith
>>> my_string = full_name[:]
>>> print(my_string)
Patty Lynn Smith
>>> letters = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ'
>>> print(letters[0:26:2])
ACEGIKMOQSUYW
>>> print(letters[::2])
ACEGIKMOQSUYW
>>> print(letters[::-1])
ZYXWVUTSRQPONMLKJIHGFEDCBA

```

13

## Testing, Searching, and Manipulating Strings

14

- You can use the `in` operator to determine whether one string is contained in another string
  - General format: `string1 in string2`
    - `string1` and `string2` can be string literals or variables referencing strings
- Similarly you can use the `not in` operator to determine whether one string is not contained in another string

```

text = 'Four score and seven years ago'
if 'seven' in text:
    print('The string "seven" was found.')
else:
    print('The string "seven" was not found.')

```

## String Methods

15

- Strings in Python have many types of methods, divided into different types of operations
  - General format:
 

```
mystring.method(arguments)
```
- Some methods test a string for specific characteristics
  - Generally Boolean methods, that return `True` if a condition exists, and `False` otherwise

## String Methods (cont'd.)

16

| Method                 | Description  |
|------------------------|--|
| <code>isalnum()</code> | Returns true if the string contains only alphabetic letters or digits and is at least one character in length. Returns false otherwise.  |
| <code>isalpha()</code> | Returns true if the string contains only alphabetic letters and is at least one character in length. Returns false otherwise.  |
| <code>isdigit()</code> | Returns true if the string contains only numeric digits and is at least one character in length. Returns false otherwise.  |
| <code>islower()</code> | Returns true if all of the alphabetic letters in the string are lowercase, and the string contains at least one alphabetic letter. Returns false otherwise.  |
| <code>isspace()</code> | Returns true if the string contains only whitespace characters and is at least one character in length. Returns false otherwise. (Whitespace characters are spaces, newlines ( <code>\n</code> ), and tabs ( <code>\t</code> )). |
| <code>isupper()</code> | Returns true if all of the alphabetic letters in the string are uppercase, and the string contains at least one alphabetic letter. Returns false otherwise.  |

### Program 8-5 (string\_test.py)

17

```

1 # This program demonstrates several string testing methods.
2
3 def main():
4     # Get a string from the user.
5     user_string = input('Enter a string: ')
6
7     print('This is what I found about that string:')
8
9     # Test the string.
10    if user_string.isalnum():
11        print('The string is alphanumeric.')
12    if user_string.isdigit():
13        print('The string contains only digits.')
14    if user_string.isalpha():
15        print('The string contains only alphabetic characters.')
16    if user_string.isspace():
17        print('The string contains only whitespace characters.')
18    if user_string.islower():
19        print('The letters in the string are all lowercase.')
20    if user_string.isupper():
21        print('The letters in the string are all uppercase.')
22
23 # Call the string.
24 main()

```

### Program Output (with input shown in bold)

```

Enter a string: abc Enter
This is what I found about that string:
The string is alphanumeric.
The string contains only alphabetic characters.
The letters in the string are all lowercase.

```

### Program Output (with input shown in bold)

```

Enter a string: 123 Enter
This is what I found about that string:
The string is alphanumeric.
The string contains only digits.

```

### Program Output (with input shown in bold)

```

Enter a string: 123ABC Enter
This is what I found about that string:
The string is alphanumeric.
The letters in the string are all uppercase.

```

18

## String Methods (cont'd.)

- Some methods return a copy of the string, to which modifications have been made
  - Simulate strings as mutable objects
- String comparisons are case-sensitive
  - Uppercase characters are distinguished from lowercase characters
  - `lower` and `upper` methods can be used for making case-insensitive string comparisons

| Method                    | Description   |
|---------------------------|---|
| <code>lower()</code>      | Returns a copy of the string with all alphabetic letters converted to lowercase. Any character that is already lowercase, or is not an alphabetic letter, is unchanged.   |
| <code>lstrip()</code>     | Returns a copy of the string with all leading whitespace characters removed. Leading whitespace characters are spaces, newlines ( <code>\n</code> ), and tabs ( <code>\t</code> ) that appear at the beginning of the string. |
| <code>lstrip(char)</code> | The <i>char</i> argument is a string containing a character. Returns a copy of the string with all instances of <i>char</i> that appear at the beginning of the string removed.   |
| <code>rstrip()</code>     | Returns a copy of the string with all trailing whitespace characters removed. Trailing whitespace characters are spaces, newlines ( <code>\n</code> ), and tabs ( <code>\t</code> ) that appear at the end of the string.     |
| <code>rstrip(char)</code> | The <i>char</i> argument is a string containing a character. The method returns a copy of the string with all instances of <i>char</i> that appear at the end of the string removed.  |
| <code>strip()</code>      | Returns a copy of the string with all leading and trailing whitespace characters removed.   |
| <code>strip(char)</code>  | Returns a copy of the string with all instances of <i>char</i> that appear at the beginning and the end of the string removed.  |
| <code>upper()</code>      | Returns a copy of the string with all alphabetic letters converted to uppercase. Any character that is already uppercase, or is not an alphabetic letter, is unchanged.   |

```
>>> letters = 'WXYZ'
>>> print(letters, letters.lower())
WXYZ wxyz
>>> letters = 'WXYZ'
>>> print(letters.lower())
wxyz
>>> print(letters)
WXYZ
>>> letters = 'abcd'
>>> print(letters.upper())
ABCD

>>> letters = ' middle '
>>> letters.strip()
'middle'
>>> letters.rstrip()
' middle'
>>> letters.lstrip()
'middle '
>>> letters = 'mmidleee'
>>> letters.strip('m')
'idlee'
>>> letters.lstrip('m')
'idlee'
>>> letters.rstrip('e')
'mmmidl'
>>> letters.rstrip('e').lstrip('m')
'idl'
```

## String Methods (cont'd.)

- Programs commonly need to search for substrings
- Several methods to accomplish this:
  - `endswith(substring)`: checks if the string ends with *substring*
    - Returns `True` or `False`
  - `startswith(substring)`: checks if the string starts with *substring*
    - Returns `True` or `False`

```
filename = input('Enter the filename: ')
if filename.endswith('.txt'):
    print('That is the name of a text file.')
elif filename.endswith('.py'):
    print('That is the name of a Python source file.')
elif filename.endswith('.doc'):
    print('That is the name of a word processing document.')
else:
    print('Unknown file type.')
```

## String Methods (cont'd.)

- Several methods to accomplish this (cont'd):
  - `find(substring)`: searches for *substring* within the string
    - Returns lowest index of the substring, or if the substring is not contained in the string, returns -1
  - `replace(substring, new_string)`:
    - Returns a copy of the string where every occurrence of *substring* is replaced with *new\_string*

```
string = 'Four score and seven years ago'
position = string.find('seven')
if position != -1:
    print('The word "seven" was found at index', position)
else:
    print('The word "seven" was not found.')
```

This code will display

The word "seven" was found at index 15

```
string = 'Four score and seven years ago'
new_string = string.replace('years', 'days')
print(new_string)
```

This code will display

Four score and seven days ago

26

## String Methods (cont'd.)

| Method                             | Description  |
|------------------------------------|--|
| <code>endswith(substring)</code>   | The <i>substring</i> argument is a string. The method returns true if the string ends with <i>substring</i> .  |
| <code>find(substring)</code>       | The <i>substring</i> argument is a string. The method returns the lowest index in the string where <i>substring</i> is found. If <i>substring</i> is not found, the method returns -1. |
| <code>replace(old, new)</code>     | The <i>old</i> and <i>new</i> arguments are both strings. The method returns a copy of the string with all instances of <i>old</i> replaced by <i>new</i> .                            |
| <code>startswith(substring)</code> | The <i>substring</i> argument is a string. The method returns true if the string starts with <i>substring</i> .  |

27

## The Repetition Operator

- **Repetition operator:** makes multiple copies of a string and joins them together
  - The \* symbol is a repetition operator when applied to a string and an integer
    - String is left operand; number is right
  - General format: `string_to_copy * n`
  - Variable references a new string which contains multiple copies of the original string

```
>>> my_string = 'w' * 5
>>> print(my_string)
wwwww
>>> print('Hello' * 5)
HelloHelloHelloHelloHello
```

28

**Program 8-8** (repetition\_operator.py)

```

1 # This program demonstrates the repetition operator. Z
2 ZZ
3
4 def main(): ZZZ
5     # Print nine rows increasing in length. ZZZZ
6     for count in range(1, 10): ZZZZZ
7         print('Z' * count) ZZZZZZ
8
9     # Print nine rows decreasing in length. ZZZZZZZZ
10    for count in range(8, 0, -1): ZZZZZZZZZ
11        print('Z' * count) ZZZZZZZZZ
12
13 # Call the main function. ZZZZZZZZ
14 main() ZZZZZZZ

```

## Program Output

Z  
ZZ  
ZZZ  
ZZZZ  
ZZZZZ  
ZZZZZZ  
ZZZZZZZ  
ZZZZZZZZ  
ZZZZZZZZZ  
ZZZZZZZZZ  
ZZZZZZZZZ  
ZZZZZZZ  
ZZZZZZ  
ZZZZZ  
ZZZZ  
ZZZ  
ZZ  
Z

29

## Splitting a String

- split method: returns a list containing the words in the string
  - By default, uses space as separator
  - Can specify a different separator by passing it as an argument to the `split` method

```
>>> date_string = '11/26/2018'
>>> date_list = date_string.split('/')
>>> print(date_list)
['11', '26', '2018']
```

30

### Program 8-9 (string\_split.py)

```
1 # This program demonstrates the split method.
2
3 def main():
4     # Create a string with multiple words.
5     my_string = 'One two three four'
6
7     # Split the string.
8     word_list = my_string.split()
9
10    # Print the list of words.
11    print(word_list)
12
13 # Call the main function.
14 main()
```

### Program Output

```
['One', 'two', 'three', 'four']
```

**Program 8-10** (split\_date.py)

31

```
1 # This program calls the split method, using the
2 # '/' character as a separator.
3
4 def main():
5     # Create a string with a date.
6     date_string = '11/26/2018'
7
8     # Split the date.
9     date_list = date_string.split('/')
10
11     # Display each piece of the date.
12     print('Month:', date_list[0])
13     print('Day:', date_list[1])
14     print('Year:', date_list[2])
15
16 # Call the main function.
17 main()
```

**Program Output**

```
Month: 11
Day: 26
Year: 2018
```

32

## Summary

- This chapter covered:
  - String operations, including:
    - Methods for iterating over strings
    - Repetition and concatenation operators
    - Strings as immutable objects
    - Slicing strings and testing strings
    - String methods
    - Splitting a string