

# ORACLES AND CHOICE SEQUENCES FOR TYPE-THEORETIC PRAGMATICS

---

Jon Sterling

October 8, 2015

joint work with Darryl McAdams

## INTRODUCTION

---



[[*A woman walked in.*]]



[[*A woman walked in.*]]

▽

( $\Sigma p \in \textit{Woman}$ )

[[*A woman walked in.*]]

$\nabla$

$(\Sigma p \in \textit{Woman}) \textit{WalkedIn}(p)$

[[*She sat down*]]



[[*She sat down*]]

▽

*SatDown*(???)



[[*A woman walked in. She sat down*]]



[[*A woman walked in. She sat down*]]

$\nabla$

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p))$

[[A woman walked in. She sat down]]

▽

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p)) \text{SatDown}(???)$

[[A woman walked in. She sat down]]

▽

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p)) \text{SatDown}(\pi_1(x))$

## THE “DONKEY SENTENCE”

[[*Every farmer who owns a donkey beats it.*]]

$\nabla$

$(\Pi p \in (\Sigma x \in \textit{Farmer}) (\Sigma y \in \textit{Donkey}) \textit{Owns}(x; y))$

# THE “DONKEY SENTENCE”

[[*Every farmer who owns a donkey beats it.*]]

▽

$(\Pi p \in (\Sigma x \in \text{Farmer}) (\Sigma y \in \text{Donkey}) \text{Owns}(x; y)) \text{Beats}(\text{???}; \text{???})$

## THE “DONKEY SENTENCE”

[[Every farmer who owns a donkey beats it.]]

$\nabla$

$(\Pi p \in (\Sigma x \in \text{Farmer}) (\Sigma y \in \text{Donkey}) \text{Owns}(x; y)) \text{Beats}(\pi_1(p); \pi_1(\pi_2(p)))$

## TWO THINGS TO DEAL WITH



## TWO THINGS TO DEAL WITH

- terms for presuppositions

## TWO THINGS TO DEAL WITH

- terms for presuppositions
- resolution of presuppositions

## TWO THINGS TO DEAL WITH

- terms for presuppositions
- resolution of presuppositions

## TWO THINGS TO DEAL WITH

- terms for presuppositions (this talk)
- resolution of presuppositions

## THE **require** ORACLE: STATICS

---



**require** : (0; 1)

(operator)

**require**  $x : A$  **in**  $N \stackrel{\text{def}}{=} \textbf{require}(A; x.N)$

(notation)

**require** : (0; 1)

(operator)

**require**  $x : A$  **in**  $N \stackrel{\text{def}}{=} \text{require}(A; x.N)$

(notation)

$$\frac{\Gamma \vdash A \text{ type} \quad \Gamma, x : A \vdash N \in B}{\Gamma \vdash \text{require } x : A \text{ in } N \in B}$$

(require)



*[[A woman walked in. She sat down]]*

$\nabla$

*$(\Sigma x \in (\Sigma p \in Woman) WalkedIn(p)) SatDown(???)$*

[[A woman walked in. She sat down]]

▽

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p))$  **require**  $y : \text{Woman}$  **in**  $\text{SatDown}(y)$

The meaning of a sentence is a logical proposition.

~~The meaning of a sentence is a logical proposition.~~

~~The meaning of a sentence is a logical proposition.~~

The meaning of a sentence is a type-theoretic expression which may evaluate to a canonical proposition.

~~The meaning of a sentence is a logical proposition.~~

The meaning of a sentence is a type-theoretic expression which may evaluate to a canonical proposition.

~~The meaning of a sentence is a logical proposition.~~

The meaning of a sentence is a type-theoretic expression which may evaluate to a canonical proposition.

What we want:

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p))$  **require**  $y : \text{Woman}$  **in**  $\text{SatDown}(y)$

$\sim$

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p)) \pi_1(x)$

~~The meaning of a sentence is a logical proposition.~~

The meaning of a sentence is a type-theoretic expression which may evaluate to a canonical proposition.

What we want:

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p))$  **require**  $y : \text{Woman}$  **in**  $\text{SatDown}(y)$

$\sim$

$(\Sigma x \in (\Sigma p \in \text{Woman}) \text{WalkedIn}(p)) \pi_1(x)$

where  $M \sim N \stackrel{\text{def}}{=} (M \leq N) \wedge (N \leq M)$



# EVERY GRAMMATICAL SENTENCE HAS A MEANING

## EVERY GRAMMATICAL SENTENCE HAS A MEANING

...but only some of them denote propositions (types)!

$$\frac{M \in A \quad [M/x] N \Downarrow N'}{\text{require } x : A \text{ in } N \Downarrow N'} \quad (??)$$

$$\frac{M \in A \quad [M/x] N \Downarrow N'}{\text{require } x : A \text{ in } N \Downarrow N'} \quad (??)$$

Can the above be made precise?

$$\frac{M \in A \quad [M/x] N \Downarrow N'}{\text{require } x : A \text{ in } N \Downarrow N'} \quad (??)$$

Can the above be made precise? There are two problems:

$$\frac{M \in A \quad [M/x] N \Downarrow N'}{\text{require } x : A \text{ in } N \Downarrow N'} \quad (??)$$

Can the above be made precise? There are two problems:

1. impredicativity

$$\frac{M \in A \quad [M/x] N \Downarrow N'}{\text{require } x : A \text{ in } N \Downarrow N'} \quad (??)$$

Can the above be made precise? There are two problems:

1. impredicativity
2. non-determinism

(HOLD THAT THOUGHT)



## A POSITIVE EXAMPLE

[[ *The President ran a marathon* ]]



[[ *The President ran a marathon* ]]

▽

**require**  $x : \textit{President}$  **in**  $(\Sigma y \in \textit{Marathon}) \textit{Ran}(x; y)$

## A POSITIVE EXAMPLE

**require**  $x : \textit{President}$  **in**  $(\Sigma y \in \textit{Marathon}) \textit{Ran}(x; y)$

**require**  $x : \textit{President}$  **in**  $(\Sigma y \in \textit{Marathon}) \textit{Ran}(x; y)$

$\Downarrow$

$(\Sigma y \in \textit{Marathon}) \textit{Ran}(\textit{Obama}; y)$

## A NEGATIVE EXAMPLE

[[ *The unicorn ran a marathon* ]]





[[ *The unicorn ran a marathon* ]]

∇

**require**  $x : \textit{Unicorn}$  **in**  $(\Sigma y \in \textit{Marathon}) \textit{Ran}(x; y)$

[[ *The unicorn ran a marathon* ]]

$\nabla$

**require**  $x : \textit{Unicorn}$  **in**  $(\Sigma y \in \textit{Marathon}) \textit{Ran}(x; y)$

(not a proposition)

IS require COMPUTATIONALLY EFFECTIVE?

Yes, but we need two things:

Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge

Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge
2. non-determinism must be eliminated

Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge (via forcing)
2. non-determinism must be eliminated

Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge (via forcing)
2. non-determinism must be eliminated

$$w \Vdash \mathcal{I}$$



Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge (via forcing)
2. non-determinism must be eliminated (via choice sequences)

$$w \Vdash \mathcal{I}$$

Yes, but we need two things:

1. judgments shall be local / sensitive to knowledge (via forcing)
2. non-determinism must be eliminated (via choice sequences)

$$\boxed{\alpha \Vdash_w \mathcal{I}}$$

## THE CREATING SUBJECT

---



All mathematics is a mental construction performed by an idealized subject, subject to the following observations about knowledge:

All mathematics is a mental construction performed by an idealized subject, **subject to the following observations about knowledge:**

All mathematics is a mental construction performed by an idealized subject, subject to the following observations about knowledge:

1. experiences are never forgotten (monotonicity, functoriality)

All mathematics is a mental construction performed by an idealized subject, subject to the following observations about knowledge:

1. experiences are never forgotten (monotonicity, functoriality)
2. at a point in time, the subject knows whether or not it has experienced a judgment (decidability)



All mathematics is a mental construction performed by an idealized subject, **subject to the following observations about knowledge**:

1. experiences are never forgotten (**monotonicity, functoriality**)
2. at a point in time, the subject knows whether or not it has experienced a judgment (**decidability**)

## Corollary

*The meaning of a judgment  $\mathcal{J}$  must be explained in terms of its forcing condition,  $w \Vdash \mathcal{J}$ , for any stage/world  $w$ .*

...

2. at a point in time, the subject knows whether or not it has experienced a judgment (decidability)

...

2. at a point in time, the subject knows whether or not it has experienced a judgment (decidability)

### Remark

*Contra Dummett, I by no means take the above as requiring that the following shall be true in a constructive metatheory, divorced from time:*

$$\forall w. \forall \mathcal{J}. \llbracket w \Vdash \mathcal{J} \rrbracket \vee \neg \llbracket w \Vdash \mathcal{J} \rrbracket \quad (\text{Dummett's infelicity})$$

*The above is impossible in a Beth model.*



logical consequence  $\Rightarrow$  semantic consequence

*Brouwer?, Martin-Löf, Sundholm*  $\Rightarrow$  *Brouwer?, Heyting, Allen, Zeilberger*

logical consequence  $\Rightarrow$  semantic consequence

*Brouwer?, Martin-Löf, Sundholm  $\Rightarrow$  Brouwer?, Heyting, Allen, Zeilberger*

proof conditions  $\Rightarrow$  assertion conditions

*Martin-Löf, Sundholm  $\Rightarrow$  Heyting, Van Atten*

logical consequence  $\Rightarrow$  semantic consequence

*Brouwer?, Martin-Löf, Sundholm  $\Rightarrow$  Brouwer?, Heyting, Allen, Zeilberger*

proof conditions  $\Rightarrow$  assertion conditions

*Martin-Löf, Sundholm  $\Rightarrow$  Heyting, Van Atten*

global meaning explanation  $\Rightarrow$  local meaning explanation

*Husserl, Dummett, Martin-Löf  $\Rightarrow$  Brouwer?, Beth, Kripke,  
Grothendieck, Lawvere, Joyal*

assertion acts (judgments) are intensional (local)



assertion acts (judgments) are intensional (local)

$$|_x \mathcal{J}(x)$$

(general judgment)

assertion acts (judgments) are intensional (local)

$|_x \mathcal{I}(x)$

(general judgment)

$\mathcal{I}_2 (\mathcal{I}_1)$

(hypothetical judgment)

assertion acts (judgments) are intensional (local)

$|_x \mathcal{I}(x)$

(general judgment)

$\mathcal{I}_2 (\mathcal{I}_1)$

(hypothetical judgment)

$M \Downarrow N$

(evaluation)

assertion acts (judgments) are intensional (local)

$ _x \mathcal{I}(x)$	(general judgment)
$\mathcal{I}_2 (\mathcal{I}_1)$	(hypothetical judgment)
$M \Downarrow N$	(evaluation)
$A$ <i>type</i>	(typehood)

assertion acts (judgments) are intensional (local)

$ _x \mathcal{I}(x)$	(general judgment)
$\mathcal{I}_2 (\mathcal{I}_1)$	(hypothetical judgment)
$M \Downarrow N$	(evaluation)
$A \text{ type}$	(typehood)
$A \text{ verif}$	(verification)

assertion acts (judgments) are intensional (local)

$ _x \mathcal{I}(x)$	(general judgment)
$\mathcal{I}_2 (\mathcal{I}_1)$	(hypothetical judgment)
$M \Downarrow N$	(evaluation)
$A \text{ type}$	(typehood)
$A \text{ verif}$	(verification)
$A \text{ true}$	(truth)

assertion acts (judgments) are intensional (local)

$ _x \mathcal{I}(x)$	(general judgment)
$\mathcal{I}_2 (\mathcal{I}_1)$	(hypothetical judgment)
$M \Downarrow N$	(evaluation)
$A \text{ type}$	(typehood)
$A \text{ verif}$	(verification)
$A \text{ true}$	(truth)
$M = N \in A$	(membership)

assertion acts (judgments) are intensional (local)

$w \Vdash  _x \mathcal{J}(x)$	(general judgment)
$w \Vdash \mathcal{J}_2 (\mathcal{J}_1)$	(hypothetical judgment)
$w \Vdash M \Downarrow N$	(evaluation)
$w \Vdash A \text{ type}$	(typehood)
$w \Vdash A \text{ verif}$	(verification)
$w \Vdash A \text{ true}$	(truth)
$w \Vdash M = N \in A$	(membership)



$w \Vdash |_x \mathcal{I}(x)$

(general judgment)

$w \Vdash \mathcal{I}_2 (\mathcal{I}_1)$

(hypothetical judgment)

$$w \Vdash |_x \mathcal{I}(x) \quad \Longleftrightarrow \quad \dots$$

$$w \Vdash \mathcal{I}_2 (\mathcal{I}_1) \quad \Longleftrightarrow \quad \dots$$

$$w \Vdash |_x \mathcal{I}(x) \iff \forall u \succeq w. \forall x \in \mathcal{D}_u. u \Vdash \mathcal{I}(x)$$

$$w \Vdash \mathcal{I}_2 (\mathcal{I}_1) \iff \forall u \succeq w. u \Vdash \mathcal{I}_1 \Rightarrow u \Vdash \mathcal{I}_2$$

$$\begin{aligned}
 w \Vdash |_x \mathcal{I}(x) &\iff \forall u \geq w. \forall x \in \mathcal{D}_u. u \Vdash \mathcal{I}(x) \\
 w \Vdash \mathcal{I}_2 (\mathcal{I}_1) &\iff \forall u \geq w. u \Vdash \mathcal{I}_1 \Rightarrow u \Vdash \mathcal{I}_2
 \end{aligned}$$

where  $\mathcal{D}_w$  is the species of constructions that have been effected by stage  $w$

The meaning of a proposition/type is an intensional (world-indexed) specification of verification acts, i.e. a local meaning explanation for  $w \Vdash P \text{ } \textit{verif}$  (and its synthesis).

The meaning of a proposition/type is an intensional (world-indexed) specification of verification acts, i.e. a local meaning explanation for  $w \Vdash P \text{ } \textit{verif}$  (and its synthesis).

For a type  $A$ , implicit in the explanation of  $w \Vdash P \text{ } \textit{verif}$  is a PER  $\mathcal{V}[[A]]_w \subseteq \mathcal{D}_w \times \mathcal{D}_w$  whose members **reflect** the computational content of verification acts.

Truth (**justification**) consists in recognizing the effectiveness of a procedure for **verification**.

Truth (**justification**) consists in recognizing the effectiveness of a procedure for **verification**.

In the model, this corresponds to the inevitability of verification (i.e. a bar, in which verification occurs at all nodes):

$$w \Vdash A \text{ true} \iff \exists \mathfrak{B} \text{ bars } w. \forall u \in \mathfrak{B}. u \Vdash A \text{ verif} \quad (\text{due to Dummett})$$



The analytic judgments of type theory are reflections on mathematical activity.

The analytic judgments of type theory are reflections on mathematical activity.

1. **Canonical membership** reflects **verification**

$$\mathcal{V}[[A]]_w(M, N) \bowtie w \Vdash A \text{ verif}$$

The analytic judgments of type theory are reflections on mathematical activity.

1. **Canonical membership** reflects **verification**
2. **Membership** reflects **justification**

$$w \Vdash M = N \in A \not\bowtie w \Vdash A \text{ true}$$

The analytic judgments of type theory are reflections on mathematical activity.

1. **Canonical membership** reflects **verification**
2. **Membership** reflects **justification**
3. **Computation** reflects **the recognition of a bar**

$$w \Vdash M = N \in A \not\bowtie w \Vdash A \text{ true}$$

The analytic judgments of type theory are reflections on mathematical activity.

1. **Canonical membership** reflects **verification**
2. **Membership** reflects **justification**
3. **Computation** reflects **the recognition of a bar**

$$\wedge \left\{ \begin{array}{l} w \Vdash M \Downarrow M' \\ w \Vdash N \Downarrow N' \\ w \Vdash \mathcal{Z} \llbracket A \rrbracket_w (M', N') \end{array} \right\} \bowtie \exists \mathcal{B} \text{ bars } w. \forall u \in \mathcal{B}. u \Vdash A \text{ } \textit{verif}$$

## THE require ORACLE: DYNAMICS

---

$$\frac{\overline{\mathfrak{S}(\langle \rangle)}}{\mathfrak{S}(\vec{u})} \quad \frac{\mathfrak{S}(\vec{u}) \quad |_n \rho(n) < n \quad (n \in \mathbb{N}^+)}{\mathfrak{S}(\vec{u} \sim \rho)} \quad (\text{spread law})$$

$$\frac{\alpha \Vdash_t A \Downarrow A' \quad |\mathcal{A}_{A'}(t)| = \ell \quad \text{hd}(\alpha)(\ell) = j \quad \text{tl}(\alpha) \Vdash_t [\mathcal{A}_{A'}(j)/x] N \Downarrow N'}{\alpha \Vdash_t \text{require } x : A \text{ in } N \Downarrow N'} \quad (\text{for } \alpha \in \mathfrak{S})$$

QUESTIONS?