

GROUND PENETRATING RADAR (GPR)

NJJ-200K



SPECIFICATION

Method	:	Electromagnetic wave radar method
Frequency band	:	700MHz to 3500MHz (center frequency: 2100MHz)
Objects to be explored	:	Reinforcing bars, buried pipes (iron pipes, PVC pipes, CD pipes, etc.), cavities, junkers, etc
Measurement depth	:	5 to 450mm (for concrete dielectric constant 6.2, rebar diameter 6 mm, and listed rebar)
Depth display range	:	Display range setting "shallow, shallow wide: 0 to 147mm", "standard, standard wide: 0 to 299mm", "deep, deep wide: 0 to 602mm" (relative permittivity setting: 8.0)
Measurement depth resolution	:	Shallow mode/standard mode: 1mm, deep mode: 2mm
Horizontal resolution	:	Objects under 75mm depth: 75mm Objects at 75mm depth: Interval greater than depth. *Actual measurement value for standard concrete (depth: rebar clearance = 1: 0.2 Reinforcement with a rebar clearance of 15mm can be distinguished at a depth of 75mm. At a depth of 175 mm, it is possible to distinguish reinforcing bars with a gap of to distinguish reinforcing bars with a gap of 40 mm.
Horizontal distance resolution	:	2.5mm
Display mode	:	B mode (vertical cross section), BA mode (vertical cross section, reflection waveform display),

		C mode (3D data planar image)
Image processing	:	During scanning: real-time automatic surface wave processing, real-time manual subtraction processing, shallow filter, back processing (average + automatic sensitivity fixed + automatic sensitivity, average, OFF) During non-scanning: fixed surface wave processing, user surface wave processing, subtraction processing, manual surface wave processing, average wave processing, peak processing, original image reproduction processing, automatic sensitivity adjustment.
Display screen	:	Smartphone, tablet PC
Relative permittivity setting range	:	2.0 to 20.0, 0.1 steps
Maximum scanning speed	:	Approx. 80cm/s with overspeed buzzer (in search mode setting "U double speed")
Control functions	:	Up to 297 drawing markers (99 points x 3 groups), battery capacity display, screen vertical/horizontal switching display, rebar automatic detection function, rebar detection automatic detection function, rebar detection assist function
Data save function	:	Saves data in the built-in memory of smartphones and tablet PCs. Approximately 150 lines of data can be saved when using a memory capacity of 2GByte (when saving 20m exploration data in binary format)
Operating temperature range	:	0 to 50°C (excluding smartphones)
Power	:	Dedicated battery
Continuous use time	:	7 hours (when the battery is fully charged, in the case of our recommended smartphone)
Dust-proof and drip-proof structure	:	IP54 category 2
Supported OS	:	Android™4.2
Dimensions		With handle attached: 149±2.5(W) x 207±2.5(D) x 134.5±2.5(H)m (including wheels), with handle removed: 149±2.5(W) x 207±2.5(D) x 74.5 ±2.5(H)m (including wheels)
Weight	:	Approx. 1kg (including battery, excluding smartphone)

