This PDF was created with https://tianfei.chat , free download: https://tianfei.chat/article/one-click-webpage-to-pdf-tools/?from=saved_pdf_file
From: http://118.185.187.137/moodle/mod/quiz/review.php?attempt=354929&cmid=3319

Problem 1: Finding Complexit...
Problem 2: Finding Complexit...
Problem 3: Finding Complexit...
Problem 4: Finding Complexit...
Problem 5: Finding Complexit...
Greedy Algorithms
1-G-Coin Problem
2-G-Cookies Problem
3-G-Burger Problem
4-G-Array Sum max problem
5-G-Product of Array element...
Divide and Conquer
1-Number of Zeros in a Given ...
2-Majority Element
3-Finding Floor Value
4-Two Elements sum to x

3-G-Burger Problem

Started on	Monday, 24 August 2026, 2:12 PM
State	Finished
Completed on	Monday, 31 August 2026, 11:21 AM
Time taken	6 days 21 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00 Flag question

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a dist
If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For e
burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1$
But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum
he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the

Input Format

First Line contains the number of burgers
Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    return (*(int *)b - *(int *)a);  // Descending order
}

int main() {
    int n;
    scanf("%d", &n);

    int calories[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &calories[i]);
    }

    // Greedy: eat burgers in decreasing order of calories
    qsort(calories, n, sizeof(int), compare);

    long long total = 0;
    long long power = 1;  // 3^0

    for (int i = 0; i < n; i++) {
        total += calories[i] * power;
        power *= n;
    }

    printf("%lld\n", total);

    return 0;
}
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

Back to Course

WEBxPDF
Converting your page to PDF...