

### ESL-DDSK-S5-11W-12750

Page 1 of 4

### **Key Features & Benefits:**

- •5CCT Field Selectable
- Compatible with 3" and 4" J Boxes
- Wet Location Rated
- •120 VAC Triac Dimmable
- •T24 Compliant
- Easy Surface Mount Installation
- Optional Trim Kits\*

#### **Product Specifications:**

Wattage: 11 Watts Selectable Kelvin:

2700K-3000K-3500K-4000K-5000K Lumen Output: Up to 792 Lumens

Efficacy: Up to 70 lm/W

Input Voltage: 120 VAC CRI: >90

Operating Temperature: -4°F to 104°F Operational Lifetime: 50,000 hrs Dimensions: 5.6" x 5.6" x H 1.18"

Project: Date: Catalog #: Notes:



















### **Ordering Guide:**













| - | GENERATION         |
|---|--------------------|
| _ | 1                  |
|   | (1) 1st Generation |







VOLTAGE



| FIELD INSTALLED ACCESSORIES |   |
|-----------------------------|---|
| ESL-DDSK-EMBAT              | Replacement battery for EMG models only     |
| TRIM KITS                   |   |
| ESL-DDSK1-R5-Tff            | 5" DDSK field installable round trim kit*   |
| ESL-DDSK1-S5-Tff            | 5" DDSK field installable square trim kit*  |
| ESL-DDSK1-R7-Tff            | 7" DDSK field installable round trim kit*   |
| ESL-DDSK1-S7-Tff            | 7" DDSK field installable square trim kit*  |
| ESL-DDSK1-R9-Tff            | 9" DDSK field installable round trim kit*   |
| ESL-DDSK1-S9-Tff            | 9" DDSK field installable square trim kit*  |
| ESL-DDSK1-R11-Tff           | 11" DDSK field installable round trim kit*  |
| ESL-DDSK1-S11-Tff           | 11" DDSK field installable square trim kit* |



Finishes: (ff)=(MW) Field Paintable, (BK) Black, (BN) Brushed Nickel, (BZ) Bronze, (CP) Copper

Accessories Sold Separately

<sup>\*</sup>Contact ESL Representative for more information regarding Trim Kit lead times.



## ESL-DDSK-S5-11W-12750

Page 2 of 4

### **Catalog Data:**

### LED DECORATIVE DISK—TRIAC DIMMING

| ITEM#                                  | WATTAGE | SELECTABLE<br>KELVIN | MAX LUMEN<br>OUTPUT | MAX EFFICACY<br>(lm/w) | CRI | INPUT<br>VOLTAGE | DIMENSIONS               |
|--|---------|----------------------|---------------------|------------------------|-----|------------------|--------------------------|
| 5" ROUND                               |         |                      |                     | (,)                    |     | 10202            |                          |
|  |         | 2700K                | 704                 | 62                     |     |                  |                          |
| ECL DDCV DE 44W 427E0                  | 4414    | 3000K                | 752                 | 67                     | 00  | 120 \ / 4 C      | Ø E CO!! . LL440!!       |
| ESL-DDSK-R5-11W-12750                  | 11W     | 3500K<br>4000K       | 785<br>784          | 69<br>70               | 90  | 120 VAC          | Ø 5.63" x H 1.18"        |
|  | -       | 5000K                | 792                 | 69                     |     |                  |                          |
| 5" SQUARE                              |         |                      |                     |                        |     |                  |                          |
|  | -       | 2700K<br>3000K       | 670<br>716          | 59<br>64               |     |                  |                          |
| ESL-DDSK-S5-11W-12750                  | 11W     | 3500K                | 733                 | 66                     | 90  | 120 VAC          | 5.6" x 5.6" x H 1.18"    |
| 201                                    |         | 4000K                | 735                 | 65                     |     | .20 17.10        | 0.0 × 0.0 × 110          |
|  |         | 5000K                | 727                 | 65                     |     |                  |                          |
| 7" ROUND                               |         | 27004                | 000                 | 6.4                    |     |                  |                          |
|  |         | 2700K<br>3000K       | 900<br>962          | 64<br>69               |     |                  |                          |
| ESL-DDSK-R7-14W-12750                  | 14W     | 3500K                | 1,004               | 72                     | 90  | 120 VAC          | Ø 7.09" x H 1.18"        |
|  |         | 4000K                | 1,035               | 74                     |     |                  |                          |
|  |         | 5000K                | 1,004               | 73                     |     |                  |                          |
|  |         | 2700K                | 1,078               | 78                     |     |                  |                          |
| FCL DDCV D7 14W 127F0 FMC              | 1414    | 3000K                | 1,143               | 84                     | 00  | 120 1/40         | Ø 7.00" I I 110"         |
| ESL-DDSK-R7-14W-12750-EMG              | 14W     | 3500K<br>4000K       | 1,196<br>1,219      | 88<br>91               | 90  | 120 VAC          | Ø 7.08" x H 1.18"        |
|  |         | 5000K                | 1,222               | 89                     |     |                  |                          |
| " SQUARE                               |         |                      | •                   |                        |     |                  |                          |
|  |         | 2700K                | 862                 | 62                     |     |                  |                          |
|  |         | 3000K                | 914                 | 66                     |     |                  |                          |
| ESL-DDSK-S7-14W-12750                  | 14W     | 3500K                | 946                 | 69                     | 90  | 120 VAC          | 7.11" x 7.11" x H 1.18"  |
|  | -       | 4000K<br>5000K       | 938<br>923          | 68<br>68               |     |                  |                          |
|  |         | 2700K                | 1,027               | 75                     |     |                  |                          |
|  | •       | 3000K                | 1,092               | 81                     |     |                  |                          |
| ESL-DDSK-S7-14W-12750-EMG <sup>†</sup> | 14W     | 3500K                | 1,159               | 87                     | 90  | 120 VAC          | 7.11" x 7.11" x H 1.18"  |
|  |         | 4000K                | 1,196               | 89                     |     |                  |                          |
|  |         | 5000K                | 1,199               | 88                     |     |                  |                          |
| 9" ROUND                               |         | 2700K                | 1,396               | 71                     |     |                  |                          |
|  | -       | 3000K                | 1,476               | 75                     |     |                  |                          |
| 501 BB01/B0 001/140750                 | 20W     | 3500K                | 1,568               | 80                     | 90  | 120 VAC          | Ø 9.06" x H 1.18"        |
| ESL-DDSK-R9-20W-12750                  |         | 4000K                | 1,576               | 80                     |     |                  |                          |
|  |         | 5000K                | 1,569               | 80                     |     |                  |                          |
|  |         | 2700K                | 1,558               | 78                     |     |                  |                          |
| ESL-DDSK-R9-20W-12750-EMG              | 20W     | 3000K<br>3500K       | 1,646<br>1,715      | 83<br>89               | 90  | 120 VAC          | Ø 9.05" x H 1.18"        |
| E3L-DD3K-R9-20W-12750-EMIG             | 2000    | 4000K                | 1,746               | 89                     | 90  | 120 VAC          | Ø 9.05 X H 1.16          |
|  |         | 5000K                | 1,738               | 89                     |     |                  |                          |
| 9" SQUARE                              |         |                      |                     |                        |     |                  |                          |
|  |         | 2700K                | 1,346               | 68                     |     |                  |                          |
| FCL DDCV CO 20W 427F0                  | 2011    | 3000K                | 1,451               | 73                     | 00  | 120 \ / 4 C      | 0.00" 0.00" 11440"       |
| ESL-DDSK-S9-20W-12750                  | 20W     | 3500K<br>4000K       | 1,503<br>1,488      | 73<br>76               | 90  | 120 VAC          | 9.08" x 9.08" x H 1.18"  |
|  |         | 5000K                | 1,451               | 76                     |     |                  |                          |
|  |         | 2700K                | 1,371               | 72                     |     |                  |                          |
|  |         | 3000K                | 1,437               | 77                     |     |                  |                          |
| ESL-DDSK-S9-20W-12750-EMG <sup>†</sup> | 20W     | 3500K                | 1,492               | 81                     | 90  | 120 VAC          | 9.08" x 9.08" x H 1.18"  |
|  |         | 4000K                | 1,512               | 81                     |     |                  |                          |
|  |         | 5000K                | 1,470               | 78                     |     |                  |                          |
| 11" ROUND                              |         | 2700K                | 1,768               | 71                     |     |                  |                          |
|  |         | 3000K                | 1,866               | 75                     |     |                  |                          |
| ESL-DDSK-R11-25W-12750                 | 25W     | 3500K                | 2,005               | 81                     | 90  | 120 VAC          | Ø 11.0" x H 1.18"        |
|  |         | 4000K                | 2,009               | 81                     |     |                  |                          |
|  |         | 5000K                | 2,004               | 81                     |     |                  |                          |
| 1" SQUARE                              |         | 2700K                | 1,760               | 71                     |     |                  |                          |
|  |         | 3000K                | 1,887               | 71<br>76               |     |                  |                          |
| ESL-DDSK-S11-25W-12750                 | 25W     | 3500K                | 1,966               | 80                     | 90  | 120 VAC          | 11.04" x 11.02" x H 1.18 |
|  |         |                      |                     |                        |     |                  |                          |
| ESE-DDSN-311-25W-12730                 | •       | 4000K                | 1,924               | 79                     |     |                  |                          |

Copyright © 2023 ESL Vision, LLC. All rights reserved. Rev: 12/19/23







## ESL-DDSK-S5-11W-12750

Page 3 of 4

### **Catalog Data:**

### LED DECORATIVE DISK-DUAL DIMMING MULTI-VOLT

| ITEM#   | WATTAGE | SELECTABLE<br>KELVIN    | MAX LUMEN<br>OUTPUT     | MAX EFFICACY<br>(lm/w) | CRI | INPUT<br>VOLTAGE | DIMENSIONS                 |
|---|---------|-------------------------|-------------------------|------------------------|-----|------------------|----------------------------|
| 5" ROUND MULTI-VOLT                             |         |                         |                         | (                      |     |                  |                            |
|   |         | 2700K                   | 883                     | 81                     |     |                  |                            |
|   |         | 3000K                   | 917                     | 85                     |     |                  |                            |
| ESL-DDSK-R5-11W-12750-MV                        | 11W     | 3500K                   | 953                     | 90                     | 90  | 120-277 VAC      | Ø 5.59" x H 1.18"          |
|   | -       | 4000K                   | 963                     | 90                     |     |                  |                            |
|   |         | 5000K                   | 953                     | 88                     |     |                  |                            |
| 5" SQUARE MULTI-VOLT                            |         | 2700K                   | 701                     | 65                     |     |                  |                            |
|   | -       | 3000K                   | 738                     | 70                     |     |                  |                            |
| ESL-DDSK-S5-11W-12750-MV                        | 11W     | 3500K                   | 772                     | 74                     | 90  | 120-277 VAC      | 5.6" x 5.6" x H 1.18"      |
|   |         | 4000K                   | 785                     | 75                     |     |                  |                            |
|   | •       | 5000K                   | 767                     | 72                     |     |                  |                            |
| " ROUND MULTI-VOLT                              |         |                         |                         |                        |     |                  |                            |
|   |         | 2700K                   | 1,135                   | 84                     |     |                  |                            |
|   |         | 3000K                   | 1,203                   | 91                     |     |                  |                            |
| ESL-DDSK-R7-14W-12750-MV                        | 14W .   | 3500K                   | 1,241                   | 94                     | 90  | 120-277 VAC      | Ø 7.08" x H 1.18"          |
|   |         | 4000K                   | 1,273                   | 98                     |     |                  |                            |
|   |         | 5000K                   | 1,264                   | 95                     |     |                  |                            |
|   |         | 2700K<br>3000K          | 1,145                   | 85<br>92               |     |                  |                            |
| ESL-DDSK-R7-14W-12750-MV-EMG                    | 14W     | 3500K                   | 1,204<br>1,255          | 98                     | 90  | 120-277 VAC      | Ø 7.08" x H 1.18"          |
| 23L-DD3K-R7-14W-12750-WV-EWIG                   | 14 44   | 4000K                   | 1,273                   | 96                     | 90  | 120-277 VAC      | Ø 7.06 X H 1.16            |
|   |         | 5000K                   | 1,267                   | 97                     |     |                  |                            |
| " SQUARE MULTI-VOLT                             |         | 300010                  | 1,207                   | 37                     |     |                  |                            |
| SQUARE MOETI-VOET                               |         | 2700K                   | 980                     | 73                     |     |                  |                            |
|   | •       | 3000K                   | 1,039                   | 78                     |     |                  |                            |
| ESL-DDSK-S7-14W-12750-MV                        | 14W     | 3500K                   | 1,078                   | 83                     | 90  | 120-277 VAC      | 7.11" x 7.11" x H 1.18"    |
|   |         | 400 OK                  | 1,088                   | 83                     |     |                  |                            |
|   |         | 5000K                   | 1,058                   | 79                     |     |                  |                            |
|   |         | 2700K                   | 1,007                   | 73                     |     |                  |                            |
|   | -       | 3000K                   | 1,085                   | 80                     |     |                  |                            |
| ESL-DDSK-S7-14W-12750-MV-EMG <sup>†</sup>       | 14W     | 3500K                   | 1,132                   | 85                     | 90  | 120-277 VAC      | 7.11" x 7.11" x H 1.18"    |
|   | -       | 4000K                   | 1,148                   | 86                     |     |                  |                            |
|   |         | 5000K                   | 1,126                   | 83                     |     |                  |                            |
| 9" ROUND MULTI-VOLT                             |         | 2700K                   | 1,660                   | 88                     |     |                  |                            |
|   |         | 3000K                   | 1,735                   | 93                     |     |                  |                            |
| ESL-DDSK-R9-20W-12750-MV                        | 20W     | 3500K                   | 1,789                   | 97                     | 90  | 120-277 VAC      | Ø 9.05" x H 1.18"          |
| 102 BBOK NO 20W 12700 WV                        | 2011    | 4000K                   | 1,854                   | 101                    | 30  | 120 277 VAC      | Ø 5.05 X 11 1.10           |
|   |         | 5000K                   | 1,843                   | 99                     |     |                  |                            |
|   |         | 2700K                   | 1,665                   | 86                     |     |                  |                            |
|   |         | 3000K                   | 1,750                   | 93                     |     |                  |                            |
| ESL-DDSK-R9-20W-12750-MV-EMG <sup>†</sup>       | 20W     | 3500K                   | 1,832                   | 98                     | 90  | 120-277 VAC      | Ø 9.05" x H 1.18"          |
|   |         | 4000K                   | 1,869                   | 98                     |     |                  |                            |
|   |         | 5000K                   | 1,864                   | 98                     |     |                  |                            |
| 9" SQUARE MULTI-VOLT                            |         |                         |                         |                        |     |                  |                            |
|   |         | 2700K                   | 1,462                   | 80                     |     |                  |                            |
|   | 2011    | 3000K                   | 1,542                   | 86                     | 00  | 420 277 \ / 40   | 0.00" 0.00" 11.440         |
| ESL-DDSK-S9-20W-12750-MV†                       | 20W     | 3500K                   | 1,608                   | 91                     | 90  | 120-277 VAC      | 9.08" x 9.08" x H 1.18     |
|   | -       | 4000K<br>5000K          | 1,616<br>1,571          | 91<br>86               |     |                  |                            |
|   |         | 2700K                   | 1,329                   | 72                     |     |                  |                            |
|   |         | 3000K                   | 1,395                   | 77                     |     |                  |                            |
| ESL-DDSK-S9-20W-12750-MV-EMG <sup>+</sup>       | 20W     | 3500K                   | 1,461                   | 82                     | 90  | 120-277 VAC      | 9.08" x 9.08" x H 1.18     |
| -25 DD3K-33-20W-12/30-WV-EWIG                   | ==      | 4000K                   | 1,485                   | 83                     |     |                  |                            |
|   |         | 5000K                   | 1,458                   | 80                     |     |                  |                            |
| 1" ROUND MULTI-VOLT                             |         |                         |                         |                        |     |                  |                            |
|   | -       | 2700K                   | 2,147                   | 94                     |     |                  |                            |
|   |         | 3000K                   | 2,249                   | 100                    |     |                  |                            |
| ESL-DDSK-R11-25W-12750-MV <sup>†</sup>          | 25W     | 3500K                   | 2,315                   | 104                    | 90  | 120-277 VAC      | Ø 11.0" x H 1.18"          |
|   | -       | 4000K                   | 2,367                   | 106                    |     |                  |                            |
|   |         | 5000K                   | 2,343                   | 103                    |     |                  |                            |
|   |         | 27001                   | 2.024                   | 07                     |     |                  |                            |
| 1" SQUARE MULTI-VOLT                            |         | 2700K                   | 2,024                   | 87                     |     |                  |                            |
| 1" SQUARE MULTI-VOLT                            |         | 20001/                  | 2426                    |                        |     |                  |                            |
| 11" SQUARE MULTI-VOLT                           | 2EW.    | 3000K                   | 2,126                   | 93                     | 90  | 120 277 1/40     | 11 0 4" × 11 0 4" × 11 146 |
| 1" SQUARE MULTI-VOLT ESL-DDSK-S11-25W-12750-MV† | 25W     | 3000K<br>3500K<br>4000K | 2,126<br>2,210<br>2,245 | 93<br>98<br>99         | 90  | 120-277 VAC      | 11.04" × 11.04" × H 1.18   |

Copyright © 2023 ESL Vision, LLC. All rights reserved. Rev: 12/19/23









### ESL-DDSK-S5-11W-12750


Page 4 of 4

#### **Dimensions:**



| ITEM#                                     | A DI    | MENSIOI<br>B | NS<br>C | WEIGHT (LBS) |
|---|---------|--------------|---------|--------------|
| 5" ROUND                                  |         |              |         |              |
| ESL-DDSK-R5-11W-12750                     | Ø 5.63" | -            | 1.18"   | .63          |
| ESL-DDSK-R5-11W-12750-MV                  | Ø 5.59" | _            | 1.18"   | .70          |
| 7" ROUND                                  |         |              |         |              |
| ESL-DDSK-R7-14W-12750                     | Ø 7.09" | -            | 1.18"   | .86          |
| ESL-DDSK-R7-14W-12750-EMG                 | Ø 7.08" | _            | 1.18"   | 1.28         |
| ESL-DDSK-R7-14W-12750-MV                  | Ø 7.08" | _            | 1.18"   | .95          |
| ESL-DDSK-R7-14W-12750-MV-EMG              | Ø 7.08" | _            | 1.18"   | 1.3          |
| 9" ROUND                                  |         |              |         |              |
| ESL-DDSK-R9-20W-12750                     | Ø 9.06" | -            | 1.18"   | 1.25         |
| ESL-DDSK-R9-20W-12750-EMG <sup>†</sup>    | Ø 9.05" | _            | 1.18"   | 1.67         |
| ESL-DDSK-R9-20W-12750-MV                  | Ø 9.05" | _            | 1.18"   | 1.29         |
| ESL-DDSK-R9-20W-12750-MV-EMG <sup>†</sup> | Ø 9.05" | _            | 1.18"   | 1.69         |
| 11" ROUND                                 |         |              |         |              |
| ESL-DDSK-R11-25W-12750                    | Ø 11.0" | -            | 1.18"   | 1.68         |
| ESL-DDSK-R11-25W-12750-MV <sup>†</sup>    | Ø 11.0" | _            | 1.18"   | 1.74         |





| ITEM#                                     | A D    | IMENSION<br>B | IS<br>C | WEIGHT (LBS) |
|---|--------|---------------|---------|--------------|
| 5" SQUARE                                 |        |               |         |              |
| ESL-DDSK-S5-11W-12750                     | 5.6"   | 5.6"          | 1.18"   | .75          |
| ESL-DDSK-S5-11W-12750-MV                  | 5.6"   | 5.6"          | 1.18"   | .78          |
| 7" SQUARE                                 |        |               |         |              |
| ESL-D DSK-S7-14W-12750                    | 7.11"  | 7.11"         | 1.18"   | 1.03         |
| ESL-DDSK-S7-14W-12750-EMG <sup>†</sup>    | 7.11"  | 7.11"         | 1.18"   | 1.44         |
| ESL-DDSK-S7-14W-12750-MV                  | 7.11"  | 7.11"         | 1.18"   | 1.07         |
| ESL-DDSK-S7-14W-12750-MV-EMG <sup>†</sup> | 7.11"  | 7.11"         | 1.18"   | 1.46         |
| 9" SQUARE                                 |        |               |         |              |
| ESL-DDSK-S9-20W-12750                     | 9.08"  | 9.08"         | 1.18"   | 1.56         |
| ESL-DDSK-S9-20W-12750-EMG                 | 9.08"  | 9.08"         | 1.18"   | 2.09         |
| ESL-DDSK-S9-20W-12750-MV <sup>+</sup>     | 9.08"  | 9.08"         | 1.18"   | 1.61         |
| ESL-DDSK-S9-20W-12750-MV-EMG <sup>†</sup> | 9.08"  | 9.08"         | 1.18"   | 2.11         |
| 11" SQUARE                                |        |               |         |              |
| ESL-DDSK-S11-25W-12750                    | 11.04" | 11.04"        | 1.18"   | 2.12         |
| ESL-DDSK-S11-25W-12750-MV <sup>†</sup>    | 11.04" | 11.04"        | 1.18"   | 2.2          |

<sup>&</sup>lt;sup>†</sup>Contact your representative for lead times

### **DDSK Compatible Dimmers:**

| NON-EMG TRIAC     |
|-------------------|
| Lutron DVCL-153P  |
| Lutron LECL-153PH |
| Lutron LECL-153PH |
| Lutron CTCL-153PH |
| Leviton 6672      |
| Leviton 6674      |
| Leviton IPSD6     |
| Leviton DSL06     |
| Leviton IPL06     |
| Leviton DSM10     |

| EMG TRIAC         |
|-------------------|
| Lutron DVCL-303   |
| Lutron LECL-153PH |
| Lutron CT-600P    |
| Lutron CTCL-153PH |
| Leviton 6672      |
| Leviton 6674      |
| Leviton DSL06     |
| Leviton IPL06     |
| Leviton DSM10     |
| Leviton PD-6WCL   |

### **DDSK-MV Compatible Dimmers:**

| REGULAR AND EMG TRIAC      |
|----------------------------|
| Lutron DVCL-153P Diva      |
| Lutron DVWCL-153PH Diva    |
| Lutron LECL-153PH-WH Lunea |
| Lutron TGCL-153PH          |
| Lutron CTCL-153PH Skylark  |
| Leviton 6672               |
| Leviton 6674               |
| Leviton IPSD6              |
| Leviton DSL06              |
| Leviton IPL06              |
| Leviton DSM10              |
| Cooper TAL06P-C2           |

