## **LV113**

## PATH, WALKWAY AND AREA LIGHT





Lens: Clear, Heat Resistant, Tempered Glass

► Lamp: MR16 Bi-Pin Base (50W Maximum) Available in 27K or 65K (LED)

MODEL NUMBER	LAMP Type	ILLUMINANT Type	WATTS (W)	VOLTS (V)	LAMP(S) INCLUDED?
LV113	MR16	HALOGEN	20	12	YES
LV113-LED3	MR16-LED	LED	3	12	YES
LV113-LED5	MR16-LED	LED	5	12	YES
LV113-LED7	MR16-LED	LED	7	12	YES
LV113-LED4-RGBW	MR16-LED	LED	4	12	YES

Pre-wired with UL Listed Direct Burial Wire/Cable

▶ 1/2" NPT

► Ground Spike Included for Installation

► **Connector Available:** P-CN01 (sold separately)

► **RGBW Lamp Requires/Remote:** P-RMT-DL-MR16-LED-4W-MC (sold separately)

Available Finish: Black, Green

ETL Approved

31.25"		
0.25"	<b>24.</b> 2 (101	<b>25 "</b> AL)

Overall Dimensions: 24.25"H x 3.00"W x 9.00"D

Maximum Height: 24.25"

Width: 3.00"

Maximum Depth: 9.00"

Weight: 1.00 lbs

Approximate Wire Length: 24"

**Box Dimensions:** 

24.75"H x 9.88"W x 3.13"D

