


TYPE LDAU LDBU

Features

- Modular design
- Easy to assemble
- UL listed 90° C 600 Volts
- Electro-tin plated aluminum
- Multiple conductor capability

Benefits

- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.






F

Catalog Number	Fig. No.	Connector		Primary			Secondary			Ampere Rating Per Pole
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	
LDBU-112-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
DBU-112A-350	1			350kcmil-6	1	3/8	4-14	12	Slot	310
LDAU-112A-350	2			350kcmil-6	1	3/8	4-14	12	Slot	310
LDBU-16-350	1			350kcmil-6	1	3/8	2/0-14	6	Slot	310
LDAU-16-350	2			350kcmil-6	1	3/8	2/0-14	6	Slot	310
LDBU-16-500	1			500kcmil-4	1	3/8	2/0-14	6	Slot	380
LDAU-16-500	2			500kcmil-4	1	3/8	2/0-14	6	Slot	380
LDBU-26-350	1			350kcmil-6	2	3/8	2/0-14	6	Slot	620
LDAU-26-350	2			350kcmil-6	2	3/8	2/0-14	6	Slot	620
LDBU-212-4/0	1			4/0-6	2	3/8	4-14	12	Slot	460
LDAU-212-4/0	2			4/0-6	2	3/8	4-14	12	Slot	460
LDBU-212-500	1			500kcmil-4	2	3/8	4-14	12	Slot	760
LDAU-212-500	2			500kcmil-4	2	3/8	4-14	12	Slot	760
LDBU-26-500	1			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDAU-26-500	2			500kcmil-4	2	3/8	2/0-14	6	3/16	760
LDBU-24-500	1			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDAU-24-500	2			500kcmil-4	2	3/8	4/0-6	4	5/16	760
LDBU-11-500	1			500kcmil-4	1	3/8	500kcmil-4	4	3/8	380
LDAU-11-500	2			500kcmil-4	1	3/8	500kcmil-4	4	3/8	380
LDBU-22-350	1			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDAU-22-350	2			350kcmil-6	2	3/8	350kcmil-6	2	3/8	620
LDBU-22-500	1			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760
LDAU-22-500	2			500kcmil-4	2	3/8	500kcmil-4	2	3/8	760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158



Dimensions

A	B	C	D=Dia.	E	F	G	H	J=Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50