


Aluminum Long Barrel 2 Hole Compression Lugs



- AL9CU Listed - For Both Aluminum and Copper Conductors
- Pre-filled with Oxide Inhibitor
- Made of High-Conductivity Seamless Aluminum
- Electro-Tin Plating Resists Corrosion, Reduces Contact Resistance for Maximum Conductivity
- Dual Mounting Holes for Superior Contact Integrity
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486B AL9CU Listed for Applications Thru 35KV



DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	STUD SIZE	COLOR CODE	A	C	J	B	D	F	E	G	PL	S	BOX QTY
93110	1/0 STR.	3/8	TAN	.39	.63	3.50	1.20	.85	.24	.41	.38	1.87	1.00	10
93111	1/0 STR.	1/2	TAN	.39	.63	4.75	1.20	.85	.24	.51	.63	3.12	1.75	20
93109	2/0 STR.	3/8	OLIVE	.44	.69	4.80	1.30	.94	.24	.41	.63	3.12	1.00	20
93112	2/0 STR.	1/2	OLIVE	.44	.69	4.80	1.30	.94	.24	.51	.63	3.12	1.75	20
93113	3/0 STR.	3/8	RUBY	.48	.76	5.00	1.40	1.03	.28	.41	.63	3.12	1.00	20
93114	3/0 STR.	1/2	RUBY	.48	.76	5.00	1.40	1.03	.28	.51	.63	3.12	1.75	20
93115	4/0 STR.	3/8	WHITE	.55	.84	5.25	1.40	1.15	.29	.41	.63	3.12	1.00	12
93116	4/0 STR.	1/2	WHITE	.55	.84	5.25	1.40	1.15	.29	.51	.63	3.12	1.75	12
93117	250 MCM	3/8	RED	.59	.92	5.31	1.50	1.26	.32	.41	.63	3.12	1.00	12
93118	250 MCM	1/2	RED	.59	.92	5.31	1.50	1.26	.32	.51	.63	3.12	1.75	12
93119	300 MCM	3/8	BLUE	.65	1.01	5.50	1.60	1.37	.35	.41	.63	3.12	1.00	9
93120	300 MCM	1/2	BLUE	.65	1.01	5.50	1.60	1.37	.35	.51	.63	3.12	1.75	9
93121	350 MCM	3/8	BROWN	.72	1.12	5.87	1.90	1.52	.39	.41	.63	3.12	1.00	6
93122	350 MCM	1/2	BROWN	.72	1.12	5.87	1.90	1.52	.39	.51	.63	3.12	1.75	6
93123	400 MCM	3/8	GREEN	.76	1.19	6.43	2.30	1.61	.42	.41	.63	3.12	1.00	6
93124	400 MCM	1/2	GREEN	.76	1.19	6.43	2.30	1.61	.42	.51	.63	3.12	1.75	6
93125	500 MCM	3/8	PINK	.84	1.32	6.50	2.50	1.79	.47	.41	.63	3.12	1.00	6
93126	500 MCM	1/2	PINK	.84	1.32	6.50	2.50	1.79	.47	.51	.63	3.12	1.75	6
93127	500 MCM	5/8	PINK	.84	1.32	6.50	2.50	1.79	.47	.67	.63	3.12	1.75	6
93129	600 MCM	3/8	BLACK	.92	1.44	6.75	2.60	1.96	.51	.41	.63	3.12	1.00	4
93128	600 MCM	1/2	BLACK	.92	1.44	6.75	2.60	1.96	.51	.51	.63	3.12	1.75	4
93131	600 MCM	5/8	BLACK	.92	1.44	6.75	2.60	1.96	.51	.67	.63	3.12	1.75	4
93132	750 MCM	3/8	YELLOW	1.03	1.60	7.37	3.20	2.19	.55	.41	.63	3.12	1.00	4
93130	750 MCM	1/2	YELLOW	1.03	1.60	7.37	3.2	2.19	.55	.51	.63	3.12	1.75	4
93133	750 MCM	5/8	YELLOW	1.03	1.60	7.37	3.2	2.19	.55	.67	.63	3.12	1.75	4

Aluminum Long Barrel Compression Splices



DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	COLOR CODE	A	C	LENGTH (L)	BOX QTY
93208	8 STR.	BLUE	.16	.30	1.38	50
93210	6 STR.	GRAY	.20	.34	1.63	50
93212	4 STR.	GREEN	.25	.44	2.00	30
93214	2 STR.	PINK	.31	.53	2.38	30
93216	1 STR.	GOLD	.35	.53	2.38	15
93218	1/0 STR.	TAN	.39	.63	2.50	20
93220	2/0 STR.	OLIVE	.44	.69	2.63	20
93222	3/0 STR.	RUBY	.48	.76	2.88	15
93224	4/0 STR.	WHITE	.55	.84	3.13	10
93226	250 MCM	RED	.59	.92	3.25	9
93228	300 MCM	BLUE	.65	1.01	3.25	9
93230	350 MCM	BROWN	.72	1.12	3.88	6
93232	400 MCM	GREEN	.76	1.19	4.88	6
93234	500 MCM	PINK	.84	1.32	5.00	6
93236	600 MCM	BLACK	.92	1.44	5.13	4
93238	750 MCM	YELLOW	1.03	1.60	5.38	4

- AL9CU Listed - for both Aluminum and Copper Conductors
- Pre-filled with Oxide Inhibitor
- Made of High-Conductivity Seamless Aluminum
- Uniform Bright Electro-Tin Plating Resists Corrosion, Reduces Contact Resistance for Maximum Conductivity
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486B AL9CU Listed for Applications Thru 35KV