


Steel EMT Rain Tight Compression Connectors



- Use to connect EMT conduit to steel outlet box, load center, or other metal enclosure in a dry or wet location
- Internal Sealing Ring & Knockout Gasket create Raintight Seal
- Heavy Steel Walls, Zinc Plated
- Concrete Tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
I4970	1/2"	1.14	.51	1.08	50	500
I4971	3/4"	1.42	.51	1.35	25	250
I4972	1"	1.58	.57	1.65	10	100
I4973	1-1/4"	1.60	.61	2.02	10	100
I4974	1-1/2"	1.93	.63	2.24	10	50
I4975	2"	2.23	.67	2.80	5	50
I4976	2-1/2"	2.80	.83	3.60	-	12
I4977	3"	3.00	.83	4.25	-	12
I4978	3-1/2"	3.35	.83	4.80	-	6
I4979	4"	3.47	.83	5.24	-	6




Steel EMT Rain Tight Compression Connectors-Insulated Throat



- Use to connect EMT conduit to steel outlet box, load center, or other metal enclosure in dry or wet location
- Internal Sealing Ring & Knockout Gasket create Raintight Seal
- Heavy Steel Walls, Zinc Plated
- Insulated throat
- Concrete Tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
I4980	1/2"	1.18	.51	1.08	50	500
I4981	3/4"	1.46	.51	1.35	25	250
I4982	1"	1.61	.57	1.65	10	100
I4983	1-1/4"	1.69	.61	2.02	10	100
I4984	1-1/2"	2.00	.61	2.24	10	50
I4985	2"	2.36	.67	2.76	5	50
I4986	2-1/2"	2.87	.83	3.62	-	12
I4987	3"	3.07	.83	4.25	-	12
I4988	3-1/2"	3.42	.83	4.80	-	6
I4989	4"	3.54	.83	5.24	-	6



Steel EMT Compression Rain Tight Couplings



- Use to connect two lengths of EMT conduit together in a dry or wet location
- Internal Sealing Ring creates Rain Tight Seal
- Heavy Steel Walls, Zinc Plated
- Concrete Tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
I4990	1/2"	1.81	1.08	50	500
I4991	3/4"	1.89	1.35	25	250
I4992	1"	2.30	1.65	10	100
I4993	1-1/4"	2.68	2.02	10	100
I4994	1-1/2"	2.74	2.24	10	50
I4995	2"	2.95	2.76	5	50
I4996	2-1/2"	3.90	3.62	-	12
I4997	3"	4.11	4.25	-	12
I4998	3-1/2"	4.53	4.80	-	6
I4999	4"	4.65	5.24	-	6

