



Nylon Insulated Ring Terminals

NEW
BULK PACKS



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50


MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
I1312	RED	22-16	#4	.126	.216	.197	.728	.433	.157	.067	.030	100	1,000
I1314	RED	22-16	#6	.146	.260	.248	.803	.433	.157	.067	.030	100	1,000
I1314B	RED	22-16	#6	.146	.260	.248	.803	.433	.157	.067	.030	1,000	20,000
I1316	RED	22-16	#8	.169	.315	.276	.858	.433	.157	.067	.030	100	1,000
I1316B	RED	22-16	#8	.169	.315	.276	.858	.433	.157	.067	.030	1,000	20,000
I1318	RED	22-16	#10	.209	.315	.276	.858	.433	.157	.067	.030	100	1,000
I1320	RED	22-16	1/4	.252	.457	.433	1.094	.433	.157	.067	.030	100	1,000
I1322	RED	22-16	5/16	.331	.457	.433	1.094	.433	.157	.067	.030	100	1,000
I1324	RED	22-16	3/8	.413	.535	.547	1.240	.433	.157	.067	.030	100	1,000
I1326	RED	22-16	1/2	.512	.756	.630	1.433	.433	.157	.067	.030	100	1,000
I1328	RED	22-16	9/16	.591	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
I1330	RED	22-16	5/8	.669	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
I1332	RED	22-16	3/4	.827	1.063	.827	1.783	.433	.157	.067	.031	100	1,000
I1334	BLUE	16-14	#4	.126	.260	.189	.740	.433	.177	.091	.031	100	1,000
I1336	BLUE	16-14	#6	.146	.260	.248	.803	.433	.177	.091	.031	100	1,000
I1338	BLUE	16-14	#8	.169	.335	.307	.898	.433	.177	.091	.031	100	1,000
I1338B	BLUE	16-14	#8	.169	.335	.307	.898	.433	.177	.091	.031	1,000	20,000
I1340	BLUE	16-14	#10	.209	.335	.307	.898	.433	.177	.091	.031	100	1,000
I1340B	BLUE	16-14	#10	.209	.335	.307	.898	.433	.177	.091	.031	1,000	20,000
I1342	BLUE	16-14	1/4	.252	.472	.433	1.094	.433	.177	.091	.031	100	1,000
I1342B	BLUE	16-14	1/4	.252	.472	.433	1.094	.433	.177	.091	.031	1,000	10,000
I1344	BLUE	16-14	5/16	.331	.472	.433	1.094	.433	.177	.091	.031	100	1,000
I1346	BLUE	16-14	3/8	.413	.535	.547	1.240	.433	.177	.091	.031	100	1,000
I1348	BLUE	16-14	1/2	.512	.756	.630	1.433	.433	.177	.091	.031	100	1,000
I1350	BLUE	16-14	9/16	.591	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
I1352	BLUE	16-14	5/8	.669	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
I1354	BLUE	16-14	3/4	.827	1.063	.827	1.783	.433	.177	.091	.031	100	1,000
I1356	YELLOW	12-10	#6	.146	.283	.240	.894	.512	.252	.134	.039	100	1,000
I1358	YELLOW	12-10	#8	.169	.283	.240	.894	.512	.252	.134	.039	100	1,000
I1358B	YELLOW	12-10	#8	.169	.283	.240	.894	.512	.252	.134	.039	500	10,000
I1360	YELLOW	12-10	#10	.209	.374	.329	1.024	.512	.252	.134	.039	100	1,000
I1360B	YELLOW	12-10	#10	.209	.374	.329	1.024	.512	.252	.134	.039	500	10,000
I1362	YELLOW	12-10	1/4	.252	.472	.413	1.161	.512	.252	.134	.039	100	1,000
I1362B	YELLOW	12-10	1/4	.252	.472	.413	1.161	.512	.252	.134	.039	500	10,000
I1364	YELLOW	12-10	5/16	.331	.591	.524	1.339	.512	.252	.134	.039	100	1,000
I1366	YELLOW	12-10	3/8	.413	.591	.524	1.339	.512	.252	.134	.039	100	1,000
I1368	YELLOW	12-10	1/2	.512	.756	.630	1.520	.512	.252	.134	.039	100	1,000
I1370	YELLOW	12-10	9/16	.591	1.260	.992	2.134	.512	.252	.134	.039	100	1,000
I1372	YELLOW	12-10	5/8	.669	1.260	.992	2.134	.512	.252	.134	.039	100	1,000
I1374	YELLOW	12-10	3/4	.827	1.260	.992	2.134	.512	.252	.134	.039	100	1,000