


# Water-Tight Service Entrance Connectors - Zinc Die-Cast



- Compression Type SEU Connector
- Used to Connect Service Entrance Cable to a Service Enclosure in Wet Locations
- Accepts 2 Insulated Conductors, 1 Bare
- U/Flat Style Conductor Only
- Assembled with Rubber Grommet and Steel Washer
- Locknut Included

DIMENSIONS = INCHES

| CAT. NO. | TRADE SIZE | CABLE SIZE | MAX GROMMET OPENING |       | OVERALL DIMENSIONS |      | INNER BOX | OUTER BOX |
|----------|------------|------------|---------------------|-------|--------------------|------|-----------|-----------|
|          |            |            | LENGTH              | WIDTH | A                  | B    |           |           |
| 15370    | 1"         | #8         | .67                 | .40   | 1.67               | 1.45 | 20        | 100       |
| 15371    | 1"         | #6         | .77                 | .50   | 1.67               | 1.45 | 20        | 100       |
| 15372    | 1"         | #4         | .81                 | .53   | 1.67               | 1.45 | 20        | 100       |
| 15373    | 1-1/4"     | #3         | .92                 | .56   | 2.05               | 1.80 | 10        | 50        |
| 15374    | 1-1/4"     | #2         | .98                 | .59   | 2.05               | 1.80 | 10        | 50        |
| 15375    | 1-1/4"     | #1         | 1.09                | .65   | 2.05               | 1.80 | 10        | 50        |
| 15377    | 1-1/2"     | #2/0       | 1.34                | .86   | 2.31               | 2.02 | 10        | 50        |
| 15379    | 2"         | #2/0       | 1.34                | .86   | 2.82               | 2.39 | 5         | 25        |
| 15380    | 2"         | #3/0       | 1.37                | .87   | 2.82               | 2.39 | 5         | 25        |
| 15381    | 2"         | #4/0       | 1.50                | .90   | 2.82               | 2.39 | 5         | 25        |
| 15382    | 2"         | #4/0       | 1.73                | 1.11  | 2.82               | 2.39 | 5         | 25        |



Service Entrance




## Underground Feed UF To Box Connector - Zinc Die Cast

- Used to Connect Underground Feeder Cables (UF) To Weatherproof Enclosures in Wet Locations.
- Assembled with a Rubber Grommet and Steel Washer
- Sealing Locknut System

DIMENSIONS = INCHES

| CAT. NO. | TRADE SIZE | CABLE SIZE            | MAX GROMMET OPENING |       | OVERALL DIMENSIONS |      | INNER BOX | OUTER BOX |
|----------|------------|-----------------------|---------------------|-------|--------------------|------|-----------|-----------|
|          |            |                       | LENGTH              | WIDTH | A                  | B    |           |           |
| 15386    | 1/2"       | 14/2, 12/2, 10/2      | .475                | .235  | 1.22               | 1.14 | 25        | 250       |
| 15387    | 3/4"       | 14/3, 12/3, 10/3, 8/2 | .720                | .260  | 1.34               | 1.20 | 25        | 250       |



- UL 467 listed connector for use with Equipment Ground Conductors, Ground Electrode Conductors and Bonding Jumpers
- The Kenny Clamp bonds the enclosure of a service panelboard, load center, separately derived system or switchboard to the grounding electrode conductor per the requirements of NEC 250.8; 312.5(A); 250.53 D(2); 250.52 (A)(1); 250.52(A)(3); 250.66; 250.104 (D)(1); 250.24; 450.10(A)
- Assures good metallic connection and low impedance path for grounding and bonding of electrical equipment
- 12,000 Amp listed and tested
- Brass

| CAT. NO. | MODEL NO. | TRADE SIZE     | DIMENSIONS |      | INNER BOX | OUTER BOX |
|----------|-----------|----------------|------------|------|-----------|-----------|
|          |           |                | A          | B    |           |           |
| 15390    | KC8ST     | 8 AWG STRANDED | 1.75       | 1.06 | 10        | 100       |
| 15391    | KC8SO     | 8 AWG SOLID    | 1.75       | 1.06 | 10        | 100       |
| 15392    | KC6SO     | 6 AWG SOLID    | 1.75       | 1.06 | 10        | 100       |
| 15393    | KC6ST     | 6 AWG STRANDED | 1.75       | 1.06 | 10        | 100       |
| 15394    | KC4SO     | 4 AWG SOLID    | 1.75       | 1.06 | 10        | 100       |
| 15395    | KC4ST     | 4 AWG STRANDED | 1.75       | 1.06 | 10        | 100       |
| 15396    | KC2ST     | 2 AWG STRANDED | 1.75       | 1.06 | 10        | 100       |
| 15397    | KCIAST    | 1/0 STRANDED   | 1.75       | 1.06 | 10        | 100       |
| 15398    | KC2AST    | 2/0 STRANDED   | 1.75       | 1.06 | 10        | 100       |
| 15399    | KC3AST    | 3/0 STRANDED   | 1.75       | 1.06 | 10        | 100       |

## Kenny Clamps

