




Copper Short Barrel 1 Hole Compression Lugs



- High Conductivity Seamless Copper
- Electro-Tin Plating Resists Corrosion, Reduces Contact Resistance for Maximum Conductivity
- Single Mounting Hole
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486A Listed for Applications Thru 35KV

DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	STUD SIZE	COLOR CODE	A	C	J	B	D	F	E	G	PL	BOX QTY
94010	8 STR.	#10	RED	.172	.272	1.34	.44	.42	.08	.21	.29	.65	80
94012	8 STR.	1/4	RED	.172	.272	1.34	.44	.42	.08	.25	.29	.65	80
94013	8 STR.	5/16	RED	.172	.272	1.34	.44	.50	.08	.33	.29	.65	80
94014	8 STR.	3/8	RED	.172	.272	1.34	.44	.56	.08	.41	.31	.65	80
94016	6 STR.	#10	BLUE	.204	.297	1.77	.81	.42	.07	.21	.31	.69	60
94018	6 STR.	1/4	BLUE	.204	.297	1.77	.81	.42	.07	.25	.31	.69	60
94020	6 STR.	5/16	BLUE	.204	.297	1.77	.81	.49	.07	.33	.31	.69	60
94021	6 STR.	3/8	BLUE	.204	.297	1.77	.81	.60	.08	.41	.31	.69	60
94024	4 STR.	#10	GRAY	.252	.343	1.50	.71	.49	.08	.21	.36	.75	45
94026	4 STR.	1/4	GRAY	.250	.344	1.81	.81	.49	.09	.25	.36	.75	45
94028	4 STR.	5/16	GRAY	.250	.344	1.81	.81	.49	.09	.33	.36	.75	45
94030	4 STR.	3/8	GRAY	.250	.344	1.81	.81	.56	.09	.41	.36	.75	45
94031	4 STR.	1/2	GRAY	.250	.344	1.81	.81	.70	.09	.51	.36	.75	45
94034	2 STR.	1/4	BROWN	.315	.422	1.93	.88	.60	.10	.25	.37	.81	25
94036	2 STR.	5/16	BROWN	.315	.422	1.93	.88	.60	.10	.33	.37	.81	25
94038	2 STR.	3/8	BROWN	.315	.422	1.93	.88	.60	.10	.41	.37	.81	25
94039	2 STR.	1/2	BROWN	.315	.422	1.93	.88	.70	.10	.51	.37	.81	25
94042	1 STR.	1/4	GREEN	.359	.469	2.01	.88	.67	.11	.25	.37	.81	20
94044	1 STR.	5/16	GREEN	.359	.469	2.01	.88	.67	.11	.33	.37	.81	20
94046	1 STR.	3/8	GREEN	.359	.469	2.01	.88	.67	.11	.41	.37	.81	20
94047	1 STR.	1/2	GREEN	.359	.469	2.01	.88	.70	.11	.51	.37	.81	20
94050	1/0 STR.	1/4	PINK	.390	.520	2.01	.88	.74	.13	.25	.37	.81	12
94052	1/0 STR.	5/16	PINK	.390	.520	2.01	.88	.74	.13	.33	.37	.81	12
94054	1/0 STR.	3/8	PINK	.390	.520	2.01	.88	.74	.13	.41	.37	.81	12
94055	1/0 STR.	1/2	PINK	.390	.520	2.01	.88	.74	.13	.51	.37	.81	12
94058	2/0 STR.	1/4	BLACK	.441	.563	2.32	.94	.81	.12	.25	.48	1.06	10
94060	2/0 STR.	5/16	BLACK	.441	.563	2.32	.94	.81	.12	.33	.48	1.06	10
94062	2/0 STR.	3/8	BLACK	.441	.563	2.32	.94	.81	.12	.41	.48	1.06	10
94064	2/0 STR.	1/2	BLACK	.441	.563	2.32	.94	.81	.12	.51	.48	1.06	10
94066	3/0 STR.	1/4	ORANGE	.492	.622	2.52	1.00	.90	.13	.25	.48	1.06	20
94068	3/0 STR.	5/16	ORANGE	.492	.622	2.52	1.00	.90	.13	.33	.48	1.06	20
94070	3/0 STR.	3/8	ORANGE	.492	.622	2.52	1.00	.90	.13	.41	.48	1.06	20
94072	3/0 STR.	1/2	ORANGE	.492	.622	2.52	1.00	.90	.13	.51	.48	1.06	20
94074	4/0 STR.	1/4	PURPLE	.547	.689	2.52	1.00	1.00	.13	.25	.48	1.06	20
94076	4/0 STR.	5/16	PURPLE	.547	.689	2.52	1.00	1.00	.13	.33	.48	1.06	20
94078	4/0 STR.	3/8	PURPLE	.547	.689	2.52	1.00	1.00	.13	.41	.48	1.06	20
94080	4/0 STR.	1/2	PURPLE	.547	.689	2.52	1.00	1.00	.13	.51	.48	1.06	20