

Insulated Splices - Single Side Entry



Dual-Rated
CU9AL
90°C 600V



CONNECTORS
Insulated Connectors

- Wire Entry from 1 (Same) Side in Stub Termination Configuration

DIMENSIONS = INCHES

CAT. NO.	WIRE PORTS	WIRE RANGE	ALLEN HEX	LENGTH	HEIGHT	BOX QTY
97513	3	4-14	SLOTTED	1.50	1.45	12
97514	4			1.92		12
97515	5			2.33		6
97516	6			2.75		4
97518	8			3.59		3
97519	3	2-14	SLOTTED	1.60	1.50	6
97520	4			2.02		6
97521	5			2.43		4
97522	6			2.85		4
97524	8			3.69		3
97525	3	1/0-14	3/16	1.90	1.85	8
97526	4			2.49		6
97527	5			3.08		4
97528	6			3.67		4
97530	8			4.85		3
97533	3	2/0-6	3/16	1.90	1.85	8
97534	4			2.49		6
97535	5			3.08		4
97536	6			3.67		4
97538	8			4.85		3
97579	3	3/0-6	1/4	2.10	1.99	6
97580	4			2.87		6
97581	5			3.64		4
97582	6			4.41		3
97584	8			5.96		3
97543	3	250-6	5/16	2.40	2.49	6
97544	4			3.29		4
97545	5			4.17		4
97546	6			5.06		4
97548	8			6.83		3
97553	3	350-6	5/16	2.80	2.64	6
97554	4			3.85		4
97555	5			4.90		4
97556	6			5.95		3
97558	8			8.06		3
97585	3	500-4	5/16	3.18	3.03	4
97586	4			4.35		4
97587	5			5.53		4
97588	6			6.70		2
97590	8			9.05		2
97563	3	600-250	5/16	3.40	3.11	4
97564	4			4.68		4
97565	5			5.95		4
97566	6			7.23		2
97568	8			9.78		2
97573	3	750-250	3/8	3.60	3.60	4
97574	4			5.03		4
97575	5			6.45		4
97576	6			7.88		4
97578	8			10.73		2

