

Thin Wall Heat Shrink Tubing - 4' Length

- Flexible Polyolefin Heat Shrink Tubing
- 2:1 Shrink Ratio
- 600 Volt
- 257°F (125°C) Continuous Operation
- For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- UL 224 Recognized



DIMENSIONS = INCHES

CAT NO.	LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	BAG QTY
68072	4 FT	BLACK	.078	.029	1
68074	4 FT	BLACK	.098	.039	1
68076	4 FT	BLACK	.137	.059	1
68078	4 FT	BLACK	.211	.098	1
68080	4 FT	BLACK	.250	.117	1
68082	4 FT	BLACK	.367	.176	1
68084	4 FT	BLACK	.484	.234	1
68086	4 FT	BLACK	.827	.390	1
68088	4 FT	BLACK	1.26	.590	1
68382	4 FT	CLEAR	.078	.029	1
68383	4 FT	CLEAR	.098	.039	1
68384	4 FT	CLEAR	.137	.059	1
68385	4 FT	CLEAR	.211	.098	1
68386	4 FT	CLEAR	.250	.117	1
68387	4 FT	CLEAR	.367	.176	1
68388	4 FT	CLEAR	.484	.234	1
68389	4 FT	CLEAR	.827	.390	1
68391	4 FT	RED	.078	.029	1
68392	4 FT	RED	.098	.039	1
68393	4 FT	RED	.137	.059	1
68394	4 FT	RED	.211	.098	1
68395	4 FT	RED	.250	.117	1
68396	4 FT	RED	.367	.176	1
68397	4 FT	RED	.484	.234	1
68398	4 FT	RED	.827	.390	1
68399	4 FT	RED	1.26	.590	1
68400	4 FT	GREEN	.078	.029	1
68401	4 FT	GREEN	.098	.039	1
68402	4 FT	GREEN	.137	.059	1
68403	4 FT	GREEN	.211	.098	1
68404	4 FT	GREEN	.250	.117	1
68405	4 FT	GREEN	.367	.176	1
68406	4 FT	GREEN	.484	.234	1
68407	4 FT	GREEN	.827	.390	1
68408	4 FT	GREEN	1.26	.590	1
68409	4 FT	WHITE	.078	.029	1
68410	4 FT	WHITE	.098	.039	1
68411	4 FT	WHITE	.137	.059	1
68412	4 FT	WHITE	.211	.098	1
68413	4 FT	WHITE	.250	.117	1
68414	4 FT	WHITE	.367	.176	1
68415	4 FT	WHITE	.484	.234	1
68416	4 FT	WHITE	.827	.390	1
68417	4 FT	WHITE	1.26	.590	1
68418	4 FT	BLUE	.078	.029	1
68419	4 FT	BLUE	.098	.039	1
68420	4 FT	BLUE	.137	.059	1
68421	4 FT	BLUE	.211	.098	1
68422	4 FT	BLUE	.250	.117	1
68423	4 FT	BLUE	.367	.176	1
68424	4 FT	BLUE	.484	.234	1
68425	4 FT	BLUE	.827	.390	1
68426	4 FT	BLUE	1.26	.590	1

