


Clear Insulated 2 Conductor - Dual Side Entry



- Clear Insulation
- 6061-T6 Aluminum
- Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- Pre-filled with Oxide Inhibitor
- Easy Re-Entry for Changes, Inspection or Troubleshooting
- Plugs Marked with Connector Max Wire Size for Easy ID
- CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- One Wire Per Terminal
- Temperature Range of -49°F to 194°F (-45° to 90°C)
- 600 Volt
- Rated For Use with 90°C Cables
- ANSI C119.4 & UL 486A & 486B Listed



DIMENSIONS = INCHES

	CAT. NO.	WIRE RANGE	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
	97312	4-14	SLOTTED	1.13	1.25	1.38	12
	97332	2-14	SLOTTED	1.15	1.50	1.42	12
NEW	97342	1/0-2	3/16	1.69	1.80	1.93	10
	97352	2/0-6	3/16	1.69	1.80	1.93	10
	97372	3/0-6	1/4	2.00	1.74	2.00	6
	97392	250-6	5/16	2.18	2.48	2.37	6

DIMENSIONS = INCHES

	CAT. NO.	WIRE RANGE	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
	97412	350-6	5/16	2.50	2.67	2.50	6
	97432	500-6	5/16	2.98	3.38	2.85	4
NEW	97532	600-250	5/16	2.98	3.38	2.85	4
NEW	97631	750-250	3/8	3.33	3.44	3.52	2
NEW	97632*	750-250	3/8	3.33	3.44	3.52	2

* Dual Set Screw Configuration (4 Set Screws - 2 Per Port)

Clear Insulated Dual Side Entry



DIMENSIONS = INCHES

	CAT. NO.	NO. OF PORTS	WIRE RANGE	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
	97314	3	4-14	SLOTTED	1.50	1.21	1.45	6
	97316	4			1.92			6
	97320	6			2.75			4
	97322	8			3.59			3
	97333	3	2-14	SLOTTED	1.60	1.21	1.45	6
	97334	4			2.02			6
	97336	6			2.85			4
	97338	8			3.69			3
	97354	3	2/0-14	3/16	1.90	1.80	1.85	8
	97356	4			2.49			6
	97360	6			3.67			4
	97362	8			4.85			3
	97373	3	3/0-14	1/4	2.10	2.09	1.99	6
NEW	97374	4			2.87			6
	97376	6			4.41			3
	97378	8			5.96			3
	97394	3	250-6	5/16	2.40	2.40	2.49	6
	97396	4			3.29			4
	97400	6			5.06			3
	97402	8			6.83			3
	97414	3	350-250	5/16	2.80	2.75	2.64	6
	97416	4			3.85			4
	97420	6			5.95			3
	97422	8			8.06			3
	97434	3	500-250	5/16	3.18	2.97	3.03	4
	97436	4			4.35			4
	97440	6			6.70			2
	97442	8			9.05			2
	97539	3	600-250	5/16	3.40	3.25	3.11	4
NEW	97540	4			4.68			4
	97541	6			7.23			2
	97542	8			9.78			2
	97425	3	750-250	3/8	3.60	3.85	3.60	4
NEW	97426	4			5.03			4
	97427	6			7.88			4
	97428	8			10.73			2