

Cold Shrink

- Submersible Rated for Cable Jacket Repair & Splicing
- Conforms to ANSI C119.1 1986
- Silicone Rubber Jacketing Material
- Durable Tear Resistant Removable Rip-Cord Core
- 1000V Rated for Primary Insulation
- UV Resistant



DIMENSIONS = INCHES

CAT. NO.	CONDUCTOR RANGE	APPLICATION RANGE	LENGTH	VOLTAGE	BAG QTY	CASE QTY
68302	#2-1/0	0.37-0.57	8	1000	1	10
68304	2/0-400	0.57-1.35	9	1000	1	10
68306	500-800	0.97-1.95	9	1000	1	10
68308	500-800	0.97-1.95	12	1000	1	10
68310	900-1000	1.32-2.65	9	1000	1	10
68312	1250-2000	1.63-3.67	9	1000	1	10

Heat Shrink End Caps

- Simple & effective method for sealing cable ends, pipe & conduit
- Superior Resistance to Weathering, Moisture Contamination, Adverse Environmental Conditions & Common Fluid/Solvents
- Adhesive Liner provides complete environmental protection & insulation
- Heat Indicating Lines
- Continuous Operating Temperature -67°F to 230°F (-55°C to 110°C)
- Rated to 1KV 194°F (90°C) Continuous Use
- UL486D - Shrink Temperature of 248°F (120°C)
- Black Color

DIMENSIONS = INCHES

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68232	2-4/0	3.5	.75	.22	.08
68234	300-1000MCM	4.0	1.30	.40	.08
68236	500-1500MCM	4.5	1.50	.50	.08
68238	900-2500MCM	4.5	2.05	.75	.08
68240	2000-2500MCM	5.0	2.75	1.00	.08



Medium Wall Heat Shrink Tubing - 3:1 Shrink Ratio



DIMENSIONS = INCHES

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68112	12-6	4 FT	.40	.15	.080
68114	8-1/0	4 FT	.75	.22	.080
68116	2-4/0	4 FT	1.10	.40	.080
68118	-	4 FT	1.30	.40	.080
68120	3/0-400	4 FT	1.50	.50	.080
68122	-	4 FT	1.70	.50	.080
68124	250-750	4 FT	2.05	.75	.080
68126	-	4 FT	2.75	1.00	.080
68128	800-1250	4 FT	3.50	1.18	.095
68130	1500-2500	4 FT	4.70	1.57	.105
68132	-	4 FT	6.70	2.30	.110
ROLLS					
68142	12-6	50 FT	.40	.15	.080
68144	8-1/0	25 FT	.75	.22	.080
68146	2-4/0	25 FT	1.10	.40	.080
68148	3/0-400	50 FT	1.50	.50	.080
68150	-	50 FT	1.70	.50	.080
68152	250-750	25 FT	2.05	.75	.080
68154	800-1250	25 FT	3.50	1.18	.095
68156	1500-2500	50 FT	4.70	1.57	.105



- 3:1 Shrink Ratio
- Suitable for Electrical and Mechanical Applications where Lighter Weight and Flexibility are Important
- Seals and Protects Cable Splices and Terminations
- High Resistance to Impact and Abrasion
- 4' Lengths have Adhesive Liner for Complete Environmental Protection and Insulation
- Continuous Operating Temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink Temperature: 248°F (120°C)
- Rated for 600-2500V
- UL486D
- Black Color