



Clear Insulated In-line Splices



Dual-Rated
CU9AL
90°C 600V

- Clear Insulation
- 6061-T6 Aluminum
- Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- Pre-filled with Oxide Inhibitor
- Easy Re-Entry for Changes, Inspection or Troubleshooting
- Plugs Marked with Connector Max Wire Size for Easy ID
- CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- One Wire Per Terminal
- Temperature Range of -49°F to 194°F (-45° to 90°C)
- 600 Volt
- Rated For Use with 90°C Cables
- ANSI C119.4 & UL 486A & 486B Listed



DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
97302	2-14	SLOTTED	3.46	.82	1.62	12
NEW 97303	1/0-14	3/16	3.55	.96	2.05	12
97304	2/0-2	3/16	3.50	.99	1.95	12
97305	250-6	5/16	4.26	1.26	2.28	4
97306	350-6	5/16	5.21	1.33	2.63	4
97307	500-6	5/16	5.99	1.84	3.19	2
NEW 97308	600-250	5/16	6.18	1.77	3.17	2
NEW 97309	750-250	3/8	7.39	1.84	3.55	2

Clear Insulated Connectors - Single Side Entry



DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE	PORTS	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
97324	4-14	2	SLOTTED	1.13	1.10	1.38	12
97450	4-14	3	SLOTTED	1.50	1.10	1.45	12
97451	4-14	4	SLOTTED	1.92	1.10	1.45	12
97326	2-14	2	SLOTTED	1.15	1.20	1.42	12
97458	2-14	3	SLOTTED	1.60	1.20	1.50	12
97459	2-14	4	SLOTTED	2.02	1.20	1.50	12
97328	1/0-2	2	3/16	1.69	1.80	1.93	10
97465	1/0-2	3	3/16	1.90	1.80	1.93	10
97466	1/0-2	4	3/16	2.49	1.80	1.93	10
97330	2/0-6	2	3/16	1.69	1.80	1.93	10
97473	2/0-6	3	3/16	1.90	1.80	1.93	10
97474	2/0-6	4	3/16	2.49	1.80	1.93	10
97331	3/0-6	2	1/4	2.00	1.90	1.99	6
97481	3/0-6	3	1/4	2.10	1.90	1.99	6
97482	3/0-6	4	1/4	2.87	1.90	1.99	6

CAT. NO.	WIRE RANGE	PORTS	ALLEN HEX	LENGTH	WIDTH	HEIGHT	BOX QTY
97487	250-6	2	5/16	2.18	2.48	2.37	6
97488	250-6	3	5/16	2.40	2.48	2.37	6
97489	250-6	4	5/16	3.29	2.48	2.37	4
97494	350-6	2	5/16	2.50	2.67	2.64	6
97495	350-6	3	5/16	2.80	2.67	2.64	4
97496	350-6	4	5/16	3.85	2.67	2.64	4
97501	500-6	2	5/16	2.98	2.70	2.85	12
97502	500-6	3	5/16	3.18	2.70	2.85	4
97503	500-6	4	5/16	4.35	2.70	2.85	4
97505	600-250	2	5/16	2.98	2.95	2.85	4
97506	600-250	3	5/16	3.40	2.95	2.85	4
97507	600-250	4	5/16	4.68	2.95	2.85	4
97509	750-250	2	3/8	3.33	3.44	3.52	4
97510	750-250	3	3/8	3.60	3.44	3.52	4
97511	750-250	4	3/8	5.03	3.44	3.52	4