



Heavy Wall Heat Shrink Tubing



DIMENSIONS = INCHES



- 3:1 Shrink Ratio
- Provides maximum reliability for insulating and protection of cable joints and terminations
- Withstands Severe Mechanical Requirements of U.R.D. Submersible and Direct Burial Installations
- High Impact, Abrasion, Corrosion and Chemical Resistance
- Rated for 600-2500V, 90°C Continuous Use
- 4 FT Lengths have Thermoplastic Adhesive Liner
- Provides Complete Environmental Protection and Insulation
- Meets: UL 486D, CSA C22.2 No. 198.2, ANSI C119.1, Western Underground Guide Numbers 2.4, 2.5, ICEA and NEMA insulation thickness Standard
- Continuous operating temperature: -67°F to 230°F
- Shrink temperature: 248°F (120°C)
- Heavy Wall holds better mechanically & has better underground protection than medium wall
- Black color

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68162	#14-#10	4 FT	0.35	0.12	.07
68164	#8-#6	4 FT	0.51	0.16	.09
68166	#6-#2	4 FT	0.75	0.24	.09
68168	#1-#3/0	4 FT	1.10	0.35	.12
68170	2/0-350	4 FT	1.50	0.47	.16
68172	250-500	4 FT	2.00	0.63	.16
68174	600-1000	4 FT	2.70	0.87	.16
68176	800-1250	4 FT	3.54	1.18	.16
68178	1500-2500	4 FT	4.72	1.57	.17
ROLLS					
68182	#14-#10	25 FT	0.35	0.12	.07
68186	#6-#2	25 FT	0.75	0.24	.09
68188	#1-#3/0	25 FT	1.10	0.35	.12
68190	2/0-350	25 FT	1.50	0.47	.16
68192	250-500	25 FT	2.00	0.63	.16
68194	600-1000	25 FT	2.70	0.87	.16
68196	800-1250	25 FT	3.54	1.18	.16

Heavy Wall Heat Shrink Tubing - Flame Retardant



- 3:1 Shrink Ratio allows Various Shapes & Contours to be Accommodated
- Insulates & Protects Electrical Splices & terminations where maximum flame retardants is required
- Adhesive sealant liner provides complete environmental protection and insulation

- High impact and abrasion resistance capable of withstanding severe mechanical abuse in Submersible and Direct Burial installations
- Will Not Split or Rupture during installation
- Flame Retardant
- Meets: UL 486D, CSA C22.2 No. 198.2, ANSI C119.1, Western Underground Guides Nos. 2.4, 2.5, MIL-DTL-23053/15, IEEE 383 Vertical Flame Test, ANSI C37.20.2, ICEA S-19-8 and NEMA insulation thickness requirements
- Rated for 1KV, 90°C continuous use
- Continuous operating temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink temperature: 248°F (120°C)
- Black color

DIMENSIONS = INCHES

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS	BAG QTY
68004	1-8 AWG	6 IN	0.40	0.13	.09	10
68008	6-2 AWG	6 IN	0.75	0.24	.09	10
68011	1-3/0 AWG	8 IN	1.10	0.35	.12	5
68012	1-3/0 AWG	12 IN	1.10	0.35	.12	1
68015	2/0-350 MCM	8 IN	1.50	0.47	.16	4
68020	250-500 MCM	12 IN	2.00	0.63	.16	1
4 FT LENGTHS						
68022	12-8 AWG	4 FT	0.40	0.13	.09	1
68023	6-2 AWG	4 FT	0.75	0.24	.09	1
68024	1-3/0 AWG	4 FT	1.10	0.35	.12	1
68025	2/0-350 MCM	4 FT	1.50	0.47	.16	1
68026	250-500 MCM	4 FT	2.00	0.63	.16	1