


# EMT Compression Connectors - Zinc Die Cast



- To secure and terminate EMT to knockouts in concrete tight box, dry or damp location applications
- Male NPSM hub threads
- Concrete tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

| CAT. NO. | TRADE SIZE | DIMENSIONS |      |      | INNER BOX | OUTER BOX |
|----------|------------|------------|------|------|-----------|-----------|
|          |            | A          | B    | C    |           |           |
| I4910    | 1/2"       | 1.24       | .98  | .59  | 50        | 500       |
| I4911    | 3/4"       | 1.26       | 1.22 | .78  | 25        | 250       |
| I4912    | 1"         | 1.46       | 1.46 | 1.00 | 15        | 150       |
| I4913    | 1-1/4"     | 1.83       | 1.85 | 1.32 | 10        | 100       |
| I4914    | 1-1/2"     | 1.85       | 2.07 | 1.53 | 10        | 40        |
| I4915    | 2"         | 2.01       | 2.54 | 1.99 | 5         | 20        |
| I4916    | 2-1/2"     | 2.54       | 3.37 | 2.35 | -         | 12        |
| I4917    | 3"         | 2.54       | 3.94 | 2.95 | -         | 12        |
| I4918    | 3-1/2"     | 2.60       | 4.45 | 3.43 | -         | 6         |
| I4919    | 4"         | 2.60       | 1.94 | 3.91 | -         | 6         |




# EMT Compression Connectors - Insulated Throat - Zinc Die Cast



- To secure and terminate EMT to knockouts in concrete tight box, dry or damp location application
- Male NPSM hub threads
- Concrete tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

| CAT. NO. | TRADE SIZE | DIMENSIONS |      |      | INNER BOX | OUTER BOX |
|----------|------------|------------|------|------|-----------|-----------|
|          |            | A          | B    | C    |           |           |
| I4920    | 1/2"       | 1.28       | .98  | .59  | 50        | 500       |
| I4921    | 3/4"       | 1.32       | 1.22 | .78  | 25        | 250       |
| I4922    | 1"         | 1.52       | 1.46 | 1.00 | 15        | 150       |
| I4923    | 1-1/4"     | 1.89       | 1.85 | 1.32 | 10        | 100       |
| I4924    | 1-1/2"     | 1.91       | 2.07 | 1.53 | 10        | 40        |
| I4925    | 2"         | 2.09       | 2.54 | 1.99 | 5         | 20        |
| I4926    | 2-1/2"     | 2.62       | 3.37 | 2.35 | -         | 12        |
| I4927    | 3"         | 2.62       | 3.94 | 2.95 | -         | 12        |
| I4928    | 3-1/2"     | 2.68       | 4.45 | 3.43 | -         | 6         |
| I4929    | 4"         | 2.68       | 4.94 | 3.91 | -         | 6         |



# EMT Compression Couplings - Zinc Die Cast



- To join lengths of EMT for concrete tight, dry or damp location applications
- Concrete tight
- UL Listed for EMT Conduit
- 2-1/2" - 4" are also UL Listed for use with Rigid & IMC

DIMENSIONS = INCHES

| CAT. NO. | TRADE SIZE | DIMENSIONS |      | INNER BOX | OUTER BOX |
|----------|------------|------------|------|-----------|-----------|
|          |            | A          | B    |           |           |
| I4930    | 1/2"       | 1.69       | .98  | 50        | 500       |
| I4931    | 3/4"       | 1.73       | 1.22 | 25        | 250       |
| I4932    | 1"         | 1.85       | 1.46 | 15        | 150       |
| I4933    | 1-1/4"     | 2.36       | 1.85 | 10        | 100       |
| I4934    | 1-1/2"     | 2.40       | 2.07 | 10        | 50        |
| I4935    | 2"         | 2.44       | 2.54 | 5         | 20        |
| I4936    | 2-1/2"     | 3.15       | 3.37 | -         | 12        |
| I4937    | 3"         | 3.15       | 3.94 | -         | 12        |
| I4938    | 3-1/2"     | 3.27       | 4.45 | -         | 6         |
| I4939    | 4"         | 3.27       | 4.94 | -         | 6         |

