




Aluminum Service Entrance Cap - Clamp On



- Clamp-on type head used with Rigid conduit, IMC or E.M.T. for pulling service drop conductors
- Cast Aluminum
- Bar type Clamp
- Heavy pressure clamp in body
- Weather resistant
- Assembled with electrical grade phenolic insulator with multiple holes

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15520	1/2"	2.68	2.50	2.19	-	100
15521	3/4"	3.04	2.76	2.39	-	100
15522	1"	3.48	2.96	2.58	-	100
15523	1-1/4"	4.22	3.27	3.06	-	60
15524	1-1/2"	5.22	4.28	3.49	-	60
15525	2"	6.68	5.81	4.33	-	30
15526	2-1/2"	9.94	7.05	6.54	1	4
15527	3"	11.69	8.54	6.93	1	4
15528	3-1/2"	11.69	8.54	7.28	1	4
15529	4"	11.69	8.54	7.86	1	4



Service Entrance




Aluminum Service Entrance Cap - Conduit Mount Threaded

- Conduit Mount Head used with Rigid or IMC for Pulling Service Entrance Conductors
- Weather Resistant
- Assembled with Electrical Grade Phenolic Insulator with multiple holes

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15530	1/2"	1.97	2.68	2.29	-	100
15531	3/4"	2.13	3.04	2.66	-	100
15532	1"	2.36	3.48	2.96	-	100
15533	1-1/4"	2.68	4.22	3.11	-	60
15534	1-1/2"	3.39	5.22	4.06	-	60
15535	2"	4.33	6.69	5.28	-	30
15536	2-1/2"	6.30	9.94	6.69	1	4
15537	3"	7.99	11.69	8.08	1	4
15538	3-1/2"	7.99	11.69	8.08	1	4
15539	4"	7.99	11.69	8.08	1	4



Aluminum Service Entrance Cap - Slip Fitter Mast Head

- Slip Fitter Mast Head used with Rigid or IMC Conduit for Pulling Service Drop conductors
- Cast Aluminum
- Mast type Clamp
- Screw does not bear directly on conduit
- Weather Resistant
- Assembled with electrical grade phenolic insulator with multiple holes

DIMENSIONS = INCHES

CAT. NO.	CONDUIT SIZE	INSULATOR CAP SIZE	DIMENSIONS			SET SCREW	BOX QTY
			A	B	C		
15540	2"	1-1/4"	3.46	1.95	3.75	1/4-20 X 5/8	50
15541	2-1/2"	1-1/4"	3.46	1.95	3.75	1/4-20 X 1/2	50
15542	2-1/2"	2"	4.68	1.95	4.88	1/4-20 X 5/8	50

