


# GB Xtreme® TERMINALS

Constructed with Heat Shrink insulation - adhesive lined to waterproof and environmentally seal electrical connections when crimped and heated.

- Insulates and protects connections from wire pullout, moisture intrusion and abrasion.
- Heat-activated adhesive melts and flows to create a seal.
- Resists salt water, oil, gasoline and other environmental contaminants.
- Rated at 600 Volt Max.
- Temperature rating: -67° to 221°F (-55° to 105°C).
- 2.5:1 shrink ratio.
- Heat to 275°F (135°C).


## BUTT SPLICES



AMT-120, AMT-123 & AMT-126

| Part #    | Color           | Pack Qty. | Length (L) |       | Barrel I.D. (C) |           | Wire Range    |
|-----------|-----------------|-----------|------------|-------|-----------------|-----------|---------------|
|           |                 |           | Inches     | MM    | Inches          | MM        |               |
| AMT-120   | Red             | 3/Clam    | 1.33       | 33.71 | 0.07            | 1.7       | #22 - #18 AWG |
| AMT-4120  | Red             | 8/Clam    | 1.33       | 33.71 | 0.07            | 1.7       | #22 - #18 AWG |
| AMT-121   | Red             | 25/Clam   | 1.33       | 33.71 | 0.07            | 1.7       | #22 - #18 AWG |
| AMT-123   | Blue            | 3/Clam    | 1.33       | 33.71 | 0.09            | 2.3       | #16 - #14 AWG |
| AMT-4123  | Blue            | 7/Clam    | 1.33       | 33.71 | 0.09            | 2.3       | #16 - #14 AWG |
| AMT-124   | Blue            | 25/Clam   | 1.33       | 33.71 | 0.09            | 2.3       | #16 - #14 AWG |
| AMT-126   | Yellow          | 3/Clam    | 1.33       | 33.71 | 0.13            | 3.4       | #12 - #10 AWG |
| AMT-5126  | Yellow          | 4/Clam    | 1.33       | 33.71 | 0.13            | 3.4       | #12 - #10 AWG |
| AMT-4126  | Yellow          | 5/Clam    | 1.33       | 33.71 | 0.13            | 3.4       | #12 - #10 AWG |
| AMT-127   | Yellow          | 25/Clam   | 1.33       | 33.71 | 0.13            | 3.4       | #12 - #10 AWG |
| AMT-5121* | Red             | 5/Clam    | 1.61       | 40.89 | 0.07            | 1.7       | #22 - #18 AWG |
| XTM-240*  | Red             | 6/Clam    | 1.61       | 40.89 | 0.07            | 1.7       | #22 - #18 AWG |
| AMT-5123* | Blue            | 5/Clam    | 1.61       | 40.89 | 0.09            | 2.3       | #16 - #14 AWG |
| XTM-245*  | Blue            | 6/Clam    | 1.61       | 40.89 | 0.09            | 2.3       | #16 - #14 AWG |
| XTM-250*  | Yellow          | 4/Clam    | 1.61       | 40.89 | 0.13            | 3.4       | #12 - #10 AWG |
| GBX-TK*   | Red/Blue/Yellow | 24/Clam   | 1.61       | 40.89 | .07 - .13       | 1.7 - 3.4 | #22 - #10 AWG |

\*Solder Ring Terminals




AMT-100, AMT-103 & AMT-108

## RING TERMINALS

| Part #    | Color  | Pack Qty. | Length (L) |       | Width (W) |       | Barrel I.D. (C) |     | Wire Range    | Stud Size |
|-----------|--------|-----------|------------|-------|-----------|-------|-----------------|-----|---------------|-----------|
|           |        |           | Inches     | MM    | Inches    | MM    | Inches          | MM  |               |           |
| AMT-100   | Red    | 3/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.067           | 1.7 | #22 - #18 AWG | 10        |
| AMT-4100  | Red    | 6/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.067           | 1.7 | #22 - #18 AWG | 10        |
| AMT-103   | Blue   | 3/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.091           | 2.3 | #16 - #14 AWG | 8         |
| AMT-4103  | Blue   | 6/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.091           | 2.3 | #16 - #14 AWG | 8         |
| AMT-106   | Yellow | 3/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.131           | 3.4 | #12 - #10 AWG | 8         |
| AMT-108   | Yellow | 3/Clam    | 1.88       | 47.75 | 0.56      | 14.22 | 0.131           | 3.4 | #12 - #10 AWG | 1/4"      |
| AMT-4106  | Yellow | 5/Clam    | 1.37       | 34.80 | 0.4       | 10.16 | 0.131           | 3.4 | #12 - #10 AWG | 10        |
| AMT-5104* | Blue   | 4/Clam    | 1.67       | 42.42 | 0.4       | 10.16 | 0.091           | 2.3 | #16 - #14 AWG | 10        |
| AMT-5106* | Yellow | 3/Clam    | 1.67       | 42.42 | 0.4       | 10.16 | 0.131           | 3.4 | #12 - #10 AWG | 10        |


\*Solder Ring Terminals



AMT-110, AMT-113 & AMT-116

## SPADE TERMINALS

| Part #   | Color  | Pack Qty. | Length (L) |       | Width (W) |       | Barrel I.D. (C) |     | Wire Range    | Stud Size |
|----------|--------|-----------|------------|-------|-----------|-------|-----------------|-----|---------------|-----------|
|          |        |           | Inches     | MM    | Inches    | MM    | Inches          | MM  |               |           |
| AMT-110  | Red    | 3/Clam    | 1.38       | 35.05 | 0.36      | 9.14  | 0.067           | 1.7 | #22 - #18 AWG | 8 to 10   |
| AMT-4110 | Red    | 6/Clam    | 1.38       | 35.05 | 0.36      | 9.14  | 0.067           | 1.7 | #22 - #18 AWG | 8 to 10   |
| AMT-113  | Blue   | 3/Clam    | 1.38       | 35.05 | 0.36      | 9.14  | 0.091           | 2.3 | #16 - #14 AWG | 8 to 10   |
| AMT-4113 | Blue   | 6/Clam    | 1.38       | 35.05 | 0.36      | 9.14  | 0.091           | 2.3 | #16 - #14 AWG | 8 to 10   |
| AMT-116  | Yellow | 3/Clam    | 1.39       | 35.05 | 0.4       | 10.16 | 0.131           | 3.4 | #12 - #10 AWG | 8 to 10   |
| AMT-4116 | Yellow | 5/Clam    | 1.39       | 35.05 | 0.4       | 10.16 | 0.131           | 3.4 | #12 - #10 AWG | 8 to 10   |



## DISCONNECT- SOLDER



XTM-220, XTM-225

| Part #  | Color | Pack Qty.    | Length (L)  |               | Width (W) |       | Barrel I.D. (C) |     | Wire Range    | Tab Size | Type      |
|---------|-------|--------------|-------------|---------------|-----------|-------|-----------------|-----|---------------|----------|-----------|
|         |       |              | Inches      | MM            | Inches    | MM    | Inches          | MM  |               |          |           |
| XTM-220 | Red   | 3 Pairs/Clam | 1.47 - 1.55 | 37.34 - 39.37 | 0.23      | 5.842 | 0.067           | 1.7 | #22 - #18 AWG | .250"    | F/M Pairs |
| XTM-225 | Blue  | 3 Pairs/Clam | 1.47 - 1.55 | 37.34 - 39.37 | 0.26      | 6.604 | 0.091           | 2.3 | #16 - #14 AWG | .250"    | F/M Pairs |

