

Non-Insulated Ferrules - DIN Standard



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

TERMINAL MATERIAL:


Electro-Tin Plated Tubular Copper No Insulation

FEATURES: Flared Barrel

MAXIMUM ELECTRIC RATING: 221°F (105°C)

600V

COLOR CODE: N/A



DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	L	W	D	C	BAG QTY	MASTER BAG QTY
I2802	26	.236	.059	.043	.031	100	1,000
I2804	26	.276	.059	.043	.031	100	1,000
I2806	24	.236	.059	.043	.031	100	1,000
I2808	24	.315	.059	.043	.031	100	1,000
I2810	22	.236	.067	.051	.039	100	1,000
I2812	22	.315	.067	.051	.039	100	1,000
I2814	22	.394	.067	.051	.039	100	1,000
I2816	20	.236	.075	.059	.047	100	1,000
I2818	20	.315	.075	.059	.047	100	1,000
I2820	20	.394	.075	.059	.047	100	1,000
I2822	20	.472	.075	.059	.047	100	1,000
I2824	18	.315	.087	.067	.055	100	1,000
I2826	18	.394	.087	.067	.055	100	1,000
I2828	18	.472	.087	.067	.055	100	1,000
I2830	16	.276	.098	.079	.067	100	1,000
I2832	16	.315	.098	.079	.067	100	1,000
I2834	16	.394	.098	.079	.067	100	1,000
I2836	16	.472	.098	.079	.067	100	1,000
I2838	16	.591	.098	.079	.067	100	1,000
I2840	16	.709	.098	.079	.067	100	1,000
I2842	14	.276	.130	.102	.091	100	1,000
I2844	14	.394	.130	.102	.091	100	1,000
I2846	14	.472	.130	.102	.091	100	1,000
I2848	14	.591	.130	.102	.091	100	1,000
I2850	14	.709	.130	.102	.091	100	1,000
I2852	12	.354	.154	.126	.110	100	1,000
I2854	12	.472	.154	.126	.110	100	1,000
I2856	12	.591	.154	.126	.110	100	1,000
I2858	12	.709	.154	.126	.110	100	1,000
I2860	10	.394	.185	.154	.138	100	1,000
I2862	10	.472	.185	.154	.138	100	1,000
I2864	10	.591	.185	.154	.138	100	1,000
I2866	10	.709	.185	.154	.138	100	1,000
I2868	10	.787	.185	.154	.138	100	1,000
I2870	8	.472	.228	.193	.177	100	-
I2872	8	.591	.228	.193	.177	100	-
I2874	8	.709	.228	.193	.177	100	-
I2876	8	.787	.228	.193	.177	100	-
I2878	6	.472	.283	.244	.228	100	-
I2880	6	.591	.283	.244	.228	100	-
I2882	6	.709	.283	.244	.228	100	-
I2884	6	.787	.283	.244	.228	100	-
I2886	6	.984	.283	.244	.228	100	-
I2888	6	1.260	.283	.244	.228	100	-
I2890	4	.591	.358	.311	.295	100	-
I2892	4	.709	.358	.311	.295	100	-
I2894	4	.984	.358	.311	.295	100	-
I2896	4	1.260	.358	.311	.295	100	-
I2898	2	.709	.402	.343	.327	100	-
I2900	2	.984	.402	.343	.327	100	-
I2902	2	1.260	.402	.343	.327	100	-
I2904	1/0	.709	.500	.429	.406	100	-
I2906	1/0	.866	.500	.429	.406	100	-
I2908	1/0	1.260	.500	.429	.406	100	-



WIRE MANAGEMENT

Ferrules