

Copper Ground Clamps - U Bolt - 1 Conductor

- U-Bolt Style Clamp
- For Connecting 1 Ground Wire Parallel or 90° to Water Pipe, Copper Tubing, Ground Rod, Rebar or Fencing
- Use with Continuous Ground Loops
- Cast of High Strength High Conductivity Copper Alloy
- Stainless Steel Bolts, Nuts & Lock Washers
- UL 467 Listed for Direct Burial In Soil or Concrete



DIMENSIONS = INCHES

CAT. NO.	ROD SIZE	PIPE SIZE	WIRE RANGE		DIMENSIONS			BOX QTY
			MIN	MAX	WIDTH	HEIGHT	THREAD	
91732	5/8 OR 3/4	1/2	8 SOL	4 STR	2	2-7/16	3/8 X 16	5
91733	5/8 OR 3/4	1/2	4 SOL	2/0 STR	2	2-7/16	3/8 X 16	5
91734	5/8 OR 3/4	1/2	2/0 SOL	250 MCM	2-1/16	2-3/4	3/8 X 16	5
91735	7/8 OR 1	1/2 OR 3/4	4 SOL	2/0 STR	2-1/4	3	3/8 X 16	5
91736	7/8 OR 1	1/2 OR 3/4	2/0 SOL	250 MCM	2-5/16	3-3/16	3/8 X 16	5
91737	-	1	4 SOL	2/0 STR	2-9/16	3-3/16	3/8 X 16	5
91738	-	1	2/0 SOL	250 MCM	2-9/16	3-3/16	3/8 X 16	5
91740	-	1-1/4	4 SOL	250 MCM	3	3-1/2	3/8 X 16	5
91742	-	1-1/2	4 SOL	250 MCM	3-1/4	4	3/8 X 16	5
91744	-	2	4 SOL	250 MCM	3-3/4	4-3/8	3/8 X 16	5
91746	-	2-1/2	4 SOL	250 MCM	4-1/4	5	3/8 X 16	5
91748	-	3	4 SOL	250 MCM	4-7/8	5-5/8	3/8 X 16	5
91750	-	3-1/2	4 SOL	250 MCM	5-3/8	6-1/4	3/8 X 16	5

Copper Ground Clamps - U Bolt - 2 Conductor

- U-Bolt Style Clamp
- For Connecting 2 Ground Wires Parallel or 90° to Water Pipe, Copper Tubing, Ground Rod, Rebar or Fencing
- Use with Continuous Ground Loops
- Cast of High Strength High Conductivity Copper Alloy
- Stainless Steel Bolts, Nuts & Lock Washers
- UL 467 Listed for Direct Burial In Soil or Concrete



DIMENSIONS = INCHES

CAT. NO.	PIPE SIZE	WIRE RANGE		DIMENSIONS			BOX QTY
		MIN	MAX	WIDTH	HEIGHT	THREAD	
91752	1	4 SOL	250 MCM	2-5/8	3-3/8	3/8-16	5
91756	1-1/2	4 SOL	250 MCM	3-1/4	4	3/8-16	5
91758	2	4 SOL	250 MCM	3-3/4	4-3/8	3/8-16	5
91760	2-1/2	4 SOL	250 MCM	4-1/4	5	3/8-16	5
91762	3	4 SOL	250 MCM	4-7/8	5-5/8	3/8-16	5
91764	3-1/2	4 SOL	250 MCM	5-3/8	6-1/4	3/8-16	5

Copper Ground Clamps - U Bolt - 3 Conductor

- U-Bolt Style Clamp
- For Connecting 3 Ground Wires Parallel or 90° to Water Pipe, Copper Tubing, Ground Rod, Rebar or Fencing
- Use with Continuous Ground Loops
- Cast of High Strength High Conductivity Copper Alloy
- Stainless Steel Bolts, Nuts & Lock Washers
- UL 467 Listed for Direct Burial In Soil or Concrete



DIMENSIONS = INCHES

CAT. NO.	PIPE SIZE	WIRE RANGE MIN	MAX	DIMENSIONS		BOX QTY
				WIDTH	HEIGHT	
91766	1/4	4 SOL	250 MCM	3-5/8	2-3/4	5
91767	3/8	4 SOL	250 MCM	3-1/2	3	5
91768	1/2 OR 3/4	4 SOL	250 MCM	3-7/8	3-3/8	5
91769	1	4 SOL	250 MCM	4-1/8	3-1/2	5
91770	1-1/4	4 SOL	250 MCM	4-1/2	3-7/8	5
91771	1-1/2	4 SOL	250 MCM	4-3/4	4-1/4	5
91772	2	4 SOL	250 MCM	5-1/4	5	5
91773	2-1/2	4 SOL	250 MCM	5-7/8	5-1/4	5
91774	3	4 SOL	250 MCM	6-3/8	5-3/4	5
91775	3-1/2	4 SOL	250 MCM	6-3/4	6-3/8	5
91776	4	4 SOL	250 MCM	7-1/4	6-3/4	5