

120W/150W/160W



体积小、重量轻、环保无噪音、免维护; 方便维修;提供欠压保护、过压保护、过载 保护、过温保护及短路保护;转换效率高达90%, 有较高的瞬间启动功能;适用于汽车、轮船、 移动办公等。





NFA

Innovation for greener living

120W/150W/160W







产品信息

信息 1

150W 6955

160W 774

7682	6955	7747
100W	110W	110W
12. 8VDC-13. 2VDC	12. 8VDC-13. 2VDC	12. 8VDC-13. 2VDC
210VAC-235VAC	210VAC-235VAC	205VAC-245VAC
50±2HZ	50±2HZ	50±2HZ
<0. 2A	<0. 2A	<0. 2A
15. 5VDC	15. 5VDC	15. 5VDC
10±0.3V	10±0.3V	10±0.3V
方波	方波	方波
有	有	有
	100W 12. 8VDC-13. 2VDC 210VAC-235VAC 50±2HZ <0. 2A 15. 5VDC 10±0. 3V 方波	100W 110W 12.8VDC-13.2VDC 12.8VDC-13.2VDC 210VAC-235VAC 210VAC-235VAC 50±2HZ 50±2HZ (0.2A 15.5VDC 15.5VDC 15.5VDC 15.5VDC 15.5VDC 5分波 方波 方波

外观规格

外观尺寸	95*72*18mm	91*67*15mm	100. 4*67. 5*25. 9mm
产品净重 (g)	111g	101g	117g
保修承诺	1年	1年	1年

包装规格

包装方式	彩盒+PVC	彩盒+PVC	彩盒+PVC
包装尺寸	187*48*252mm	187*48*252mm	187*48*252mm

